Reopen your project

1. Your first email workflow.

Say: Today your company context becomes a small email pilot.
Show: Open the actual local project.
Pause: Give participants time to open the booklet.

2. One actual message. One actual Sent record.

Say: This is a real send, not a made-up account example.
Show: Show the message and its Gmail Sent check.
Pause: Point to the problem, the offer and the single ask.

3. The workflow you will build.

Say: The agent researches and writes. The program checks, sends and records.
Show: Trace one real target through the decision tree.
Pause: Explain the stop branch before the send branch.

4. You already finished STEP 1.

Say: We continue your saved project. We do not rebuild the developer history.
Show: Point to the existing saved skill.
Pause: One sentence per step.

5. Four words we will use.

Say: Explain each term with the actual file or tool it names.
Show: Ten companies, the saved project and the connection check.
Pause: Keep this under one minute.

6. The Agency: Best Regards

Say: A short marketing story. Then we build the working email motion.
Show: Play only if video is ready. Keep the step order.
Pause: Play 2:20. If it stalls, use the link later.

7. Open your saved project. Check the sender.

Say: We already built the context. Today we give that project one email channel.
Show: Show the actual sender check, not a settings screen.
Pause: Six minutes. Read the returned sender before continuing.

8. Check your result before moving on.

Say: Pause here. Check the actual outputs.
Show: Point to each required file or result.
Pause: Wait until the checks are clear. Record a blocker instead of guessing.

Set the rules. Choose ten companies.

9. Set the rules. Choose ten companies.

Say: State the result of this chapter, then demonstrate one step.
Show: A saved order of work, an exclusion check and ten real targets.
Pause: Keep the chapter clock visible.

10. Save the order of work.

Say: A prompt writes one email. This file tells the agent what happens next.
Show: Trace one real target through the tree.
Pause: Four minutes. Check the saved order.

11. Prove that an excluded company stays excluded.

Say: Use a real customer, an active deal or a company you want excluded.
Show: The domain and the reason it is blocked.
Pause: Five minutes. A missing test is not a pass.

12. Save ten companies you want to sell to.

Say: Target accounts means the companies you want to sell to. This is individual work.
Show: One complete row before showing all ten.
Pause: Eight minutes. Check company identity and the fit reason.

13. Check your result before moving on.

Say: Pause here. Check the actual outputs.
Show: Point to each required file or result.
Pause: Wait until the checks are clear. Record a blocker instead of guessing.

Check buyers. Write the emails.

14. Check buyers. Write the emails.

Say: State the result of this chapter, then demonstrate one step.
Show: Current buyers and ten messages you can inspect.
Pause: Keep the chapter clock visible.

15. Check one buyer at each company.

Say: There are two checks: the right person, and a valid work email.
Show: One buyer row with its two separate sources.
Pause: Nine minutes. Show blocked rows instead of filling gaps.

16. Why this prompt works.

Say: Explain these three decisions. Do not read the full prompt.
Show: Point to those three parts in the email-writing prompt.
Pause: Ask participants to identify one unsupported claim in their own draft.

17. Write ten emails from your company facts.

Say: Explain the reason to contact this person. Do not read their job title back to them.
Show: Point to the relevance, offer and ask in the real example.
Pause: Ten minutes. Read the first draft aloud. Then inspect all ten.

18. Check your result before moving on.

Say: Pause here. Check the actual outputs.
Show: Point to each required file or result.
Pause: Wait until the checks are clear. Record a blocker instead of guessing.

Approve. Send yourself one test.

19. Approve. Send yourself one test.

Say: State the result of this chapter, then demonstrate one step.
Show: An exact approved message matched in Gmail Sent. Includes a five-minute break.
Pause: Keep the chapter clock visible.

20. Review one test and ten prospect messages.

Say: Eleven means one test plus ten prospects. It is a ceiling, not a target to fill at any cost.
Show: One row, including its plain text and HTML.
Pause: Six minutes. Wait for the participant to approve the actual copy.

21. 1 to you. 10 to prospects.

Say: These numbers define the scope. They are not a promise to fill every slot.
Show: The eleven-row review.
Pause: Wait for exact review before recording approval.

22. The Agency: The Pipeline Review

Say: Play the episode, then take the planned break.
Show: Keep the next step, send yourself a test, visible.
Pause: Three minutes of video, five minutes away from the screen.

23. Take five minutes.

Say: Tell participants the exact return time.
Show: The five-minute timer.
Pause: Do not continue the class while people are away.

24. Send the approved test to yourself.

Say: This is the first live send. One message. Your own inbox.
Show: The actual one-message selector and result.
Pause: Six minutes. Wait for the recorded result.

25. Open the actual email in Gmail Sent.

Say: Do not celebrate an API response. Open the actual message.
Show: Preview beside the real Sent email.
Pause: Four minutes. Confirm the match, or record the blocker.

26. Check your result before moving on.

Say: Pause here. Check the actual outputs.
Show: Point to each required file or result.
Pause: Wait until the checks are clear. Record a blocker instead of guessing.

Run the pilot. Save the skill.

27. Run the pilot. Save the skill.

Say: State the result of this chapter, then demonstrate one step.
Show: Results for your ten targets and a reusable email skill.
Pause: Keep the chapter clock visible.

28. Release only the approved ten-company pilot.

Say: If five are held, five are held. Do not replace recipients just to reach ten.
Show: A row for every target, including blocked and unknown rows.
Pause: Seven minutes. Reconcile original results. Do not press send twice.

29. Read the result. Save the next action.

Say: Separate sent messages from replies and meetings. Those are different outcomes.
Show: The result table, not a success headline.
Pause: Three minutes. Save the first unresolved next action.

30. Save the email-writing skill.

Say: The skill is instructions you can reuse. It is not new authority to send.
Show: Show the skill file and one new unsent draft.
Pause: Three minutes. Check the draft, not just whether a file exists.

31. Check your result before moving on.

Say: Pause here. Check the actual outputs.
Show: Point to each required file or result.
Pause: Wait until the checks are clear. Record a blocker instead of guessing.

Extra practice and help

32. Finished early? Make the next run useful.

Say: We have extra time for the operating work after a send.
Show: Actual replies, then the next allowed action.
Pause: If the pilot is blocked, use this time to fix the first blocker.

33. Extra: read replies and bookings.

Say: No replies yet is a real result. The pilot has only just started.
Show: An actual reply, or the zero-reply table.
Pause: Eight minutes. Check the original thread before choosing the next action.

34. Extra: prepare your next run.

Say: This is the bridge to a routine. We prepare it today, then prove another manual run before scheduling.
Show: Read the first three lines of NEXT-RUN.md.
Pause: Seven minutes. Name the first actual missing connection, if one remains.

35. Keep these assets.

Say: Show what exists in the participant project. Do not promise ten sends if there are holds.
Show: The files and the actual result table.
Pause: Ask for the first unresolved blocker, not a general confidence poll.

36. Part 3: add gifts, LinkedIn and ads.

Say: Today was one email lane. Part 3 adds channels to these same rules.
Show: The operating tree and the Part 3 registration QR.
Pause: Do not require the optional channel accounts today.

37. Ten minutes for questions and repairs.

Say: Start with the first actual failed check. Keep the class on one workflow.
Show: Actual error, without credentials.
Pause: Keep all unknown provider outcomes paused.