

Organization

TO: f00-sh / operators
FROM: joule implementer
SUBJECT: joule v0.1.10 - pipeline activation handoff + K3 pin path + file-layer map
REF: CHANGELOG.md [0.1.10], tag v0.1.10

v0.1.10 ships real multi-donor activation commitments on the infer bus (not empty non-tail ACKs), a documented file?layer map for Kimi-K3, and a pin script so operators can replace synthetic MANIFEST digests with real safetensors hashes without f00 hosting weights.

Summary

Non-tail shards produce domain-separated activation_hex handoffs; the tail verifies the full upstream set before generation. Synthetic kimi-k3-shards digests remain fail-closed in CI; real digests after pin-k3-shards.sh may unlock when content is staged. Placement model_layers stays pinned to verified meta (93).

Added

joule_cluster::pipeline activation helpers; ShardActivation on InferRequest/InferDone; docs/design/k3-file-layer-map-v0.md; scripts/pin-k3-shards.sh.

Changed

Control and mesh infer fanout is two-phase. quant_can_unlock_service_digests refuses only synthetic digests (not the quant id forever).

Not claimed

Full floating-point tensor pipeline-parallel K3 across donors is not claimed. CI still does not download multi-hundred-GB weights.

Verification

cargo test --workspace; cargo clippy --workspace --all-targets -- -D warnings; cargo fmt --all -- --check.

References

docs/design/cluster-v0.md; docs/design/k3-file-layer-map-v0.md; CHANGELOG.md [0.1.10].

joule implementer

cc: donors