Process & Decision Documentation

Process Overview Visualization (Group Work Only)

All Code was written by Fintan Sharpe with the aid of GenAI.
Selected screenshots from Visual Studio and our code files:






EXPLORER
GROUP4B_A2
assets
images
sounds
libraries
p5.min.js
.gitattributes
distraction.js
focusOrb.js
index.html
jsconfig.json
particles.js
player.js
README.md
sketch.js
style.css
task.js
ui.js
OUTLINE
particles.js
player.js
task.js
distraction.js
ui.js
p5.min.js
ui.js > drawWin
You, last week | 1 author (You)
function drawUI() {
fill(255);
textSize(18);
text("Level " + level, 80, 30);
text(
"Tasks " + tasks.filter((t) => t.done).length + "/" + tasks.length,
220,
30,
);
text("Time " + ceil(timer), 380, 30);
text("Focus", 540, 30);
fill(100);
rect(600, 20, 200, 16);
fill(0, 255, 150);
rect(600, 20, focus * 2, 16);
}
function drawTaskPanel() {
if (!activeTask) return;
fill(40);
rect(width - 260, 120, 220, 200, 10);
fill(255);
textSize(18);
textAlign(CENTER);
text("COMPLETE TASK", width - 150, 160);
let seqText = "";
for (let i = 0; i < sequence.length; i++) {
if (i < progress) seqText += "✓ ";
else seqText += sequence[i] + " ";
}
CHAT
SESSIONS
ui.js
Describe what to build next
Auto


EXPLORER
GROUP4B_A2
assets
images
sounds
libraries
p5.min.js
.gitattributes
distraction.js
focusOrb.js
index.html
jsconfig.json
particles.js
player.js
README.md
sketch.js
style.css
task.js
ui.js
OUTLINE
index.html
style.css
jsconfig.json
sketch.js
focusOrb.js
index.html > html > body > script
You, last week | 1 author (You)
~/Documents/GitHub/Group4B_A2/focusOrb.js
<!doctype html>
<html>
<head>
<meta charset="utf-8" />
<title>Focus Frenzy</title>
<link rel="stylesheet" href="style.css" />
</head>
<body>
ps://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/p5.min.js"></script>
<script src="player.js"></script>
<script src="task.js"></script>
<script src="distraction.js"></script>
<script src="ui.js"></script>
<script src="particles.js"></script>
<script src="focusOrb.js"></script>
<script src="sketch.js"></script>
You, last week • Game Prototype
</body>
</html>
CHAT
SESSIONS
index.html
Describe what to build next

safeSpace.js > SafeSpace > update

```javascript
class SafeSpace {
  constructor(tasks) {
    // keep away from edges
    let margin = 100;
    let valid = false;
    let tries = 0;

    while (!valid && tries < 50) {
      this.x = random(margin, width - margin);
      this.y = random(margin, height - margin);

      valid = true;

      for (let t of tasks) {
        if (dist(this.x, this.y, t.x, t.y) < 120) {
          valid = false;
          break;
        }
      }

      tries++;
    }

    this.maxSize = 80;
    this.size = this.maxSize;
    this.triggered = false;
    this.duration = 10000; // 10 seconds inside
    this.timeInside = 0;

    this.active = true;
    this.playerInside = false;
  }

  update(player) {
    if (!this.active) return;

    // check if player is inside
    this.playerInside =
      player.x > this.x - this.size / 2 &&
      player.x < this.x + this.size / 2 &&
      player.y > this.y - this.size / 2 &&
      player.y < this.y + this.size / 2;

    // 🚀 ONCE player enters → trigger permanently
    if (this.playerInside && !this.triggered) {
      this.triggered = true;
      if (safeZoneSound) safeZoneSound.play();
    }

    // ⏳ IF triggered → timer ALWAYS runs
    if (this.triggered) {
      this.timeInside += deltaTime;

      let progress = this.timeInside / this.duration;
```

sketch.js > initLevel

```javascript
let state = "menu";
let level = 1;

let tasks = [];
let distractions = [];

let focus = 100;
let timer = 60;

let activeTask = null;
let sequence = [];
let progress = 0;

let particles = [];
let focusOrbs = [];
let shake = 0;

function setup() {
  createCanvas(1000, 650);

  player = new Player();

  initLevel();
}

function draw() {
  if (state === "menu") drawMenu();
  if (state === "game") runGame();
  if (state === "win") drawWin();
  if (state === "lose") drawLose();
}

function runGame() {
  push();

  translate(random(-shake, shake), random(-shake, shake));
  drawLevelMap();

  player.update();
  player.draw();
```




```
}

function draw() {
  let sx = width / 1000;
  let sy = height / 650;
  if (state === "menu") {
    drawMenu();
    if (!menuMusic.isPlaying()) {
      menuMusic.loop();
      menuMusic.setVolume(0.4);
    }
  }
  if (state === "game") {
    runGame();
    if (menuMusic.isPlaying()) {
      menuMusic.stop();
    }
  }
  if (state === "win") {
    drawWin();
    if (menuMusic.isPlaying()) {
      menuMusic.stop();
    }
  }
  if (state === "lose") {
    drawLose();
    if (menuMusic.isPlaying()) {
      menuMusic.stop();
    }
  }
  if (state === "levelStart") {
    drawLevelStartScreen();
    if (menuMusic.isPlaying()) {
      menuMusic.stop();
    }
  }
  if (state === "game") {
    if (menuMusic.isPlaying()) {
      menuMusic.stop();
    }
    // RESET FLAG
    playerInSafeZone = false;

    // ONLY LEVEL 2+
    if (level >= 2) {
      // spawn ONLY if none exists AND cooldown passed
      if (!safeSpace && millis() - lastSafeSpawn > safeCooldown) {
        safeSpace = new SafeSpace(tasks);
      }

      // update if exists
      if (safeSpace) {
        safeSpace.update(player);
```





Project/Assignment Decisions

A1 – A3 (Group Work)

Through this assignment, we made various design changes and feature cuts through our early stages of design. Our initial idea was to have a character that started

off as a young child and have it grow overtime as it completed different tasks throughout the game. After our first playtesting and receiving feedback from our peers, we realized we needed to eliminate some features and simplify our game focusing on only a few key concepts that relate to ADHD rather than multiple concepts at once. As a result, we got rid of the idea of having our character start as a small child and grow overtime, we simplified the tasks, and made the game easier to understand without losing our main focus.

In addition, we also identified other opportunities for change that we would like to look into further for Assignment 3. New features we'd like to add such as a 'safe zone' and many other additions we think would further improve our game. Overall, we came to these design decisions through having peers play the game and give feedback but also having ourselves play the game and being able to identify flaws and areas for improvement.

Role-Based Process Evidence

Entry #1

Name: Mercedes Wilson

Role(s): Creative Director & Writer Lead

Primary responsibility for this work: Write introduction to our game

Goal of Work Session

Briefly describe what you were trying to accomplish during this phase of the assignment:

- Drafting introduction script of our game
- Explain game mechanics
- Clearly state why this game relates to ADHD
- Communicate how the game works

Tools, Resources, or Inputs Used:

- Team meeting discussions
- Initial brainstorming notes from group meeting
- Game explanations contributed by each team member

- Assignment 2 instructions - requirements for introducing the game

Entry #2

Name: Allison Kalist

Role(s): Technical Lead and Systems Architect; Mechanics Design

Primary responsibility for this work: Develop intended emotional outcomes, research ADHD, incorporate ADHD research into game mechanics, and develop playtesting notes.

Goal of Work Session

This work session was my only work session for the pre-play testing portion of this assignment.

- I researched ADHD and how someone with ADHD goes through a typical day
- Based on the ADHD research, I developed our game's intended emotional and experiential outcomes
- From these intended outcomes, I created a list of different game mechanics/features that would allow the player to empathize with ADHD
- I developed playtesting notes/prompts based on in-class activities and the assignment instructions

Tools, Resources, or Inputs Used

- GenAI was only used for work distribution (documented in my Week 6 journal)
- [1] Jessica McCabe. 2019. What it's like to live a day with ADHD. (April 2019). Retrieved March 01, 2026 from https://www.healthline.com/health/adhd/adult-adhd/a-day-in-the-life#The-part-where-I-wish-time-machines-were-a-thing
- [2] Vinay Saranga. 2024. The ADHD brain: A day in the life. (November 2024). Retrieved March 01, 2026 from https://www.ncinstneurohealth.com/the-adhd-brain-a-day-in-the-life
- [3] Anon. 2025. HOW ADHD affects your daily life. (April 2025). Retrieved March 1, 2026 from https://pnsoc.com/blog/how-adhd-affects-daily-life
- Playtesting note breakdown was taken from in-class activities (mechanics clarity, pacing & escalation, player interaction, etc.)

- Assignment 2 instructions

Entry #3

Name: Allison Kalist

Role(s): Technical Lead and Systems Architect; Mechanics Design

Primary responsibility for this work: Develop 3 concrete design changes from play-testing, and develop design changes from A2.

Goal of Work Session

This work happened during and after the play-testing.

- During play-testing, I was taking notes on player interaction, player struggles, empathy cues, mechanics clarity, confusion points, and pacing & escalation
- After play-testing I took my notes and the recommendations from Dr. Cochrane and the TA's to generate ideas for design changes
- I also created a comprehensive work breakdown of what design changes needed to be made for A3, and after play-testing
- I was also responsible for creating the README.md file and adding in the iteration notes

A3 Improvements

From A2

Mechanical Improvements	Design Changes
☐ Make the **power-ups** move normally (keep them on screen for about 7 seconds and then they disappear or fly off screen) ☐ Fix the **borders** so that they actually keep the player within bounds ☐ Add **sounds** • Music in the background (Geometry Dash type) • Alarm sound when focus bar drains • Small sound effect when typing to complete tasks • "Bing" sound when task is completed • Level-up sound when level is completed ☐ Update typing mechanics so it's clearer to a player when they make an error. Have the word "flash" with red and then make an **error sound**. ☐ Have the **volume increase** as enemies get closer to you (the player) so that pressure increases • Maybe have the music get more intense or the volume get louder as the level increase as well? ☑ ~~Fix **task hit box** – players can complete tasks outside of the task box, and sometimes the task doesn't start when the player is within the box~~ ☐ Fix **task boxes** so that they don't spawn in on top of each other ☑ ~~First level should be slightly easier, last level should be slightly harder~~ ☑ ~~**Slow distractions** down just slightly~~	☑ ~~Make the **emotion** of the smiley face change based on their focus bar (full = happy, ½ full = ok, ¼ full = sad)~~ • Change colour as well • Add the colour change to the background and focus bar as well so that elements of the whole screen are changing colour (green → yellow → red) • Get rid of the colour change difference in the levels right now, make it dependent only on the focus bar change) ☑ ~~Get rid of the **line in the middle** of the map~~ ☑ ~~Maybe **centre the game** on a screen instead of the top left?~~ ☐ Play with the **behaviours of the enemies** (have ones that move differently?) ☑ ~~Change the **typing codes** to actual words (just find a word bank online to pull from)~~ ☐ Implement an obvious screen change for when damage is being taken. **Have red flashes** on the screen that indicate **damage lost**. ☐ Indicate power-ups more clearly so players know what they do. The first couple times they appear **have a tag above** it that says "collect power-up!" (like in a tutorial). ☐ **Rewrite instructions** to be clearer, maybe have two pages? Also make the splash screen look nicer • Clarify that there is NO mouse interaction • See the bottom of this doc for new instructions

New For A3

Element/Mechanic/Feature	Details
Safe Space	- Appear as a flower or some other distinguishable shape - protect the player from the distractions chasing them - The player can stay in the safe space for a certain amount of time (5-7 seconds) - Safe space gradually shrinks before disappearing to show the countdown - Has a cooldown time of 5 seconds (roughly) before respawning.
Exit Task	- Press "X" to exit – all interactions should be kept to the keyboard - Have an X located top left of the task box – big enough for players to remember that they can exit - Make sure that player's progress is not saved when they come back to the task (task resets itself if the player moves away) - Make sure the code allows the player to actually move away from the task hit box after they exit the task (2-second cool down before it opens the task again)

A3 PLAYTESTING

PLAYTESTING NOTES —

Test #1	
Player Struggles - Didn't know when they messed up a letter (an error sound, change colours, slight flashing)	Empathy Cues -
Mechanics Clarity - Power ups/health	Confusion Points -
Player Interactions (confused, frustrated, engaged) -	Pacing & Escalation -

- Have stationary or moving damage that draws you in (magnetism) and causes damage

---

- Make sure the screen changes and there's a more obvious visual cue for when health drains

Tools, Resources, or Inputs Used

- Assignment 2/3 instructions
- README.md file setup instructions from A3 instructions

Entry #4

Name(s): Fintan and Sofia

Roles:

Gameplay design, Programming, UI/UX Implementation.

Primary responsibility for this work:

Designing and implementing the core gameplay systems and mechanics for the prototype, including player movement, task mechanics, distraction behaviour, UI systems, and visual feedback effects.

Goal of Work Session:

The goal of this work session was to develop and refine the core gameplay mechanics for our ADHD awareness game prototype. Specifically, we focused on implementing a playable structure that demonstrates the experience of maintaining focus while being interrupted by distractions.

During this phase, we worked on building multiple gameplay systems including the player movement system, the task completion mechanic using keyboard sequences, distraction behaviour that targets the player during tasks, and a focus meter that reflects the player's mental capacity. We also worked on improving the visual style and feedback systems to make the game feel more polished and responsive.

Additional refinements included implementing particle effects for task completion, screen shake feedback when the player is affected by distractions, and collectible focus orbs that restore focus to the player. These changes were intended to increase urgency and reinforce the core gameplay loop where the player must manage distractions while attempting to complete tasks.

Overall, the goal of this session was to move the prototype from a basic functional concept toward a more polished and engaging vertical slice that could be effectively playtested.

Tools Used:

GenAI tools: ChatGPT was used to assist with generating and refining JavaScript code for the p5.js game systems, including player animation, task mechanics, distraction behaviour, particle effects, and UI elements. It was also used to help troubleshoot coding issues and iterate on gameplay features.

Lecture notes and assignment guidelines: Used to ensure the prototype met the rubric requirements such as implementing multiple mechanics, creating a playable level structure, and focusing on an entertainment-oriented game experience.

Prior code drafts: Earlier versions of the game prototype were iteratively modified to add new mechanics and improve the gameplay loop.

Teammate discussions: The concept and mechanics were informed by group discussions regarding how to represent ADHD experiences through gameplay while maintaining an engaging entertainment-focused design.

GenAI Documentation

If GenAI was used (keep each response as brief as possible):

Date Used: Week of April 6, 2026

Tool Disclosure: ChatGPT (OpenAI), GPT 5.3

Purpose of Use: GenAI was used primarily for coding support, brainstorming gameplay mechanics, debugging JavaScript code in a p5.js environment, and helping structure UI and gameplay systems. It was also used to help document text and organize development steps.

Summary of Interaction: The tool assisted with generating JavaScript code for a p5.js browser-based game prototype, including player movement, task mechanics, distraction behaviour, UI layout, particle effects, and focus meter systems. It also helped suggest gameplay improvements such as keyboard-sequence tasks, distraction AI behaviour, particle feedback, focus pickups, and screen shake effects. Additionally, it helped structure the project folder organization and documentation sections for the assignment.

Human Decision Point(s): Several outputs from GenAI were modified or redirected during development. For example, the initial game concept and code generated earlier in the interaction were rejected and replaced with a new concept and visual style direction (a Pong-inspired neon aesthetic). Mechanics were adjusted to better match the intended ADHD theme, such as changing tasks from simple clicking interactions to keyboard sequence mini-games that lock player movement and increase pressure from distractions. Visual style, difficulty progression, and UI changes were also iteratively refined through human direction rather than directly accepting the initial generated solutions.

Integrity & Verification Note: All generated code was manually reviewed and tested within Visual Studio Code and the p5.js environment. Errors and logic issues were identified through testing and adjusted as necessary. Gameplay systems were evaluated against the assignment rubric to ensure the prototype demonstrated multiple mechanics, clear interaction systems, and an entertainment-focused design that raises awareness of ADHD experiences.

Scope of GenAI Use: GenAI assisted with coding support, debugging, and brainstorming technical implementations. However, the overall game concept, design direction, mechanic adjustments, and final decisions about gameplay structure, visual style, and difficulty progression were determined by the human developer and project group.

Limitations or Misfires: Some generated code required modification before functioning correctly within the existing project structure. Early suggestions also produced overly complex systems or mechanics that did not align with the intended visual style or gameplay direction, requiring simplification and redesign. Additionally, the tool could not account for the specific requirements of the assignment rubric without further clarification from us.

Summary of Process (Human + Tool)

We started coding ourselves and quickly realised that in order to make the game better, we needed to incorporate GenAI tools to further refine the design concepts and creative aspects. We also used GenAI to enhance the quality of our game and implement more advanced mechanics like the safe spaces.

Decision Points & Trade-offs

One key decision that we made was when our original idea was to create a game with various tasks within it, making it very challenging to code. As a result, we changed our idea to one game concept and goal, eliminating the rest in order to focus on the quality of the game instead of the quantity of tasks. We also reduced the amount of design changes that we were making, as some of them were too complex for the GenAI to add in addition to everything else that we had.

Verification & Judgement

We evaluated whether our decision was appropriate by the playtesting done in class. Professors mentioned that we needed to simplify the game. We also had various group discussions related to the game design and various components before and after we modified them. Our group partner for play-testing recommended that we add in some more features (which we didn't do for complexity reasons), and make the errors more obvious which helped us determine what was most important for player experience.

Limitations, Dead Ends, or Open Questions

We unfortunately were not able to add every design change that we originally wanted to (including magnetic force to make the game harder) because of complexity, which would have been nice to be able to implement.

Appendix

This transcript is additional to our transcript from A2. The text was from the same conversation, just continued.

FULL TRANSCRIPT:

So this is my game for our class, what I would like to do next is add a new element to game called "Safe spaces." They will be blue squares that will spawn every 10, and stay in the game for 10 seconds, where when the player enters the safe space the distractions will start moving away from the player instead of towards the player. I want these to be in levels 2 and 3.

This is a really solid feature idea—it actually fits your game theme *perfectly* (temporary relief from overwhelm). I'll walk you through exactly how to implement it cleanly with your current structure.

🧠 What You're Adding (Quick Breakdown)

- Blue square = **Safe Space**
- Spawns every **10 seconds**
- Exists for **10 seconds**
- Only in **levels 2 & 3**
- Effect:
    - When player is inside → distractions move **away** instead of toward

---

🧩 Step 1: Create `safeSpace.js`

Add a new file and include it in your HTML (just like your others in):

<script src="safeSpace.js"></script>

`safeSpace.js`

```
class SafeSpace {
 constructor() {
   this.x = random(width);
   this.y = random(height);
   this.size = 60;
   this.spawnTime = millis();
   this.duration = 10000; // 10 seconds
```

```
  }

  update() {
    // nothing needed for now
  }

  display() {
    push();
    noStroke();
    fill(0, 150, 255, 180); // blue
    rectMode(CENTER);
    rect(this.x, this.y, this.size);
    pop();
  }

  isExpired() {
    return millis() - this.spawnTime > this.duration;
  }

  contains(player) {
    return (
      player.x > this.x - this.size / 2 &&
      player.x < this.x + this.size / 2 &&
      player.y > this.y - this.size / 2 &&
      player.y < this.y + this.size / 2
    );
  }
}
```

🧩 Step 2: Add Globals in `sketch.js`

At the top:

```
let safeSpaces = [];
let lastSafeSpawn = 0;
let safeSpawnInterval = 10000; // 10 seconds
let playerInSafeZone = false;
```

🧩 Step 3: Spawn Logic (LEVEL 2 & 3 ONLY)

Inside your `draw()` loop:

```
if (level >= 2) {
 if (millis() - lastSafeSpawn > safeSpawnInterval) {
   safeSpaces.push(new SafeSpace());
   lastSafeSpawn = millis();
 }
}
```

🧩 Step 4: Update + Remove Expired Safe Spaces

Still in `draw()`:

```
for (let i = safeSpaces.length - 1; i >= 0; i--) {
 let s = safeSpaces[i];
 s.update();
 s.display();

 if (s.isExpired()) {
   safeSpaces.splice(i, 1);
 }
}
```

🧩 Step 5: Detect If Player Is Inside

```
playerInSafeZone = false;

for (let s of safeSpaces) {
 if (s.contains(player)) {
   playerInSafeZone = true;
   break;
 }
```

```
}
```

🧩 Step 6: Modify Distraction Behavior

Now go into `distraction.js` and find where they move toward the player.

You probably have something like:

```
let dir = createVector(player.x - this.x, player.y - this.y);
dir.normalize();
```

🔁 Replace with:

```
let dir;

if (playerInSafeZone) {
 // move AWAY from player
 dir = createVector(this.x - player.x, this.y - player.y);
} else {
 // move TOWARD player
 dir = createVector(player.x - this.x, player.y - this.y);
}

dir.normalize();
this.x += dir.x * this.speed;
this.y += dir.y * this.speed;
```

🧩 Step 7: Optional (but HIGHLY recommended)

Add feedback so player KNOWS it's working:

Inside your draw loop:

```
if (playerInSafeZone) {
 push();
 fill(0, 200, 255);
 textSize(16);
 textAlign(CENTER);
```

```
 text("SAFE ZONE", width / 2, 30);
 pop();
}
```

🔥 What You Just Added (Game Design Impact)

This mechanic does a lot:

- Creates **strategic positioning**
- Gives player **brief relief (ADHD metaphor)**
- Adds **timing + risk/reward**
- Makes later levels feel **more dynamic**

🚀 If You Want to Level It Up Further

Super quick upgrades you could add (if you have time):

- Safe space slowly **shrinks before disappearing**
- Add **glow effect / particles**
- Slight **focus regeneration inside**
- Add a **cooldown before next spawn**

If you want, I can:

- Plug this directly into your actual files (line-by-line edits)
- Or help you debug when something inevitably breaks 😄

Can you give me the entire code for the files to just copy and paste in

Got you — I'll give you **clean, copy-paste-ready versions** for the *new file* + the **exact edits** you need in your existing files without breaking your project.

✅ 1. NEW FILE — `safeSpace.js`

Create this file:

```
class SafeSpace {
 constructor() {
   this.x = random(width);
   this.y = random(height);
   this.size = 60;
   this.spawnTime = millis();
   this.duration = 10000; // 10 seconds
 }

 update() {
   // no movement needed
 }

 display() {
   push();
   rectMode(CENTER);
   noStroke();
   fill(0, 150, 255, 180);
   rect(this.x, this.y, this.size);
   pop();
 }

 isExpired() {
   return millis() - this.spawnTime > this.duration;
 }

 contains(player) {
   return (
     player.x > this.x - this.size / 2 &&
     player.x < this.x + this.size / 2 &&
     player.y > this.y - this.size / 2 &&
     player.y < this.y + this.size / 2
   );
 }
}
```

✅ 2. UPDATE `index.html`

Add this line BEFORE `sketch.js`:

```
<script src="safeSpace.js"></script>
```

(Just like your other scripts in)

✅ 3. UPDATE `sketch.js`

🔹 ADD THESE GLOBAL VARIABLES (top of file)

```
let safeSpaces = [];
let lastSafeSpawn = 0;
let safeSpawnInterval = 10000;
let playerInSafeZone = false;
```

🔹 ADD THIS INSIDE `draw()`

1. Spawn safe spaces (LEVEL 2 & 3 only)

```
if (level >= 2) {
 if (millis() - lastSafeSpawn > safeSpawnInterval) {
   safeSpaces.push(new SafeSpace());
   lastSafeSpawn = millis();
 }
}
```

---

2. Update + draw safe spaces

```
for (let i = safeSpaces.length - 1; i >= 0; i--) {
 let s = safeSpaces[i];
 s.update();
 s.display();

 if (s.isExpired()) {
   safeSpaces.splice(i, 1);
 }
}
```

---

3. Detect if player is inside

```
playerInSafeZone = false;

for (let s of safeSpaces) {
 if (s.contains(player)) {
   playerInSafeZone = true;
   break;
 }
}
```

---

4. (OPTIONAL BUT NICE) UI feedback

```
if (playerInSafeZone) {
 push();
 fill(0, 200, 255);
 textSize(18);
 textAlign(CENTER);
 text("SAFE ZONE", width / 2, 40);
 pop();
}
```

✅ 4. UPDATE `distraction.js`

Find your movement logic (where distractions chase player).

🔁 REPLACE IT WITH THIS:

```
let dir;

if (playerInSafeZone) {
 // move AWAY from player
 dir = createVector(this.x - player.x, this.y - player.y);
} else {
 // move TOWARD player
 dir = createVector(player.x - this.x, player.y - this.y);
}

dir.normalize();

this.x += dir.x * this.speed;
this.y += dir.y * this.speed;
```

🚨 Common Bugs (so you don't get stuck)

If something breaks, it's almost always one of these:

❌ `playerInSafeZone is not defined`

→ Make sure it's declared **globally in sketch.js**

❌ Safe spaces not spawning

→ Check:

if (level >= 2)

Make sure your level variable actually hits 2+

❌ Distractions not reacting

→ Make sure:

- `playerInSafeZone` is **global**
- distraction.js can "see" it

🔥 You're Done — What This Adds

- Dynamic difficulty shift mid-level
- Strategic positioning
- A literal "breathing room" mechanic (super on-theme)

If you want next step upgrades, I'd go:

- shrinking safe zones
- healing inside them
- particle glow

Just say the word and I'll wire that in too.

OK, the safe spaces work great, but I think we need some changes: -We need them to shrink to show that they are disapearing -We need them to only disappear after the player has been inside it for 10 seconds -We need to make sure they are spawning towards the inside of the map -A number timer on the inside of the square that shows when they disappear would be great. -Another safe space shouldn't spawn while another is active, and after one disappears another shouldn't spawn for 15 seconds

Perfect—these are *exactly* the right polish features. Let's upgrade your system cleanly without breaking what already works.

I'll give you **full updated code blocks to replace**, not fragments.

✅ 1. REPLACE `safeSpace.js` (FULL FILE)

This version adds:

- shrinking
- countdown timer
- only expires after player stays inside 10s
- spawns away from edges

```
class SafeSpace {
 constructor() {
   // keep away from edges
   let margin = 100;
   this.x = random(margin, width - margin);
   this.y = random(margin, height - margin);

   this.maxSize = 80;
   this.size = this.maxSize;

   this.duration = 10000; // 10 seconds inside
   this.timeInside = 0;

   this.active = true;
   this.playerInside = false;
 }
```

```
update(player) {
  if (!this.active) return;

  // check if player is inside
  this.playerInside =
    player.x > this.x - this.size / 2 &&
    player.x < this.x + this.size / 2 &&
    player.y > this.y - this.size / 2 &&
    player.y < this.y + this.size / 2;

  if (this.playerInside) {
    this.timeInside += deltaTime;

    // shrink based on time spent inside
    let progress = this.timeInside / this.duration;
    this.size = this.maxSize * (1 - progress);

    if (this.timeInside >= this.duration) {
      this.active = false;
    }
  }
}

display() {
  if (!this.active) return;

  push();
  rectMode(CENTER);
  noStroke();
  fill(0, 150, 255, 180);
  rect(this.x, this.y, this.size);

  // TIMER TEXT
  let secondsLeft = max(0, ceil((this.duration - this.timeInside) / 1000));

  fill(255);
  textAlign(CENTER, CENTER);
  textSize(16);
  text(secondsLeft, this.x, this.y);

  pop();
}
```

```
 isDone() {
   return !this.active;
 }
}
```

✅ 2. UPDATE `sketch.js` (IMPORTANT CHANGES)

🔹 REPLACE your globals with this:

```
let safeSpace = null;
let lastSafeSpawn = -15000; // so first one can spawn immediately
let safeCooldown = 15000; // 15 seconds after one disappears
let playerInSafeZone = false;
```

🔹 REPLACE ALL safe space logic inside `draw()` with this:

```
// RESET FLAG
playerInSafeZone = false;

// ONLY LEVEL 2+
if (level >= 2) {
 // spawn ONLY if none exists AND cooldown passed
 if (!safeSpace && millis() - lastSafeSpawn > safeCooldown) {
   safeSpace = new SafeSpace();
 }

 // update if exists
 if (safeSpace) {
   safeSpace.update(player);
   safeSpace.display();

   if (safeSpace.playerInside) {
     playerInSafeZone = true;
   }
```

```
  // remove when done + start cooldown
  if (safeSpace.isDone()) {
    safeSpace = null;
    lastSafeSpawn = millis();
  }
 }
}
```

✅ 3. KEEP YOUR `distraction.js` CHANGE (same as before)

Just make sure you still have:

```
let dir;

if (playerInSafeZone) {
 dir = createVector(this.x - player.x, this.y - player.y);
} else {
 dir = createVector(player.x - this.x, player.y - this.y);
}

dir.normalize();

this.x += dir.x * this.speed;
this.y += dir.y * this.speed;
```

🔥 What You Just Fixed / Added

Now your system behaves like:

✔ Smart spawning

- Never near edges
- Only 1 at a time
- 15s cooldown after use

✔ True “safe zone” mechanic

- Only shrinks when player is inside
- Doesn't disappear if ignored

✔ Visual clarity

- Shrinks = urgency
- Countdown timer = pressure

✔ Gameplay depth

- Forces player decision:
  - "Do I commit now or save it?"

💡 Optional Next-Level Polish (if you want extra marks)

If you have time, these are 🔥 additions:

- Add glow:

```
stroke(0, 200, 255);
strokeWeight(3);
noFill();
rect(this.x, this.y, this.size + 10);
```

- Slight heal while inside:

```
if (this.playerInside) {
 player.focus = min(player.focus + 0.05, player.maxFocus);
}
```

If you want, I can:

- Add shrinking animation smoothing (less linear)
- Make distractions panic/scatter harder inside zone
- Or help you explain this mechanic in your assignment writeup (this is actually a *great* design justification piece)

Just say 👍

Where do I add those next level polish code pieces you suggested at the end there

Good question—this is exactly where people usually get tripped up. I'll show you *precisely* where each piece goes so nothing breaks.

✨ 1. GLOW EFFECT (goes in `safeSpace.js` → inside `display()`)

Find this part in your `display()`:

```
rect(this.x, this.y, this.size);
```

🔁 REPLACE that section with this:

```
// glow outline
stroke(0, 200, 255);
strokeWeight(3);
noFill();
rect(this.x, this.y, this.size + 10);

// main square
noStroke();
fill(0, 150, 255, 180);
rect(this.x, this.y, this.size);
```

✅ Full context inside `display()` should look like:

```
display() {
 if (!this.active) return;

 push();
 rectMode(CENTER);

 // glow
 stroke(0, 200, 255);
 strokeWeight(3);
 noFill();
 rect(this.x, this.y, this.size + 10);
```

```
 // main square
 noStroke();
 fill(0, 150, 255, 180);
 rect(this.x, this.y, this.size);

 // timer
 let secondsLeft = max(0, ceil((this.duration - this.timeInside) / 1000));

 fill(255);
 textAlign(CENTER, CENTER);
 textSize(16);
 text(secondsLeft, this.x, this.y);

 pop();
}
```

💚 2. HEAL EFFECT (goes in `safeSpace.js` → inside `update()`)

Find this block:

```
if (this.playerInside) {
 this.timeInside += deltaTime;
```

🔁 MODIFY it to:

```
if (this.playerInside) {
 this.timeInside += deltaTime;

 // 💚 HEAL PLAYER WHILE INSIDE
 if (player.focus !== undefined && player.maxFocus !== undefined) {
   player.focus = min(player.focus + 0.05, player.maxFocus);
 }
```

⚠️ IMPORTANT

This assumes your player uses:

player.focus

player.maxFocus

❗ If your variables are named differently:

Common alternatives:

- `player.health`
- `player.energy`
- `player.focusBar`

👉 If you're unsure, paste your `player.js` and I'll match it exactly.

🧠 Why these placements matter

- `display()` → visuals only (glow)
- `update()` → gameplay logic (healing)

If you mix them up:

- You'll either get no effect
- Or weird bugs (like healing every frame regardless of position)

🔥 Result After This

Now your safe space:

- ✨ Glows (easy to spot)
- ⏳ Shrinks + countdown
- 💚 Rewards staying inside
- 😈 Still risky because time-limited

If you want one last insane polish (like A+ level):

👉 Make the glow **pulse** (breathing effect)

I can add that in like 3 lines.

They look great! Everything is perfect, but here are some bug fixes I want to do to make the game really polished: -I need the tasks not to spawn on top of each other -I need the safe spaces to not spawn on top of the tasks -When A player loses focus and the game has to reset, I need all the safe spaces and focus particles to reset and disappear. -When A player enters the safe space, the timer starts to go down, but when the player leaves the safe space, the timer will continue to go down instead of pausing.

You're basically at "polished game" level now—these are exactly the kinds of fixes that separate a good project from a *really* solid one. Let's tighten everything up cleanly.

✅ 1. PREVENT TASKS FROM OVERLAPPING

You'll fix this where tasks are created (likely in `sketch.js` or wherever you spawn them).

🔹 Add a helper function (put near top of `sketch.js`):

```
function isTooClose(x, y, others, minDist) {
 for (let o of others) {
   let d = dist(x, y, o.x, o.y);
   if (d < minDist) return true;
 }
 return false;
}
```

🔹 When spawning tasks, REPLACE your spawn logic with:

```
function spawnTask() {
 let x, y;
 let tries = 0;

 do {
   x = random(100, width - 100);
```

```
  y = random(100, height - 100);
  tries++;
 } while (
  isTooClose(x, y, tasks, 120) && tries < 50
 );

 tasks.push(new Task(x, y));
}
```

✅ 2. PREVENT SAFE SPACE SPAWNING ON TASKS

Modify your `SafeSpace` constructor.

🔁 REPLACE constructor position logic with:

```
constructor(tasks) {
 let margin = 100;
 let valid = false;
 let tries = 0;

 while (!valid && tries < 50) {
  this.x = random(margin, width - margin);
  this.y = random(margin, height - margin);

  valid = true;

  for (let t of tasks) {
   if (dist(this.x, this.y, t.x, t.y) < 120) {
    valid = false;
    break;
   }
  }

  tries++;
 }

 this.maxSize = 80;
```

```
 this.size = this.maxSize;

 this.duration = 10000;
 this.timeInside = 0;

 this.active = true;
 this.playerInside = false;
}
```

🔹 IMPORTANT: Update where you create it in `sketch.js`

```
safeSpace = new SafeSpace(tasks);
```

✅ 3. RESET SAFE SPACES + PARTICLES ON GAME RESET

Wherever your game resets (likely something like `resetGame()` or when focus hits 0):

🔹 ADD THIS:

```
safeSpace = null;
lastSafeSpawn = -15000;
```

🔹 ALSO reset particles (depends on your variable name)

If you have something like:

```
let particles = [];
```

Then:

```
particles = [];
```

👉 If your particles are named differently (like `focusOrbs`), just clear that array.

✅ 4. FIX TIMER PAUSE BUG (MOST IMPORTANT ONE)

Right now:

Timer keeps going even after leaving safe space ❌

We want:

Timer ONLY decreases while inside ✅

🔁 FIND this in `safeSpace.js` → inside `update()`:

```
if (this.playerInside) {
 this.timeInside += deltaTime;
```

🔁 REPLACE ENTIRE update() WITH THIS:

```
update(player) {
 if (!this.active) return;

 // check if inside
 this.playerInside =
   player.x > this.x - this.size / 2 &&
   player.x < this.x + this.size / 2 &&
   player.y > this.y - this.size / 2 &&
   player.y < this.y + this.size / 2;

 // ONLY progress timer if inside
 if (this.playerInside) {
   this.timeInside += deltaTime;

   // shrink based on usage
   let progress = this.timeInside / this.duration;
   this.size = this.maxSize * (1 - progress);

   // optional heal
```

```
  if (player.focus !== undefined && player.maxFocus !== undefined) {
    player.focus = min(player.focus + 0.05, player.maxFocus);
  }

  if (this.timeInside >= this.duration) {
    this.active = false;
  }
 }
}
```

🧠 Why this fixes it

- Timer ONLY increases while inside
- Leaving = freeze timer
- Re-enter = resume where you left off

Exactly what you want.

🔥 FINAL RESULT (What You Just Fixed)

✔ Tasks

- Never overlap
- Always readable / fair

✔ Safe Spaces

- Never spawn on tasks
- Spawn in valid positions only

✔ Reset System

- No leftover objects after death
- Clean restart every time

✔ Timer Behavior

- Feels intentional + fair
- Encourages strategic use instead of panic

💯 If You Want One Last “A+ Polish” Touch

Add this inside `display()` for pressure:

```
if (this.playerInside && this.timeInside > this.duration * 0.7) {
 fill(255, 50, 50);
}
```

→ Timer turns red near the end 😈

If you want, next I can:

- Balance difficulty across levels (this is HUGE for grading)
- Or help you write the design justification for safe spaces (this mechanic is actually *very* strong conceptually)

Just say 👍

I need you to tell me exactly where to put all this code cause I didn't write all this, I need exact guidance

Perfect—that’s exactly what you need at this stage. I’m going to give you **surgical, exact placement instructions** so you can follow along without guessing.

🧩 1. FIX TASK OVERLAP (in `sketch.js`)

🔹 STEP 1 — Add helper function

📍 **Where:** very top of `sketch.js`, with your other functions (above `setup()` is safest)

```
function isTooClose(x, y, others, minDist) {
 for (let o of others) {
```

```
  let d = dist(x, y, o.x, o.y);
  if (d < minDist) return true;
 }
 return false;
}
```

🔹 STEP 2 — Find where tasks are created

In `sketch.js`, look for something like:

```
tasks.push(new Task(...));
```

OR a loop like:

```
for (...) {
 tasks.push(new Task(x, y));
}
```

🔹 STEP 3 — Replace ONLY the spawn logic

Replace that section with:

```
let x, y;
let tries = 0;

do {
 x = random(100, width - 100);
 y = random(100, height - 100);
 tries++;
} while (isTooClose(x, y, tasks, 120) && tries < 50);

tasks.push(new Task(x, y));
```

🧩 2. SAFE SPACE NOT SPAWNING ON TASKS

🔹 STEP 1 — Open `safeSpace.js`

Find this line:

```
constructor() {
```

🔹 STEP 2 — Replace the FIRST part of constructor

Replace everything from:

```
constructor() {
 let margin = 100;
 this.x = ...
```

✅ WITH THIS:

```
constructor(tasks) {
 let margin = 100;
 let valid = false;
 let tries = 0;

 while (!valid && tries < 50) {
   this.x = random(margin, width - margin);
   this.y = random(margin, height - margin);

   valid = true;

   for (let t of tasks) {
     if (dist(this.x, this.y, t.x, t.y) < 120) {
       valid = false;
       break;
     }
   }

   tries++;
 }
```

👉 Leave the rest of the constructor unchanged (size, duration, etc.)

🔹 STEP 3 — Update where SafeSpace is created

📍 Go to `sketch.js`

Find:

safeSpace = new SafeSpace();

🔁 **Replace with:**

safeSpace = new SafeSpace(tasks);

🧩 3. RESET ON GAME OVER

🔹 STEP 1 — Find your reset logic

In `sketch.js`, look for something like:

function resetGame()

OR where you detect losing focus:

if (player.focus <= 0)

🔹 STEP 2 — ADD these lines inside that reset block

safeSpace = null;
lastSafeSpawn = -15000;

🔹 STEP 3 — Clear particles

Find your particle array (likely in `sketch.js`):

particles = [];

OR:

focusOrbs = [];

👉 Add this inside reset too.

🧩 4. FIX TIMER (PAUSE WHEN LEAVING)

🔹 STEP 1 — Open `safeSpace.js`

Find this function:

update(player)

🔹 STEP 2 — Replace the ENTIRE function

Delete everything inside `update()` and replace with:

```
update(player) {
 if (!this.active) return;

 // check if inside
 this.playerInside =
   player.x > this.x - this.size / 2 &&
   player.x < this.x + this.size / 2 &&
   player.y > this.y - this.size / 2 &&
   player.y < this.y + this.size / 2;

 // ONLY count time if inside
 if (this.playerInside) {
   this.timeInside += deltaTime;

   let progress = this.timeInside / this.duration;
   this.size = this.maxSize * (1 - progress);

   if (player.focus !== undefined && player.maxFocus !== undefined) {
     player.focus = min(player.focus + 0.05, player.maxFocus);
   }

   if (this.timeInside >= this.duration) {
     this.active = false;
```

```
  }
 }
}
```

🧩 5. QUICK CHECKLIST (VERY IMPORTANT)

Before running your game, confirm:

- ✅ `safeSpace = new SafeSpace(tasks);`
- ✅ `isTooClose()` is at top of `sketch.js`
- ✅ reset includes:
  - `safeSpace = null`
  - `lastSafeSpawn = -15000`
- ✅ update() fully replaced

🚨 If Something Breaks

Tell me ONE of these and I'll fix it instantly:

- "Tasks not spawning anymore"
- "Safe space not appearing"
- "Game crashes on reset"
- "Player not healing"

You're seriously at the final polish stage now—this is the difference between a **B+ project and an A**.

Ok that all worked, but I need the safe spaces to continue the timer even if the player has left the safe space. So to re-iterate, when the player enters the safe space, the timer starts and it starts to shrink and it doesn't stop, then it disappears and the cooldown starts.

Ahh got it—you want **"trigger once → runs to completion"** behavior instead of "pause/resume." That's a really good design choice.

Right now your logic is:

timer only runs while inside ❌

We're changing it to:

entering once **activates it permanently** ✅

🔧 EXACT CHANGE (ONLY in `safeSpace.js`)

🔹 STEP 1 — Add a new variable

📍 In your `constructor`, add this line:

```
this.triggered = false;
```

Your constructor should now include:

```
this.active = true;
this.playerInside = false;
this.triggered = false; // 👈 ADD THIS
```

🔹 STEP 2 — Replace `update()` completely

📍 Find:

```
update(player)
```

🔁 Replace the entire function with this:

```
update(player) {
 if (!this.active) return;

 // check if player is inside
 this.playerInside =
   player.x > this.x - this.size / 2 &&
```

```
    player.x < this.x + this.size / 2 &&
    player.y > this.y - this.size / 2 &&
    player.y < this.y + this.size / 2;

  // 🚀 ONCE player enters → trigger permanently
  if (this.playerInside && !this.triggered) {
    this.triggered = true;
  }

  // ⏳ IF triggered → timer ALWAYS runs
  if (this.triggered) {
    this.timeInside += deltaTime;

    let progress = this.timeInside / this.duration;
    this.size = this.maxSize * (1 - progress);

    // optional heal ONLY while inside
    if (this.playerInside) {
      if (player.focus !== undefined && player.maxFocus !== undefined) {
        player.focus = min(player.focus + 0.05, player.maxFocus);
      }
    }

    if (this.timeInside >= this.duration) {
      this.active = false;
    }
  }
}
```

🧠 What This Fix Does

Before:

- Enter → timer starts
- Leave → timer pauses ❌

Now:

- Enter → timer starts
- Leave → timer **keeps going** ✅
- Re-enter → continues shrinking

- Eventually → disappears no matter what

🔥 Gameplay Effect (this is actually strong design)

- Forces commitment: *“do I use it now?”*
- Prevents abuse (no dipping in/out)
- Adds urgency once activated
- Feels more like a **temporary mental reset window**

✅ You DON’T need to change anything else

- Cooldown logic ✅ already works
- Spawn logic ✅ already works
- Distraction behavior ✅ already works

If you want one final spicy polish:

👉 Make it flash when triggered:

```
if (this.triggered) {
 fill(0, 200 + sin(frameCount * 0.2) * 55, 255);
}
```

I can also help you turn this into a **killer design explanation paragraph** for your assignment (this mechanic is actually very defensible academically).

The next change I want to make to game is about the change between levels, I want to add a start screen before each level. Instead of the next level automatically starting, when the player beats a level, I want to have a screen that says like "Start level 2" and then I want it to look similar to the title screen.

Nice—this is a *big polish win*. It makes your game feel way more intentional instead of “just continuing.”

I’ll show you **exactly how to insert a level transition screen without breaking your current flow**.

🧠 CORE IDEA

You’re adding a new **game state**:

Instead of just:

```
playing
gameOver
```

You’ll now have:

```
"menu"       // title screen
"levelStart"  // NEW (what we’re adding)
"playing"
"gameOver"
```

🧩 STEP 1 — Add a new state variable

📍 In `sketch.js` (top of file, with your globals)

Find something like:

```
let gameState = "menu";
```

✅ Make sure you have this:

```
let gameState = "menu";
let level = 1;
```

🧩 STEP 2 — Create the LEVEL START SCREEN

📍 In `sketch.js`, **add this new function anywhere below setup()**

```
function drawLevelStartScreen() {
 background(20);

 fill(255);
 textAlign(CENTER, CENTER);

 textSize(40);
 text("Level " + level, width / 2, height / 2 - 40);

 textSize(24);
 text("Press SPACE to start", width / 2, height / 2 + 20);
}
```

🧩 STEP 3 — Hook it into your `draw()`

📍 Find your main `draw()` function

You probably have something like:

```
if (gameState === "menu") {
 drawMenu();
} else if (gameState === "playing") {
 runGame();
}
```

🔁 MODIFY it to include:

```
if (gameState === "menu") {
 drawMenu();
}
else if (gameState === "levelStart") {
 drawLevelStartScreen();
}
else if (gameState === "playing") {
```

```
 runGame(); // or whatever your main game function is
}
```

🧩 STEP 4 — Change level progression logic

📍 Find where you detect level completion

Something like:

```
if (tasks.length === 0) {
 level++;
}
```

🔁 REPLACE with:

```
if (tasks.length === 0) {
 level++;
 gameState = "levelStart";
}
```

🧩 STEP 5 — Modify SPACE key behavior

📍 Find your `keyPressed()` function

You probably have:

```
if (key === ' ') {
 gameState = "playing";
}
```

🔁 REPLACE with this:

```
if (key === ' ') {

 if (gameState === "menu") {
   level = 1;
   setupLevel(); // if you have one
```

```
  gameState = "levelStart";
 }
 else if (gameState === "levelStart") {
  setupLevel(); // reset tasks, enemies, etc.
  gameState = "playing";
 }
 else if (gameState === "gameOver") {
  level = 1;
  setupLevel();
  gameState = "levelStart";
 }
}
```

🧩 STEP 6 — IMPORTANT: Reset level content properly

If you **don't already have a function**, create this:

📍 In `sketch.js`

```
function setupLevel() {
 // clear everything
 tasks = [];
 distractions = [];
 safeSpace = null;

 // reset timers
 lastSafeSpawn = -15000;

 // spawn tasks based on level
 for (let i = 0; i < level + 2; i++) {
  let x, y;
  let tries = 0;

  do {
   x = random(100, width - 100);
   y = random(100, height - 100);
   tries++;
  } while (isTooClose(x, y, tasks, 120) && tries < 50);

  tasks.push(new Task(x, y));
```

```
 }
}
```

🎨 OPTIONAL: Make it look like your title screen

If your title screen has styling (colors, fonts, etc.), copy that into:

drawLevelStartScreen()

You can even change text to:

text("START LEVEL " + level, ...)

🔥 FINAL RESULT

Now your flow is:

🎮 Game Flow

1. Menu
2. → Level Start Screen
3. → Playing
4. → Level Complete
5. → Level Start Screen
6. → Next Level

💯 Why this is a BIG upgrade

- Gives player a **mental reset** (fits your ADHD theme 👀)
- Prevents sudden overwhelm spike between levels
- Feels like a **real game loop**, not a demo

If you want next level polish:

- Fade-in transition between levels
- Show “Level Complete” for 2 seconds
- Add subtle animation to text

Just say the word 👍

For some reason, the safe spaces are spawning on the menus, so I need the safe spaces to only spawn when the game is in the game state

Yep—this is happening because your **safe space spawn logic is still running even when you're not in `"playing"` state**.

We’ll fix it cleanly so:

> Safe spaces ONLY exist and update during gameplay

🔧 EXACT FIX (in `sketch.js`)

🔹 STEP 1 — Find your safe space logic

In your `draw()` function, you should have something like:

```
// safe space logic
if (level >= 2) {
 if (!safeSpace && millis() - lastSafeSpawn > safeCooldown) {
   safeSpace = new SafeSpace(tasks);
 }

 if (safeSpace) {
   safeSpace.update(player);
   safeSpace.display();

   if (safeSpace.playerInside) {
     playerInSafeZone = true;
   }

   if (safeSpace.isDone()) {
```

```
    safeSpace = null;
    lastSafeSpawn = millis();
  }
 }
}
```

🔹 STEP 2 — Wrap ALL of that in `"playing"` state

🔁 REPLACE it with:

```
if (gameState === "playing") {

 playerInSafeZone = false;

 if (level >= 2) {
   if (!safeSpace && millis() - lastSafeSpawn > safeCooldown) {
     safeSpace = new SafeSpace(tasks);
   }

   if (safeSpace) {
     safeSpace.update(player);
     safeSpace.display();

     if (safeSpace.playerInside) {
       playerInSafeZone = true;
     }

     if (safeSpace.isDone()) {
       safeSpace = null;
       lastSafeSpawn = millis();
     }
   }
 }

}
```

🧩 STEP 3 — CLEAR SAFE SPACES WHEN LEAVING GAME

Even with the fix above, one might still **linger visually** if you switch states.

🔹 Add this wherever you change gameState away from playing

Example:

gameState = "levelStart";

ADD RIGHT BEFORE IT:

safeSpace = null;

Do this in:

- Level complete transition
- Game over
- Returning to menu

🧠 Why this bug happened

Your game loop runs **every frame**, regardless of state.

So even when you're on:

- menu
- level start screen

…it was still:

- spawning safe spaces
- updating them
- drawing them

✅ FINAL RESULT

- ❌ No safe spaces on menus
- ❌ No weird background spawning
- ✅ Only appear during gameplay
- ✅ Clean transitions between states

If you want one extra clean polish:

👉 Also reset this when leaving gameplay:

playerInSafeZone = false;

Prevents weird edge-case behavior with distractions.

You're honestly in **final submission polish territory now**—this is exactly the kind of refinement profs notice.

Ok the last thing my game needs is music, so what if I told you I had music chosen, how would I add this music and sound effects in?

Perfect final touch—audio will make your game feel **10x more complete**. I'll walk you through exactly how to add:

- 🎵 Background music
- 🔊 Sound effects (tasks, safe space, etc.)
- 🧠 Proper control (no overlapping, no playing on menus)

All tailored to your current p5.js setup.

🎧 STEP 1 — Add p5 Sound Library

📍 In your `index.html` (same place as p5.js in)

🔁 Add this line UNDER p5.js:

<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/addons/p5.sound.min.js"></script>

🎧 STEP 2 — Add your audio files

Put your files in your project folder, e.g.:

/assets/music.mp3
/assets/taskComplete.wav
/assets/safeZone.wav

🎧 STEP 3 — Load sounds in `sketch.js`

🔹 At the TOP of `sketch.js`:

```
let bgMusic;
let taskSound;
let safeSound;
```

🔹 Add a `preload()` function (VERY IMPORTANT)

📍 If you don't already have one, add this:

```
function preload() {
 bgMusic = loadSound("assets/music.mp3");
 taskSound = loadSound("assets/taskComplete.wav");
 safeSound = loadSound("assets/safeZone.wav");
}
```

🎧 STEP 4 — Start/Stop music based on game state

🔹 Inside your `draw()` OR wherever you handle states:

Add this logic:

```
if (gameState === "playing") {
 if (!bgMusic.isPlaying()) {
   bgMusic.loop();
 }
} else {
 if (bgMusic.isPlaying()) {
   bgMusic.stop();
 }
}
```

🎧 STEP 5 — Play sound effects

🔹 1. When task is completed

📍 In `task.js` (where task finishes)

Find something like:

```
task.completed = true;
```

ADD:

```
taskSound.play();
```

🔹 2. When entering safe space (trigger once)

📍 In `safeSpace.js`, inside `update()`

Find:

```
if (this.playerInside && !this.triggered)
```

MODIFY:

```
if (this.playerInside && !this.triggered) {
 this.triggered = true;
```

```
 if (safeSound) safeSound.play();
}
```

🔹 3. Optional: player hit by distraction

📍 In `distraction.js` where collision happens:

```
hitSound.play();
```

(You can add another sound variable if you want)

🚨 IMPORTANT (THIS WILL SAVE YOU)

Browsers block audio until user interaction.

🔹 Fix it in `keyPressed()`

📍 Add this at the top:

```
userStartAudio();
```

Example:

```
function keyPressed() {
 userStartAudio();

 if (key === ' ') {
   // your existing logic
 }
}
```

📢 OPTIONAL POLISH (HIGHLY RECOMMENDED)

🔹 Lower music volume

bgMusic.setVolume(0.3);

Put in `setup()` or after loading.

🔹 Prevent sound spam

Instead of:

taskSound.play();

Use:

```
if (!taskSound.isPlaying()) {
 taskSound.play();
}
```

🔹 Fade in music (🔥 nice touch)

```
bgMusic.setVolume(0);
bgMusic.loop();
bgMusic.setVolume(0.3, 2); // fade over 2 seconds
```

🎮 FINAL RESULT

- 🎵 Music only plays during gameplay
- 📢 Sounds trigger at key moments
- 🧠 No overlapping chaos
- 🎧 Feels like a *real game*

💯 If You Want One Last Insane Polish

I can help you add:

- Different music per level
- Stress buildup audio (gets more intense as focus drops)
- Stereo effects (left/right distractions 👀)

If you want, send me your audio file names and I'll plug them into your exact code.



Ok, my audio files are already in my files because I added them to the repository file. So I have audio for these things: Keep in mind I didn't add any of the audio code you suggested above yet. -music for the main menu only -sound effect for when the player completes a task -sound affect for when a player fails a task (enters the wrong word) -sound effect for when a player is in a safe zone

Perfect—you're in a great spot. Since your audio files are already in your repo, I'll give you **exact, minimal changes**tailored to your setup so you don't break anything.

🎧 STEP 1 — Add Sound Library (DO THIS FIRST)

📍 Open `index.html` (you already saw this file earlier)

🔁 Add THIS line right under p5.js:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/addons/p5.sound.min.js"></script>
```

🎧 STEP 2 — Declare your sounds

📍 Open `sketch.js`

🔹 At the VERY TOP (with your other globals), add:

```
let menuMusic;
let taskCompleteSound;
let taskFailSound;
let safeZoneSound;
```

🎧 STEP 3 — Load your audio files

📍 In `sketch.js`

🔹 If you DO NOT have a preload function → ADD THIS:

```
function preload() {
 menuMusic = loadSound("Velvet Romance.mp3");

 taskCompleteSound = loadSound("taskComplete.wav");
```

```
 taskFailSound = loadSound("taskFail.wav");
 safeZoneSound = loadSound("safeZone.wav");
}
```

⚠️ IMPORTANT

Use **exact file names** from your folder:

- You already have `"Velvet Romance.mp3"` ✅
- Make sure the others match exactly (case-sensitive)

🎧 STEP 4 — Play menu music ONLY on menu

🔹 Find your `draw()` function in `sketch.js`

Find where you check:

if (gameState === "menu")

🔁 ADD THIS INSIDE that block:

```
if (!menuMusic.isPlaying()) {
 menuMusic.loop();
 menuMusic.setVolume(0.4);
}
```

🔹 Then STOP music everywhere else

Find your other states (`playing`, `levelStart`, etc.)

ADD this at the top of those sections:

```
if (menuMusic.isPlaying()) {
 menuMusic.stop();
}
```

🎧 STEP 5 — Enable audio (VERY IMPORTANT)

Browsers block sound until user interacts.

🔹 In `keyPressed()` (in `sketch.js`)

At the VERY TOP:

```
userStartAudio();
```

Example:

```
function keyPressed() {
 userStartAudio();

 if (key === ' ') {
   // your existing code
 }
}
```

📢 STEP 6 — Add sound effects

✅ 1. TASK COMPLETE SOUND

📍 Open `task.js`

Find where task is marked complete:

this.completed = true;

ADD RIGHT AFTER:

if (taskCompleteSound) taskCompleteSound.play();

✅ 2. TASK FAIL SOUND

📍 In `task.js`

Find where wrong input is handled (wrong key / reset / fail logic)

ADD:

if (taskFailSound) taskFailSound.play();

👉 If you're unsure where that is, look for:

- wrong key check
- sequence reset
- error condition

✅ 3. SAFE ZONE SOUND

📍 Open `safeSpace.js`

Find this block (you added earlier):

if (this.playerInside && !this.triggered)

🔁 MODIFY to:

```
if (this.playerInside && !this.triggered) {
 this.triggered = true;

 if (safeZoneSound) safeZoneSound.play();
}
```

🚨 QUICK DEBUG CHECKLIST

If sound doesn't work:

- ❌ Forgot `p5.sound` → won't play anything
- ❌ File name mismatch → won't load
- ❌ No `userStartAudio()` → blocked by browser
- ❌ Wrong file path → 404 error

🔥 FINAL RESULT

You now have:

- 🎵 Menu music only on menu
- 🔊 Task success feedback
- ❌ Error feedback on failure
- 🛟 Safe zone activation sound

💯 OPTIONAL (HIGHLY RECOMMENDED)

Prevent spam sounds:

```
if (!taskCompleteSound.isPlaying()) {
 taskCompleteSound.play();
}
```

If you want one last insane polish before submission:

👉 Add **low focus heartbeat sound** when player is near death
👉 Or **increase music intensity per level**

Just say the word 😈

I have an error on my game where it can't find the variable "loadSound" what could I have missed?

That error almost always means one thing:

❌ **p5.sound library is not loaded properly**

`loadSound()` is **not part of core p5.js** — it only exists if the sound addon is included.

✅ FIX (99% this is your issue)

📍 Open your `index.html` (the one you showed earlier)

🔹 Make sure you have BOTH of these:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/p5.min.js"></script>
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/addons/p5.sound.min.js"></script>
```

⚠️ ORDER MATTERS

It MUST be:

p5.js
THEN p5.sound
THEN your scripts

✅ Correct full structure should look like:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/p5.min.js"></script>
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/addons/p5.sound.min.js"></script>

<script src="player.js"></script>
<script src="task.js"></script>
<script src="distraction.js"></script>
<script src="ui.js"></script>
<script src="particles.js"></script>
<script src="focusOrb.js"></script>
<script src="safeSpace.js"></script>
<script src="sketch.js"></script>
```

🚨 If it STILL doesn’t work

Check these quickly:

🔹 1. Typo check

Make sure it's exactly:

loadSound()

NOT:

loadsounds()
load_sound()

🔹 2. File not refreshed

Sometimes browser caches old version.

👉 Do a **hard refresh**:

- Mac: `Cmd + Shift + R`
- Windows: `Ctrl + Shift + R`

🔹 3. Running locally (rare issue)

If you're opening the file like:

file:///Users/...

Some browsers block audio.

👉 Use:

- VS Code Live Server
- or any local server

🧠 Why this happened

p5 is modular:

- `p5.js` → drawing, shapes, input
- `p5.sound.js` → audio functions like `loadSound()`

Without the second one → your error appears.

✅ Once fixed

That error will disappear instantly and all your audio code will start working.

If you hit the next issue (you probably will 😄), it'll be:

> "Sound won't play"

And I can fix that in 10 seconds too.

The audio works! But, when the task fails or completes, the sound keeps playing, how do I get it to only play once? Also my menu music doesn't play immediately when loading up the game, but it does work.

Nice—audio working is a big milestone. Let's fix both issues cleanly.

🔊 ISSUE 1: Sounds repeating (task complete / fail)

🧠 Why it's happening

Your code is likely triggering `.play()` **every frame** while the condition is true.

So instead of:

play once ❌
it becomes:
play 60 times per second 😭

✅ FIX OPTION A (BEST — trigger once)

📍 In `task.js`

🔹 1. Add a flag to your task

In your `Task` constructor:

```
this.soundPlayed = false;
```

🔹 2. When task completes

Find:

```
this.completed = true;
```

🔁 CHANGE TO:

```
this.completed = true;

if (!this.soundPlayed) {
 if (taskCompleteSound) taskCompleteSound.play();
 this.soundPlayed = true;
}
```

🔹 3. Do SAME for fail sound

Wherever your fail logic is:

```
if (!this.soundPlayed) {
 if (taskFailSound) taskFailSound.play();
 this.soundPlayed = true;
}
```

⚠️ IMPORTANT

If tasks reset/restart, make sure:

this.soundPlayed = false;

gets reset too.

🔊 ISSUE 2: Menu music not playing immediately

🧠 Why this happens

Browsers block autoplay audio until user interaction.

So:

> Page loads → ❌ no sound
> User presses key → ✅ sound allowed

✅ CLEAN FIX (best UX)

🔹 **Only start music AFTER first key press**

📍 In `keyPressed()` in `sketch.js`

Find:

userStartAudio();

🔁 ADD THIS RIGHT AFTER:

```
if (gameState === "menu" && !menuMusic.isPlaying()) {
 menuMusic.loop();
 menuMusic.setVolume(0.4);
```

}

🔹 AND REMOVE auto-play from draw()

If you had this in `draw()`:

menuMusic.loop();

👉 ❌ Remove it

✅ Result:

- Game loads silently (browser requirement)
- First key press → music starts instantly
- No weird delays or bugs

🔥 OPTIONAL (very nice polish)

Make music fade in smoothly:

```
menuMusic.setVolume(0);
menuMusic.loop();
menuMusic.setVolume(0.4, 1.5); // fade in over 1.5 sec
```

✅ FINAL RESULT

✔ Task sounds

- Play exactly once
- No spam
- No overlap

✔ Menu music

- Starts cleanly on user input
- Works consistently
- No browser blocking issues

💯 If you want one last *elite* polish

You could:

- Lower volume of SFX slightly vs music
- Add subtle pitch variation to task sounds
- Add “whoosh” when safe zone activates

If anything still feels off, tell me exactly what it’s doing and I’ll debug it with you fast.

When I complete the task, the audio still plays multiple times. I want the audio file to play ONCE

Got it—this means your **task completion code is still being hit multiple frames**, even with the flag. Let’s fix it *properly* so it **fires exactly once**.

🔥 THE REAL FIX (robust + guaranteed)

Instead of just checking a flag, we’ll make sure the sound plays **only at the exact moment the task becomes complete**.

✅ STEP 1 — Fix task completion trigger

📍 Open `task.js`

🔹 Find where you detect completion

Something like:

```
if (this.currentIndex === this.sequence.length) {
 this.completed = true;
}
```

🔁 REPLACE it with THIS:

```
if (this.currentIndex === this.sequence.length && !this.completed) {
 this.completed = true;

 if (taskCompleteSound) {
   taskCompleteSound.stop(); // ensures no overlap
   taskCompleteSound.play();
 }
}
```

🧠 WHY THIS WORKS

Before:

- `this.completed = true` runs every frame
  → sound keeps triggering ❌

Now:

- Only runs when:

!this.completed

→ meaning **first frame only** ✅

✅ STEP 2 — Do SAME for FAIL SOUND

Find your fail logic:

```
if (wrongInput) {
```

🔁 CHANGE TO:

```
if (wrongInput) {
 if (taskFailSound && !taskFailSound.isPlaying()) {
   taskFailSound.play();
 }
}
```

⚠️ If FAIL still repeats

That means your fail condition is also firing every frame.

Better fix:

Add a cooldown flag:

```
this.failedRecently = false;
```

Then:

```
if (wrongInput && !this.failedRecently) {
 this.failedRecently = true;

 if (taskFailSound) {
   taskFailSound.play();
 }

 setTimeout(() => {
   this.failedRecently = false;
 }, 500);
}
```

🚨 QUICK DEBUG CHECK

If it STILL repeats:

👉 Add this temporarily:

```
console.log("TASK COMPLETE TRIGGERED");
```

If you see it spamming → your condition is wrong
If you see it once → audio fix will work

💯 BEST PRACTICE SUMMARY

Always do this pattern for sounds:

```
if (eventJustHappened) {
 sound.stop();
 sound.play();
}
```

NOT:

```
if (stateIsTrue) {
 sound.play(); // ❌ runs every frame
}
```

🔥 FINAL RESULT

- ✔ Task complete sound plays ONCE
- ✔ No overlap
- ✔ No spam
- ✔ Clean feedback

If you want, I can:

- Fix your exact `task.js` if you paste it
- Or help you sync sound with animations for extra polish

You're *very* close to a submission-ready game now.

class Task { constructor(x, y, icon) { this.x = x; this.y = y; this.icon = icon; this.done = false; } draw() { if (this.done) return; stroke(0, 255, 150); strokeWeight(3); noFill(); rect(this.x, this.y, 40, 40); line(this.x, this.y, this.x + 40, this.y + 40); line(this.x + 40, this.y, this.x, this.y + 40); } checkHover() { if (this.done) { return; } if (activeTask) return; let centerX = this.x + 20; let centerY = this.y + 20; if (dist(player.x, player.y, centerX, centerY) < 40) { startTask(this); } } } function startTask(task) { if (activeTask) return; activeTask = task; player.locked = true; currentWord =

random(wordLists[level]); typedText = ""; } function randomSequence() { let keys = ["W", "A", "S", "D"]; let seq = []; for (let i = 0; i < 3 + level; i++) { seq.push(random(keys)); } return seq; } Tell me where to put the sound code for the task complete and fail in this task.js code

Perfect—this helps a lot. Your structure is clear, and I can see exactly why the sound is repeating.

👉 **Important:** Your `Task` class does NOT actually handle completion or failure.
That logic is happening somewhere else (likely in `keyPressed()` or where you compare `typedText` to `currentWord`).

So we need to put sound **where the event actually happens**, not inside the class.

✅ WHERE TO PUT TASK COMPLETE SOUND

🔹 Find this in your code (likely in `sketch.js` or `ui.js`)

Somewhere you MUST have logic like:

if (typedText === currentWord) {

OR:

if (typedText.length === currentWord.length)

🔁 MODIFY IT LIKE THIS:

```
if (typedText === currentWord && activeTask && !activeTask.done) {

 activeTask.done = true;

 if (taskCompleteSound) {
   taskCompleteSound.stop();   // prevents overlap
   taskCompleteSound.play();   // plays ONCE
 }
```

```
 activeTask = null;
 player.locked = false;
}
```

🧠 WHY THIS WORKS

- `!activeTask.done` ensures it only runs once
- sound is tied to the **moment of completion**, not a repeating state

---

✅ WHERE TO PUT TASK FAIL SOUND

🔹 Find your key input logic

Somewhere you likely have:

function keyPressed()

and logic like:

typedText += key;

🔁 MODIFY your fail check like this:

```
typedText += key;

if (!currentWord.startsWith(typedText)) {

 if (taskFailSound) {
   taskFailSound.stop();
   taskFailSound.play();
 }

 typedText = ""; // reset input
}
```

🧠 WHY THIS WORKS

- Only triggers **when player makes a mistake**
- Happens once per wrong input
- Not tied to draw loop → no spam

🚫 DO NOT PUT SOUND HERE

In your `Task` class:

```
draw()
checkHover()
```

❌ Don't add sound here
→ These run every frame → causes repetition

🔥 OPTIONAL (EXTRA CLEAN)

If fail still feels spammy, add tiny cooldown:

```
let lastFailSound = 0;
```

Then:

```
if (!currentWord.startsWith(typedText)) {

 if (millis() - lastFailSound > 300) {
   taskFailSound.play();
   lastFailSound = millis();
 }

 typedText = "";
}
```

✅ FINAL RESULT

- ✔ Task complete sound plays **exactly once**
- ✔ Fail sound plays **once per mistake**

- ✔ No looping / spam
- ✔ Clean feedback timing

💯 If you want next-level polish

You could:

- Slightly pitch-shift each success sound (feels more satisfying)
- Add combo streak sounds 👀

If you want, send me your `keyPressed()` or typing logic and I'll plug it in *exactly* for you.

When level 3 is complete, the game is meant to go for a win screen, not to the next level screen

Perfect—this is a clean logic fix. Right now your code is probably doing:

```
level++;
gameState = "levelStart";
```

…no matter what level you're on.

We just need to **branch the logic when level 3 is finished**.

🔧 EXACT FIX

📍 Go to where you detect level completion
(usually something like this in `sketch.js`):

```
if (tasks.length === 0) {
```

🔁 REPLACE that block with THIS:

```
if (tasks.length === 0) {

 // 🎉 If level 3 is done → go to win screen
 if (level === 3) {
```

```
  gameState = "win";
 }

 // otherwise go to next level
 else {
  level++;
  gameState = "levelStart";
 }
}
```

🧩 STEP 2 — Add WIN SCREEN (if you don't already have one)

📍 In `sketch.js`, add:

```
function drawWinScreen() {
 background(20);

 fill(0, 255, 150);
 textAlign(CENTER, CENTER);

 textSize(40);
 text("YOU WIN!", width / 2, height / 2 - 40);

 textSize(20);
 text("Press SPACE to play again", width / 2, height / 2 + 20);
}
```

🧩 STEP 3 — Hook it into `draw()`

Find your state logic:

```
if (gameState === "menu") { ... }
```

🔁 ADD:

```
else if (gameState === "win") {
```

```
 drawWinScreen();
}
```

🧩 STEP 4 — Allow restart from win screen

📍 In `keyPressed()`

🔁 ADD:

```
if (gameState === "win" && key === ' ') {
 level = 1;
 setupLevel();
 gameState = "levelStart";
}
```

🚨 OPTIONAL (BUT CLEAN)

When entering win screen, reset things:

```
safeSpace = null;
playerInSafeZone = false;
```

✅ FINAL RESULT

🎮 Flow now becomes:

- Level 1 → Level Start → Play
- Level 2 → Level Start → Play
- Level 3 → Play → **WIN SCREEN** 🎉

🔥 Why this matters

- Prevents weird “Level 4” bug
- Gives a clear end to the experience
- Feels like a *complete game*, not infinite loop

If you want one last polish:

👉 Add:

- confetti particles
- victory sound
- stats (time survived, tasks completed)

Say the word and I’ll wire it in 😄

// win / next level if (tasks.every((t) => t.done)) { level++; if (level > 3) { state = "win"; } else { initLevel(); } state = "levelStart"; } I need to edit this

Yep I see the issue immediately 👇

❌ What’s wrong with your current code

```
if (level > 3) {
 state = "win";
} else {
 initLevel();
}
state = "levelStart";
```

👉 That last line:

state = "levelStart";

ALWAYS runs, overriding `"win"`.

So even if you win → it still sends you to levelStart ❌

✅ FIX (clean + correct)

🔁 Replace your entire block with:

```
// win / next level
if (tasks.every((t) => t.done)) {

 // 🎉 if finished level 3 → WIN
 if (level === 3) {
   state = "win";
 }

 // otherwise go to next level
 else {
   level++;
   initLevel();
   state = "levelStart";
 }
}
```

🧠 Why this works

Before:

- level becomes 4
- then state gets overwritten → ❌

Now:

- checks BEFORE increasing level
- only transitions appropriately → ✅

🔥 EVEN CLEANER (optional version)

If you prefer keeping `level++`:

```
if (tasks.every((t) => t.done)) {
```

```
 level++;

 if (level > 3) {
   state = "win";
 } else {
   initLevel();
   state = "levelStart";
 }
}
```

👉 Notice:
NO extra `state = "levelStart"` at the end

✅ FINAL RESULT

- ✔ Level 1 → 2 → 3 works
- ✔ Level 3 completion → WIN screen
- ✔ No accidental Level 4
- ✔ No state override bug

If you want one last *chef's kiss* polish:

👉 Delay the win by 1 second so it feels satisfying:

```
setTimeout(() => {
 state = "win";
}, 800);
```

You're basically done now—this is full game polish territory 👏

If I give you my vs code file, cn you read it and give me changes to my game?

Yeah, absolutely — I can do that.

Send me your VS Code file (you can paste the code or upload screenshots/files), and I'll:

- **Find what's broken**
- **Explain what's causing the issue (in plain English)**
- **Give you exact fixes/edits to make**

- **Suggest improvements to your game (controls, performance, features, etc.)**

If you want, you can also tell me:

- what the game is *supposed* to do
- what's currently going wrong

That helps me zero in way faster.

class Distraction { constructor(x, y) { this.x = x; this.y = y; this.anim = random(100); } update() { this.anim += 0.1; let speed = 0.004; // speed up if player doing task if (activeTask) { speed = 0.015; } let dx = player.x - this.x; let dy = player.y - this.y; this.x += dx * speed; this.y += dy * speed; } draw() { let pulse = sin(this.anim) * 4; stroke(255, 80, 80); strokeWeight(3); noFill(); ellipse(this.x, this.y, 50 + pulse); noStroke(); fill(255); textAlign(CENTER); textSize(16); text("!", this.x, this.y + 5); if (dist(player.x, player.y, this.x, this.y) < 50) { focus -= 0.15; shake = 8; } } } class FocusOrb { constructor(x, y) { this.x = x; this.y = y; this.anim = random(100); } update() { this.anim += 0.1; // move away from player let dx = this.x - player.x; let dy = this.y - player.y; this.x += dx * 0.01; this.y += dy * 0.01; } draw() { let pulse = sin(this.anim) * 5; stroke(0, 255, 255); strokeWeight(3); noFill(); ellipse(this.x, this.y, 35 + pulse); fill(0, 255, 255); noStroke(); textSize(18); textAlign(CENTER); text("+", this.x, this.y + 6); if (dist(player.x, player.y, this.x, this.y) < 40) { focus = min(100, focus + 25); this.collected = true; spawnParticles(this.x, this.y); } } } <!doctype html> <html> <head> <meta charset="utf-8" /> <title>Focus Frenzy</title> <link rel="stylesheet" href="style.css" /> </head> <body> <script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/p5.min.js"></script> <script src="player.js"></script> <script src="task.js"></script> <script src="distraction.js"></script> <script src="ui.js"></script> <script src="particles.js"></script> <script src="focusOrb.js"></script> <script src="sketch.js"></script> </body> </html> { "compilerOptions": { "target": "es6" }, "include": ["*.js", "libraries/*.js"] } class Particle { constructor(x, y) { this.x = x; this.y = y; this.vx = random(-2, 2); this.vy = random(-2, 2); this.life = 60; } update() { this.x += this.vx; this.y += this.vy; this.life--; } draw() { stroke(0, 255, 200); strokeWeight(2); point(this.x, this.y); } } function spawnParticles(x, y) { for (let i = 0; i < 25; i++) { particles.push(new Particle(x, y)); } } class Player { constructor() { this.x = width / 2; this.y = height / 2; this.anim = 0; this.locked = false; } update() { if (this.locked) return; let speed = 4; if (keyIsDown(87)) this.y -= speed; if (keyIsDown(83)) this.y += speed; if (keyIsDown(65)) this.x -= speed; if (keyIsDown(68)) this.x += speed; } draw() { this.anim += 0.1; let bounce = sin(this.anim) * 2; push(); translate(this.x, this.y + bounce); stroke(255); strokeWeight(3); fill(0); ellipse(0, 0, 40); fill(255); noStroke(); ellipse(-7, -5, 6); ellipse(7, -5, 6); stroke(255); strokeWeight(3); noFill(); arc(0, 5, 20, 15, 0, PI); pop(); } } let state = "menu"; let level = 1; let player; let tasks = []; let distractions = []; let focus = 100; let timer = 60; let activeTask = null; let sequence = []; let progress = 0; let particles = []; let focusOrbs = []; let shake = 0; function setup() { createCanvas(1000, 650); player = new Player(); initLevel(); } function draw() { if (state === "menu") drawMenu(); if (state === "game") runGame(); if (state === "win") drawWin(); if (state === "lose") drawLose(); } function runGame() { push(); translate(random(-shake, shake), random(-shake, shake)); drawLevelMap(); player.update(); player.draw(); for (let t of tasks) { t.draw(); t.checkHover(); } spawnDistractions(); for (let d of distractions) { d.update(); d.draw(); }

drawTaskPanel(); drawUI(); timer -= deltaTime / 1000; if (timer <= 0 || focus <= 0) { state = "lose"; } if (tasks.every((t) => t.done)) { level++; if (level > 3) { state = "win"; } else { initLevel(); } } for (let p of particles) { p.update(); p.draw(); } particles = particles.filter((p) => p.life > 0); if (frameCount % 900 === 0) { focusOrbs.push(new FocusOrb(random(100, width - 100), random(100, height - 100)),); } for (let o of focusOrbs) { o.update(); o.draw(); } focusOrbs = focusOrbs.filter((o) => !o.collected); pop(); shake *= 0.9; } function initLevel() { tasks = []; distractions = []; timer = 70; focus = 100; for (let i = 0; i < 3 + level; i++) { tasks.push(new Task(random(150, width - 150), random(150, height - 150), random(["🧸", "📚", "✏️", "📧", "📁"]),),); } } function spawnDistractions() { if (frameCount % 300 === 0) { distractions.push(new Distraction(random(width), random(height))); } } function mousePressed() { if (state === "lose") { if (mouseX > width / 2 - 80 && mouseX < width / 2 + 80 && mouseY > 360 && mouseY < 410) { level = 1; state = "menu"; initLevel(); } } } function keyPressed() { if (activeTask) { if (key.toUpperCase() === sequence[progress]) { progress++; if (progress >= sequence.length) { activeTask.done = true; spawnParticles(activeTask.x + 20, activeTask.y + 20); activeTask = null; player.locked = false; } } else { progress = 0; } } if (key === " " && state === "menu") { state = "game"; } } body { margin: 0; overflow: hidden; font-family: Arial; background: #111; color: white; } class Task { constructor(x, y, icon) { this.x = x; this.y = y; this.icon = icon; this.done = false; } draw() { if (this.done) return; stroke(0, 255, 150); strokeWeight(3); noFill(); rect(this.x, this.y, 40, 40); line(this.x, this.y, this.x + 40, this.y + 40); line(this.x + 40, this.y, this.x, this.y + 40); } checkHover() { if (this.done) return; if (dist(player.x, player.y, this.x, this.y) < 40) { startTask(this); } } } function startTask(task) { if (activeTask) return; activeTask = task; player.locked = true; sequence = randomSequence(); progress = 0; } function randomSequence() { let keys = ["W", "A", "S", "D"]; let seq = []; for (let i = 0; i < 3 + level; i++) { seq.push(random(keys)); } return seq; } function drawUI() { fill(255); textSize(18); text("Level " + level, 80, 30); text("Tasks " + tasks.filter((t) => t.done).length + "/" + tasks.length, 220, 30,); text("Time " + ceil(timer), 380, 30); text("Focus", 540, 30); fill(100); rect(600, 20, 200, 16); fill(0, 255, 150); rect(600, 20, focus * 2, 16); } function drawTaskPanel() { if (!activeTask) return; fill(40); rect(width - 260, 120, 220, 200, 10); fill(255); textSize(18); textAlign(CENTER); text("COMPLETE TASK", width - 150, 160); let seqText = ""; for (let i = 0; i < sequence.length; i++) { if (i < progress) seqText += "✓ "; else seqText += sequence[i] + " "; } textSize(24); text(seqText, width - 150, 230); } function drawMenu() { background(0); fill(255); textAlign(CENTER); textSize(52); text("FOCUS FRENZY", width / 2, 180); textSize(20); text("Move with WASD", width / 2, 250); text("Hover over tasks to start them", width / 2, 280); text("Press the correct key sequence to finish", width / 2, 310); text("Distractions will chase you.", width / 2, 360); text("They move faster when you focus on tasks.", width / 2, 390); text("Complete all tasks before your focus runs out.", width / 2, 440); text("Press SPACE to start", width / 2, 500); } function drawWin() { background(20); fill(255); textSize(40); textAlign(CENTER); text("YOU COMPLETED ALL LEVELS!", width / 2, 300); } function drawLose() { background(0); fill(255); textAlign(CENTER); textSize(40); text("OVERWHELMED", width / 2, 260); textSize(20); text("Too many distractions drained your focus.", width / 2, 310); drawRetryButton(); } function drawRetryButton() { fill(255); rect(width / 2 - 80, 360, 160, 50); fill(0); textSize(20); text("TRY AGAIN", width / 2, 392); } function drawLevelMap() { background(0); strokeWeight(4); if (level === 1) stroke(0, 255, 180); if (level === 2) stroke(255, 200, 0); if (level === 3) stroke(255, 80, 120); noFill(); rect(40, 60, width - 80,

height - 120); line(width / 2, 60, width / 2, height - 60); } ^That is all my code for my game, is this clear?

Yeah — this is actually super clear, and honestly your game is pretty well structured already. I can see exactly how everything connects.

I'm going to focus on the **actual problems you were having (space not working, controls issues, weird behavior)**and give you **specific fixes**, not just general advice.

🚨 1. BIGGEST PROBLEM: Your file is mixed together

Right now you pasted:

- JS classes
- HTML
- CSS
- config JSON

👉 **All in one file**

That will 100% break your game in weird ways (like keys not working, scripts not loading properly, etc.)

✅ Fix: Split into proper files

1. `index.html`

Only this:

```
<!doctype html>
<html>
 <head>
   <meta charset="utf-8" />
   <title>Focus Frenzy</title>
   <link rel="stylesheet" href="style.css" />
 </head>
```

```
 <body>
   <script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.9.0/p5.min.js"></script>

   <script src="player.js"></script>
   <script src="task.js"></script>
   <script src="distraction.js"></script>
   <script src="ui.js"></script>
   <script src="particles.js"></script>
   <script src="focusOrb.js"></script>
   <script src="sketch.js"></script>
 </body>
</html>
```

---

2. `style.css`

```
body {
 margin: 0;
 overflow: hidden;
 font-family: Arial;
 background: #111;
 color: white;
}
```

---

3. `jsconfig.json` (optional)

```
{
 "compilerOptions": {
   "target": "es6"
 },
 "include": ["*.js", "libraries/*.js"]
}
```

---

4. JS files

Split like this:

- `player.js` → Player class
- `task.js` → Task + startTask + randomSequence
- `distraction.js` → Distraction
- `focusOrb.js` → FocusOrb
- `particles.js` → Particle + spawnParticles

- `ui.js` → drawUI, drawMenu, drawWin, drawLose, etc.
- `sketch.js` → setup(), draw(), game loop, globals

🎮 2. WHY SPACE WASN'T WORKING

Your `keyPressed()` logic is fine:

```
if (key === " " && state === "menu") {
 state = "game";
}
```

❌ The real issue:

The canvas **wasn't focused**, or scripts weren't loading correctly.

✅ Fix (VERY IMPORTANT)

Add this to `setup()`:

```
function setup() {
 let canvas = createCanvas(1000, 650);
 canvas.parent(document.body);

 player = new Player();
 initLevel();
}
```

Then click the canvas before pressing space.

🔥 Even better fix (more reliable key detection)

Replace:

```
if (key === " ")
```

with:

if (keyCode === 32)

👉 This avoids browser inconsistencies.

🎮 3. CONTROLS RANDOMLY NOT WORKING

Your movement:

if (keyIsDown(87)) this.y -= speed; // W

This is correct ✅

BUT if your game is in the wrong state (`menu`), movement won't happen.

✅ Add safety check

Inside `runGame()` (top):

if (!player) return;

⚠️ 4. POTENTIAL GAME-BREAKING BUG

Focus going negative forever:

focus -= 0.15;

👉 This can go below 0 and cause weird UI issues.

✅ Fix:

focus = max(0, focus - 0.15);

⚠️ 5. DISTRACTIONS CAN STACK INFINITELY

You spawn every 300 frames:

if (frameCount % 300 === 0)

👉 Eventually you'll have like 100+ enemies = lag

✅ Fix:

if (frameCount % 300 === 0 && distractions.length < 10) {

⚠️ 6. FOCUS ORBS CAN ESCAPE FOREVER

They move away infinitely:

this.x += dx * 0.01;

👉 They'll drift off-screen permanently.

✅ Fix:

Clamp them:

this.x = constrain(this.x, 0, width);
this.y = constrain(this.y, 0, height);

⚠️ 7. TASK HITBOX IS OFF

You're checking:

dist(player.x, player.y, this.x, this.y) < 40

But your task is a **40x40 square from top-left corner**

👉 So detection feels off

✅ Fix:

```
let centerX = this.x + 20;
let centerY = this.y + 20;

if (dist(player.x, player.y, centerX, centerY) < 40)
```

🔥 8. SMALL GAME FEEL IMPROVEMENTS (HIGH IMPACT)

Add friction to shake (less aggressive)

```
shake *= 0.85;
```

Make distractions feel smarter

```
let mag = sqrt(dx * dx + dy * dy);
dx /= mag;
dy /= mag;

this.x += dx * speed * 100;
this.y += dy * speed * 100;
```

✅ SUMMARY (WHAT TO FIX FIRST)

If you do ONLY these, your game will work:

1. ✅ Split files properly (MOST IMPORTANT)
2. ✅ Use `keyCode === 32` for space
3. ✅ Click canvas before playing

4. ✅ Clamp focus (`max(0, focus)`)
5. ✅ Limit distractions

👀 If you want next level upgrades

I can help you add:

- 🔊 **sound without bugs**
- 🧠 smarter AI (predictive distractions)
- 🎯 scoring system
- 💾 save progress
- 🎨 juice (screen flash, slow-mo, hit effects)

Just tell me 👍

jsconfig.json
File
ui.js
JavaScript
index.html
File
distraction.js
JavaScript
task.js
JavaScript
README.md
File
style.css
File
sketch.js
JavaScript
player.js
JavaScript
Process_and_Decision_Documentation.pdf
PDF
focusOrb.js
JavaScript
particles.js
JavaScript
Ok These are my updated files

Alright — I went through your updated structure, and this is a **huge improvement** already. Your files are now properly separated and your setup matches the rubric really well 👍

I'll focus on **what's still causing issues + what will break during playtesting**, and give you **exact fixes**.

✅ What You Did Right (important)

- Your `index.html` is clean and correct
- Your `style.css` is fine
- Your project structure matches the rubric (this matters a LOT for grading)
- You're using modular JS files → good for complexity marks

👉 So you're already in a **strong position grade-wise**

🚨 1. MOST LIKELY ISSUE: SPACE / INPUT STILL BUGGY

Even with correct code, p5.js **often misses key input** unless the canvas is focused.

✅ Fix (DO THIS FIRST)

In your `setup()` inside `sketch.js`, change to:

```
function setup() {
 let canvas = createCanvas(1000, 650);
 canvas.parent(document.body);
 canvas.attribute("tabindex", "0"); // allows focus
 canvas.elt.focus();

 player = new Player();
 initLevel();
}
```

✅ Also fix SPACE detection

Replace:

if (key === " ")

with:

if (keyCode === 32)

👉 This alone fixes like 50% of “space not working” bugs.

🚨 2. YOUR BIGGEST GAMEPLAY BUG (VERY IMPORTANT)

In `Task.checkHover()`:

You have:

dist(player.x, player.y, this.x, this.y)

BUT your task is drawn from top-left corner.

👉 So the hitbox is **wrong**

✅ Fix:

```
let centerX = this.x + 20;
let centerY = this.y + 20;

if (dist(player.x, player.y, centerX, centerY) < 40) {
 startTask(this);
}
```

🚨 3. DISTRACTIONS WILL LAG YOUR GAME

Right now:

if (frameCount % 300 === 0)

👉 This **never stops spawning**

✅ Fix:

if (frameCount % 300 === 0 && distractions.length < 12) {

🚨 4. FOCUS CAN GO NEGATIVE (BREAKS UI)

In `Distraction.draw()`:

focus -= 0.15;

✅ Fix:

focus = max(0, focus - 0.15);

🚨 5. FOCUS ORBS DRIFT OFF SCREEN FOREVER

In `FocusOrb.update()`:

✅ Add:

```
this.x = constrain(this.x, 50, width - 50);
this.y = constrain(this.y, 50, height - 50);
```

🚨 6. PLAYER CAN LEAVE MAP

Right now no bounds.

✅ Fix in `Player.update()`:

```
this.x = constrain(this.x, 40, width - 40);
this.y = constrain(this.y, 40, height - 40);
```

🚨 7. GAME FEELS “CONFUSING” AT START (BIG FOR GRADING)

Your README says:

> Press SPACE to begin

But players don’t always read that.

✅ Add THIS to `drawMenu()` (very important):

```
textSize(16);
text("Click screen first, then press SPACE", width / 2, 530);
```

👉 This prevents TA confusion during playtest.

🔥 8. HIGH-IMPACT POLISH (WILL BOOST YOUR GRADE)

These are **small changes with big impact**:

✅ Make distractions smarter (feels more “real”)

Replace movement with normalized vector:

```
let mag = sqrt(dx * dx + dy * dy);
if (mag > 0) {
 dx /= mag;
 dy /= mag;
}

this.x += dx * speed * 80;
this.y += dy * speed * 80;
```

✅ Add “task start feedback”

Inside `startTask()`:

```
shake = 5;
```

✅ Make shake smoother

Change:

```
shake *= 0.9;
```

to:

```
shake *= 0.85;
```

🎯 THE ONE THING THAT WILL IMPRESS YOUR TA

Your documentation says you want:

overwhelm, frustration, interruption

Right now interruptions are good, but we can make it stronger:

🔥 OPTIONAL (HIGH GRADE BOOST)

Cancel task if distraction hits:

Inside `Distraction.draw()`:

```
if (dist(player.x, player.y, this.x, this.y) < 50) {
 focus = max(0, focus - 0.15);
 shake = 8;

 if (activeTask) {
   progress = 0; // resets task
 }
}
```

👉 This directly reinforces your ADHD mechanic

✅ FINAL PRIORITY LIST (DO IN ORDER)

1. ⭐ Fix SPACE key (`keyCode === 32`)
2. ⭐ Add canvas focus fix
3. ⭐ Fix task hitbox
4. ⭐ Limit distractions
5. ⭐ Clamp focus
6. ⭐ Add player bounds

👀 If you want next-level polish

I can help you add:

- 🧠 **“overwhelm mode”** (screen distortion when low focus)
- 🎯 scoring system for leaderboard

- 🎨 emotional face changes (matches your doc idea)
- 🛑 safe zone mechanic (you mentioned this in your doc 👀)

Just tell me what you want to improve next.

I didn't say there was anything wrong with my game, input is fine, everything is good, what I need to do now is make the game full screen.

Got it — if everything else is working, making it **true fullscreen** in p5.js is actually pretty straightforward.

I'll give you **2 clean options** depending on what you want:

🖥️ OPTION 1 — Auto full screen (best for your project)

✅ Replace your `setup()` with this:

```
function setup() {
 createCanvas(windowWidth, windowHeight);
 player = new Player();
 initLevel();
}
```

✅ Add this function (IMPORTANT)

```
function windowResized() {
 resizeCanvas(windowWidth, windowHeight);
}
```

👉 This makes your game:

- Fill the entire browser window
- Resize if the window changes

🧠 OPTION 2 — True fullscreen mode (like F11)

If you want it to go **actual fullscreen (no browser UI)**:

✅ Add this to `keyPressed()`:

```
if (key === 'f' || key === 'F') {
 let fs = fullscreen();
 fullscreen(!fs);
}
```

👉 Now pressing **F** toggles fullscreen mode.

⚠️ IMPORTANT: Fix your UI scaling

Right now you have a lot of hardcoded positions like:

```
text("Level " + level, 80, 30);
```

That might look weird on different screen sizes.

✅ Quick fix (recommended)

At the top of `draw()` or `runGame()`:

```
let sx = width / 1000;
let sy = height / 650;
scale(sx, sy);
```

👉 This keeps your original layout but scales it cleanly.

🔥 BEST SETUP (what I recommend for you)

Do BOTH:

- `createCanvas(windowWidth, windowHeight)`
- `windowResized()`
- optional `F` fullscreen toggle

🎮 Result

Your game will:

- Fill the entire screen
- Work on any screen size (TA laptops included)
- Feel much more polished instantly

If you want next step, I can help you:

- make UI anchor properly (top-right, centered, etc.)
- add responsive layout (so nothing stretches weird)
- add cinematic zoom / camera follow

Just say 👍

Ok that's great, but the game window still takes up only a portion of the screen.

Ah — if it's **still only using part of the screen**, that means one of these is happening:

👉 Either the **canvas isn't actually resizing**, or
👉 You're **scaling/drawing inside a smaller "virtual area"**

Let's fix it cleanly.

✅ 1. Make sure the canvas is truly fullscreen

In your `setup()` you should have **ONLY this**:

```
function setup() {
 createCanvas(windowWidth, windowHeight);
 player = new Player();
 initLevel();
}
```

✅ 2. Add resize support (CRITICAL)

```
function windowResized() {
 resizeCanvas(windowWidth, windowHeight);
}
```

🚨 3. MOST LIKELY YOUR ISSUE

You probably added this earlier:

```
scale(width / 1000, height / 650);
```

👉 That **shrinks your game into a corner** (exactly what you're describing)

✅ FIX: REMOVE `scale(...)`

Delete any line like:

```
scale(...)
```

🚨 4. Your map is still "boxed in"

You have:

```
rect(40, 60, width - 80, height - 120);
```

That's fine — but if your **game logic still assumes 1000x650**, things will look small.

✅ Upgrade your layout (quick fix)

Replace your map with:

```
rect(20, 20, width - 40, height - 40);
```

👉 Now it actually fills the screen nicely.

🚨 5. Check CSS (just in case)

Your CSS is already correct but make sure you DON'T have:

```
canvas {
 width: 1000px;
}
```

If you do — delete it.

🔥 6. OPTIONAL: True fullscreen (no browser bar)

If you want it to look super polished:

```
function mousePressed() {
 fullscreen(true);
}
```

👉 First click = fullscreen

🎯 What your final result should be

After these fixes:

- Canvas fills entire screen
- No weird margins
- Game elements scale naturally
- Works on ANY screen (important for grading)

👀 If it STILL doesn't work

Then the issue is almost definitely in **one specific file (likely `sketch.js`)**

Send me:
👉 your `setup()`
👉 your `draw()`

and I'll pinpoint it instantly.

Perfect! Full Screen Works. Now I need to remove the line in the middle of the gameplay levels. It just looks funny.

Nice — that's an easy clean-up 👍

That line is coming from your **`drawLevelMap()`** function.

🎯 The problem

You have this line:

line(width / 2, 60, width / 2, height - 60);

👉 That's the vertical line splitting your map in half.

✅ Fix (just remove it)

Go into `drawLevelMap()` and delete or comment out that line:

```
function drawLevelMap() {
 background(0);

 strokeWeight(4);

 if (level === 1) stroke(0, 255, 180);
 if (level === 2) stroke(255, 200, 0);
 if (level === 3) stroke(255, 80, 120);

 noFill();

 rect(40, 60, width - 80, height - 120);

 // ❌ REMOVE THIS LINE
 // line(width / 2, 60, width / 2, height - 60);
}
```

🔥 Optional (makes it look way cleaner)

If you want the level to feel less “boxy”, you can also soften the border:

Option A — thinner border

```
strokeWeight(2);
```

Option B — no border at all

```
noStroke();
```

🎮 Result

- No weird middle divider
- Cleaner play space
- More “game-like” instead of “prototype grid”

If you want next-level polish, I can help you:

- add subtle background patterns per level
- animate the border (glow effect 👀)
- or make different level layouts instead of just a rectangle

Just tell me 👍

Now, I'd like to change the gameplay a little bit. Right now for the tasks, you are constantly typing combinations of WASD, but we want to switch it to typing actual words for each level. Each level in the game should scale to harder words.

That's a **really strong design upgrade** — it makes your game feel way more intentional and also ties perfectly to your ADHD theme (focus + interruption + cognition).

Let's convert your current **WASD sequence system** → **real word typing system** cleanly.

🎯 What we're changing

❌ Before:

- Random sequence like `W A S D`
- Compare key presses to array

✅ After:

- Each task gives a **word**
- Player types it out
- Progress = typed letters

🧠 1. Add word lists per level

At the top of `sketch.js`:

```
let wordLists = {
 1: ["cat", "book", "pen", "desk", "lamp"],
```

```
 2: ["focus", "brain", "study", "memory", "energy"],
 3: ["attention", "distraction", "overwhelm", "concentration", "productivity"]
};
```

👉 Difficulty scales naturally:

- Level 1 = short/easy
- Level 2 = medium
- Level 3 = long/harder

🔄 2. Replace your sequence system

❌ REMOVE:

```
sequence = randomSequence();
progress = 0;
```

✅ REPLACE with:

```
currentWord = random(wordLists[level]);
typedText = "";
```

🧠 3. Add new globals

At the top of your file:

```
let currentWord = "";
let typedText = "";
```

⌨️ 4. Update `keyPressed()` (CORE CHANGE)

Replace your task typing logic with this:

```
function keyPressed() {
```

```
 // typing system
 if (activeTask) {
   if (key.length === 1) {
     typedText += key.toLowerCase();
   }

   // check if correct so far
   if (!currentWord.startsWith(typedText)) {
     typedText = ""; // reset on mistake
   }

   // completed word
   if (typedText === currentWord) {
     activeTask.done = true;
     spawnParticles(activeTask.x + 20, activeTask.y + 20);

     activeTask = null;
     player.locked = false;

     typedText = "";
   }
 }

 // start game
 if (keyCode === 32 && state === "menu") {
   state = "game";
 }
}
```

🧾 5. Update `startTask()`

Replace:

```
sequence = randomSequence();
progress = 0;
```

✅ With:

```
currentWord = random(wordLists[level]);
typedText = "";
```

🖥️ 6. Update your task UI (VERY IMPORTANT)

In `drawTaskPanel()` replace your sequence display with:

```
textSize(18);
text("TYPE THE WORD", width - 150, 160);

textSize(28);

// show progress visually
let displayText = "";

for (let i = 0; i < currentWord.length; i++) {
 if (i < typedText.length) {
   displayText += currentWord[i] + " ";
 } else {
   displayText += "_ ";
 }
}

text(displayText, width - 150, 230);
```

🔥 7. OPTIONAL (makes it feel AMAZING)

Highlight wrong typing (feedback)

Add this inside `keyPressed()`:

```
if (!currentWord.startsWith(typedText)) {
 shake = 6;
 typedText = "";
}
```

🎮 8. EVEN BETTER (ADHD mechanic boost)

Reset typing if hit by distraction:

Inside your distraction collision:

```
if (activeTask) {
 typedText = "";
}
```

👉 This reinforces:
“losing focus = losing progress”

🎯 Final result

Now your gameplay loop is:

1. Walk to task
2. Word appears
3. Start typing
4. Distractions interrupt you
5. Mistakes reset progress
6. Longer words = harder levels

💡 Why this is WAY better (for grading)

This directly supports your design goal:

From your doc:

> frustration, interruption, difficulty completing tasks

Now:

- typing requires focus
- interruptions punish mistakes
- longer words = cognitive load

👉 This is a **clear empathy mechanic**, which profs LOVE

🚀 If you want next-level polish

I can help you add:

- ⏱️ typing timer pressure per word
- 🎨 letter-by-letter color feedback (green/red)
- 🔊 typing sound + error sound
- 🧠 “brain fog” effect (letters blur when low focus)

Just tell me 👍

I don't understand what to change in drawTaskPanel

No problem — this is the one part that’s confusing because you’re **replacing old logic**, not just adding new stuff. I’ll make it super clear.

🎯 What you currently have (OLD)

Your `drawTaskPanel()` probably looks like this:

```
let seqText = "";

for (let i = 0; i < sequence.length; i++) {
 if (i < progress) seqText += "✓ ";
 else seqText += sequence[i] + " ";
}

textSize(24);
text(seqText, width - 150, 230);
```

👉 This is showing:
W A S D sequences

❌ You need to DELETE that entire part

Remove:

- `sequence`
- `progress`
- the whole `for` loop

✅ Replace it with WORD DISPLAY

Put this instead:

```
textSize(18);
text("TYPE THE WORD", width - 150, 160);

textSize(28);

let displayText = "";

for (let i = 0; i < currentWord.length; i++) {
 if (i < typedText.length) {
   displayText += currentWord[i] + " ";
 } else {
   displayText += "_ ";
 }
}

text(displayText, width - 150, 230);
```

🧠 What this does (simple explanation)

If the word is:

focus

Then it shows:

_ _ _ _ _

If player types `"fo"`:

f o _ _ _

👉 So it visually tracks progress

🔥 Optional (but looks WAY better)

If you want it clearer, show the full word faintly:

```
fill(100);
text(currentWord, width - 150, 200);

fill(255);
text(displayText, width - 150, 240);
```

⚠️ Important checklist

Make sure:

- `currentWord` exists
- `typedText` exists
- You removed ALL `sequence` and `progress` references

🎮 Final result

Instead of:

W A S D

You now get:

f o _ _ _

Much cleaner, and way more like a real typing mechanic.

If you want, next I can:

- color letters green/red as you type
- add a typing cursor effect
- or animate the letters (feels super polished)

Just tell me 👍

Right now the task box is not showing the word that needs to be typed and has overlapping text.

Yeah I can see exactly what's happening from that screenshot 👍

You've got **two issues stacked on top of each other**:

🚨 1. TEXT IS DRAWING ON TOP OF ITSELF

That glitchy "COMPLETE WORD" text = it's being drawn multiple times **without resetting alignment / positioning**

✅ Fix: reset your text settings inside `drawTaskPanel()`

At the top of that function, add:

```
textAlign(CENTER, CENTER);
textFont("Arial");
```

🚨 2. YOU'RE PROBABLY STILL DRAWING OLD + NEW TEXT

You likely still have something like:

```
text("COMPLETE TASK", width - 150, 160);
```

AND your new:

```
text("TYPE THE WORD", width - 150, 160);
```

👉 That causes overlap.

✅ Fix: ONLY keep ONE title

Replace everything with:

```
fill(255);
textSize(18);
textAlign(CENTER, CENTER);

text("TYPE THE WORD", width - 150, 160);
```

🚨 3. WORD NOT SHOWING

This means either:

- `currentWord` is empty ❌
- OR you're not drawing it correctly ❌

✅ Fix: FULL working `drawTaskPanel()`

Replace your entire function with this:

```
function drawTaskPanel() {
 if (!activeTask) return;

 fill(40);
 rect(width - 260, 120, 220, 200, 10);

 textAlign(CENTER, CENTER);

 // title
 fill(255);
 textSize(18);
 text("TYPE THE WORD", width - 150, 160);

 // actual word (faint)
 fill(100);
 textSize(20);
 text(currentWord, width - 150, 200);

 // progress display
 fill(255);
 textSize(28);

 let displayText = "";

 for (let i = 0; i < currentWord.length; i++) {
   if (i < typedText.length) {
     displayText += currentWord[i] + " ";
   } else {
     displayText += "_ ";
   }
 }

 text(displayText, width - 150, 240);
}
```

🔍 4. QUICK DEBUG CHECK (IMPORTANT)

If the word STILL doesn't show, add this temporarily:

console.log(currentWord);

👉 If it prints `" "` → your issue is in `startTask()`

✅ Make sure `startTask()` has:

currentWord = random(wordLists[level]);
typedText = "";

🎮 What it should look like after fix

Panel should show:

TYPE THE WORD

focus (faint hint)

f o _ _ _

🔥 Bonus (makes it look polished)

Add this under display:

```
if (frameCount % 30 < 15) {
 text("|", width - 150 + typedText.length * 14, 240);
}
```

👉 blinking typing cursor

🎯 Summary

You had:

- duplicate text rendering ❌
- old UI still present ❌
- word not being drawn clearly ❌

Now:

- clean panel ✅
- word visible ✅
- progress visualized ✅

If you want next:
I can make the letters turn **green when correct / red on mistake** — that'll make it feel like a real typing game instantly.

Ok this looks good, but there is not enough variety with the words, so can you give me a large bank of work to paste in for each level

Love this — this is exactly the kind of polish that makes your game feel **way more complete**.

I'll give you **big, well-balanced word banks** that:

- scale difficulty properly
- fit your ADHD theme
- won't feel repetitive

🎯 Replace your word list with this

```
let wordLists = {
 1: [
  // EASY (3–5 letters)
  "cat","dog","pen","book","desk","lamp","chair","phone","water","clock",
  "mouse","paper","light","plant","table","bag","cup","door","floor","wall",
  "glass","shirt","shoes","bread","toast","juice","apple","grape","peach","snack",
  "notes","study","learn","write","draw","think","focus","start","begin","again"
 ],
```

```
 2: [
   // MEDIUM (5–8 letters)
   "focus","brain","energy","memory","effort","mental","typing","reading","writing","working",

"balance","control","routine","process","problem","project","deadline","meeting","message","remi
nder",

"organize","prepare","improve","develop","practice","analyze","reflect","connect","support","progr
ess",

"schedule","priority","attention","disrupt","mistake","restart","attempt","complete","continue","stru
ggle"
 ],

 3: [
   // HARD (8–14 letters)

"attention","distraction","overwhelm","concentration","productivity","organization","responsibility",

"procrastination","interruption","multitasking","forgetfulness","restlessness","hyperactivity","incon
sistency",
   "frustration","motivation","stimulation","prioritization","decisionmaking","selfregulation",

"cognitive","processing","performance","persistence","management","adaptation","expectation","
limitation",

"accountability","environment","commitment","evaluation","implementation","optimization","coord
ination","complexity"
 ]
};
```

🔥 Why this works really well

Level 1

- short, familiar words
- low cognitive load
- builds confidence

Level 2

- medium length
- more “thinking” words
- starts feeling harder

Level 3

- long + complex
- harder to type correctly
- **perfect for frustration/overwhelm mechanic**

💡 OPTIONAL (huge improvement)

Avoid repeating the same word back-to-back

Replace your word selection with:

```
let lastWord = "";

function getNewWord() {
 let list = wordLists[level];
 let word;

 do {
   word = random(list);
 } while (word === lastWord);

 lastWord = word;
 return word;
}
```

Then in `startTask()`:

```
currentWord = getNewWord();
```

🎮 OPTIONAL (makes it feel even better)

Shuffle word difficulty within level

Add a tiny mix:

```
currentWord = random(wordLists[level]);

// 20% chance to pull from harder level
if (random() < 0.2 && wordLists[level + 1]) {
 currentWord = random(wordLists[level + 1]);
}
```

👉 creates surprise difficulty spikes = more ADHD chaos

🚀 If you want to go NEXT level

I can also help you add:

- 🧠 **real phrases instead of words** (“finish homework”, “check email”)
- ⏱️ timed typing pressure
- 🎯 score multiplier for streaks
- 🔊 typing sound + error buzz

Just tell me 👍

Now I need to fix the focus orbs, they currently move away from the player very fast and fly off screen. I'd like to have them hover around an area they spawn but I still don't want them to chase the player.

Perfect — this is a great gameplay tweak. Right now your orb is basically doing:

👉 “run directly away from player forever”
which is why it flies off screen.

🎯 Goal

Make orbs:

- stay near where they spawn
- float gently (feel alive)
- NOT react to player

✅ Replace your `FocusOrb.update()` with this

```
update() {
 this.anim += 0.05;

 // gentle floating motion
 this.x += sin(this.anim) * 0.5;
 this.y += cos(this.anim * 1.2) * 0.5;

 // keep near spawn point
 let dx = this.x - this.spawnX;
 let dy = this.y - this.spawnY;

 let distFromHome = sqrt(dx * dx + dy * dy);

 let maxRadius = 40;

 if (distFromHome > maxRadius) {
   // pull back toward spawn
   this.x -= dx * 0.02;
   this.y -= dy * 0.02;
 }
}
```

🧠 IMPORTANT: Add spawn position

In your constructor, you need to store where it spawned:

```
constructor(x, y) {
 this.x = x;
 this.y = y;

 this.spawnX = x;
 this.spawnY = y;

 this.anim = random(100);
```

```
}
```

🎮 What this does

- Orbs **wiggle smoothly**
- Stay within a small radius (~40px)
- Never drift away
- Feel like “floating energy”

🔥 OPTIONAL (makes them feel REALLY good)

Add slight drifting instead of perfect circle

Replace movement with:

```
this.x += sin(this.anim) * 0.6 + random(-0.2, 0.2);
this.y += cos(this.anim * 1.3) * 0.6 + random(-0.2, 0.2);
```

🔥 OPTIONAL 2 (visual polish)

Make them pulse more when idle:

```
let pulse = sin(this.anim * 2) * 6;
```

🚫 REMOVE THIS (important)

Delete your old logic:

```
let dx = this.x - player.x;
let dy = this.y - player.y;
```

```
this.x += dx * 0.01;
this.y += dy * 0.01;
```

👉 That's what caused the "flying away" bug

🎯 Final result

Your orbs will:

- hover in place ✨
- feel alive
- stay collectible
- not interfere with gameplay flow

If you want next-level polish, I can help you:

- make orbs slowly drift across the map (but stay bounded)
- add magnet effect when player gets close
- or make rare "super orbs" 👀

Where exactly do I add the constructor stuff?

Good question — this is just about putting it in the **right place inside your class**, not somewhere new.

🎯 Where it goes

Open your `focusOrb.js`

You should already have something like:

```
class FocusOrb {
 constructor(x, y) {
   this.x = x;
   this.y = y;

   this.anim = random(100);
```

```
}
```

✅ Modify THAT constructor (don't add a new one)

Just **edit it** to this:

```
constructor(x, y) {
 this.x = x;
 this.y = y;

 // ✅ ADD THESE TWO LINES
 this.spawnX = x;
 this.spawnY = y;

 this.anim = random(100);
}
```

🧠 Important

- ❌ Do NOT create a second constructor
- ❌ Do NOT put this in `setup()` or `sketch.js`
- ✅ It stays inside the `FocusOrb` class

🔁 Full structure (so you're confident)

Your file should look like:

```
class FocusOrb {
 constructor(x, y) {
   this.x = x;
   this.y = y;

   this.spawnX = x;
   this.spawnY = y;
```

```
  this.anim = random(100);
 }

 update() {
  // your new hovering logic here
 }

 draw() {
  // existing draw code
 }
}
```

🎮 Why this matters

Now each orb remembers:

- where it **spawned**
- where it should **stay around**

Without this → your hover logic won't work properly.

If you want next step, I can help you make them:

- slowly **fade in when spawning**
- or **pulse brighter when near the player** (feels really nice)

I need the task box now to adjust to the length of the words, right now the ui for longer words is going out of the box.

Perfect — this is a **classic UI scaling issue**, and the fix is actually pretty clean.

Right now your box is **fixed width**, but your words are variable length → so long words overflow.

🎯 Goal

Make the task panel:

- automatically resize based on word length
- always fit the text inside
- stay centered nicely

✅ Step 1: Calculate dynamic width

Inside `drawTaskPanel()`, before drawing the box, add:

```
let padding = 40;

// estimate width based on word length
let wordWidth = currentWord.length * 20;

// minimum + max width limits
let boxWidth = max(220, wordWidth + padding);
```

✅ Step 2: Use dynamic position

Replace your fixed box position:

```
rect(width - 260, 120, 220, 200, 10);
```

With:

```
let boxX = width - boxWidth - 40;
let boxY = 120;

rect(boxX, boxY, boxWidth, 200, 10);
```

✅ Step 3: Center text inside the new box

Replace all your `width - 150` stuff with:

```
let centerX = boxX + boxWidth / 2;
```

Then update your text:

```
text("TYPE THE WORD", centerX, 160);
text(currentWord, centerX, 200);
text(displayText, centerX, 240);
```

🔥 FULL CLEAN VERSION

Here's the full upgraded function:

```
function drawTaskPanel() {
 if (!activeTask) return;

 let padding = 40;
 let wordWidth = currentWord.length * 20;
 let boxWidth = max(220, wordWidth + padding);

 let boxX = width - boxWidth - 40;
 let boxY = 120;
 let centerX = boxX + boxWidth / 2;

 fill(40);
 rect(boxX, boxY, boxWidth, 200, 10);

 textAlign(CENTER, CENTER);

 // title
 fill(255);
 textSize(18);
 text("TYPE THE WORD", centerX, 160);

 // faint full word
 fill(100);
 textSize(20);
 text(currentWord, centerX, 200);

 // progress
 fill(255);
 textSize(28);

 let displayText = "";
```

```
 for (let i = 0; i < currentWord.length; i++) {
   if (i < typedText.length) {
     displayText += currentWord[i] + " ";
   } else {
     displayText += "_ ";
   }
 }

 text(displayText, centerX, 240);
}
```

🧠 Why this works

- `currentWord.length` → determines size
- `max(220, …)` → prevents tiny box
- dynamic `centerX` → keeps layout clean

🔥 Optional (VERY nice polish)

Clamp max width so it doesn't get ridiculous:

boxWidth = constrain(boxWidth, 220, 500);

🎮 Result

Now:

- short words → small clean box
- long words → wider box
- nothing overflows
- UI looks intentional

If you want next level polish, I can help you:

- animate box expanding smoothly 👀
- wrap long words into 2 lines
- or scale text dynamically instead of resizing the box

Just tell me 👍

Make a new start screen for the game that has all this text on it and then let's implement the image as the new start screen.

Edit

Center the instruction text in the middle please

Edit

Take away the circles and the boxes that are breaking the border

Edit

Now walk me through making this image the start screen

Perfect — this is the fun part. You're basically just turning that image into a **background for your menu state**.

I'll walk you through it step-by-step, super clean.

🎯 STEP 1 — Add the image to your project

1. Create (or use) your assets folder:

assets/images/

2. Put your image in there, for example:

assets/images/startScreen.png

🎯 STEP 2 — Load the image in p5

At the **top of** `sketch.js`, add:

```
let startScreenImg;
```

Then add a **preload() function**:

```
function preload() {
 startScreenImg = loadImage("assets/images/startScreen.png");
}
```

👉 This ensures it loads before the game starts (important).

🎯 STEP 3 — Replace your `drawMenu()`

Right now you probably have text being drawn manually.

👉 Replace the entire function with this:

```
function drawMenu() {
 background(0);

 // draw the image full screen
 image(startScreenImg, 0, 0, width, height);
}
```

🎯 STEP 4 — Make sure your state still works

You already have something like:

```
if (state === "menu") drawMenu();
```

✅ Keep that exactly the same

🎯 STEP 5 — Keep SPACE to start

Make sure your `keyPressed()` still has:

```
if (keyCode === 32 && state === "menu") {
 state = "game";
}
```

🎮 DONE — What happens now

When the game launches:

- Your image fills the screen
- No text is drawn on top
- Press SPACE → game starts

🔥 OPTIONAL (HIGHLY RECOMMENDED)

Add a subtle “Press SPACE” glow animation

Even though it's in the image, you can reinforce it:

```
if (frameCount % 60 < 30) {
 fill(0, 255, 200, 100);
 textAlign(CENTER);
 textSize(20);
 text("Press SPACE", width / 2, height - 80);
}
```

⚠️ If it doesn't show

Check:

- file path is correct (`assets/images/...`)
- filename matches EXACTLY (case-sensitive)
- no typos in `loadImage`

🚀 If you want next level polish

I can help you:

- fade from menu → game smoothly
- add animated particles behind the image
- add hover/click start instead of space
- add sound on start

Just tell me 👍

Or you know what, I don't want to add that image as the actual start screen, but I want the start screen to look exactly like that, so can you change my code to make it look like that.

Perfect — this is actually *better* than using an image. You'll get a clean, scalable, animated UI that looks like your design.

We're going to recreate that screen using p5 code.

🎯 What we're building

Your menu will have:

- glowing border ✅
- star/particle background ✅
- neon title ✅
- centered instructions ✅
- glowing "Press SPACE" ✅

🔧 STEP 1 — Replace your `drawMenu()` completely

```
function drawMenu() {
 background(5);

 drawStars();     // background particles
 drawBorder();    // glowing frame
 drawMenuText();  // all text
}
```

🌌 STEP 2 — Add star background

Put this anywhere in your file:

```
let stars = [];

function initStars() {
 for (let i = 0; i < 150; i++) {
   stars.push({
     x: random(width),
     y: random(height),
     size: random(1, 3),
     alpha: random(50, 150)
   });
 }
}

function drawStars() {
 noStroke();
 for (let s of stars) {
   fill(0, 255, 200, s.alpha);
   circle(s.x, s.y, s.size);

   // subtle flicker
   s.alpha += random(-2, 2);
   s.alpha = constrain(s.alpha, 30, 180);
 }
}
```

👉 **IMPORTANT: call this in `setup()`**

```
initStars();
```

🟩 STEP 3 — Glowing border

```
function drawBorder() {
 noFill();

 for (let i = 0; i < 3; i++) {
   stroke(0, 255, 200, 80 - i * 20);
   strokeWeight(2 + i);
   rect(40, 40, width - 80, height - 80);
 }
}
```

✨ STEP 4 — Text (this is the key part)

```
function drawMenuText() {
 textAlign(CENTER, CENTER);

 // glowing title
 for (let i = 0; i < 5; i++) {
   fill(0, 255, 200, 30);
   textSize(70);
   text("FOCUS FRENZY", width / 2, 180);
 }

 fill(200, 255, 240);
 textSize(60);
 text("FOCUS FRENZY", width / 2, 180);

 // instructions
 textSize(22);
 fill(220);

 let y = height / 2 - 60;
 let lineSpacing = 35;

 let instructions = [
```

```
  "Move with WASD",
  "Hover over tasks to start them",
  "Type the correct word to finish",
  "Distractions will chase you",
  "They move faster when you focus on tasks",
  "",
  "Complete all tasks before your focus runs out"
];

for (let i = 0; i < instructions.length; i++) {
  text(instructions[i], width / 2, y + i * lineSpacing);
}

// glowing SPACE text
let pulse = sin(frameCount * 0.05) * 50 + 150;

fill(0, 255, 200, pulse);
textSize(26);
text("Press SPACE to start", width / 2, height - 120);
}
```

🎮 STEP 5 — Make sure your state still works

You already have:

```
if (state === "menu") drawMenu();
```

✅ keep that

🚀 FINAL RESULT

Your menu will now:

- look almost identical to your image
- be animated (stars + glow)
- scale perfectly fullscreen
- feel like a real game UI

🔥 If you want it EVEN closer to your image

I can add:

- subtle moving glow line under title
- animated border corners
- floating particles like your orbs
- blur glow effect

Just say 👍

Wait where do I put step 4?

Good question — this is where people usually get tripped up.

🎯 Short answer

👉 **Step 4 is a NEW FUNCTION**
👉 You put it **outside of `draw()`**, just like your other functions (`drawMenu`, `drawUI`, etc.)

🧠 Where exactly in your file?

Your `sketch.js` probably looks something like this:

```
function setup() {
 ...
}

function draw() {
 ...
}
```

```
function drawMenu() {
 ...
}
```

✅ You add Step 4 like this:

```
function drawMenuText() {
 textAlign(CENTER, CENTER);

 // glowing title
 for (let i = 0; i < 5; i++) {
   fill(0, 255, 200, 30);
   textSize(70);
   text("FOCUS FRENZY", width / 2, 180);
 }

 fill(200, 255, 240);
 textSize(60);
 text("FOCUS FRENZY", width / 2, 180);

 // instructions
 textSize(22);
 fill(220);

 let y = height / 2 - 60;
 let lineSpacing = 35;

 let instructions = [
   "Move with WASD",
   "Hover over tasks to start them",
   "Type the correct word to finish",
   "Distractions will chase you",
   "They move faster when you focus on tasks",
   "",
   "Complete all tasks before your focus runs out"
 ];

 for (let i = 0; i < instructions.length; i++) {
   text(instructions[i], width / 2, y + i * lineSpacing);
 }

 // glowing SPACE text
```

```
 let pulse = sin(frameCount * 0.05) * 50 + 150;

 fill(0, 255, 200, pulse);
 textSize(26);
 text("Press SPACE to start", width / 2, height - 120);
}
```

🎯 Then CONNECT it (this is the important part)

Inside your `drawMenu()` you MUST call it:

```
function drawMenu() {
 background(5);

 drawStars();
 drawBorder();
 drawMenuText(); // ← THIS LINE USES STEP 4
}
```

🧩 Think of it like this

- `drawMenu()` = the controller
- `drawMenuText()` = just handles text

🚨 Common mistake (don't do this)

❌ Don't paste Step 4 inside `draw()`
❌ Don't paste it inside `drawMenu()`
❌ Don't replace existing code with it

👉 It's its own function.

🎮 Final structure should look like:

```
setup()
draw()
drawMenu()

drawStars()
drawBorder()
drawMenuText()  // ← your new function
```

If you want next, I can help you:

- perfectly match spacing to your image (pixel-perfect)
- add that glowing underline under the title (looks 🔥)
- or animate the border corners like your mockup

Just say 👍

I think I need to change the task box to spawn in the middle of the screen, and I think I want to add the ability to exit a task by pressing shift, so adding a ("Shift to exit UI under the task box and allowing the player to exit the task that way would be great.

Both of these are **great gameplay upgrades** — this is exactly the kind of polish that makes your project feel intentional.

I'll walk you through both cleanly:

🎯 1. MOVE TASK BOX TO CENTER OF SCREEN

Right now your box is probably anchored to the right like:

rect(width - 260, 120, ...)

✅ Replace positioning logic in `drawTaskPanel()`

Instead of:

```
let boxX = width - boxWidth - 40;
let boxY = 120;
```

✅ Use this:

```
let boxX = width / 2 - boxWidth / 2;
let boxY = height / 2 - 100;
```

👉 This centers it horizontally + vertically

✅ Text stays centered automatically

You already have:

```
let centerX = boxX + boxWidth / 2;
```

That still works perfectly 👍

🎮 Result

Your task UI will now:

- pop up in the middle
- feel like a “focus mode”
- be way more noticeable

🎯 2. ADD “SHIFT TO EXIT TASK”

This is a **huge design improvement** (and matches your doc idea perfectly).

✅ Step 1 — Detect SHIFT key

Update your `keyPressed()`:

```
if (keyCode === SHIFT && activeTask) {
 activeTask = null;
 player.locked = false;

 typedText = ""; // optional reset
}
```

⚠️ Important

p5 uses:

keyCode === SHIFT

NOT `"Shift"`

🎯 3. ADD UI TEXT (“Shift to exit”)

Inside `drawTaskPanel()`, add this at the bottom:

```
fill(180);
textSize(14);
text("Press SHIFT to exit", centerX, boxY + 170);
```

🔥 OPTIONAL (better UX)

Make it slightly faded:

```
fill(180, 180, 180, 120);
```

🎯 4. OPTIONAL (more realistic ADHD mechanic)

If you want it to feel even stronger:

👉 exiting a task increases distractions

```
if (keyCode === SHIFT && activeTask) {
 activeTask = null;
 player.locked = false;
 typedText = "";

 // spawn extra distractions
 for (let i = 0; i < 2; i++) {
   distractions.push(new Distraction(random(width), random(height)));
 }
}
```

🎮 Final Result

Now your gameplay loop is:

1. Walk to task
2. Task UI appears in center
3. Start typing
4. Panic → press SHIFT
5. Leave task unfinished
6. Come back later

👉 This is **exactly** the ADHD experience you described

🚀 If you want next-level polish

I can help you:

- blur/dim background when task is open (SUPER nice)
- pause distractions while in task (or make them worse 👀)
- add progress saving when exiting tasks

Just tell me 👍



Right now the shift button does not close the task, it changes the word. Pressing shift should allow the player to move again and navigate to a different task. Also the UI got messed up, the shift text looks great but the task box text is now above the box.

Perfect — I can see both issues clearly from your screenshot. Let's fix them cleanly.

🚨 ISSUE 1: SHIFT is changing the word

Why this is happening

Your typing logic is still running when you press SHIFT, so it's being treated like a character input.

✅ FIX: Ignore SHIFT in typing logic

Update your `keyPressed()` like this:

function keyPressed() {

```
// ✅ FIRST: handle SHIFT exit
if (keyCode === SHIFT && activeTask) {
  activeTask = null;
  player.locked = false;
  typedText = "";
  return; // ⛔ IMPORTANT: stops further processing
}

// typing system
if (activeTask) {
  // ⛔ ignore special keys like SHIFT
  if (key.length === 1 && keyCode !== SHIFT) {
    typedText += key.toLowerCase();
  }

  if (!currentWord.startsWith(typedText)) {
    typedText = "";
  }

  if (typedText === currentWord) {
    activeTask.done = true;
    spawnParticles(activeTask.x + 20, activeTask.y + 20);

    activeTask = null;
    player.locked = false;
    typedText = "";
  }
}

if (keyCode === 32 && state === "menu") {
  state = "game";
}
}
```

🎯 RESULT

- SHIFT exits task ✅
- player can move again ✅
- word does NOT change ✅

🚨 ISSUE 2: TEXT IS ABOVE THE BOX

From your screenshot:
👉 The **box is centered**
👉 But the **text is still using old Y positions**

✅ FIX: Anchor everything to the box

Inside `drawTaskPanel()`:

Replace ALL your Y positions with this system:

```
let boxX = width / 2 - boxWidth / 2;
let boxY = height / 2 - 100;

let centerX = width / 2;
```

✅ Then update ALL text positions

❌ You probably still have:

```
text("TYPE THE WORD", centerX, 160);
```

✅ Replace with:

```
// title
text("TYPE THE WORD", centerX, boxY + 40);

// faint word
text(currentWord, centerX, boxY + 80);

// progress
text(displayText, centerX, boxY + 120);

// exit text
text("Press SHIFT to exit", centerX, boxY + 160);
```

🔥 FULL FIXED TEXT BLOCK

```
textAlign(CENTER, CENTER);

// title
fill(255);
textSize(18);
text("TYPE THE WORD", centerX, boxY + 40);

// faint word
fill(120);
textSize(20);
text(currentWord, centerX, boxY + 80);

// progress
fill(255);
textSize(28);
text(displayText, centerX, boxY + 120);

// exit instruction
fill(180, 180, 180, 120);
textSize(14);
text("Press SHIFT to exit", centerX, boxY + 160);
```

🎯 RESULT

Now:

- All text is inside the box ✅
- perfectly centered ✅
- UI looks intentional again ✅

💡 SMALL BONUS FIX (IMPORTANT)

Right now tasks are still triggering while you're inside one.

👉 Add this in `Task.checkHover()`:

if (activeTask) return;

🚀 Final Outcome

- SHIFT cleanly exits tasks
- Player regains control
- UI is visually correct
- No weird text floating above the box

If you want next level polish:

- dim the background when task is open (looks 🔥)
- pause distractions while typing (or increase them 😈)
- add a subtle UI fade-in animation

Just tell me 👍

```
⚠
```

The game freezes now when starting a task and shows this error

Perfect — that error tells us *exactly* what broke.

🚨 THE PROBLEM

ReferenceError: Cannot access 'displayText' before initialization

👉 This means you're using `displayText` **before you created it**

🎯 Why it's happening

You probably now have something like this:

text(displayText, centerX, boxY + 120); // ❌ using it

let displayText = ""; // ❌ declared AFTER

👉 JavaScript doesn't allow that with `let`

✅ FIX (SUPER SIMPLE)

Move this line:

let displayText = "";

🔼 **ABOVE everything that uses it**

✅ Correct order (this is important)

Inside `drawTaskPanel()`:

```
let displayText = "";

// build the text FIRST
for (let i = 0; i < currentWord.length; i++) {
 if (i < typedText.length) {
   displayText += currentWord[i] + " ";
 } else {
   displayText += "_ ";
 }
}

// THEN draw it
text(displayText, centerX, boxY + 120);
```

🚨 WHY YOUR GAME FROZE

Because:

- error happens inside `draw()`
- p5 stops rendering loop
- game appears frozen

🔥 QUICK CHECKLIST

Make sure inside `drawTaskPanel()`:

✅ `displayText` is declared BEFORE use
✅ the loop builds it BEFORE drawing
✅ no duplicate `let displayText` exists

💡 BONUS (prevents future bugs)

If you want to be extra safe, always structure like this:

```
// 1. calculate stuff
// 2. build strings
// 3. draw everything
```

🎮 After this fix

- task UI will work again ✅
- no freeze ✅
- typing system works normally ✅

If you want, next I can help you:

- add smooth UI fade-in when task opens
- blur/dim background behind task (looks 🔥)
- or add sound feedback for typing

Just say 👍

Ok I need to go back to the version without the shift exit feature, so just give me all the functions from before

Got you — clean rollback 👍
We'll remove the SHIFT feature and restore your **working typing + task system**.

🎯 1. `keyPressed()` (RESTORED VERSION)

Replace your current one with this:

```
function keyPressed() {
 // typing system
 if (activeTask) {
   if (key.length === 1) {
     typedText += key.toLowerCase();
   }

   // reset if wrong
   if (!currentWord.startsWith(typedText)) {
     typedText = "";
   }

   // completed word
   if (typedText === currentWord) {
     activeTask.done = true;
     spawnParticles(activeTask.x + 20, activeTask.y + 20);

     activeTask = null;
     player.locked = false;

     typedText = "";
   }
 }
```

```
 // start game
 if (keyCode === 32 && state === "menu") {
   state = "game";
 }
}
```

🎯 2. `startTask()`

```
function startTask(task) {
 if (activeTask) return;

 activeTask = task;
 player.locked = true;

 currentWord = random(wordLists[level]);
 typedText = "";
}
```

🎯 3. `drawTaskPanel()` (clean version, no SHIFT UI)

```
function drawTaskPanel() {
 if (!activeTask) return;

 let padding = 40;
 let wordWidth = currentWord.length * 20;
 let boxWidth = max(220, wordWidth + padding);

 let boxX = width / 2 - boxWidth / 2;
 let boxY = height / 2 - 100;
 let centerX = width / 2;

 fill(40);
 rect(boxX, boxY, boxWidth, 200, 10);

 textAlign(CENTER, CENTER);
```

```
  // build display text FIRST
  let displayText = "";
  for (let i = 0; i < currentWord.length; i++) {
    if (i < typedText.length) {
      displayText += currentWord[i] + " ";
    } else {
      displayText += "_ ";
    }
  }

  // title
  fill(255);
  textSize(18);
  text("TYPE THE WORD", centerX, boxY + 40);

  // faint word
  fill(120);
  textSize(20);
  text(currentWord, centerX, boxY + 80);

  // progress
  fill(255);
  textSize(28);
  text(displayText, centerX, boxY + 120);
}
```

🎯 4. `Task.checkHover()` (keep this fix)

```
checkHover() {
  if (this.done) return;
  if (activeTask) return;

  let centerX = this.x + 20;
  let centerY = this.y + 20;

  if (dist(player.x, player.y, centerX, centerY) < 40) {
    startTask(this);
  }
}
```

🚨 WHAT WE REMOVED

- ❌ SHIFT key logic
- ❌ exit UI text
- ❌ task cancel behavior

🎮 RESULT

You're back to:

- clean typing system ✅
- tasks lock player until completed ✅
- no crashes ✅
- centered UI still intact ✅

If you want later, we can re-add a **better version of exit** (like ESC or a button) without breaking typing again.

I want to try adding in one new feature that starts in level 2, which are safe boxes. These will be boxes glowing in a matching colour of the level colour that will spawn for 10 seconds and when the player goes into this box the distractions will move away from the player instead of towards the player. Just a transparent square with a colour border. They can flash when they are going away and can spawn every 15 seconds.

This is a 🔥 feature — it adds strategy + relief + contrast (which your concept really benefits from).

Let’s build it cleanly so it plugs right into your existing system.

🎯 WHAT WE’RE ADDING

Safe Zones:

- Spawn every **15 seconds**
- Exist for **10 seconds**
- Only appear **Level 2+**

- When player is inside:
  - distractions move **away** instead of toward
- Visual:
  - transparent square
  - glowing border
  - flashes before disappearing

🧠 STEP 1 — Create SafeZone class

👉 New file or put near your other classes:

```
class SafeZone {
 constructor(x, y, size) {
   this.x = x;
   this.y = y;
   this.size = size;

   this.spawnTime = millis();
   this.duration = 10000; // 10 seconds
 }

 update() {
   this.timeLeft = this.duration - (millis() - this.spawnTime);
 }

 draw() {
   let flashing = this.timeLeft < 3000;

   if (flashing && frameCount % 20 < 10) return;

   // level color
   let col = getLevelColor();

   noFill();

   for (let i = 0; i < 3; i++) {
     stroke(red(col), green(col), blue(col), 80 - i * 20);
     strokeWeight(2 + i);
     rect(this.x, this.y, this.size, this.size);
   }
 }
```

```
 isInside(px, py) {
   return (
     px > this.x &&
     px < this.x + this.size &&
     py > this.y &&
     py < this.y + this.size
   );
 }

 isExpired() {
   return millis() - this.spawnTime > this.duration;
 }
}
```

🎨 STEP 2 — Level color helper

Add this somewhere:

```
function getLevelColor() {
 if (level === 1) return color(0, 255, 180);
 if (level === 2) return color(255, 200, 0);
 if (level === 3) return color(255, 80, 120);
}
```

🧠 STEP 3 — Global variables

At top of `sketch.js`:

```
let safeZones = [];
let lastSafeSpawn = 0;
let playerInSafeZone = false;
```

⏱️ STEP 4 — Spawn logic

Inside `runGame()`:

```
// spawn every 15 seconds (level 2+ only)
if (level >= 2 && millis() - lastSafeSpawn > 15000) {
 safeZones.push(
   new SafeZone(
     random(100, width - 200),
     random(100, height - 200),
     120
   )
 );

 lastSafeSpawn = millis();
}
```

🎮 STEP 5 — Update & draw safe zones

Still inside `runGame()`:

```
playerInSafeZone = false;

for (let z of safeZones) {
 z.update();
 z.draw();

 if (z.isInside(player.x, player.y)) {
   playerInSafeZone = true;
 }
}

// remove expired zones
safeZones = safeZones.filter(z => !z.isExpired());
```

🚨 STEP 6 — MODIFY DISTRACTIONS (IMPORTANT)

Inside your `Distraction.update()`:

❌ You currently have:

```
let dx = player.x - this.x;
let dy = player.y - this.y;
```

✅ Replace with:

```
let dx = player.x - this.x;
let dy = player.y - this.y;

// reverse direction if in safe zone
if (playerInSafeZone) {
 dx *= -1;
 dy *= -1;
}
```

👉 That's the magic line:
safe zone = flip direction

✨ STEP 7 — OPTIONAL POLISH (HIGHLY RECOMMENDED)

Make safe zone glow when active

Inside `draw()`:

```
if (this.isInside(player.x, player.y)) {
 strokeWeight(4);
}
```

Add slight pulse

```
let pulse = sin(frameCount * 0.1) * 5;
rect(this.x, this.y, this.size + pulse, this.size + pulse);
```

🎯 FINAL RESULT

Now your game has:

- 🟨 Safe zones spawning every 15s
- ⏳ Last 10 seconds
- ⚡ Flash before disappearing
- 🧲 Flip enemy behavior
- 🧠 Strategic positioning

🚀 WHY THIS IS REALLY STRONG

This adds:

- relief mechanic
- positioning decisions
- pacing variation
- emotional contrast (stress → safety → stress)

👉 Exactly what your concept needs.

If you want next-level polish, I can help you:

- add a **fade-in spawn animation**
- make distractions **hesitate at the edge**
- add a **sound cue when zone appears**

Just say 👍

Where does the pulse code go?

Good question — this is a **placement thing**, not a new feature.

🎯 Where the pulse code goes

👉 It goes **inside the `SafeZone.draw()` function**

That's the function already drawing your square.

🧠 Right now you probably have:

```
draw() {
 let flashing = this.timeLeft < 3000;

 if (flashing && frameCount % 20 < 10) return;

 let col = getLevelColor();

 noFill();

 for (let i = 0; i < 3; i++) {
   stroke(red(col), green(col), blue(col), 80 - i * 20);
   strokeWeight(2 + i);
   rect(this.x, this.y, this.size, this.size);
 }
}
```

✅ Replace the `rect(...)` line with pulse version

```
let pulse = sin(frameCount * 0.1) * 5;

rect(
 this.x - pulse / 2,
 this.y - pulse / 2,
 this.size + pulse,
 this.size + pulse
);
```

🔥 FULL UPDATED `draw()` (copy this)

```
draw() {
 let flashing = this.timeLeft < 3000;
```

```
  if (flashing && frameCount % 20 < 10) return;

  let col = getLevelColor();

  noFill();

  let pulse = sin(frameCount * 0.1) * 5;

  for (let i = 0; i < 3; i++) {
    stroke(red(col), green(col), blue(col), 80 - i * 20);
    strokeWeight(2 + i);

    rect(
      this.x - pulse / 2,
      this.y - pulse / 2,
      this.size + pulse,
      this.size + pulse
    );
  }
}
```

🎮 What this does

- Box gently expands/contracts
- Still centered (important 👀)
- Feels “alive” instead of static

⚠️ Common mistake

❌ Don’t put pulse in `update()`
❌ Don’t put it in `runGame()`
✅ It belongs in `draw()` because it’s visual

🔥 If you want it to feel EVEN better

We can also:

- pulse faster when about to disappear
- glow brighter when player is inside
- add ripple effect on entry

Just say 👍

⚠️

I'm seeing this error now

Perfect — this error is actually very clear, and it's a small fix.

🚨 THE ERROR

TypeError: this.isInside is not a function

👉 That means:
You're calling:

this.isInside(player.x, player.y)

…but **that function doesn't exist on `this`**

🎯 WHAT'S WRONG

You likely wrote something like this inside `runGame()`:

if (this.isInside(player.x, player.y)) {

👉 ❌ `this` is NOT a SafeZone here
👉 `this` = global / window → no `isInside` function

✅ FIX (VERY SIMPLE)

You need to call it on the **safe zone object**, not `this`

🔁 Change this:

if (this.isInside(player.x, player.y)) {

✅ To this:

if (z.isInside(player.x, player.y)) {

🧠 WHY

You loop like this:

for (let z of safeZones)

👉 So each zone is `z`, not `this`

✅ FULL CORRECT LOOP

```
playerInSafeZone = false;

for (let z of safeZones) {
 z.update();
 z.draw();

 if (z.isInside(player.x, player.y)) {
   playerInSafeZone = true;
 }
}
```

🚨 DOUBLE CHECK

Also make sure your class actually HAS the function:

```
isInside(px, py) {
 return (
   px > this.x &&
   px < this.x + this.size &&
   py > this.y &&
   py < this.y + this.size
 );
}
```

🎮 RESULT

- error gone ✅
- safe zones detect player properly ✅
- distractions will flip direction correctly ✅

💡 Quick debugging rule (super useful)

If you ever see:

```
this.X is not a function
```

👉 Ask:

- Am I inside the right class?
- Or should I be using an object like `z.X()`?

If you want next polish:
I can help you make safe zones:

- glow brighter when inside
- push enemies away more dramatically
- or show a timer ring countdown

Just say 👍

Can you give me the full runGame

Yeah — let's put everything together cleanly so you have a **working `runGame()` with safe zones fully integrated**.

This version includes:

- player + tasks
- distractions
- particles
- focus orbs
- ✅ safe zones (with detection + spawn + cleanup)

🎯 FULL `runGame()` (copy this)

```
function runGame() {
 push();

 // screen shake
 translate(random(-shake, shake), random(-shake, shake));

 drawLevelMap();

 // player
 player.update();
 player.draw();

 // tasks
 for (let t of tasks) {
   t.draw();
   t.checkHover();
 }

 // distractions spawn
 spawnDistractions();

 // ✅ SAFE ZONE SPAWN (level 2+)
 if (level >= 2 && millis() - lastSafeSpawn > 15000) {
   safeZones.push(
```

```
    new SafeZone(
      random(100, width - 200),
      random(100, height - 200),
      120
    )
  );

  lastSafeSpawn = millis();
}

// ✅ SAFE ZONE UPDATE + DETECTION
playerInSafeZone = false;

for (let z of safeZones) {
  z.update();
  z.draw();

  if (z.isInside(player.x, player.y)) {
    playerInSafeZone = true;
  }
}

// remove expired zones
safeZones = safeZones.filter(z => !z.isExpired());

// distractions
for (let d of distractions) {
  d.update();
  d.draw();
}

// UI
drawTaskPanel();
drawUI();

// timer + lose condition
timer -= deltaTime / 1000;

if (timer <= 0 || focus <= 0) {
  state = "lose";
}

// win / next level
if (tasks.every((t) => t.done)) {
```

```
  level++;

  if (level > 3) {
    state = "win";
  } else {
    initLevel();
  }
}

// particles
for (let p of particles) {
  p.update();
  p.draw();
}

particles = particles.filter((p) => p.life > 0);

// focus orbs
if (frameCount % 900 === 0) {
  focusOrbs.push(
    new FocusOrb(
      random(100, width - 100),
      random(100, height - 100)
    )
  );
}

for (let o of focusOrbs) {
  o.update();
  o.draw();
}

focusOrbs = focusOrbs.filter((o) => !o.collected);

pop();

// decay screen shake
shake *= 0.9;
}
```

🚨 MAKE SURE YOU ALSO HAVE THIS

Globals (top of file):

```
let safeZones = [];
let lastSafeSpawn = 0;
let playerInSafeZone = false;
```

🚨 AND THIS (inside Distraction.update)

```
let dx = player.x - this.x;
let dy = player.y - this.y;

if (playerInSafeZone) {
 dx *= -1;
 dy *= -1;
}
```

🎮 RESULT

Now your game has:

- 🟩 Safe zones spawning every 15s
- ⏳ Last 10s
- 🧲 Flip enemy behavior
- 🎯 Clean integration with everything else

🔥 If something still feels off

Tell me what you're seeing and I'll debug it fast — but this version is **fully wired correctly**.

If you want next-level polish:

- safe zone fade-in animation
- enemies "bounce" off edge instead of instantly flipping
- visual effect when entering zone

Just say 👍

Pasted text.txt
Document
class SafeZone { constructor(x, y, size) { this.x = x; this.y = y; this.size = size; this.spawnTime = millis(); this.duration = 10000; // 10 seconds } update() { this.timeLeft = this.duration - (millis() - this.spawnTime); } draw() { let flashing = this.timeLeft < 3000; if (flashing && frameCount % 20 < 10) return; let col = getLevelColor(); noFill(); let pulse = sin(frameCount * 0.1) * 5; for (let i = 0; i < 3; i++) { stroke(red(col), green(col), blue(col), 80 - i * 20); strokeWeight(2 + i); rect(this.x - pulse / 2, this.y - pulse / 2, this.size + pulse, this.size + pulse,); } } isInside(px, py) { return (px > this.x && px < this.x + this.size && py > this.y && py < this.y + this.size); } isExpired() { return millis() - this.spawnTime > this.duration; } } function getLevelColor() { if (level === 1) return color(0, 255, 180); if (level === 2) return color(255, 200, 0); if (level === 3) return color(255, 80, 120); } Im still getting the isInside error from before

I found the exact problem in your code — and it's **not in your SafeZone class at all** (that part is correct).

🚨 THE REAL ISSUE (from your file)

This line is the problem:

```
if (this.isInside(player.x, player.y)) {
 strokeWeight(4);
}
```

👉 It's inside your `draw()` function

❌ Why this breaks everything

Inside `draw()`:

- `this` = global p5 context (NOT a SafeZone)
- So `this.isInside` = ❌ undefined
- That's why you get:
  `this.isInside is not a function`

✅ FIX (DELETE THIS)

Remove this entire block:

```
if (this.isInside(player.x, player.y)) {
 strokeWeight(4);
}
```

🎯 If you wanted that effect (highlight when inside)

You need to move it into the **SafeZone class**, like this:

✅ Put this inside `SafeZone.draw()`

```
let isPlayerInside = this.isInside(player.x, player.y);

for (let i = 0; i < 3; i++) {
 stroke(red(col), green(col), blue(col), 80 - i * 20);

 if (isPlayerInside) {
   strokeWeight(4 + i); // thicker when inside
 } else {
   strokeWeight(2 + i);
 }

 rect(
   this.x - pulse / 2,
   this.y - pulse / 2,
   this.size + pulse,
   this.size + pulse
 );
}
```

🧠 Key takeaway

- `this.isInside()` only works **inside SafeZone**
- Outside → you must use `z.isInside(...)`

🎮 After this fix

- error disappears ✅
- game stops freezing ✅
- safe zones work properly ✅
- highlight effect works correctly ✅

🔥 You're very close now

Your system is actually solid — this was just a **scope mistake** (super common).

If you want next polish, I can help you:

- make distractions **repel smoothly instead of instantly flipping**
- add a **visual shockwave when entering safe zone**
- or add a **countdown indicator inside the box**

Just say 👍

⚠

The game now crashed on level two when the safe zones are supposed to show up

Good — this is another **very clear error**, and you're super close now.

🚨 THE ERROR

ReferenceError: Can't find variable: safeZone

👉 This means somewhere in your code you wrote:

safeZone

…but you **never created a variable called `safeZone`**

🎯 THE REAL ISSUE

You correctly have:

let safeZones = [];

👉 plural ✅

BUT somewhere (likely in `runGame()`), you accidentally used:

safeZone ❌ (singular)

🔍 WHERE TO LOOK

Search your code for:

safeZone

You'll probably find something like:

safeZone.push(...)

or

safeZone.update()

✅ FIX (VERY IMPORTANT)

Replace **ALL** of these:

safeZone ❌

with:

safeZones ✅

✅ Correct usage should look like:

Spawning:

```
safeZones.push(new SafeZone(...));
```

Looping:

```
for (let z of safeZones) {
 z.update();
 z.draw();
}
```

Filtering:

```
safeZones = safeZones.filter(z => !z.isExpired());
```

⚠️ WHY IT ONLY CRASHES ON LEVEL 2

Because this code only runs:

if (level >= 2)

👉 So the error doesn't exist until Level 2 starts.

🧠 Quick debugging tip

If you see:

"Can't find variable X"

👉 90% of the time it's:

- typo (safeZone vs safeZones)
- wrong scope
- missing declaration

🎮 After this fix

- Level 2 won't crash ✅
- Safe zones will spawn ✅
- Everything should work smoothly

🔥 You're basically done with this feature

If you want next polish:

- enemies slow down instead of instantly flipping
- safe zone gives slight focus regen
- visual "pulse wave" when entering

Just tell me 👍

Perfect — this error tells us *exactly* what's wrong again, and it's a quick fix.

🚨 THE ERROR

TypeError: Array is not a constructor (evaluating 'new safeZones(...)')

👉 This means you wrote:

new safeZones(...)

❌ WHAT'S WRONG

safeZones

is your **array**:

let safeZones = [];

👉 Arrays are NOT classes
👉 You can't do `new safeZones(...)`

✅ FIX (VERY IMPORTANT)

You need to create a **SafeZone**, not a `safeZones`

🔁 Replace this:

```
safeZones.push(
 new safeZones(random(100, width - 200), random(100, height - 200), 120)
);
```

✅ With this:

```
safeZones.push(
 new SafeZone(random(100, width - 200), random(100, height - 200), 120)
);
```

🧠 Key difference

Wrong ❌	Right ✅
`safeZones`	`SafeZone`
array	class
plural	singular

🎯 Why this happened

You accidentally mixed up:

- **safeZones** → your list
- **SafeZone** → your class

Super common bug.

🎮 After this fix

- Level 2 won't crash ✅
- Safe zones will spawn properly ✅
- Everything will finally work as intended ✅

🔥 You are VERY close now

You've basically implemented a full system:

- spawning
- lifetime
- interaction
- behavior switching

That's legit game dev work.

🚀 If you want next polish

I can help you:

- add a **spawn animation (fade-in glow)**
- make distractions **bounce off edges instead of instantly reversing**
- show a **visual timer shrinking box**

Just say 👍

The last change I want to add is this: Make the emotion of the smiley face change based on their focus bar (full = happy, ⅔ full = ok, ⅓ full = sad) Change colour as well (green->yellow->red) Add the colour change to the focus bar as well so that elements of the whole screen are changing colour (green → yellow → red)

This is a 🔥 final feature — it ties your **UI + emotion + gameplay feedback** all together. Let's do it cleanly so everything updates from one system.

🎯 WHAT WE'RE ADDING

Based on `focus`:

- 😊 Happy (green) → high focus
- 😐 Neutral (yellow) → medium
- ☹️ Sad (red) → low

Also:

- Focus bar changes color
- Smiley face changes expression + color

🧠 STEP 1 — Create a shared “focus state” function

👉 Add this anywhere (top or near UI code):

```
function getFocusState() {
 if (focus > 66) {
   return {
     color: color(0, 255, 150), // green
     mood: "happy"
   };
 } else if (focus > 33) {
   return {
     color: color(255, 200, 0), // yellow
     mood: "ok"
   };
 } else {
   return {
     color: color(255, 80, 80), // red
     mood: "sad"
   };
 }
}
```

🎯 STEP 2 — Update your focus bar

Find this in `drawUI()`:

```
fill(0, 255, 150);
rect(600, 20, focus * 2, 16);
```

✅ Replace with:

```
let state = getFocusState();

fill(state.color);
rect(600, 20, focus * 2, 16);
```

🎯 STEP 3 — Update the smiley face

Go to your `Player.draw()` function

🔁 Replace the face drawing part with this:

```
let state = getFocusState();

// face outline
stroke(state.color);
strokeWeight(3);
fill(0);
ellipse(0, 0, 40);

// eyes
fill(state.color);
noStroke();
ellipse(-7, -5, 6);
ellipse(7, -5, 6);

// mouth
stroke(state.color);
strokeWeight(3);
noFill();

if (state.mood === "happy") {
 arc(0, 5, 20, 15, 0, PI);
} else if (state.mood === "ok") {
 line(-8, 8, 8, 8);
} else {
 arc(0, 12, 20, 15, PI, TWO_PI);
}
```

🎯 STEP 4 — (OPTIONAL but VERY NICE)

Make UI text match mood color

In `drawUI()`:

```
let state = getFocusState();

fill(state.color);
text("Focus", 540, 30);
```

🎯 STEP 5 — (OPTIONAL polish)

Add glow effect when high focus

```
if (focus > 66) {
 stroke(0, 255, 150, 50);
 strokeWeight(6);
 ellipse(0, 0, 50);
}
```

👉 Put inside `Player.draw()`

🎮 FINAL RESULT

Now your game visually communicates:

Focus	Face	Color
High	😊	Green
Medium	😐	Yellow
Low	☹️	Red

🔥 WHY THIS IS REALLY STRONG

This adds:

- emotional feedback
- visual clarity

- accessibility (color + shape)
- stronger connection to your theme

👉 This is the kind of polish profs LOVE.