



## IOS STATIC ANALYSIS REPORT



🍏 DVIA-v2 (2.0)

File Name:


DVIA-v2.ipa

Identifier: com.hightitudehacks.DVIAswiftv2

Scan Date: June 24, 2026, 2:47 p.m.

App Security Score: 42/100 (MEDIUM RISK)

Grade:



Trackers Detection: 3/432

|  HIGH |  MEDIUM |  INFO |  SECURE |  HOTSPOT |
|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| 1                                                                                      | 6                                                                                        | 2                                                                                      | 0                                                                                          | 2                                                                                           |



FILE INFORMATION

**File Name:** DVIA-v2.ipa  
**Size:** 9.2MB  
**MD5:** b919e84e7d35f68e16b6cd05d8e3b1ce  
**SHA1:** 1dd38869cb0a5b9bdb57a46341547e1cc0dac8ca  
**SHA256:** dabf92a5ca1cc00221fa3a12f1b58f1095da5698ea4dcb92ab0c64699cff6d5f



APP INFORMATION

**App Name:** DVIA-v2  
**App Type:** Swift  
**Identifier:** com.hightitudehacks.DVIAswiftv2  
**SDK Name:** iphoneos17.0  
**Version:** 2.0  
**Build:** 1  
**Platform Version:** 17.0  
**Min OS Version:** 12.0  
**Supported Platforms:** iPhoneOS,



BINARY INFORMATION

**Arch:** ARM64  
**Sub Arch:** CPU\_SUBTYPE\_ARM64\_ALL  
**Bit:** 64-bit  
**Endian:** <

# #CUSTOM URL SCHEMES

| URL NAME                        | SCHEMES           |
|---------------------------------|-------------------|
| com.hightitudehacks.DVIAswiftv2 | dvia<br>dviaswift |

# ≡ APPLICATION PERMISSIONS

| PERMISSIONS              | STATUS    | INFO                                             | REASON IN MANIFEST                                                    |
|--------------------------|-----------|--------------------------------------------------|-----------------------------------------------------------------------|
| NSCameraUsageDescription | dangerous | Access the Camera.                               | To demonstrate the misuse of Camera, please grant it permission once. |
| NSFaceIDUsageDescription | normal    | Access the ability to authenticate with Face ID. | The app needs FaceID permission                                       |

# 🔒 APP TRANSPORT SECURITY (ATS)

HIGH: 1 | WARNING: 0 | INFO: 0 | SECURE: 0

| NO | ISSUE                                                  | SEVERITY | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----|--------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1  | App Transport Security AllowsArbitraryLoads is allowed | high     | App Transport Security restrictions are disabled for all network connections. Disabling ATS means that unsecured HTTP connections are allowed. HTTPS connections are also allowed, and are still subject to default server trust evaluation. However, extended security checks like requiring a minimum Transport Layer Security (TLS) protocol version—are disabled. This setting is not applicable to domains listed in NSExceptionDomains. |

# </> IPA BINARY CODE ANALYSIS

HIGH: 0 | WARNING: 3 | INFO: 2 | SECURE: 0 | SUPPRESSED: 0

| NO | ISSUE                                               | SEVERITY | STANDARDS                                                                                                                                           | DESCRIPTION                                                                                                             |
|----|-----------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| 1  | Binary makes use of insecure API(s)                 | warning  | <b>CWE:</b> CWE-676: Use of Potentially Dangerous Function<br><b>OWASP Top 10:</b> M7: Client Code Quality<br><b>OWASP MASVS:</b> MSTG-CODE-8       | The binary may contain the following insecure API(s) _fopen , _memcpy , _printf , _scanf , _strcpy , _strlen , _strncpy |
| 2  | Binary makes use of the insecure Random function(s) | warning  | <b>CWE:</b> CWE-330: Use of Insufficiently Random Values<br><b>OWASP Top 10:</b> M5: Insufficient Cryptography<br><b>OWASP MASVS:</b> MSTG-CRYPTO-6 | The binary may use the following insecure Random function(s) _random                                                    |
| 3  | Binary makes use of Logging function                | info     | <b>CWE:</b> CWE-532: Insertion of Sensitive Information into Log File<br><b>OWASP MASVS:</b> MSTG-STORAGE-3                                         | The binary may use _NSLog function for logging.                                                                         |
| 4  | Binary makes use of malloc function                 | warning  | <b>CWE:</b> CWE-789: Uncontrolled Memory Allocation<br><b>OWASP Top 10:</b> M7: Client Code Quality<br><b>OWASP MASVS:</b> MSTG-CODE-8              | The binary may use _malloc function instead of calloc                                                                   |
| 5  | Binary uses WebView Component.                      | info     | <b>OWASP MASVS:</b> MSTG-CODE-9                                                                                                                     | The binary may use UIWebView Component.                                                                                 |

## IPA BINARY ANALYSIS

| PROTECTION   | STATUS | SEVERITY | DESCRIPTION                                                                                                                                                                                                                                     |
|--------------|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NX           | True   | info     | The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.                                                                                                                           |
| PIE          | True   | info     | The binary is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.                                                                      |
| STACK CANARY | True   | info     | This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return. |

| PROTECTION       | STATUS | SEVERITY | DESCRIPTION                                                                                                                                                                                                                                       |
|------------------|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARC              | True   | info     | The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities. |
| RPATH            | True   | warning  | The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.                 |
| CODE SIGNATURE   | True   | info     | This binary has a code signature.                                                                                                                                                                                                                 |
| ENCRYPTED        | False  | warning  | This binary is not encrypted.                                                                                                                                                                                                                     |
| SYMBOLS STRIPPED | False  | warning  | Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.                                               |

## DYNAMIC LIBRARY & FRAMEWORK BINARY ANALYSIS

| NO | DYLIB/Framework | NX | STACK CANARY | ARC | RPATH | CODE SIGNATURE | ENCRYPTED | SYMBOLS STRIPPED |
|----|-----------------|----|--------------|-----|-------|----------------|-----------|------------------|
|----|-----------------|----|--------------|-----|-------|----------------|-----------|------------------|

| NO | DYLIB/Framework                                                | NX                                                                                                                                                                | STACK<br>CANARY                                                                                                                                                                                                                                                                             | ARC                                                                                                                                                                                                                                                                                           | RPATH                                                                                                                                                                                                                                                                            | CODE<br>SIGNATURE                                                             | ENCRYPTED                                                                     | SYMBOLS<br>STRIPPED                                                                                                                                                                                                                                 |
|----|----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1  | Payload/DVIA-v2.app/Frameworks/RealmSwift.framework/RealmSwift | <p>True<br/><a href="#">info</a></p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p> | <p>True<br/><a href="#">info</a></p> <p>The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.</p> | <p>True<br/><a href="#">warning</a></p> <p>The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a code signature.</p> | <p>False<br/><a href="#">warning</a></p> <p>This binary is not encrypted.</p> | <p>False<br/><a href="#">warning</a></p> <p>Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.</p> |

| NO | DYLIB/Framework                                      | NX                                                                                                                                                                | STACK<br>CANARY                                                                                                                                                                                                                                                                             | ARC                                                                                                                                                                                                                                                                                           | RPATH                                                                                                                                                                                                                                                                            | CODE<br>SIGNATURE                                                             | ENCRYPTED                                                                     | SYMBOLS<br>STRIPPED                                                                                                                                                                                                                                 |
|----|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2  | Payload/DVIA-v2.app/Frameworks/Parse.framework/Parse | <p>True<br/><a href="#">info</a></p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p> | <p>True<br/><a href="#">info</a></p> <p>The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.</p> | <p>True<br/><a href="#">warning</a></p> <p>The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a code signature.</p> | <p>False<br/><a href="#">warning</a></p> <p>This binary is not encrypted.</p> | <p>False<br/><a href="#">warning</a></p> <p>Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.</p> |

| NO | DYLIB/Framework                                      | NX                                                                                                                                                                | STACK<br>CANARY                                                                                                                                                                                                                                                                             | ARC                                                                                                                                                                                                                                                                                           | RPATH                                                                                                                                                                                                                                                                            | CODE<br>SIGNATURE                                                             | ENCRYPTED                                                                     | SYMBOLS<br>STRIPPED                                                                                                                                                                                                                                 |
|----|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3  | Payload/DVIA-v2.app/Frameworks/Bolts.framework/Bolts | <p>True<br/><a href="#">info</a></p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p> | <p>True<br/><a href="#">info</a></p> <p>The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.</p> | <p>True<br/><a href="#">warning</a></p> <p>The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a code signature.</p> | <p>False<br/><a href="#">warning</a></p> <p>This binary is not encrypted.</p> | <p>False<br/><a href="#">warning</a></p> <p>Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.</p> |

| NO | DYLIB/Framework                                      | NX                                                                                                                                                                | STACK CANARY                                                                                                                                                                                                                                                                                | ARC                                                                                                                                                                                                                                                                                           | RPATH                                                                                                                                                                                                                                                                            | CODE SIGNATURE                                                                | ENCRYPTED                                                                     | SYMBOLS STRIPPED                                                                                                                                                                                                                                    |
|----|------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4  | Payload/DVIA-v2.app/Frameworks/Realm.framework/Realm | <p>True<br/><a href="#">info</a></p> <p>The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.</p> | <p>True<br/><a href="#">info</a></p> <p>The binary is compiled with Automatic Reference Counting (ARC) flag. ARC is a compiler feature that provides automatic memory management of Objective-C objects and is an exploit mitigation mechanism against memory corruption vulnerabilities.</p> | <p>True<br/><a href="#">warning</a></p> <p>The binary has Runpath Search Path (@rpath) set. In certain cases an attacker can abuse this feature to run arbitrary executable for code execution and privilege escalation. Remove the compiler option -rpath to remove @rpath.</p> | <p>True<br/><a href="#">info</a></p> <p>This binary has a code signature.</p> | <p>False<br/><a href="#">warning</a></p> <p>This binary is not encrypted.</p> | <p>False<br/><a href="#">warning</a></p> <p>Debug Symbols are available. To strip debugging symbols, set Strip Debug Symbols During Copy to YES, Deployment Postprocessing to YES, and Strip Linked Product to YES in project's build settings.</p> |

## </> CODE ANALYSIS

| NO | ISSUE | SEVERITY | STANDARDS | FILES |
|----|-------|----------|-----------|-------|
|----|-------|----------|-----------|-------|

# ! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

|        |                |
|--------|----------------|
| DOMAIN | COUNTRY/REGION |
|--------|----------------|

## DOMAIN MALWARE CHECK

| DOMAIN          | STATUS | GEOLOCATION                                                                                                                                                                               |
|-----------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| goo.gl          | ok     | IP: 142.251.43.142<br>Country: United States of America<br>Region: California<br>City: Mountain View<br>Latitude: 37.405991<br>Longitude: -122.078514<br>View: <a href="#">Google Map</a> |
| www.example.edu | ok     | IP: 104.20.35.130<br>Country: United States of America<br>Region: California<br>City: San Francisco<br>Latitude: 37.775700<br>Longitude: -122.395203<br>View: <a href="#">Google Map</a>  |
| certs.apple.com | ok     | IP: 17.253.18.197<br>Country: Brazil<br>Region: Sao Paulo<br>City: Sao Paulo<br>Latitude: -23.547501<br>Longitude: -46.636108<br>View: <a href="#">Google Map</a>                         |

| DOMAIN                   | STATUS | GEOLOCATION                                                                                                                                                                                |
|--------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| damnvulnerableiosapp.com | ok     | IP: 3.33.251.168<br>Country: United States of America<br>Region: Washington<br>City: Seattle<br>Latitude: 47.627499<br>Longitude: -122.346199<br>View: <a href="#">Google Map</a>          |
| api.parse.com            | ok     | IP: 57.144.210.141<br>Country: United States of America<br>Region: California<br>City: Palo Alto<br>Latitude: 37.441879<br>Longitude: -122.143021<br>View: <a href="#">Google Map</a>      |
| www.thejuniperfund.org   | ok     | IP: 198.185.159.144<br>Country: United States of America<br>Region: New York<br>City: New York City<br>Latitude: 40.734699<br>Longitude: -74.005898<br>View: <a href="#">Google Map</a>    |
| example.com              | ok     | IP: 104.20.23.154<br>Country: United States of America<br>Region: California<br>City: San Francisco<br>Latitude: 37.775700<br>Longitude: -122.395203<br>View: <a href="#">Google Map</a>   |
| www.youtube.com          | ok     | IP: 142.251.222.206<br>Country: United States of America<br>Region: California<br>City: Mountain View<br>Latitude: 37.405991<br>Longitude: -122.078514<br>View: <a href="#">Google Map</a> |

| DOMAIN                   | STATUS | GEOLOCATION                                                                                                                                                                                                                                 |
|--------------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| crl.apple.com            | ok     | <b>IP:</b> 17.253.18.196<br><b>Country:</b> Brazil<br><b>Region:</b> Sao Paulo<br><b>City:</b> Sao Paulo<br><b>Latitude:</b> -23.547501<br><b>Longitude:</b> -46.636108<br><b>View:</b> <a href="#">Google Map</a>                          |
| www.example.net0         | ok     | No Geolocation information available.                                                                                                                                                                                                       |
| ssl.google-analytics.com | ok     | <b>IP:</b> 142.251.221.168<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> Mountain View<br><b>Latitude:</b> 37.405991<br><b>Longitude:</b> -122.078514<br><b>View:</b> <a href="#">Google Map</a> |
| crl3.digicert.com        | ok     | <b>IP:</b> 23.11.39.161<br><b>Country:</b> Thailand<br><b>Region:</b> Krung Thep Maha Nakhon<br><b>City:</b> Bangkok<br><b>Latitude:</b> 13.750000<br><b>Longitude:</b> 100.516670<br><b>View:</b> <a href="#">Google Map</a>               |
| api.login.yahoo.com      | ok     | <b>IP:</b> 106.10.248.157<br><b>Country:</b> Singapore<br><b>Region:</b> Singapore<br><b>City:</b> Singapore<br><b>Latitude:</b> 1.289670<br><b>Longitude:</b> 103.850067<br><b>View:</b> <a href="#">Google Map</a>                        |

| DOMAIN                   | STATUS | GEOLOCATION                                                                                                                                                                                                                                |
|--------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| api.mixpanel.com         | ok     | <b>IP:</b> 35.186.241.51<br><b>Country:</b> United States of America<br><b>Region:</b> Missouri<br><b>City:</b> Kansas City<br><b>Latitude:</b> 39.099731<br><b>Longitude:</b> -94.578568<br><b>View:</b> <a href="#">Google Map</a>       |
| www.google-analytics.com | ok     | <b>IP:</b> 216.239.38.178<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> Mountain View<br><b>Latitude:</b> 37.405991<br><b>Longitude:</b> -122.078514<br><b>View:</b> <a href="#">Google Map</a> |
| www.example.com          | ok     | <b>IP:</b> 172.66.147.243<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> San Francisco<br><b>Latitude:</b> 37.775700<br><b>Longitude:</b> -122.395203<br><b>View:</b> <a href="#">Google Map</a> |
| cacerts.digicert.com     | ok     | <b>IP:</b> 23.11.39.161<br><b>Country:</b> Thailand<br><b>Region:</b> Krung Thep Maha Nakhon<br><b>City:</b> Bangkok<br><b>Latitude:</b> 13.750000<br><b>Longitude:</b> 100.516670<br><b>View:</b> <a href="#">Google Map</a>              |
| data.flurry.com          | ok     | No Geolocation information available.                                                                                                                                                                                                      |

| DOMAIN                | STATUS | GEOLOCATION                                                                                                                                                                                                                                 |
|-----------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| highaltitudehacks.com | ok     | <b>IP:</b> 185.199.109.153<br><b>Country:</b> United States of America<br><b>Region:</b> Pennsylvania<br><b>City:</b> California<br><b>Latitude:</b> 40.065632<br><b>Longitude:</b> -79.891708<br><b>View:</b> <a href="#">Google Map</a>   |
| realm.io              | ok     | <b>IP:</b> 108.158.251.57<br><b>Country:</b> United States of America<br><b>Region:</b> Washington<br><b>City:</b> Redmond<br><b>Latitude:</b> 47.682899<br><b>Longitude:</b> -122.120903<br><b>View:</b> <a href="#">Google Map</a>        |
| www.google.com        | ok     | <b>IP:</b> 142.251.153.119<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> Mountain View<br><b>Latitude:</b> 37.405991<br><b>Longitude:</b> -122.078514<br><b>View:</b> <a href="#">Google Map</a> |
| www.digicert.com      | ok     | <b>IP:</b> 45.60.125.229<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> Redwood City<br><b>Latitude:</b> 37.532440<br><b>Longitude:</b> -122.248833<br><b>View:</b> <a href="#">Google Map</a>    |
| www.example.org       | ok     | <b>IP:</b> 172.66.157.237<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> San Francisco<br><b>Latitude:</b> 37.775700<br><b>Longitude:</b> -122.395203<br><b>View:</b> <a href="#">Google Map</a>  |

| DOMAIN              | STATUS | GEOLOCATION                                                                                                                                                                                                                                 |
|---------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| google.com          | ok     | <b>IP:</b> 142.250.76.174<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> Mountain View<br><b>Latitude:</b> 37.405991<br><b>Longitude:</b> -122.078514<br><b>View:</b> <a href="#">Google Map</a>  |
| ocsp.apple.com      | ok     | <b>IP:</b> 17.253.18.197<br><b>Country:</b> Brazil<br><b>Region:</b> Sao Paulo<br><b>City:</b> Sao Paulo<br><b>Latitude:</b> -23.547501<br><b>Longitude:</b> -46.636108<br><b>View:</b> <a href="#">Google Map</a>                          |
| ocsp.digicert.com0m | ok     | No Geolocation information available.                                                                                                                                                                                                       |
| www.digicert.com1   | ok     | No Geolocation information available.                                                                                                                                                                                                       |
| www.apple.com       | ok     | <b>IP:</b> 23.60.109.28<br><b>Country:</b> Japan<br><b>Region:</b> Tokyo<br><b>City:</b> Tokyo<br><b>Latitude:</b> 35.689507<br><b>Longitude:</b> 139.691696<br><b>View:</b> <a href="#">Google Map</a>                                     |
| twitter.com         | ok     | <b>IP:</b> 162.159.140.229<br><b>Country:</b> United States of America<br><b>Region:</b> California<br><b>City:</b> San Francisco<br><b>Latitude:</b> 37.775700<br><b>Longitude:</b> -122.395203<br><b>View:</b> <a href="#">Google Map</a> |

| DOMAIN           | STATUS | GEOLOCATION                                                                                                                                                                                                                        |
|------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cfg.flurry.com   | ok     | <b>IP:</b> 27.123.42.205<br><b>Country:</b> India<br><b>Region:</b> Maharashtra<br><b>City:</b> Mumbai<br><b>Latitude:</b> 19.014410<br><b>Longitude:</b> 72.847939<br><b>View:</b> <a href="#">Google Map</a>                     |
| github.com       | ok     | <b>IP:</b> 20.207.73.82<br><b>Country:</b> United States of America<br><b>Region:</b> Washington<br><b>City:</b> Redmond<br><b>Latitude:</b> 47.682899<br><b>Longitude:</b> -122.120903<br><b>View:</b> <a href="#">Google Map</a> |
| www.example.org0 | ok     | No Geolocation information available.                                                                                                                                                                                              |

## EMAILS

| EMAIL                                                 | FILE                                                 |
|-------------------------------------------------------|------------------------------------------------------|
| defaultrealm@host.com<br>test123@gmail.com<br>j2@j.rj | DVIA-v2.app/DVIA-v2                                  |
| defaultrealm@host.com<br>test123@gmail.com            | IPA Strings Dump                                     |
| help@realm.io                                         | Payload/DVIA-v2.app/Frameworks/Realm.framework/Realm |

## TRACKERS

| TRACKER          | CATEGORIES               | URL                                                                                                                 |
|------------------|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| Flurry           | Analytics, Advertisement | <a href="https://reports.exodus-privacy.eu.org/trackers/25">https://reports.exodus-privacy.eu.org/trackers/25</a>   |
| Google Analytics | Analytics                | <a href="https://reports.exodus-privacy.eu.org/trackers/48">https://reports.exodus-privacy.eu.org/trackers/48</a>   |
| MixPanel         | Analytics                | <a href="https://reports.exodus-privacy.eu.org/trackers/118">https://reports.exodus-privacy.eu.org/trackers/118</a> |

 SCAN LOGS

| Timestamp           | Event                               | Error |
|---------------------|-------------------------------------|-------|
| 2026-06-24 14:47:43 | iOS Binary (IPA) Analysis Started   | OK    |
| 2026-06-24 14:47:43 | Generating Hashes                   | OK    |
| 2026-06-24 14:47:43 | Extracting IPA                      | OK    |
| 2026-06-24 14:47:43 | Unzipping                           | OK    |
| 2026-06-24 14:47:43 | iOS File Analysis and Normalization | OK    |
| 2026-06-24 14:47:43 | iOS Info.plist Analysis Started     | OK    |
| 2026-06-24 14:47:43 | Finding Info.plist in iOS Binary    | OK    |

|                     |                                                                          |    |
|---------------------|--------------------------------------------------------------------------|----|
| 2026-06-24 14:47:43 | Fetching Details from App Store: com.hightitudehacks.DVIAswiftv2         | OK |
| 2026-06-24 14:47:45 | Searching for secrets in plist files                                     | OK |
| 2026-06-24 14:47:45 | Starting Binary Analysis                                                 | OK |
| 2026-06-24 14:47:45 | Dumping Classes from the binary                                          | OK |
| 2026-06-24 14:47:45 | Running jtool against the binary for dumping classes                     | OK |
| 2026-06-24 14:47:52 | Library Binary Analysis Started                                          | OK |
| 2026-06-24 14:47:52 | Framework Binary Analysis Started                                        | OK |
| 2026-06-24 14:47:52 | Analyzing Payload/DVIA-v2.app/Frameworks/RealmSwift.framework/RealmSwift | OK |
| 2026-06-24 14:47:52 | Analyzing Payload/DVIA-v2.app/Frameworks/Parse.framework/Parse           | OK |
| 2026-06-24 14:47:52 | Analyzing Payload/DVIA-v2.app/Frameworks/Bolts.framework/Bolts           | OK |
| 2026-06-24 14:47:52 | Analyzing Payload/DVIA-v2.app/Frameworks/Realm.framework/Realm           | OK |
| 2026-06-24 14:47:53 | Extracting String Metadata                                               | OK |

|                     |                                               |    |
|---------------------|-----------------------------------------------|----|
| 2026-06-24 14:47:53 | Extracting URL and Email from IPA             | OK |
| 2026-06-24 14:47:57 | Performing Malware check on extracted domains | OK |
| 2026-06-24 14:48:14 | Fetching IPA icon path                        | OK |
| 2026-06-24 14:48:21 | Detecting Trackers from Domains               | OK |
| 2026-06-24 14:48:22 | Saving to Database                            | OK |

---

### Report Generated by - MobSF v4.5.0

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).