**MOTOROLA**
*intelligence everywhere™*

*digital dna™*

**by Peter Topping**
**Applications Engineering**
**Motorola, East Kilbride**

## Introduction

As versatile, low pin-count and low cost variants of the MC68HC(9)08 range of MCUs, the MC68HC908QY1, QY4, QT1 and QT4 have many potential applications. They incorporate easily and quickly programmable FLASH memory for their program code. Their cost is minimised by not adding any byte programmable EEPROM (Electrically Erasable Programmable Read Only Memory) as this functionality can be facilitated using a small portion of the FLASH memory.

There are many types of application which are enhanced by the inclusion of non-volatile data storage. External serial EEPROMs are thus sometimes added to systems using low-cost MCUs with no on-chip EEPROM. If, however, the chip has FLASH memory for its application software then a portion of it can be used to emulate EEPROM thus obviating the additional cost and complexity incurred by an extra chip. Using less than a hundred bytes of code, this application note presents a method of doing this. It allows the FLASH to behave like EEPROM and, at the same time, enhances its endurance in terms of the available number of write cycles.

The FLASH memory in the MC68HC908QY/QT family is organised in pages of 64 bytes. Although individual bytes can be programmed, an erase operation necessarily applies to a whole page. By using different bytes within a page each time a block of data is saved, the number of write cycles can be extended beyond its specification of 10,000. The improvement factor is the number of times the data block fits into a page. A 6-byte data block, for example, would fit in 10 times and thus guarantee 100,000 writes. Only once a page is full, and another data save is required, is the page erased and the cycle started again.

To use the EEPROM emulation code, the data to be saved is put into a RAM buffer of user-defined length. This unit will be referred to as a data "block" and can be any size from 1 byte to a full page (64 bytes) according to the

requirements of the application. Any number of block types consistent with the number of FLASH memory pages available can be used. Each block can be the most appropriate size for its particular data.

The method described here is just one of many different strategies which can be adopted to facilitate non-volatile data storage using FLASH rather than EEPROM. These vary greatly from using the FLASH to "shadow" a block of data held in RAM to setting up a file system which allows different types of tagged data to be saved cumulatively in an arbitrary order. In the latter method the tagging would allow a request for any data type to return its most recent value. Once the FLASH block was full, all the most recent data would be transferred to a second block and the process continued using the two blocks alternately. The method described here provides a combination of versatility and simplicity that is particularly appropriate for the MC68HC08 family and other low-end and mid-range MCU/MPU applications.

## Emulated EPROM interface

EEPROM can be used for data-logging or the storing of equipment status during power-down, node addresses, calibration data, cryptographic keys, radio or television frequencies or channel numbers and for numerous other types of data. For this reason a versatile interface is required. The method adopted here is similar to that presented for the MC68HC908GP32 in Application Note AN2183. This allows a page of FLASH to be used for each data type using the block size most appropriate for that data. **Figure 1** shows a typical example of the use of the write routine presented here. It is assumed that the data to be saved is in RAM starting at address $8C (see below).

```
ldhx    #$F040      ;FLASH page address used for this data
lda     #7          ;data block size
jsr     WrtBlock    ;write the block of data from RAM to FLASH
```

**Figure 1. Example use of the write routine**

The block size can be as small as a single byte and as large as a full page of 64 bytes. However, as the FLASH programming routine attempts to save the data in a different place in the page each time it is called, there is no benefit if the block size is over 32 bytes. This is because there would be room for only a single block in the page which would be erased, and the same FLASH bytes written to, every time data was saved.

Often the different bytes of data will serve different purposes when a particular block is read so the reading routine does not actually read the whole block. Instead it returns the start address of the most recently saved data block in the 16-bit index register (H:X) and the first byte of the data in the accumulator.

**Figure 2** shows the code required. Once the address is available the user can use indexed addressing to access the required bytes. This method has the advantage of not forcing the use of a RAM buffer while still allowing the retrieved data to be used as required for the particular application.

```
    ldhx    #$F040      ;FLASH page for this data
    lda     #7          ;data block size
    jsr     RdBlock     ;get pointer to latest data block (1st byte in A)
```

**Figure 2. Basic use of the read routine**

In a radio, for example, each station could have two bytes of frequency information and eight bytes of ASCII data for the station name. The frequency bytes would need to be latched into a PLL and the station name data sent serially to a display module. There could be a further byte to specify waveband etc., which should be put onto an I/O port. In this type of application, the designer may wish this data to be saved as a single 11-byte data block or split up into 2 or 3 separate blocks. The method presented here allows either strategy.

Sometimes, for example when fetching a cryptographic key, there may be a requirement to transfer some or all of the data block into a contiguous area of RAM. The example code shown below illustrates the use of the read routine to perform this function. It transfers a complete block of data into RAM starting at the address defined by DATA. If DATA is $8C then this code exactly complements the write routine which transfers a block in the other direction. Although the write routine must use $8C, this data reading software could use any available RAM locations.

```
        ldhx    #$F040      ;example FLASH page for data
        lda     #7          ;example data block size
        psha                ;save initial byte count (block size)
        jsr     RdBlock     ;get pointer to latest data block
        txa                 ;get address LS byte
        add     1,sp        ;add block size
        deca                ;and decrement
        tax                 ;H:X now point to last byte in block

again:  pshx
        pshh                ;save H:X
        lda     ,x          ;get a byte of data
        clrh
        ldx     3,sp        ;byte count now in H:X
        sta     DATA-1,x    ;put byte into RAM
        pulh
        pulx                ;retrieve FLASH data pointer
        decx                ;and point to next (previous) byte
        dec     1,sp        ;decrement byte count
        bne     again       ;finished ?

        pula                ;fix stack
```

**Figure 3. Example use of the read routine
to retrieve a complete block of data**

The data saving method presented here necessarily includes some history of the saved data. In some applications this may be of value. The number of old blocks available will of course depend on the current position in the page and there will sometimes be none. If historical data is always required then it is possible to use two pages for the same block of data thus guaranteeing that at least one page of historical data will always be available. This capability is not included in this application note but it could be added to the application software prior to calling the read and write routines. Clearly the most important aspect would be to keep track of which of the two pages holds the most recent data. This approach would also increase further the number of write cycles available for this block of data.

One disadvantage of the simple method presented here is that it necessarily assumes that the block writing process will not be interrupted by a power-fail or any other unexpected event that stops the application. If this occurs during the data saving procedure the page being written to (or erased) may be left in an intermediate state from which valid data is not available. It is up to the system designer to minimise the possibility of this happening and/or facilitate acceptable recovery or default behaviour if the data is corrupted. In this respect, however, the emulated EEPROM is superior to most serial EEPROM implementations due to the much shorter writing time.

## FLASH memory

The FLASH memory used in the MC68HC908 family of devices allows very fast programming. Including software overhead, programming can be carried out at over 10 bytes per millisecond which is a factor of a hundred faster than most EEPROMs. An additional consideration is the page erase time of 4ms but this doesn't occur prior to every write. Careful management in the application software can thus avoid always having to allow for the possibility of this happening prior to saving data if this potential delay is unacceptable.

In the case of the MC68HC908QY/QT devices, a page of FLASH consists of two rows of 32 bytes each for a total of 64 bytes. FLASH memory is programmed a row (or part of a row) at a time but erased in pages. Although some data sheets discourage writing to a particular row more than once without erasing it in between, there is no technical reason why this should not be done. It is also allowable to write to only part of a row at a time, there being in practice no minimum number of bytes which must be programmed each time a row is written to.

The only restriction is that the total write time between erases should not exceed $t_{HV}$ (4ms) per row. This is ensured by the software: each of the 32 bytes is only written once between erases so the maximum time is 32 x 35µs i.e. 1.12ms. In this application the number of bytes in a block is not restricted so

there will sometimes be some unused bytes at the end of the page. Clearly block sizes of 1, 2, 4 etc. (any power of 2) will use all 64 bytes in their page.

The code section of any FLASH based application should always be protected against accidental erasure using, in the case of MC68HC908 MCUs, the FLASH block protection register, FLBPR[1]. As it works by protecting all FLASH above a particular memory address, the area of FLASH used as EEPROM should be at the start (lowest address) of the FLASH memory. This allows it to be enabled for erasure and programming while the program code, starting at a higher address, is fully protected. (see references 1 and 4).

## On-chip ROM routine

Like other small members of the MC68HC908 family, the MC68HC908QY and QT devices have FLASH program/erase software included in on-chip ROM code. This code is used during factory test and burn-in. On larger devices like the GP32 this testing is carried out using code downloaded into RAM but variants with 256 bytes or less of RAM (128 in the case of the MC68HC908QY/QT) cannot do this efficiently because of the limited space.

The code included in the MC68HC908GR, KX, JL/JK and JB devices is described in Application Note AN1831. The code in the MC68HC908QY and QT devices operates in the same way, the only significant difference being the entry addresses for the routines. The ROM routines PrgRnge and EraRnge are used in this application note. Their use requires the equates shown below.

```
EraRnge     equ     $2806       ;FLASH erase routine in internal ROM
PgrRnge     equ     $2809       ;FLASH program routine in internal ROM
```

**Figure 4. Equates required to access the on-chip ROM subroutines**

The read routine in ROM is not used in this application. It can read a whole data block and place it in RAM and is even capable of verifying the contents of FLASH against RAM. Usually neither of these functions will be required in an actual application and the much simpler read routine RdBlock is used here.

The programming routine in ROM, PrgRnge, can program over row boundaries. This greatly simplifies the block search code developed for this

---

1. The FLASH block protection register, FLBPR, is actually a page protection register as it can be specified to protect the FLASH in increments of a page. In this application note, the word "block" refers to the user-defined data block that can be any size from 1 byte to a full page of 64 bytes.

application note as there is no requirement to take the row boundary into account. The whole page is thus available to hold as many blocks as possible.

The programming routine uses RAM location CPUSpd ($89) to determine the bus speed, LstAddr ($8A and $8B) to save the end address in FLASH and a data buffer starting at BfrStrt ($8C). The data buffer is the length of a data block. Before writing a block it is thus necessary to put the data to be stored into RAM locations from BfrStrt to BfrStrt +blocksize-1 and to leave the 4 locations from $88 to $8B available for use by the ROM routines. The first FLASH address is held in the index register and thus does not require to be stored in RAM. The erase routine in ROM, EraRnge, uses CtrlByt ($88) for control information.

The use of the 4 bytes is shown in **Figure 5** and described in more detail in Application Note AN1831. It is important that CtrlByt and CPUSpd are initialised correctly. CtrlByt allows the on-chip erase routine to distinguish between a page erase and a mass erase (not used in this application). CPUSpd tells the erase and programming routines what the bus speed is so that the program and erase delays can be calculated correctly. Correct timing assumes that there are no interrupts during erasing or programming and they are automatically disabled during the execution of the ROM subroutines. The application code should re-enable interrupts if required.

| Location | RAM address | Bytes | Use |
|----------|-------------|-------|-----|
| CtrlByt | $88 | 1 | Control bits |
| CPUSpd | $89 | 1 | Bus speed in units of 0.25MHz |
| LstAddr | $8A – $8B | 2 | FLASH block end address |
| BfrStrt | $8C => | block size | Data buffer |

**Figure 5. RAM locations used by the on-chip ROM subroutines**

The software subroutines in ROM handle the 4 RAM locations and no intervention is required except to change the data written to CPUSpd in the "WrtBlock" routine. This is shown as 13 (decimal) assuming that the internal clock is being used to obtain a 3.2 MHz bus speed. It should be changed if required to the value of the actual bus speed being used. The number should be the bus speed in units of 0.25MHz.

The data buffer at BfrStrt is the size of a data block. As multiple data block sizes are possible, the simplest way to organise an application's RAM would be to allocate a data buffer the same length as the largest block used. This is however not strictly necessary as only the RAM used for a particular block is

required and any unused RAM can be utilised for other purposes. Indeed all of the RAM used by the EEPROM emulation code can serve other purposes when it is not actually required for saving data to non-volatile memory. Clearly care would be required, perhaps by permanently allocating the required RAM, if saving data could be initiated by an interrupt.

## Software

The key to this type of use of FLASH is knowing where the latest block of data is situated within its page. This is required so that the latest block can be read and so that, if new data has to be written, it is put into the next available block-sized space in the page. If there is no room then the whole page is erased and the data is written at the start of the page. The current location could be held in RAM but would need to be remembered for each data type. Even more troublesome would be the requirement to provide non-volatile storage of this information so the strategy adopted here avoids the need to remember the current position.

Instead, every time a read or write is requested, the page is scanned to find the location of the latest data or the first available erased block. This has the disadvantage that the signature used to signify an unused block ($FF in the first byte) has to be forbidden as valid data and it is up to the main application software to ensure that this doesn't occur. Clearly this signature could be made less restrictive by modifying the code to require that more bytes (perhaps the complete block) have to be erased ($FF) to signify an unused block. Alternatively, a dummy byte could be added at the start of the data block thus avoiding any restrictions on the data.

The search is performed by the subroutine "FindClear" which is used by both the read and write procedures to determine the status of the data in the page. The subroutine requires that the block size is pushed onto the stack before it is called. It subtracts this size from the page size to obtain the bytes remaining after the first block and then reads the first byte of the first block. If it is $FF, the subroutine exits with $FF in the accumulator to indicate that an erased block was found. The first block will in fact only be erased if data has never been stored to this page so this is a special case.

Usually the first read will not be $FF and the subroutine uses the number of bytes remaining after the first block to check if there is room for another. If not then the subroutine exits with the accumulator clear to indicate that no erased block is available. If there is room, the code checks the first byte of the next block for the signature of $FF. This process is repeated until the location of the first erased block (if there is one) is found. On exit from "FindClear", the index register contains the address of the next available block unless their isn't one in which case it points to the last complete block.

**Figure 6. FindClear flow diagram**

The Write routine "WrtBlock" initialises the RAM locations CtrlByt and CPUSpd and pushes the block size onto the stack before calling "FindClear". It then checks the accumulator and, if it is $FF, goes ahead and writes the data block using the address left in the 16-bit index register (H:X) by "FindClear". If it isn't $FF, there is no room for another block and the page is erased and the address initialised to the start of the page. The data can then be written. This involves saving in RAM (at LstAddr) the address of the last byte to be written before calling the programming subroutine.



**Figure 7. WrtBlock flow diagram**

The read routine also uses "FindClear" to determine the status of the page but, as the address of the first erased block is returned, it has to go back a block to access the data. There are two exceptional cases when going back a block is not appropriate. If the page is full and no erased block is found, "FindClear" returns the address of the last complete block of data so the address is already correct for reading. Also, in the situation where there is no saved data, "FindClear" will return the address of the first block in the page. If this happens, going back a block would go into the previous page. The address is therefore not modified and the data, including the first byte returned in the accumulator, will be $FF.

**Figure 8. RdBlock flow diagram**

**References**

1. MC68HC908QY4/D, technical data sheet

2. Application Note AN1831, "Using MC68HC908 On-chip FLASH Programming Routines"

3. Application Note AN2183, "Using FLASH as EEPROM on the MC68HC908GP32"

4. Engineering Bulletin EB398, "Techniques to Protect MCU Applications Against Malfunction due to Code Run-away"

## Software listing

```
  1
  2   ;**********************************************************************
  3   ;*                                                                    *
  4   ;*        EEPROM Emulation using FLASH in MC68HC908QT/QY MCUs         *
  5   ;*                                                                    *
  6   ;*  QTEEApp.asm                            Copyright (c) Motorola 2002 *
  7   ;*                                                                    *
  8   ;**********************************************************************
  9   ;*                                                                    *
 10   ;*  Description: Read and Write subroutines which facilitate the      *
 11   ;*  saving and retrieval of blocks of data of user-defined size       *
 12   ;*  in non-volatile FLASH memory in such a way that the write-erase    *
 13   ;*  cycling capability of the FLASH is extended up to 64 times its     *
 14   ;*  specification of 10,000 cycles.                                    *
 15   ;*                                                                    *
 16   ;*  Include files: none                                               *
 17   ;*                                                                    *
 18   ;*  Documentation: MC68HC908QY4/D Technical Data Sheet.               *
 19   ;*  Application Note AN2346 - "EEPROM Emulation using FLASH in         *
 20   ;*  MC68HC908QT/QY MCUs".                                             *
 21   ;*                                                                    *
 22   ;*  This software is classified as Engineering Sample Software.       *
 23   ;*                                                                    *
 24   ;**********************************************************************
 25   ;*                                                                    *
 26   ;* Author:       Peter Topping - TSPG Applications - East Kilbride    *
 27   ;*                                                                    *
 28   ;* Update History:                                                    *
 29   ;*                                                                    *
 30   ;* Rev     Date       Author  Description of Change                   *
 31   ;* ------  ---------  ------  ------------------------------------ *
 32   ;* ES 0.1  22-Aug-02  PT      Initial release                        *
 33   ;*                                                                    *
 34   ;*                                                                    *
 35   ;*                                                                    *
 36   ;*                                                                    *
 37   ;**********************************************************************
 38   ;*                                                                    *
 39   ;* Motorola reserves the right to make changes without further notice*
 40   ;* to any product herein to improve reliability, function, or design.*
 41   ;* Motorola does not assume any liability arising out of the          *
 42   ;* application or use of any product, circuit, or software described *
 43   ;* herein; neither does it convey any license under its patent rights*
 44   ;* nor the rights of others.  Motorola products are not designed,     *
 45   ;* intended, or authorized for use as components in systems intended *
 46   ;* for surgical implant into the body, or other applications intended*
 47   ;* to support life, or for any other application in which the failure*
 48   ;* of the Motorola product could create a situation where personal   *
 49   ;* injury or death may occur.  Should Buyer purchase or use Motorola *
 50   ;* products for any such intended or unauthorized application, Buyer *
 51   ;* shall indemnify and hold Motorola and its officers, employees,    *
 52   ;* subsidiaries, affiliates, and distributors harmless against all   *
 53   ;* claims, costs, damages, and expenses, and reasonable attorney     *
 54   ;* fees arising out of, directly or indirectly, any claim of personal*
 55   ;* injury or death associated with such unintended or unauthorized   *
 56   ;* use, even if such claim alleges that Motorola was negligent       *
 57   ;* regarding the design or manufacture of the part.                  *
 58   ;*                                                                    *
 59   ;* Motorola is a registered trademark of Motorola, Inc.              *
 60   ;*                                                                    *
 61   ;**********************************************************************
 62
 63   ;*  Equates for ROM Subroutines and start of RAM
 64
 65   EraRnge     equ     $2806           ;FLASH erase routine in ROM
 66   PgrRnge     equ     $2809           ;FLASH programming routine in ROM
 67   CtrlByt     equ     $88             ;control byte for ROM subroutines
 68   CPUSpd      equ     $89             ;CPU speed in units of 0.25MHz
 69   LstAddr     equ     $8A             ;last FLASH address to be programmed
 70
 71
 72               org     $FC00
 73
 74
```

The address column values on the left:
```
0000    65
0000    66
0000    67
0000    68
0000    69

FC00    72
```

```
                 75
                 76  ;********************************************************************
                 77  ;*                                                                  *
                 78  ;*  RdBlock - Reads a block of data from FLASH and puts it in RAM   *
                 79  ;*                                                                  *
                 80  ;*  Calling convention:    ldhx   #Blk1page                        *
                 81  ;*                         lda    #Blk1Size                        *
                 82  ;*                         jsr    RdBlock                          *
                 83  ;*                                                                  *
                 84  ;*  Inputs:  H:X - pointing to start of FLASH page used for data    *
                 85  ;*          A   - block size                                       *
                 86  ;*                                                                  *
                 87  ;*  Returns: H:X - pointing to start of FLASH block containing data *
                 88  ;*          A   - data from first byte of block                    *
                 89  ;*                                                                  *
                 90  ;*  Uses:   FindClear                                              *
                 91  ;*                                                                  *
                 92  ;********************************************************************
                 93
FC00 [02] 87     94  RdBlock:    psha                ;save block size
FC01 [04] AD32   95              bsr    FindClear    ;find first erased block
                 96
FC03 [02] A1FF   97              cmp    #$FF         ;was an erased block found ?
FC05 [03] 260A   98              bne    skipdec      ;if not then don't go back a block
FC07 [01] 9F     99              txa                 ;get LS byte of address
FC08 [02] A43F  100              and    #$3F         ;only look at address within page
FC0A [03] 2705  101              beq    skipdec      ;if 0 then no data so don't go back
FC0C [01] 9F    102              txa                 ;if not get LS byte of address again
FC0D [04] 9EE001 103             sub    1,sp         ;and subtract block size to point
FC10 [01] 97    104              tax                 ;to start of valid data block
                105
FC11 [02] F6    106  skipdec:    lda    ,x           ;get first byte of data
FC12 [02] A701  107              ais    #1           ;de-allocate stack
FC14 [04] 81    108              rts
                109
                110
                111  ;********************************************************************
                112  ;*                                                                  *
                113  ;*  WrtBlock - Writes a block of data into FLASH from RAM buffer     *
                114  ;*                                                                  *
                115  ;*  Calling convention:    ldhx   #Blk1page                        *
                116  ;*                         lda    #Blk1Size                        *
                117  ;*                         jsr    WrtBlock                         *
                118  ;*                                                                  *
                119  ;*  Inputs:  H:X - pointing to start of FLASH page used for data    *
                120  ;*          A   - block size                                       *
                121  ;*                                                                  *
                122  ;*  Returns: nothing                                               *
                123  ;*                                                                  *
                124  ;*  Uses:   FindClear, EraRnge (ROM), PgrRnge (ROM)                *
                125  ;*                                                                  *
                126  ;********************************************************************
                127
FC15 [04] 6E0D89 128  WrtBlock:   mov    #13,CPUSpd   ;3.2MHz/0.25MHz = 13
FC18 [03] 3F88  129              clr    CtrlByt      ;page (not mass) erase
FC1A [02] 87    130              psha                ;save block size
FC1B [04] AD18  131              bsr    FindClear    ;find first available erased block
FC1D [02] A1FF  132              cmp    #$FF         ;erased block found ?
FC1F [03] 2707  133              beq    blkfnd       ;if so write to it
FC21 [05] CD2806 134             jsr    EraRnge      ;if not then erase page
FC24 [01] 9F    135              txa                 ;get LS byte of FLASH address
FC25 [02] A4C0  136              and    #$C0         ;and reset it to start of page
FC27 [01] 97    137              tax                 ;H:X now pointing to first block
                138
FC28 [02] 86    139  blkfnd:     pula                ;get block size
FC29 [02] 89    140              pshx                ;save start address LS byte
FC2A [04] 9EEB01 141             add    1,sp         ;add block size to LS byte
FC2D [01] 4A    142              deca                ;back to last address in block
FC2E [01] 97    143              tax                 ;last address now in H:X
FC2F [04] 358A  144              sthx   LstAddr      ;save in RAM for use by ROM routine
FC31 [02] 88    145              pulx                ;restore X (H hasn't changed)
FC32 [03] CC2809 146             jmp    PgrRnge      ;program block (includes RTS)
                147
                148
```

```
                         149  ;************************************************************************
                         150  ;*                                                                     *
                         151  ;*  FindClear - Finds first erased block within page                   *
                         152  ;*                                                                     *
                         153  ;*  Inputs:  H:X - pointing to start of page used for required data   *
                         154  ;*           Stack - block size last thing on stack                    *
                         155  ;*                                                                     *
                         156  ;*  Returns if erased block found:                                     *
                         157  ;*           H:X - pointing to start of first erased block in page     *
                         158  ;*           A   - $FF                                                 *
                         159  ;*  Returns if no erased block found (page full):                      *
                         160  ;*           H:X - pointing to start of last written block             *
                         161  ;*           A   - $00                                                 *
                         162  ;*                                                                     *
                         163  ;************************************************************************
                         164
FC35 [02] A640           165  FindClear:  lda   #$40         ;number of bytes in a page
FC37 [04] 9EE003         166              sub   3,sp         ;less number in first block
FC3A [02] 87             167              psha               ;save bytes left
                         168
FC3B [02] F6             169  floop:      lda   ,x           ;get first data byte in block
FC3C [02] A1FF           170              cmp   #$FF         ;erased byte ?
FC3E [03] 270F           171              beq   finish1      ;if so then exit, otherwise try next
                         172
FC40 [02] 86             173              pula               ;bytes left
FC41 [04] 9EE003         174              sub   3,sp         ;less number in next block
FC44 [02] 87             175              psha               ;resave bytes left
FC45 [03] 2B07           176              bmi   finish2      ;enough for another block ?
                         177
FC47 [01] 9F             178              txa                ;yes, get LS byte of address
FC48 [04] 9EEB04         179              add   4,sp         ;add block size
FC4B [01] 97             180              tax                ;put it back (can't be a carry)
FC4C [03] 20ED           181              bra   floop        ;and try again
                         182
FC4E [01] 4F             183  finish2:    clra               ;no room (A shouldn't be $FF)
FC4F [02] A701           184  finish1:    ais   #1           ;fix stack pointer
FC51 [04] 81             185              rts
                         186
                         187
                         188
```

```
 Symbol Table

BLKFND          FC28
CPUSPD          0089
CTRLBYT         0088
ERARNGE         2806
FINDCLEAR       FC35
FINISH1         FC4F
FINISH2         FC4E
FLOOP           FC3B
LSTADDR         008A
PGRRNGE         2809
RDBLOCK         FC00
SKIPDEC         FC11
WRTBLOCK        FC15
```

# Appendix

The code shown in the listing in this appendix is an alternative to that shown in the previous section. It uses a different WrtBlock routine that does not use the erase routine, EraRnge, which is included in the on-chip ROM.

This alternative code is appropriate for use with early mask sets of the MC68HC908QY/QT (1L69J, 2L69J and 3L69J) which have the FLASH control logic error described in errata 68HC908QY/QTMSE3.

There are two blocks of FLASH memory in the M68HC908QY/QT MCU which are selected internally by array select signals. Address values are protected against changes after a page erase sequence has started. Any attempt to write a new address after HVEN=1 is blocked. However, due to a logic error in these mask sets, the latching of the array select signals is not blocked so it is possible that one page in one array could be unintentionally erased when a page erase is performed on a page in the other array.

EraRnge refreshes the COP by periodically writing to address $FFFF. This is in the top FLASH array so a write to this location while erasing (using EraRnge) a FLASH page in the bottom array ($EE00-$FDFF) can result in the erroneous erasure of a page in the top array. This occurs regardless of the protection status of the page in the top array.

To avoid this problem it is thus necessary, on the mask sets with this problem, to avoid using the on-chip erase routine. The alternative code shown below replaces this routine with one downloaded into RAM.

Although functionally equivalent, the replacement software uses half of the available RAM (from $C0 to $FF) and is thus intended only as an interim solution until silicon without the logic fault is available.

## Alternative software listing

```
                        1  ;*********************************************************************
                        2  ;*                                                                  *
                        3  ;*        EEPROM Emulation using FLASH in MC68HC908QT/QY MCUs        *
                        4  ;*                                                                  *
                        5  ;*  This listing includes an alternative Write subroutine to the    *
                        6  ;*  one presented in Application Note AN2346. It avoids using the    *
                        7  ;*  908QT/QY erase routine in ROM and thus the additional page erase *
                        8  ;*  described in Errata 68HC908QY/QTMSE3. It downloads code into     *
                        9  ;*  RAM and uses all of the top half of the RAM (from $C0 to $FF).   *
                       10  ;*                                                                  *
                       11  ;*  The main subroutine "WrtBlock" is the same as in the Application *
                       12  ;*  Note code except that it calls "EEEPage" instead of the ROM      *
                       13  ;*  subroutine "EraRnge". As long as this change is made to          *
                       14  ;*  WrtBlock, the only aditional code required is "EEEPage" and      *
                       15  ;*  "EEEinRAM". The FLASH reading routine "RdBlock" and the          *
                       16  ;*  subroutine "FindClear" are identical to those in the Application *
                       17  ;*  Note.                                                            *
                       18  ;*                                                                  *
                       19  ;*  Peter Topping                                  18th July 2002   *
                       20  ;*                                                                  *
                       21  ;*********************************************************************
                       22
0000                   23  PgrRnge     equ    $2809          ;FLASH programming routine in ROM
0000                   24  CtrlByt     equ    $88            ;control byte for ROM subroutines
0000                   25  CPUSpd      equ    $89            ;CPU speed in units of 0.25MHz
0000                   26  LstAddr     equ    $8A            ;last FLASH address to be programmed
                       27
                       28  ;*  Additional equates
0000                   29  ERASE       equ    %00000010      ;erase bit in FLCR
0000                   30  HVEN        equ    %00001000      ;high voltage bit in FLCR
0000                   31  ERAHVEN     equ    %00001010      ;erase and high voltage bits in FLCR
0000                   32  FLBPR       equ    $FFBE          ;flash block protect reg (flash)
0000                   33  FLCR        equ    $FE08          ;FLASH control register
                       34
FD00                   35              org    $FD00
                       36
                       37  ;*********************************************************************
                       38  ;*                                                                  *
                       39  ;*  RdBlock - Reads a block of data from FLASH and puts it in RAM    *
                       40  ;*                                                                  *
                       41  ;*  Calling convention:    ldhx   #Blk1page                         *
                       42  ;*                         lda    #Blk1Size                         *
                       43  ;*                         jsr    RdBlock                           *
                       44  ;*                                                                  *
                       45  ;*  Inputs:  H:X - pointing to start of FLASH page used for data    *
                       46  ;*          A   - block size                                        *
                       47  ;*                                                                  *
                       48  ;*  Returns: H:X - pointing to start of FLASH block containing data *
                       49  ;*          A   - data from first byte of block                     *
                       50  ;*                                                                  *
                       51  ;*  Uses:   FindClear                                               *
                       52  ;*                                                                  *
                       53  ;*********************************************************************
                       54
FD00 [02] 87           55  RdBlock:    psha                  ;save block size
FD01 [04] AD32         56              bsr    FindClear      ;find first erased block
FD03 [02] A1FF         57              cmp    #$FF           ;was an erased block found ?
FD05 [03] 260A         58              bne    skipdec        ;if not then don't go back a block
FD07 [01] 9F           59              txa                   ;get LS byte of address
FD08 [02] A43F         60              and    #$3F           ;only look at address within page
FD0A [03] 2705         61              beq    skipdec        ;if 0 then no data so don't go back
FD0C [01] 9F           62              txa                   ;if not get LS byte of address again
FD0D [04] 9EE001       63              sub    1,sp           ;and subtract block size to point
FD10 [01] 97           64              tax                   ;to start of valid data block
                       65
FD11 [02] F6           66  skipdec:    lda    ,x             ;get first byte of data
FD12 [02] A701         67              ais    #1             ;de-allocate stack
FD14 [04] 81           68              rts
                       69
                       70
                       71
                       72
                       73
                       74
```

```
                 75  ;*********************************************************************
                 76  ;*                                                                  *
                 77  ;*  WrtBlock - Writes a block of data into FLASH from RAM buffer    *
                 78  ;*                                                                  *
                 79  ;*  Calling convention:     ldhx   #Blk1page                       *
                 80  ;*                          lda    #Blk1Size                       *
                 81  ;*                          jsr    WrtBlock                        *
                 82  ;*                                                                  *
                 83  ;*  Inputs: H:X - pointing to start of FLASH page used for data    *
                 84  ;*          A   - block size                                       *
                 85  ;*                                                                  *
                 86  ;*  Returns: nothing                                               *
                 87  ;*                                                                  *
                 88  ;*  Uses:   FindClear, EEEPage, EEEinRAM (RAM), PgrRnge (ROM)      *
                 89  ;*                                                                  *
                 90  ;*********************************************************************
                 91
FD15 [04] 6E0D89 92  WrtBlock:   mov    #13,CPUSpd   ;3.2MHz/0.25MHz = 13
FD18 [03] 3F88   93              clr    CtrlByt      ;page (not mass) erase
FD1A [02] 87     94              psha                ;save block size
FD1B [04] AD18   95              bsr    FindClear    ;find first available erased block
FD1D [02] A1FF   96              cmp    #$FF         ;erased block found ?
FD1F [03] 2707   97              beq    blkfnd       ;if so write to it
FD21 [05] CDFD52 98              jsr    EEEPage      ;if not then erase page
FD24 [01] 9F     99              txa                 ;get LS byte of FLASH address
FD25 [02] A4C0   100             and    #$C0         ;and reset it to start of page
FD27 [01] 97     101             tax                 ;H:X now pointing to first block
                 102
FD28 [02] 86     103 blkfnd:     pula                ;get block size
FD29 [02] 89     104             pshx                ;save start address LS byte
FD2A [04] 9EEB01 105             add    1,sp         ;add block size to LS byte
FD2D [01] 4A     106             deca                ;back to last address in block
FD2E [01] 97     107             tax                 ;last address now in H:X
FD2F [04] 358A   108             sthx   LstAddr      ;save in RAM for use by ROM routine
FD31 [02] 88     109             pulx                ;restore X (H hasn't changed)
FD32 [03] CC2809 110             jmp    PgrRnge      ;program block (includes RTS)
                 111
                 112 ;*********************************************************************
                 113 ;*                                                                  *
                 114 ;*  FindClear - Finds first erased block within page                *
                 115 ;*                                                                  *
                 116 ;*  Inputs: H:X - pointing to start of page used for required data  *
                 117 ;*          block size last thing on stack                          *
                 118 ;*                                                                  *
                 119 ;*  Returns if erased block found:                                 *
                 120 ;*          H:X - pointing to start of first erased block in page   *
                 121 ;*          A   - $FF                                               *
                 122 ;*  Returns if no erased block found (page full):                  *
                 123 ;*          H:X - pointing to start of last written block           *
                 124 ;*          A   - $00                                              *
                 125 ;*                                                                  *
                 126 ;*********************************************************************
                 127
FD35 [02] A640   128 FindClear:  lda    #$40         ;number of bytes in a page
FD37 [04] 9EE003 129             sub    3,sp         ;less number in first block
FD3A [02] 87     130             psha                ;save bytes left
                 131
FD3B [02] F6     132 floop:      lda    ,x           ;get first data byte in block
FD3C [02] A1FF   133             cmp    #$FF         ;erased byte ?
FD3E [03] 270F   134             beq    finish1      ;if so then exit, otherwise try next
                 135
FD40 [02] 86     136             pula                ;bytes left
FD41 [04] 9EE003 137             sub    3,sp         ;less number in next block
FD44 [02] 87     138             psha                ;resave bytes left
FD45 [03] 2B07   139             bmi    finish2      ;enough for another block ?
                 140
FD47 [01] 9F     141             txa                 ;yes, get LS byte of address
FD48 [04] 9EEB04 142             add    4,sp         ;add block size
FD4B [01] 97     143             tax                 ;put it back (can't be a carry)
FD4C [03] 20ED   144             bra    floop        ;and try again
                 145
FD4E [01] 4F     146 finish2:    clra                ;no room but A can't be $FF
FD4F [02] A701   147 finish1:    ais    #1           ;fix stack pointer
FD51 [04] 81     148             rts
```

```
          149
          150   ;************************************************************************
          151   ;*                                                                      *
          152   ;*  EEEPage - Erases a page of emulated EEPROM FLASH                    *
          153   ;*                                                                      *
          154   ;*  Calling convention:     ldhx   #EEPage                             *
          155   ;*                          jsr    EEEpage                             *
          156   ;*                                                                      *
          157   ;*  Inputs:  H:X - pointing into FLASH page to be erased               *
          158   ;*                                                                      *
          159   ;*  Returns: H:X - unchanged                                           *
          160   ;*                                                                      *
          161   ;************************************************************************
          162
FD52 [02] 89    163   EEEPage:     pshx                   ;save FLASH address in RAM for
FD53 [02] 8B    164                pshh                   ;retrieval from within RAM routine
FD54 [03] 450034 165                ldhx   #RAMsize       ;get size of RAM resident routine
FD57 [04] D6FD66 166   loadloop:    lda    EEEinRAM-1,x   ;get a byte of code
FD5A [02] 87    167                psha                   ;and put it into RAM
FD5B [03] 5BFA  168                dbnzx  loadloop        ;finished ?
FD5D [01] 85    169                tpa                    ;get CCR
FD5E [02] 9B    170                sei                    ;disable interrupts
FD5F [02] 95    171                tsx                    ;pointer to RAM routine
FD60 [04] FD    172                jsr    ,x             ;execute RAM routine
FD61 [02] A734  173                ais    #RAMsize        ;de-allocate stack space
FD63 [02] 8A    174                pulh                   ;restore FLASH address
FD64 [02] 88    175                pulx
FD65 [02] 84    176                tap                    ;restore CCR
FD66 [04] 81    177                rts
                178
                179   ;************************************************************************
                180   ;*                                                                      *
                181   ;*  EEEinRAM - RAM resident part of EEEPage                            *
                182   ;*                                                                      *
                183   ;*  Calling convention:     ldhx   #{pointer to routine}               *
                184   ;*                          jsr    ,x                                  *
                185   ;*                                                                      *
                186   ;*  Delays calculated to give the required times assuming the bus       *
                187   ;*  clock is 3.2MHz + 25% ie 4.0MHz.                                    *
                188   ;*                                                                      *
                189   ;************************************************************************
                190
FD67 [02] 87    191   EEEinRAM:    psha                   ;save CCR
FD68 [04] D60034 192                lda    (RAMsize),x    ;retrieve FLASH address MSB from RAM
FD6B [04] DE0035 193                ldx    (RAMsize+1),x  ;and LS byte
FD6E [02] 87    194                psha
FD6F [02] 8A    195                pulh                   ;MSB into h (address is now in H:X)
FD70 [02] A602  196                lda    #ERASE
FD72 [04] C7FE08 197                sta    FLCR           ;set ERASE bit in control register
FD75 [04] C6FFBE 198                lda    FLBPR          ;read block protection register
FD78 [02] F7    199                sta    ,x             ;write to an address within page
FD79 [02] A60E  200                lda    #14            ;3 cycle loop so 14 times for delay
FD7B [03] 4BFE  201                dbnza  *              ;of 10us at 4 MHz (14*3/4MHz=10.5us)
                202
FD7D [02] A60A  203                lda    #ERAHVEN        ;ERASE and HVEN bit
FD7F [04] C7FE08 204                sta    FLCR           ;set HVEN bit in control register
FD82 [02] AE28  205                ldx    #40            ;40 times
FD84 [02] A686  206   tloop:       lda    #134           ;100us delay
FD86 [03] 4BFE  207                dbnza  *              ;for 4ms of HVEN high
FD88 [03] 5BFA  208                dbnzx  tloop          ;40*(5+134*3)/4MHz=4070us
                209
FD8A [02] A608  210                lda    #HVEN
FD8C [04] C7FE08 211                sta    FLCR           ;clear ERASE bit
FD8F [02] A607  212                lda    #7             ;3 cycle loop so 7 times for delay
FD91 [03] 4BFE  213                dbnza  *              ;of 10us at 4 MHz (7*3/4MHz=5.2us)
                214
FD93 [01] 4F    215                clra
FD94 [04] C7FE08 216                sta    FLCR           ;clear HVEN bit
FD97 [02] 86    217                pula                   ;restore CCR (2 cycles)
FD98 [03] 21FE  218                brn    *              ;3 more cycles ie >1us
FD9A [04] 81    219                rts
                220
FD9B            221   RAMsize      equ    (*-EEEinRAM)
                222
```

```
 Symbol Table

BLKFND          FD28
CPUSPD          0089
CTRLBYT         0088
EEEINRAM        FD67
EEEPAGE         FD52
ERAHVEN         000A
ERASE           0002
FINDCLEAR       FD35
FINISH1         FD4F
FINISH2         FD4E
FLBPR           FFBE
FLCR            FE08
FLOOP           FD3B
HVEN            0008
LOADLOOP        FD57
LSTADDR         008A
PGRRNGE         2809
RAMSIZE         0034
RDBLOCK         FD00
SKIPDEC         FD11
TLOOP           FD84
WRTBLOCK        FD15
```

**HOW TO REACH US:**

**USA/EUROPE/LOCATIONS NOT LISTED:**

Motorola Literature Distribution;
P.O. Box 5405, Denver, Colorado 80217
1-303-675-2140 or 1-800-441-2447

**JAPAN:**

Motorola Japan Ltd.; SPS, Technical Information Center,
3-20-1, Minami-Azabu Minato-ku, Tokyo 106-8573 Japan
81-3-3440-3569

**ASIA/PACIFIC:**

Motorola Semiconductors H.K. Ltd.;
Silicon Harbour Centre, 2 Dai King Street,
Tai Po Industrial Estate, Tai Po, N.T., Hong Kong
852-26668334

**TECHNICAL INFORMATION CENTER:**

1-800-521-6274

HOME PAGE:

http://www.motorola.com/semiconductors

**MOTOROLA**