

VALIDATING THE OBJECT CALISTHENICS

Evaluation and Prototypical Implementation of Tool Support

Student Research Paper

for the certification examinations for the
Bachelor of Science

Degree Course Applied Computer Science

Baden-Wuerttemberg Cooperative State University Karlsruhe

by

Fabian Schwarz-Fritz

Publication date:	January 21, 2014
Time required for processing:	12 Weeks
Matriculation number:	212024979
Course:	TINF11B2
Vocational training company:	SAP AG, Walldorf
Reviewer:	Daniel Lindner
Reviewer's company:	Softwareschneiderei GmbH, Karlsruhe

unzulässig und strafbar. Das gilt insbesondere für Vervielfältigungen, Übersetzungen, Mikroverfilmungen sowie die Einspeicherung und Verarbeitung in elektronischen Systemen.

© 2014

Eidesstattliche Erklärung

Unless otherwise indicated in the text or references, or acknowledged above, this thesis

Validating the Object Calisthenics - Evaluation and Prototypical Implementation of Tool Support

is entirely the product of my own scholarly work. This thesis has not been submitted either in whole or part, for a degree at this or any other university or institution. This is to certify that the printed version is equivalent to the submitted electronic one.

Karlsruhe, den January 21, 2014

FABIAN SCHWARZ-FRITZ

Sperrvermerk - TODO ??? INFORMIEREN. Gehört das der SAP AG

Die Ergebnisse der Arbeit stehen ausschließlich dem auf dem Deckblatt aufgeführten Ausbildungsbetrieb zur Verfügung.

Abstract

Hier bitte den Abstract Ihrer Arbeit eintragen. Der Abstract sollte nicht länger als eine halbe Seite sein. Bitte klären Sie mit Ihrem Studiengangsleiter ab, ob der Abstract in englischer oder deutscher Sprache (oder möglicherweise sogar in beiden Sprachen) verfasst werden soll.

Contents

Eidesstattliche Erklärung	I
Abbreviations	V
List of Figures	VI
List of Tables	VII
1 Introduction	1
1.1 Exercising Better Object Oriented Programming Skills: a Concept by Jeff Bay	2
1.2 Tool Support to Validate the Object Calisthenics	3
2 Object Calisthenics by Jeff Bay - Patterns and Principals	4
2.1 Problems of procedural code	4
2.1.1 Problems of procedural code	4
2.2 Advantages of object orientation	7
2.2.1 Cohesion	8
2.2.2 coupling	9
2.2.3 duplication	9
2.2.4 encapsulation	9
2.2.5 testability	10
2.2.6 readablitiy	10
2.2.7 focus	11
2.3 The Rules and their Background	11
2.3.1 Rule 1: "Use One Level of Indentation per Method"	12
2.3.2 Rule 2: "Don't Use the else Keyword"	16
2.3.3 Rule 3: "Wrap All Primitives and Strings"	17
2.3.4 Rule 4: "Use Only One Dot per Line"	17
2.3.5 Rule 5: "Don't Abbreviate"	17
2.3.6 Rule 6: "Keep All Entities Small"	17
2.3.7 Rule 7: "Don't Use Any Classes with More Than Two Instance Variables"	17
2.3.8 Rule 8: "Use First-Class Collections"	17
2.3.9 Rule 9: "Don't Use Any Getters/Setters/Properties"	18
2.4 Discussing the Rules	18
2.4.1 Similarities	18
2.4.2 Precedence	18

2.4.3	Conclusion and Outcome	18
3	Tool Support to Validate the Object Calisthenics - Evaluation	19
3.1	Advantages of Tool Support	19
3.2	Working Environment	19
3.3	Evaluation of Rule Validation	19
3.3.1	Validation of Rule 1	20
3.3.2	Validation of Rule 2	20
3.3.3	Validation of Rule 3	20
3.3.4	Validation of Rule 4	20
3.3.5	Validation of Rule 5	20
3.3.6	Validation of Rule 6	21
3.3.7	Validation of Rule 7	21
3.3.8	Validation of Rule 8	21
3.3.9	Validation of Rule 9	21
3.4	Result of the Evaluation	21
3.5	Future Work	21
4	Prototypical Implementation of Tool Support	22
4.1	Requirements	22
4.2	Architecture	22
4.3	Exemplary Rule Validation	22
4.4	Resulting Prototype	22
4.5	Outlook and Future Work	22
5	Conclusion	23
	Bibliography	24

Abbreviations

DHBW	Duale Hochschule Baden-Württemberg
OSS	Open Source Software
Sem	Semester

List of Figures

List of Tables

1 Introduction

Jeff Bay's "Object Calisthenics" [Bay, 2008] are nine rules that train the software developer to write better object oriented code. He created concrete rules out of general software principals and patterns. These rules shall be applied in a short exercise, usually about two to four hours. With these concrete rules the trainee doing the exercise can improve his software development skills, which is helping him when applying general software principals and patterns to real world software projects. The exercise and the reasons for it are described in this chapter, in section [?].

This paper is divided into three chapters.

Chapter 2 describes Jeff Bay's rule and what let him establish the nine rules. It poses Jeff Bay's reasons for today's problems of software development.

The chapter describes every rule step by step. Within this description, a source code example is given. A bad example firstly exemplifies how the code looks like without the rule. A good example, validating the rule, then shows the advantages of the resulting source code when applying the rule. These examples are described shortly. After describing the examples, it researches concepts behind the rule. It describes the problems that would occur without the rule. After explaining the problems behind the rule and Jeff Bay's rule, a more detailed analysis ensues. In this detailed analysis, patterns and principals are described and ideas and concepts are examined. Section 2.3 describes these principles detailed for every rule, step by step. In the end, the section 2.4 furthermore discusses the rules shortly.

Chapter 3 investigates possible tool support to validate the Object Calisthenics. First, the section 3.1 describes general advantages of tool support. The section 3.3 goes through every rule presents the possibilities to validate the given rule. Advantages and disadvantages of the implementation are explained and a short conclusion of every rule is drawn. Section 3.4 then summarizes the results of the evaluation of rule validation. Lastly, section 3.5 further ideas of rule validation and links for further work.

The last chapter 4 describes a prototypical implementation done during this research. The prototype shows the practicability of the evaluation results.

1.1 Exercising Better Object Oriented Programming Skills: a Concept by Jeff Bay

Jeff Bay's "Object Calisthenics" [Bay, 2008] are an exercise to improve the quality of Object Oriented code. According to him, the chapter "will give new programmers an opportunity to learn best practices while writing their own code." [Bay, 2008, p. 70].

The book "The thoughtworks anthology. Essays on Software Technology and Innovation"[ThoughtWorks inc. p. 70-79] was released in 2008. The whole paper consists of thirteen chapters discussing various topics and ideas on how to improve software development. The essays discuss problems and ideas on languages, tool support, software principals and software quality. One of the paper's chapter describes the rules of the Object Calisthenics. Furthermore it shortly describes their purpose and outcome and why the author Jeff Bay created these rules.

All essays in the book [ThoughtWorks inc., 2008] are written by developers working at the company "Thoughtworks inc". The company is well known for creating, designing and supporting high quality software. The company is to be said to be one of the most future oriented company in terms of technology and software principals. They describe themselves as "[...] a software company and community of passionate individuals whose purpose is to revolutionize software design, creation and delivery, while advocating for positive social change [...]" [ThoughtWorks inc.].

The Object Calisthenics are nine programming rules helping to write good object oriented code. But moreover the Object Calisthenics are an exercise to improve the quality of Object Oriented code. Good Object Oriented Code is hard to learn when coming from procedural code. Many developers think in Object Oriented code – but do they really write good Object Oriented Software? That is the question that Jeff Bay poses in his essay.

Usually the developer doesn't use these rules in real world project but applies them in short two hour exercises in which he designs and implements minimalist software with little requirements. This could be a Minesweeper or a Tic Tac Toe game for example. These training challenges should lead the developer to write better code and be more aware of code quality in real world projects.

With these little training sessions, the Object Calisthenics help to create highly object oriented code in small projects. When applying the rules, the developers automatically fulfill many important software patterns and principals leading to higher code quality than the code would have without the given rules. By training developers to focus the rules they automatically apply various helpful and important software principals and software patterns.

The developer is supposed to "spend 20 hours and 1,000 lines writing code that conforms 100 %" to these rules" [ThoughtWorks inc., 2008, p. 80]. He is convinced the developer will "break old habits" [ThoughtWorks inc., 2008, p. 80]. Furthermore he promises that the exercise will change the way "that you may have lived with for your whole programming

life." [ThoughtWorks inc., 2008, p. 80]. According to Bay, this change is the result of the developer's need to rethink and lateral thinking. He is genuine that by this process the developers perspective on existing code and the way he will write code in the future will change radically. As just described this rethinking is only possible in small, lucid projects. This is for example a project with 1,000 lines of code, as suggested by Jeff Bay.

However, Jeff Bay's idea is that by this process of rethinking the code quality of the code written by the developer will improve. Of course this will only work if the developer recognizes the ideas and principals behind the rules, and hereby accepts the positive outcome of the resulting code. Hopefully he is able accept the positive value of the resulting code. When he is working in real world projects he hopefully remembers parts of the rules, resulting ideas or principals and concepts behind the rules. Because of the improvement of his software development skill, he is then able to apply the concepts to real world project. The result is a tremendously improved code quality in the real world project.

Improving the quality of software's implementation by little training sessions - that is his idea, basically. Jeff Bay included also this idea in the name of the rules. The word "Calisthenics" indistinguishable describes the approach, the idea and the outcome of the exercise.

As already said, the background of every rule is described in chapter 2.

1.2 Tool Support to Validate the Object Calisthenics

The purpose of the Object Calisthenics was already described. However, in this paper the focus lies on the evaluation and prototypical implementation of tool support, validating the rules of the Object Calisthenics.

Evaluating the possibility to create tool support validating the Object Calisthenics is the main part of this report. It has two main advantages - efficiency and quality.

Providing tool support for the rules of the Object Calisthenics could improve the time the developer uses to conducts the exercise. This efficiency increase simply makes it easier to do the exercise.

Furthermore it might reveal rule violations that where not detected by the developer yet. Therefore it could guarantee that the developer sticks to the rules. This is a quality improvement.

Therefore, the next chapter 2 describes the rules Object Calisthenics to understand the software principals and quality metrics behind the Object Calisthenics.

As already mentioned, the ensuing chapter 3 discusses tool support for every rule. the prototypical implementation is described in chapter 4.

2 Object Calisthenics by Jeff Bay - Patterns and Principals

This chapter describes the patterns and principals behind the Object Calisthenics.

Firstly, in section 2.1 the advantages of the Object Calisthenics are described. Before explaining the advantages of Object Orientation, the problems of non object oriented code are discussed.

In the second section 2.3, Jeff Bay's rules for better object oriented programming are described step by step. Every rule is described, explained and a good and bad example are given. The examples conduce to understand the problem and the solution given by the rule. Furthermore patterns and principals behind the rules are explained.

2.1 Problems of procedural code

There seem to be problems with procedural, non object oriented code in software. By saying non object oriented software, procedural code is meant. Jeff Bay lists the most important ones in [ThoughtWorks inc., 2008, p.70]. These disadvantages and problems of procedural source code are explained in the following.

2.1.1 Problems of procedural code

In procedural code the behavior is described by step by step operations resulting in an algorithm.

No bundle of data and behavior

The operations, also called commands, in procedural code usually access multiple data structures storing and managing data during the execution time. In procedural code steps can be consolidated by using methods with output and input parameters. Methods can summarize multiple commands to an abstract step that can be executed by a caller. Therefore procedural code provides a solution for structuring algorithms.

But there is another problem remaining. By simply looking at the data structures, the developer cannot see possible operations on the data structure. Of course, he is able to see what is stored in the data structure. However, he is not able to see which operations can be executed on the data structure and how the data structure is supposed to be used. He can only get that information by reading through the algorithm step by step and remembering the possible operations on the data structure. In procedural code there is not clear coherence between the data

structure and its problem specific operations. There is no solution for the problem of bundling data and behavior given in procedural software development.

Furthermore there is no encapsulation of the data structures, hiding the implementation from the abstract definition of possible operations. Also, procedural software lacks of encapsulation. The concept of scoping therefore realizing encapsulation is not given in procedural code.

Maintainability

The just described problem of the low cohesion of data structure and problem specific operations makes maintainability of procedural code hard. Source code of long lasting software has to be maintained years after the initial design and the first implementation. In old and large code bases changes are hard to conduct. This is because the cohesion of behavior and data structures and the bad encapsulation between the different data structures is low. To be able to compensate the cohesion, relatively much documentation and much time to read the code is necessary. Therefore the low cohesion makes the conduction of maintenance software changes hard.

Not understandable

Another problem, closely related to the problem of maintainability, is the understandability of code. As already said, the problem of the low cohesion makes it hard to dedicate the operations to the data structures. The difficulty to dedicate operations to the appropriate data structures makes the understanding of the code hard. By reading through a part of an algorithm, the developer does not know which operations will be executed on which data structure. Secondly, when there are multiple operations on many different data structures, the developer has to remember all these state changes of the data structures. Therefore procedural code is often hard to understand.

No modularity

In modern software development the separation in different modules is a core concept.

Modular programming "breaks down program functions into modules, each of which accomplishes one function and contains all the source code and variables needed to accomplish that function." [About.com]. In [About.com] Juergen Haas also states that the concept of modularity enables the programmer to debug and maintain difficult source code more easily.

A module only contains all necessary information and operations to perform the steps necessary. All other information is not visible by the module, it is hidden in other modules that are responsible for other tasks. However, within one module the developer is not distracted by other operations or data structures that are not related to the module, because they are hidden.

Structure

As already said, procedural code is only structured in different algorithm steps. The data structures are can't be encapsulated. This makes structuring procedural code extremely hard, because there is no mechanism enabling the developer to give structure by hiding information. The only way to give structure is to sort different methods in different files. But even if a data structure and its functions are put in a different file, the data structure is not hidden from the other files. The data structure can be manipulated in every other position of the program.

Overview

This point is closely related to the just explained problem of structuring the program. The only way to sort or separate something can be done by using separate files. But still, this does not solve the problem of information hiding and therefore an overview is not given.

In procedural code it is not possible to put problem related data into a abstract data types.

No reusability

In procedural code it is hard to reuse code. This is a result of the missing encapsulation and the missing modularity that was explained previously.

As already said in procedural code, a method often interacts with many variables of the system that are not encapsulated. A method can interact with all system variables. This leads the developer to not separate the program into different parts with their own responsibility and their own well encapsulated data structures and operations.

When using multiple files in procedural code, at some point the order of inclusion of these files has to be determined. When another file is imported there is no guarantee that the included files does already execute an operation. Furthermore, cyclic dependencies can occur that have to be resolved manually.

However in object oriented software the concept of encapsulation, respectively scoping, of data structures is integrated in the concept of object orientation. In good object oriented software every module and object has a clear scope and is well encapsulated. This makes it easy to reuse the object or module. Firstly, it's dependencies are clear visible. They are not order specific, because they do not determine the order of the inclusion of files, but they determine the types that are used by the class. Secondly, the inner state expressed by data structures is hidden from everything that is not part of the module. The developer does not have to apprehend other modules to change internal states of the module. Thirdly, the operations that can be executed on the object are well defined. The developer can document those interfaces to help developers using the interface to understand how the module or object works.

2.2 Advantages of object orientation

The described problems and disadvantages that were described in the previous chapter 2.1, led to the use of object orientation. All in all it is generally stated that object orientation and its related principals saves us from the problems, described in 2.1 and provides a proper solution.

According to Jeff Bay the change from programming in an procedural way towards programming object oriented style is hard to learn. "Transitioning from procedural development to object-oriented design requires a major shift in thinking that is more difficult than it seems" [Bay, 2008, p. 70]. According to Jeff Bay, however, the procedural way of thinking is still in the mind of many developers. "Transitioning from procedural development to object-oriented design requires a major shift in thinking that is more difficult than it seems" [Bay, 2008, p. 70]. "Many developers assume they're doing a good job with OO design, when in reality they're unconsciously stuck in procedural habits that are hard to break" [Bay, 2008, p.70]. Not only the problem of the difficulty to learn a different way of thinking and coding when changing from procedural to object oriented code is a problem. But also the fact that it is easy for a developer to write procedural code. The disadvantages of procedural code are do not occur immediately. Many of the problems when dealing with procedural source code occur late. That means that the developer does not get an immediate feedback about the quality of his code while writing it, but realizes the bad design of the procedural written code after he conducted a change. And even worse, when he is not realize the disadvantages of procedural code, 'there is no motivation for him to change that behaviour'. Furthermore when creating code and not maintaining legacy code it is generally easier to write procedural code than to write object oriented code. Creating procedural code is significantly easier than creating object oriented code in the first place. The creation and the management of objects and a good implementation of encapsulation is difficult. But the quality of these two features, that are special for good object oriented software, are hard to realize. Whereas implementing the same functionality in procedural code is significantly easier.

Therefore it is easier for the developer to write procedural code, than it is to write object oriented code.

Using the concept of object orientation helps to create software that as multiple advantages. These advantages are described later in this section. Before I will explain the advantages or core concept stated by Jeff Bay, I will summarize the characteristics and compare procedural and object oriented code very shortly.

Procedural code is more like a step-by-step description of sequenced commands. Seldom information hiding is used in procedural code. Furthermore multiple operations manipulate data, but there is no bundling of data and behaviour in one secluded unit.

In object oriented software however such a bundling in units exists. Data and behavior are put together in classes and packages. A unit using another unit uses the interface of the unit to determine possible operations, and uses it as required. The actual implementation and the actual data structures are hidden from the calling unit.

In object oriented software tasks that do not have the same area of responsibility, are separated. If a unit has to offer functionality where it does not the domain knowledge to implement it, it delegates the task to another unit, implementing the desired behavior. Otherwise the unit would not do exactly and only what it is supposed to do. To satisfy the definition of a module it need to have a high cohesion and should only do the one thing that is dedicated to that unit. The definition cohesion was already explained in 2.1.1. Therefore the object delegates its work to other units that are dedicated to that well defined and specific task.

There is a third point that is typical for object orientation. The things that are represented in software not only mapped by representing a list of commands, but having concrete representations for the real world. These concrete representations are object that model real world things directly and bundle the behavior and representation of a real world object directly. This enables to separate in different models and make the models reusable. By doing so the particular modules are reusable and are simple and easy to use. This led object orientation to the four pillars of object orientation: encapsulation, abstraction, inheritance, polymorphism. These pillars are the generally accepted basic advantages of object orientation.

Jeff Bay however enhances the advantages by "core concepts" and "core qualities" that mark good object oriented code. The qualities are: cohesion, loose coupling, zero duplication, encapsulation, testability, readability and focus. Bay does not further explain these qualities. In the next paragraph I will go through all the qualities and explain them shortly.

Because Jeff Bay's exercise was already described in 1.1, after the description of the code qualities, the detailed explanation of Jeff Bays nine rules will follow.

2.2.1 Cohesion

Cohesion describes "degree to which the elements of a module belong together"[Yourdon, 1979]. It is a software measurement describing how strongly related pieces of functionality are. Therefore it describes how well the units of a system are grouped. When units, dedicated to a similar purpose, are part of the same group and no nonrelated unit is part of the group, the group has a high cohesion. A module with high cohesion has strongly related and very focused responsibilities[?]. Generally cohesion is not described as an enumerable number, but one is distinguishing between high cohesion and low cohesion. Low cohesion is considered bad whereas high cohesion is considered good.

There are different advantages of high cohesion. In object orientation for example, when methods of a class have a similar responsibilities, the object tends to have a high cohesion. All object's methods are dedicated to the one task dedicated for the object. The object does not provide any other methods and does not perform any other tasks that are not related its actual task. Therefore it is easy for the developer to understand the behaviour of the object and to understand what the object is doing, when it is interacting within application. High cohesion can also enhance the readability of code, because the reader is not distracted by method calls that are related to other tasks than the dedicated one. It is ensured that the operations of the implemented methods is only related to the task that the methods shall perform.

Low cohesion in contrast is bad, because the just described advantages of focus, readability and easiness to understand. The cohesion is decreased from high cohesion to low cohesion, when different aspects are implemented in one class. The result is a system that is more difficult to maintain and to understand system.

2.2.2 coupling

Coupling is a metric that describes the knowledge of a class about its surrounding objects. Loose coupling can be described by two attributes. Firstly, if a class knows less about the surrounding classes and only uses well defined, generic interfaces to those classes. It does not have knowledge about the concrete implementation of the class. Secondly, if the state of a class does not depend on the state of another state, or at least only depends on the state provided by the class directly, and not by other classes provided by that class but only uses the provided methods. When this is not the case, the classes are strongly coupled. The "lack of coupling means that the elements of our system are better isolated from each other and from change" [?]. Because the changes of an classes interface, for example when conducting a refactoring, do only spread to the directly related neighbor classes, loose coupling is considered a good object oriented style. It is easier to change loosely coupled classes than strongly coupled classes. Another aspect of loose coupling is the Dependency Inversion Principle (DIP). Martin describes the Dependency Inversion Principle (DIP) in [Martin, 2008] as following: "In essence, the DIP says that our classes should depend upon abstractions, not on concrete details" [Martin, 2008].

2.2.3 duplication

If there is no duplicated code in software, then the quality of zero duplication is fulfilled. If there is no duplication of components or algorithms, the components are reusable and do not have to be rewritten in a similar way. In some cases the component can be slightly adapted, but in the end it is working for all parts of the software that use the component. The metric indicating no duplication in source code is called code duplication.

2.2.4 encapsulation

When a class or a module hides its internal state it is considered encapsulated. When class B is well encapsulated and there are well defined methods that can be executed, then a class A using class B, can depend on the methods, therefore the provided operations. There is no part in the implementation of class A where it depends on a variable of class B. Then class A does not depend on the inner state of class B. Therefore class B can implement its algorithms and state management independent from all using classes. Well encapsulated classes "restrict component's access"[Wikipedia, Encapsulation]. Furthermore, well encapsulated classes "bundle [...] methods that implement operations on data"[Wikipedia, Encapsulation]. The data is then "hidden behind the specified methods"[Wikipedia, Encapsulation].

2.2.5 testability

Testability describes how testable a class or module is. There is no metric describing the degree of testability but there are some metrics describing the tests themselves. One metric is code coverage. It is an indicator on how many lines of code are covered by tests. The line is regarded as "tested" when there is a test that is running through a line of code. It is not guaranteed that every line occurring in the code coverage metric is actually testing the related behavior of the line. The just described type of code coverage is called "line coverage", because it counts the lines that are tested in a test run. There are also other types of coverages. These are function coverage, that indicate how many functions in the software are covered by tests. There is condition coverage and there is branch coverage, indicating how many of the possible branches of the program are covered by tests.

2.2.6 readability

Readability basically consists of three different aspects. The first aspect refers to the easiness of understanding a certain amount of source code. It is basically the metric for the quality of readability. The more source code can be understood within a specified amount of time, the more readable the code is. This makes readable code important. But it is one of the central qualities in software, because much time is spent with reading existing code. In [Martin, 2008], Martin describes quotes Grady Booch and Dave Thomas on statements about the readability of source code. Grady Booch describes readability in the following way. "Clean code is simple and direct. Clean code reads like well-written prose. Clean code never obscures the designer's intent but rather is full of crisp abstractions and straightforward lines of control." [Martin, 2008, p. 8]. He clearly sets the focus on the style of the resulting code. According to him, the code should be very easy to understand and read like an easily understandable book. Dave Thomas focuses more on the fact that readable code is also readable for others. Even more he has the problem of naming variables, functions and units. Furthermore he states that minimal and clear dependencies make code cleaner and more readable, because it thereby is readily comprehensible. "Clean code can be read, and enhanced by a developer other than its original author. [...] It has meaningful names. It provides one way rather than many ways for doing one thing. It has minimal dependencies, which are explicitly defined, and provides a clear and minimal API." [Martin, 2008, p. 9].

Two other aspects are important when looking at the readability of source code. It is generally known that well placed documentation at parts of the code that are hard to understand, help the reader to grasp the code he reads. Therefore good documentation enhances the readability of source code.

In [Martin, 2008] Martin describes the third important factor for ensuring readability. Martin's "step down rule" is a rule ensuring the separation of different layers of abstraction. Classes or components describe different levels of abstractions. Abstract level classes are usually the "top-level" entry point when calling a module or a library, whereas low level classes execute very problem specific operations. The step down rule states that this hierarchical ordering of functions exists. In addition it says that all functions that are declared in one class should all

be on the same level of abstractions. Furthermore very method of a higher level should only call functions declared on a lower level. The result is a composition of functions going from a abstract to a concrete level. For the reader of the code it is easier to understand the resulting code because he know exactly in which level of abstraction he is located. He can therefore navigate more easily to the desired code positions. Furthermore he doesn't have to understand every detail of the whole code, but can use the the higher levels of abstraction to understand quickly what the code is doing.

2.2.7 focus

The last quality Jeff Bay describes in [ThoughtWorks inc., 2008] is focus. Focus is the description of "doing one thing". Every unit is dedicated to one task it has to manage and fulfill successfully. Focus describes not only this dedication, but furthermore states that the unit shouldn't do anything more. Consequently, the module contains no operations that are not related to that task. If it has to trigger other tasks that are not related to its dedication, it uses methods on other units that are specialized on this task. This means the module delegates all tasks that are not part of its dedication to other units. These units themselves are dedicated to the delegated task. Focus is very similar to the just described quality coupling in chapter 1.1.

2.3 The Rules and their Background

The instruction on how to conduct the exercise was already describe in the beginning, in chapter 1.1. This chapter describes the rules of the Object Calisthenics itself.

In the chapter I will go through every rule, step-by-step. Every every section will describe the patterns an principals behind the rules, elucidate design patterns and best practices that correspond with the rules. Each rule will furthermore exempify the rule by a good and a bad example.

=== FOR EACH rule/subsection IN rules/subsections: Every rule is described one after the other with the information that is already documented in the committed work of the "research" phase:

- Explain the rule. Use quotes of paper.
- Every chapter gives short explanation, a good and a bad example. These examples are explained shortly.
- Furthermore every chapter describes the software patterns and software principals behind every rule. These are for example design patterns, software principals and best practices.
- Refer to other sources to be able to explain clearly but shortly. Summarize complex patterns instead of explaining every pattern and principal in detail.
- Make sure the principals behind are easy to read: A advanced reader should not be bored by detailed explanation and a beginner reader should be able to understand the main message and idea behind the principal and idea.
- The outcome of every rule is then summarized.

2.3.1 Rule 1: "Use One Level of Indentation per Method"

With his first rule, "Use One Level of Indentation per Method", Jeff Bay's tries to tackle the problem of low cohesion and ensure that one class is only operating on one level of abstraction. These two problems and their solutions are presented in the following.

The metric cohesion, which was already described in 2.2.1, describes how well an object is focused and how well it is dedicated to one single task. The principle of "doing one thing", that Fowler describes in [Martin, 2008], was already mentioned in 2.2.7. Jeff Bay's Rule "Use One Level of Indentation per Method" takes the principle of cohesion which is often applied on a class level and applies it on the method level. By doing so he ensures that a method is only doing what it is supposed to do and therefore delegates all non-relevant tasks.

There are two important principles behind the rule.

The idea of delegating all non relevant work and therefore raise the cohesion can be done in the following way. This is ensuring that the method is only manipulating data that is related directly to the method. This means ensuring the method does not manipulate data that is accessed via multiple getter methods, other method calls or iterations. Such an access would change data that is not related directly to the object itself. Therefore a foreign object would manipulate the data of another object - instead of calling a method on the object. As already described other, just called "foreign objects", can be accessed via method calls and control structures like while, for and do-while loops. Therefore when accessing an object with nested control structures, the methods is likely to change such "foreign object". There are two rule by Jeff Bay that prohibit such a "deep" access to those "foreign objects" data structures. One is this rule, restricting the nesting of control-structures and the other rule is Rule 4 "Use only one dot per line" restricting the "deep" access via chained method calls.

As already mentioned, there is another principle that plays an important role, when looking at the rule. The idea of "one level of abstraction", which is described by Martin Fowler in [Martin, 2008], is the other one. The basic idea of the "one level of abstraction" principle was already introduced in ???. Martin Fowler states that a method should only operate within one level of abstraction and delegate all other tasks that are on a lower level to another class. Fowler states the rule as important, because it hard for humans to follow. "This may be the hardest of these heuristics to interpret and follow. Though the idea is plain enough, humans are just far too good at seamlessly mixing levels of abstraction". When a method is operation on two levels of abstraction, no always, but often using nested control structures in order to access the "deeper" objects and to conduct data manipulation on a lower level. Transferring those operations not only results in a better abstraction. After a split up of tasks in object on different levels, the cohesion of the objects raises. Furthermore the object on a abstract level does not have to do operations on a low level, but is using another object to undertake the task. The result in many cases is that the object on the abstract level does not have to use that much control structures to perform the task, because it simply delegates all work that is not on its abstraction level. Therefore the nesting of control structures disappears automatically. In his Rule, however, Jeff Bay prohibits the nesting of control structure and therewith forces the developer to use different levels of abstraction ab initio.

The following code example describes a bad and a good example of the rule. The first example is showing a possible implementation and the second example is showing a refactor example, which satisfies the rule and as a high cohesion and only operates on one level of abstraction.

For reasons of simplicity, the following java examples do not contain imports and the main method is always in the class that is used first.

The problem implemented to exemplify is quite simple: A school has multiple classes with students. The goal is to get the average age of all students in the school.

```
1 package reportexamples.rule1.example1;
2
3 import java.util.List;
4
5 public class School {
6
7     private List<SchoolClass> classes;
8
9     private void count() {
10         int sum = 0;
11         for (SchoolClass classe : classes) {
12             List<Student> students = classe.
13                 getStudents();
14             for (Student stuent : students) {
15                 ++sum;
16             }
17         }
18
19         public static void main(String[] args) {
20             School school = new School();
21             school.count();
22         }
23
24 }
```

As the listing 2.3.1 shows, the method *count* simply iterates over all classes of the school, then reads out all students of the class and counts their number. This operation uses nested for loops to determine the number of students. A first improvement would be to use multiple methods to get rid of the nested control structures. This is depicted in 2.3.1. In this example, the control structures are not nested anymore, but method calls are used to conduct the counting of the deeper data. The deeper data in this case are the *Students* because their are contained by the *SchoolClass*.

```
1 package reportexamples.rule1.example2;
2
3 import java.util.List;
```

```

4
5 public class School {
6
7     private List<SchoolClass> classes;
8
9     private void count() {
10         int sum = 0;
11         for (SchoolClass classe : classes) {
12             sum = countStudents(sum, classe);
13         }
14     }
15
16     private int countStudents(int sum, SchoolClass classs)
17     {
18         List<Student> students = classs.getStudents();
19         for (Student stuent : students) {
20             ++sum;
21         }
22         return sum;
23     }
24
25     public static void main(String[] args) {
26         School school = new School();
27         school.count();
28     }
29 }

```

Even if 2.3.1 now fulfils the rule, there is still problem remaining. The class *School* is still operating on the data that is contained by the class *SchoolClass*. However the number of students in a school and the number of students in a class are two different concerns and they should not only be separated but be well placed in their corresponding classes. Then the the result is a higher cohesion, because the operations are placed perecisely at the classes. Therefore extracting the method that is counting the students of a class to the *SchoolClass* is a step, improving the code even more. Listing ?? and ?? show the two classes with their corresponding counting methods, that are now located to the proper classes.

```

1 package reportexamples.rule1.example3;
2
3 import java.util.List;
4
5 public class School {
6
7     private List<SchoolClass> classes;
8
9     private void count() {


```



```
10         int sum = 0;
11         for (SchoolClass classe : classes) {
12             classe.countStudents(sum, classe);
13         }
14     }
15
16     public static void main(String[] args) {
17         School school = new School();
18         school.count();
19     }
20
21 }
```

```
1 package reportexamples.rule1.example3;
2
3 import java.util.List;
4
5 public class SchoolClass {
6
7     private List<Student> students;
8
9     public int countStudents(int sum, SchoolClass classs)
10     {
11         for (Student stuent : students) {
12             ++sum;
13         }
14         return sum;
15     }
16 }
```

The example shows exemplifies how Rule 1 "Use One Level of Indentation per Method" can improve the readability of code and the cohesion of the classes. The resulting classes are therefore easier to test, easier to understand and more focused on doing on dedicated task. The graphic in 2.3.1 shows exactly this. The operations on a deep abstraction level or operations on nested structures are not done on the abstract level. In contrast, the abstract level uses the lower level object to conduct low level operations.



2.3.2 Rule 2: "Don't Use the else Keyword"

Jeff Bay's Rule 2 "Don't Use the else Keyword", tackles the lack of understanding and usage of polymorphism. In ?? he states that many developers learn if/else constructs from day one. Therefore they are used to the usage of the construct. Even worse they learn the proper usage of polymorphism later on in their career. As a result the "way of thinking" in if/else constructs is still firmly established in developers' brains.

As commonly stated, the excessive use of conditionals leads to code that is hardly readable. Even worse it leads to code duplication. This is because the developer does not see the usage of an if/else construct from the outside of the class. Therefore if he does not know the class where object is used, he simply rewrites the behaviour that is already implemented in another method. Assumed there would be an object that had a clear description of the implemented behaviour and could be reused, then this error would not occur. Furthermore the conditional within the method could also be implemented by different implementation behind a common interface. The setting of the direction would then not happen when passing the if/else construct, but the method would simply call another method of an object and the concrete implementation of a common interface determines the code that is executed.

There are several ways to reduce the usage of if/else conditionals and increase the overview and readability of the coding. The three ways of doing so are: early return, the Null Object Pattern and the Strategy or State pattern. These three approaches are exemplified in the next paragraph.

asdf

2.3.3 Rule 3: "Wrap All Primitives and Strings"

The following code example describes a bad and a good example of the rule. The first example is showing a possible implementation and the second example is showing a refactor example, which satisfies the rule and as a high cohesion and only operates on one level of abstraction.

For reasons of simplicity, the following java examples do not contain imports and the main method is always in the class that is used first.

The example 2.3.3 shows a class used to create an **HTML! (HTML!)** element containing an auto incremented identifier *id* and a String *content*. In the method *sayHello* an **HTML! (HTML!)** element is assembled and printed on the given *PrintStream* of the method. The method appends the **HTML! (HTML!)**, a technical markup language and a domain dependent variable, and the *content*, to the printer. The technical **HTML! (HTML!)** is a formatting information on a low level. The content however is a domain dependent information, that is not dependent on the markup that is used. This is a violation of the "one level of abstraction" principle.

A solution is to extract the markup from the domain dependent information. In the following, an improved version of the problem is shown. In this example the high level information *content* and the low level markup information are separated strictly. The new class *HtmlElement* now represents a **HTML! (HTML!)** element with an *id* and a *content*. The class depicted in listing is listed show the *HtmlElement*.

Even if the new introduced class *HtmlElement* is on a low level, very close to the markup language and not domain dependant, it is abstracting a simple structure of a regular **HTML! (HTML!)** element. Therefore the class can be reused by other classes

asdf

2.3.4 Rule 4: "Use Only One Dot per Line"

asdf

2.3.5 Rule 5: "Don't Abbreviate"

asdf

2.3.6 Rule 6: "Keep All Entities Small"

asdf

2.3.7 Rule 7: "Don't Use Any Classes with More Than Two Instance Variables"

asdf

2.3.8 Rule 8: "Use First-Class Collections"

asdf

2.3.9 Rule 9: "Don't Use Any Getters/Setters/Properties"

asdf

2.4 Discussing the Rules

2.4 === This chapter is discussing the rules shortly.

=== Use quotes from Jeff's text: He also gives a short summary of his text in the end

2.4.1 Similarities

=== Are there similarities in the rules? Is it possible to categorize the rules in terms of: - Do they have the same intention? - Are they related to the same "big picture" idea (example: encapsulation or abstraction)

Categorize rules: Are there similarities from perspective of principle? ??? Together with next chapter?

2.4.2 Precedence

=== Make clear that this is my own estimation and not related to Jeff's text. Prioritize the rules.

=== To be determined: How long is this chapter?

// Yada yada yada: Own estimation: what's the most important rule? What do I think? What does the author think? Reason with descriptions and examples given

2.4.3 Conclusion and Outcome

=== Give a short and precise conclusion of the Object Calisthenic: Purpose, exercise, stuff to learn, skill improvement.

=== Also Summarize what most of the rules are about:

RESERACH page 21:

- behaviour and operation oriented
- LoD and loose coupling
- talk to friends
- talk the protocol specified by the object's operation
- Next page: conclusion, no else ,naming,

all in all: Duplication of code and idea ==> "Simple and elegant Abstractions"

3 Tool Support to Validate the Object Calisthenics - Evaluation

3.1 Advantages of Tool Support

=== What is a tool? Why do tools help? What makes tools strong? Why do tools matter for developers? Possible outcome of tool support for the OC's? Already described in the Introduction (chapter 1). Describe this more in detail here if necessary.

3.2 Working Environment

=== Describe AST generally. Say that Eclipse provides types representing the parts of code syntax. This is seen as given.

=== Refer to other references explaining AST.

=== Describe shortly how it is possible to do an AST validation with eclipse.

=== Say that: "Eclipse" terms for AST nodes are quite similar to general terms for java's nodes in ASTs. In this report the standard terms are used. These are not further described in this paper.

→ Example: Describe that "MethodDeclaration" consists of different other nodes representing the declaration of a method. Describe the structure of the child nodes of the node as far necessary. Do not embark on a discussion about what exactly is allowed as method declaration.

=== Therefore: Give reference for questions about "parameter", "type", "class", "expression" or "statement". Say that the validation in the next section is exactly implemented as described. One validation implementation example is explained exemplary in the Prototype chapter.

3.3 Evaluation of Rule Validation

=== Say that the prioritization of the rules (in terms of the rule validation) and the "ranking" is given in the end. The sections of this chapter are "rule specific", even if the next subsections refer to each other.

=== FOREACH Rule/Subsection IN Rules/Subsections:

- Similarities found out in description may be similar in this validation? Categorize the rules in groups to form a validation perspective. (E.g.: Validation of rule y is very similar to the validation of rule x that was already explained.)

- Use examples given in description chapter to describe the typical structure of the rule.


- Explain "the positive case": What is the positive structure, satisfying the rule. Where does a rule violation occur when the structure is not fulfilled. (Example: Positive case: maximum of

2 instance variables. If not fulfilled: Discussion Rule violation information occurs on the level of the class or on the level of the third instance variable?

- What checks have to be done for the validation?
- Discussion of 'rule dependencies' within one rule (example: wrapper has to determine possible wrapper classes first before being able to indicate the use of a primitive/string in a non-wrapper class...)
- -> solution found/no solution found
- Therefore: Be self-critical: Now, were a "solution" is found (or not), describe the problems that occur with the described implementation
- If there are cases where the rule cannot be validated: Why is it hard to validate. Where does the validation fail? How is it possible to "trick" a good implementation (Example: wrap of primitives can be "tricked" with 'return new Wrapper(instancevariable)'...)

3.3.1 Validation of Rule 1

Cool, I can draw trees:



3.3.2 Validation of Rule 2

asdf

3.3.3 Validation of Rule 3

asdf

3.3.4 Validation of Rule 4

asdf

3.3.5 Validation of Rule 5

asdf

3.3.6 Validation of Rule 6

asdf

3.3.7 Validation of Rule 7

asdf

3.3.8 Validation of Rule 8

asdf

3.3.9 Validation of Rule 9

asdf

3.4 Result of the Evaluation

=== Give a summary on how hard it was to implement the rules. Where does the rule validator fail. Summarize results of the evaluation. Be positive: Do not forget to emphasize the good and working parts of the evaluation tool and accent the positive outcome of them.

3.5 Future Work

=== Be philosophical: What is still to be done in terms of rule validation.

=== If many rules cannot be validated: Future work might be a software where the user can "mark" structures as given. (Example: If it is not possible to determine if a class is a wrapper class, the user could "mark" it as a wrapper class and the validation algorithm might work...)

=== If many rules can be validated: Future work might be the configuration of the rule validator. "pluggable" rules that the user can implement himself? Or "configurable" rule: Use of 2/3/4 instance variables per class.

4 Prototypical Implementation of Tool Support

=== This chapter describes the implementation of the prototype.

4.1 Requirements

=== Describe requirements for the prototype. Depends on how "good" the prototype is....

4.2 Architecture

=== Describe overall architecture.

=== How about a package overview and a short description: What do the classes of the package do and how do they interact in the software?

4.3 Exemplary Rule Validation

=== One example implementation of one rule validation. Idea: Implementation of an ASTVisitor class...

4.4 Resulting Prototype

=== If the prototype is really good: swagger and present it as a good software, that might be used in trainings?

=== If not: Be proud of what is there :). This is only a prototype. What could be improved in a better implementation? Is it even possible to do a better implementation in terms of the rule validation (depends on the outcome of chapter 3).

=== Show screenshot and describe UI. What is possible to do with the client

=== Independent from the quality of the prototype: What are ideas that are still out there for the prototype? How could the product improve?

4.5 Outlook and Future Work

=== Possible future work, dependent on what is said in the previous section.

5 Conclusion

=== Conclusion of the result of this work. Do not explain in detail, but refer to the Introduction:

What was good, what was bad?

TODO: Have fun writing and stay happy :)

Bibliography

- [FoBa03] Foo, John; Bar, Belinda: *Titel : Untertitel*,
Verlagsort: Verlag, Jahr der Auflage. S. 10-20
- [Le01] Autor Name: *Titel des Buches*, New York: Penguin Books, 2001.
- LITERATUR:
- [Bay, 2008] Bay, Jeff: *Object Calisthenics*.
In: ThoughtWorks inc. (eds): *The ThoughtWorks Anthology. Essays on Software Technology and Innovation*.
Raleigh, North California; Dallas, Texas: The Pragmatic Bookshelf, 2008, p. 70–80.
- [ThoughtWorks inc., 2008] ThoughtWorks inc. (eds): *The ThoughtWorks Anthology. Essays on Software Technology and Innovation*.
Raleigh, North California; Dallas, Texas: The Pragmatic Bookshelf, 2008.
- [Gamma et al., 1994] Gamma, Eric; Helm, Richard; Johnson, Ralph; Vlissides, John: *Design Patterns. Elements of Reusable Object-Oriented Software*.
Amsterdam: Addison-Wesley Longman, 1994.
- [Martin, 2008] Martin, Robert Cecil: *Clean Code. A Handbook of Agile Software Craftsmanship*.
n.p., Prentice Hall International, 2008.
- [Fowler et al., 1999] Fowler, Martin: *Refactoring. Improving the Design of Existing Code*.
Amsterdam: Addison-Wesley Longman, 1999.
- [Evans, 2003] Evans, Eric: *Domain-Driven Design. Tackling Complexity in the Heart of Software*.
Amsterdam: Addison-Wesley Longman, 2003.
- [Yourdon, 1979] Yourdon, Edward; Constantine, Larry: *Structured Design: Fundamentals of a Discipline of Computer Program and Systems Design*. Yourdon Press, 1979
asdfklsajklj INTERNET
- [Eclipse Documentation] The Eclipse Foundation: *Eclipse documentation - Eclipse Kepler*.
URL <http://help.eclipse.org/kepler/index.jsp>.
- [Wikipedia] Wikipedia. The Free Encyclopedia.
URL <http://www.wikipedia.org>.

[About.com] Haas, Juergen: *Modular Programming*.

URL <http://linux.about.com/cs/linux101/g/modularprogramm.htm>.

[ToughtWorks inc.] Thoughtworks inc.

URL thoughtworks.com/about-us (17 November 2013).