

Package ‘directlabels’

April 8, 2017

Maintainer Toby Dylan Hocking <toby.hocking@r-project.org>

Author Toby Dylan Hocking

Version 2017.03.31

License GPL-3

Title Direct Labels for Multicolor Plots

Description An extensible framework
for automatically placing direct labels onto multicolor 'lattice' or
'ggplot2' plots.
Label positions are described using Positioning Methods
which can be re-used across several different plots.
There are heuristics for examining ``trellis" and ``ggplot" objects
and inferring an appropriate Positioning Method.

URL <http://directlabels.r-forge.r-project.org/>

LazyData true

Suggests MASS, inlinedocs, ggplot2 (>= 2.0), lattice, alphahull, nlme,
ElemStatLearn, lars, latticeExtra

Imports grid, quadprog

Collate utility.function.R compare.R dotplot.R lineplot.R
densityplot.R ggplot2.R positioning.functions.R doc.R lattice.R
scatterplot.R contourplot.R

NeedsCompilation no

Repository CRAN

Date/Publication 2017-04-08 20:37:04 UTC

R topics documented:

directlabels-package	4
ahull.grid	4
ahull.points	5
angled.bboxes	5
angled.endpoints	5

apply.method	6
big.bboxes	7
bottom.pieces	7
bumpup	8
calc.borders	8
calc.bboxes	9
check.for.columns	9
chull.grid	10
chull.points	10
default.ahull	10
default.picker	11
defaultpf.ggplot	11
defaultpf.trellis	12
direct.label	12
direct.label.ggplot	14
direct.label.trellis	14
dl.combine	15
dl.jitter	17
dl.move	18
dl.summarize	19
dl.trans	19
dlcompare	20
dldoc	21
dlgrob	22
draw.polygons	23
draw.rects	23
drawDetails.dlgrob	24
edges.to.outside	24
empty.grid	25
enlarge.box	26
extract.plot	26
extract.posfun	27
extreme.grid	27
extreme.points	28
far.from.others.borders	28
filltemplate	29
first.bumpup	29
first.points	29
first.polygons	30
first.qp	30
gapply	31
gapply.fun	31
GeomDI	32
geom_dl	32
get.means	34
getLegendVariables	35
ignore.na	35
in1box	36

in1 which	36
inside	37
iris.l1.cluster	37
label.endpoints	38
label.pieces	39
lasso.labels	39
last.bumpup	39
last.points	40
last.polygons	40
last.qp	40
lattice.translators	41
legends2hide	41
lines2	42
make.tiebreaker	42
maxvar.points	43
maxvar.qp	43
merge_recurse	44
midrange	44
normal.l2.cluster	45
only.unique.vals	46
outside.ahull	46
outside.chull	47
panel.superpose.dl	47
pkgFun	49
polygon.method	50
positioning.functions	51
project.onto.segments	55
projectionSeconds	56
qp.labels	57
reduce.cex.lr	59
rhtmlscape	60
SegCost	61
smart.grid	61
static.labels	62
svmtrain	62
top.bumptime	63
top.bumpup	63
top.pieces	64
top.points	64
top.qp	65
uselegend.ggplot	65
uselegend.trellis	65
vertical.qp	66
visualcenter	66
xlimits	67
ylimits	67

directlabels-package *Direct labels for multicolor plots in lattice or ggplot2*

Description

An extensible framework for automatically placing direct labels onto multicolor lattice or ggplot2 plots. Label positions are described using Positioning Methods which can be re-used across several different plots. There are heuristics for examining "trellis" and "ggplot" objects and inferring an appropriate Positioning Method.

Details

Package: directlabels
 Maintainer: Toby Dylan Hocking <toby@sg.cs.titech.ac.jp>
 Author: Toby Dylan Hocking
 Version: 2014.6.13
 License: GPL-3
 Title: Direct labels for multicolor plots in lattice or ggplot2
 URL: <http://directlabels.r-forge.r-project.org/>
 LazyData: true
 Suggests: MASS, inlinedocs, ggplot2 (>= 0.9.1), lattice, alphahull, reshape2, nlme, ElemStatLearn, proto, lars, latticeExtra
 Depends: grid, quadprog
 Collate: utility.function.R compare.R dotplot.R lineplot.R densityplot.R ggplot2.R positioning.functions.R doc.R lattice.

Author(s)

Toby Dylan Hocking

ahull.grid *ahull grid*

Description

Label the closest point on the alpha hull of the data.

Usage

"ahull.grid"

ahull.points	<i>ahull points</i>
--------------	---------------------

Description

Calculate the points on the ashape.

Usage

```
ahull.points(d, ..., ahull = default.ahull(d))
```

Arguments

d
...
ahull

Author(s)

Toby Dylan Hocking

angled.boxes	<i>angled boxes</i>
--------------	---------------------

Description

Draw a box with the label inside, at the point furthest away from the plot border and any other curve.

Usage

```
"angled.boxes"
```

angled.endpoints	<i>angled endpoints</i>
------------------	-------------------------

Description

Useful for labeling lines that all end at the top.

Usage

```
"angled.endpoints"
```

 apply.method

Apply a Positioning Method

Description

Run a Positioning Method list on a given data set. This function contains all the logic for parsing a Positioning Method and sequentially applying its elements to the input data to obtain the label positions.

Usage

```
apply.method(method, d, columns.to.check = c("x", "y",
      "groups"), ..., debug = FALSE)
```

Arguments

method	<p>Direct labeling Positioning Method. Starting from the data frame of points to plot for the panel, the elements of the Positioning Method list are applied in sequence, and then each row of the resulting data frame is used to draw a direct label. The elements of a Positioning Method list can be</p> <ul style="list-style-type: none"> • a Positioning Function is any function(d,...) which takes a data.frame d with columns x,y,groups and returns another data.frame representing the positions of the desired direct labels. For a description of all the columns that are interpreted for drawing direct labels, see drawDetails.dlgrob. For example, maxvar.points is a Positioning Function that returns a data.frame with columns x,y,groups,hjust,vjust. • a character vector of length 1 is treated as the name of an R object. For example, specifying "maxvar.points" means to look up the variable called maxvar.points and use that. Using the name of a Positioning Function is preferable to specifying the Positioning Function itself, since then the name is visible in the Positioning Method list, which is more interpretable when debugging. • a named list element is used to add or update variables in the data.frame of direct labels to plot. For example list("first.points",cex=1.5) means take only the first points of every group and then set the cex column to 1.5. • an element of a Positioning Method list can be another Positioning Method list, in which case the elements of the inner list are applied.
d	Data frame to which we apply the Positioning Method. The x and y columns should be in centimeters (cm), so that Positioning Methods can easily calculate the L2/Euclidean/visual distance between pairs of points.
columns.to.check	After applying each Positioning Method list element, we check for the presence of these columns, and if not found we stop with an error.
...	Named arguments, passed to Positioning Functions.
debug	If TRUE, print each Positioning Method list element and the direct label data.frame that results from its evaluation.

Value

The final data frame returned after applying all of the items in the Positioning Method list, with x and y in units of cm.

Author(s)

Toby Dylan Hocking

big_boxes	<i>big boxes</i>
-----------	------------------

Description

Calculate big boxes around the means of each cluster.

Usage

```
"big_boxes"
```

bottom.pieces	<i>bottom pieces</i>
---------------	----------------------

Description

Positioning Method for the bottom of a group of points.

Usage

```
bottom.pieces(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

`bumpup`*bumpup*

Description

Sequentially bump labels up, starting from the bottom, if they collide with the label underneath.

Usage

```
bumpup(d, ...)
```

Arguments

`d`

`...`

Author(s)

Toby Dylan Hocking

`calc.borders`*calc.borders*

Description

Calculate bounding box based on newly calculated width and height.

Usage

```
calc.borders(d, ...)
```

Arguments

`d` Data frame of point labels, with new widths and heights in the `w` and `h` columns.

`...` ignored.

Author(s)

Toby Dylan Hocking

`calc.bboxes`*calc boxes*

Description

Calculate boxes around labels, for collision detection.

Usage

```
calc.bboxes(d, debug = FALSE, ...)
```

Arguments

`d`

`debug`

`...`

Author(s)

Toby Dylan Hocking

`check.for.columns`*check for columns*

Description

Stop if a data.frame does not have some columns.

Usage

```
check.for.columns(d, must.have)
```

Arguments

`d` data.frame to check.

`must.have` column names to check.

Author(s)

Toby Dylan Hocking

chull.grid	<i>chull grid</i>
------------	-------------------

Description

Label the closest point on the convex hull of the data.

Usage

```
"chull.grid"
```

chull.points	<i>chull points</i>
--------------	---------------------

Description

Calculate the points on the convex hull.

Usage

```
chull.points(d, ...)
```

Arguments

```
d
...
```

Author(s)

Toby Dylan Hocking

default.ahull	<i>default ahull</i>
---------------	----------------------

Description

Calculate the default alpha parameter for ashape based on the average size of label boxes.

Usage

```
default.ahull(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

default.picker	<i>default picker</i>
----------------	-----------------------

Description

Look at options() for a user-defined default Positioning Method picker, and use that (or the hard-coded default picker), with the calling environment to figure out a good default.

Usage

```
default.picker(f)
```

Arguments

f Object class to look for (trellis or ggplot).

Author(s)

Toby Dylan Hocking

defaultpf.ggplot	<i>defaultpf ggplot</i>
------------------	-------------------------

Description

Default method selection method for ggplot2 plots.

Usage

```
defaultpf.ggplot(geom, p, L, colvar, ...)
```

Arguments

geom
p
L
colvar
...

Author(s)

Toby Dylan Hocking

defaultpf.trellis	<i>defaultpf.trellis</i>
-------------------	--------------------------

Description

If no Positioning Method specified, choose a default using this function. The idea is that this is called with all the variables in the environment of `panel.superpose.dl`, and this can be user-customizable by setting the `directlabels.defaultpf.lattice` option to a function like this.

Usage

```
defaultpf.trellis(lattice.fun.name, groups, type, ...)
```

Arguments

`lattice.fun.name`

`groups`

`type`

`...`

Author(s)

Toby Dylan Hocking

direct.label	<i>Direct labels for color decoding</i>
--------------	---

Description

Add direct labels to a plot, and hide the color legend. Modern plotting packages like `lattice` and `ggplot2` show automatic legends based on the variable specified for color, but these legends can be confusing if there are too many colors. Direct labels are a useful and clear alternative to a confusing legend in many common plots.

Usage

```
direct.label(p, method = NULL, debug = FALSE)
```

Arguments

p	The "trellis" or "ggplot" object with things drawn in different colors.
method	Positioning Method, which determines the positions of the direct labels as a function of the plotted data. If NULL, we examine the plot p and try to choose an appropriate default. See apply.method for more information about Positioning Methods.
debug	Show debug output?

Value

A plot with direct labels and no color legend.

Author(s)

Toby Dylan Hocking

Examples

```
if(require(ggplot2)){
  ## Add direct labels to a ggplot2 scatterplot, making sure that each
  ## label is close to its point cloud, and doesn't overlap points or
  ## other labels.
  scatter <- qplot(jitter(hwy),jitter(cty),data=mpg,colour=class,
                   main="Fuel efficiency depends on car size")
  print(direct.label(scatter))
}

## direct labels for lineplots that do not overlap and do not go off
## the plot.
library(nlme)
library(lattice)
oldopt <- lattice.options(panel.error=NULL)
ratplot <-
  xyplot(weight~Time|Diet,BodyWeight,groups=Rat,type='l',layout=c(3,1))
## Using the default Positioning Method (maxvar.qp), the labels are
## placed on the side which is most spread out, so in multipanel
## plots they sometimes end up on different sides.
print(direct.label(ratplot))
## To put them on the same side, just manually specify the
## Positioning Method.
print(direct.label(ratplot,"last.qp"))

lattice.options(oldopt)
```

`direct.label.ggplot` *direct label ggplot*

Description

Direct label a ggplot2 grouped plot.

Usage

```
## S3 method for class 'ggplot'  
direct.label(p, method = NULL, debug = FALSE)
```

Arguments

<code>p</code>	The ggplot object.
<code>method</code>	Method for direct labeling as described in apply.method .
<code>debug</code>	Show debug output?

Value

The ggplot object with direct labels added.

Author(s)

Toby Dylan Hocking

`direct.label.trellis` *direct label trellis*

Description

Add direct labels to a grouped lattice plot. This works by parsing the trellis object returned by the high level plot function, and returning it with a new panel function that will plot direct labels using the specified method.

Usage

```
## S3 method for class 'trellis'  
direct.label(p, method = NULL, debug = FALSE)
```

Arguments

<code>p</code>	The lattice plot (result of a call to a high-level lattice function).
<code>method</code>	Method for direct labeling as described in apply.method .
<code>debug</code>	Show debug output?

Value

The lattice plot.

Author(s)

Toby Dylan Hocking

dl.combine

Combine output of several methods

Description

Apply several Positioning methods to the original data frame.

Usage

```
dl.combine(...)
```

Arguments

... Several Positioning Methods.

Value

A Positioning Method that returns the combined data frame after applying each specified Positioning Method.

Author(s)

Toby Dylan Hocking

Examples

```
## Simple example: label the start and endpoints
library(nlme)
library(lattice)
ratplot <- xyplot(weight~Time|Diet,BodyWeight,groups=Rat,type='l',layout=c(3,1))
##ratplot <- qplot(Time,weight,data=BodyWeight,group=Rat,colour=Rat,geom="line",facets=~Diet)
both <- dl.combine("first.points","last.points")
rat.both <- direct.label(ratplot,"both")
print(rat.both)
## grid.edit(gPath("panel-3-3",".*","GRID.dlgrob"),
##           method=list(cex=2,fontfamily="bold","both"),
##           grep=TRUE)
## can also do this by repeatedly calling direct.label
rat.repeated <-
  direct.label(direct.label(ratplot,"last.points"),"first.points")
print(rat.repeated)
## grid.edit(gPath("panel-3-5",".*","GRID.dlgrob.first.points"),
```

```

##          method=list(cex=2,fontfamily="bold","both"),
##          grep=TRUE)
if(require(ggplot2)){
  rp2 <- qplot(Time,weight,data=BodyWeight,geom="line",facets=~Diet,colour=Rat)
  print(direct.label(direct.label(rp2,"last.points"),"first.points"))
  print(direct.label(rp2,"both"))
}

mylars <- function
## Least angle regression algorithm for calculating lasso solutions.
(x,
  ## Matrix of predictor variables.
  y,
  ## Vector of responses.
  epsilon=1e-6
  ## If correlation < epsilon, we are done.
){
  xscale <- scale(x) # need to work with standardized variables
  b <- rep(0,ncol(x))# coef vector starts at 0
  names(b) <- colnames(x)
  ycor <- apply(xscale,2,function(xj)sum(xj*y))
  j <- which.max(ycor) # variables in active set, starts with most correlated
  alpha.total <- 0
  out <- data.frame()
  while(1){## lar loop
    xak <- xscale[,j] # current variables
    r <- y-xscale%*%b # current residual
    ## direction of parameter evolution
    delta <- solve(t(xak)%*%xak)%*%t(xak)%*%r
    ## Current correlations (actually dot product)
    intercept <- apply(xscale,2,function(xk)sum(r*xk))
    ## current rate of change of correlations
    z <- xak%*%delta
    slope <- apply(xscale,2,function(xk)-sum(z*xk))
    ## store current values of parameters and correlation
    out <- rbind(out,data.frame(variable=colnames(x),
                                coef=b,
                                corr=abs(intercept),
                                alpha=alpha.total,
                                arclength=sum(abs(b)),
                                coef.unscaled=b/attr(xscale,"scaled:scale")))
    if(sum(abs(intercept)) < epsilon)#corr==0 so we are done
      return(transform(out,s=arclength/max(arclength)))
    ## If there are more variables we can enter into the regression,
    ## then see which one will cross the highest correlation line
    ## first, and record the alpha value of where the lines cross.
    d <- data.frame(slope,intercept)
    d[d$intercept<0,] <- d[d$intercept<0,]*-1
    d0 <- data.frame(d[j[1],])# highest correlation line
    d2 <- data.frame(rbind(d,-d),variable=names(slope))#reflected lines
    ## Calculation of alpha for where lines cross for each variable
    d2$alpha <- (d0$intercept-d2$intercept)/(d2$slope-d0$slope)
    subd <- d2[(!d2$variable%in%colnames(x)[j])&d2$alpha>epsilon,]
  }
}

```



```

subd <- subd[which.min(subd$alpha),]
nextvar <- subd$variable
alpha <- if(nrow(subd))subd$alpha else 1
## If one of the coefficients would hit 0 at a smaller alpha
## value, take it out of the regression and continue.
hit0 <- xor(b[j]>0,delta>0)&b[j]!=0
alpha0 <- -b[j][hit0]/delta[hit0]
takeout <- length(alpha0)&&min(alpha0) < alpha
if(takeout){
  i <- which.min(alpha0)
  alpha <- alpha0[i]
}
b[j] <- b[j]+alpha*delta ## evolve parameters
alpha.total <- alpha.total+alpha
## add or remove a variable from the active set
j <- if(takeout)j[j!=which(names(i)==colnames(x))]]
  else c(j,which(nextvar==colnames(x)))
}
}

## Calculate lasso path, plot and label
mylasso <- dl.combine(lasso.labels, last.qp)

if(require(ElemStatLearn)){
  pros <- subset(prostate,select=-train,train==TRUE)
  ycol <- which(names(pros)=="lpsa")
  x <- as.matrix(pros[-ycol])
  y <- unlist(pros[ycol])
  res <- mylars(x,y)
  P <- xyplot(coef~arclength,res,groups=variable,type="l")
  plot(direct.label(P,"mylasso"))
  if(require(ggplot2)){
    p <- ggplot(res,aes(arclength,coef,colour=variable))+
      geom_line(aes(group=variable))
    direct.label(p,"mylasso")
  }
}

if(require(lars)){
  data(diabetes,envir=environment())
  dres <- with(diabetes,mylars(x,y))
  P <- xyplot(coef~arclength,dres,groups=variable,type="l")
  plot(direct.label(P,"mylasso"))
}

```

dl.jitter

dl.jitter

Description

Jitter the label positions.

Usage

```
dl.jitter(d, ...)
```

Arguments

```
d
...
```

Author(s)

Toby Dylan Hocking

dl.move

Manually move a direct label

Description

Sometimes there is 1 label that is placed oddly by another Positioning Function. This function can be used to manually place that label in a good spot.

Usage

```
dl.move(group, x, y, ...)
```

Arguments

group	Group to change.
x	Horizontal position of the new label.
y	Vertical position of the new label. If missing(y) and !missing(x) then we will calculate a new y value using linear interpolation.
...	Variables to change for the specified group

Value

A Positioning Function that moves a label into a good spot.

Author(s)

Toby Dylan Hocking

Examples

```

if(require(ggplot2)){
  library(lattice)
  scatter <- xyplot(jitter(cty)~jitter(hwy),mpg,groups=class,aspect=1)
  dlcompare(list(scatter),
            list("extreme.grid",
                `+dl.move`=list(extreme.grid,dl.move("suv",15,15))))
  p <- qplot(log10(gamma),rate,data=svmtrain,group=data,colour=data,
            geom="line",facets=replicate~nu)
  adjust.kif <- dl.move("KIF11",-0.9,hjust=1,vjust=1)
  dlcompare(list(p+xlim(-8,7)),
            list("last.points",
                `+dl.move`=list(last.points,adjust.kif)))
}

```

dl.summarize

*dl summarize***Description**

summarize which preserves important columns for direct labels.

Usage

```
dl.summarize(OLD, ...)
```

Arguments

OLD data frame
 ...

Author(s)

Toby Dylan Hocking

dl.trans

*Direct label data transform***Description**

Make a function that transforms the data. This is for conveniently making a function that calls transform on the data frame, with the arguments provided. See examples.

Usage

```
dl.trans(...)
```

Arguments

... Arguments to pass to transform.

Value

A Positioning Function.

Author(s)

Toby Dylan Hocking

Examples

```
complicated <- list(dl.trans(x=x+10),
                    gaply.fun(d[-2,]),
                    rot=c(30,180))

library(lattice)
direct.label(dotplot(VADeaths, type="o"), complicated, TRUE)
```

dlcompare

Direct label comparison plot

Description

Compare several plots and/or label placement methods. This creates a custom grid graphics display based on lattice and/or ggplot2 output. Plots will be on the columns and positioning methods will be on the rows.

Usage

```
dlcompare(plots, pos.funs, rects = TRUE, row.items = "plots",
          debug = FALSE)
```

Arguments

plots	List of ggplot2 or lattice plots. List names will be used to annotate the plot.
pos.funs	List of label placement methods to apply to each plot. List names, or function names if specified as character strings, will be used to annotate the plot.
rects	Draw rectangles around each plot, creating a grid?
row.items	If "plots" then put plots on the rows and method on the columns. Otherwise, do the opposite.
debug	Show debug output?

Author(s)

Toby Dylan Hocking

Examples

```

library(lattice)
oldopt <- lattice.options(panel.error=NULL)

## Compare two plots of the same data using lattice and ggplot2.
deaths.by.sex <- list(male=mdeaths, female=fdeaths)
deaths.list <- list()
for(sex in names(deaths.by.sex)){
  deaths.ts <- deaths.by.sex[[sex]]
  deaths.list[[sex]] <-
    data.frame(year=as.numeric(time(deaths.ts)),
               sex,
               deaths=as.integer(deaths.ts))
}
deaths <- do.call(rbind, deaths.list)
death.plot.list <-
  list(lattice=xyplot(deaths~year,deaths,groups=sex,type="l"))
if(require(ggplot2)){
  death.plot.list$ggplot2 <-
    qplot(year,deaths,data=deaths,colour=sex,geom="line")
}

if(names(dev.cur())!="postscript"){##to avoid error on pkg check.
  ## Use some exotic labeling options with different rotation, font
  ## face, family, and alpha transparency.
  exotic <- list("last.points",
                rot=c(0,180),
                fontsize=c(10,20),
                fontface=c("bold","italic"),
                fontfamily=c("mono","serif"),
                alpha=c(0.25,1))
  dlcompare(death.plot.list, list(exotic))
}

lattice.options(oldopt)

## Compare a legend with direct labels on the same plot.
library(nlme)
if(require(ggplot2)){
  ggrat <- qplot(Time,weight,data=BodyWeight,
                colour=Rat,geom="line",facets=~Diet)
  pfun <- list("legend","direct labels"="last.qp")
  dlcompare(list(ggrat),pfun,rects=FALSE,row.items="posfun")
}

```

Description

Positioning Methods for direct labels are supposed to work with only certain plot types. Each Positioning Method is defined in R/file.R and plot examples are found in tests/doc/file/*.R so that we can automatically assemble a database of example plots from the code.

Usage

```
dldoc(pkgdir = "..")
```

Arguments

pkgdir Package directory root.

Value

Matrix of lists describing example plots and matching builtin Positioning Methods.

Author(s)

Toby Dylan Hocking

dlgrob

dlgrob

Description

Make a grid grob that will draw direct labels.

Usage

```
dlgrob(data, method, debug = FALSE, axes2native = identity,
      ...)
```

Arguments

data Data frame including points to plot in native coordinates.
 method Positioning Method.
 debug
 axes2native
 ...

Author(s)

Toby Dylan Hocking

`draw.polygons`*draw polygons*

Description

Draw polygons around label positions.

Usage

```
draw.polygons(d, ...)
```

Arguments

d

...

Author(s)

Toby Dylan Hocking

`draw.rects`*draw rects*

Description

Positioning Function that draws boxes around label positions. Need to have previously called `calc.boxes`. Does not edit the data frame.

Usage

```
draw.rects(d, ...)
```

Arguments

d

...

Author(s)

Toby Dylan Hocking

drawDetails.dlgrob	<i>drawDetails dlgrob</i>
--------------------	---------------------------

Description

Process data points using the Positioning Method and draw the resulting direct labels. This is called for every panel with direct labels, every time the plot window is resized.

Usage

```
## S3 method for class 'dlgrob'
drawDetails(x, recording)
```

Arguments

x	<p>The dlgrob list object. x\$method should be a Positioning Method list and x\$data should be a data.frame with the following variables:</p> <p>x,y numeric horizontal and vertical positions of direct labels, in native units. These are converted to cm units before applying the Positioning Method.</p> <p>groups factor that indices the different groups, and colour indicates the corresponding group colour.</p> <p>hjust and vjust (optional) numeric values usually in [0,1] that control the justification of the text label relative to the x,y position.</p> <p>rot (optional) numeric value in [0,360] that specifies the degrees which the text should be rotated.</p> <p>cex, alpha, fontface, fontfamily (optional) passed to gpar.</p> <p>Additionally, x\$debug should be set to TRUE or FALSE, and x\$axestonative should be a function that converts units shown on the axes to native units of x\$data[,c("x","y")].</p>
recording	

Author(s)

Toby Dylan Hocking

edges.to.outside	<i>edges to outside</i>
------------------	-------------------------

Description

Given a list of edges from the convex or alpha hull, and a list of cluster centers, calculate a point near to each cluster on the outside of the hull.

Usage

```
edges.to.outside(edges, centers, debug = FALSE, ...)
```

Arguments

```
edges
centers
debug
...
```

Author(s)

Toby Dylan Hocking

empty.grid

empty grid

Description

Label placement method for scatterplots that ensures labels are placed in different places. A grid is drawn over the whole plot. Each cluster is considered in sequence and assigned to the point on this grid which is closest to the point given by the input data points. Makes use of `attr(d,"orig.data")`.

Usage

```
empty.grid(d, debug = FALSE, ...)
```

Arguments

d	Data frame of target points on the scatterplot for each label.
debug	Show debugging info on the plot?
...	ignored.

Value

Data frame with columns groups x y, 1 line for each group, giving the positions on the grid closest to each cluster.

Author(s)

Toby Dylan Hocking

`enlarge.box`*enlarge box*

Description

Make text bounding box larger by some amount.

Usage

```
enlarge.box(d, ...)
```

Arguments

`d`

`...`

Author(s)

Toby Dylan Hocking

`extract.plot`*Extract plot and definition for documentation*

Description

Given an R code file, execute it, store the definition, and save the resulting plot in a variable.

Usage

```
extract.plot(f)
```

Arguments

`f` R code file with plot example.

Author(s)

Toby Dylan Hocking

extract.posfun	<i>Extract Positioning Method for documentation</i>
----------------	---

Description

Use inlinedocs to extract comments and definitions from code, then for each item found add the value and its name to the list.

Usage

```
extract.posfun(f)
```

Arguments

f	R code file, which should contain only Positioning Methods that can be used with examples defined in the doc/ subdirectory with the same name.
---	--

Value

List of lists, each of which describes one Positioning Method defined in f.

Author(s)

Toby Dylan Hocking

extreme.grid	<i>extreme grid</i>
--------------	---------------------

Description

Label each point cloud near the extremities of the plot region.

Usage

```
"extreme.grid"
```

extreme.points	<i>extreme points</i>
----------------	-----------------------

Description

Label the points furthest from the middle for each group.

Usage

```
extreme.points(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

far.from.others.borders	<i>far from others borders</i>
-------------------------	--------------------------------

Description

Find the point on each curve which maximizes the distance to the plot border or to another curve.

Usage

```
far.from.others.borders(all.groups, ..., debug = FALSE)
```

Arguments

all.groups
...
debug

Author(s)

Toby Dylan Hocking

filltemplate	<i>filltemplate</i>
--------------	---------------------

Description

Fill in occurrences of OBJ\$item in the file template with the value in R of L\$item.

Usage

```
filltemplate(L, template)
```

Arguments

L
template

Author(s)

Toby Dylan Hocking

first.bumpup	<i>first bumpup</i>
--------------	---------------------

Description

Label first points, bumping labels up if they collide.

Usage

```
"first.bumpup"
```

first.points	<i>first points</i>
--------------	---------------------

Description

Positioning Method for the first of a group of points.

Usage

```
first.points(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

first.polygons	<i>first polygons</i>
----------------	-----------------------

Description

Draw a speech polygon to the first point.

Usage

"first.polygons"

first.qp	<i>first qp</i>
----------	-----------------

Description

Label first points from QP solver that ensures labels do not collide.

Usage

"first.qp"

gapply

gapply

Description

apply a Positioning Method to every group. works like ddply from plyr package, but the grouping column is always called groups, and the Positioning Method is not necessarily a function (but can be).

Usage

```
gapply(d, method, ..., groups = "groups")
```

Arguments

d	data frame with column groups.
method	Positioning Method to apply to every group separately.
...	additional arguments, passed to Positioning Methods.
groups	can also be useful for piece column.

Value

data frame of results after applying FUN to each group in d.

Author(s)

Toby Dylan Hocking

gapply.fun

Direct label groups independently

Description

Makes a function you can use to specify the location of each group independently.

Usage

```
gapply.fun(expr)
```

Arguments

expr	Expression that takes a subset of the d data frame, with data from only a single group, and returns the direct label position.
------	--

Value

A Positioning Function.

Author(s)

Toby Dylan Hocking

Examples

```
complicated <- list(dl.trans(x=x+10),
                    gapply.fun(d[-2,]),
                    rot=c(30,180))

library(lattice)
direct.label(dotplot(VADeaths,type="o"),complicated,TRUE)
```

GeomDl	<i>GeomDl</i>
--------	---------------

Description

ggproto object implementing direct labels.

Usage

"GeomDl"

geom_dl	<i>geom dl</i>
---------	----------------

Description

Geom that will plot direct labels.

Usage

```
geom_dl(mapping = NULL, data = NULL, ..., method = stop("must specify method= argument"),
        debug = FALSE, na.rm = TRUE, parse = FALSE, stat = "identity",
        position = "identity", inherit.aes = TRUE)
```


Arguments

mapping	aes(label=variable_that_will_be_used_as_groups_in_Positioning_Methods).
data	data.frame to start with for direct label computation.
...	passed to params.
method	Positioning Method for direct label placement, passed to apply.method.
debug	Show directlabels debugging output?
na.rm	passed to params.
parse	parse text labels as plotmath expressions? not yet supported, but I would be open to accepting a PR if somebody wants to implement that.
stat	passed to layer.
position	passed to layer.
inherit.aes	inherit aes from global ggplot definition?

Author(s)

Toby Dylan Hocking

Examples

```
if(require(ggplot2)){
  vad <- as.data.frame.table(VADeaths)
  names(vad) <- c("age", "demographic", "deaths")
  ## color + legend
  leg <- ggplot(vad, aes(deaths, age, colour=demographic))+
    geom_line(aes(group=demographic))+
    xlim(8, 80)
  print(direct.label(leg, list("last.points", rot=30)))
  ## this is what direct.label is doing internally:
  labeled <- leg+
    geom_dl(aes(label=demographic), method=list("last.points", rot=30))+
    scale_colour_discrete(guide="none")
  print(labeled)
  ## no color, just direct labels!
  p <- ggplot(vad, aes(deaths, age))+
    geom_line(aes(group=demographic))+
    geom_dl(aes(label=demographic), method="top.qp")
  print(p)
  ## add color:
  p+aes(colour=demographic)+
    scale_colour_discrete(guide="none")
  ## add linetype:
  p+aes(linetype=demographic)+
    scale_linetype(guide="none")
  ## no color, just direct labels
  library(nlme)
  bwbase <- ggplot(BodyWeight, aes(Time, weight, label=Rat))+
    geom_line(aes(group=Rat))+
    facet_grid(.~Diet)
```

```

bw <- bwbase+geom_dl(method="last.qp")
print(bw)
## add some more direct labels
bw2 <- bw+geom_dl(method="first.qp")
print(bw2)
## add color
colored <- bw2+aes(colour=Rat)+
  scale_colour_discrete(guide="none")
print(colored)
## or just use direct.label if you use color:
direct.label(bwbase+aes(colour=Rat),dl.combine("first.qp","last.qp"))

## iris data example
giris <- ggplot(iris,aes(Petal.Length,Sepal.Length))+
  geom_point(aes(shape=Species))
giris.labeled <- giris+
  geom_dl(aes(label=Species),method="smart.grid")+
  scale_shape_manual(values=c(setosa=1, virginica=6, versicolor=3),
    guide="none")
##png("~/R/directlabels/www/scatter-bw-ggplot2.png",h=503,w=503)
print(giris.labeled)
##dev.off()
}

```

get.means

get means

Description

Positioning Function for the mean of each cluster of points.

Usage

```
get.means(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

getLegendVariables	<i>getLegendVariables</i>
--------------------	---------------------------

Description

get the aes which are variable in one legend.

Usage

```
getLegendVariables(mb)
```

Arguments

mb

Author(s)

Toby Dylan Hocking

ignore.na	<i>ignore na</i>
-----------	------------------

Description

Remove rows for which either x or y is NA

Usage

```
ignore.na(d, ...)
```

Arguments

d

...

Author(s)

Toby Dylan Hocking

in1box

in1box

Description

Calculate how many points fall in a box.

Usage

```
in1box(p, box)
```

Arguments

p
box

Author(s)

Toby Dylan Hocking

in1which

in1which

Description

Calculate which points fall in a box.

Usage

```
in1which(p, box)
```

Arguments

p data frame of points with columns x and y and many rows.
box data frame of 1 row with columns left right top bottom.

Author(s)

Toby Dylan Hocking

inside

inside

Description

Calculate for each box how many points are inside.

Usage

```
inside(boxes, points)
```

Arguments

boxes	Data frame of box descriptions, each row is 1 box, need columns left right top bottom.
points	Data frame of points, each row is 1 point, need columns x y.

Value

Vector of point counts for each box.

Author(s)

Toby Dylan Hocking

iris.l1.cluster

Clustering of the iris data with the l1 clusterpath

Description

The l1 clustering algorithm from the clusterpath package was applied to the iris dataset and the breakpoints in the solution path are stored in this data frame.

Usage

```
data(iris.l1.cluster)
```

Format

A data frame with 9643 observations on the following 8 variables.

row a numeric vector: row of the original iris data matrix

Species a factor with levels setosa versicolor virginica: Species from corresponding row

alpha a numeric vector: the value of the optimal solution.

lambda a numeric vector: the regularization parameter (ie point in the path).

col a factor with levels Sepal.Length Sepal.Width Petal.Length Petal.Width: column from the original iris data.

gamma a factor with levels 0: parameter from clustering.

norm a factor with levels 1 parameter from clustering.

solver a factor with levels path algorithm used for clustering.

Source

clusterpath package

References

clusterpath article

Examples

```
data(iris.l1.cluster,package="directlabels")
iris.l1.cluster$y <- iris.l1.cluster$alpha
if(require(ggplot2)){
  p <- ggplot(iris.l1.cluster,aes(lambda,y,group=row,colour=Species))+
    geom_line(alpha=1/4)+
    facet_grid(col~.)
  p2 <- p+xlim(-0.0025,max(iris.l1.cluster$lambda))
  print(direct.label(p2,list(first.points,get.means)))
}
```

label.endpoints	<i>label endpoints</i>
-----------------	------------------------

Description

Make a Positioning Method that labels a certain x value.

Usage

```
label.endpoints(FUN, HJUST)
```

Arguments

FUN	FUN(d\$x) should return an index of which point to label. for example you can use which.min or which.max.
HJUST	hjust of the labels.

Value

A Positioning Method like first.points or last.points.

Author(s)

Toby Dylan Hocking

label.pieces

*label pieces***Description**

Make a Positioning Method that will, for every piece, select points and assign a vjust value.

Usage

label.pieces(FUN, VJUST)

Arguments

FUN

VJUST

Author(s)

Toby Dylan Hocking

lasso.labels

*lasso labels***Description**

Label points at the zero before the first nonzero y value.

Usage

"lasso.labels"

last.bumpup

*last bumpup***Description**

Label last points, bumping labels up if they collide.

Usage

"last.bumpup"

last.points	<i>last points</i>
-------------	--------------------

Description

Positioning Method for the last of a group of points.

Usage

```
last.points(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

last.polygons	<i>last polygons</i>
---------------	----------------------

Description

Draw a speech polygon to the last point.

Usage

```
"last.polygons"
```

last.qp	<i>last qp</i>
---------	----------------

Description

Label last points from QP solver that ensures labels do not collide.

Usage

```
"last.qp"
```

lattice.translators	<i>lattice translators</i>
---------------------	----------------------------

Description

Some lattice plot functions do some magic in the background to translate the data you give them into the data points that are plotted onscreen. We have to replicate this magic in native coordinate space before applying the Positioning Method in cm space. These functions accomplish this translation.

Usage

```
"lattice.translators"
```

legends2hide	<i>legends2hide</i>
--------------	---------------------

Description

Extract guides to hide from a ggplot.

Usage

```
legends2hide(p)
```

Arguments

p

Value

NULL if no legends with colour or fill to hide.

Author(s)

Toby Dylan Hocking

lines2

lines2

Description

Positioning Method for 2 groups of longitudinal data. One curve is on top of the other one (on average), so we label the top one at its maximal point, and the bottom one at its minimal point. Vertical justification is chosen to minimize collisions with the other line. This may not work so well for data with high variability, but then again lineplots may not be the best for these data either.

Usage

```
lines2(d, offset = 0.3, ...)
```

Arguments

d	The data.
offset	Offset from 0 or 1 for the vjust values.
...	ignored.

Author(s)

Toby Dylan Hocking

make.tiebreaker

make tiebreaker

Description

Make a tiebreaker function that can be used with qp.labels.

Usage

```
make.tiebreaker(x.var, tiebreak.var)
```

Arguments

x.var
tiebreak.var

Author(s)

Toby Dylan Hocking

maxvar.points	<i>maxvar points</i>
---------------	----------------------

Description

Do first or last, whichever has points most spread out.

Usage

```
maxvar.points(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

maxvar.qp	<i>maxvar qp</i>
-----------	------------------

Description

Label first or last points, whichever are more spread out, and use a QP solver to make sure the labels do not collide.

Usage

```
"maxvar.qp"
```

merge_recurse	<i>merge recurse</i>
---------------	----------------------

Description

Copied from reshape.

Usage

```
merge_recurse(dfs, ...)
```

Arguments

dfs

...

Author(s)

Toby Dylan Hocking

midrange	<i>midrange</i>
----------	-----------------

Description

Point halfway between the min and max

Usage

```
midrange(x)
```

Arguments

x

Author(s)

Toby Dylan Hocking

normal.l2.cluster

*Clustering of some normal data in 2d with the l2 clusterpath***Description**

The l2 clustering algorithm from the clusterpath package was applied to some randomly generated data in 2 dimensions, and the solutions found using the descent algorithm are stored in this data frame.

Usage

```
data(normal.l2.cluster)
```

Format

The format is: List of 2 \$ pts : 'data.frame': 320 obs. of 3 variables: ..\$ class: Factor w/ 8 levels "1","2","3","4",...: 1 1 1 1 1 1 1 1 1\$ x : num [1:320] -2.73 -3.63 -2.13 -1.27 -2.98\$ y : num [1:320] -3.89 -3.43 -3.42 -3.17 -2.75 ... \$ path:Classes 'l2', 'clusterpath' and 'data.frame': 21760 obs. of 7 variables: ..\$ x : num [1:21760] -2.73 -3.63 -2.13 -1.27 -2.98\$ y : num [1:21760] -3.89 -3.43 -3.42 -3.17 -2.75\$ lambda: num [1:21760] 0 0 0 0 0 0 0 0 0\$ row : Factor w/ 320 levels "1","2","3","4",...: 1 2 3 4 5 6 7 8 9 10\$ gamma : Factor w/ 1 level "0.1": 1 1 1 1 1 1 1 1 1\$ norm : Factor w/ 1 level "2": 1 1 1 1 1 1 1 1 1\$ solver: Factor w/ 1 level "descent.nocheck": 1 1 1 1 1 1 1 1 1- attr(*, "data")= num [1:320, 1:2] -2.73 -3.63 -2.13 -1.27 -2.98- attr(*, "dimnames")=List of 2\$: NULL\$: chr [1:2] "x" "y" ..- attr(*, "alphacolnames")= chr [1:2] "x" "y" ..- attr(*, "weight.pts")= num [1:320, 1:2] -2.73 -3.63 -2.13 -1.27 -2.98- attr(*, "dimnames")=List of 2\$: NULL\$: chr [1:2] "x" "y"

Source

clusterpath package

References

clusterpath article

Examples

```
data(normal.l2.cluster)
if(require(ggplot2)){
  p <- ggplot(normal.l2.cluster$path, aes(x,y))+
    geom_path(aes(group=row), colour="grey")+
    geom_point(aes(size=lambda), colour="grey")+
    geom_point(aes(colour=class), data=normal.l2.cluster$pts)+
    coord_equal()
  print(direct.label(p))
}
```

only.unique.vals	<i>only unique vals</i>
------------------	-------------------------

Description

Create a 1-row data.frame consisting of only the columns for which there is only 1 unique value.

Usage

```
only.unique.vals(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

outside.ahull	<i>outside ahull</i>
---------------	----------------------

Description

Calculate closest point on the alpha hull with size of the boxes, and put it outside that point.

Usage

```
outside.ahull(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

outside.chull	<i>outside chull</i>
---------------	----------------------

Description

Calculate closest point on the convex hull and put it outside that point. Assume d is the center for each point cloud and then use orig.data to calculate hull.

Usage

```
outside.chull(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

panel.superpose.dl	<i>panel superpose dl</i>
--------------------	---------------------------

Description

Call panel.superpose for the data points and then for the direct labels. This is a proper lattice panel function that behaves much like panel.superpose.

Usage

```
panel.superpose.dl(x, y = NULL, subscripts, groups,  
  panel.groups, method = NULL, .panel.superpose = lattice::panel.superpose,  
  type = "p", debug = FALSE, ...)
```

Arguments

x	Vector of x values.
y	Vector of y values.
subscripts	Subscripts of x,y,groups.
groups	Vector of group ids.
panel.groups	To be parsed for default labeling method, and passed to panel.superpose.
method	Positioning Method for direct labeling. NULL indicates to choose a Positioning Method based on the panel.groups function.

<code>.panel.superpose</code>	The panel function to use for drawing data points.
<code>type</code>	Plot type, used for default method dispatch.
<code>debug</code>	passed to <code>dlgrob</code> .
<code>...</code>	passed to real panel function, and to translator.

Author(s)

Toby Dylan Hocking

Examples

```

loci <- data.frame(ppp=c(rbeta(800,10,10),rbeta(100,0.15,1),rbeta(100,1,0.15)),
                    type=factor(c(rep("NEU",800),rep("POS",100),rep("BAL",100))))
## 3 equivalent ways to make the same plot:
library(lattice)
print(direct.label( ## most user-friendly
                  densityplot(~ppp,loci,groups=type,n=500)
                  ))
print(direct.label( ## exactly the same as above but with specific panel fns
                  densityplot(~ppp,loci,groups=type,n=500,
                              panel=lattice::panel.superpose,
                              panel.groups="panel.densityplot")
                  ))
## using panel.superpose.dl as the panel function automatically adds
## direct labels
print(densityplot(~ppp,loci,groups=type,n=500,
                  panel=panel.superpose.dl,panel.groups="panel.densityplot"))

## Exploring custom panel and panel.groups functions
library(nlme)
## Say we want to use a simple linear model to explain rat body weight:
fit <- lm(weight~Time+Diet+Rat,BodyWeight)
bw <- BodyWeight
bw$.fitted <- predict(fit,BodyWeight)
## lots of examples to come, all with these arguments:
ratxy <- function(...){
  xyplot(weight~Time|Diet,bw,groups=Rat,type="l",layout=c(3,1),...)
}
## No custom panel functions:
##regular <- ratxy(par.settings=simpleTheme(col=c("red","black")))
regular <- ratxy()
print(regular) ## normal lattice plot
print(direct.label(regular)) ## with direct labels

## The direct label panel function panel.superpose.dl can be used to
## display direct labels as well:
print(ratxy(panel=panel.superpose.dl,panel.groups="panel.xyplot"))
print(ratxy(panel=function(...)
            panel.superpose.dl(panel.groups="panel.xyplot",...)))

## Not very user-friendly, since default label placement is

```



```

## impossible, but these should work:
print(ratxy(panel=panel.superpose.dl,panel.groups=panel.xyplot,
            method=first.points))
print(ratxy(panel=function(...)
            panel.superpose.dl(panel.groups=panel.xyplot,...),
            method=first.points))

## Custom panel.groups functions:
## This panel.groups function will display the model fits:
panel.model <- function(x,subscripts,col.line,...){
  panel.xyplot(x=x,subscripts=subscripts,col.line=col.line,...)
  llines(x,bw[subscripts,".fitted"],col=col.line,lty=2)
}
pg <- ratxy(panel=lattice::panel.superpose,panel.groups=panel.model)
print(pg)
## If you use panel.superpose.dl with a custom panel.groups function,
## you need to manually specify the Positioning Method, since the
## name of panel.groups is used to infer a default:
print(direct.label(pg,method="first.qp"))
print(ratxy(panel=panel.superpose.dl,panel.groups="panel.model",
            method="first.qp"))

## Custom panel function that draws a box around values:
panel.line1 <- function(ps=lattice::panel.superpose){
  function(y,...){
    panel.abline(h=range(y))
    ps(y=y,...)
  }
}
custom <- ratxy(panel=panel.line1())
print(custom)
print(direct.label(custom))
## Alternate method, producing the same results, but using
## panel.superpose.dl in the panel function. This is useful for direct
## label plots where you use several datasets.
print(ratxy(panel=panel.line1(panel.superpose.dl),panel.groups="panel.xyplot"))

## Lattice plot with custom panel and panel.groups functions:
both <- ratxy(panel=panel.line1(),panel.groups="panel.model")
print(both)
print(direct.label(both,method="first.qp"))
print(ratxy(panel=panel.line1(panel.superpose.dl),
            panel.groups=panel.model,method="first.qp"))

```

Description

<https://github.com/tdhock/directlabels/issues/2> CRAN won't complain about this version of :::

Usage

```
pkgFun(fun, pkg = "ggplot2")
```

Arguments

fun

pkg

Author(s)

Toby Dylan Hocking

<code>polygon.method</code>	<i>polygon method</i>
-----------------------------	-----------------------

Description

Make a Positioning Method that places non-overlapping speech polygons at the first or last points.

Usage

```
polygon.method(method, space, data.col, na.col)
```

Arguments

method

space

data.col

na.col

Author(s)

Toby Dylan Hocking

Description

When adding direct labels to a grouped plot, label placement can be specified using a Positioning Method (or a list of them), of the form `function(d,...)`, where `d` is a data frame of the points to plot, with columns `x y groups`. The job of the Positioning Method(s) is to return the position of each direct label you want to plot as a data frame, with 1 row for each label. Thus normally a Positioning Method will return 1 row for each group. Several built-in Positioning Methods are discussed below, but you can also create your own, either from scratch or by using `dl.indep` and `dl.trans`.

Author(s)

Toby Dylan Hocking <toby.hocking@inria.fr>

Examples

```
## Not run:
### contourplot Positioning Methods
for(p in list({
  ## Example from help(contourplot)
  require(stats)
  require(lattice)
  attach(environmental)
  ozo.m <- loess((ozone^(1/3)) ~ wind * temperature * radiation,
    parametric = c("radiation", "wind"), span = 1, degree = 2)
  w.marginal <- seq(min(wind), max(wind), length.out = 50)
  t.marginal <- seq(min(temperature), max(temperature), length.out = 50)
  r.marginal <- seq(min(radiation), max(radiation), length.out = 4)
  wtr.marginal <- list(wind = w.marginal, temperature = t.marginal,
    radiation = r.marginal)
  grid <- expand.grid(wtr.marginal)
  grid[, "fit"] <- c(predict(ozo.m, grid))
  detach(environmental)
  library(ggplot2)
  p <- ggplot(grid, aes(wind, temperature, z=fit))+
    stat_contour(aes(colour=..level..))+
    facet_wrap(~radiation)

},
{
  ## example from help(stat_contour)
  library(reshape2)
  volcano3d <- melt(volcano)
  names(volcano3d) <- c("x", "y", "z")
  library(ggplot2)
  p <- ggplot(volcano3d, aes(x, y, z = z))+
    stat_contour(aes(colour = ..level..))
})){
```

```

    print(direct.label(p,"bottom.pieces"))
    print(direct.label(p,"top.pieces"))
  }

### densityplot Positioning Methods
for(p in list({
  data(Chem97,package="mlmRev")
  library(lattice)
  p <- densityplot(~gcsescore|gender,Chem97,
    groups=factor(score),layout=c(1,2),
    n=500,plot.points=FALSE)
},
{
  library(reshape2)
  iris2 <- melt(iris,id="Species")
  library(lattice)
  p <- densityplot(~value|variable,iris2,groups=Species,scales="free")
},
{
  loci <- data.frame(ppp=c(rbeta(800,10,10),rbeta(100,0.15,1),rbeta(100,1,0.15)),
    type=factor(c(rep("NEU",800),rep("POS",100),rep("BAL",100))))
  library(ggplot2)
  p <- qplot(ppp,data=loci,colour=type,geom="density")
})){
  print(direct.label(p,"top.bumptime"))
  print(direct.label(p,"top.bumpup"))
  print(direct.label(p,"top.points"))
}

### dotplot Positioning Methods
for(p in list({
  library(lattice)
  p <- dotplot(VADeaths,xlim=c(8,85),type="o")
},
{
  vad <- as.data.frame.table(VADeaths)
  names(vad) <- c("age","demographic","deaths")
  library(ggplot2)
  p <- qplot(deaths,age,data=vad,group=demographic,geom="line",colour=demographic)+
    xlim(8,80)
})){
  print(direct.label(p,"angled.endpoints"))
  print(direct.label(p,"top.qp"))
}

### lineplot Positioning Methods
for(p in list({
  data(BodyWeight,package="nlme")
  library(lattice)
  p <- xyplot(weight~Time|Diet,BodyWeight,groups=Rat,type='l',
    layout=c(3,1),xlim=c(-10,75))
},
{

```

```

data(Chem97,package="mlmRev")
library(lattice)
p <- qqmath(~gcsescore|gender,Chem97,groups=factor(score),
            type=c('l','g'),f.value=ppoints(100))
},
{
data(Chem97,package="mlmRev")
library(lattice)
p <- qqmath(~gcsescore,Chem97,groups=gender,
            type=c("l","g"),f.value=ppoints(100))
},
{
data(prostate,package="ElemStatLearn")
pros <- subset(prostate,select==train,train==TRUE)
ycol <- which(names(pros)== "lpsa")
x <- as.matrix(pros[-ycol])
y <- pros[[ycol]]
library(lars)
fit <- lars(x,y,type="lasso")
beta <- scale(coef(fit),FALSE,1/fit$normx)
arclength <- rowSums(abs(beta))
library(reshape2)
path <- data.frame(melt(beta),arclength)
names(path)[1:3] <- c("step","variable","standardized.coef")
library(ggplot2)
p <- ggplot(path,aes(arclength,standardized.coef,colour=variable))+
  geom_line(aes(group=variable))+
  ggtitle("LASSO path for prostate cancer data calculated using the LARS")+
  xlim(0,20)
},
{
data(projectionSeconds, package="directlabels")
p <- ggplot(projectionSeconds, aes(vector.length/1e6))+
  geom_ribbon(aes(ymin=min, ymax=max,
                fill=method, group=method), alpha=1/2)+
  geom_line(aes(y=mean, group=method, colour=method))+
  ggtitle("Projection Time against Vector Length (Sparsity = 10
  guides(fill="none")+
  ylab("Runtime (s)")
},
{
## complicated ridge regression lineplot ex. fig 3.8 from Elements of
## Statistical Learning, Hastie et al.
myridge <- function(f,data,lambdac=c(exp(-seq(-15,15,l=200)),0)){
  require(MASS)
  require(reshape2)
  fit <- lm.ridge(f,data,lambdac=lambdac)
  X <- data[-which(names(data)==as.character(f[[2]]))]
  Xs <- svd(scale(X)) ## my d's should come from the scaled matrix
  dsq <- Xs$d^2
  ## make the x axis degrees of freedom
  df <- sapply(lambdac,function(l)sum(dsq/(dsq+l)))
  D <- data.frame(t(fit$coef),lambdac,df) # scaled coefs

```

```

molt <- melt(D,id=c("lambda","df"))
## add in the points for df=0
limpts <- transform(subset(molt,lambda==0),lambda=Inf,df=0,value=0)
rbind(limpts,molt)
}
data(prostate,package="ElemStatLearn")
pros <- subset(prostate,train==TRUE,select=-train)
m <- myridge(lpsa~.,pros)
library(lattice)
p <- xyplot(value~df,m,groups=variable,type="o",pch="+",
  panel=function(...){
    panel.xyplot(...)
    panel.abline(h=0)
    panel.abline(v=5,col="grey")
  },
  xlim=c(-1,9),
  main="Ridge regression shrinks least squares coefficients",
  ylab="scaled coefficients",
  sub="grey line shows coefficients chosen by cross-validation",
  xlab=expression(df(lambda)))
},
{
library(ggplot2)
tx <- time(mdeaths)
Time <- ISOdate(floor(tx),round(tx
uk.lung <- rbind(data.frame(Time,sex="male",deaths=as.integer(mdeaths)),
  data.frame(Time,sex="female",deaths=as.integer(fdeaths)))
p <- qplot(Time,deaths,data=uk.lung,colour=sex,geom="line")+
  xlim(ISOdate(1973,9,1),ISOdate(1980,4,1))
)){
  print(direct.label(p,"angled.bboxes"))
  print(direct.label(p,"first.bumpup"))
  print(direct.label(p,"first.points"))
  print(direct.label(p,"first.polygons"))
  print(direct.label(p,"first.qp"))
  print(direct.label(p,"lasso.labels"))
  print(direct.label(p,"last.bumpup"))
  print(direct.label(p,"last.points"))
  print(direct.label(p,"last.polygons"))
  print(direct.label(p,"last.qp"))
  print(direct.label(p,"lines2"))
  print(direct.label(p,"maxvar.points"))
  print(direct.label(p,"maxvar.qp"))
}

### scatterplot Positioning Methods
for(p in list({
data(mpg,package="ggplot2")
m <- lm(cty~displ,data=mpg)
mpgf <- fortify(m,mpg)
library(lattice)
library(latticeExtra)
p <- xyplot(cty~hwy|manufacturer,mpgf,groups=class,aspect="iso",

```

```

      main="City and highway fuel efficiency by car class and manufacturer")+
      layer_(panel.abline(0,1,col="grey90"))
    },
    {
      data(mpg,package="ggplot2")
      m <- lm(cty~displ,data=mpg)
      mpgf <- fortify(m,mpg)
      library(lattice)
      p <- xyplot(jitter(.resid)~jitter(.fitted),mpgf,groups=factor(cyl))
    },
    {
      library(lattice)
      p <- xyplot(jitter(Sepal.Length)~jitter(Petal.Length),iris,groups=Species)
    },
    {
      data(mpg,package="ggplot2")
      library(lattice)
      p <- xyplot(jitter(cty)~jitter(hwy),mpg,groups=class,
        main="Fuel efficiency depends on car size")
    },
    {
      library(ggplot2)
      data(mpg,package="ggplot2")
      p <- qplot(jitter(hwy),jitter(cty),data=mpg,colour=class,
        main="Fuel efficiency depends on car size")
    },
    {
      data(normal.l2.cluster,package="directlabels")
      library(ggplot2)
      p <- ggplot(normal.l2.cluster$path,aes(x,y))+
        geom_path(aes(group=row),colour="grey")+
        geom_point(aes(size=lambda),colour="grey")+
        geom_point(aes(colour=class),data=normal.l2.cluster$pts,pch=21,fill="white")+
        coord_equal()
    }){
      print(direct.label(p,"ahull.grid"))
      print(direct.label(p,"chull.grid"))
      print(direct.label(p,"extreme.grid"))
      print(direct.label(p,"smart.grid"))
    }
  }

## End(Not run)

```

project.onto.segments *project onto segments*

Description

Given a point and a set of line segments representing a convex or alpha hull, calculate the closest point on the segments.

Usage

```
project.onto.segments(m, h, debug = FALSE, ...)
```

Arguments

m	m is 1 row, a center of a point cloud, we need to find the distance to the closest point on each segment of the convex hull.
h	Data frame describing the line segments of the convex or alpha hull.
debug	
...	ignored

Author(s)

Toby Dylan Hocking

projectionSeconds	<i>Timings of projection algorithms</i>
-------------------	---

Description

Timings of seconds for 3 projection algorithms.

Usage

```
data(projectionSeconds)
```

Format

A data frame with 603 observations on the following 6 variables.

vector.length	a numeric vector
method	a factor with levels Heap Random Sort
mean	a numeric vector
sd	a numeric vector
min	a numeric vector
max	a numeric vector

Source

Mark Schmidt's prettyPlot code for MATLAB <http://www.di.ens.fr/~mschmidt/Software/prettyPlot.html>

qp.labels

*Make a Positioning Method for non-overlapping lineplot labels***Description**

Use a QP solver to find the best places to put the points on a line, subject to the constraint that they should not overlap.

Usage

```
qp.labels(target.var, lower.var, upper.var, order.labels = function(d) order(d[,
  target.var]), limits = NULL)
```

Arguments

target.var	Variable name of the label target.
lower.var	Variable name of the lower limit of each label bounding box.
upper.var	Variable name of the upper limit of each label bounding box.
order.labels	Function that takes the data.frame of labels and returns an ordering, like from the order function. That ordering will be used to reorder the rows. This is useful to e.g. break ties when two groups have exactly the same value at the endpoint near the label.
limits	Function that takes the data.frame of labels and returns a numeric vector of length 2. If finite, these values will be used to add constraints to the QP: limits[1] is the lower limit for the first label's lower.var, and limits[2] is the upper limit for the last labels's upper.var. Or NULL for no limits.

Value

Positioning Method that adjusts target.var so there is no overlap of the label bounding boxes, as specified by upper.var and lower.var.

Author(s)

Toby Dylan Hocking

Examples

```
SegCost$error <- factor(SegCost$error, c("FP", "FN", "E", "I"))
if(require(ggplot2)){
  fp.fn.colors <- c(FP="skyblue", FN="#E41A1C", I="black", E="black")
  fp.fn.sizes <- c(FP=2.5, FN=2.5, I=1, E=1)
  fp.fn.linetypes <- c(FP="solid", FN="solid", I="dashed", E="solid")
  err.df <- subset(SegCost, type!="Signal")

  kplot <- ggplot(err.df, aes(segments, cost))+
    geom_line(aes(colour=error, size=error, linetype=error))+
```

```

facet_grid(type~bases.per.probe)+
scale_linetype_manual(values=fp.fn.linetypes)+
scale_colour_manual(values=fp.fn.colors)+
scale_size_manual(values=fp.fn.sizes)+
scale_x_continuous(limits=c(0,20),breaks=c(1,7,20),minor_breaks=NULL)+
theme_bw()+theme(panel.margin=grid::unit(0,"lines"))

## The usual ggplot without direct labels.
print(kplot)

## Get rid of legend for direct labels.
no.leg <- kplot+guides(colour="none",linetype="none",size="none")

## Default direct labels.
direct.label(no.leg)

## Explore several options for tiebreaking and limits. First let's
## make a qp.labels Positioning Method that does not tiebreak.
no.tiebreak <- list("first.points",
                    "calc.bboxes",
                    qp.labels("y","bottom","top"))
direct.label(no.leg, no.tiebreak)

## Look at the weird labels in the upper left panel. The E curve is
## above the FN curve, but the labels are the opposite! This is
## because they have the same y value on the first points, which are
## the targets for qp.labels. We need to tiebreak.
qp.break <- qp.labels("y","bottom","top",make.tiebreaker("x","y"))
tiebreak <- list("first.points",
                 "calc.bboxes",
                 "qp.break")
direct.label(no.leg, tiebreak)

## Enlarge the text size and spacing.
tiebreak.big <- list("first.points",
                    cex=2,
                    "calc.bboxes",
                    dl.trans(h=1.25*h),
                    "calc.borders",
                    "qp.break")
direct.label(no.leg, tiebreak.big)

## Even on my big monitor, the FP runs off the bottom of the screen
## in the top panels. To avoid that you can specify a limits
## function.

## Below, the ylimits function uses the limits of each panel, so
## labels appear inside the plot region. Also, if you resize your
## window so that it is small, you can see that the text size of the
## labels is decreased until they all fit in the plotting region.
qp.limited <- qp.labels("y","bottom","top",make.tiebreaker("x","y"),ylimits)
tiebreak.lim <- list("first.points",
                    cex=2,

```

```

      "calc.bboxes",
      dl.trans(h=1.25*h),
      "calc.borders",
      "qp.limited")
  direct.label(no.leg, tiebreak.lim)
}

```

reduce.cex.lr

reduce cex lr

Description

If left or right edges of the text are going out of the plotting region, then decrease cex until it fits. We call calc.bboxes inside, so you should set cex before using this.

Usage

```
reduce.cex.lr(d, ...)
```

Arguments

```

d
...

```

Author(s)

Toby Dylan Hocking

Examples

```

if(require(ElemStatLearn) && require(lars) && require(ggplot2)){
  pros <- subset(prostate,select=-train,train=TRUE)
  ycol <- which(names(pros)=="lpsa")
  x <- as.matrix(pros[-ycol])
  y <- pros[[ycol]]
  fit <- lars(x,y,type="lasso")
  beta <- scale(coef(fit),FALSE,1/fit$normx)
  arclength <- rowSums(abs(beta))

  path.list <- list()
  for(variable in colnames(beta)){
    standardized.coef <- beta[, variable]
    path.list[[variable]] <-
      data.frame(step=seq_along(standardized.coef),
                 arclength,
                 variable,
                 standardized.coef)
  }
  path <- do.call(rbind, path.list)
}

```

```
p <- ggplot(path,aes(arclength,standardized.coef,colour=variable))+
  geom_line(aes(group=variable))

## the legend isn't very helpful.
print(p)

## add direct labels at the end of the lines.
direct.label(p, "last.points")

## on my screen, some of the labels go off the end, so we can use
## this Positioning Method to reduce the text size until the labels
## are on the plot.
direct.label(p, list("last.points","reduce.cex.lr"))

## the default direct labels for lineplots are similar.
direct.label(p)
}
```

rhtmlscape

rhtmlscape

Description

for standards compliance we should escape <>&

Usage

```
rhtmlscape(code)
```

Arguments

code R code to be displayed on a HTML page between pre tags.

Value

Standards compliant HTML to display.

Author(s)

Toby Dylan Hocking

SegCost	Cost of segmentation models
Description	
20 segmentation models were fit to 2 simulated signals, and several different error measures were used to quantify the model fit.	
Usage	
data(SegCost)	
Format	
A data frame with 560 observations on the following 5 variables.	
bases.per.probe a factor with levels 374 7: the sampling density of the signal.	
segments numeric: the model complexity measured using number of segments.	
cost numeric: the cost value.	
type a factor with levels Signal Breakpoint Complete Incomplete Positive: how to judge model fit? Signal: log mean squared error between latent signal and estimated signal. Breakpoint: exact breakpoint error. Complete: annotation error with a complete set of annotations. Incomplete: annotation error with only half of those annotations. Positive: no negative annotations.	
error a factor with levels E FP FN I: what kind of error? FP = False Positive, FN = False Negative, I = Imprecision, E = Error (sum of the other terms).	
Source	
PhD thesis of Toby Dylan Hocking, chapter Optimal penalties for breakpoint detection using segmentation model selection.	
smart.grid	smart grid

Description

Search the plot region for a label position near the center of each point cloud.

Usage

"smart.grid"

static.labels	<i>static labels</i>
---------------	----------------------

Description

to hard-code label positions...

Usage

```
static.labels(x, y, groups, ...)
```

Arguments

```
x
y
groups
...
```

Author(s)

Toby Dylan Hocking

svmtrain	<i>False positive rates from several 1-SVM models</i>
----------	---

Description

Support Vector Machine density estimation (1-SVM) was applied to a set of negative control samples, and then used to test on a positive control.

Usage

```
data(svmtrain)
```

Format

A data frame with 378 observations on the following 5 variables.

replicate a factor with levels 1 2 3, the experimental replicate. We fit 1-SVM models to each replicate separately.

rate a numeric vector, the percent of observations that were outside the trained model.

data a factor with levels KIF11 test train, which set of observations did we measure. test and train are each 50% random splits of the negative controls in the experiment, and KIF11 is the positive control in the experiment.

gamma a numeric vector, the tuning parameter of the radial basis function kernel.

nu a numeric vector, the regularization parameter of the 1-SVM.

top.bumptime	<i>top bumptime</i>
--------------	---------------------

Description

Label the tops, bump labels up to avoid other labels, then to the side to avoid collisions with points.

Usage

```
top.bumptime(d, debug = FALSE, ...)
```

Arguments

d
debug
...

Author(s)

Toby Dylan Hocking

top.bumpup	<i>top bumpup</i>
------------	-------------------

Description

Label the tops, but bump labels up to avoid collisions.

Usage

```
"top.bumpup"
```

`top.pieces`*top pieces*

Description

Positioning Method for the top of a group of points.

Usage

```
top.pieces(d, ...)
```

Arguments

d

...

Author(s)

Toby Dylan Hocking

`top.points`*top points*

Description

Positioning Method for the top of a group of points.

Usage

```
top.points(d, ...)
```

Arguments

d

...

Author(s)

Toby Dylan Hocking

top.qp	<i>top qp</i>
--------	---------------

Description

Label points at the top, making sure they don't collide.

Usage

"top.qp"

uselegend.ggplot	<i>uselegend ggplot</i>
------------------	-------------------------

Description

Show the ggplot2 legend, for comparison.

Usage

uselegend.ggplot(p, ...)

Arguments

- | | |
|-----|--------------------|
| p | The ggplot object. |
| ... | Ignored. |

Author(s)

Toby Dylan Hocking

uselegend.trellis	<i>uselegend trellis</i>
-------------------	--------------------------

Description

Add a legend to a trellis plot, for comparison.

Usage

uselegend.trellis(p, ...)

Arguments

p	The trellis object.
...	Ignored.

Author(s)

Toby Dylan Hocking

vertical.qp	<i>vertical qp</i>
-------------	--------------------

Description

Make a Positioning Function from a set of points on a vertical line that will be spaced out using qp.labels.

Usage

```
vertical.qp(M)
```

Arguments

M

Author(s)

Toby Dylan Hocking

visualcenter	<i>visualcenter</i>
--------------	---------------------

Description

Point in the middle of the min and max for each group.

Usage

```
visualcenter(d, ...)
```

Arguments

d
...

Author(s)

Toby Dylan Hocking

`xlimits`*xlimits*

Description

Return the positions of the plot horizontal limits in cm, for use as the limit argument to `qp.labels`.

Usage

```
xlimits(...)
```

Arguments

...

Author(s)

Toby Dylan Hocking

`ylimits`*ylimits*

Description

Return the positions of the plot vertical limits in cm, for use as the limit argument to `qp.labels`.

Usage

```
ylimits(...)
```

Arguments

...

Author(s)

Toby Dylan Hocking

Index

*Topic **datasets**

- `iris.l1.cluster`, 37
- `normal.l2.cluster`, 45
- `projectionSeconds`, 56
- `SegCost`, 61
- `svmtrain`, 62

*Topic **package**

- `directlabels-package`, 4

- `ahull.grid`, 4
- `ahull.points`, 5
- `angled.bboxes`, 5
- `angled.endpoints`, 5
- `apply.method`, 6, 13, 14

- `big.bboxes`, 7
- `bottom.pieces`, 7
- `bumpup`, 8

- `calc.borders`, 8
- `calc.bboxes`, 9
- `check.for.columns`, 9
- `chull.grid`, 10
- `chull.points`, 10

- `default.ahull`, 10
- `default.picker`, 11
- `defaultpf.ggplot`, 11
- `defaultpf.trellis`, 12
- `direct.label`, 12
- `direct.label.ggplot`, 14
- `direct.label.trellis`, 14
- `directlabels(directlabels-package)`, 4
- `directlabels-package`, 4
- `dl.combine`, 15
- `dl.jitter`, 17
- `dl.move`, 18
- `dl.summarize`, 19
- `dl.trans`, 19
- `dlcompare`, 20

- `dldoc`, 21
- `dlgrob`, 22
- `draw.polygons`, 23
- `draw.rects`, 23
- `drawDetails.dlgrob`, 6, 24

- `edges.to.outside`, 24
- `empty.grid`, 25
- `enlarge.box`, 26
- `extract.plot`, 26
- `extract.posfun`, 27
- `extreme.grid`, 27
- `extreme.points`, 28

- `far.from.others.borders`, 28
- `filltemplate`, 29
- `first.bumpup`, 29
- `first.points`, 29
- `first.polygons`, 30
- `first.qp`, 30

- `gapply`, 31
- `gapply.fun`, 31
- `geom_dl`, 32
- `GeomDL`, 32
- `get.means`, 34
- `getLegendVariables`, 35

- `ignore.na`, 35
- `in1box`, 36
- `in1which`, 36
- `inside`, 37
- `iris.l1.cluster`, 37

- `label.endpoints`, 38
- `label.pieces`, 39
- `lasso.labels`, 39
- `last.bumpup`, 39
- `last.points`, 40
- `last.polygons`, 40
- `last.qp`, 40

`lattice.translators`, 41
`legends2hide`, 41
`lines2`, 42

`make.tiebreaker`, 42
`maxvar.points`, 43
`maxvar.qp`, 43
`merge_recurse`, 44
`midrange`, 44

`normal.l2.cluster`, 45

`only.unique.vals`, 46
`outside.ahull`, 46
`outside.chull`, 47

`panel.superpose.dl`, 47
`pkgFun`, 49
`polygon.method`, 50
`positioning.functions`, 51
`positioning.methods`
 (`positioning.functions`), 51
`project.onto.segments`, 55
`projectionSeconds`, 56

`qp.labels`, 57

`reduce.cex.lr`, 59
`rhtmlscape`, 60

`SegCost`, 61
`smart.grid`, 61
`static.labels`, 62
`svmtrain`, 62

`top.bumptwice`, 63
`top.bumpup`, 63
`top.pieces`, 64
`top.points`, 64
`top.qp`, 65

`uselegend.ggplot`, 65
`uselegend.trellis`, 65

`vertical.qp`, 66
`visualcenter`, 66

`xlimits`, 67

`ylimits`, 67