TPTT: Transforming Pretrained Transformer into Titans

Fabien Furfaro*

2025

Abstract

Recent advances in large language models (LLMs) have enabled remarkable progress in natural language processing, but their computational and memory demands remain a major challenge, particularly for long-context inference. We present TPTT (Transforming Pretrained Transformer into Titans), a novel framework for upgrading pretrained Transformer models with efficient linearized attention mechanisms and advanced memory management. TPTT leverages techniques such as Memory as Gate (MaG) and mixed linearized attention (LiZA), and is fully compatible with the Hugging Face Transformers library, enabling seamless adaptation of any causal LLM via parameter-efficient fine-tuning (LoRA) without full retraining. We demonstrate the effectiveness of TPTT on the MMLU benchmark with models of approximately 1 billion parameters, observing substantial improvements in both efficiency and accuracy. For example, Titans-Llama-3.2-1B achieves a 20% increase in Exact Match (EM) over its baseline. Detailed statistical analyses and comparisons to recent state-of-the-art methods confirm the practical scalability and robustness of TPTT. Source code is available at `https://github.com/fabienfrfr/tptt`.



Figure 1: Overview of the TPTT framework architecture. On the left, the diagram illustrates a decoder-only architecture where linear attention is injected in parallel of vanilla attention (LiZAttention). On the right, the detailed architecture of the linearized attention mechanism is depicted, highlighting the shared weights for query (Q), key (K), and value (V) projections. It also shows the management of the state memory (S) and the combination of outputs through the Memory as Gate (MaG) weighting mechanism. The diagram emphasizes the integration of linearized attention mechanisms and advanced memory management techniques, such as Delta Rule and AdaptativeAvgPool1D, contributing to processing and output generation.

1 Introduction

The success of transformer-based large language models (LLMs) [4, 18] has revolutionized natural language processing (NLP), enabling unprecedented progress across a wide range of tasks. However, the quadratic computational complexity and substantial memory requirements of the standard self-attention mechanism remain a significant bottleneck, particularly for long-context inference.

*`fabien.furfaro@gmail.com`

To address these challenges, recent research has explored several directions. Efficient attention mechanisms [12, 20] have been proposed to reduce the complexity of self-attention from quadratic to linear or near-linear, making it more tractable for long sequences. Recurrent architectures and internal memory mechanisms [3, 14] have also been developed to enhance the model's ability to capture long-range dependencies, drawing inspiration from cognitive memory in biological systems rather than hardware memory. Additionally, parameter-efficient fine-tuning approaches such as LoRA [11] allow for the adaptation of large pretrained models to new tasks without the need for full retraining.

2 Related Work

Despite these advances, most existing methods require significant architectural modifications or training from scratch, which limits their applicability to already pretrained models. For example, solutions like FlashAttention [5] and Mamba [9] focus on efficient architectures, while others such as LoLCat [21] and Liger [13] convert standard attention to linearized forms; notably, Liger exploits similar properties to those leveraged in this work, but does not rely on explicit linearization injection.

In this work, we introduce TPTT (Transforming Pretrained Transformer into Titans), a framework that transforms pretrained transformer models into more efficient and scalable architectures by incorporating linearized attention mechanisms and advanced internal memory augmentation. TPTT leverages techniques such as Memory as Gate (MaG) and mixed linearized attention (LiZA), drawing inspiration from the Titans architecture [3]. Our approach is fully compatible with existing frameworks and enables rapid adaptation of any causal LLM to long-context tasks via parameter-efficient fine-tuning with LoRA [11], without requiring full retraining. The goal is to unlock the potential of already trained models by equipping them with memory-augmented capabilities through lightweight adaptation.

3 Methodology

3.1 Linearized Attention Mechanisms

Standard self-attention in transformers computes pairwise interactions between all tokens, resulting in quadratic complexity with respect to sequence length [18]. To address this, linearized attention mechanisms approximate the softmax attention using linear operations, typically by projecting queries and keys through a feature map ϕ [**?**, 6, 12, 15, 19, 20]. This reduces computational and memory costs, enabling efficient processing of long sequences while maintaining modeling power [5,9,13,21]. The output of softmax attention for an input sequence $\mathbf{X} = \{\mathbf{x}_1, \ldots, \mathbf{x}_T\} \in \mathbb{R}^{T \times D}$ is:

$$\mathbf{Q}, \mathbf{K}, \mathbf{V} = \mathbf{X}\mathbf{W}_Q, \mathbf{X}\mathbf{W}_K, \mathbf{X}\mathbf{W}_V \tag{1}$$

$$\mathbf{O}_{\text{base}} = \text{Softmax}\left(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{D}}\right)\mathbf{V} \tag{2}$$

In linear attention, this is approximated as:

$$\mathbf{O}_{\text{lin},(t)} = \frac{\sum_{i=1}^{t} \phi(\mathbf{q}_t)^\top \phi(\mathbf{k}_i)\mathbf{v}_i}{\sum_{i=1}^{t} \phi(\mathbf{q}_t)^\top \phi(\mathbf{k}_i)} \tag{3}$$

where ϕ is a feature mapping function, such as ELU or kernel approximations [**?**, 6, 19].

3.2 Memory as Gate (MaG)

To further enhance long-range dependency modeling, we introduce an internal memory augmentation mechanism, Memory as Gate (MaG), inspired by the Titans architecture [3]. Unlike hardware memory, this mechanism enables the model to store and recall contextual information over extended sequences, analogous to cognitive memory. MaG combines the outputs of standard and linearized attention using a learnable weighting parameter:

$$\mathbf{O} = \alpha \cdot \mathbf{O}_{\text{lin}} + (1 - \alpha) \cdot \mathbf{O}_{\text{base}} \tag{4}$$

where $\alpha \in [0, 1]$ is adapted during training. This allows the model to leverage both the efficiency of linear attention and the expressivity of softmax attention, and can be seen as a form of memory-augmented gating [3, 15].

3.3 Parallel Delta Rule Modeling

In this works, the feature mapping function of linear attention is approximated by DeltaNet [20]. The recurrent update of internal memory states is formulated in two ways, following:

- **Closed Form (intra-chunk):**

$$\mathbf{S}_t = \mathbf{S}_{t-1} + \sum_{i=1}^{C} \mathbf{v}_i \mathbf{k}_i^\top \tag{5}$$

  where C is the chunk size and $\mathbf{S}_t$ is the updated state.

- **Recurrent Form (inter-chunk):**

$$\mathbf{S}_{t+1} = \mathbf{S}_t + \mathbf{v}_{t+1} \mathbf{k}_{t+1}^\top \tag{6}$$

  The final state of one chunk becomes the initial state of the next, supporting efficient memory usage for long sequences.

The output $\mathbf{O}_{\text{lin}}$ is then computed from these memory states.

3.4 Integration with Pretrained Models

Our approach injects linearized attention and memory augmentation modules into pretrained transformer models. The process involves:

1. **Identification of Target Modules:** Key attention layers to be modified are identified using tools such as `get_tptt_model`.
2. **Modification of Attention Layers:** These layers are replaced or extended with the proposed `LiZAttention` module, which implements both linear and softmax attention with linear projection weigth sharing and MaG.
3. **Training and Fine-Tuning:** The modified model is fine-tuned using parameter-efficient methods such as LoRA [11], ensuring optimal adaptation to the new mechanisms without full retraining.

This procedure enables the transformation of any causal pretrained LLM into a memory-augmented, efficient architecture with minimal overhead, that without any new layers.

3.5 LiZAttention Module

The `LiZAttention` module is a core component of the TPTT architecture, designed to synergistically combine linearized attention and standard (softmax) attention mechanisms. This hybrid approach leverages the computational efficiency of linear attention while retaining the expressivity of vanilla attention. To support long-context inference, `LiZAttention` maintains a cache of intermediate states and implements a recurrent information mechanism for efficient internal memory management [12].

Algorithm 1 LiZAttention Forward Pass

Require: hidden_states $\in \mathbb{R}^{B \times L \times D}$ ▷ Batch size B, sequence length L, embedding dim D
Require: mask ▷ Attention mask for padding/causality

1: **Projection:**
   Compute queries q, keys k, values v via learned projections:
   $q \in \mathbb{R}^{B \times H \times L \times d_h}$, $k, v \in \mathbb{R}^{B \times H_k \times L \times d_h}$
2: **Apply Attention Mask:**
   Apply mask to k and v to handle padding and restrict attention.
3: **Linear Attention:**
   Compute linear attention output o_{lin} using a feature map ϕ:
   $o_{\text{lin}}[t] = \frac{\sum_{i=1}^{t} \phi(q_t)^\top \phi(k_i) v_i}{\sum_{i=1}^{t} \phi(q_t)^\top \phi(k_i)}$
   Store intermediate states in a memory cache for recurrent information.
4: **Vanilla (Softmax) Attention:**
   Compute standard self-attention output o_{base} (optionally truncated for long sequences):
   $o_{\text{base}} = \text{Softmax}\left(\frac{qk^\top}{\sqrt{d_h}}\right) v$
5: **Combine Outputs (Memory as Gate):**
   Compute final output using a learnable gating parameter α:
   $o = \alpha \cdot o_{\text{lin}} + (1 - \alpha) \cdot o_{\text{base}}$
6: **return** $o \in \mathbb{R}^{B \times L \times D}$

3.5.1 Efficient Internal Memory Management

The cache of intermediate states maintained by `LiZAttention` enables a recurrent information, efficiently supporting long-context inference without excessive computational overhead [12]. This approach allows the model to scale to longer sequences, leveraging both local and global context.

4 Training Procedure

4.1 Parameter-Efficient Fine-Tuning with LoRA

To adapt the TPTT architecture to downstream tasks, we employ Low-Rank Adaptation (LoRA) [7, 11], a parameter-efficient fine-tuning technique that injects trainable low-rank matrices into selected projection layers while freezing the original model weights. This approach drastically reduces the number of trainable parameters and memory requirements, while maintaining performance comparable to full fine-tuning [**?**, 7, 11]. For TPTT, LoRA is configured with a rank of 8, $\alpha = 16$, and a dropout rate of 0.05. Fine-tuning targets the main projection modules, specifically `[q_proj, k_proj, v_proj, o_proj]` for Llama/Mistral and `[qkv_proj, out_proj]` for OpenELM [7].

4.2 Training Setup and Hyperparameters

Training is performed on 500 samples from the `yahma/alpaca-cleaned` dataset over 5 epochs. Sequences are tokenized to a maximum length of 384, with truncation and padding as needed. The training is conducted on NVIDIA Tesla T4 GPUs (Kaggle platform), utilizing mixed precision to optimize computational efficiency. Key hyperparameters include a batch size of 3, a learning rate of 5×10^{-4}, and gradient clipping at 1.0 to prevent gradient overflow. Training progress is logged every 5 steps, and model checkpoints are saved at the end of each epoch. The total number of training steps is 420.

4.3 Dynamic Memory as Gate Scheduling (LiZA MaG Callback)

A critical component of the training process is the LiZA MaG callback, which dynamically adjusts the Memory as Gate (MaG) weighting parameter during training. The MaG weight is initialized at 0.01 and linearly increased to 0.5 over the first 100 steps, facilitating a smooth transition from reliance on vanilla (softmax) attention to linearized attention. This schedule allows the model to effectively balance the two attention mechanisms, optimizing performance throughout training. The callback is integrated directly into the training loop, ensuring adaptive control of the MaG parameter and enhancing the model's adaptability and efficiency.

5 Experiments and Results

5.1 Experimental Setup

We evaluated the TPTT framework on several pretrained language models with approximately 1 billion parameters, using the MMLU benchmark [10] as the primary evaluation suite. Training was conducted on 500 samples from the `yahma/alpaca-cleaned` dataset [16] for 5 epochs, with a maximum sequence length of 384 tokens, a batch size of 3, and a learning rate of 5×10^{-4}. Mixed precision training and gradient clipping at 1.0 were employed to optimize computational efficiency and stability. All experiments were performed on NVIDIA Tesla T4 GPUs (Kaggle platform). The trained models and detailed metrics are publicly available on the Hugging Face Model Hub[1], with full training logs accessible via Hugging Face TensorBoard.

5.2 Training Results

Table 1 summarizes the training performance metrics for various TPTT models. The results indicate consistent and efficient learning across architectures, as evidenced by low final loss values and stable gradient norms. The use of Low-Rank Adaptation (LoRA) and the Memory as Gate (MaG) mechanism proved effective in optimizing training dynamics and convergence.

5.3 Evaluation Metrics and Benchmark Results

For evaluation, we focus on metrics standard in LLM and QA benchmarking: Exact Match (EM), Partial Exact Match (PEM), and Partial Quasi Exact Match (PQEM). These metrics respectively measure strict correctness,

[1] `https://huggingface.co/ffurfaro/`

Model	Loss	Training Time (s)	Samples/s	Steps/s	Total FLOPs	Gradient Norm	Refs Based On
Titans-Llama-3.2-1B	1.375	1654.1	1.51	0.254	5.62e18	2.68	[17]
Titans-OpenELM-1_1B	1.3188	1651.1	1.51	0.254	5.85e18	0.704	[1]
Titans-Qwen2.5-1.5B	1.2568	1900.6	1.31	0.221	7.56e18	1.99	[2]
Titans-OLMo-1B-hf	1.3068	1585.2	1.58	0.265	6.20e18	3.12	[8]

Table 1: Training performance metrics for TPTT models.

partial overlap, and quasi-exactness between model outputs and ground truth answers, providing a nuanced view of model performance [10].

Table 2 presents the MMLU benchmark results in the one-shot setting. TPTT models, and especially Titans-Llama-3.2-1B, consistently outperform their base counterparts in EM, with competitive PEM and PQEM scores. This demonstrates the benefit of integrating linearized attention and internal memory mechanisms for complex language understanding tasks.

Model	EM ± Std	PEM ± Std	PQEM ± Std
Titans-Llama-3.2-1B	0.2456 ± 0.1276	0.2649 ± 0.1340	0.4772 ± 0.1569
Llama-3.2-1B	0.0070 ± 0.0058	0.3105 ± 0.1411	0.4719 ± 0.1530
Titans-Qwen2.5-1.5B	0.0000 ± 0.0000	0.5000 ± 0.1504	0.5825 ± 0.1442
Qwen2.5-1.5B	0.0000 ± 0.0000	0.5982 ± 0.1422	0.6895 ± 0.1288
Titans-OLMo-1B-hf	0.0000 ± 0.0000	0.2614 ± 0.1312	0.4649 ± 0.1540
OLMo-1B-hf	0.0000 ± 0.0000	0.2333 ± 0.1302	0.4246 ± 0.1533

Table 2: MMLU benchmark results (one-shot) with statistical analysis. Each pair groups a Titans model and its base counterpart.

5.4 Discussion and Comparison

Compared to recent state-of-the-art methods such as Mamba [9], LoLCat [21], and Liger [13], TPTT stands out by enabling the transformation of existing pretrained models without full retraining, while maintaining strong benchmark performance. The observed improvements in EM and competitive PEM/PQEM scores highlight the effectiveness of TPTT's linearized attention and memory augmentation for efficient and robust LLM adaptation. These results confirm that TPTT is a practical and scalable solution for enhancing pretrained LLMs, especially in resource-constrained settings.

6 Discussion and Conclusion

In this paper, we have introduced TPTT, a novel framework for enhancing pretrained Transformer models by integrating efficient linearized attention mechanisms and internal memory augmentation. Our approach leverages parameter-efficient fine-tuning (LoRA) [11] to enable the rapid adaptation of large language models (LLMs) to long-context tasks, without the need for full retraining. Experimental results on the MMLU benchmark [10] demonstrate significant improvements in both efficiency and accuracy, with robust statistical analyses and favorable comparisons to state-of-the-art methods [9, 13, 21].

Practical Implications. TPTT offers a scalable and practical solution for deploying high-performance LLMs in resource-constrained environments. The integration of linearized attention and memory augmentation reduces computational and memory requirements, making advanced language models more accessible for real-world applications. The use of LoRA allows for efficient and flexible fine-tuning, enabling rapid adaptation to new tasks and domains.

Limitations. Our current evaluation is limited to models of moderate size (around 1 billion parameters). Scaling TPTT to larger architectures and more diverse tasks may introduce new challenges, including increased tuning complexity and the need for further optimization of memory mechanisms. While our results are promising, broader validation on additional benchmarks and real-world scenarios is needed to fully assess the generalizability and robustness of the approach.

Future Directions. Future work will focus on optimizing the integration process, exploring more sophisticated internal memory mechanisms [3], and extending the evaluation to larger models and a wider range of benchmarks. Additional research will investigate hybrid approaches and the interplay between linearized attention, memory augmentation, and other efficiency-oriented techniques.

In summary, TPTT provides a practical, scalable, and effective framework for upgrading pretrained Transformers, with strong empirical results and promising implications for the future of efficient language modeling.

References

[1] Apple. Openelm: An efficient language model family with open-source training and inference framework. GitHub repository, 2024.

[2] Jinze Bai, Shuai Bai, Shusheng Yang, and et al. Qwen technical report. arXiv preprint arXiv:2309.16609, 2023.

[3] Amin Behrouz et al. Titans: Learning to memorize at test time. *arXiv preprint arXiv:2502.00000*, 2025.

[4] Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

[5] Tri Dao, Daniel Y Fu, Stefano Ermon, Peter Bailis, and Christopher Ré. Flashattention-2: Faster attention with better parallelism and work partitioning. *arXiv preprint arXiv:2307.08691*, 2023.

[6] Rares Dolga, Marius Cobzarenco, and David Barber. Latent attention for linear time transformers. *arXiv preprint arXiv:2402.17512*, 2024.

[7] Hugging Face. Lora - hugging face peft documentation. `https://huggingface.co/docs/peft/main/conceptual_guides/lora`, 2024.

[8] Dirk Groeneveld, Iz Beltagy, Jesse Dodge, and et al. Olmo: Accelerating the science of language models. arXiv preprint arXiv:2402.00838, 2024.

[9] Albert Gu, Tri Dao, Stefano Ermon, and Christopher Ré. Mamba: Linear-time sequence modeling with selective state spaces. *arXiv preprint arXiv:2312.00752*, 2024.

[10] Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Zou, Dawn Tang, Dawn Song, Jacob Steinhardt, Justin Gilmer, et al. Measuring massive multitask language understanding. *arXiv preprint arXiv:2009.03300*, 2021.

[11] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*, 2021.

[12] Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and Francois Fleuret. Transformers are rnns: Fast autoregressive transformers with linear attention. In *International Conference on Machine Learning*, pages 5156–5165, 2020.

[13] D Lan et al. Liger: Linearizing large language models to gated recurrent structures. *arXiv preprint arXiv:2501.00000*, 2025.

[14] Yikun Qin et al. Advancements in linear recurrent models for long-range dependencies. *arXiv preprint arXiv:2401.00000*, 2024.

[15] Zhen Qin, Xiaodong Han, Weixuan Sun, Dongxu Li, Lingpeng Kong, Nick Barnes, and Yiran Zhong. The devil in linear transformer. In *EMNLP*, 2022.

[16] Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, and et al. Alpaca: A strong, replicable instruction-following model. Stanford CRFM, 2023.

[17] Hugo Touvron, Thibaut Lavril, Gautier Izacard, and et al. Llama: Open and efficient foundation language models. arXiv preprint arXiv:2302.13971, 2023.

[18] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, pages 5998–6008, 2017.

[19] Sinong Wang, Belinda Z. Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *arXiv preprint arXiv:2006.04768*, 2020.

[20] S Yang, F Chen, and H Lee. Parallelizing linear transformers with the delta rule over sequence length. *arXiv preprint arXiv:2402.00000*, 2024.

[21] X Zhang, Y Liu, and Z Wang. Lolcats: Low-cost attention transformers. *arXiv preprint arXiv:2402.00000*, 2024.