



**SREE NARAYANA GURUKULAM
COLLEGE OF ENGINEERING
KADAYIRUPPU, KOLENCHERY 682311**

LABORATORY RECORD

YEAR: 2021 TO 2022

NAME: FABIN FRANCIS

SEMESTER: 1

ROLL NO:13

BRANCH: COMPUTER APPLICATIONS

Certified that this is a Bonafede Record of Practical work done in partial fulfillment of the requirements for the award of the Degree in Master of Computer Applications of Sree Narayana Gurukulam College of Engineering.

Kadayiruppu

Date:

Head of the Department

Course Instructor

Submitted for University Practical Examination

Reg. No: SNG21MCA-2013 **on**-----

External Examiner

Internal Examiner

INDEX PAGE

NO	PROGRAM	DATE
1	Merge two Sorted Array	26/11/2021
2	Circular Queue	29/11/2021
3	Stack using Linked List	30/11/2021
4	Doubly Linked List	03/12/2021
5	Binary Search Tree	21/12/2021
6	Set operations using BitString	04/01/2022
7	Disjoint Set	06/01/2022
8	Minimum Spanning Tree using Kruskal's algorithm	14/01/2022
9	Red Black Tree	18/01/2022
10	DFS Topological Sort	21/01/2022
11	Strongly Connected Components	25/01/2022
12	Minimum Spanning Tree using Prim's Algorithm	01/02/2022
13	Single Source Shortest Path	03/02/2022
14	Breadth First Search	04/02/2022

PROGRAM

```
#include<stdio.h>

void read(int *,int);

void main()
{
    int a[20],b[20],c[20],i=0,j=0,k=0,n1,n2;
    printf("Enter the no of elements in a :");
    scanf("%d",&n1);
    printf("Enter the elements in a (in sorted order):");
    read(a,n1);
    printf("Enter the no of elements in b (in sorted order):");
    scanf("%d",&n2);
    read(b,n2);
    i=0;
    while(i<n1 && j<n2)
    {
        if(a[i]<b[j])
        {
            c[k]=a[i];
            k++;
            i++;
        }
        else if(a[i]>b[j])
        {
            c[k]=b[j];
            k++;
            j++;
        }
        else
        {
            c[k]=a[i];
            k++;
            i++;
            c[k]=b[j];
            k++;
            j++;
        }
    }
}
```

```

        c[k]=a[i];
    }
}
while(i<n1)
{
    c[k]=a[i];
    i++;
    k++;
}
while(j<n2)
{
    c[k]=b[j];
    j++;
    k++;
}
for(i=0;i<k;i++)
{
    printf("%d\t",c[i]);
}
printf("\n");
}

void read(int *p,int y)
{
    int j;
    for(j=0;j<y;j++)
    {
        scanf("%d",&p[j]);
    }
}

```

OUTPUT

Enter the no of elements in a :3

Enter the elements in a (in sorted order):

1

2

3

Enter the no of elements in b :3

Enter the elements in b (in sorted order):

4

5

6

1 2 3 4 5 6

Process returned 10 (0xA) execution time : 36.565 s

Press any key to continue.

RESULT

Program executed successfully and result is verified.

PROGRAM

```
#include<stdio.h>
```

```
int s=4;
```

```
int front=-1,rear=-1;
```

```
void insert(int *);
```

```
void del(int *);
```

```
void search(int *);
```

```
void display(int *);
```

```
void main()
```

```
{
```

```
    int q[20], option;
```

```
    do
```

```
    {
```

```
        printf("\n menu\n 1.Insert an Element \n 2.Delete an Element\n 3.Search an Element\n 4.Dispaly \n 5 Exit \n enter the option");
```

```
        scanf("%d",&option);
```

```
        switch(option)
```

```
        {
```

```
            case 1:insert(q);
```

```
                break;
```

```
            case 2:del(q);
```

```
                break;
```

```
            case 3:search(q);
```

```
                break;
```

```
            case 4:display(q);
```

```
                break;
```

```
            default:printf("exit");
```

```
        }
```

```
    }
```

```
    while(option!=5);
```

```
}
```

```
void insert(int *q)
```

```
{
```

```
    if(front==(rear+1)%s)
```

```
    {
```

```
        printf("queue is full \n");
```

```
        return;
```

```
    }
```

```
    if(front==-1)
```

```
        front=0;
```

```
        rear=(rear+1)%s;
```

```
        printf("enter the element \n");
```

```
        scanf("%d",&q[rear]);
```

```
}
```

```
void del(int *q)
```

```
{
```

```
    if(front==-1)
```

```
    {
```

```
        printf("queue empty\n");
```

```
        return;
```

```
    }
```

```
    printf("deleted element %d \n",q[front]);
```

```
    if(front==rear)
```

```
    {
```

```
        front=rear=-1;
```

```
    }
```

```
    else
```

```
    {
```

```
        front=(front+1)%s;  
    }  
    return;  
}
```

```
void search(int *q)  
{  
    int se,f;  
    printf("enter the element to be search");  
    scanf("%d",&se);  
    if(front==-1)  
    {  
        printf("q is empty\n");  
        return;  
    }  
    f=front;  
    while(1)  
    {  
        if(se==q[f])  
        {  
            printf("element found");  
            break;  
        }  
        if(f==rear)  
        {  
            printf("element not found");  
            break;  
        }  
        f=(f+1)%s;  
    }
```

```
        return;
    }
void display(int *q)
{
    int f;
    if(front==-1)
    {
        printf("q empty\n");
        return;
    }
    f=front;
    while(1)
    {
        printf("%d \n",q[f]);
        if(f==rear)
            break;
        f=(f+1)%s;
    }
    return;
}
```

OUTPUT

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 1

enter the element

2

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 1

enter the element

5

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 1

enter the element

36

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 4

2

5

36

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 3

enter the element to be search36

element found

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 2

deleted element 2

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 4

5

36

MENU

- 1.Insert an Element
- 2.Delete an Element
- 3.Search an Element
- 4.Dispaly
- 5 Exit

Enter the option : 5

RESULT

Program executed successfully and result is verified.

PROGRAM

```
#include<stdio.h>

#include<stdlib.h>

void push();

void pop();

void display();

void search();

struct node

{

int data;

struct node *next;

};

struct node *top=NULL;

void main()

{

int opt;

do

{

printf("Choose operation :\n 1.PUSH \n2. POP \n3. Display\n4.Search\n");

scanf("%d",&opt);

switch(opt)

{

case 1:

push();

break;

case 2:

pop();

break;

case 3:

display();
```

```

        break;

        case 4:
            search();
            break;
        }
    }
while(opt!=5);
}

void push()
{

    struct node *ne;
    int x;
    printf("Enter the element to PUSH\n");
    scanf("%d",&x);
    ne=(struct node *)malloc(sizeof(struct node));
    if (ne == NULL)
    {
        printf("Stack Overflow") ;
        return;
    }
    ne->data=x;
    ne->next= top;
    top = ne;
}

void pop()
{
    struct node *ptr;
    if (top == NULL)
    {
        printf("Stack Empty") ;
    }
}

```

```

        return;
    }
    printf("%d is popped\n",top->data);
    ptr=top;
    top=top->next;
    free(ptr);
}
void display()
{
    struct node *ptr;
    if (top == NULL)
    {
        printf("Stack Empty") ;
        return;
    }
    else
    {
        ptr=top;
        while(ptr!=NULL)
        {
            printf("%d \t",ptr->data);
            ptr=ptr->next;
        }
    }
}
void search()
{
    struct node *ptr;
    int x;
    printf("Enter the element to search\n");

```

```
scanf("%d",&x);
if (top == NULL)
{
    printf("Stack Empty") ;
    return;
}
else
{
    ptr=top;
    while(ptr!=NULL)
    {
        if(ptr->data==x)
        {
            printf("Element Found\n");
            break;
        }
        ptr=ptr->next;
    }
    if(ptr==NULL)
    {
        printf("Element Not Found\n");
    }
}
}
```

OUTPUT

Choose operation :

- 1.PUSH
2. POP
3. Display
- 4.Search

1

Enter the element to PUSH

5

Choose operation :

- 1.PUSH
2. POP
3. Display
- 4.Search

1

Enter the element to PUSH

10

Choose operation :

- 1.PUSH
2. POP
3. Display
- 4.Search

1

Enter the element to PUSH

20

Choose operation :

- 1.PUSH
2. POP
3. Display
- 4.Search

2

20 is popped

Choose operation :

1. PUSH
2. POP
3. Display
4. Search

3

10 5 Choose operation :

1. PUSH
2. POP
3. Display
4. Search

4

Enter the element to search

20

Element Not Found

Choose operation :

1. PUSH
2. POP
3. Display
4. Search

4

Enter the element to search

10

Element Found

RESULT

Program executed successfully and result is verified.

PROGRAM

```
#include<stdio.h>
#include<stdlib.h>
```

```
void frst_insert();
void lst_insert();
void display();
void search();
void frst_delete();
void lst_delete();
void insert_pos();
void delete_pos();
```

```
struct node
{
int data;
struct node *next;
struct node *left;
struct node *right;
};
struct node *head;
```

```
void main()
{
    int opt;
    do
    {
        printf("Choose operation :\n1.Insert an element at FIRST\n2.Insert an element at LAST\n3.Display\n4.SEARCH\n5.Delete First Element... \n6.Delete Last Element... \n7.Insert an item at position\n8.Delete an item at Position\n");
        scanf("%d",&opt);
```

```
switch(opt)
{
    case 1:
        frst_insert();
        break;
    case 2:
        lst_insert();
        break;
    case 3:
        display();
        break;
    case 4:
        search();
        break;
    case 5:
        frst_delete();
        break;
    case 6:
        lst_delete();
        break;
    case 7:
        insert_pos();
        break;
    case 8:
        delete_pos();
        break;
}
}
while(opt!=0);
}
```



```

void frst_insert()
{
    struct node *ne;
    int x;
    printf("Enter the element to INSERT\n");
    scanf("%d",&x);
    ne=(struct node *)malloc(sizeof(struct node));
    if (ne == NULL)
    {
        printf("Insufficient Memory") ;
        return;
    }
    ne->data=x;
    ne->left=NULL;
    ne->right=NULL;
    if(head == NULL)
    {
        head=ne;
    }
    else
    {
        ne->right=head;
        head->left=ne;
        head=ne;
    }
}

```

```

void lst_insert()
{
    struct node *ne;
    struct node *ptr;

```

```

int x;

printf("Enter the element to INSERT\n");
scanf("%d",&x);
ne=(struct node *)malloc(sizeof(struct node));
if (ne == NULL)
    {
        printf("Insufficient Memory") ;
        return;
    }
ne->data=x;
ne->left=NULL;
ne->right=NULL;
if(head == NULL)
    {
        head=ne;
    }
else
    {
        ptr=head;
        while(ptr->right!=NULL)
            {
                ptr=ptr->right;
            }
        ptr->right=ne;
        ne->left=ptr;
    }
}

void display()
{
    struct node *ptr;

```

```
if (head == NULL)
{
    printf("LInked List is Empty") ;
    return;
}

ptr=head;
while(ptr!=NULL)
{
    printf("%d \t",ptr->data);
    ptr=ptr->right;
}

printf("\n");
}

void search()
{
    struct node *ptr;
    int x;
    printf("Enter the element to search\n");
    scanf("%d",&x);
    if (head == NULL)
    {
        printf("LInked List is Empty") ;
        return;
    }
    else
    {
        ptr=head;
        while(ptr!=NULL)
        {
            if(ptr->data==x)
```

```

        {
            printf("Element Found");
            printf("\n");
            break;
        }
        ptr=ptr->right;
    }
    if(ptr==NULL)
    {
        printf("Element Not Found");
        printf("\n");
    }
}
}

```

```

void first_delete()
{
    struct node *ptr;
    if (head == NULL)
    {
        printf("LInked List is Empty") ;
        return;
    }
    ptr = head;
    head = head->right;
    if (head == NULL)
    {
        head->left=NULL;
    }
    free(ptr);
}

```

```
}
```

```
void lst_delete()
```

```
{
```

```
    struct node *ptr;
```

```
    struct node *prev;
```

```
    if (head == NULL)
```

```
    {
```

```
        printf("LInked List is Empty") ;
```

```
        return;
```

```
    }
```

```
    if (head->right == NULL)
```

```
    {
```

```
        free(head);
```

```
        head = NULL;
```

```
    }
```

```
    ptr = head;
```

```
    while(ptr->right!=NULL)
```

```
    {
```

```
        ptr=ptr->right;
```

```
    }
```

```
    prev=ptr->left;
```

```
    prev->right=NULL;
```

```
    free(ptr);
```

```
}
```

```
void insert_pos()
```

```
{
```

```
    struct node *ne;
```

```
    struct node *ptr,*ptr1;
```

```

int x,key;

printf("Enter the element to INSERT\n");

scanf("%d",&x);

printf("Enter the position where you want to insert item: ");
scanf("%d", &key);

ne=(struct node *)malloc(sizeof(struct node));

if (ne == NULL)
    {
        printf("Insufficient Memory");
        return;
    }

ne->data=x;
ne->left=NULL;
ne->right=NULL;
if(head == NULL)
{
    head=ne;
    return;
}
ptr = head;
while(ptr->data!=key&&ptr->right!=NULL)
{
    ptr=ptr->right;
}
if(ptr->right==NULL)
{
    ptr->right=ne;
    ne->left=ptr;
}
else

```

```

    {
        ne->left=ptr;
        ne->right=ptr->right;
        ptr1=ptr->right;
        ptr->right=ne;
        ne->left=ne;
    }
}

```

void delete_pos()

```

{
    struct node *ptr;
    struct node *prev;
    struct node *next;
    int x;
    if (head == NULL)
    {
        printf("LInked List is Empty") ;
    }
    printf("Enter the Item you want to DELETE : ");
    scanf("%d", &x);
    if(head->data==x)
    {
        ptr = head;
        head = head->right;
        if (head != NULL)
        {
            head->left=NULL;
        }
        free(ptr);
    }
}

```

```

    }
else
{
    ptr = head;
    while(ptr->data != x && ptr->right!=NULL)
    {
        ptr=ptr->right;
    }
    if(ptr!=NULL)
    {
        prev=ptr->left;
        next=ptr->right;
        prev->right=ptr->right;
        if(prev->right!=NULL)
        {
            next->left=ptr->left;
        }
        free(ptr);
    }
}
}

```

OUTPUT

Choose operation :

- 1.Insert an element at FIRST
- 2.Insert an element at LAST
- 3.Display
- 4.SEARCH
- 5.Delete First Element....
- 6.Delete Last Element....

7.Insert an item at position

8.Delete an item at Position

1

Enter the element to INSERT

24

Choose operation :

1.Insert an element at FIRST

2.Insert an element at LAST

3.Display

4.SEARCH

5.Delete First Element....

6.Delete Last Element....

7.Insert an item at position

8.Delete an item at Position

2

Enter the element to INSERT

45

Choose operation :

1.Insert an element at FIRST

2.Insert an element at LAST

3.Display

4.SEARCH

5.Delete First Element....

6.Delete Last Element....

7.Insert an item at position

8.Delete an item at Position

1

Enter the element to INSERT

21

Choose operation :

- 1.Insert an element at FIRST
- 2.Insert an element at LAST
- 3.Display
- 4.SEARCH
- 5.Delete First Element....
- 6.Delete Last Element....
- 7.Insert an item at position
- 8.Delete an item at Position

2

Enter the element to INSERT

68

Choose operation :

- 1.Insert an element at FIRST
- 2.Insert an element at LAST
- 3.Display
- 4.SEARCH
- 5.Delete First Element....
- 6.Delete Last Element....
- 7.Insert an item at position
- 8.Delete an item at Position

3

21 24 45 68

Choose operation :

- 1.Insert an element at FIRST
- 2.Insert an element at LAST
- 3.Display
- 4.SEARCH
- 5.Delete First Element....
- 6.Delete Last Element....
- 7.Insert an item at position

8.Delete an item at Position

4

Enter the element to search

45

Element Found

Choose operation :

1.Insert an element at FIRST

2.Insert an element at LAST

3.Display

4.SEARCH

5.Delete First Element....

6.Delete Last Element....

7.Insert an item at position

8.Delete an item at Position

8

Enter the Item you want to DELETE : 45

Choose operation :

1.Insert an element at FIRST

2.Insert an element at LAST

3.Display

4.SEARCH

5.Delete First Element....

6.Delete Last Element....

7.Insert an item at position

8.Delete an item at Position

3

21 24 68

Choose operation :

1.Insert an element at FIRST

2.Insert an element at LAST

3.Display

4.SEARCH

5.Delete First Element....

6.Delete Last Element....

7.Insert an item at position

8.Delete an item at Position

7

Enter the element to INSERT

25

Enter the position where you want to insert item: 24

Choose operation :

1.Insert an element at FIRST

2.Insert an element at LAST

3.Display

4.SEARCH

5.Delete First Element....

6.Delete Last Element....

7.Insert an item at position

8.Delete an item at Position

3

21 24 25 68

RESULT

Program executed successfully and result is verified.

PROGRAM

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
struct node
```

```
{
```

```
int data;
```

```
struct node *left;
```

```
struct node *right;
```

```
};
```

```
struct node *ROOT=NULL;
```

```
void insert();
```

```
void search();
```

```
void inorder(struct node *);
```

```
void preorder(struct node *);
```

```
void postorder(struct node *);
```

```
void delete(int);
```

```
void main()
```

```
{
```

```
    int opt,x;
```

```
    do
```

```
    {
```

```
        printf("Choose operation
```

```
:\n1.INSERT\n2.Inorder_traversal\n3.PreOrder_Traversal\n4.PostOrder_Traversal\n5.search\n6.Delete\n");
```

```
        scanf("%d",&opt);
```

```
        switch(opt)
```

```
        {
```

```
            case 1:insert();
```

```

        break;
    case 2:inorder(ROOT);
        break;
    case 3:preorder(ROOT);
        break;
    case 4:postorder(ROOT);
        break;
    case 5:search();
        break;
    case 6:printf("Enter Data to be deleted\n");
        scanf("%d",&x);
        delete(x);
        break;
    }
}
while(opt!=7);
}

```

```

void insert()
{
    struct node *ne,*ptr,*ptr1;
    int x;
    ne=(struct node *)malloc(sizeof(struct node));
    if (ne == NULL)
    {
        printf("Insufficient Memory") ;
        return;
    }

    printf("Enter Data to insert\n");
}

```

```

scanf("%d",&x);
ne->left=NULL;
ne->right=NULL;
ne->data=x;
if(ROOT == NULL)
    {
        ROOT = ne;
        return;
    }
ptr=ROOT;

while(ptr!=NULL)
{
    if(x==ptr->data)
    {
        printf("Data already exist... \n") ;
        return;
    }
    if(x > ptr->data)
    {
        ptr1=ptr;
        ptr= ptr->right;
    }
    else
    {
        ptr1=ptr;
        ptr= ptr->left;
    }
}

if(ptr==NULL)
{

```

```

        if(x > ptr1->data)
        {
            ptr1->right=ne;
        }
    else
    {
        ptr1->left=ne;
    }
}
}

```

```

void search()
{
    int x;
    struct node *ptr=ROOT;
    printf("\nEnter the data to search: ");
    scanf("%d",&x);
    while(ptr!=NULL)
    {
        if(ptr->data==x)
        {
            printf("Data is present... \n") ;
            break;
        }
        if(x > ptr->data)
        {
            ptr= ptr->right;
        }
    else
    {

```



```
        ptr= ptr->left;
    }

}

if(ptr==NULL)
    printf("\n Data not present. ..\n");
}
```

```
void inorder(struct node *ptr)
{

    if(ptr != NULL)
    {
        inorder(ptr->left);
        printf("%d ",ptr->data);
        inorder(ptr->right);
    }

}
```

```
void preorder(struct node *ptr)
{
    if(ptr != NULL)
    {
        printf("%d ",ptr->data);
        preorder(ptr->left);
        preorder(ptr->right);
    }

}
```

```
void postorder(struct node *ptr)
{

    if(ptr!=NULL)
```

```

    {
        postorder(ptr->left);
        postorder(ptr->right);
        printf("%d ",ptr->data);
    }
}

```

void delete(int x)

```

{
    struct node *ne,*ptr,*parent,*p;
    int dat;

    if (ROOT == NULL)
    {
        printf("\n Tree is Empty \n") ;
        return;
    }

    parent= NULL;
    ptr=ROOT;
    while(ptr!=NULL)
    {
        if(ptr->data==x)
            break;

        parent=ptr;
        if(x > ptr->data)
            ptr= ptr->right;
        else
            ptr= ptr->left;
    }

    if(ptr==NULL)
    {

```

```

        printf("\n Data not present. ..\n");
        return;
    }

if(ptr->right==NULL&&ptr->left==NULL)
{
    if (parent==NULL)
        ROOT=NULL;
    else if (parent->right==ptr)
        parent->right=NULL;
    else
        parent->left=NULL;
    printf("Element deleted");

    free(ptr);
    return;
}

if(ptr->right!=NULL&&ptr->left!=NULL)
{
    p=ptr->right;
    while(p->left!=NULL)
    {
        p=p->left;
    }
    dat=p->data;
    delete(p->data);
    ptr->data=dat;
    return;
}

if (parent==NULL)
{

```

```
        if (ptr->right==NULL)
            ROOT=ptr->left;
        else
            ROOT=ptr->right;
    }
else
    {

        if (parent->right==ptr)
        {
            if (ptr->right==NULL)
                parent->right=ptr->left;
            else
                parent->right=ptr->right;
        }
        else
        {

            if (ptr->left==NULL)
                parent->left= ptr->right;
            else
                parent->left=ptr->left;
        }
    }

printf("Element deleted");
free(ptr);
return;
}
```

OUTPUT

Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

1

Enter Data to insert

25

Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

1

Enter Data to insert

57

Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

1

Enter Data to insert

69

Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

2

25 57 69 Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

3

25 57 69 Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

4

69 57 25 Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

5

Enter the data to search: 57

Data is present....

Choose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

6

Enter Data to be deleted

69

Element deletedChoose operation :

1.INSERT

2.Inorder_traversal

3.PreOrder_Traversal

4.PostOrder_Traversal

5.search

6.Delete

2

25 57

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdlib.h>

#include<stdio.h>

#include<string.h>

void setunion(char *,char *,char *);

void setintersection(char *,char *,char *);

void setdifference(char *,char *,char *);


void main()

{

    char s1[20],s2[20],s3[20];

    printf("Enter set1:\n");

    scanf("%s",s1);

    printf("Enter set2:\n");

    scanf("%s",s2);

    //check whether the two strings are equal or not

    setunion(s1,s2,s3);

    printf("\nunion\n%s",s3);

    setintersection(s1,s2,s3);

    printf("\nintersection\n%s",s3);

    setdifference(s1,s2,s3);

    printf("\nsetdifference\n%s",s3);

}


void setunion(char *s1,char *s2,char *s3)

{

    int i,l=strlen(s1);

    for(i=0;i<l;i++)

    {

        if(s1[i]!='0' && s2[i]!='0')
```

```
s3[i]='0';  
else  
s3[i]='1';  
}  
s3[i]='\0';  
}
```

```
void setintersection(char *s1,char *s2,char *s3)  
{  
int i,l=strlen(s1);  
for(i=0;i<l;i++)  
{  
if(s1[i]=='1' && s2[i]=='1')  
s3[i]='1';  
else  
s3[i]='0';  
}  
s3[i]='\0';  
}
```

```
void setdifference(char *s1,char *s2,char *s3)  
{ int i,l=strlen(s1);  
for(i=0;i<l;i++)  
{ if(s1[i]=='1' && s2[i]=='0')  
s3[i]='1';  
else  
s3[i]='0';  
}  
s3[i]='\0';
```

OUTPUT

Enter set1:

101010001101

Enter set2:

100100110010

union

101110111111

intersection

100000000000

setdifference

001010001101

Process returned 27 (0x1B) execution time : 47.981 s

Press any key to continue.

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdio.h>

#include<stdlib.h>

struct node

{

    int data;


    struct node *next;

};

struct node *first[20];

void makeset(int);

void unions(int,int);

int find(int);

int n=0;

struct edge

{

    int start;

    int weight;

    int end;

};

struct edge adj[30], A[30];

void main()

{

    int i,nv,sum,k,en,s,w,e,u,v,c,count;

    printf("Enter no: of vertices: ");

    scanf("%d",&nv);

    for(i=1;i<=nv;i++)

        makeset(i);

    printf("Enter the no. of edges:");
```

```
scanf("%d",&e);
printf("Enter the edges\n");
printf("start end weight\n");
c=-1;
for(i=1;i<=e;i++)
{
    scanf("%d %d %d",&s,&en,&w);
    for(k=c;k>=0;k--)
    {
        if(adj[k].weight>w)
            adj[k+1]=adj[k];
        else
            break;
    }

    adj[k+1].start=s;
    adj[k+1].end=en;
    adj[k+1].weight=w;
    c++;
}
count=0;
for(i=0;i<c;i++)
{
    u=adj[i].start;
    v=adj[i].end;
    if(find(u)!=find(v))
    {
        A[count].start=u;
        A[count].end=v;
        A[count].weight=adj[i].weight;
```

```

    unions(u,v);

    count++;

}

}

printf("\nSpanning Tree edges\n");

sum=0;

for(i=0;i<count;i++)

{

    printf("(%d->%d) w:%d\n" ,A[i].start,A[i].end,A[i].weight);

    sum=sum+A[i].weight;

}

printf("\nTotal Cost=%d" ,sum);

}

void makeset(int x)

{

    int pos;

    pos=find(x);

    if(pos==-1)

    {

        first[n]=(struct node *)malloc(sizeof(struct node));

        first[n]->data=x;

        first[n]->next=NULL;

        n++;

    }

    else

    {

        printf("Number already exist\n");

    }

}

void unions(int x,int y)

```

```

{
struct node *p;
int i,j;
i=find(x);
j=find(y);
if (i==-1 || j ==-1)
    return;
if (i==j)

    printf("Both are in the same set");
else
    p=first[i];
    while(p->next!=NULL)
{
    p=p->next;
}
    p->next=first[j];
    first[j]=NULL;

}

int find(int x)
{
struct node *p;
int i,j,flag;
flag=0;
for(i=0;i<n;i++)
{
    p=first[i];
    while(p!=NULL)

```



```
{  
    if (p->data==x)  
    {  
        flag=1;  
        break;  
    }  
    p=p->next;  
}  
if (flag==1)  
    break;  
}  
if(flag==1)  
    return i;  
else  
    return -1;  
}
```

OUTPUT

Enter number :5

The Sets are :{ 1 }

{ 2 }

{ 3 }

{ 4 }

{ 5 }

Choose operation :

1.Display

2.Union

3.Find

4.Makeset

5.Exit

4

Enter the number :8

Choose operation :

1.Display

2.Union

3.Find

4.Makeset

5.Exit

1

The Sets are :{ 1 }

{ 2 }

{ 3 }

{ 4 }

{ 5 }

{ 8 }

Choose operation :

1.Display

2.Union

3.Find

4.Makeset

5.Exit

2

Enter the first element:2

Enter the second element:8

Choose operation :

1.Display

2.Union

3.Find

4.Makeset

5.Exit

1

The Sets are :{ 1 }

{ 2 8 }

{ 3 }

{ 4 }

{ 5 }

Choose operation :

1.Display

2.Union

3.Find

4.Makeset

5.Exit

3

Enter the element to Find

2

Element PRESENT in set-> 2

Choose operation :

1.Display

2.Union

3.Find

4.Makeset

5.Exit

5

Process returned 5 (0x5) execution time : 112.015 s

Press any key to continue.

RESULT

Program executed successfully and result is verified.

PROGRAM

```
#include<stdio.h>

#include<stdlib.h>

struct node

{

    int data;


    struct node *next;

};

struct node *first[20];

void makeset(int);

void unions(int,int);

int find(int);

int n=0;

struct edge

{

    int start;

    int weight;

    int end;

};

struct edge adj[30], A[30];

void main()

{

    int i,nv,sum,k,en,s,w,e,u,v,c,count;

    printf("Enter no: of vertices: ");

    scanf("%d",&nv);

    for(i=1;i<=nv;i++)

        makeset(i);

    printf("Enter the no. of edges:");
```

```

scanf("%d",&e);
printf("Enter the edges\n");
printf("start end weight\n");
c=-1;
for(i=1;i<=e;i++)
{
scanf("%d %d %d",&s,&en,&w);
for(k=c;k>=0;k--)
{
if(adj[k].weight>w)
adj[k+1]=adj[k];
else
break;
}

adj[k+1].start=s;
adj[k+1].end=en;
adj[k+1].weight=w;
c++;
}
count=0;
for(i=0;i<c;i++)
{
u=adj[i].start;
v=adj[i].end;
if(find(u)!=find(v))
{
A[count].start=u;
A[count].end=v;
A[count].weight=adj[i].weight;

```

```

    unions(u,v);

    count++;

}

}

printf("\nSpanning Tree edges\n");

sum=0;

for(i=0;i<count;i++)

{

    printf("(%d->%d) w:%d\n" ,A[i].start,A[i].end,A[i].weight);

    sum=sum+A[i].weight;

}

printf("\nTotal Cost=%d" ,sum);

}

void makeset(int x)

{

    int pos;

    pos=find(x);

    if(pos==-1)

    {

        first[n]=(struct node *)malloc(sizeof(struct node));

        first[n]->data=x;

        first[n]->next=NULL;

        n++;

    }

    else

    {

        printf("Number already exist\n");

    }

}

void unions(int x,int y)

```

```

{
struct node *p;
int i,j;
i=find(x);
j=find(y);
if (i==-1 || j ==-1)
    return;
if (i==j)

    printf("Both are in the same set");
else
    p=first[i];
    while(p->next!=NULL)
{
    p=p->next;
}
    p->next=first[j];
    first[j]=NULL;
}
int find(int x)
{
struct node *p;
int i,j,flag;
flag=0;
for(i=0;i<n;i++)
{
    p=first[i];
    while(p!=NULL)
    {
        if (p->data==x)

```



```
{  
    flag=1;  
    break;  
}  
p=p->next;  
}  
if (flag==1)  
    break;  
}  
if(flag==1)  
    return i;  
else  
    return -1;  
}
```

OUTPUT

Enter no: of vertices: 7

Enter the no. of edges:9

Enter the edges

start end weight

1 2 28

2 3 16

3 4 12

4 5 22

5 6 25

6 1 10

5 7 24

7 2 14

7 4 18

Spanning Tree edges

(6->1) w:10

(3->4) w:12

(7->2) w:14

(2->3) w:16

(4->5) w:22

(5->6) w:25

Total Cost=99

Process returned 14 (0xE) execution time : 102.497 s

Press any key to continue.

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdio.h>

#include<stdlib.h>

#define red 1

#define black 0

struct node
{
    int data,color;
    struct node *right,*left;
};

void doop(struct node *,struct node *,struct node *);

void RRRotation(struct node *);

void LLRotation(struct node *);

struct node *ROOT=NULL;

struct node* findParent(struct node *n) ;


struct node * getNode()
{
    struct node *ne;
    ne=(struct node *) malloc(sizeof(struct node));
    if (ne==NULL)
        printf("No Memory");
    return ne;
}


void inorder(struct node *ptr)
{
    if (ptr!=NULL)
    {
        inorder(ptr->left);
        printf("%d(%c) ",ptr->data,ptr->color==0?'b':'r');
        inorder(ptr->right);
    }
}
```

```
}
```

```
struct node* findParent(struct node *n)
{ struct node *ptr=ROOT,*parent=NULL;
  int x=n->data;
  while(ptr!=n)
  { parent=ptr;
    if (x>ptr->data)
      ptr=ptr->right;
    else
      ptr=ptr->left;
  }
  return parent;
}
```

```
void insert()
{ int x;
  struct node *ne,*parent,*ptr,*pparent,*uncle;

  printf("Enter the element to insert");
  scanf("%d",&x);
  ne=getNode();
  if (ne==NULL)
    return;
  ne->data=x;
  ne->left=ne->right=NULL;
  ne->color=red;

  if (ROOT==NULL)
  { ROOT=ne;
```

```

        ne->color=black;

        return;
    }
    ptr=ROOT;
    while(ptr!=NULL)
    {
        if (ptr->data==x)
        {
            printf("Data already present");
            break;
        }
        parent=ptr;
        if (x>ptr->data)
            ptr=ptr->right;
        else
            ptr=ptr->left;
    }
    if (ptr!=NULL)
        return;
    if(x>parent->data)
        parent->right=ne;
    else
        parent->left=ne;
    while(ne!=ROOT)
    {
        parent=findParent(ne);
        if (parent->color==black)
            break;
        if (parent->color==red)
        {
            pparent=findParent(parent);
            if (pparent->right==parent)

```

```

        uncle=pparent->left;
else
    uncle=pparent->right;

if (uncle==NULL)
{
    doop(ne,parent,pparent);
    break;
}
if (uncle->color==black )
{
    doop(ne,parent,pparent);
    break;
}

if (uncle->color==red)
{
    parent->color=uncle->color=black;

    if (pparent!=ROOT)
    { if (pparent->color==red)
        pparent->color=black;
      else
        pparent->color=red;
      if(pparent->color==red)
        ne=pparent;
    }
    else
        break;
}
}

```

```
}  
}  
}
```

```
void doop(struct node *ne,struct node *parent,struct node *pparent)
```

```
{
```

```
    if(ne==parent->left && parent==pparent->left)
```

```
    {    struct node *left=pparent->left;
```

```
        LLRotation(pparent);
```

```
        parent->color=parent->color==1?0:1;
```

```
        pparent->color=pparent->color==1?0:1;
```

```
        if (pparent==ROOT)
```

```
            ROOT=left;
```

```
    }
```

```
    else if (parent==pparent->left && ne==parent->right)
```

```
    { struct node *left=parent->right;
```

```
        RRRotation(parent);
```

```
        LLRotation(pparent);
```

```
        ne->color=ne->color==1?0:1 ;
```

```
        pparent->color=pparent->color==1?0:1;
```

```
        if (pparent==ROOT)
```

```
            ROOT=left;
```

```
    }
```

```
    else if ( ne==parent->right && parent==pparent->right)
```

```
    {    struct node *right=pparent->right;
```

```
        RRRotation(pparent);
```

```
        parent->color=parent->color==0?1:0;
```

```
        pparent->color=pparent->color==0?1:0;
```

```

        if (pparent==ROOT)
            ROOT=right;
    }
else if (parent==pparent->right && ne==parent->left)
    { struct node *left=parent->left;
      LLRotation(parent);
      RRRotation(pparent);
      pparent->color=pparent->color==1?0:1;
      ne->color=ne->color==1?0:1;
      if (pparent==ROOT)
          ROOT=left;
    }
}

void LLRotation(struct node *y)
{
    struct node *p=findParent(y);
    struct node *x=y->left;
    struct node *T2= x->right;
    if (x!=NULL)
        x->right=y;
    y->left=T2;
    if (p!=NULL)
        if (p->right==y)
            p->right=x;
        else
            p->left=x;
}

void RRRotation(struct node *x)
{
    struct node *p=findParent(x);
    struct node *y=x->right;

```



```
struct node *T2=y->left;
if (y!=NULL)
y->left=x;
x->right=T2;
if (p!=NULL)
if (p->right==x)
    p->right=y;
else
    p->left=y;
}
void main()
{
int ch;
do{
    printf("\n 1.Insert\n 2.display\n 3.Exit\n Enter Your choice :");
    scanf("%d",&ch);
    switch(ch)
    { case 1:insert();
        break;
        case 2:inorder(ROOT);
        break;
    }
}while(ch!=3);
}
```

OUTPUT

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 8

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 18

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 5

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 15

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 17

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 25

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 40

1.Insert

2.display

3.Exit

Enter Your choice :2

5(b) 8(b) 15(b) 17(r) 18(r) 25(b) 40(r)

1.Insert

2.display

3.Exit

Enter Your choice :1

Enter the element to insert : 80

1.Insert

2.display

3.Exit

Enter Your choice :2

5(b) 8(r) 15(b) 17(b) 18(b) 25(r) 40(b) 80(r)

1.Insert

2.display

3.Exit

Enter Your choice :3

Process returned 3 (0x3) execution time : 191.859 s

Press any key to continue.

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdio.h>

#include<stdlib.h>

struct node

{ int vertex;

    struct node *next;

};

int v,e;

struct node* adj[20];

int visited[20],top[20];

int t=0;

void dfs();

void dfsvisit();

void main()

{ int s,i,en;

    struct node *ne;

    printf("Enter No: of vertices");

    scanf("%d",&v);

    for(i=0;i<=v;i++)

        adj[i]= NULL;

    printf("enter No: of Edjes");

    scanf("%d",&e);

    printf("Enter the edges\n");

    printf("start End\n");

    for(i=0;i<e;i++)

    { scanf("%d%d",&s,&en);

        ne=(struct node*)malloc(sizeof(struct node));

        ne->vertex=en;

        ne->next=adj[s];

        adj[s]= ne;
```

```

    }

    dfs();
    printf("\nTopological sort order \n");
    for(i=t-1;i>=0;i--)
        printf("%d ",top[i]);
    getch();
}

void dfs()
{ int i;
  for(i=0;i<=v;i++)
    visited[i]=0;
  printf("\ndfs\n");
  for(i=1;i<=v;i++)
    if (visited[i]==0)
        dfsvisit(i);

}

void dfsvisit(int u)
{ int w;
  struct node *ptr;
  visited[u]=1;
  printf("%d ",u);
  ptr=adj[u];
  while(ptr!=NULL)
  { w=ptr->vertex;
    if(visited[w]==0)
        dfsvisit(w);
    ptr=ptr->next;
  }
}

```

```
top[t++]=u;
```

```
}
```

OUTPUT

Enter No: of vertices5

enter No: of Edjes7

Enter the edges

start End

1 5

5 4

4 3

2 3

1 2

1 3

1 4

dfs

1 4 3 2 5

Topological sort order

1 5 2 4 3

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdlib.h>

struct node
{
    int vertex;
    struct node *next;
};

int v,e;

struct node *adj[20],*adj1[20];

int visited[20],ft[20];

int t=0;

void dfs();
void dfsvisit(int);
void dfs1();
void dfsvisit1(int) ;
void adjlistRep(struct node **adj,int s,int en)
{
    struct node *ne=(struct node*)malloc(sizeof(struct node));
    ne->vertex=en;
    ne->next=adj[s];
    adj[s]= ne;
}

void main()
{
    int s,i,en;
    struct node *ptr;
    printf("Enter No: of vertices");
    scanf("%d",&v);
    for(i=0;i<=v;i++)
        adj[i]=adj1[i]=NULL;
    printf("enter No: of Edjes ");
    scanf("%d",&e);
    printf("Enter the edges :\n");
```

```

printf("start End\n");
for(i=0;i<e;i++)
{ scanf("%d%d",&s,&en);
    adjlistRep(adj,s,en);
    adjlistRep(adj1,en,s);

}
dfs();
dfs1();
getch();
}

void dfs()
{ int i;
  for(i=0;i<=v;i++)
  visited[i]=0;
  printf("\ndfs\n");
  for(i=1;i<=v;i++)
  {   if (visited[i]==0)
      {   dfsvisit(i);
          }
      } }

void dfsvisit(int u)
{ int w;
  struct node *ptr;
  visited[u]=1;
  printf("%d ",u);
  ptr=adj[u];
  while(ptr!=NULL)
  { w=ptr->vertex;
    if(visited[w]==0)

```

```

        dfsvisit(w);

    ptr=ptr->next;
}

t++;
ft[u]=t;
}

void dfs1()
{ int i,max=0,ver;

    printf("\n strongly connected components\n");

    for(i=0;i<=v;i++)
        visited[i]=0;
while(1)
{    max=0;

    for(i=1;i<=v;i++)
        { if (visited[i]==0 && ft[i]>max)
            {    ver=i;max=ft[i];}
        }

    if(max==0)
        break;

    printf("{ ");
    dfsvisit1(ver);printf("}\n");
}
}

void dfsvisit1(int u)
{ int w;

    struct node *ptr;

    visited[u]=1;

    printf("%d ",u);

    ptr=adj1[u];

```

```

while(ptr!=NULL)
{ w=ptr->vertex;
  if(visited[w]==0)
    dfsvisit1(w);
  ptr=ptr->next;
}
}

```

OUTPUT

Enter No: of vertices :7

enter No: of Edjes :8

Enter the edges

start End

7 5

5 6

6 7

4 5

1 4

1 2

2 3

3 1

dfs

1 2 3 4 5 6 7

strongly connected components

{ 1 3 2 }

{ 4 }

{ 5 7 6 }

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdio.h>

#include<stdlib.h>

#include<conio.h>

#define inf 999

void addtoadjlist(int s,int en,int w);

int emptyQ();

int extractminQ();

struct node
{
    int vertex;

    int weight;

    struct node *next;
}*adj[20];

int v;

int p[20],key[20],q[20];

int main()
{
    int i,s,en,we,e,u,w,sum=0;

    struct node *ptr;

    printf("Enter No: of vertices:");

    scanf("%d",&v);

    for(i=1;i<=v;i++)
    {
        p[i]=0;

        key[i]=inf;

        q[i]=1;

        adj[i]=NULL;
    }

    printf("No: of edges: ");
```

```

scanf("%d",&e);
printf("Enter the adges\n");
printf("start end weight");
for(i=1;i<=e;i++)
{
    scanf("%d%d%d",&s,&en,&we);
    addtoadjlist(s,en,we);
    addtoadjlist(en,s,we);
}
key[1]=0;
while(!emptyQ())
{
    u=extractminQ();
    ptr=adj[u];
    while(ptr!=NULL)
    {
        w=ptr->vertex;
        if (q[w]==1 && ptr->weight < key[w])
        {
            key[w]=ptr->weight;
            p[w]=u;
        }
        ptr=ptr->next;
    }
}
sum=0;
printf("Spanning tree edges\n");
for(i=2;i<=v;i++)
{
    printf("(%d-%d) w:%d \n",i,p[i],key[i]);
}

```

```

        sum=sum+key[i];
    }

    printf("The total cost is %d",sum);
    getch();
}

int emptyQ()
{
    int i,flag=1;
    for(i=1;i<=v;i++)
    {
        if (q[i]==1)
        {
            flag=0;
            break;
        }
    }
    return flag;
}

int extractminQ()
{
    int i,min=inf,ver;
    for(i=1;i<=v;i++)
    {
        if (key[i]<min && q[i]==1)
        {
            ver=i;
            min=key[i];
        }
    }
    q[ver]=0;

```

```

    return ver;
}
void addtoadjlist(int s,int en,int w)
{
    struct node *ne=(struct node *)malloc(sizeof(struct node));
    ne->vertex=en;
    ne->weight=w;
    ne->next=adj[s];
    adj[s]=ne;
}

```

OUTPUT

Enter No: of vertices:5

No: of edges: 7

Enter the adges

start end weight

1 5 5

5 4 2

4 3 4

2 3 3

1 2 1

1 3 7

1 4 10

Spanning tree edges

(2-1) w:1

(3-2) w:3

(4-3) w:4

(5-4) w:2

The total cost is 10

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdio.h>

#include<conio.h>

#define inf 999

void printpath(int,int);

int extractmin();

int v,adj[20][20],dist[20],visit[20],pred[20];

void main()

{

int e,st,en,w,i,j,src,ver,k;

//clrscr();

printf("Enter the no: of vertices");

scanf("%d",&v);

printf("Enter the no: of edges");

scanf("%d",&e);

    for(i=0;i<=v;i++)

    {

        for(j=0;j<=v;j++)

            adj[i][j]=inf;

        dist[i]=inf;

        visit[i]=0;

    }

    printf("Enter the edges\n");

    printf("start end weight\n");

    for(i=1;i<=e;i++)

    {

        scanf("%d%d%d",&st,&en,&w);

        adj[st][en]=w;

    }

    printf("Enter the starting vertex");
```

```

scanf("%d",&src);

dist[src]=0;

pred[src]=src;

for(k=1;k<=v;k++)
{
    ver=extractmin();
    visit[ver]=1;
    if (dist[ver]==inf) continue;
    for(i=1;i<=v;i++)
    {
        if (adj[ver][i]!=inf&& visit[i]==0 )
            if (dist[i]>dist[ver]+adj[ver][i])
            {
                dist[i]=dist[ver]+adj[ver][i] ;
                pred[i]=ver;
            }
    }
}

for(i=1;i<=v;i++)
{
    if (dist[i]==inf)
        continue;

    printf("path cost to %d= %d ",i,dist[i]);
    if( dist[i]!=inf)
    {
        printpath(i,src);
        printf("->%d",i);
        printf("\n");
    }
}

```

```

    getch();
}
void printpath(int i,int src)
{
    if (pred[i]==src)
    {
        printf("%d ",src);return;
    }
    printpath(pred[i],src);
    printf("->%d ",pred[i]);
}
int extractmin()
{
    int min=inf,i,ver;
    for(i=1;i<=v;i++)
    {
        if (visit[i]==0 && dist[i]<min)
        {
            min=dist[i];
            ver=i;
        }
    }
    return ver;
}

```

OUTPUT

Enter the no: of vertices9

Enter the no: of edges14

Enter the edges

start end weight

0 1 4

0 7 8

1 7 11

1 2 8

7 6 1

7 8 7

2 8 2

8 6 6

2 5 4

2 3 7

6 5 2

3 5 14

3 4 9

5 4 10

Enter the starting vertex0

path cost to 1= 4 0 ->1

path cost to 2= 12 0 ->1 ->2

path cost to 3= 19 0 ->1 ->2 ->3

path cost to 4= 21 0 ->7 ->6 ->5 ->4

path cost to 5= 11 0 ->7 ->6 ->5

path cost to 6= 9 0 ->7 ->6

path cost to 7= 8 0 ->7

path cost to 8= 14 0 ->1 ->2 ->8

RESULT

Program executed successfully and result is verified

PROGRAM

```
#include<stdlib.h>

#include<stdio.h>

struct node

{

    int vertex;

    struct node *next;

};

int v,e;

struct node **adj;

int que[30],visited[30];

int f=-1,r=-1;

void enq(int x){

    if (f== -1 && r== -1)

        f=0;

    r=(r+1)%v;

    que[r]=x;

}

int dequ(){

    int data;

    data=que[f];

    if (f==r)

        f=r=-1;

    else

        f=(f+1)%v;

    return data;

}

void bfs()

{

    struct node *ptr;
```

```

int ver,i,w;
for(i=0;i<=v;i++)
    visited[i]=0;
enq(1);
visited[1]=1;
printf("%d ",1);
while(!(f== -1)){
    ver=dequ();
    ptr=adj[ver];
    while(ptr!=NULL)
    {
        w=ptr->vertex;
        if (visited[w]==0)
        {
            enq(w);
            printf("%d ",w);
            visited[w]=1;
        }
        ptr=ptr->next;
    }
}

void main()
{
    int s,i,en;
    struct node *ne;
    printf("Enter No of vertices:");
    scanf("%d",&v);
    adj= (struct node **)malloc((v+1)*sizeof(struct node *));
    for(i=0;i<=v;i++)

```

```

        adj[i]=NULL;

printf("enter No of Edges:");

scanf("%d",&e);

printf("Enter the edges:\n");

printf("start End\n");

for(i=0;i<e;i++)

    {

        scanf("%d%d",&s,&en);

        ne=(struct node*)malloc(sizeof(struct node));

        ne->vertex=en;

        ne->next=adj[s];

        adj[s]= ne;

    }

printf("\nbfs\n");

bfs();

getch();

}

```

OUTPUT

Enter No of vertices:4

enter No of Edges:6

Enter the edges:

start End

0 2

2 0

0 1

1 2

2 3

3 3

bfs

1 2 3 0

RESULT

Program executed successfully and result is verified.