

Efficient convolution using the DFT

Digital Signal Processing with a focus on audio signals

Fabio Antonacci

February 18, 2026

Background: convolution theorem

- ▶ The convolution operation is at the basis of many signal processing tasks
- ▶ For instance, it enables the computation of the output of digital systems, provided the input signal and the impulse response:

$$y(n) = x(n) * h(n) = \sum_{k=-\infty}^{\infty} x(k)h(n-k)$$

Background: convolution theorem

- ▶ The convolution operation is at the basis of many signal processing tasks
- ▶ For instance, it enables the computation of the output of digital systems, provided the input signal and the impulse response:

$$y(n) = x(n) * h(n) = \sum_{k=-\infty}^{\infty} x(k)h(n-k)$$

- ▶ An important theorem states that convolution is equivalent to a product in the frequency domain:

$$Y(e^{j\omega}) = X(e^{j\omega}) \cdot H(e^{j\omega})$$


Circular convolution

- ▶ A similar theorem exists also for the DFT (sampled version of the DTFT)
- ▶ As the DFT is implicitly periodic in both time and frequency domains, it turns that the convolution theorem involves the circular (cyclic) convolution. For N -points DFT we have, indeed:

$$Y(k) = X(k) \cdot H(k) \quad \longleftrightarrow \quad y(n) = \sum_{k=0}^{N-1} x(k)h(n-k)_N$$

Convolution of finite length signals

- ▶ In practical cases, performing the convolution in the frequency domain may be very efficient
- ▶ Let us consider the simplest case, i.e. that of convolving two finite-length signals:
 - ▶ $x(n)$, input signal with length N_x
 - ▶ $h(n)$, impulse response with length N_h
- ▶ The output signal $y(n) = x(n) * h(n)$ will be time-limited, too, with total length $N = N_x + N_h - 1$ samples, i.e.:



Convolution of finite length signals: computational complexity

- Computing the output signal means calculating the convolution sum:

$$y(n) = x(n) * h(n) = \sum_{k=-\infty}^{\infty} x(k)h(n-k)$$

Convolution of finite length signals: computational complexity

- ▶ Computing the output signal means calculating the convolution sum:

$$y(n) = x(n) * h(n) = \sum_{k=-\infty}^{\infty} x(k)h(n-k)$$

- ▶ As the signals are time-limited, the total number of operations are finite. Specifically, we must compute a total of $(N_x + N_h - 1) \times N_h$ products

Convolution of finite length signals: computational complexity

- ▶ Computing the output signal means calculating the convolution sum:

$$y(n) = x(n) * h(n) = \sum_{k=-\infty}^{\infty} x(k)h(n-k)$$

- ▶ As the signals are time-limited, the total number of operations are finite. Specifically, we must compute a total of $(N_x + N_h - 1) \times N_h$ products
- ▶ The complexity order of time-domain convolution can therefore be approximated as $O(N^2)$

Convolution of finite length signals: computational complexity

- ▶ Computing the output signal means calculating the convolution sum:

$$y(n) = x(n) * h(n) = \sum_{k=-\infty}^{\infty} x(k)h(n-k)$$

- ▶ As the signals are time-limited, the total number of operations are finite. Specifically, we must compute a total of $(N_x + N_h - 1) \times N_h$ products
- ▶ The complexity order of time-domain convolution can therefore be approximated as $O(N^2)$
- ▶ **Idea:** what about computing the convolution in the frequency domain (simple product) instead of working in the time domain?

Convolution using the DFT: idea and motivations

- ▶ The DFT can be computed efficiently using the Fast Fourier Transform (FFT) algorithm

Convolution using the DFT: idea and motivations

- ▶ The DFT can be computed efficiently using the Fast Fourier Transform (FFT) algorithm
- ▶ Specifically, when the signal length N is a power of 2, the computational complexity of the FFT is $O(N \log N)$

Convolution using the DFT: idea and motivations

- ▶ The DFT can be computed efficiently using the Fast Fourier Transform (FFT) algorithm
- ▶ Specifically, when the signal length N is a power of 2, the computational complexity of the FFT is $O(N \log N)$
- ▶ We can therefore exploit the (circular) convolution theorem to speed-up the computation of convolution:
 - ▶ Compute FFT of $x(n)$ and $h(n)$: $O(N \log N)$
 - ▶ Compute the products $Y(k) = X(k)H(k)$: $O(N)$
 - ▶ Compute IFFT of $Y(k)$: $O(N \log N)$

Convolution using the DFT: idea and motivations

- ▶ The DFT can be computed efficiently using the Fast Fourier Transform (FFT) algorithm
- ▶ Specifically, when the signal length N is a power of 2, the computational complexity of the FFT is $O(N \log N)$
- ▶ We can therefore exploit the (circular) convolution theorem to speed-up the computation of convolution:
 - ▶ Compute FFT of $x(n)$ and $h(n)$: $O(N \log N)$
 - ▶ Compute the products $Y(k) = X(k)H(k)$: $O(N)$
 - ▶ Compute IFFT of $Y(k)$: $O(N \log N)$

Result: overall complexity of FFT-based convolution is $O(N \log N)$ (lower than in the time domain!)

Dealing with circular convolution

- ▶ The main issue about using the DFT is that cyclic convolution is involved

Dealing with circular convolution

- ▶ The main issue about using the DFT is that cyclic convolution is involved
- ▶ Suppose that the DFTs are of length N , the circular convolution can be rewritten as:

$$\begin{aligned}y(n) &= \sum_{k=0}^{N-1} x(k)h(n-k)_N \\&= \sum_{k=0}^n x(k)h(n-k) + \sum_{k=n+1}^{N-1} x(k)h(n-k+N), \quad \text{for } 0 \leq n \leq N-1\end{aligned}$$

- ▶ If we want the circular convolution to be equal to the linear a-cyclic convolution between $x(n)$ and $h(n)$, the second summation must be null, i.e.

$$c(n) = \sum_{k=n+1}^{N-1} x(k)h(n-k+N) = 0, \quad \text{for } 0 \leq n \leq N-1$$

Dealing with circular convolution

- ▶ The main issue about using the DFT is that cyclic convolution is involved
- ▶ Suppose that the DFTs are of length N , the circular convolution can be rewritten as:

$$\begin{aligned} y(n) &= \sum_{k=0}^{N-1} x(k)h(n-k)_N \\ &= \sum_{k=0}^n x(k)h(n-k) + \sum_{k=n+1}^{N-1} x(k)h(n-k+N), \quad \text{for } 0 \leq n \leq N-1 \end{aligned}$$

Dealing with circular convolution

- ▶ The main issue about using the DFT is that cyclic convolution is involved
- ▶ Suppose that the DFTs are of length N , the circular convolution can be rewritten as:

$$\begin{aligned} y(n) &= \sum_{k=0}^{N-1} x(k)h(n-k)_N \\ &= \sum_{k=0}^n x(k)h(n-k) + \sum_{k=n+1}^{N-1} x(k)h(n-k+N), \quad \text{for } 0 \leq n \leq N-1 \end{aligned}$$

- ▶ If we want the circular convolution to be equal to the linear a-cyclic convolution between $x(n)$ and $h(n)$, the second summation must be null, i.e.

$$c(n) = \sum_{k=n+1}^{N-1} x(k)h(n-k+N) = 0, \quad \text{for } 0 \leq n \leq N-1$$

Dealing with circular convolution (cont')

- ▶ We know that:
 - ▶ $x(n)$ has duration N_x , so we set $x(n) = 0$ for $n \geq N_x$ and $n < 0$
 - ▶ $h(n)$ has duration N_h , so we set $h(n) = 0$ for $n \geq N_h$ and $n < 0$

Dealing with circular convolution (cont')

- ▶ We know that:
 - ▶ $x(n)$ has duration N_x , so we set $x(n) = 0$ for $n \geq N_x$ and $n < 0$
 - ▶ $h(n)$ has duration N_h , so we set $h(n) = 0$ for $n \geq N_h$ and $n < 0$
- ▶ Therefore, we can force the summation $c(n)$ to be identically zero if we select

$$N \geq N_x + N_h - 1$$

- ▶ Note that $N_x + N_h - 1$ is exactly the duration of the output signal $y(n) = x(n) * h(n)$

Dealing with circular convolution (cont')

- ▶ We know that:
 - ▶ $x(n)$ has duration N_x , so we set $x(n) = 0$ for $n \geq N_x$ and $n < 0$
 - ▶ $h(n)$ has duration N_h , so we set $h(n) = 0$ for $n \geq N_h$ and $n < 0$
- ▶ Therefore, we can force the summation $c(n)$ to be identically zero if we select

$$N \geq N_x + N_h - 1$$

- ▶ Note that $N_x + N_h - 1$ is exactly the duration of the output signal $y(n) = x(n) * h(n)$
- ▶ Considering N -length signals in place of their original lengths correspond to **zero-padding**, i.e. appending trailing zeros to reach the length N

Dealing with circular convolution (cont')





- ▶ We know that:
 - ▶ $x(n)$ has duration N_x , so we set $x(n) = 0$ for $n \geq N_x$ and $n < 0$
 - ▶ $h(n)$ has duration N_h , so we set $h(n) = 0$ for $n \geq N_h$ and $n < 0$
- ▶ Therefore, we can force the summation $c(n)$ to be identically zero if we select

$$N \geq N_x + N_h - 1$$

- ▶ Note that $N_x + N_h - 1$ is exactly the duration of the output signal $y(n) = x(n) * h(n)$
- ▶ Considering N -length signals in place of their original lengths correspond to **zero-padding**, i.e. appending trailing zeros to reach the length N
- ▶ Remark: to fully exploit the efficiency of the FFT algorithm, N should be selected as a power of 2

Zero-padding

Example of zero-padding of the two sequences to be convolved:



Zero-padding and time-domain aliasing

- ▶ Note that the condition $N \geq N_x + N_h - 1$ can be interpreted as an anti-aliasing one
- ▶ Indeed, if we add an insufficient number of zeros (i.e., the final signals length is $N < N_x + N_h - 1$), we have $c(n) \neq 0$ in general
- ▶ Recall that the DFT corresponds to sampling the DTFT: we must sample it at least at $N_x + N_h - 1$ points to avoid overlapping replicas in the time domain!
- ▶ If we don't add enough zeros, some of our convolution terms “wrap around” and add back upon others (due to modulo indexing): this generates **time domain aliasing**

Convolution using the DFT: algorithm

Convolution using the DFT: algorithm

1. Compute the N -points DFTs of $x(n)$ and $h(n)$:

$$X(k) = \sum_{n=0}^{N-1} x(n) e^{-j \frac{2\pi kn}{N}}, \quad k = 0, 1, \dots, N-1$$

$$H(k) = \sum_{n=0}^{N-1} h(n) e^{-j \frac{2\pi kn}{N}}, \quad k = 0, 1, \dots, N-1$$

Convolution using the DFT: algorithm

1. Compute the N -points DFTs of $x(n)$ and $h(n)$:

$$X(k) = \sum_{n=0}^{N-1} x(n)e^{-j\frac{2\pi kn}{N}}, \quad k = 0, 1, \dots, N-1$$

$$H(k) = \sum_{n=0}^{N-1} h(n)e^{-j\frac{2\pi kn}{N}}, \quad k = 0, 1, \dots, N-1$$

2. Compute the products (convolution in frequency domain):

$$Y(k) = X(k)H(k), \quad k = 0, 1, \dots, N-1$$

Convolution using the DFT: algorithm

1. Compute the N -points DFTs of $x(n)$ and $h(n)$:

$$X(k) = \sum_{n=0}^{N-1} x(n)e^{-j\frac{2\pi kn}{N}}, \quad k = 0, 1, \dots, N-1$$

$$H(k) = \sum_{n=0}^{N-1} h(n)e^{-j\frac{2\pi kn}{N}}, \quad k = 0, 1, \dots, N-1$$

2. Compute the products (convolution in frequency domain):

$$Y(k) = X(k)H(k), \quad k = 0, 1, \dots, N-1$$

3. Obtain the output signal via N -points IDFT:

$$y(n) = \frac{1}{N} \sum_{k=0}^{N-1} Y(k)e^{j\frac{2\pi kn}{N}}, \quad n = 0, 1, \dots, N-1$$

Convolution of indefinite length signals

- ▶ We saw that we can perform efficient linear convolution of two finite length sequences using Fourier based techniques

Convolution of indefinite length signals

- ▶ We saw that we can perform efficient linear convolution of two finite length sequences using Fourier based techniques
- ▶ There are some situations where it will not be practical to perform the convolution of two signals using a single FFT:
 - ▶ N_x is extremely large
 - ▶ Real time operation (we can't wait until the signal ends)

Convolution of indefinite length signals

- ▶ We saw that we can perform efficient linear convolution of two finite length sequences using Fourier based techniques
- ▶ There are some situations where it will not be practical to perform the convolution of two signals using a single FFT:
 - ▶ N_x is extremely large
 - ▶ Real time operation (we can't wait until the signal ends)
- ▶ Theoretically, there is no problem doing this with direct convolution: since $h(n)$ is finite-length, we only need to store the past N_h samples of the input signal
- ▶ However, this would require N_h products for each output sample

Overlap and add: overview

- ▶ For the above reason, filtering directly in the time domain can be extremely time-consuming when N_h is large
- ▶ Again, a more efficient solution is that of computing the convolution in the frequency domain

Overlap and add: overview

- ▶ For the above reason, filtering directly in the time domain can be extremely time-consuming when N_h is large
- ▶ Again, a more efficient solution is that of computing the convolution in the frequency domain
- ▶ **Idea:** use overlap-and-add to process the signal on a frame basis
 - ▶ processing one frame (segment) at a time
 - ▶ compute FFT convolution on each frame separately
 - ▶ put it all back together correctly (we'll see how to)

Overlap and add: overview

- ▶ For the above reason, filtering directly in the time domain can be extremely time-consuming when N_h is large
- ▶ Again, a more efficient solution is that of computing the convolution in the frequency domain
- ▶ **Idea:** use overlap-and-add to process the signal on a frame basis
 - ▶ processing one frame (segment) at a time
 - ▶ compute FFT convolution on each frame separately
 - ▶ put it all back together correctly (we'll see how to)
- ▶ **Frames** (or **segments**) from the input signal $x(n)$ are extracted as


$$x_m(n) \triangleq x(n)w(n - mR) , n \in (-\infty, +\infty) ,$$

where:

- ▶ $w(n)$ is a length M window (rectangular/Hamming/...)
- ▶ m is the frame index
- ▶ R is the hop-size

Overlap-and-add: overview (cont')

Example of frame extraction:



Constant overlap-and-add condition

- ▶ For this frame-by-frame spectral processing to work, we must be able to reconstruct $x(n)$ from the individual overlapping frames.

Constant overlap-and-add condition

- For this frame-by-frame spectral processing to work, we must be able to reconstruct $x(n)$ from the individual overlapping frames. This can be written as

$$x(n) = \sum_{m=-\infty}^{+\infty} x_m(n) = \sum_{m=-\infty}^{+\infty} x(n)w(n - mR) = x(n) \sum_{m=-\infty}^{+\infty} w(n - mR)$$

Constant overlap-and-add condition

- ▶ For this frame-by-frame spectral processing to work, we must be able to reconstruct $x(n)$ from the individual overlapping frames. This can be written as

$$x(n) = \sum_{m=-\infty}^{+\infty} x_m(n) = \sum_{m=-\infty}^{+\infty} x(n)w(n - mR) = x(n) \sum_{m=-\infty}^{+\infty} w(n - mR)$$


- ▶ It follows that

$$x(n) = \sum_{m=-\infty}^{+\infty} x_m(n) \iff \sum_{m=-\infty}^{+\infty} w(n - mR) = 1$$

- ▶ The last equality plays a key-role in overlap-and-add convolution, and it is called **Constant Overlap-And-Add (COLA) condition** on the analysis window $w(n)$

Constant overlap-and-add condition (cont')

- ▶ All windows which obey the COLA will yield perfect reconstruction of the original signal from the data frames by overlap-add
- ▶ There is no constraint on window type, only that the window overlap-adds to a constant for the hop size used
- ▶ Examples (where M is the generic window length):
 - ▶ Rectangular window at 0% overlap ($R = M$)
 - ▶ Rectangular window at 50% overlap ($R \approx M/2$, i.e., $R = M/2$ if M is even, $R = (M - 1)/2$ if M is odd)
 - ▶ Hamming window at 50% overlap ($R \approx M/2$)
 - ▶ Hamming window at 75% overlap ($R \approx M/4$)
 - ▶ Triangular (Bartlett) window at 50% overlap (see figure below)
 - ▶ Any window with $R = 1$



Frequency-domain convolution via OLA

- ▶ Once a suitable window has been selected, the convolution process can be expressed as follows:

$$y(n) = x(n) * h(n) = \sum_{m=-\infty}^{\infty} x_m(n) * h(n)$$

- ▶ The last equation tells that the overall convolution operation can be separated into a summation of finite-length convolutions on signal segments
- ▶ The segment convolutions can be accomplished in the frequency domain, exploiting the efficiency of the FFT algorithm

Frequency-domain convolution via OLA (cont')

- ▶ Let's denote the result of the m th convolution as

$$y_m(n) = x_m(n) * h(n)$$

Frequency-domain convolution via OLA (cont')

- ▶ Let's denote the result of the m th convolution as

$$y_m(n) = x_m(n) * h(n)$$

- ▶ To compute the DFT, it is convenient to shift-back the frames to the origin. Let's define:

$$\tilde{x}_m(n) \triangleq \text{SHIFT}_{mR}[x_m(n)] \triangleq x_m(n + mR)$$

$$\tilde{y}_m(n) \triangleq \text{SHIFT}_{mR}[y_m(n)] \triangleq y_m(n + mR) = \tilde{x}_m(n) * h(n)$$

Frequency-domain convolution via OLA (cont')

- ▶ Let's denote the result of the m th convolution as

$$y_m(n) = x_m(n) * h(n)$$

- ▶ To compute the DFT, it is convenient to shift-back the frames to the origin. Let's define:

$$\tilde{x}_m(n) \triangleq \text{SHIFT}_{mR}[x_m(n)] \triangleq x_m(n + mR)$$

$$\tilde{y}_m(n) \triangleq \text{SHIFT}_{mR}[y_m(n)] \triangleq y_m(n + mR) = \tilde{x}_m(n) * h(n)$$

- ▶ This way, the signals are so that:
 - ▶ $\tilde{x}_m(n) = 0$ for $n < 0$ and $n \geq M$
 - ▶ $\tilde{y}_m(n) = 0$ for $n < 0$ and $n \geq N_h$

Frequency-domain convolution via OLA (cont')

- ▶ The m th convolution can be safely performed using N -points DFTs, paying attention to:
 - ▶ select $N \geq M + N_h - 1$ for avoiding aliasing problems
 - ▶ zero-pad both $\tilde{x}_m(n)$ and $h(n)$ to reach length N

Frequency-domain convolution via OLA (cont')

- ▶ The m th convolution can be safely performed using N -points DFTs, paying attention to:
 - ▶ select $N \geq M + N_h - 1$ for avoiding aliasing problems
 - ▶ zero-pad both $\tilde{x}_m(n)$ and $h(n)$ to reach length N
- ▶ The N -points DFTs are thus computed as

$$\tilde{X}_m(k) = \sum_{n=0}^{N-1} \tilde{x}_m(n) e^{-j \frac{2\pi kn}{N}}$$

$$H(k) = \sum_{n=0}^{N-1} h(n) e^{-j \frac{2\pi kn}{N}}$$

Frequency-domain convolution via OLA (cont')

- ▶ The time-domain convolution corresponds to a multiplication in the frequency-domain:

$$\tilde{Y}_m(k) = \tilde{X}_m(k) \cdot H(k)$$

Frequency-domain convolution via OLA (cont')

- ▶ The time-domain convolution corresponds to a multiplication in the frequency-domain:

$$\tilde{Y}_m(k) = \tilde{X}_m(k) \cdot H(k)$$

- ▶ The time-domain segment is then recovered via N -points IDFT:

$$\tilde{y}_m(n) = \frac{1}{N} \sum_{k=0}^{N-1} \tilde{Y}_m(k) e^{j \frac{2\pi kn}{N}}$$

Frequency-domain convolution via OLA (cont')

- ▶ The time-domain convolution corresponds to a multiplication in the frequency-domain:

$$\tilde{Y}_m(k) = \tilde{X}_m(k) \cdot H(k)$$

- ▶ The time-domain segment is then recovered via N -points IDFT:

$$\tilde{y}_m(n) = \frac{1}{N} \sum_{k=0}^{N-1} \tilde{Y}_m(k) e^{j \frac{2\pi kn}{N}}$$

- ▶ The overall output signal is finally obtained by superposing all the filtered segments, remembering to shift back each segment to the right position:

$$y(n) = \sum_{m=-\infty}^{\infty} \text{SHIFT}_{-mR} [\tilde{y}_m(n)] = \sum_{m=-\infty}^{\infty} \tilde{y}_m(n - mR) = \sum_{m=-\infty}^{\infty} y_m(n)$$

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero
2. Divide $x(n)$ into length- N segments $x_m(n)$

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero
2. Divide $x(n)$ into length- N segments $x_m(n)$
3. For each block repeat:

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero
2. Divide $x(n)$ into length- N segments $x_m(n)$
3. For each block repeat:
 - ▶ Obtain $\tilde{x}_m(n)$ by shifting $x_m(n)$ to the origin

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero
2. Divide $x(n)$ into length- N segments $x_m(n)$
3. For each block repeat:
 - ▶ Obtain $\tilde{x}_m(n)$ by shifting $x_m(n)$ to the origin
 - ▶ Zero-pad $h(n)$ and $\tilde{x}_m(n)$ to length $N \geq M + N_h - 1$

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero
2. Divide $x(n)$ into length- N segments $x_m(n)$
3. For each block repeat:
 - ▶ Obtain $\tilde{x}_m(n)$ by shifting $x_m(n)$ to the origin
 - ▶ Zero-pad $h(n)$ and $\tilde{x}_m(n)$ to length $N \geq M + N_h - 1$
 - ▶ Obtain $\tilde{y}_m(n)$ by performing alias-free convolution using the FFT

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero
2. Divide $x(n)$ into length- N segments $x_m(n)$
3. For each block repeat:
 - ▶ Obtain $\tilde{x}_m(n)$ by shifting $x_m(n)$ to the origin
 - ▶ Zero-pad $h(n)$ and $\tilde{x}_m(n)$ to length $N \geq M + N_h - 1$
 - ▶ Obtain $\tilde{y}_m(n)$ by performing alias-free convolution using the FFT
 - ▶ Obtain $y_m(n)$ by shifting $\tilde{y}_m(n)$ back to the original position

Frequency-domain convolution via OLA: algorithm

Collecting the equations discussed before, we can summarize the overlap-and-add algorithm:

1. Initialize an output buffer $y(n)$ at zero
2. Divide $x(n)$ into length- N segments $x_m(n)$
3. For each block repeat:
 - ▶ Obtain $\tilde{x}_m(n)$ by shifting $x_m(n)$ to the origin
 - ▶ Zero-pad $h(n)$ and $\tilde{x}_m(n)$ to length $N \geq M + N_h - 1$
 - ▶ Obtain $\tilde{y}_m(n)$ by performing alias-free convolution using the FFT
 - ▶ Obtain $y_m(n)$ by shifting $\tilde{y}_m(n)$ back to the original position
 - ▶ Overlap and add $y_m(n)$ to the output buffer $y(n)$

Overlap-and-add example

