Experimental Methodology — Key Concepts

Lesson 5 — Technologies for Artificial Intelligence

Fabio Antonini — Università degli Studi dell'Aquila

6 November 2026 · a one-page index

Contents

A score is a measurement 1
Cross-validation 2
What error is made of 2
Learning curves 3
Leakage cross-validation cannot catch 3
Reproducibility 3

An index, not a summary. Each entry says what a term means and where the handout treats it properly. Use this to find your way back into the text, or to check before an exercise that there is no word here you could not define.

A score is a measurement

Unbiased is not precise. Holding data out makes a test score right on average. It does nothing whatever to make it repeatable, and the two are routinely confused. → § 2.1

Error bar on a test score. A score is computed on a finite sample; a different sample gives a different number, and how different is a property of the sample's size. → § 2.2

The count of the rarer class. What actually governs the precision of a classification metric — not the size of the dataset. The diagnostic question is *how many positives are in the test set?* → § 2.4

Why it is the rarer class. A metric computed over the positives is a proportion over m_+ draws, so its standard error carries m_+ in the denominator and the healthy rows do not appear in it at all. → § 2.4

Why flattering results are dangerous. A disappointing score makes you keep working; a delightful one makes you stop. The errors that survive are the ones nobody had reason to look for. → § 2.3

Selection on noise. Choosing between models with a noisy number is worse than reporting one, because noise does not average out when it is used to decide — it decides. → § 3

Parameters and hyperparameters. The coefficients and intercept a fit estimates from the data are parameters. What it does not estimate — penalty strength, number of neighbours, tree depth, and the decision threshold applied after the fit — are hyperparameters: they govern the fitting or

the decision, and are chosen from outside by comparison. Not "fixed before the fit": the threshold is chosen after it. → § 3

`C` in scikit-learn. The reciprocal of a penalty strength, so small `C` is heavy regularisation. It runs opposite to lesson 3's λ. → § 3

Two recipes for choosing a hyperparameter. One fixed before the fit needs its own fits for every candidate, then a refit of the winner; one chosen after the fit, like a threshold, is tried on the probabilities of a single fit. Either way the test set is scored once, at the end. → § 3

Cross-validation

k-fold cross-validation. Cut the data into k parts, train on $k-1$ and score on the one left out, the validation fold, rotating until every row has been predicted exactly once by a model that never saw it. → § 4.1

Fold and round. A fold is a part of the data; a round is one fit and one score, so one model per round. scikit-learn calls a round a split. → § 4.1

What it estimates. The performance of a *procedure* applied to a dataset of about this size — not of any one fitted model, of which there are k. → § 4.2

Its pessimism. Each round's model trains on a fraction of the data, so the estimate describes a slightly smaller training set than the one you will ship. The bias is in the safe direction. → § 4.2

Confidence interval. An estimate plus or minus about two standard errors, a range built to contain the true value in 95 of 100 repeated experiments. → § 4.3

Why the usual error bar is optimistic. $s/\sqrt{k}$ assumes independent scores. Overlapping training sets can correlate them, and a standard deviation computed from a handful of scores is itself rough, too small more often than not. → § 4.3

The variance of a mean of correlated measurements. The variance of a sum collects the covariances as well as the variances, which is the term $s/\sqrt{k}$ silently sets to zero. → § 4.3

Stratified folds. Folds that keep each class in its overall proportion, so a rare class cannot land almost entirely in one of them. → § 4.4

Repeated k-fold. The whole cross-validation run with several shuffles and averaged; it removes the dependence on how the folds were cut, not the uncertainty about new data. → § 4.5

Grouped folds. Splitting along the axis you must generalise across, when several rows share a source — a patient, a document, a machine. The group label is passed apart from the features and is never one of them. → § 4.6

Time-ordered splits. Training on a prefix and testing on what comes next, because real use always predicts forward. → § 4.6

What error is made of

Bias. Being consistently wrong: models fitted to different samples all miss the truth in the same way. Not the bias of an estimate, which sections 2 and 7 use. → § 5.1

Variance. Being unreliable: models fitted to different samples disagree wildly, worst at the edges of the range, where all the points lie on one side. → § 5.1

Irreducible noise. The part of the error that is a property of the data, not of the model. No method and no quantity of data goes below it. → § 5.1

The decomposition. Expected squared error equals bias squared plus variance plus noise. An identity, not an approximation. → § 5.2

The noise floor. The value that decomposition's last term sets. A test error *below* it is evidence of leakage, not of excellence; a training error can go below it by fitting the noise. → § 5.3

Model choice depends on sample size. The complexity that minimises total error moves as data grows — which is why a paper's result on a larger dataset may honestly fail to reproduce on yours. → § 5.4

Training error against validation error. The diagnosis without the truth: training error high means bias; validation far above training means variance. Both come from cross-validation inside the training data, never from the test set. → § 5.5

Learning curves

Learning curve. Training and cross-validated scores plotted against the number of examples used. The *shapes* carry the diagnosis. → § 6

High bias. The curves meet, and meet low. A more flexible model or better features help; more data does not. → § 6.1

High variance. A wide gap between a high training score and a lower validation one. What to do depends on the *slope*: still rising means collect more, flattened means regularise or simplify. → § 6.1

Leakage cross-validation cannot catch

Fold leakage. A step fitted on all the data before the folds are cut, so the selection has already seen every validation row. Cross-validation does not fail here; it is lied to. → § 7.1

Searching a large space on a small sample. The residual optimism that survives even an honest fold-wise fit: a spurious correlation present in *these* rows is present in every subset of them. → § 7.2

Optimism of `best_score_`. The maximum of many noisy estimates is biased upward even when every estimate measures the same quantity. → § 7.3

Nested cross-validation. Run the entire search inside an outer training fold and score on the outer test fold. It measures what *searching* costs; it is not a way to choose. → § 7.4

Train, validation, test. Fit on the first, choose on the second, report once on the third. The honest number is expected to be worse than the cheating one. → § 8

Reproducibility

Seeds. Fix them and write them down — but a fixed seed buys repeatability, not stability: a perfectly reproducible run can still be a lucky one. → § 9.1

Library versions. Defaults change between releases, so a result nobody can reproduce in two years was never reproducible. → § 9.2

What belongs in a report. The metric, the spread and how it was estimated; how many positives the test set held; every seed and version; and which choices were made on which data. → § 10