

Stochastic Neighborhood Embedding

Weekly AI pills

Fabio Brau.

2020-11-13

SSSA, Emerging Digital Technologies, Pisa.

ISTITUTO
DI TECNOLOGIE DELLA
COMUNICAZIONE,
DELL'INFORMAZIONE
E DELLA
PERCEZIONE



Scuola Superiore
Sant'Anna




1. Entropy and Kullback–Leibler divergence
2. From SNE to t-SNE
3. Application for Visualization
4. Issues



(t)-Stochastic Neighborhood Embedding

Aims

- Dimensionality Reduction
- Data Visualization
 1. Exploration
 2. Visual Clustering



Example of Data Visualization
taken from (Tasic et al., 2018)

Algorithm



Algorithm: Workflow

1. Represent each sample $x_i \in \mathcal{X}$ with $y_i \in \mathcal{Y}$ in a low-dimensional space

$$\Phi : \underset{\subseteq \mathbb{R}^n}{\mathcal{X}} \longrightarrow \underset{\subseteq \mathbb{R}^2}{\mathcal{Y}}$$

2. Convert **Geometrical Information** to **Probabilistic Distribution**

p_{ij} : “Probability that x_i is *similar* to x_j ”

q_{ij} : “Probability that y_i is *similar* to y_j ”

3. Compare distribution \mathcal{P} of \mathcal{X} to distribution \mathcal{Q} of \mathcal{X}
4. Adjust the representation Φ to make distributions closer.

Observation

The embedding Φ is defined point-wise, i.e Φ is only defined over \mathcal{X} through the definition $\Phi(x_i) = y_i$. Another way to say “ y_i are the parameters of Φ ” (Future works?).

Algorithm: Workflow

1. Represent each sample $x_i \in \mathcal{X}$ with $y_i \in \mathcal{Y}$ in a low-dimensional space

$$\Phi : \underset{\subseteq \mathbb{R}^n}{\mathcal{X}} \longrightarrow \underset{\subseteq \mathbb{R}^2}{\mathcal{Y}}$$

2. Convert **Geometrical Information** to **Probabilistic Distribution**

$p_{i|j}$: “Probability that x_i is *similar* to x_j ”

$q_{i|j}$: “Probability that y_i is *similar* to y_j ”

3. Compare distribution \mathcal{P} of \mathcal{X} to distribution \mathcal{Q} of \mathcal{X}
4. Adjust the representation Φ to make distributions closer.

Observation

The embedding Φ is defined **point-wise**, i.e Φ is only defined over \mathcal{X} through the definition $\Phi(x_i) = y_i$. Another way to say “ y_i are the parameters of Φ ” (Future works?).

Algorithm: Similarity and Probability Distribution

Definition (Similarity with Gaussian Kernel)

For each x_i we consider the similarity

$$\forall j \neq i, \quad p_{ij} = \frac{\exp(-\|x_i - x_j\|^2 / (2\sigma_i)^2)}{\sum_{k \neq i} \exp(-\|x_i - x_k\|^2 / (2\sigma_i)^2)} \quad (\mathcal{P}_i)$$

where σ_i is an hyper-parameter depending on x_i .

How σ_i impacts on p_{ij} ?

Algorithm: Similarity and Probability Distribution

Definition (Similarity with Gaussian Kernel)


For each x_i we consider the similarity

$$\forall j \neq i, \quad p_{i|j} = \frac{\exp(-\|x_i - x_j\|^2 / (2\sigma_i)^2)}{\sum_{k \neq i} \exp(-\|x_i - x_k\|^2 / (2\sigma_i)^2)} \quad (\mathcal{P}_i)$$

where σ_i is an hyper-parameter depending on x_i .

How σ_i impacts on $p_{i|j}$?

Similarity to (0,0) for sigma=0.1



Algorithm: Similarity and Probability Distribution

Definition (Similarity with Gaussian Kernel)


For each x_i we consider the similarity

$$\forall j \neq i, \quad p_{i|j} = \frac{\exp(-\|x_i - x_j\|^2 / (2\sigma_i)^2)}{\sum_{k \neq i} \exp(-\|x_i - x_k\|^2 / (2\sigma_i)^2)} \quad (\mathcal{P}_i)$$

where σ_i is an hyper-parameter depending on x_i .

How σ_i impacts on $p_{i|j}$?

Similarity to (0,0) for sigma=0.2



Algorithm: Similarity and Probability Distribution


Definition (Similarity with Gaussian Kernel)

For each x_i we consider the similarity

$$\forall j \neq i, \quad p_{i|j} = \frac{\exp(-\|x_i - x_j\|^2 / (2\sigma_i)^2)}{\sum_{k \neq i} \exp(-\|x_i - x_k\|^2 / (2\sigma_i)^2)} \quad (\mathcal{P}_i)$$

where σ_i is an hyper-parameter depending on x_i .

How σ_i impacts on $p_{i|j}$?



Algorithm: Similarity and Probability Distribution


Definition (Similarity with Gaussian Kernel)

For each x_i we consider the similarity

$$\forall j \neq i, \quad p_{ij} = \frac{\exp(-\|x_i - x_j\|^2 / (2\sigma_i)^2)}{\sum_{k \neq i} \exp(-\|x_i - x_k\|^2 / (2\sigma_i)^2)} \quad (\mathcal{P}_i)$$

where σ_i is an hyper-parameter depending on x_i .

How σ_i impacts on p_{ij} ?



Algorithm: Similarity and Probability Distribution


Definition (Similarity with Gaussian Kernel)

For each x_i we consider the similarity

$$\forall j \neq i, \quad p_{ij} = \frac{\exp(-\|x_i - x_j\|^2 / (2\sigma_i)^2)}{\sum_{k \neq i} \exp(-\|x_i - x_k\|^2 / (2\sigma_i)^2)} \quad (\mathcal{P}_i)$$

where σ_i is an hyper-parameter depending on x_i .

How σ_i impacts on p_{ij} ?



Algorithm: Similarity and Probability Distribution

In the same manner we can define similarity in \mathcal{Y} .

$$\forall j \neq i, \quad q_{i|j} = \frac{\exp(-\|y_i - y_j\|^2)}{\sum_{k \neq i} \exp(-\|y_i - y_k\|^2)} \quad (\mathcal{Q}_i)$$

Observation

\mathcal{P}_i and \mathcal{Q}_i are probability distributions for each i .

1. $0 \leq p_{i|j}, q_{i|j} \leq 1$ for each $j \neq i$
2. $\sum_{j \neq i} p_{i|j} = \sum_{j \neq i} q_{i|j} = 1$



Algorithm: Kullback-Leibler Divergence

Definition (K.L Divergence)

Let $\mathcal{P} = \{p_1, \dots, p_n\}$ and $\mathcal{Q} = \{q_1, \dots, q_n\}$ distributions

$$KL(\mathcal{P}, \mathcal{Q}) = \sum_i p_i \log_2 \left(\frac{p_i}{q_i} \right) \quad (1)$$

We can compare $\mathcal{P}_i, \mathcal{Q}_i$ for each i by taking

$$C(\mathcal{Y}) := \sum_i KL(\mathcal{P}_i, \mathcal{Q}_i) \quad (2)$$

Observation: The cost function C is differentiable in y_i

$$\begin{aligned} \frac{\partial C}{\partial y_i} &= 2 \sum_{j \neq i} (p_{i|j} + p_{j|i} - q_{i|j} - q_{j|i}) (y_i - y_j) \\ &= \left[\sum_{j \neq i} (p_{i|j} + p_{j|i}) (y_i - y_j) \right] - \left[\sum_{j \neq i} (q_{i|j} + q_{j|i}) (y_i - y_j) \right] \end{aligned} \quad (3)$$

Attractive Repulsive

SNE Algorithm

1. Choose $\Phi^{(0)}$ embedding, i.e choose $\{y_i^{(0)}\}$
2. Compute \mathcal{P}_i and \mathcal{Q}_i distributions.
3. Minimize $C(\mathcal{Y})$ through Gradient Descent with momentum

$$y_i^{(t+1)} = y_i^{(t)} - \eta \frac{\partial C}{\partial y_i} + \alpha (y_i^{(t)} - y_i^{(t-1)}), \quad \forall i$$

How to find σ_i ?

SNE Algorithm

1. Choose $\Phi^{(0)}$ embedding, i.e choose $\{y_i^{(0)}\}$
2. Compute \mathcal{P}_i and \mathcal{Q}_i distributions.
3. Minimize $C(\mathcal{Y})$ through Gradient Descent with momentum

$$y_i^{(t+1)} = y_i^{(t)} - \eta \frac{\partial C}{\partial y_i} + \alpha (y_i^{(t)} - y_i^{(t-1)}), \quad \forall i$$

How to find σ_i ?

Shannon Entropy





Shannon Entropy, Perplexity

Let $\mathcal{P} = \{p_1, \dots, p_n\}$ and $\mathcal{Q} = \{q_1, \dots, q_n\}$ distributions

$$\text{Shannon Entropy} \quad \mathbb{H}(\mathcal{P}) = - \sum_i p_i \log_2(p_i)$$

$$\text{Perplexity} \quad \text{Perp}(\mathcal{P}) = 2^{\mathbb{H}(\mathcal{P})}$$

How σ_i and Perplexity are related?



Perplexity measures the number of samples in a neighborhood.