

The engsymbols package*

Fábio Fortkamp
fabio@fabiofortkamp.com

December 5, 2014

1 Introduction

This document describes the `engsymbols` package, a collection of macros to facilitate the writing of common engineering symbols.

The following packages are prerequisites:

- `bm`
- `amsmath`
- `esdiff`

This package follows the conventions specified by ISO standards of typesetting mathematics [1]. The main points of this convention are:

- variables are always written in italic, *and also* in bold for vector and matrices
- in other words, vectors don't have arrows above it
- subscripts and superscripts are written in roman upright font when they do not indicate a variable per se; e.g. when they refer to a physical object, a fluid phase, a state etc

`engsymbols` is actually just a collection of commands I, as a Ph.D. student in Mechanical Engineering, find useful, and I hope others can find it to. There aren't any special design principles, except that:

- Command names are not short, but are descriptive. The user can always define an alias, and many editors can parse the packages and offer tab completion.
- These macros are not intended to be the absolute true way of scientific writing. As I said, I try to follow some standards and observe what is commonly used.

Please notice that the user should refer to other references such as papers and textbooks to get the meaning of the symbols I describe here.

*This document corresponds to `engsymbols` v0.1, dated 2014/12/05.

2 Available commands

2.1 Special symbols

First we have some basic symbols, commands that take no arguments.

`\volume` This `\volume` macro typesets a special symbol \mathcal{V} to indicate the total volume of something. The more logical V is avoided, mainly in fluid mechanics texts, because it's used for velocity. I chose the calligraphic \mathcal{V} because the often used \forall is really ugly and is intended to use with logical propositions ("for all $x \dots$ ").

`\hheat` The symbols \hbar (`\hheat`) and \hbar_m (`\hmass`) are used in some textbooks to indicate the convection heat (or mass) transfer coefficient and to avoid confusion with enthalpy h . I'm aware that \hbar is also used for the reduced Planck constant, but I don't think it's used in engineering literature. I also know that the distinction between an enthalpy value and a heat transfer coefficient value can be inferred by the context, but in a equation with many terms, including terms with enthalpy and heat transfer rates, this can make things clearer. Also notice the m subscript in roman fonts; it's a coefficient for mass transfer, and not a coefficient for a variable m .

`\diffusivitybinary` I deal with mixtures a lot, so there is `\diffusivitybinary` \mathcal{D}_{12} , which is used to indicate the mass diffusivity of a binary mixture.

`\universalgasconstant` Finally, there is a command `\universalgasconstant` to write R_u , the universal gas constant. The u index (also in roman font) marks this as a constant; each fluid has its own "gas constant", defined as $R = \frac{R_u}{M}$, where M is the molar mass; hence for a mixture, this gas constant varies with the composition, and of course different fluids have different R . R_u is universal for all fluids.

References

- [1] Claudio Beccari. Typesetting mathematics for science and technology according to iso 31/xi. *TUGboat*, 18(1):39–48, 1997.