

There is a collection of input strings and a collection of query strings. For each query string, determine how many times it occurs in the list of input strings. Return an array of the results.

Example

strings = ['ab', 'ab', 'abc']

queries = ['ab', 'abc', 'bc']

There are **2** instances of 'ab', **1** of 'abc' and **0** of 'bc'. For each query, add an element to the return array, *results* = [2, 1, 0].

Function Description

Complete the function `matchingStrings` in the editor below. The function must return an array of integers representing the frequency of occurrence of each query string in *strings*.

`matchingStrings` has the following parameters:

- string *strings*[n] - an array of strings to search
- string *queries*[q] - an array of query strings

Returns

- int[q]: an array of results for each query

Input Format

The first line contains an integer n , the size of $strings[]$.

Each of the next n lines contains a string $strings[i]$.

The next line contains q , the size of $queries[]$.

Each of the next q lines contains a string $queries[i]$.

Constraints

$$1 \leq n \leq 1000$$

$$1 \leq q \leq 1000$$

$$1 \leq |strings[i]|, |queries[i]| \leq 20.$$

Sample Input 1

[Copy](#) [Download](#)

```
4
aba
baba
aba
xzxb
3
aba
xzxb
ab
```

Sample Output 1

```
2
1
0
```

Sample Input 2

[Copy](#) [Download](#)

```
3
def
de
fgh
3
de
lmn
fgh
```

Sample Output 2

```
1
0
1
```

Sample Input 3

[Copy](#) [Download](#)

```
13
abcde
sdaklfj
asdjf
na
basdn
sdaklfj
asdjf
na
asdjf
na
basdn
sdaklfj
asdjf
5
abcde
sdaklfj
asdjf
na
basdn
```

Sample Output 3

1

3

4

3

2