fmocdmac — FM's OCD LaTeX Macro*

Fabio Mogavero
fm@fabiomogavero.com

Released 2023/02/14

Abstract

This package contains almost all the latex macros I heavily use in my tcs research activity and, in particular, in the writing of conference and journal articles. As few of my co-authors have kindly pointed out, and probably many have thought, they are somehow a clear expression of an underlying ocd-like behavior... hence the name!

1 Implementation & Usage

1 ⟨*package⟩

Required external packages:

```
2
3 \RequirePackage{etoolbox}
4
5 \RequirePackage{xargs}
6 \RequirePackage{xspace}
7 \RequirePackage{stringstrings}
8
```

Package options:

```
9
10 %% Auxiliary packages
11 \newif\ifaux@ \aux@false
12 \DeclareOption{aux}{\aux@true}
13 \DeclareOption{noaux}{\aux@false}
14
15 %% AMS defaults
16 \newif\ifamsdef@ \amsdef@true
17 \DeclareOption{noamsdef}{\amsdef@false}
18
19 %% AMS theorem tools
20 \newif\ifamsthm@ \amsthm@true
21 \DeclareOption{noamsthm}{\amsthm@false}
22
23 %% Extended Theorem tools
24 \newif\ifthmtls@ \thmtls@true
25 \DeclareOption{nothmtls}{\thmtls@false}
26
27 %% Enumeration tools
28 \newif\ifenmtls@ \enmtls@true
29 \DeclareOption{noenmtls}{\enmtls@false}
30
31 %% Hyper reference
32 \newif\ifhypref@ \hypref@true
33 \DeclareOption{nohypref}{\hypref@false}
34
```

*This document describes version v0.15 of the fmocdmac package, last revised 2023/02/14.

```
%% Font tools
\newif\iffnttls@ \fnttls@true
\DeclareOption{nofnttls}{\fnttls@false}

%% Camera-ready version
\newif\ifcrv@ \crv@false
\DeclareOption{crv}{\crv@true}

%% Change bars
\newif\ifchgbar@ \chgbar@false
\DeclareOption{chgbar}{\chgbar@true}

%% Line numbers
\newif\iflinnum@ \linnum@false
\DeclareOption{linnum}{\linnum@true}


%% Text macro generation
\newif\iftxtgen@ \txtgen@false
\DeclareOption{txtgen}{\txtgen@true}
\DeclareOption{notxtgen}
  {\txtgen@false\text@false\com@false\gam@false\log@false\aut@false}

%% Math macro generation
\newif\ifmthgen@ \mthgen@false
\DeclareOption{mthgen}{\mthgen@true}
\DeclareOption{nomthgen}
  {\mthgen@false\math@false\gam@false\log@false\aut@false}


%% Elementary macros for text
\newif\iftext@ \text@false
\DeclareOption{text}{\text@true\txtgen@true}
\DeclareOption{notext}{\text@false}

%% Elementary macros for math
\newif\ifmath@ \math@false
\DeclareOption{math}{\math@true\mthgen@true}
\DeclareOption{nomath}{\math@false}


%% Macros for computational-complexity classes
\newif\ifcom@ \com@false
\DeclareOption{com}{\com@true\txtgen@true}
\DeclareOption{nocom}{\com@false}


%% Macros for games
\newif\ifgam@ \gam@false
\DeclareOption{gam}{\gam@true\txtgen@true\mthgen@true}
\DeclareOption{nogam}{\gam@false}

%% Macros for logics
\newif\iflog@ \log@false
\DeclareOption{log}{\log@true\txtgen@true\mthgen@true}
\DeclareOption{nolog}{\log@false}

%% Macros for automata
\newif\ifaut@ \aut@false
\DeclareOption{aut}{\aut@true\txtgen@true\mthgen@true}
\DeclareOption{noaut}{\aut@false}


```

```
%% Format-related tricks
\newif\iffrm@ \frm@false
\DeclareOption{frm}{\frm@true}
\DeclareOption{nofrm}{\frm@false}


%% Figure-related tricks
\newif\iffig@ \fig@false
\DeclareOption{fig}{\fig@true}
\DeclareOption{nofig}{\fig@false}

%% Wrapfig package
\newif\ifwrpfig@ \wrpfig@true
\DeclareOption{nowrpfig}{\wrpfig@false}


%% Table-related tricks
\newif\iftab@ \tab@false
\DeclareOption{tab}{\tab@true}
\DeclareOption{notab}{\tab@false}


%% Algorithm-related tricks
\newif\ifalg@ \alg@false
\DeclareOption{alg}{\alg@true}
\DeclareOption{noalg}{\alg@false}

```

Option-processing code:

```

\DeclareOption*{\PackageWarning{fmocdmac}{Unknown~`\CurrentOption'}}%

\ExecuteOptions{aux,txtgen,mthgen,text,math,com,gam,log,aut}%

\ProcessOptions\relax%

\ifcsdef{if@twocolumn}{}{\newif\if@twocolumn}

```

Package main body:

```

%%*****************************************************************************%%
%%** Auxiliary Alphabet Letters ************************************************%%
%%*****************************************************************************%%
```

`\omicron` **Auxiliary Greek lowercase letter:** ... to do!

```
\csdef{omicron}{o}
```

`\Alpha, ...` **Auxiliary Greek uppercase letters:** ... to do!

```
\csdef{Alpha}{A} \csdef{Beta}{B} \csdef{Epsilon}{E} \csdef{varEpsilon}{E}
\csdef{Zeta}{Z} \csdef{Eta}{H} \csdef{Iota}{I} \csdef{Kappa}{K}
\csdef{varKappa}{K} \csdef{Mu}{M} \csdef{Nu}{N} \csdef{Omicron}{O}
\csdef{Rho}{P} \csdef{varRho}{P} \csdef{Tau}{T} \csdef{Chi}{X}

%%*****************************************************************************%%
%%*****************************************************************************%%
%%** Tools *********************************************************************%%
%%*****************************************************************************%%
```

`\empchk` **Emptiness check:** `\empchk{`$\langle A\rangle$`}{`$\langle B\rangle$`}` evaluates to the empty string, if Argument $\langle A\rangle$ is empty, and to Argument $\langle B\rangle$, otherwise.

- `\empchk{}{B}` = “”
- `\empchk{A}{B}` = “B”

```
\newcommand{\empchk}[2]
  {\if&#1&\else#2\fi}
```

\defval **Default value:** `\defval{`⟨*A*⟩`}{`⟨*B*⟩`}` evaluates to Argument ⟨*B*⟩, if Argument ⟨*A*⟩ is empty, and to Argument ⟨*A*⟩ itself, otherwise.

- `\defval{}{B}` = "B"
- `\defval{A}{B}` = "A"

```
\newcommand{\defval}[2]
  {\if&#1&#2\else#1\fi}
```

```
%%*****************************************************************************%%
```

\arglef **Left extension:** `\arglef{`⟨*A*⟩`}{`⟨*B*⟩`}` evaluates to the concatenation ⟨*AB*⟩ of the two arguments, if Argument ⟨*B*⟩ is non-empty, and to the empty string, otherwise.

- `\arglef{A}{}` = ""
- `\arglef{A}{B}` = "AB"

```
\newcommand{\arglef}[2]
  {\empchk{#2}{#1#2}}
```

\argrig **Right extension:** `\argrig{`⟨*A*⟩`}{`⟨*B*⟩`}` evaluates to the concatenation ⟨*AB*⟩ of the two arguments, if Argument ⟨*A*⟩ is non-empty, and to the empty string, otherwise.

- `\argrig{}{B}` = ""
- `\argrig{A}{B}` = "AB"

```
\newcommand{\argrig}[2]
  {\empchk{#1}{#1#2}}
```

\argmid **Middle extension:** `\argmid{`⟨*A*⟩`}{`⟨*B*⟩`}{`⟨*C*⟩`}` evaluates to the concatenation ⟨*ABC*⟩ of the three arguments, if Argument ⟨*B*⟩ is non-empty, and to the empty string, otherwise.

- `\argmid{A}{}{C}` = ""
- `\argmid{A}{B}{C}` = "ABC"

```
\newcommand{\argmid}[3]
  {\empchk{#2}{#1#2#3}}
```

\argsep **Separators:** `\argsep{`⟨*A*⟩`}{`⟨*B*⟩`}{`⟨*C*⟩`}` evaluates to Argument ⟨*C*⟩, if Argument ⟨*A*⟩ is empty, to Argument ⟨*A*⟩, if Argument ⟨*C*⟩ is empty, and to the concatenation ⟨*ABC*⟩, otherwise.

- `\argsep{}{B}{C}` = "C"
- `\argsep{A}{B}{}` = "A"
- `\argsep{A}{}{C}` = "AC"
- `\argsep{A}{B}{C}` = "ABC"

```
\newcommand{\argsep}[3]
  {\if&#1&#3\else#1\arglef{#2}{#3}\fi}
```

```
%%*****************************************************************************%%
```

\varcmd **Variadic commands:** `\varcmd{`⟨*A*⟩`}{`⟨*B*⟩`}{`⟨*C*⟩`}{`⟨*D*⟩`}{`⟨*E*⟩`}{`⟨*F*⟩`}` ... to do!

```
\newcommand{\varcmd}[6]
  {\expandafter\newcommand\csname gobble#1arg\endcsname[2]
    {\csname check#1arg\endcsname{\argsep{##1}{#4}{\empchk{##2}{{##2}}}}}%
  \expandafter\newcommand\csname check#1arg\endcsname[1]
    {\csname @ifnextchar\endcsname%
      \bgroup{\csname gobble#1arg\endcsname{##1}}{#2{##1#5}#6}}%
  \expandafter\newcommand\csname#1\endcsname[1]
    {\csname check#1arg\endcsname{#3##1}}}
```

```
%%*****************************************************************************%%
```

\seqoftag **Sequence of tags:** \seqoftag{⟨A⟩}{⟨B⟩}{⟨C⟩} ... to do!

```
\newcommand{\seqoftag}[3]
  {\@for\itr:={#1}\do%
    {\expandafter\csedef{\itr#2}%
      {\noexpand\csname #3\endcsname{\itr}}}}
```

\seqofcmd **Sequence of commands:** \seqofcmd{⟨A⟩}{⟨B⟩}{⟨C⟩} ... to do!

```
\newcommand{\seqofcmd}[3]
  {\@for\itr:={#1}\do%
    {\expandafter\csedef{\itr#2}%
      {\noexpand\csname #3\endcsname{\csname \itr\endcsname}}}}
```

```
%%*************************************************************************%%
```

\seqoflatlow **Sequence of Latin lowercase letters:** \seqoflatlow{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqoflatlow}
  {\seqoftag{a,b,c,d,e,f,g,h,i,j,k,l,m,n,o,p,q,r,s,t,u,v,w,x,y,z}}
```

\seqoflatupp **Sequence of Latin uppercase letters:** \seqoflatupp{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqoflatupp}
  {\seqoftag{A,B,C,D,E,F,G,H,I,J,K,L,M,N,O,P,Q,R,S,T,U,V,W,X,Y,Z}}
```

\seqoflatlet **Sequence of Latin letters:** \seqoflatlet{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqoflatlet}[2]
  {\seqoflatlow{#1}{#2}\seqoflatupp{#1}{#2}}
```

```
%%*************************************************************************%%
```

\seqofgrklow **Sequence of Greek lowercase letters:** \seqofgrklow{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqofgrklow}
  {\seqofcmd{alpha,beta,gamma,delta,epsilon,varepsilon,zeta,eta,theta,vartheta,%
  iota,kappa,varkappa,lambda,mu,nu,xi,omicron,pi,varpi,rho,varrho,sigma,%
  varsigma,tau,upsilon,phi,varphi,chi,psi,omega}}
```

\seqofgrkupp **Sequence of Greek uppercase letters:** \seqofgrkupp{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqofgrkupp}
  {\seqofcmd{Alpha,Beta,Gamma,Delta,Epsilon,varEpsilon,Zeta,Eta,Theta,varTheta,%
  Iota,Kappa,varKappa,Lambda,Mu,Nu,Xi,Omicron,Pi,varPi,Rho,varRho,Sigma,%
  varSigma,Tau,Upsilon,Phi,varPhi,Chi,Psi,Omega}}
```

\seqofgrklet **Sequence of Greek letters:** \seqofgrklet{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqofgrklet}[2]
  {\seqofgrklow{#1}{#2}\seqofgrkupp{#1}{#2}}
```

```
%%*************************************************************************%%
```

\seqoflow **Sequence of lowercase letters:** \seqoflow{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqoflow}[2]
  {\seqoflatlow{#1}{#2}\seqofgrklow{#1}{#2}}
```

\seqofupp **Sequence of uppercase letters:** \seqofupp{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqofupp}[2]
  {\seqoflatupp{#1}{#2}\seqofgrkupp{#1}{#2}}
```

\seqoflet **Sequence of all letters:** \seqoflet{⟨A⟩}{⟨B⟩} ... to do!

```
\newcommand{\seqoflet}[2]
  {\seqoflow{#1}{#2}\seqofupp{#1}{#2}}
```

```
%%*************************************************************************%%
```

```
%%*************************************************************************%%
%%** Auxiliary Packages ****************************************************%%
%%*************************************************************************%%
\ifaux@

\ifamsdef@
  % AMS Packages
  \RequirePackage{amsmath}
  \RequirePackage{amssymb}
  \RequirePackage{stmaryrd}
  \interdisplaylinepenalty=2500
\fi

\ifamsthm@
  % AMS Theorem Tools
  \RequirePackage{amsthm}
\fi

\ifthmtls@
  % Extended Theorem Tools
  \RequirePackage{thmtools, thm-restate}
\fi

\ifenmtls@
  % Enumeration Tools
  \RequirePackage{paralist}
\fi

\ifhypref@
  % Hyper References
  \RequirePackage{hyperref}
  \hypersetup {
    pdfsubject    = {},
    pdfkeywords   = {},
    pdfproducer   = {},
    pdfcreator    = {},
    pdfpagemode   = {UseNone},
    pdfstartview  = {FitH},
    urlcolor      = {blue},
    colorlinks
  }
\fi

\iffnttls@
  % Font Tools
  \RequirePackage[final]{microtype}
\fi

\ifcrv@
  % Camera-Ready Version

  %%...

\else
  % Draft Version

  %%...

  \ifchgbar@
    % Change Bars
    \RequirePackage{changebar}
  \fi

```

```
  \iflinnum@
    % Line Numbers
    \if@twocolumn
      \RequirePackage[switch, columnwise, mathlines]{lineno}\linenumbers
    \else
      \RequirePackage[columnwise, mathlines]{lineno}\linenumbers
    \fi
  \fi

  %%...

\fi

\fi
%%*****************************************************************************%%
%%*****************************************************************************%%
%%** Auxiliary Font Declarations ***********************************************%%
%%*****************************************************************************%%
```

\mathbbo **Bbo Math Font:** ... to do!

```
\ifdef{\mathbbo}{}{\DeclareMathAlphabet{\mathbbo}{U}{bbold}{m}{n}}
```

\matheus **Eus Math Font:** ... to do!

```
\ifdef{\matheus}{}{\DeclareMathAlphabet{\matheus}{U}{eus}{m}{n}}
```

\mathpzc **Pzc Math Font:** ... to do!

```
\ifdef{\mathpzc}{}{\DeclareMathAlphabet{\mathpzc}{T1}{pzc}{m}{it}}
```

\mathscr **Scr Math Font:** ... to do!

```
\ifdef{\mathscr}{}{\DeclareMathAlphabet{\mathscr}{U}{rsfs}{m}{n}}
```

```
%%*****************************************************************************%%
%%*****************************************************************************%%
%%** Text Meta Commands ********************************************************%%
%%*****************************************************************************%%
```

\newtxt ... to do!

- `\newtxt[\rmfamily]{Name}[sub][sup][Ext]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}\mathrm{Ext}$"
- `\newtxt[\sffamily]{Name}[sub][sup][Ext]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}\mathsf{Ext}$"
- `\newtxt[\ttfamily]{Name}[sub][sup][Ext]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}\mathtt{Ext}$"

```
\newcommandx{\newtxt}[5][1=, 3=, 4=, 5=]
  {\text{#1#2\txtsubsup[#1]{#3}{#4}#5}\xspace}
```

\newtxtsty ... to do!

- `\newtxtsty{\rmfamily}{Name}[sub][sup][Ext]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}\mathrm{Ext}$"
- `\newtxtsty{\rmfamily}[\sffamily]{Name}[sub][sup][Ext]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}\mathsf{Ext}$"
- `\newtxtsty{\rmfamily}[\ttfamily]{Name}[sub][sup][Ext]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}\mathtt{Ext}$"

```
\newcommandx{\newtxtsty}[2][2=]
  {\newtxt[\defval{#2}{#1}]}
```

\newtxtarg ... to do!

- `\newtxtarg[\rmfamily]{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}\mathrm{Ext1(Arg)Ext2}$"
- `\newtxtarg[\sffamily]{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}\mathsf{Ext1(Arg)Ext2}$"
- `\newtxtarg[\ttfamily]{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}\mathtt{Ext1(Arg)Ext2}$"

```
\newcommandx{\newtxtarg}[7][1=, 3=, 4=, 5=, 7=]
  {\newtxt[#1]{#2}[#3][#4][\argmid{#5(){#6}{)#7}]}
```

\newtxtargsty ... to do!

- `\newtxtargsty{\rmfamily}{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}\mathrm{Ext1(Arg)Ext2}$"

- `\newtxtargsty{\rmfamily}[\sffamily]{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}$Ext1(Arg)Ext2"
- `\newtxtargsty{\rmfamily}[\ttfamily]{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}$Ext1(Arg)Ext2"

```
\newcommandx{\newtxtargsty}[2][2=]
  {\newtxtarg[\defval{#2}{#1}]}
```

`\newtxtoarg` ... to do!

- `\newtxtoarg[\rmfamily]{Name}[sub][sup][Arg]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}$(Arg)"
- `\newtxtoarg[\sffamily]{Name}[sub][sup][Arg]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}$(Arg)"
- `\newtxtoarg[\ttfamily]{Name}[sub][sup][Arg]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}$(Arg)"

```
\newcommandx{\newtxtoarg}[5][1=, 3=, 4=, 5=]
  {\newtxtarg[#1]{#2}[#3][#4][]{#5}[]}
```

`\newtxtoargsty` ... to do!

- `\newtxtoargsty{\rmfamily}{Name}[sub][sup][Arg]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}$(Arg)"
- `\newtxtoargsty{\rmfamily}[\sffamily]{Name}[sub][sup][Arg]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}$(Arg)"
- `\newtxtoargsty{\rmfamily}[\ttfamily]{Name}[sub][sup][Arg]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}$(Arg)"

```
\newcommandx{\newtxtoargsty}[2][2=]
  {\newtxtoarg[\defval{#2}{#1}]}
```

`\newtxtpar` ... to do!

- `\newtxtpar[\rmfamily]{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}$Ext1[Par]Ext2"
- `\newtxtpar[\sffamily]{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}$Ext1[Par]Ext2"
- `\newtxtpar[\ttfamily]{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}$Ext1[Par]Ext2"

```
\newcommandx{\newtxtpar}[7][1=, 3=, 4=, 5=, 7=]
  {\newtxt[#1]{#2}[#3][#4][\argmid{#5[}{#6}{]#7}]}
```

`\newtxtparsty` ... to do!

- `\newtxtparsty{\rmfamily}{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}$Ext1[Par]Ext2"
- `\newtxtparsty{\rmfamily}[\sffamily]{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}$Ext1[Par]Ext2"
- `\newtxtparsty{\rmfamily}[\ttfamily]{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}$Ext1[Par]Ext2"

```
\newcommandx{\newtxtparsty}[2][2=]
  {\newtxtpar[\defval{#2}{#1}]}
```

`\newtxtopar` ... to do!

- `\newtxtopar[\rmfamily]{Name}[sub][sup][Par]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}$[Par]"
- `\newtxtopar[\sffamily]{Name}[sub][sup][Par]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}$[Par]"
- `\newtxtopar[\ttfamily]{Name}[sub][sup][Par]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}$[Par]"

```
\newcommandx{\newtxtopar}[5][1=, 3=, 4=, 5=]
  {\newtxtpar[#1]{#2}[#3][#4][]{#5}[]}
```

`\newtxtoparsty` ... to do!

- `\newtxtoparsty{\rmfamily}{Name}[sub][sup][Par]` = "$\mathrm{Name}_{\mathrm{sub}}^{\mathrm{sup}}$[Par]"
- `\newtxtoparsty{\rmfamily}[\sffamily]{Name}[sub][sup][Par]` = "$\mathsf{Name}_{\mathsf{sub}}^{\mathsf{sup}}$[Par]"
- `\newtxtoparsty{\rmfamily}[\ttfamily]{Name}[sub][sup][Par]` = "$\mathtt{Name}_{\mathtt{sub}}^{\mathtt{sup}}$[Par]"

```
\newcommandx{\newtxtoparsty}[2][2=]
  {\newtxtopar[\defval{#2}{#1}]}
```

`\txtsubsup` ... to do!

- `\txtsubsup{sub}{}` = "$_{\mathrm{sub}}$"; `\txtsubsup{}{sup}` = "$^{\mathrm{sup}}$"; `\txtsubsup{sub}{sup}` = "$_{\mathrm{sub}}^{\mathrm{sup}}$"
- `\txtsubsup[\sffamily]{Aa}{Bb}` = "$^{\mathsf{Bb}}_{\mathsf{Aa}}$"
- `\txtsubsup[\ttfamily]{Aa}{Bb}` = "$^{\mathtt{Bb}}_{\mathtt{Aa}}$"

```
\newcommand{\txtsubsup}[3][]
  {\ensuremath{\empchk{#2}{_{\text{#1#2}}}\empchk{#3}{^{\text{#1#3}}}}}
```

```
%%*************************************************************************%%
```

`\txt` ... to do!

- `\txt{Name}[sub][sup][Ext]` = "$\text{Name}_{\text{sub}}^{\text{sup}}\text{Ext}$"
- `\txt[\scshape]{Name}[sub][sup][Ext]` = "$\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{Ext}$"
- `\txt[\bfseries]{Name}[sub][sup][Ext]` = "$\mathbf{Name}_{\mathbf{sub}}^{\mathbf{sup}}\mathbf{Ext}$"

```
\newcommand{\txt}
  {\newtxtsty{\txtsty}}
```

`\txtarg` ... to do!

- `\txtarg{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\text{Name}_{\text{sub}}^{\text{sup}}\text{Ext1(Arg)Ext2}$"
- `\txtarg[\scshape]{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{Ext1(Arg)Ext2}$"
- `\txtarg[\bfseries]{Name}[sub][sup][Ext1]{Arg}[Ext2]` = "$\mathbf{Name}_{\mathbf{sub}}^{\mathbf{sup}}\mathbf{Ext1(Arg)Ext2}$"

```
\newcommand{\txtarg}
  {\newtxtargsty{\txtsty}}
```

`\txtoarg` ... to do!

- `\txtoarg{Name}[sub][sup][Arg]` = "$\text{Name}_{\text{sub}}^{\text{sup}}\text{(Arg)}$"
- `\txtoarg[\scshape]{Name}[sub][sup][Arg]` = "$\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{(Arg)}$"
- `\txtoarg[\bfseries]{Name}[sub][sup][Arg]` = "$\mathbf{Name}_{\mathbf{sub}}^{\mathbf{sup}}\mathbf{(Arg)}$"

```
\newcommand{\txtoarg}
  {\newtxtoargsty{\txtsty}}
```

`\txtpar` ... to do!

- `\txtpar{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\text{Name}_{\text{sub}}^{\text{sup}}\text{Ext1[Par]Ext2}$"
- `\txtpar[\scshape]{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{Ext1[Par]Ext2}$"
- `\txtpar[\bfseries]{Name}[sub][sup][Ext1]{Par}[Ext2]` = "$\mathbf{Name}_{\mathbf{sub}}^{\mathbf{sup}}\mathbf{Ext1[Par]Ext2}$"

```
\newcommand{\txtpar}
  {\newtxtparsty{\txtsty}}
```

`\txtopar` ... to do!

- `\txtopar{Name}[sub][sup][Par]` = "$\text{Name}_{\text{sub}}^{\text{sup}}\text{[Par]}$"
- `\txtopar[\scshape]{Name}[sub][sup][Par]` = "$\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{[Par]}$"
- `\txtopar[\bfseries]{Name}[sub][sup][Par]` = "$\mathbf{Name}_{\mathbf{sub}}^{\mathbf{sup}}\mathbf{[Par]}$"

```
\newcommand{\txtopar}
  {\newtxtoparsty{\txtsty}}
```

`\txtsty` ... to do!

```
\newcommand{\txtsty}
  {\mdseries\upshape\rmfamily}
```

```
%%*************************************************************************%%
```

`\cmdtxt` ... to do!

- `\cmdtxt{NewCmd}`; `\newcommand{txtstyNewCmd}{\scshape\ttfamily}`; `\txtNewCmd{Name}[sub][sup][Ext]` = $\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{Ext}$

```
\newcommand{\cmdtxt}[1]
  {\csdef{txt#1}{\newtxtsty{\csname txtsty#1\endcsname}}}
```

`\cmdtxtarg` ... to do!

- `\cmdtxtarg{NewCmd}`; `\newcommand{txtstyNewCmd}{\scshape\ttfamily}`; `\txtargNewCmd{Name}[sub][sup][Ext1]{Arg}[Ext2]` = $\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{Ext1(Arg)Ext2}$

```
\newcommand{\cmdtxtarg}[1]
  {\csdef{txtarg#1}{\newtxtargsty{\csname txtsty#1\endcsname}}}
```

`\cmdtxtoarg` ... to do!

- `\cmdtxtoarg{NewCmd}`; `\newcommand{txtstyNewCmd}{\scshape\ttfamily}`; `\txtoargNewCmd{Name}[sub][sup][Arg]` = $\textsc{Name}_{\textsc{sub}}^{\textsc{sup}}\textsc{(Arg)}$

```
\newcommand{\cmdtxtoarg}[1]
  {\csdef{txtoarg#1}{\newtxtoargsty{\csname txtsty#1\endcsname}}}
```

`\cmdtxtpar` ... to do!

- `\cmdtxtpar{NewCmd}`; `\newcommand{txtstyNewCmd}{\scshape\ttfamily}`;
  `\txtparNewCmd{Name}[sub][sup][Ext1]{Par}[Ext2]` = NAME$^{\text{SUP}}_{\text{SUB}}$EXT1[PAR]EXT2

```
\newcommand{\cmdtxtpar}[1]
  {\csdef{txtpar#1}{\newtxtparsty{\csname txtsty#1\endcsname}}}
```

`\cmdtxtopar` ... to do!

- `\cmdtxtopar{NewCmd}`; `\newcommand{txtstyNewCmd}{\scshape\ttfamily}`;
  `\txtoparNewCmd{Name}[sub][sup][Par]` = NAME$^{\text{SUP}}_{\text{SUB}}$[PAR]

```
\newcommand{\cmdtxtopar}[1]
  {\csdef{txtopar#1}{\newtxtoparsty{\csname txtsty#1\endcsname}}}
```

`\cmdtxtall` ... to do!

- `\cmdtxtall{NewCmd}`; `\newcommand{txtstyNewCmd}{\scshape\ttfamily}`;
  `\txtNewCmd{Name}[sub][sup][Ext]` = NAME$^{\text{SUP}}_{\text{SUB}}$EXT
  `\txtargNewCmd{Name}[sub][sup][Ext1]{Arg}[Ext2]` = NAME$^{\text{SUP}}_{\text{SUB}}$EXT1(ARG)EXT2
  `\txtoargNewCmd{Name}[sub][sup][Arg]` = NAME$^{\text{SUP}}_{\text{SUB}}$(ARG)
  `\txtparNewCmd{Name}[sub][sup][Ext1]{Par}[Ext2]` = NAME$^{\text{SUP}}_{\text{SUB}}$EXT1[PAR]EXT2
  `\txtoparNewCmd{Name}[sub][sup][Par]` = NAME$^{\text{SUP}}_{\text{SUB}}$[PAR]

```
\newcommand{\cmdtxtall}[1]
  {\cmdtxt{#1}\cmdtxtarg{#1}\cmdtxtoarg{#1}\cmdtxtpar{#1}\cmdtxtopar{#1}}

%%*****************************************************************************%%
```

`\usrtxt` ... to do!

- `\usrtxt{cmdName}{Suf}{}`; `\cmdNameSuf` = cmdName
  `\usrtxt{cmdName}{Suf}{arg}`; `\cmdNameSuf{Arg}` = cmdName(Arg)
  `\usrtxt{cmdName}{Suf}{par}`; `\cmdNameSuf{Par}` = cmdName[Par]
- `\usrtxt{cmdName}{Suf}{}[newName]`; `\cmdNameSuf` = newName
  `\usrtxt{cmdName}{Suf}{arg}[newName]`; `\cmdNameSuf{Arg}` = newName(Arg)
  `\usrtxt{cmdName}{Suf}{par}[newName]`; `\cmdNameSuf{Par}` = newName[Par]

```
\newcommandx{\usrtxt}[4][4=]
  {\csdef{#1#2}{\csname txt#3\endcsname{\defval{#4}{#1}}}}

%%*****************************************************************************%%

%%*****************************************************************************%%
%%** Math Meta Commands *******************************************************%%
%%*****************************************************************************%%
```

`\newmth` ... to do!

- `\newmth[mathrm]{Name}[sub][sup][Ext]` = "$\text{Name}^{sup}_{sub}Ext$"
- `\newmth[mathsf]{Name}[sub][sup][Ext]` = "$\mathsf{Name}^{sup}_{sub}Ext$"
- `\newmth[mathtt]{Name}[sub][sup][Ext]` = "$\mathtt{Name}^{sup}_{sub}Ext$"

```
\newcommandx{\newmth}[5][1=, 3=, 4=, 5=]
  {\ensuremath{\csname#1\endcsname{#2}\mthsubsup{#3}{#4}#5}}
```

`\newmthsty` ... to do!

- `\newmthsty{mathrm}{Name}[sub][sup][Ext]` = "$\text{Name}^{sup}_{sub}Ext$"
- `\newmthsty{mathrm}[mathsf]{Name}[sub][sup][Ext]` = "$\mathsf{Name}^{sup}_{sub}Ext$"
- `\newmthsty{mathrm}[mathtt]{Name}[sub][sup][Ext]` = "$\mathtt{Name}^{sup}_{sub}Ext$"

```
\newcommandx{\newmthsty}[2][2=]
  {\newmth[\defval{#2}{#1}]}
```

`\newmtharg` ... to do!

- `\newmtharg[mathrm]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\text{Name}^{sup}_{sub}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$"

- `\newmtharg[mathsf]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\newmtharg[mathtt]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\newmtharg*[mathrm]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathrm{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"
- `\newmtharg*[mathsf]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"
- `\newmtharg*[mathtt]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"

```
\newcommand{\newmtharg}
  {\@ifstar{\@snewmtharg}{\@newmtharg}}
\newcommandx{\@newmtharg}[7][1=, 3=, 4=, 5=, 7=]
  {\newmth[#1]{#2}[#3][#4][\argmid{#5\!\left(}{#6}{\right)\arglef{\!}{#7}}]}
\newcommandx{\@snewmtharg}[7][1=, 3=, 4=, 5=, 7=]
  {\newmth[#1]{#2}[#3][#4][\argmid{#5(}{#6}{)#7}]}
```

`\newmthargsty` ... to do!

- `\newmthargsty{mathrm}{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathrm{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\newmthargsty{mathrm}[mathsf]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\newmthargsty{mathrm}[mathtt]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\newmthargsty*{mathrm}{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathrm{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"
- `\newmthargsty*{mathrm}[mathsf]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"
- `\newmthargsty*{mathrm}[mathtt]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"

```
\newcommand{\newmthargsty}
  {\@ifstar{\@snewmthargsty}{\@newmthargsty}}
\newcommandx{\@newmthargsty}[2][2=]
  {\newmtharg[\defval{#2}{#1}]}
\newcommandx{\@snewmthargsty}[2][2=]
  {\newmtharg*[\defval{#2}{#1}]}
```

`\newmthoarg` ... to do!

- `\newmthoarg[mathrm]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\newmthoarg[mathsf]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\newmthoarg[mathtt]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\newmthoarg*[mathrm]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"
- `\newmthoarg*[mathsf]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"
- `\newmthoarg*[mathtt]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"

```
\newcommand{\newmthoarg}
  {\@ifstar{\@snewmthoarg}{\@newmthoarg}}
\newcommandx{\@newmthoarg}[5][1=, 3=, 4=, 5=]
  {\newmtharg[#1]{#2}[#3][#4][]{#5}[]}
\newcommandx{\@snewmthoarg}[5][1=, 3=, 4=, 5=]
  {\newmtharg*[#1]{#2}[#3][#4][]{#5}[]}
```

`\newmthoargsty` ... to do!

- `\newmthoargsty{mathrm}{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\newmthoargsty{mathrm}[mathsf]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\newmthoargsty{mathrm}[mathtt]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\newmthoargsty*{mathrm}{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"
- `\newmthoargsty*{mathrm}[mathsf]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"
- `\newmthoargsty*{mathrm}[mathtt]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"

```
\newcommand{\newmthoargsty}
  {\@ifstar{\@snewmthoargsty}{\@newmthoargsty}}
\newcommandx{\@newmthoargsty}[2][2=]
  {\newmthoarg[\defval{#2}{#1}]}
\newcommandx{\@snewmthoargsty}[2][2=]
  {\newmthoarg*[\defval{#2}{#1}]}
```

`\newmthpar` ... to do!

- `\newmthpar[mathrm]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathrm{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\newmthpar[mathsf]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\newmthpar[mathtt]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\newmthpar*[mathrm]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathrm{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"
- `\newmthpar*[mathsf]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"
- `\newmthpar*[mathtt]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"

```
\newcommand{\newmthpar}
  {\@ifstar{\@snewmthpar}{\@newmthpar}}
\newcommandx{\@newmthpar}[7][1=, 3=, 4=, 5=, 7=]
  {\newmth[#1]{#2}[#3][#4][\argmid{#5\!\left[}{#6}{\right]\arglef{\!}{#7}}]}
\newcommandx{\@snewmthpar}[7][1=, 3=, 4=, 5=, 7=]
  {\newmth[#1]{#2}[#3][#4][\argmid{#5[}{#6}{]#7}]}
```

`\newmthparsty` ... to do!

- `\newmthparsty{mathrm}{Name}[sub][sup] [Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathrm{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\newmthparsty{mathrm}[mathsf]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\newmthparsty{mathrm}[mathtt]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\newmthparsty*{mathrm}{Name}[sub][sup] [Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathrm{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"
- `\newmthparsty*{mathrm}[mathsf]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathsf{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"
- `\newmthparsty*{mathrm}[mathtt]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"

```
\newcommand{\newmthparsty}
  {\@ifstar{\@snewmthparsty}{\@newmthparsty}}
\newcommandx{\@newmthparsty}[2][2=]
  {\newmthpar[\defval{#2}{#1}]}
\newcommandx{\@snewmthparsty}[2][2=]
  {\newmthpar*[\defval{#2}{#1}]}
```

`\newmthopar` ... to do!

- `\newmthopar[mathrm]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}\left[Par^{Ex^{Ex}}\right]$"
- `\newmthopar[mathsf]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}\left[Par^{Ex^{Ex}}\right]$"
- `\newmthopar[mathtt]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}\left[Par^{Ex^{Ex}}\right]$"
- `\newmthopar*[mathrm]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"
- `\newmthopar*[mathsf]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"
- `\newmthopar*[mathtt]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"

```
\newcommand{\newmthopar}
  {\@ifstar{\@snewmthopar}{\@newmthopar}}
\newcommandx{\@newmthopar}[5][1=, 3=, 4=, 5=]
  {\newmthpar[#1]{#2}[#3][#4][]{#5}[]}
\newcommandx{\@snewmthopar}[5][1=, 3=, 4=, 5=]
  {\newmthpar*[#1]{#2}[#3][#4][]{#5}[]}
```

`\newmthoparsty` ... to do!

- `\newmthoparsty{mathrm}{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}\Big[Par^{Ex^{Ex}}\Big]$"
- `\newmthoparsty{mathrm}[mathsf]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}\Big[Par^{Ex^{Ex}}\Big]$"
- `\newmthoparsty{mathrm}[mathtt]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}\Big[Par^{Ex^{Ex}}\Big]$"
- `\newmthoparsty*{mathrm}{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathrm{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"
- `\newmthoparsty*{mathrm}[mathsf]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathsf{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"
- `\newmthoparsty*{mathrm}[mathtt]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"

```
\newcommand{\newmthoparsty}
  {\@ifstar{\@snewmthoparsty}{\@newmthoparsty}}
\newcommandx{\@newmthoparsty}[2][2=]
  {\newmthopar[\defval{#2}{#1}]}
\newcommandx{\@snewmthoparsty}[2][2=]
  {\newmthopar*[\defval{#2}{#1}]}
```

`\mthsubsup` ... to do!

```
\newcommand{\mthsubsup}[2]
  {\empchk{#1}{_{#1}}\empchk{#2}{^{#2}}}
```

```
%%*************************************************************************%%
```

`\mth` ... to do!

- `\mth{Name}[sub][sup][Ext]` = "$Name_{sub}^{sup}Ext$"
- `\mth[mathbf]{Name}[sub][sup][Ext]` = "$\mathbf{Name}_{sub}^{sup}Ext$"
- `\mth[mathtt]{Name}[sub][sup][Ext]` = "$\mathtt{Name}_{sub}^{sup}Ext$"

```
\newcommand{\mth}
  {\newmthsty{\mthsty}}
```

`\mtharg` ... to do!

- `\mtharg{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$Name_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\mtharg[mathbf]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathbf{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\mtharg[mathtt]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$"
- `\mtharg*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$Name_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"
- `\mtharg*[mathbf]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathbf{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"
- `\mtharg*[mathtt]{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$"

```
\newcommand{\mtharg}
  {\@ifstar{\newmthargsty*{\mthsty}}{\newmthargsty{\mthsty}}}
```

`\mthoarg` ... to do!

- `\mthoarg{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$Name_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\mthoarg[mathbf]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathbf{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\mthoarg[mathtt]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$"
- `\mthoarg*{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$Name_{sub}^{sup}(Arg^{Ex^{Ex}})$"
- `\mthoarg*[mathbf]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathbf{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"
- `\mthoarg*[mathtt]{Name}[sub][sup][Arg^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$"

```
\newcommand{\mthoarg}
  {\@ifstar{\newmthoargsty*{\mthsty}}{\newmthoargsty{\mthsty}}}
```

`\mthpar` ... to do!

- `\mthpar{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$Name_{sub}^{sup}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$"

- `\mthpar[mathbf]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathbf{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\mthpar[mathtt]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$"
- `\mthpar*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$Name_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"
- `\mthpar*[mathbf]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathbf{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"
- `\mthpar*[mathtt]{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = "$\mathtt{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$"

```
\newcommand{\mthpar}
  {\@ifstar{\newmthparsty*{\mthsty}}{\newmthparsty{\mthsty}}}
```

`\mthopar` ... to do!

- `\mthopar{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$Name_{sub}^{sup}\left[Par^{Ex^{Ex}}\right]$"
- `\mthopar[mathbf]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathbf{Name}_{sub}^{sup}\left[Par^{Ex^{Ex}}\right]$"
- `\mthopar[mathtt]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}\left[Par^{Ex^{Ex}}\right]$"
- `\mthopar*{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$Name_{sub}^{sup}[Par^{Ex^{Ex}}]$"
- `\mthopar*[mathbf]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathbf{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"
- `\mthopar*[mathtt]{Name}[sub][sup][Par^{Ex^{Ex}}]` = "$\mathtt{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$"

```
\newcommand{\mthopar}
  {\@ifstar{\newmthoparsty*{\mthsty}}{\newmthoparsty{\mthsty}}}
```

`\mthsty` ... to do!

```
\newcommand{\mthsty}
  {}
```

```
%%*************************************************************************%%
```

`\cmdmth` ... to do!

- `\cmdmth{NewCmd}`; `\newcommand{mthstyNewCmd}{\mathtt}`;
  `\mthNewCmd{Name}[sub][sup][Ext]` = $\mathtt{Name}_{sub}^{sup}Ext$

```
\newcommand{\cmdmth}[1]
  {\csdef{mth#1}{\newmthsty{mthsty#1}}}
```

`\cmdmtharg` ... to do!

- `\cmdmtharg{NewCmd}`; `\newcommand{mthstyNewCmd}{\mathtt}`;
  `\mthargNewCmd{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathtt{Name}_{sub}^{sup}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
  `\mthargNewCmd*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathtt{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$

```
\newcommand{\cmdmtharg}[1]
  {\csdef{mtharg#1}%
    {\@ifstar{\newmthargsty*{mthsty#1}}{\newmthargsty{mthsty#1}}}}
```

`\cmdmthoarg` ... to do!

- `\cmdmthoarg{NewCmd}`; `\newcommand{mthstyNewCmd}{\mathtt}`;
  `\mthoargNewCmd{Name}[sub][sup][Arg^{Ex^{Ex}}]` = $\mathtt{Name}_{sub}^{sup}\left(Arg^{Ex^{Ex}}\right)$
  `\mthoargNewCmd*{Name}[sub][sup][Arg^{Ex^{Ex}}]` = $\mathtt{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$

```
\newcommand{\cmdmthoarg}[1]
  {\csdef{mthoarg#1}%
    {\@ifstar{\newmthoargsty*{mthsty#1}}{\newmthoargsty{mthsty#1}}}}
```

`\cmdmthpar` ... to do!

- `\cmdmthpar{NewCmd}`; `\newcommand{mthstyNewCmd}{\mathtt}`;
  `\mthparNewCmd{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathtt{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
  `\mthparNewCmd*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathtt{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
\newcommand{\cmdmthpar}[1]
  {\csdef{mthpar#1}%
    {\@ifstar{\newmthparsty*{mthsty#1}}{\newmthparsty{mthsty#1}}}}
```

\cmdmthopar ... to do!

- \cmdmthopar{NewCmd}; \newcommand{mthstyNewCmd}{\mathtt};
  \mthoparNewCmd{Name}[sub][sup][Par^{Ex^{Ex}}] = $\texttt{Name}_{sub}^{sup}\Big[Par^{Ex^{Ex}}\Big]$
  \mthoparNewCmd*{Name}[sub][sup][Par^{Ex^{Ex}}] = $\texttt{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$

```
\newcommand{\cmdmthopar}[1]
  {\csdef{mthopar#1}%
    {\@ifstar{\newmthoparsty*{mthsty#1}}{\newmthoparsty{mthsty#1}}}}
```

\cmdmthall ... to do!

- \cmdmthall{NewCmd}; \newcommand{mthstyNewCmd}{\mathtt};
  \mthNewCmd{Name}[sub][sup][Ext] = $\texttt{Name}_{sub}^{sup}Ext$
  \mthargNewCmd{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2] = $\texttt{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$
  \mthargNewCmd*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2] = $\texttt{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
  \mthoargNewCmd{Name}[sub][sup][Arg^{Ex^{Ex}}] = $\texttt{Name}_{sub}^{sup}\Big(Arg^{Ex^{Ex}}\Big)$
  \mthoargNewCmd*{Name}[sub][sup][Arg^{Ex^{Ex}}] = $\texttt{Name}_{sub}^{sup}(Arg^{Ex^{Ex}})$
  \mthparNewCmd{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2] = $\texttt{Name}_{sub}^{sup}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$
  \mthparNewCmd*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2] = $\texttt{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$
  \mthoparNewCmd{Name}[sub][sup][Par^{Ex^{Ex}}] = $\texttt{Name}_{sub}^{sup}\Big[Par^{Ex^{Ex}}\Big]$
  \mthoparNewCmd*{Name}[sub][sup][Par^{Ex^{Ex}}] = $\texttt{Name}_{sub}^{sup}[Par^{Ex^{Ex}}]$

```
\newcommand{\cmdmthall}[1]
  {\cmdmth{#1}\cmdmtharg{#1}\cmdmthoarg{#1}\cmdmthpar{#1}\cmdmthopar{#1}}

%%*************************************************************************%%
```

\usrmth ... to do!

- \usrmth{cmdName}{Suf}{}; \cmdNameSuf = $cmdName$
  \usrmth{cmdName}{Suf}{arg};
  \cmdNameSuf{Arg^{Ex^{Ex}}} = $cmdName\Big(Arg^{Ex^{Ex}}\Big)$
  \cmdNameSuf*{Arg^{Ex^{Ex}}} = $cmdName(Arg^{Ex^{Ex}})$
  \usrmth{cmdName}{Suf}{par};
  \cmdNameSuf{Par^{Ex^{Ex}}} = $cmdName\Big[Par^{Ex^{Ex}}\Big]$
  \cmdNameSuf*{Par^{Ex^{Ex}}} = $cmdName[Par^{Ex^{Ex}}]$
- \usrmth{cmdName}{Suf}{}[newName]; \cmdNameSuf = $newName$
  \usrmth{cmdName}{Suf}{arg}[newName];
  \cmdNameSuf{Arg^{Ex^{Ex}}} = $newName\Big(Arg^{Ex^{Ex}}\Big)$
  \cmdNameSuf*{Arg^{Ex^{Ex}}} = $newName(Arg^{Ex^{Ex}})$
  \usrmth{cmdName}{Suf}{par}[newName];
  \cmdNameSuf{Par^{Ex^{Ex}}} = $newName\Big[Par^{Ex^{Ex}}\Big]$
  \cmdNameSuf*{Par^{Ex^{Ex}}} = $newName[Par^{Ex^{Ex}}]$

```
\newcommandx{\usrmth}[4][4=]
  {\csdef{#1#2}{%
    \@ifstar%
      {\csname mth#3\endcsname*{\defval{#4}{#1}}}%
      {\csname mth#3\endcsname{\defval{#4}{#1}}}%
  }}

%%*************************************************************************%%
```

\usrmthlatlow ... to do!

```
\newcommandx{\usrmthlatlow}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqoflatlow{#1#2}{mth#3}}
```

\usrmthlatupp ... to do!

```
\newcommandx{\usrmthlatupp}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqoflatupp{#1#2}{mth#3}}
```

\usrmthlatlet ... to do!

```
\newcommandx{\usrmthlatlet}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqoflatlet{#1#2}{mth#3}}
```

\usrmthgrklow ... to do!

```
\newcommandx{\usrmthgrklow}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqofgrklow{#1#2}{mth#3}}
```

\usrmthgrkupp ... to do!

```
\newcommandx{\usrmthgrkupp}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqofgrkupp{#1#2}{mth#3}}
```

\usrmthgrklet ... to do!

```
\newcommandx{\usrmthgrklet}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqofgrklet{#1#2}{mth#3}}
```

\usrmthlow ... to do!

```
\newcommandx{\usrmthlow}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqoflow{#1#2}{mth#3}}
```

\usrmthupp ... to do!

```
\newcommandx{\usrmthupp}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqofupp{#1#2}{mth#3}}
```

\usrmthlet ... to do!

```
\newcommandx{\usrmthlet}[4][4=]
  {\usrmth{#1}{#2}{#3}[#4]\seqoflet{#1#2}{mth#3}}
```

```
%%*************************************************************************%%
%%*************************************************************************%%
%%** Text Macro Generators ************************************************%%
%%*************************************************************************%%
\iftxtgen@
```

\txtdef, ... to do!

- \txtdef{Name}[sub][sup][Ext] = $Name_{sub}^{sup}Ext$
- \txtargdef{Name}[sub][sup][Ext1]{Arg}[Ext2] = $Name_{sub}^{sup}Ext1(Arg)Ext2$
- \txtpardef{Name}[sub][sup][Ext1]{Par}[Ext2] = $Name_{sub}^{sup}Ext1[Par]Ext2$

```
%% Style for Definitions
\cmdtxtall{def}\newcommand{\txtstydef}{\normalfont\bfseries\em}
```

\cmdtxtdef ... to do!

- \cmdtxtdef{cmdName};
  \cmdName[sub][sub][ext] = $cmdName_{sub}^{sub}ext$
- \cmdtxtdef{cmdName}[newName];
  \cmdName[sub][sub][ext] = $newName_{sub}^{sub}ext$

```
\newcommandx{\cmdtxtdef}[2][2=]
  {\usrtxt{#1}{}{def}[#2]}
```

\cmdtxtargdef ... to do!

- \cmdtxtargdef{cmdName};
  \cmdName[sub][sub][ext1]{arg}[ext2] = $cmdName_{sub}^{sub}ext1(arg)ext2$
- \cmdtxtargdef{cmdName}[newName];
  \cmdName[sub][sub][ext1]{arg}[ext2] = $newName_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdtxtargdef}[2][2=]
  {\usrtxt{#1}{}{argdef}[#2]}
```

`\cmdtxtoargdef` ... to do!

- `\cmdtxtoargdef{cmdName}`;
  `\cmdName[sub][sub][arg]` = $\boldsymbol{cmdName^{sub}_{sub}(arg)}$
- `\cmdtxtoargdef{cmdName}[newName]`;
  `\cmdName[sub][sub][arg]` = $\boldsymbol{newName^{sub}_{sub}(arg)}$

```
\newcommandx{\cmdtxtoargdef}[2][2=]
  {\usrtxt{#1}{}{oargdef}[#2]}
```

`\cmdtxtpardef` ... to do!

- `\cmdtxtpardef{cmdName}`;
  `\cmdName[sub][sub][ext1]{par}[ext2]` = $\boldsymbol{cmdName^{sub}_{sub}ext1[par]ext2}$
- `\cmdtxtpardef{cmdName}[newName]`;
  `\cmdName[sub][sub][ext1]{par}[ext2]` = $\boldsymbol{newName^{sub}_{sub}ext1[par]ext2}$

```
\newcommandx{\cmdtxtpardef}[2][2=]
  {\usrtxt{#1}{}{pardef}[#2]}
```

`\cmdtxtopardef` ... to do!

- `\cmdtxtopardef{cmdName}`;
  `\cmdName[sub][sub][par]` = $\boldsymbol{cmdName^{sub}_{sub}[par]}$
- `\cmdtxtopardef{cmdName}[newName]`;
  `\cmdName[sub][sub][par]` = $\boldsymbol{newName^{sub}_{sub}[par]}$

```
\newcommandx{\cmdtxtopardef}[2][2=]
  {\usrtxt{#1}{}{opardef}[#2]}
```

`\txtabr, ...` ... to do!

- `\txtabr{Name}[sub][sup][Ext]` = $Name^{\text{sup}}_{\text{sub}}Ext$
- `\txtargabr{Name}[sub][sup][Ext1]{Arg}[Ext2]` = $Name^{\text{sup}}_{\text{sub}}Ext1(Arg)Ext2$
- `\txtparabr{Name}[sub][sup][Ext1]{Par}[Ext2]` = $Name^{\text{sup}}_{\text{sub}}Ext1[Par]Ext2$

```
%% Style for Abbreviations
\cmdtxtall{abr}\newcommand{\txtstyabr}{\em}
```

`\cmdtxtabr` ... to do!

- `\cmdtxtabr{cmdName}`;
  `\cmdName[sub][sub][ext]` = $cmdName^{\text{sub}}_{\text{sub}}ext$
- `\cmdtxtabr{cmdName}[newName]`;
  `\cmdName[sub][sub][ext]` = $newName^{\text{sub}}_{\text{sub}}ext$

```
\newcommandx{\cmdtxtabr}[2][2=]
  {\usrtxt{#1}{}{abr}[#2]}
```

`\cmdtxtargabr` ... to do!

- `\cmdtxtargabr{cmdName}`;
  `\cmdName[sub][sub][ext1]{arg}[ext2]` = $cmdName^{\text{sub}}_{\text{sub}}ext1(arg)ext2$
- `\cmdtxtargabr{cmdName}[newName]`;
  `\cmdName[sub][sub][ext1]{arg}[ext2]` = $newName^{\text{sub}}_{\text{sub}}ext1(arg)ext2$

```
\newcommandx{\cmdtxtargabr}[2][2=]
  {\usrtxt{#1}{}{argabr}[#2]}
```

`\cmdtxtoargabr` ... to do!

- `\cmdtxtoargabr{cmdName}`;
  `\cmdName[sub][sub][arg]` = $cmdName^{\text{sub}}_{\text{sub}}(arg)$
- `\cmdtxtoargabr{cmdName}[newName]`;
  `\cmdName[sub][sub][arg]` = $newName^{\text{sub}}_{\text{sub}}(arg)$

```
\newcommandx{\cmdtxtoargabr}[2][2=]
  {\usrtxt{#1}{}{oargabr}[#2]}
```

\cmdtxtparabr ... to do!

- \cmdtxtparabr{cmdName};
  \cmdName[sub][sub][ext1]{par}[ext2] = $cmdName^{sub}_{sub}ext1[par]ext2$
- \cmdtxtparabr{cmdName}[newName];
  \cmdName[sub][sub][ext1]{par}[ext2] = $newName^{sub}_{sub}ext1[par]ext2$

```
\newcommandx{\cmdtxtparabr}[2][2=]
  {\usrtxt{#1}{}{parabr}[#2]}
```

\cmdtxtoparabr ... to do!

- \cmdtxtoparabr{cmdName};
  \cmdName[sub][sub][par] = $cmdName^{sub}_{sub}[par]$
- \cmdtxtoparabr{cmdName}[newName];
  \cmdName[sub][sub][par] = $newName^{sub}_{sub}[par]$

```
\newcommandx{\cmdtxtoparabr}[2][2=]
  {\usrtxt{#1}{}{oparabr}[#2]}
```

```
%%*************************************************************************%%
```

\txtname, ... to do!

- \txtname{Name}[sub][sup][Ext] = $\textsc{Name}^{\textsc{sup}}_{\textsc{sub}}\textsc{Ext}$
- \txtargname{Name}[sub][sup][Ext1]{Arg}[Ext2] = $\textsc{Name}^{\textsc{sup}}_{\textsc{sub}}\textsc{Ext1}(\textsc{Arg})\textsc{Ext2}$
- \txtparname{Name}[sub][sup][Ext1]{Par}[Ext2] = $\textsc{Name}^{\textsc{sup}}_{\textsc{sub}}\textsc{Ext1}[\textsc{Par}]\textsc{Ext2}$

```
%% Style for Names
\cmdtxtall{name}\newcommand{\txtstyname}{\normalfont\mdseries\scshape\sffamily}
```

\cmdtxtname ... to do!

- \cmdtxtname{cmdName};
  \cmdName[sub][sub][ext] = $\textsc{cmdName}^{\textsc{sub}}_{\textsc{sub}}\textsc{ext}$
- \cmdtxtname{cmdName}[newName];
  \cmdName[sub][sub][ext] = $\textsc{newName}^{\textsc{sub}}_{\textsc{sub}}\textsc{ext}$

```
\newcommandx{\cmdtxtname}[2][2=]
  {\usrtxt{#1}{}{name}[#2]}
```

\cmdtxtargname ... to do!

- \cmdtxtargname{cmdName};
  \cmdName[sub][sub][ext1]{arg}[ext2] = $\textsc{cmdName}^{\textsc{sub}}_{\textsc{sub}}\textsc{ext1}(\textsc{arg})\textsc{ext2}$
- \cmdtxtargname{cmdName}[newName];
  \cmdName[sub][sub][ext1]{arg}[ext2] = $\textsc{newName}^{\textsc{sub}}_{\textsc{sub}}\textsc{ext1}(\textsc{arg})\textsc{ext2}$

```
\newcommandx{\cmdtxtargname}[2][2=]
  {\usrtxt{#1}{}{argname}[#2]}
```

\cmdtxtoargname ... to do!

- \cmdtxtoargname{cmdName};
  \cmdName[sub][sub][arg] = $\textsc{cmdName}^{\textsc{sub}}_{\textsc{sub}}(\textsc{arg})$
- \cmdtxtoargname{cmdName}[newName];
  \cmdName[sub][sub][arg] = $\textsc{newName}^{\textsc{sub}}_{\textsc{sub}}(\textsc{arg})$

```
\newcommandx{\cmdtxtoargname}[2][2=]
  {\usrtxt{#1}{}{oargname}[#2]}
```

\cmdtxtparname ... to do!

- \cmdtxtparname{cmdName};
  \cmdName[sub][sub][ext1]{par}[ext2] = $\textsc{cmdName}^{\textsc{sub}}_{\textsc{sub}}\textsc{ext1}[\textsc{par}]\textsc{ext2}$
- \cmdtxtparname{cmdName}[newName];
  \cmdName[sub][sub][ext1]{par}[ext2] = $\textsc{newName}^{\textsc{sub}}_{\textsc{sub}}\textsc{ext1}[\textsc{par}]\textsc{ext2}$

```
\newcommandx{\cmdtxtparname}[2][2=]
  {\usrtxt{#1}{}{parname}[#2]}
```

\cmdtxtoparname ... to do!

- \cmdtxtoparname{cmdName};
  \cmdName[sub][sub][par] = CMDNAME$_{SUB}^{SUB}$[PAR]
- \cmdtxtoparname{cmdName}[newName];
  \cmdName[sub][sub][par] = NEWNAME$_{SUB}^{SUB}$[PAR]

```
\newcommandx{\cmdtxtoparname}[2][2=]
  {\usrtxt{#1}{}{oparname}[#2]}
```

\txtcom, ... to do!

- \txtcom{Name}[sub][sup][Ext] = NAME$_{SUB}^{SUP}$EXT
- \txtargcom{Name}[sub][sup][Ext1]{Arg}[Ext2] = NAME$_{SUB}^{SUP}$EXT1(ARG)EXT2
- \txtparcom{Name}[sub][sup][Ext1]{Par}[Ext2] = NAME$_{SUB}^{SUP}$EXT1[PAR]EXT2

```
%% Style for Complexities
\cmdtxtall{com}\newcommand{\txtstycom}{\normalfont\mdseries\scshape\rmfamily}
```

\cmdtxtcom ... to do!

- \cmdtxtcom{cmdName};
  \cmdName[sub][sub][ext] = CMDNAME$_{SUB}^{SUB}$EXT
- \cmdtxtcom{cmdName}[newName];
  \cmdName[sub][sub][ext] = NEWNAME$_{SUB}^{SUB}$EXT

```
\newcommandx{\cmdtxtcom}[2][2=]
  {\usrtxt{#1}{}{com}[#2]}
```

\cmdtxtargcom ... to do!

- \cmdtxtargcom{cmdName};
  \cmdName[sub][sub][ext1]{arg}[ext2] = CMDNAME$_{SUB}^{SUB}$EXT1(ARG)EXT2
- \cmdtxtargcom{cmdName}[newName];
  \cmdName[sub][sub][ext1]{arg}[ext2] = NEWNAME$_{SUB}^{SUB}$EXT1(ARG)EXT2

```
\newcommandx{\cmdtxtargcom}[2][2=]
  {\usrtxt{#1}{}{argcom}[#2]}
```

\cmdtxtoargcom ... to do!

- \cmdtxtoargcom{cmdName};
  \cmdName[sub][sub][arg] = CMDNAME$_{SUB}^{SUB}$(ARG)
- \cmdtxtoargcom{cmdName}[newName];
  \cmdName[sub][sub][arg] = NEWNAME$_{SUB}^{SUB}$(ARG)

```
\newcommandx{\cmdtxtoargcom}[2][2=]
  {\usrtxt{#1}{}{oargcom}[#2]}
```

\cmdtxtparcom ... to do!

- \cmdtxtparcom{cmdName};
  \cmdName[sub][sub][ext1]{par}[ext2] = CMDNAME$_{SUB}^{SUB}$EXT1[PAR]EXT2
- \cmdtxtparcom{cmdName}[newName];
  \cmdName[sub][sub][ext1]{par}[ext2] = NEWNAME$_{SUB}^{SUB}$EXT1[PAR]EXT2

```
\newcommandx{\cmdtxtparcom}[2][2=]
  {\usrtxt{#1}{}{parcom}[#2]}
```

\cmdtxtoparcom ... to do!

- \cmdtxtoparcom{cmdName};
  \cmdName[sub][sub][par] = CMDNAME$_{SUB}^{SUB}$[PAR]
- \cmdtxtoparcom{cmdName}[newName];
  \cmdName[sub][sub][par] = NEWNAME$_{SUB}^{SUB}$[PAR]

```
\newcommandx{\cmdtxtoparcom}[2][2=]
  {\usrtxt{#1}{}{oparcom}[#2]}

\fi
%%*************************************************************************%%
```

```
%%*****************************************************************************%%
%%** Math Macro Generators *****************************************************%%
%%*****************************************************************************%%
\ifmthgen@
```

`\mthname, ...` ... to do!

- `\mthname{NAME}[sub][sup][Ext]` = $\mathcal{NAME}_{sub}^{sup}Ext$
- `\mthargname{NAME}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
- `\mthargname*{NAME}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparname{NAME}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
- `\mthparname*{NAME}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Names
\cmdmthall{name}\newcommand{\mthstyname}{\mathcal}
```

`\AName, ...` ... to do!
$\mathcal{A}$, $\mathcal{B}$, $\mathcal{C}$, $\mathcal{D}$, $\mathcal{E}$, $\mathcal{F}$, $\mathcal{G}$, $\mathcal{H}$, $\mathcal{I}$, $\mathcal{J}$, $\mathcal{K}$, $\mathcal{L}$, $\mathcal{M}$, $\mathcal{N}$, $\mathcal{O}$, $\mathcal{P}$, $\mathcal{Q}$, $\mathcal{R}$, $\mathcal{S}$, $\mathcal{T}$, $\mathcal{U}$, $\mathcal{V}$, $\mathcal{W}$, $\mathcal{X}$, $\mathcal{Y}$, $\mathcal{Z}$

```
\seqoflatupp{Name}{mthname}
```

`\cmdmthname` ... to do!

- `\cmdmthname{CMDNAME}`;
  `\CMDNAMEName[sub][sub][ext]` = $\mathcal{CMDNAME}_{sub}^{sub}ext$
- `\cmdmthname{cmdName}[NEWNAME]`;
  `\cmdNameName[sub][sub][ext]` = $\mathcal{NEWNAME}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthname}[2][2=]
  {\usrmth{#1}{Name}{name}[#2]}
```

`\cmdmthargname` ... to do!

- `\cmdmthargname{CMDNAME}`;
  `\CMDNAMEName[sub][sub][ext1]{arg}[ext2]` = $\mathcal{CMDNAME}_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargname{cmdName}[NEWNAME]`;
  `\cmdNameName[sub][sub][ext1]{arg}[ext2]` = $\mathcal{NEWNAME}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargname}[2][2=]
  {\usrmth{#1}{Name}{argname}[#2]}
```

`\cmdmthoargname` ... to do!

- `\cmdmthoargname{CMDNAME}`;
  `\CMDNAMEName[sub][sub][arg]` = $\mathcal{CMDNAME}_{sub}^{sub}(arg)$
- `\cmdmthoargname{cmdName}[NEWNAME]`;
  `\cmdNameName[sub][sub][arg]` = $\mathcal{NEWNAME}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargname}[2][2=]
  {\usrmth{#1}{Name}{oargname}[#2]}
```

`\cmdmthparname` ... to do!

- `\cmdmthparname{CMDNAME}`;
  `\CMDNAMEName[sub][sub][ext1]{par}[ext2]` = $\mathcal{CMDNAME}_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparname{cmdName}[NEWNAME]`;
  `\cmdNameName[sub][sub][ext1]{par}[ext2]` = $\mathcal{NEWNAME}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparname}[2][2=]
  {\usrmth{#1}{Name}{parname}[#2]}
```

`\cmdmthoparname` ... to do!

- `\cmdmthoparname{CMDNAME}`;
  `\CMDNAMEName[sub][sub][par]` = $\mathcal{CMDNAME}_{sub}^{sub}[par]$
- `\cmdmthoparname{cmdName}[NEWNAME]`;
  `\cmdNameName[sub][sub][par]` = $\mathcal{NEWNAME}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparname}[2][2=]
  {\usrmth{#1}{Name}{oparname}[#2]}
```

`\mthfam, ...` ... to do!

- `\mthfam{NAME}[sub][sup][Ext]` $= \mathscr{NAMME}^{sup}_{sub}Ext$
- `\mthargfam{NAME}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` $= \mathscr{NAMME}^{sup}_{sub}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$
- `\mthargfam*{NAME}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` $= \mathscr{NAMME}^{sup}_{sub}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparfam{NAME}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` $= \mathscr{NAMME}^{sup}_{sub}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$
- `\mthparfam*{NAME}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` $= \mathscr{NAMME}^{sup}_{sub}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Families
\cmdmthall{fam}\newcommand{\mthstyfam}{\mathscr}
```

`\AFam, ...` ... to do!
$\mathscr{A}, \mathscr{B}, \mathscr{C}, \mathscr{D}, \mathscr{E}, \mathscr{F}, \mathscr{G}, \mathscr{H}, \mathscr{I}, \mathscr{J}, \mathscr{K}, \mathscr{L}, \mathscr{M}, \mathscr{N}, \mathscr{O}, \mathscr{P}, \mathscr{Q}, \mathscr{R}, \mathscr{S}, \mathscr{T}, \mathscr{U}, \mathscr{V}, \mathscr{W}, \mathscr{X}, \mathscr{Y}, \mathscr{Z}$

```
\seqoflatupp{Fam}{mthfam}
```

`\cmdmthfam` ... to do!

- `\cmdmthfam{CMDNAME}`;
  `\CMDNAMEFam[sub][sub][ext]` $= \mathscr{CMDNAMME}^{sub}_{sub}ext$
- `\cmdmthfam{cmdName}[NEWNAME]`;
  `\cmdNameFam[sub][sub][ext]` $= \mathscr{NEWNAMME}^{sub}_{sub}ext$

```
\newcommandx{\cmdmthfam}[2][2=]
  {\usrmth{#1}{Fam}{fam}[#2]}
```

`\cmdmthargfam` ... to do!

- `\cmdmthargfam{CMDNAME}`;
  `\CMDNAMEFam[sub][sub][ext1]{arg}[ext2]` $= \mathscr{CMDNAMME}^{sub}_{sub}ext1(arg)ext2$
- `\cmdmthargfam{cmdName}[NEWNAME]`;
  `\cmdNameFam[sub][sub][ext1]{arg}[ext2]` $= \mathscr{NEWNAMME}^{sub}_{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargfam}[2][2=]
  {\usrmth{#1}{Fam}{argfam}[#2]}
```

`\cmdmthoargfam` ... to do!

- `\cmdmthoargfam{CMDNAME}`;
  `\CMDNAMEFam[sub][sub][arg]` $= \mathscr{CMDNAMME}^{sub}_{sub}(arg)$
- `\cmdmthoargfam{cmdFam}[NEWNAME]`;
  `\cmdFamFam[sub][sub][arg]` $= \mathscr{NEWNAMME}^{sub}_{sub}(arg)$

```
\newcommandx{\cmdmthoargfam}[2][2=]
  {\usrmth{#1}{Fam}{oargfam}[#2]}
```

`\cmdmthparfam` ... to do!

- `\cmdmthparfam{CMDNAME}`;
  `\CMDNAMEFam[sub][sub][ext1]{par}[ext2]` $= \mathscr{CMDNAMME}^{sub}_{sub}ext1[par]ext2$
- `\cmdmthparfam{cmdName}[NEWNAME]`;
  `\cmdNameFam[sub][sub][ext1]{par}[ext2]` $= \mathscr{NEWNAMME}^{sub}_{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparfam}[2][2=]
  {\usrmth{#1}{Fam}{parfam}[#2]}
```

`\cmdmthoparfam` ... to do!

- `\cmdmthoparfam{CMDNAME}`;
  `\CMDNAMEFam[sub][sub][par]` $= \mathscr{CMDNAMME}^{sub}_{sub}[par]$
- `\cmdmthoparfam{cmdFam}[NEWNAME]`;
  `\cmdFamFam[sub][sub][par]` $= \mathscr{NEWNAMME}^{sub}_{sub}[par]$

```
\newcommandx{\cmdmthoparfam}[2][2=]
  {\usrmth{#1}{Fam}{oparfam}[#2]}
```

`\mthcls, ...` ... to do!

- `\mthcls{NAME}[sub][sup][Ext]` = $\mathcal{NAME}_{sub}^{sup}Ext$
- `\mthargcls{NAME}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$
- `\mthargcls*{NAME}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparcls{NAME}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$
- `\mthparcls*{NAME}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathcal{NAME}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Classes
\cmdmthall{cls}\newcommand{\mthstycls}{\matheus}
```

`\ACls, ...` ... to do!
$\mathcal{A}$, $\mathcal{B}$, $\mathcal{C}$, $\mathcal{D}$, $\mathcal{E}$, $\mathcal{F}$, $\mathcal{G}$, $\mathcal{H}$, $\mathcal{I}$, $\mathcal{J}$, $\mathcal{K}$, $\mathcal{L}$, $\mathcal{M}$, $\mathcal{N}$, $\mathcal{O}$, $\mathcal{P}$, $\mathcal{Q}$, $\mathcal{R}$, $\mathcal{S}$, $\mathcal{T}$, $\mathcal{U}$, $\mathcal{V}$, $\mathcal{W}$, $\mathcal{X}$, $\mathcal{Y}$, $\mathcal{Z}$

```
\seqoflatupp{Cls}{mthcls}
```

`\cmdmthcls` ... to do!

- `\cmdmthcls{CMDNAME}`;
  `\CMDNAMECls[sub][sub][ext]` = $\mathcal{CMDNAME}_{sub}^{sub}ext$
- `\cmdmthcls{cmdName}[NEWNAME]`;
  `\cmdNameCls[sub][sub][ext]` = $\mathcal{NEWNAME}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthcls}[2][2=]
  {\usrmth{#1}{Cls}{cls}[#2]}
```

`\cmdmthargcls` ... to do!

- `\cmdmthargcls{CMDNAME}`;
  `\CMDNAMECls[sub][sub][ext1]{arg}[ext2]` = $\mathcal{CMDNAME}_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargcls{cmdName}[NEWNAME]`;
  `\cmdNameCls[sub][sub][ext1]{arg}[ext2]` = $\mathcal{NEWNAME}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargcls}[2][2=]
  {\usrmth{#1}{Cls}{argcls}[#2]}
```

`\cmdmthoargcls` ... to do!

- `\cmdmthoargcls{CMDNAME}`;
  `\CMDNAMECls[sub][sub][arg]` = $\mathcal{CMDNAME}_{sub}^{sub}(arg)$
- `\cmdmthoargcls{cmdCls}[NEWNAME]`;
  `\cmdClsCls[sub][sub][arg]` = $\mathcal{NEWNAME}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargcls}[2][2=]
  {\usrmth{#1}{Cls}{oargcls}[#2]}
```

`\cmdmthparcls` ... to do!

- `\cmdmthparcls{CMDNAME}`;
  `\CMDNAMECls[sub][sub][ext1]{par}[ext2]` = $\mathcal{CMDNAME}_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparcls{cmdName}[NEWNAME]`;
  `\cmdNameCls[sub][sub][ext1]{par}[ext2]` = $\mathcal{NEWNAME}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparcls}[2][2=]
  {\usrmth{#1}{Cls}{parcls}[#2]}
```

`\cmdmthoparcls` ... to do!

- `\cmdmthoparcls{CMDNAME}`;
  `\CMDNAMECls[sub][sub][par]` = $\mathcal{CMDNAME}_{sub}^{sub}[par]$
- `\cmdmthoparcls{cmdCls}[NEWNAME]`;
  `\cmdClsCls[sub][sub][par]` = $\mathcal{NEWNAME}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparcls}[2][2=]
  {\usrmth{#1}{Cls}{oparcls}[#2]}
```

`\mthsig, ...` ... to do!

- `\mthsig{Name}[sub][sup][Ext]` = $\mathcal{Name}_{sub}^{sup}Ext$

- `\mthargsig{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathcal{N}ame_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$
- `\mthargsig*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathcal{N}ame_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparsig{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathcal{N}ame_{sub}^{sup}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$
- `\mthparsig*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathcal{N}ame_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Signatures
\cmdmthall{sig}\newcommand{\mthstysig}{\mathpzc}
```

`\aSig, ...` ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
$\mathcal{A}$, $\mathcal{B}$, $\mathcal{C}$, $\mathcal{D}$, $\mathcal{E}$, $\mathcal{F}$, $\mathcal{G}$, $\mathcal{H}$, $\mathcal{I}$, $\mathcal{J}$, $\mathcal{K}$, $\mathcal{L}$, $\mathcal{M}$, $\mathcal{N}$, $\mathcal{O}$, $\mathcal{P}$, $\mathcal{Q}$, $\mathcal{R}$, $\mathcal{S}$, $\mathcal{T}$, $\mathcal{U}$, $\mathcal{V}$, $\mathcal{W}$, $\mathcal{X}$, $\mathcal{Y}$, $\mathcal{Z}$
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω

```
\seqoflatlet{Sig}{mthsig}\seqofgrklow{Sig}{mthsig}
```

`\cmdmthsig` ... to do!

- `\cmdmthsig{cmdName}`;
  `\cmdNameSig[sub][sub][ext]` = $cmd\mathcal{N}ame_{sub}^{sub}ext$
- `\cmdmthsig{cmdName}[NewName]`;
  `\cmdNameSig[sub][sub][ext]` = $\mathcal{N}ew\mathcal{N}ame_{sub}^{sub}ext$

```
\newcommandx{\cmdmthsig}[2][2=]
  {\usrmth{#1}{Sig}{sig}[#2]}
```

`\cmdmthargsig` ... to do!

- `\cmdmthargsig{cmdName}`;
  `\cmdNameSig[sub][sub][ext1]{arg}[ext2]` = $cmd\mathcal{N}ame_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargsig{cmdName}[NewName]`;
  `\cmdNameSig[sub][sub][ext1]{arg}[ext2]` = $\mathcal{N}ew\mathcal{N}ame_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargsig}[2][2=]
  {\usrmth{#1}{Sig}{argsig}[#2]}
```

`\cmdmthoargsig` ... to do!

- `\cmdmthoargsig{cmdName}`;
  `\cmdNameSig[sub][sub][arg]` = $cmd\mathcal{N}ame_{sub}^{sub}(arg)$
- `\cmdmthoargsig{cmdSig}[NewName]`;
  `\cmdSigSig[sub][sub][arg]` = $\mathcal{N}ew\mathcal{N}ame_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargsig}[2][2=]
  {\usrmth{#1}{Sig}{oargsig}[#2]}
```

`\cmdmthparsig` ... to do!

- `\cmdmthparsig{cmdName}`;
  `\cmdNameSig[sub][sub][ext1]{par}[ext2]` = $cmd\mathcal{N}ame_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparsig{cmdName}[NewName]`;
  `\cmdNameSig[sub][sub][ext1]{par}[ext2]` = $\mathcal{N}ew\mathcal{N}ame_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparsig}[2][2=]
  {\usrmth{#1}{Sig}{parsig}[#2]}
```

`\cmdmthoparsig` ... to do!

- `\cmdmthoparsig{cmdName}`;
  `\cmdNameSig[sub][sub][par]` = $cmd\mathcal{N}ame_{sub}^{sub}[par]$
- `\cmdmthoparsig{cmdSig}[NewName]`;
  `\cmdSigSig[sub][sub][par]` = $\mathcal{N}ew\mathcal{N}ame_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparsig}[2][2=]
  {\usrmth{#1}{Sig}{oparsig}[#2]}
```

`\mthstr, ...` ... to do!

- `\mthstr{Name}[sub][sup][Ext]` = $\mathfrak{Name}_{sub}^{sup}Ext$
- `\mthargstr{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathfrak{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$

- `\mthargstr*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathfrak{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparstr{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathfrak{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
- `\mthparstr*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathfrak{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Structures
\cmdmthall{str}\newcommand{\mthstystr}{\mathfrak}
```

`\aStr, ...` ... to do!

$\mathfrak{a}$, $\mathfrak{b}$, $\mathfrak{c}$, $\mathfrak{d}$, $\mathfrak{e}$, $\mathfrak{f}$, $\mathfrak{g}$, $\mathfrak{h}$, $\mathfrak{i}$, $\mathfrak{j}$, $\mathfrak{k}$, $\mathfrak{l}$, $\mathfrak{m}$, $\mathfrak{n}$, $\mathfrak{o}$, $\mathfrak{p}$, $\mathfrak{q}$, $\mathfrak{r}$, $\mathfrak{s}$, $\mathfrak{t}$, $\mathfrak{u}$, $\mathfrak{v}$, $\mathfrak{w}$, $\mathfrak{x}$, $\mathfrak{y}$, $\mathfrak{z}$
$\mathfrak{A}$, $\mathfrak{B}$, $\mathfrak{C}$, $\mathfrak{D}$, $\mathfrak{E}$, $\mathfrak{F}$, $\mathfrak{G}$, $\mathfrak{H}$, $\mathfrak{I}$, $\mathfrak{J}$, $\mathfrak{K}$, $\mathfrak{L}$, $\mathfrak{M}$, $\mathfrak{N}$, $\mathfrak{O}$, $\mathfrak{P}$, $\mathfrak{Q}$, $\mathfrak{R}$, $\mathfrak{S}$, $\mathfrak{T}$, $\mathfrak{U}$, $\mathfrak{V}$, $\mathfrak{W}$, $\mathfrak{X}$, $\mathfrak{Y}$, $\mathfrak{Z}$
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, $\mathfrak{o}$, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω

```
\seqoflatlet{Str}{mthstr}\seqofgrklow{Str}{mthstr}
```

`\cmdmthstr` ... to do!

- `\cmdmthstr{cmdName}`;
  `\cmdNameStr[sub][sub][ext]` = $\mathfrak{cmdName}_{sub}^{sub}ext$
- `\cmdmthstr{cmdName}[NewName]`;
  `\cmdNameStr[sub][sub][ext]` = $\mathfrak{NewName}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthstr}[2][2=]
  {\usrmth{#1}{Str}{str}[#2]}
```

`\cmdmthargstr` ... to do!

- `\cmdmthargstr{cmdName}`;
  `\cmdNameStr[sub][sub][ext1]{arg}[ext2]` = $\mathfrak{cmdName}_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargstr{cmdName}[NewName]`;
  `\cmdNameStr[sub][sub][ext1]{arg}[ext2]` = $\mathfrak{NewName}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargstr}[2][2=]
  {\usrmth{#1}{Str}{argstr}[#2]}
```

`\cmdmthoargstr` ... to do!

- `\cmdmthoargstr{cmdName}`;
  `\cmdNameStr[sub][sub][arg]` = $\mathfrak{cmdName}_{sub}^{sub}(arg)$
- `\cmdmthoargstr{cmdStr}[NewName]`;
  `\cmdStrStr[sub][sub][arg]` = $\mathfrak{NewName}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargstr}[2][2=]
  {\usrmth{#1}{Str}{oargstr}[#2]}
```

`\cmdmthparstr` ... to do!

- `\cmdmthparstr{cmdName}`;
  `\cmdNameStr[sub][sub][ext1]{par}[ext2]` = $\mathfrak{cmdName}_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparstr{cmdName}[NewName]`;
  `\cmdNameStr[sub][sub][ext1]{par}[ext2]` = $\mathfrak{NewName}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparstr}[2][2=]
  {\usrmth{#1}{Str}{parstr}[#2]}
```

`\cmdmthoparstr` ... to do!

- `\cmdmthoparstr{cmdName}`;
  `\cmdNameStr[sub][sub][par]` = $\mathfrak{cmdName}_{sub}^{sub}[par]$
- `\cmdmthoparstr{cmdStr}[NewName]`;
  `\cmdStrStr[sub][sub][par]` = $\mathfrak{NewName}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparstr}[2][2=]
  {\usrmth{#1}{Str}{oparstr}[#2]}
```

`\mthset, ...` ... to do!

- `\mthset{Name}[sub][sup][Ext]` = $\mathrm{Name}_{sub}^{sup}Ext$
- `\mthargset{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathrm{Name}_{sub}^{sup}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
- `\mthargset*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathrm{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$

- `\mthparset{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathrm{Name}_{sub}^{sup}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$
- `\mthparset*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathrm{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Sets
\cmdmthall{set}\newcommand{\mthstyset}{\mathrm}
```

`\aSet, ...` ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω
A, B, Γ, Δ, E, E, Z, H, Θ, $\varTheta$, I, K, K, Λ, M, N, Ξ, O, Π, $\varPi$, P, P, Σ, $\varSigma$, T, Υ, Φ, $\varPhi$, X, Ψ, Ω

```
\seqoflet{Set}{mthset}
```

`\cmdmthset` ... to do!

- `\cmdmthset{cmdName}`;
  `\cmdNameSet[sub][sub][ext]` = $\mathrm{cmdName}_{sub}^{sub}ext$
- `\cmdmthset{cmdName}[NewName]`;
  `\cmdNameSet[sub][sub][ext]` = $\mathrm{NewName}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthset}[2][2=]
  {\usrmth{#1}{Set}{set}[#2]}
```

`\cmdmthargset` ... to do!

- `\cmdmthargset{cmdName}`;
  `\cmdNameSet[sub][sub][ext1]{arg}[ext2]` = $\mathrm{cmdName}_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargset{cmdName}[NewName]`;
  `\cmdNameSet[sub][sub][ext1]{arg}[ext2]` = $\mathrm{NewName}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargset}[2][2=]
  {\usrmth{#1}{Set}{argset}[#2]}
```

`\cmdmthoargset` ... to do!

- `\cmdmthoargset{cmdName}`;
  `\cmdNameSet[sub][sub][arg]` = $\mathrm{cmdName}_{sub}^{sub}(arg)$
- `\cmdmthoargset{cmdSet}[NewName]`;
  `\cmdSetSet[sub][sub][arg]` = $\mathrm{NewName}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargset}[2][2=]
  {\usrmth{#1}{Set}{oargset}[#2]}
```

`\cmdmthparset` ... to do!

- `\cmdmthparset{cmdName}`;
  `\cmdNameSet[sub][sub][ext1]{par}[ext2]` = $\mathrm{cmdName}_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparset{cmdName}[NewName]`;
  `\cmdNameSet[sub][sub][ext1]{par}[ext2]` = $\mathrm{NewName}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparset}[2][2=]
  {\usrmth{#1}{Set}{parset}[#2]}
```

`\cmdmthoparset` ... to do!

- `\cmdmthoparset{cmdName}`;
  `\cmdNameSet[sub][sub][par]` = $\mathrm{cmdName}_{sub}^{sub}[par]$
- `\cmdmthoparset{cmdSet}[NewName]`;
  `\cmdSetSet[sub][sub][par]` = $\mathrm{NewName}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparset}[2][2=]
  {\usrmth{#1}{Set}{oparset}[#2]}
```

`\cmdmthsetext` ... to do!

```
\newcommandx{\cmdmthsetext}[3][2=, 3=]
  {\cmdmthset{#1}[#2]\caselower[q]{#1}%
  \usrmthlet{\thestring}{Sym}{sym}
    [\defval{#3}{\defval{\empchk{#2}{\lowercase{#2}}}{\thestring}}]%
  \usrmthlet{\thestring}{Elm}{elm}
    [\defval{#3}{\defval{\empchk{#2}{\lowercase{#2}}}{\thestring}}]}
```

`\mthrel, ...` ... to do!

- `\mthrel{Name}[sub][sup][Ext]` = $Name_{sub}^{sup}Ext$
- `\mthargrel{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$
- `\mthargrel*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparrel{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$
- `\mthparrel*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Relations
\cmdmthall{rel}\newcommand{\mthstyrel}{\mathit}
```

`\aRel, ...` ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, L, T, U, V, W, X, Y, Z
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω
A, B, Γ, Δ, E, E, Z, H, Θ, Θ, I, K, K, Λ, M, N, Ξ, O, Π, Π, P, P, Σ, Σ, T, Υ, Φ, Φ, X, Ψ, Ω

```
\seqoflet{Rel}{mthrel}
```

`\cmdmthrel` ... to do!

- `\cmdmthrel{cmdName}`;
  `\cmdNameRel[sub][sub][ext]` = $cmdName_{sub}^{sub}ext$
- `\cmdmthrel{cmdName}[NewName]`;
  `\cmdNameRel[sub][sub][ext]` = $NewName_{sub}^{sub}ext$

```
\newcommandx{\cmdmthrel}[2][2=]
  {\usrmth{#1}{Rel}{rel}[#2]}
```

`\cmdmthargrel` ... to do!

- `\cmdmthargrel{cmdName}`;
  `\cmdNameRel[sub][sub][ext1]{arg}[ext2]` = $cmdName_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargrel{cmdName}[NewName]`;
  `\cmdNameRel[sub][sub][ext1]{arg}[ext2]` = $NewName_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargrel}[2][2=]
  {\usrmth{#1}{Rel}{argrel}[#2]}
```

`\cmdmthoargrel` ... to do!

- `\cmdmthoargrel{cmdName}`;
  `\cmdNameRel[sub][sub][arg]` = $cmdName_{sub}^{sub}(arg)$
- `\cmdmthoargrel{cmdRel}[NewName]`;
  `\cmdRelRel[sub][sub][arg]` = $NewName_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargrel}[2][2=]
  {\usrmth{#1}{Rel}{oargrel}[#2]}
```

`\cmdmthparrel` ... to do!

- `\cmdmthparrel{cmdName}`;
  `\cmdNameRel[sub][sub][ext1]{par}[ext2]` = $cmdName_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparrel{cmdName}[NewName]`;
  `\cmdNameRel[sub][sub][ext1]{par}[ext2]` = $NewName_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparrel}[2][2=]
  {\usrmth{#1}{Rel}{parrel}[#2]}
```

`\cmdmthoparrel` ... to do!

- `\cmdmthoparrel{cmdName}`;
  `\cmdNameRel[sub][sub][par]` = $cmdName_{sub}^{sub}[par]$
- `\cmdmthoparrel{cmdRel}[NewName]`;
  `\cmdRelRel[sub][sub][par]` = $NewName_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparrel}[2][2=]
  {\usrmth{#1}{Rel}{oparrel}[#2]}
```

`\mthfun, ...` ... to do!

- `\mthfun{Name}[sub][sup][Ext]` = $\mathsf{Name}_{sub}^{sup}Ext$
- `\mthargfun{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathsf{Name}_{sub}^{sup}Ext1\Big(Arg^{Ex^{Ex}}\Big)Ext2$
- `\mthargfun*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathsf{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparfun{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathsf{Name}_{sub}^{sup}Ext1\Big[Par^{Ex^{Ex}}\Big]Ext2$
- `\mthparfun*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathsf{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Functions
\cmdmthall{fun}\newcommand{\mthstyfun}{\mathsf}
```

`\aFun, ...` ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω
A, B, Γ, Δ, E, E, Z, H, Θ, $\varTheta$, I, K, K, Λ, M, N, Ξ, O, Π, $\varPi$, P, P, Σ, $\varSigma$, T, Υ, Φ, $\varPhi$, X, Ψ, Ω

```
\seqoflet{Fun}{mthfun}
```

`\cmdmthfun` ... to do!

- `\cmdmthfun{cmdName}`;
  `\cmdNameFun[sub][sub][ext]` = $\mathsf{cmdName}_{sub}^{sub}ext$
- `\cmdmthfun{cmdName}[NewName]`;
  `\cmdNameFun[sub][sub][ext]` = $\mathsf{NewName}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthfun}[2][2=]
  {\usrmth{#1}{Fun}{fun}[#2]}
```

`\cmdmthargfun` ... to do!

- `\cmdmthargfun{cmdName}`;
  `\cmdNameFun[sub][sub][ext1]{arg}[ext2]` = $\mathsf{cmdName}_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargfun{cmdName}[NewName]`;
  `\cmdNameFun[sub][sub][ext1]{arg}[ext2]` = $\mathsf{NewName}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargfun}[2][2=]
  {\usrmth{#1}{Fun}{argfun}[#2]}
```

`\cmdmthoargfun` ... to do!

- `\cmdmthoargfun{cmdName}`;
  `\cmdNameFun[sub][sub][arg]` = $\mathsf{cmdName}_{sub}^{sub}(arg)$
- `\cmdmthoargfun{cmdFun}[NewName]`;
  `\cmdFunFun[sub][sub][arg]` = $\mathsf{NewName}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargfun}[2][2=]
  {\usrmth{#1}{Fun}{oargfun}[#2]}
```

`\cmdmthparfun` ... to do!

- `\cmdmthparfun{cmdName}`;
  `\cmdNameFun[sub][sub][ext1]{par}[ext2]` = $\mathsf{cmdName}_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparfun{cmdName}[NewName]`;
  `\cmdNameFun[sub][sub][ext1]{par}[ext2]` = $\mathsf{NewName}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparfun}[2][2=]
  {\usrmth{#1}{Fun}{parfun}[#2]}
```

`\cmdmthoparfun` ... to do!

- `\cmdmthoparfun{cmdName}`;
  `\cmdNameFun[sub][sub][par]` = $\mathsf{cmdName}_{sub}^{sub}[par]$
- `\cmdmthoparfun{cmdFun}[NewName]`;
  `\cmdFunFun[sub][sub][par]` = $\mathsf{NewName}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparfun}[2][2=]
  {\usrmth{#1}{Fun}{oparfun}[#2]}
```

`\mthsym, ...` ... to do!

- `\mthsym{Name}[sub][sup][Ext]` = $\texttt{Name}_{sub}^{sup}Ext$
- `\mthargsym{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\texttt{Name}_{sub}^{sup}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
- `\mthargsym*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\texttt{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparsym{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\texttt{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
- `\mthparsym*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\texttt{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Symbols
\cmdmthall{sym}\newcommand{\mthstysym}{\mathtt}
```

`\aSym, ...` ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω
A, B, Γ, Δ, E, E, Z, H, Θ, $\mathit{\Theta}$, I, K, K, Λ, M, N, Ξ, O, Π, $\mathit{\Pi}$, P, P, Σ, $\mathit{\Sigma}$, T, Υ, Φ, $\mathit{\Phi}$, X, Ψ, Ω

```
\seqoflet{Sym}{mthsym}
```

`\cmdmthsym` ... to do!

- `\cmdmthsym{cmdName}`;
  `\cmdNameSym[sub][sub][ext]` = $\texttt{cmdName}_{sub}^{sub}ext$
- `\cmdmthsym{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][ext]` = $\texttt{NewName}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthsym}[2][2=]
  {\usrmth{#1}{Sym}{sym}[#2]}
```

`\cmdmthargsym` ... to do!

- `\cmdmthargsym{cmdName}`;
  `\cmdNameSym[sub][sub][ext1]{arg}[ext2]` = $\texttt{cmdName}_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargsym{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][ext1]{arg}[ext2]` = $\texttt{NewName}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargsym}[2][2=]
  {\usrmth{#1}{Sym}{argsym}[#2]}
```

`\cmdmthoargsym` ... to do!

- `\cmdmthoargsym{cmdName}`;
  `\cmdNameSym[sub][sub][arg]` = $\texttt{cmdName}_{sub}^{sub}(arg)$
- `\cmdmthoargsym{cmdSym}[NewName]`;
  `\cmdSymSym[sub][sub][arg]` = $\texttt{NewName}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargsym}[2][2=]
  {\usrmth{#1}{Sym}{oargsym}[#2]}
```

`\cmdmthparsym` ... to do!

- `\cmdmthparsym{cmdName}`;
  `\cmdNameSym[sub][sub][ext1]{par}[ext2]` = $\texttt{cmdName}_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparsym{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][ext1]{par}[ext2]` = $\texttt{NewName}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparsym}[2][2=]
  {\usrmth{#1}{Sym}{parsym}[#2]}
```

`\cmdmthoparsym` ... to do!

- `\cmdmthoparsym{cmdName}`;
  `\cmdNameSym[sub][sub][par]` = $\texttt{cmdName}_{sub}^{sub}[par]$
- `\cmdmthoparsym{cmdSym}[NewName]`;
  `\cmdSymSym[sub][sub][par]` = $\texttt{NewName}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparsym}[2][2=]
  {\usrmth{#1}{Sym}{oparsym}[#2]}
```

`\mthelm, ...` ... to do!

- `\mthelm{Name}[sub][sup][Ext]` = $Name_{sub}^{sup}Ext$
- `\mthargelm{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
- `\mthargelm*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparelm{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
- `\mthparelm*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $Name_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Elements
\cmdmthall{elm}\newcommand{\mthstyelm}{\mathnormal}
```

`\aElm, ...` ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω
A, B, Γ, Δ, E, E, Z, H, Θ, Θ, I, K, K, Λ, M, N, Ξ, O, Π, Π, P, P, Σ, Σ, T, Υ, Φ, Φ, X, Ψ, Ω

```
\seqoflet{Elm}{mthelm}
```

`\cmdmthelm` ... to do!

- `\cmdmthelm{cmdName}`;
  `\cmdNameElm[sub][sub][ext]` = $cmdName_{sub}^{sub}ext$
- `\cmdmthelm{cmdName}[NewName]`;
  `\cmdNameElm[sub][sub][ext]` = $NewName_{sub}^{sub}ext$

```
\newcommandx{\cmdmthelm}[2][2=]
  {\usrmth{#1}{Elm}{elm}[#2]}
```

`\cmdmthargelm` ... to do!

- `\cmdmthargelm{cmdName}`;
  `\cmdNameElm[sub][sub][ext1]{arg}[ext2]` = $cmdName_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargelm{cmdName}[NewName]`;
  `\cmdNameElm[sub][sub][ext1]{arg}[ext2]` = $NewName_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargelm}[2][2=]
  {\usrmth{#1}{Elm}{argelm}[#2]}
```

`\cmdmthoargelm` ... to do!

- `\cmdmthoargelm{cmdName}`;
  `\cmdNameElm[sub][sub][arg]` = $cmdName_{sub}^{sub}(arg)$
- `\cmdmthoargelm{cmdElm}[NewName]`;
  `\cmdElmElm[sub][sub][arg]` = $NewName_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargelm}[2][2=]
  {\usrmth{#1}{Elm}{oargelm}[#2]}
```

`\cmdmthparelm` ... to do!

- `\cmdmthparelm{cmdName}`;
  `\cmdNameElm[sub][sub][ext1]{par}[ext2]` = $cmdName_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparelm{cmdName}[NewName]`;
  `\cmdNameElm[sub][sub][ext1]{par}[ext2]` = $NewName_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparelm}[2][2=]
  {\usrmth{#1}{Elm}{parelm}[#2]}
```

`\cmdmthoparelm` ... to do!

- `\cmdmthoparelm{cmdName}`;
  `\cmdNameElm[sub][sub][par]` = $cmdName_{sub}^{sub}[par]$
- `\cmdmthoparelm{cmdElm}[NewName]`;
  `\cmdElmElm[sub][sub][par]` = $NewName_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparelm}[2][2=]
  {\usrmth{#1}{Elm}{oparelm}[#2]}
```

```
%%*************************************************************************%%
```

`\cmdmthsymelm` ... to do!

- `\cmdmthsymelm{cmdName}`;
  `\cmdNameSym[sub][sub][ext]` = $\texttt{cmdName}_{sub}^{sub}ext$
  `\cmdNameElm[sub][sub][ext]` = $cmdName_{sub}^{sub}ext$
- `\cmdmthsymelm{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][ext]` = $\texttt{NewName}_{sub}^{sub}ext$
  `\cmdNameElm[sub][sub][ext]` = $NewName_{sub}^{sub}ext$

```
\newcommandx{\cmdmthsymelm}[2][2=]
  {\cmdmthsym{#1}[#2]%
  \cmdmthelm{#1}[#2]}
```

`\cmdmthargsymelm` ... to do!

- `\cmdmthargsymelm{cmdName}`;
  `\cmdNameSym[sub][sub][ext1]{arg}[ext2]` = $\texttt{cmdName}_{sub}^{sub}ext1(arg)ext2$
  `\cmdNameElm[sub][sub][ext1]{arg}[ext2]` = $cmdName_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargsymelm{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][ext1]{arg}[ext2]` = $\texttt{NewName}_{sub}^{sub}ext1(arg)ext2$
  `\cmdNameElm[sub][sub][ext1]{arg}[ext2]` = $NewName_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargsymelm}[2][2=]
  {\cmdmthargsym{#1}[#2]%
  \cmdmthargelm{#1}[#2]}
```

`\cmdmthoargsymelm` ... to do!

- `\cmdmthoargsymelm{cmdName}`;
  `\cmdNameSym[sub][sub][arg]` = $\texttt{cmdName}_{sub}^{sub}(arg)$
  `\cmdNameElm[sub][sub][arg]` = $cmdName_{sub}^{sub}(arg)$
- `\cmdmthoargsymelm{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][arg]` = $\texttt{NewName}_{sub}^{sub}(arg)$
  `\cmdNameElm[sub][sub][arg]` = $NewName_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargsymelm}[2][2=]
  {\cmdmthoargsym{#1}[#2]%
  \cmdmthoargelm{#1}[#2]}
```

`\cmdmthparsymelm` ... to do!

- `\cmdmthparsymelm{cmdName}`;
  `\cmdNameSym[sub][sub][ext1]{par}[ext2]` = $\texttt{cmdName}_{sub}^{sub}ext1[par]ext2$
  `\cmdNameElm[sub][sub][ext1]{par}[ext2]` = $cmdName_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparsymelm{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][ext1]{par}[ext2]` = $\texttt{NewName}_{sub}^{sub}ext1[par]ext2$
  `\cmdNameElm[sub][sub][ext1]{par}[ext2]` = $NewName_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparsymelm}[2][2=]
  {\cmdmthparsym{#1}[#2]%
  \cmdmthparelm{#1}[#2]}
```

`\cmdmthoparsymelm` ... to do!

- `\cmdmthoparsymelm{cmdName}`;
  `\cmdNameSym[sub][sub][par]` = $\texttt{cmdName}_{sub}^{sub}[par]$
  `\cmdNameElm[sub][sub][par]` = $cmdName_{sub}^{sub}[par]$
- `\cmdmthoparsymelm{cmdName}[NewName]`;
  `\cmdNameSym[sub][sub][par]` = $\texttt{NewName}_{sub}^{sub}[par]$
  `\cmdNameElm[sub][sub][par]` = $NewName_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparsymelm}[2][2=]
  {\cmdmthoparsym{#1}[#2]%
  \cmdmthoparelm{#1}[#2]}

%%*************************************************************************%%
```

`\mthluop, ...` ... to do!

- \mthluop{\oplus}[sub][sup][Ext] = $\oplus_{sub}^{sup} Ext$
- \mthlbop{\oplus}[sub][sup][Ext] = $\oplus_{sub}^{sup} Ext$

```
%% Style for \LaTex Operators
\cmdmth{luop}\newcommand{\mthstyluop}[1]{\textstyle\mathop{#1}}
\cmdmth{lbop}\newcommand{\mthstylbop}[1]{\textstyle\mathbin{#1}}
```

\cmdmthluop, ... to do!

- \cmdmthluop{cmdName};
  \cmdNameUOp[sub][sub][ext] = $cmdName_{sub}^{sub} ext$
- \cmdmthluop{cmdName}[\oplus];
  \cmdNameUOp[sub][sub][ext] = $\oplus_{sub}^{sub} ext$
- \cmdmthlbop{cmdName};
  \cmdNameBOp[sub][sub][ext] = $cmdName_{sub}^{sub} ext$
- \cmdmthlbop{cmdName}[\oplus];
  \cmdNameBOp[sub][sub][ext] = $\oplus_{sub}^{sub} ext$

```
\newcommandx{\cmdmthluop}[2][2=]
  {\usrmth{#1}{UOp}{luop}[#2]}
\newcommandx{\cmdmthlbop}[2][2=]
  {\usrmth{#1}{BOp}{lbop}[#2]}
```

\mthlrel ... to do!

- \mthlrel{\preceq}[sub][sup][Ext] = $\preceq_{sub}^{sup} Ext$

```
%% Style for \LaTex Relations
\cmdmth{lrel}\newcommand{\mthstylrel}{\mathrel}
```

\cmdmthlrel ... to do!

- \cmdmthlrel{cmdName};
  \cmdNameRel[sub][sub][ext] = $cmdName_{sub}^{sub} ext$
- \cmdmthlrel{cmdName}[\preceq];
  \cmdNameRel[sub][sub][ext] = $\preceq_{sub}^{sub} ext$

```
\newcommandx{\cmdmthlrel}[2][2=]
  {\usrmth{#1}{Rel}{lrel}[#2]}
```

```
%%*************************************************************************%%
```

\mthsnt, ... to do!

- \mthsnt{Name}[sub][sup][Ext] = $\mathsf{Name}_{sub}^{sup} Ext$
- \mthargsnt{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2] = $\mathsf{Name}_{sub}^{sup} Ext1\left(Arg^{Ex^{Ex}}\right) Ext2$
- \mthargsnt*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2] = $\mathsf{Name}_{sub}^{sup} Ext1(Arg^{Ex^{Ex}}) Ext2$
- \mthparsnt{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2] = $\mathsf{Name}_{sub}^{sup} Ext1\left[Par^{Ex^{Ex}}\right] Ext2$
- \mthparsnt*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2] = $\mathsf{Name}_{sub}^{sup} Ext1[Par^{Ex^{Ex}}] Ext2$

```
%% Style for Sentences
\cmdmthall{snt}\newcommand{\mthstysnt}{\mathsf}
```

\aSnt, ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω
A, B, Γ, Δ, E, E, Z, H, Θ, $\varTheta$, I, K, K, Λ, M, N, Ξ, O, Π, $\varPi$, P, P, Σ, $\varSigma$, T, Υ, Φ, $\varPhi$, X, Ψ, Ω

```
\seqoflet{Snt}{mthsnt}
```

\cmdmthsnt ... to do!

- \cmdmthsnt{cmdName};
  \cmdNameSnt[sub][sub][ext] = $\mathsf{cmdName}_{sub}^{sub} ext$
- \cmdmthsnt{cmdName}[NewName];
  \cmdNameSnt[sub][sub][ext] = $\mathsf{NewName}_{sub}^{sub} ext$

```
\newcommandx{\cmdmthsnt}[2][2=]
  {\usrmth{#1}{Snt}{snt}[#2]}
```

`\cmdmthargsnt` ... to do!

- `\cmdmthargsnt{cmdName}`;
  `\cmdNameSnt[sub][sub][ext1]{arg}[ext2]` = $\mathsf{cmdName}^{sub}_{sub}ext1(arg)ext2$
- `\cmdmthargsnt{cmdName}[NewName]`;
  `\cmdNameSnt[sub][sub][ext1]{arg}[ext2]` = $\mathsf{NewName}^{sub}_{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargsnt}[2][2=]
  {\usrmth{#1}{Snt}{argsnt}[#2]}
```

`\cmdmthoargsnt` ... to do!

- `\cmdmthoargsnt{cmdName}`;
  `\cmdNameSnt[sub][sub][arg]` = $\mathsf{cmdName}^{sub}_{sub}(arg)$
- `\cmdmthoargsnt{cmdName}[NewName]`;
  `\cmdNameSnt[sub][sub][arg]` = $\mathsf{NewName}^{sub}_{sub}(arg)$

```
\newcommandx{\cmdmthoargsnt}[2][2=]
  {\usrmth{#1}{Snt}{oargsnt}[#2]}
```

`\cmdmthparsnt` ... to do!

- `\cmdmthparsnt{cmdName}`;
  `\cmdNameSnt[sub][sub][ext1]{par}[ext2]` = $\mathsf{cmdName}^{sub}_{sub}ext1[par]ext2$
- `\cmdmthparsnt{cmdName}[NewName]`;
  `\cmdNameSnt[sub][sub][ext1]{par}[ext2]` = $\mathsf{NewName}^{sub}_{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparsnt}[2][2=]
  {\usrmth{#1}{Snt}{parsnt}[#2]}
```

`\cmdmthoparsnt` ... to do!

- `\cmdmthoparsnt{cmdName}`;
  `\cmdNameSnt[sub][sub][par]` = $\mathsf{cmdName}^{sub}_{sub}[par]$
- `\cmdmthoparsnt{cmdName}[NewName]`;
  `\cmdNameSnt[sub][sub][par]` = $\mathsf{NewName}^{sub}_{sub}[par]$

```
\newcommandx{\cmdmthoparsnt}[2][2=]
  {\usrmth{#1}{Snt}{oparsnt}[#2]}
```

`\mthfrm, ...` ... to do!

- `\mthfrm{Name}[sub][sup][Ext]` = $Name^{sup}_{sub}Ext$
- `\mthargfrm{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $Name^{sup}_{sub}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
- `\mthargfrm*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $Name^{sup}_{sub}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparfrm{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $Name^{sup}_{sub}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
- `\mthparfrm*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $Name^{sup}_{sub}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Formulae
\cmdmthall{frm}\newcommand{\mthstyfrm}{\mathit}
```

`\aFrm, ...` ... to do!

a, b, c, d, e, f, g, h, i, j, k, l, m, n, o, p, q, r, s, t, u, v, w, x, y, z
A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z
α, β, γ, δ, ϵ, ε, ζ, η, θ, ϑ, ι, κ, $\varkappa$, λ, μ, ν, ξ, o, π, ϖ, ρ, ϱ, σ, ς, τ, υ, ϕ, φ, χ, ψ, ω
A, B, Γ, Δ, E, E, Z, H, Θ, Θ, I, K, K, Λ, M, N, Ξ, O, Π, Π, P, P, Σ, Σ, T, Υ, Φ, Φ, X, Ψ, Ω

```
\seqoflet{Frm}{mthfrm}
```

`\cmdmthfrm` ... to do!

- `\cmdmthfrm{cmdName}`;
  `\cmdNameFrm[sub][sub][ext]` = $cmdName^{sub}_{sub}ext$
- `\cmdmthfrm{cmdName}[NewName]`;
  `\cmdNameFrm[sub][sub][ext]` = $NewName^{sub}_{sub}ext$

```
\newcommandx{\cmdmthfrm}[2][2=]
  {\usrmth{#1}{Frm}{frm}[#2]}
```

`\cmdmthargfrm` ... to do!

- `\cmdmthargfrm{cmdName};`
  `\cmdNameFrm[sub][sub][ext1]{arg}[ext2]` = $cmdName^{sub}_{sub}ext1(arg)ext2$
- `\cmdmthargfrm{cmdName}[NewName];`
  `\cmdNameFrm[sub][sub][ext1]{arg}[ext2]` = $NewName^{sub}_{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargfrm}[2][2=]
  {\usrmth{#1}{Frm}{argfrm}[#2]}
```

`\cmdmthoargfrm` ... to do!

- `\cmdmthoargfrm{cmdName};`
  `\cmdNameFrm[sub][sub][arg]` = $cmdName^{sub}_{sub}(arg)$
- `\cmdmthoargfrm{cmdName}[NewName];`
  `\cmdNameFrm[sub][sub][arg]` = $NewName^{sub}_{sub}(arg)$

```
\newcommandx{\cmdmthoargfrm}[2][2=]
  {\usrmth{#1}{Frm}{oargfrm}[#2]}
```

`\cmdmthparfrm` ... to do!

- `\cmdmthparfrm{cmdName};`
  `\cmdNameFrm[sub][sub][ext1]{par}[ext2]` = $cmdName^{sub}_{sub}ext1[par]ext2$
- `\cmdmthparfrm{cmdName}[NewName];`
  `\cmdNameFrm[sub][sub][ext1]{par}[ext2]` = $NewName^{sub}_{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparfrm}[2][2=]
  {\usrmth{#1}{Frm}{parfrm}[#2]}
```

`\cmdmthoparfrm` ... to do!

- `\cmdmthoparfrm{cmdName};`
  `\cmdNameFrm[sub][sub][par]` = $cmdName^{sub}_{sub}[par]$
- `\cmdmthoparfrm{cmdName}[NewName];`
  `\cmdNameFrm[sub][sub][par]` = $NewName^{sub}_{sub}[par]$

```
\newcommandx{\cmdmthoparfrm}[2][2=]
  {\usrmth{#1}{Frm}{oparfrm}[#2]}
```

```
%%*************************************************************************%%
```

`\mthmat, ...` ... to do!

- `\mthmat{Name}[sub][sup][Ext]` = $\mathbf{Name}^{sup}_{sub}Ext$
- `\mthargmat{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathbf{Name}^{sup}_{sub}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
- `\mthargmat*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\mathbf{Name}^{sup}_{sub}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparmat{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathbf{Name}^{sup}_{sub}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
- `\mthparmat*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\mathbf{Name}^{sup}_{sub}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Matrices
\cmdmthall{mat}\newcommand{\mthstymat}[1]{\boldsymbol{\mathsf{#1}}}
```

`\aMat, ...` ... to do!

$\mathbf{a}$, $\mathbf{b}$, $\mathbf{c}$, $\mathbf{d}$, $\mathbf{e}$, $\mathbf{f}$, $\mathbf{g}$, $\mathbf{h}$, $\mathbf{i}$, $\mathbf{j}$, $\mathbf{k}$, $\mathbf{l}$, $\mathbf{m}$, $\mathbf{n}$, $\mathbf{o}$, $\mathbf{p}$, $\mathbf{q}$, $\mathbf{r}$, $\mathbf{s}$, $\mathbf{t}$, $\mathbf{u}$, $\mathbf{v}$, $\mathbf{w}$, $\mathbf{x}$, $\mathbf{y}$, $\mathbf{z}$
$\mathbf{A}$, $\mathbf{B}$, $\mathbf{C}$, $\mathbf{D}$, $\mathbf{E}$, $\mathbf{F}$, $\mathbf{G}$, $\mathbf{H}$, $\mathbf{I}$, $\mathbf{J}$, $\mathbf{K}$, $\mathbf{L}$, $\mathbf{M}$, $\mathbf{N}$, $\mathbf{O}$, $\mathbf{P}$, $\mathbf{Q}$, $\mathbf{R}$, $\mathbf{S}$, $\mathbf{T}$, $\mathbf{U}$, $\mathbf{V}$, $\mathbf{W}$, $\mathbf{X}$, $\mathbf{Y}$, $\mathbf{Z}$
$\boldsymbol{\alpha}$, $\boldsymbol{\beta}$, $\boldsymbol{\gamma}$, $\boldsymbol{\delta}$, $\boldsymbol{\epsilon}$, $\boldsymbol{\varepsilon}$, $\boldsymbol{\zeta}$, $\boldsymbol{\eta}$, $\boldsymbol{\theta}$, $\boldsymbol{\vartheta}$, $\boldsymbol{\iota}$, $\boldsymbol{\kappa}$, $\boldsymbol{\varkappa}$, $\boldsymbol{\lambda}$, $\boldsymbol{\mu}$, $\boldsymbol{\nu}$, $\boldsymbol{\xi}$, $\mathbf{o}$, $\boldsymbol{\pi}$, $\boldsymbol{\varpi}$, $\boldsymbol{\rho}$, $\boldsymbol{\varrho}$, $\boldsymbol{\sigma}$, $\boldsymbol{\varsigma}$, $\boldsymbol{\tau}$, $\boldsymbol{\upsilon}$, $\boldsymbol{\phi}$, $\boldsymbol{\varphi}$, $\boldsymbol{\chi}$, $\boldsymbol{\psi}$, $\boldsymbol{\omega}$
$\mathbf{A}$, $\mathbf{B}$, $\boldsymbol{\Gamma}$, $\boldsymbol{\Delta}$, $\mathbf{E}$, $\mathbf{E}$, $\mathbf{Z}$, $\mathbf{H}$, $\boldsymbol{\Theta}$, $\boldsymbol{\varTheta}$, $\mathbf{I}$, $\mathbf{K}$, $\mathbf{K}$, $\boldsymbol{\Lambda}$, $\mathbf{M}$, $\mathbf{N}$, $\boldsymbol{\Xi}$, $\mathbf{O}$, $\boldsymbol{\Pi}$, $\boldsymbol{\varPi}$, $\mathbf{P}$, $\mathbf{P}$, $\boldsymbol{\Sigma}$, $\boldsymbol{\varSigma}$, $\mathbf{T}$, $\boldsymbol{\Upsilon}$, $\boldsymbol{\Phi}$, $\boldsymbol{\varPhi}$, $\mathbf{X}$, $\boldsymbol{\Psi}$, $\boldsymbol{\Omega}$

```
\seqoflet{Mat}{mthmat}
```

`\cmdmthmat` ... to do!

- `\cmdmthmat{cmdName};`
  `\cmdNameMat[sub][sub][ext]` = $\mathbf{cmdName}^{sub}_{sub}ext$

- `\cmdmthmat{cmdName}[NewName]`;
  `\cmdNameMat[sub][sub][ext]` = $\mathsf{NewName}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthmat}[2][2=]
  {\usrmth{#1}{Mat}{mat}[#2]}
```

`\cmdmthargmat` ... to do!

- `\cmdmthargmat{cmdName}`;
  `\cmdNameMat[sub][sub][ext1]{arg}[ext2]` = $\mathsf{cmdName}_{sub}^{sub}ext1(arg)ext2$
- `\cmdmthargmat{cmdName}[NewName]`;
  `\cmdNameMat[sub][sub][ext1]{arg}[ext2]` = $\mathsf{NewName}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargmat}[2][2=]
  {\usrmth{#1}{Mat}{argmat}[#2]}
```

`\cmdmthoargmat` ... to do!

- `\cmdmthoargmat{cmdName}`;
  `\cmdNameMat[sub][sub][arg]` = $\mathsf{cmdName}_{sub}^{sub}(arg)$
- `\cmdmthoargmat{cmdName}[NewName]`;
  `\cmdNameMat[sub][sub][arg]` = $\mathsf{NewName}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargmat}[2][2=]
  {\usrmth{#1}{Mat}{oargmat}[#2]}
```

`\cmdmthparmat` ... to do!

- `\cmdmthparmat{cmdName}`;
  `\cmdNameMat[sub][sub][ext1]{par}[ext2]` = $\mathsf{cmdName}_{sub}^{sub}ext1[par]ext2$
- `\cmdmthparmat{cmdName}[NewName]`;
  `\cmdNameMat[sub][sub][ext1]{par}[ext2]` = $\mathsf{NewName}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparmat}[2][2=]
  {\usrmth{#1}{Mat}{parmat}[#2]}
```

`\cmdmthoparmat` ... to do!

- `\cmdmthoparmat{cmdName}`;
  `\cmdNameMat[sub][sub][par]` = $\mathsf{cmdName}_{sub}^{sub}[par]$
- `\cmdmthoparmat{cmdName}[NewName]`;
  `\cmdNameMat[sub][sub][par]` = $\mathsf{NewName}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparmat}[2][2=]
  {\usrmth{#1}{Mat}{oparmat}[#2]}
```

`\mthvec, ...` ... to do!

- `\mthvec{Name}[sub][sup][Ext]` = $\boldsymbol{Name}_{sub}^{sup}Ext$
- `\mthargvec{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\boldsymbol{Name}_{sub}^{sup}Ext1\left(Arg^{Ex^{Ex}}\right)Ext2$
- `\mthargvec*{Name}[sub][sup][Ext1]{Arg^{Ex^{Ex}}}[Ext2]` = $\boldsymbol{Name}_{sub}^{sup}Ext1(Arg^{Ex^{Ex}})Ext2$
- `\mthparvec{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\boldsymbol{Name}_{sub}^{sup}Ext1\left[Par^{Ex^{Ex}}\right]Ext2$
- `\mthparvec*{Name}[sub][sup][Ext1]{Par^{Ex^{Ex}}}[Ext2]` = $\boldsymbol{Name}_{sub}^{sup}Ext1[Par^{Ex^{Ex}}]Ext2$

```
%% Style for Vectors
\cmdmthall{vec}\newcommand{\mthstyvec}[1]{\boldsymbol{\mathit{#1}}}
```

`\aVec, ...` ... to do!

$\boldsymbol{a}$, $\boldsymbol{b}$, $\boldsymbol{c}$, $\boldsymbol{d}$, $\boldsymbol{e}$, $\boldsymbol{f}$, $\boldsymbol{g}$, $\boldsymbol{h}$, $\boldsymbol{i}$, $\boldsymbol{j}$, $\boldsymbol{k}$, $\boldsymbol{l}$, $\boldsymbol{m}$, $\boldsymbol{n}$, $\boldsymbol{o}$, $\boldsymbol{p}$, $\boldsymbol{q}$, $\boldsymbol{r}$, $\boldsymbol{s}$, $\boldsymbol{t}$, $\boldsymbol{u}$, $\boldsymbol{v}$, $\boldsymbol{w}$, $\boldsymbol{x}$, $\boldsymbol{y}$, $\boldsymbol{z}$
$\boldsymbol{A}$, $\boldsymbol{B}$, $\boldsymbol{C}$, $\boldsymbol{D}$, $\boldsymbol{E}$, $\boldsymbol{F}$, $\boldsymbol{G}$, $\boldsymbol{H}$, $\boldsymbol{I}$, $\boldsymbol{J}$, $\boldsymbol{K}$, $\boldsymbol{L}$, $\boldsymbol{M}$, $\boldsymbol{N}$, $\boldsymbol{O}$, $\boldsymbol{P}$, $\boldsymbol{Q}$, $\boldsymbol{R}$, $\boldsymbol{S}$, $\boldsymbol{T}$, $\boldsymbol{U}$, $\boldsymbol{V}$, $\boldsymbol{W}$, $\boldsymbol{X}$, $\boldsymbol{Y}$, $\boldsymbol{Z}$
$\boldsymbol{\alpha}$, $\boldsymbol{\beta}$, $\boldsymbol{\gamma}$, $\boldsymbol{\delta}$, $\boldsymbol{\epsilon}$, $\boldsymbol{\varepsilon}$, $\boldsymbol{\zeta}$, $\boldsymbol{\eta}$, $\boldsymbol{\theta}$, $\boldsymbol{\vartheta}$, $\boldsymbol{\iota}$, $\boldsymbol{\kappa}$, $\boldsymbol{\varkappa}$, $\boldsymbol{\lambda}$, $\boldsymbol{\mu}$, $\boldsymbol{\nu}$, $\boldsymbol{\xi}$, $\boldsymbol{o}$, $\boldsymbol{\pi}$, $\boldsymbol{\varpi}$, $\boldsymbol{\rho}$, $\boldsymbol{\varrho}$, $\boldsymbol{\sigma}$, $\boldsymbol{\varsigma}$, $\boldsymbol{\tau}$, $\boldsymbol{\upsilon}$, $\boldsymbol{\phi}$, $\boldsymbol{\varphi}$, $\boldsymbol{\chi}$, $\boldsymbol{\psi}$, $\boldsymbol{\omega}$
$\boldsymbol{A}$, $\boldsymbol{B}$, $\boldsymbol{\Gamma}$, $\boldsymbol{\Delta}$, $\boldsymbol{E}$, $\boldsymbol{E}$, $\boldsymbol{Z}$, $\boldsymbol{H}$, $\boldsymbol{\Theta}$, $\boldsymbol{\Theta}$, $\boldsymbol{I}$, $\boldsymbol{K}$, $\boldsymbol{K}$, $\boldsymbol{\Lambda}$, $\boldsymbol{M}$, $\boldsymbol{N}$, $\boldsymbol{\Xi}$, $\boldsymbol{O}$, $\boldsymbol{\Pi}$, $\boldsymbol{\Pi}$, $\boldsymbol{P}$, $\boldsymbol{P}$, $\boldsymbol{\Sigma}$, $\boldsymbol{\Sigma}$, $\boldsymbol{T}$, $\boldsymbol{\Upsilon}$, $\boldsymbol{\Phi}$, $\boldsymbol{\Phi}$, $\boldsymbol{X}$, $\boldsymbol{\Psi}$, $\boldsymbol{\Omega}$

```
\seqoflet{Vec}{mthvec}
```

`\cmdmthvec` ... to do!

- `\cmdmthvec{cmdName}`;
  `\cmdNameVec[sub][sub][ext]` = $\boldsymbol{cmdName}_{sub}^{sub}ext$

- \cmdmthvec{cmdName}[NewName];
  \cmdNameVec[sub][sub][ext] = $\boldsymbol{NewName}_{sub}^{sub}ext$

```
\newcommandx{\cmdmthvec}[2][2=]
  {\usrmth{#1}{Vec}{vec}[#2]}
```

\cmdmthargvec ... to do!

- \cmdmthargvec{cmdName};
  \cmdNameVec[sub][sub][ext1]{arg}[ext2] = $\boldsymbol{cmdName}_{sub}^{sub}ext1(arg)ext2$
- \cmdmthargvec{cmdName}[NewName];
  \cmdNameVec[sub][sub][ext1]{arg}[ext2] = $\boldsymbol{NewName}_{sub}^{sub}ext1(arg)ext2$

```
\newcommandx{\cmdmthargvec}[2][2=]
  {\usrmth{#1}{Vec}{argvec}[#2]}
```

\cmdmthoargvec ... to do!

- \cmdmthoargvec{cmdName};
  \cmdNameVec[sub][sub][arg] = $\boldsymbol{cmdName}_{sub}^{sub}(arg)$
- \cmdmthoargvec{cmdName}[NewName];
  \cmdNameVec[sub][sub][arg] = $\boldsymbol{NewName}_{sub}^{sub}(arg)$

```
\newcommandx{\cmdmthoargvec}[2][2=]
  {\usrmth{#1}{Vec}{oargvec}[#2]}
```

\cmdmthparvec ... to do!

- \cmdmthparvec{cmdName};
  \cmdNameVec[sub][sub][ext1]{par}[ext2] = $\boldsymbol{cmdName}_{sub}^{sub}ext1[par]ext2$
- \cmdmthparvec{cmdName}[NewName];
  \cmdNameVec[sub][sub][ext1]{par}[ext2] = $\boldsymbol{NewName}_{sub}^{sub}ext1[par]ext2$

```
\newcommandx{\cmdmthparvec}[2][2=]
  {\usrmth{#1}{Vec}{parvec}[#2]}
```

\cmdmthoparvec ... to do!

- \cmdmthoparvec{cmdName};
  \cmdNameVec[sub][sub][par] = $\boldsymbol{cmdName}_{sub}^{sub}[par]$
- \cmdmthoparvec{cmdName}[NewName];
  \cmdNameVec[sub][sub][par] = $\boldsymbol{NewName}_{sub}^{sub}[par]$

```
\newcommandx{\cmdmthoparvec}[2][2=]
  {\usrmth{#1}{Vec}{oparvec}[#2]}
```

```
\fi
%%***************************************************************************%%
```

```
%%***************************************************************************%%
%%** Elementary Macros for Text *********************************************%%
%%***************************************************************************%%
\iftext@
```

```
%%** Latin Abbreviations ****************************************************%%
```

\adhoc

- \adhoc = *ad hoc*

```
\cmdtxtabr{adhoc}[ad hoc]
```

\afortiori

- \afortiori = *a fortiori*

```
\cmdtxtabr{afortiori}[a fortiori]
```

\apriori

- \apriori = *a priori*

```
\cmdtxtabr{apriori}[a priori]
```

\aposteriori

- \aposteriori = *a posteriori*

```
\cmdtxtabr{aposteriori}[a posteriori]
```

\cf

- \cf = *cf.*

```
\cmdtxtabr{cf}[cf.]
```

\dedicto • \dedicto = *de dicto*

```
748 \cmdtxtabr{dedicto}[de dicto]
```

\defacto • \defacto = *de facto*

```
749 \cmdtxtabr{defacto}[de facto]
```

\dere • \dere = *de re*

```
750 \cmdtxtabr{dere}[de re]
```

\divideetimpera • \divideetimpera = *divide et impera*

```
751 \cmdtxtabr{divideetimpera}[divide et impera]
```

\eg • \eg = *e.g.*

```
752 \cmdtxtabr{eg}[e.g.]
```

\ergo • \ergo = *ergo*

```
753 \cmdtxtabr{ergo}
```

\errata • \errata = *errata*

```
754 \cmdtxtabr{errata}
```

\erratum • \erratum = *erratum*

```
755 \cmdtxtabr{erratum}
```

\etal • \etal = *et al.*

```
756 \cmdtxtabr{etal}[et al.]
```

\etc • \etc = *etc.*

```
757 \cmdtxtabr{etc}[etc.]
```

\ie • \ie = *i.e.*

```
758 \cmdtxtabr{ie}[i.e.]
```

\mutatismutandis • \mutatismutandis = *mutatis mutandis*

```
759 \cmdtxtabr{mutatismutandis}[mutatis mutandis]
```

\percontra • \percontra = *per contra*

```
760 \cmdtxtabr{percontra}[per contra]
```

\primafacie • \primafacie = *prima facie*

```
761 \cmdtxtabr{primafacie}[prima facie]
```

\viceversa • \viceversa = *vice versa*

```
762 \cmdtxtabr{viceversa}[vice versa]
```

\vs • \vs = *vs.*

```
763 \cmdtxtabr{vs}[vs.]
```

\viz • \viz = *viz.*

```
764 \cmdtxtabr{viz}[viz.]
```

```
765 %%*****************************************************************************%%
```

\Afortiori • \Afortiori = *A fortiori*

```
766 \cmdtxtabr{Afortiori}[A fortiori]
```

\Apriori • \Apriori = *A priori*

```
767 \cmdtxtabr{Apriori}[A priori]
```

\Aposteriori • \Aposteriori = *A posteriori*

```
\cmdtxtabr{Aposteriori}[A posteriori]
```

\Dedicto • \Dedicto = *De dicto*

```
\cmdtxtabr{Dedicto}[De dicto]
```

\Defacto • \Defacto = *De facto*

```
\cmdtxtabr{Defacto}[De facto]
```

\Dere • \Dere = *De re*

```
\cmdtxtabr{Dere}[De re]
```

\Divideetimpera • \Divideetimpera = *Divide et impera*

```
\cmdtxtabr{Divideetimpera}[Divide et impera]
```

\Eg • \Eg = *E.g.*

```
\cmdtxtabr{Eg}[E.g.]
```

\Errata • \Errata = *Errata*

```
\cmdtxtabr{Errata}
```

\Erratum • \Erratum = *Erratum*

```
\cmdtxtabr{Erratum}
```

\Mutatismutandis • \Mutatismutandis = *Mutatis mutandis*

```
\cmdtxtabr{Mutatismutandis}[Mutatis mutandis]
```

\Percontra • \Percontra = *Per contra*

```
\cmdtxtabr{Percontra}[Per contra]
```

\Primafacie • \Primafacie = *Prima facie*

```
\cmdtxtabr{Primafacie}[Prima facie]
```

\Viceversa • \Viceversa = *Vice versa*

```
\cmdtxtabr{Viceversa}[Vice versa]
```

```
%%** Italian Abbreviations ************************************************%%
```

...

```
%%*************************************************************************%%
```

...

```
%%** French Abbreviations **************************************************%%
```

\naif • \naif = *naïf*

```
\cmdtxtabr{naif}[na\"{i}f]
```

\naive • \naive = *naïve*

```
\cmdtxtabr{naive}[na\"{i}ve]
```

\role • \role = *rôle*

```
\cmdtxtabr{role}[r\^{o}le]
```

```
%%*************************************************************************%%
```

\Role • \Role = *Rôle*

```
\cmdtxtabr{Role}[R\^{o}le]
```

```
%%** English Abbreviations *************************************************%%
```

\aka • \aka = *a.k.a.*

```
\cmdtxtabr{aka}[a.k.a.]
```

\contd • \contd = *contd.*

```
\cmdtxtabr{contd}[contd.]
```

\iff • \iff = *iff*

```
\cmdtxtabr{iff}
```

\iht • \iht = *i.h.t.*

```
\cmdtxtabr{iht}[i.h.t.]
```

\stx • \stx = *s.t.*

```
\cmdtxtabr{stx}[s.t.]
```

\resp • \resp = *resp.*

```
\cmdtxtabr{resp}[resp.]
```

\wrt • \wrt = *w.r.t.*

```
\cmdtxtabr{wrt}[w.r.t.]
```

\wlogx • \wlogx = *w.l.o.g.*

```
\cmdtxtabr{wlogx}[w.l.o.g.]

%%*************************************************************************%%
```

\Contd • \Contd = *Contd.*

```
\cmdtxtabr{Contd}[Contd.]
```

\Wlogx • \Wlogx = *W.l.o.g.*

```
\cmdtxtabr{Wlogx}[W.l.o.g.]

\fi
%%*************************************************************************%%
%%*************************************************************************%%
%%** Elementary Macros for Math *******************************************%%
%%*************************************************************************%%
\ifmath@
%%** General Notation *****************************************************%%
```

\defeq, \seteq ...

```
\DeclareRobustCommand{\defeq}
  {\@ifstar%
    {\mthlbop{\stackrel{\text{\textup{def}}}{=}}%
    {\mthlbop{\triangleq}}}
\DeclareRobustCommand{\seteq}
  {\@ifstar{\mthlbop{:=}}{\mthlbop{:=}}}

%%*************************************************************************%%
```

\implies, ...

```
\DeclareRobustCommand{\implies}
  {\mthlrel{\Rightarrow}}
\DeclareRobustCommand{\notimplies}
  {\mthlrel{\not\Rightarrow}}
```

\implied, ...

```
\DeclareRobustCommand{\implied}
  {\mthlrel{\Leftarrow}}
\DeclareRobustCommand{\notimplied}
  {\mthlrel{\not\Leftarrow}}
```

```
\coimplies, ...  ...
                 \DeclareRobustCommand{\coimplies}
                   {\mthlrel{\Leftrightarrow}}
                 \DeclareRobustCommand{\notcoimplies}
                   {\mthlrel{\not\!\Leftrightarrow}}

                 %%*************************************************************************%%

  \cmodels, ...  ...
                 \DeclareRobustCommand{\cmodels}
                   {\mthlrel{\models}}
                 \DeclareRobustCommand{\notcmodels}
                   {\mthlrel{\not\models}}

   \cequiv, ...  ...
                 \DeclareRobustCommand{\cequiv}
                   {\mthlrel{\equiv}}
                 \DeclareRobustCommand{\notcequiv}
                   {\mthlrel{\not\equiv}}

                 %%*************************************************************************%%

        \denot   ...
                 \DeclareRobustCommand{\denot}
                   {\@ifstar{\@denot}{\@denot[\left][\right]}}
                 \DeclareRobustCommandx{\@denot}[3][1=, 2=]
                   {\mth{\argmid{#1\llbracket}{#3}{#2\rrbracket}}}

                 %%*************************************************************************%%

\dual, \adj, ...  ...
                 \DeclareRobustCommand{\dual}[1]
                   {\mth{\overline{#1}}}
                 \DeclareRobustCommand{\adj}[1]
                   {\mth{\mathring{#1}}}
                 \DeclareRobustCommand{\der}[1]
                   {\mth{\widehat{#1}}}
                 \DeclareRobustCommand{\trn}[1]
                   {\mth{\widetilde{#1}}}

          \vec   ...
                 \DeclareRobustCommand{\vec}
                   {\@ifstar{\@svec}{\@vec}}
                 \DeclareRobustCommand{\@vec}[1]
                   {\mth{\mathaccent"017E{#1}}}
                 \DeclareRobustCommand{\@svec}[1]
                   {\mth{\overline{#1}}}

                 %%*************************************************************************%%

\enumeration, ...  ...
                 \varcmd{enumeration}{\mth}{}{,}{}{}
                 \varcmd{enumerationx}{\mth}{}{;}{}{}

  \sequence, ...  ...
                 \varcmd{sequence}{\mth}{\left[}{,}{\right]}{}
                 \varcmd{sequencel}{\mth}{\left[}{,}{\right.}{}
                 \varcmd{sequencer}{\mth}{\left.}{,}{\right]}{}
                 \varcmd{sequencex}{\mth}{\left[}{;}{\right]}{}
                 \varcmd{sequencexl}{\mth}{\left[}{;}{\right.}{}
                 \varcmd{sequencexr}{\mth}{\left.}{;}{\right]}{}
```

```
\tuple, ...  ...
```
```
\varcmd{tuple}{\mth}{\left\langle}{,}{\right\rangle}{}
\varcmd{tuplel}{\mth}{\left\langle}{,}{\right.}{}
\varcmd{tupler}{\mth}{\left.}{,}{\right\rangle}{}
\varcmd{tuplex}{\mth}{\left\langle}{;}{\right\rangle}{}
\varcmd{tuplexl}{\mth}{\left\langle}{;}{\right.}{}
\varcmd{tuplexr}{\mth}{\left.}{;}{\right\rangle}{}
```
```
%%** Sets ********************************************************************%%
```
```
  \set, ...  ...
```
```
\DeclareRobustCommand{\set}
  {\@ifstar{\@set}{\@set[\left][\middle][\right]}}
\DeclareRobustCommandx{\@set}[5][1=, 2=, 3=]
  {\mth{\argmid{#1\lbrace}{\argsep{#4}{\,#2\vert\,}{#5}}{#3\rbrace}}}
\DeclareRobustCommand{\setl}
  {\@ifstar{\@setl}{\@setl[\left][\right]}}
\DeclareRobustCommandx{\@setl}[3][1=, 2=]
  {\mth{\argmid{#1\lbrace}{#3}{\,#2\vert\!}}}
\DeclareRobustCommand{\setr}
  {\@ifstar{\@setr}{\@setr[\left.][\right]}}
\DeclareRobustCommandx{\@setr}[3][1=, 2=]
  {\mth{\argmid{#1}{#3}{#2\rbrace}}}
```
```
    \card  ...
```
```
\DeclareRobustCommand{\card}
  {\@ifstar{\@card}{\@card[\left][\right]}}
\DeclareRobustCommandx{\@card}[3][1=, 2=]
  {\mth{\argmid{#1\lvert}{#3}{#2\rvert}}}
```
```
     \pow  ...
```
```
\DeclareRobustCommand{\pow}[1]
  {\mth{2^{\defval{#1}{\cdot}}}}
```
```
%%** Relations ****************************************************************%%
```
```
  \emptyrel  ...
```
```
\DeclareRobustCommand{\emptyrel}
  {\mth{\varnothing}}
```
```
%%****************************************************************************%%
```
```
\dom, \cod, ...  ...
```
```
\usrmth{dom}{}{argfun}
\usrmth{cod}{}{argfun}
\usrmth{rng}{}{argfun}
\usrmth{img}{}{argfun}
```
```
%%****************************************************************************%%
```
```
     \prj  ...
```
```
\DeclareRobustCommand{\prj}
  {\mthargfun{prj}}
```
```
     \rst  ...
```
```
\DeclareRobustCommand{\rst}
  {\mthlbop{\upharpoonright}}
```
```
     \cmp  ...
```
```
\DeclareRobustCommand{\cmp}
  {\mthlbop{\circ}}
```
```
%%** Functions ****************************************************************%%
```

\emptyfun …

```
\DeclareRobustCommand{\emptyfun}
  {\mth{\varnothing}}
```

```
%%**************************************************************************%%
```

\pto, \pmapsto …

```
\DeclareMathOperator{\pto}
  {\ensuremath{\rightharpoonup}}
\DeclareMathOperator{\pmapsto}
  {\ensuremath{\mathrel{\raisebox{0.5ex}{\footnotesize${\llcorner}$}%
    \kern-1.5ex\rightharpoonup}}}
```

```
%%**************************************************************************%%
```

\fix, \ifp, ... …

```
\usrmth{fix}{}{fun}
\usrmth{ifp}{}{fun}
\usrmth{lfp}{}{fun}
\usrmth{gfp}{}{fun}
```

```
%%**************************************************************************%%
```

\Aomega, \AOmega …

```
\usrmth{Aomega}{}{argset}[\omega]
\usrmth{AOmega}{}{argset}[\Omega]
```

\Atheta, \ATheta …

```
\usrmth{Atheta}{}{argset}[\theta]
\usrmth{ATheta}{}{argset}[\Theta]
```

\Aomicron, ... …

```
\usrmth{Aomicron}{}{argset}[\omicron]
\usrmth{AOmicron}{}{argset}[\Omicron]
```

```
%%** Numbers ***************************************************************%%
```

\SetB …

```
\DeclareRobustCommand{\SetB}
  {\mthset[mathbb]{B}}
```

\SetF …

```
\DeclareRobustCommand{\SetF}
  {\mthset[mathbb]{F}}
```

\SetN, ... …

```
\DeclareRobustCommand{\SetN}
  {\mthset[mathbb]{N}}
\DeclareRobustCommand{\SetNI}[1][]
  {\SetN[\infty #1]}
```

\SetZ, ... …

```
\DeclareRobustCommand{\SetZ}
  {\mthset[mathbb]{Z}}
\DeclareRobustCommand{\SetZI}[1][]
  {\SetZ[\pm\infty #1]}
\DeclareRobustCommand{\SetZPI}[1][]
  {\SetZ[+\infty #1]}
\DeclareRobustCommand{\SetZNI}[1][]
  {\SetZ[-\infty #1]}
```

```
\SetQ, ...  ...
```
```
\DeclareRobustCommand{\SetQ}
  {\mthset[mathbb]{Q}}
\DeclareRobustCommand{\SetQI}[1][]
  {\SetQ[\pm\infty #1]}
\DeclareRobustCommand{\SetQPI}[1][]
  {\SetQ[+\infty #1]}
\DeclareRobustCommand{\SetQNI}[1][]
  {\SetQ[-\infty #1]}
```
```
\SetR, ...  ...
```
```
\DeclareRobustCommand{\SetR}
  {\mthset[mathbb]{R}}
\DeclareRobustCommand{\SetRI}[1][]
  {\SetR[\pm\infty #1]}
\DeclareRobustCommand{\SetRPI}[1][]
  {\SetR[+\infty #1]}
\DeclareRobustCommand{\SetRNI}[1][]
  {\SetR[-\infty #1]}
```
```
\SetC, ...  ...
```
```
\DeclareRobustCommand{\SetC}
  {\mthset[mathbb]{C}}
\DeclareRobustCommand{\SetCI}[1][]
  {\SetC[\infty #1]}
```
```
%%*****************************************************************************%%
```
```
 \num, ...  ...
```
```
\DeclareRobustCommand{\num}[1]
  {\mth{[#1]}}
\DeclareRobustCommand{\numcc}[2]
  {\mth{[\argsep{#1}{,}{#2}]}}
\DeclareRobustCommand{\numco}[2]
  {\mth{[\argsep{#1}{,}{#2})}}
\DeclareRobustCommand{\numoc}[2]
  {\mth{(\argsep{#1}{,}{#2}]}}
\DeclareRobustCommand{\numoo}[2]
  {\mth{(\argsep{#1}{,}{#2})}}
```
```
%%*****************************************************************************%%
```
```
      \abs  ...
```
```
\DeclareRobustCommand{\abs}
  {\@ifstar{\@abs}{\@abs[\left][\right]}}
\DeclareRobustCommandx{\@abs}[3][1=, 2=]
  {\mth{\argmid{#1\lvert}{#3}{#2\rvert}}}
```
```
\floor, \ceil  ...
```
```
\DeclareRobustCommand{\floor}
  {\@ifstar{\@floor}{\@floor[\left][\right]}}
\DeclareRobustCommandx{\@floor}[3][1=, 2=]
  {\mth{\argmid{#1\lfloor}{#3}{#2\rfloor}}}
\DeclareRobustCommand{\ceil}
  {\@ifstar{\@ceil}{\@ceil[\left][\right]}}
\DeclareRobustCommandx{\@ceil}[3][1=, 2=]
  {\mth{\argmid{#1\lceil}{#3}{#2\rceil}}}
```
```
%%*****************************************************************************%%
```
```
      \arg  ...
```
```
\usrmth{arg}{}{fun}
```

`\evn, \odd` ...

```
\usrmth{evn}{}{fun}
\usrmth{odd}{}{fun}
```

`\bst, ...` ...

```
\usrmth{bst}{}{fun}
\usrmth{argbst}{}{fun}[arg\,bst]
```

`\min, \max, ...` ...

```
\usrmth{min}{}{fun}
\usrmth{max}{}{fun}
\usrmth{argmin}{}{fun}[arg\,min]
\usrmth{argmax}{}{fun}[arg\,max]
```

`\inf, \sup` ...

```
\usrmth{inf}{}{fun}
\usrmth{sup}{}{fun}
```

```
%%** Sequences ********************************************************************%%
```

`\emptyseq` ...

```
\DeclareRobustCommand{\emptyseq}
  {\mth{\varepsilon}}
```

`\len` ...

```
\DeclareRobustCommand{\len}
  {\@ifstar{\@len}{\@len[\left][\right]}}
\DeclareRobustCommandx{\@len}[3][1=, 2=]
  {\mth{\argmid{#1\lvert}{#3}{#2\rvert}}}
```

`\fst, \lst` ...

```
\usrmth{fst}{}{argfun}
\usrmth{lst}{}{argfun}
```

```
\fi
%%*****************************************************************************%%
%%*****************************************************************************%%
%%** Macros for Computational-Complexity Classes ****************************%%
%%*****************************************************************************%%
\ifcom@
```

`\defcomcls` ... to do!

- `\defcomcls{CompClass}`;

  `\CompClass[sub][sup][arg]` = $\textsc{CompClass}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$

- `\defcomcls{CompClass}[NewClass]`;

  `\CompClass[sub][sup][arg]` = $\textsc{NewClass}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$

```
\newcommandx{\defcomcls}[2][2=]
  {\csdef{#1}{\txtoargcom{\defval{#2}{#1}}}}
```

`\defcomclsgrp` ... to do!

- `\defcomclsgrp{CompClass}`;

  `\CompClass[sub][sup][arg]` = $\textsc{CompClass}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$
  `\CoCompClass[sub][sup][arg]` = $\textsc{CoCompClass}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$
  `\CompClassE[sub][sup][arg]` = $\textsc{CompClass-easy}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$
  `\CoCompClassE[sub][sup][arg]` = $\textsc{CoCompClass-easy}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$
  `\CompClassH[sub][sup][arg]` = $\textsc{CompClass-hard}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$
  `\CoCompClassH[sub][sup][arg]` = $\textsc{CoCompClass-hard}_{\text{SUB}}^{\text{SUP}}(\text{ARG})$

`\CompClassC[sub][sup][arg]` = $\textsc{CompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoCompClassC[sub][sup][arg]` = $\textsc{CoCompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

`\DCompClass[sub][sup][arg]` = $\textsc{DCompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClass[sub][sup][arg]` = $\textsc{CoDCompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\DCompClassE[sub][sup][arg]` = $\textsc{DCompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClassE[sub][sup][arg]` = $\textsc{CoDCompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\DCompClassH[sub][sup][arg]` = $\textsc{DCompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClassH[sub][sup][arg]` = $\textsc{CoDCompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\DCompClassC[sub][sup][arg]` = $\textsc{DCompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClassC[sub][sup][arg]` = $\textsc{CoDCompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

`\NCompClass[sub][sup][arg]` = $\textsc{NCompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoNCompClass[sub][sup][arg]` = $\textsc{CoNCompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\NCompClassE[sub][sup][arg]` = $\textsc{NCompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoNCompClassE[sub][sup][arg]` = $\textsc{CoNCompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\NCompClassH[sub][sup][arg]` = $\textsc{NCompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoNCompClassH[sub][sup][arg]` = $\textsc{CoNCompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\NCompClassC[sub][sup][arg]` = $\textsc{NCompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoNCompClassC[sub][sup][arg]` = $\textsc{CoNCompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

`\UCompClass[sub][sup][arg]` = $\textsc{UCompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoUCompClass[sub][sup][arg]` = $\textsc{CoUCompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\UCompClassE[sub][sup][arg]` = $\textsc{UCompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoUCompClassE[sub][sup][arg]` = $\textsc{CoUCompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\UCompClassH[sub][sup][arg]` = $\textsc{UCompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoUCompClassH[sub][sup][arg]` = $\textsc{CoUCompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\UCompClassC[sub][sup][arg]` = $\textsc{UCompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoUCompClassC[sub][sup][arg]` = $\textsc{CoUCompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

`\ACompClass[sub][sup][arg]` = $\textsc{ACompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoACompClass[sub][sup][arg]` = $\textsc{CoACompClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\ACompClassE[sub][sup][arg]` = $\textsc{ACompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoACompClassE[sub][sup][arg]` = $\textsc{CoACompClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\ACompClassH[sub][sup][arg]` = $\textsc{ACompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoACompClassH[sub][sup][arg]` = $\textsc{CoACompClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\ACompClassC[sub][sup][arg]` = $\textsc{ACompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoACompClassC[sub][sup][arg]` = $\textsc{CoACompClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

- `\defcomclsgrp{CompClass}[NewClass]`;

`\CompClass[sub][sup][arg]` = $\textsc{NewClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoCompClass[sub][sup][arg]` = $\textsc{CoNewClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CompClassE[sub][sup][arg]` = $\textsc{NewClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoCompClassE[sub][sup][arg]` = $\textsc{CoNewClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CompClassH[sub][sup][arg]` = $\textsc{NewClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoCompClassH[sub][sup][arg]` = $\textsc{CoNewClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CompClassC[sub][sup][arg]` = $\textsc{NewClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoCompClassC[sub][sup][arg]` = $\textsc{CoNewClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

`\DCompClass[sub][sup][arg]` = $\textsc{DNewClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClass[sub][sup][arg]` = $\textsc{CoDNewClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\DCompClassE[sub][sup][arg]` = $\textsc{DNewClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClassE[sub][sup][arg]` = $\textsc{CoDNewClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\DCompClassH[sub][sup][arg]` = $\textsc{DNewClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClassH[sub][sup][arg]` = $\textsc{CoDNewClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\DCompClassC[sub][sup][arg]` = $\textsc{DNewClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoDCompClassC[sub][sup][arg]` = $\textsc{CoDNewClass-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

`\NCompClass[sub][sup][arg]` = $\textsc{NNewClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoNCompClass[sub][sup][arg]` = $\textsc{CoNNewClass}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\NCompClassE[sub][sup][arg]` = $\textsc{NNewClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoNCompClassE[sub][sup][arg]` = $\textsc{CoNNewClass-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\NCompClassH[sub][sup][arg]` = $\textsc{NNewClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
`\CoNCompClassH[sub][sup][arg]` = $\textsc{CoNNewClass-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

\NCompClassC[sub][sup][arg] = NNewClass-complete$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoNCompClassC[sub][sup][arg] = CoNNewClass-complete$^{\text{SUP}}_{\text{SUB}}$(ARG)

\UCompClass[sub][sup][arg] = UNewClass$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoUCompClass[sub][sup][arg] = CoUNewClass$^{\text{SUP}}_{\text{SUB}}$(ARG)
\UCompClassE[sub][sup][arg] = UNewClass-easy$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoUCompClassE[sub][sup][arg] = CoUNewClass-easy$^{\text{SUP}}_{\text{SUB}}$(ARG)
\UCompClassH[sub][sup][arg] = UNewClass-hard$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoUCompClassH[sub][sup][arg] = CoUNewClass-hard$^{\text{SUP}}_{\text{SUB}}$(ARG)
\UCompClassC[sub][sup][arg] = UNewClass-complete$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoUCompClassC[sub][sup][arg] = CoUNewClass-complete$^{\text{SUP}}_{\text{SUB}}$(ARG)

\ACompClass[sub][sup][arg] = ANewClass$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoACompClass[sub][sup][arg] = CoANewClass$^{\text{SUP}}_{\text{SUB}}$(ARG)
\ACompClassE[sub][sup][arg] = ANewClass-easy$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoACompClassE[sub][sup][arg] = CoANewClass-easy$^{\text{SUP}}_{\text{SUB}}$(ARG)
\ACompClassH[sub][sup][arg] = ANewClass-hard$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoACompClassH[sub][sup][arg] = CoANewClass-hard$^{\text{SUP}}_{\text{SUB}}$(ARG)
\ACompClassC[sub][sup][arg] = ANewClass-complete$^{\text{SUP}}_{\text{SUB}}$(ARG)
\CoACompClassC[sub][sup][arg] = CoANewClass-complete$^{\text{SUP}}_{\text{SUB}}$(ARG)

```
\newcommandx{\defcomclsgrp}[2][2=]
  {\defcomclsgrpsem{#1}{\defval{#2}{#1}}%
  \defcomclsgrpsem{#1}{\defval{#2}{#1}}[Co]}
\newcommandx{\defcomclsgrpsem}[3][3=]
  {\defcomclsgrpred{#3#1}{#2}[#3]%
  \defcomclsgrpred{#3D#1}{#2}[#3D]%
  \defcomclsgrpred{#3N#1}{#2}[#3N]%
  \defcomclsgrpred{#3U#1}{#2}[#3U]%
  \defcomclsgrpred{#3A#1}{#2}[#3A]}
\newcommandx{\defcomclsgrpred}[3][3=]
  {\defcomclsgrpcmd{#1}{#2}[#3]%
  \defcomclsgrpcmd{#1E}{#2}[#3][-easy]%
  \defcomclsgrpcmd{#1H}{#2}[#3][-hard]%
  \defcomclsgrpcmd{#1C}{#2}[#3][-complete]}%
\newcommandx{\defcomclsgrpcmd}[4][3=, 4=]
  {\csdef{#1}{\txtoargcom{#3#2#4}}}
```

\defcomhrc ... to do!

- \defcomhrc{CompHierarchy};

  CompHierarchy[sub][sup][par] = CompHierarchy$^{\text{SUP}}_{\text{SUB}}$[PAR]

- \defcomhrc{CompHierarchy}[NewHierarchy];

  CompHierarchy[sub][sup][par] = NewHierarchy$^{\text{SUP}}_{\text{SUB}}$[PAR]

```
\newcommandx{\defcomhrc}[2][2=]
  {\csdef{#1}{\txtoparcom{\defval{#2}{#1}}}}
```

```
%%*************************************************************************%%
```

\Easy, \Hard, ...

```
\cmdtxtcom{Easy}
\cmdtxtcom{Hard}
\cmdtxtcom{Complete}
```

```
%%*************************************************************************%%
```

\FPT

- \FPT[sub][sup][arg] = FPT$^{\text{SUP}}_{\text{SUB}}$(ARG)

```
\defcomcls{FPT}
```

```
%%*************************************************************************%%
```

`\Time, ...`

- `\Time[sub][sup][arg]` = $\textsc{Time}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\TimeE[sub][sup][arg]` = $\textsc{Time-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\TimeH[sub][sup][arg]` = $\textsc{Time-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\TimeC[sub][sup][arg]` = $\textsc{Time-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\DTime[sub][sup][arg]` = $\textsc{DTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DTimeE[sub][sup][arg]` = $\textsc{DTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DTimeH[sub][sup][arg]` = $\textsc{DTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DTimeC[sub][sup][arg]` = $\textsc{DTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\NTime[sub][sup][arg]` = $\textsc{NTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NTimeE[sub][sup][arg]` = $\textsc{NTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NTimeH[sub][sup][arg]` = $\textsc{NTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NTimeC[sub][sup][arg]` = $\textsc{NTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\UTime[sub][sup][arg]` = $\textsc{UTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\UTimeE[sub][sup][arg]` = $\textsc{UTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\UTimeH[sub][sup][arg]` = $\textsc{UTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\UTimeC[sub][sup][arg]` = $\textsc{UTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\ATime[sub][sup][arg]` = $\textsc{ATime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ATimeE[sub][sup][arg]` = $\textsc{ATime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ATimeH[sub][sup][arg]` = $\textsc{ATime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ATimeC[sub][sup][arg]` = $\textsc{ATime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

1040 `\defcomclsgrp{Time}`

`\Space, ...`

- `\Space[sub][sup][arg]` = $\textsc{Space}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\SpaceE[sub][sup][arg]` = $\textsc{Space-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\SpaceH[sub][sup][arg]` = $\textsc{Space-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\SpaceC[sub][sup][arg]` = $\textsc{Space-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\DSpace[sub][sup][arg]` = $\textsc{DSpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DSpaceE[sub][sup][arg]` = $\textsc{DSpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DSpaceH[sub][sup][arg]` = $\textsc{DSpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DSpaceC[sub][sup][arg]` = $\textsc{DSpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\NSpace[sub][sup][arg]` = $\textsc{NSpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NSpaceE[sub][sup][arg]` = $\textsc{NSpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NSpaceH[sub][sup][arg]` = $\textsc{NSpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NSpaceC[sub][sup][arg]` = $\textsc{NSpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\USpace[sub][sup][arg]` = $\textsc{USpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\USpaceE[sub][sup][arg]` = $\textsc{USpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\USpaceH[sub][sup][arg]` = $\textsc{USpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\USpaceC[sub][sup][arg]` = $\textsc{USpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\ASpace[sub][sup][arg]` = $\textsc{ASpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ASpaceE[sub][sup][arg]` = $\textsc{ASpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ASpaceH[sub][sup][arg]` = $\textsc{ASpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ASpaceC[sub][sup][arg]` = $\textsc{ASpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

1041 `\defcomclsgrp{Space}`

`\LogTime, ...`

- `\LogTime[sub][sup][arg]` = $\textsc{LogTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\LogTimeE[sub][sup][arg]` = $\textsc{LogTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\LogTimeH[sub][sup][arg]` = $\textsc{LogTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\LogTimeC[sub][sup][arg]` = $\textsc{LogTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\DLogTime[sub][sup][arg]` = $\textsc{DLogTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DLogTimeE[sub][sup][arg]` = $\textsc{DLogTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DLogTimeH[sub][sup][arg]` = $\textsc{DLogTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\DLogTimeC[sub][sup][arg]` = $\textsc{DLogTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\NLogTime[sub][sup][arg]` = $\textsc{NLogTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NLogTimeE[sub][sup][arg]` = $\textsc{NLogTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NLogTimeH[sub][sup][arg]` = $\textsc{NLogTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\NLogTimeC[sub][sup][arg]` = $\textsc{NLogTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- `\ULogTime[sub][sup][arg]` = $\textsc{ULogTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ULogTimeE[sub][sup][arg]` = $\textsc{ULogTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ULogTimeH[sub][sup][arg]` = $\textsc{ULogTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  `\ULogTimeC[sub][sup][arg]` = $\textsc{ULogTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

- `\ALogTime[sub][sup][arg]` = $\text{ALogTime}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ALogTimeE[sub][sup][arg]` = $\text{ALogTime-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ALogTimeH[sub][sup][arg]` = $\text{ALogTime-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ALogTimeC[sub][sup][arg]` = $\text{ALogTime-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$

1042 `\defcomclsgrp{LogTime}`

`\LogSpace, ...`

- `\LogSpace[sub][sup][arg]` = $\text{LogSpace}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\LogSpaceE[sub][sup][arg]` = $\text{LogSpace-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\LogSpaceH[sub][sup][arg]` = $\text{LogSpace-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\LogSpaceC[sub][sup][arg]` = $\text{LogSpace-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\DLogSpace[sub][sup][arg]` = $\text{DLogSpace}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DLogSpaceE[sub][sup][arg]` = $\text{DLogSpace-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DLogSpaceH[sub][sup][arg]` = $\text{DLogSpace-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DLogSpaceC[sub][sup][arg]` = $\text{DLogSpace-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\NLogSpace[sub][sup][arg]` = $\text{NLogSpace}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\NLogSpaceE[sub][sup][arg]` = $\text{NLogSpace-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\NLogSpaceH[sub][sup][arg]` = $\text{NLogSpace-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\NLogSpaceC[sub][sup][arg]` = $\text{NLogSpace-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\ULogSpace[sub][sup][arg]` = $\text{ULogSpace}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ULogSpaceE[sub][sup][arg]` = $\text{ULogSpace-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ULogSpaceH[sub][sup][arg]` = $\text{ULogSpace-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ULogSpaceC[sub][sup][arg]` = $\text{ULogSpace-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\ALogSpace[sub][sup][arg]` = $\text{ALogSpace}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ALogSpaceE[sub][sup][arg]` = $\text{ALogSpace-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ALogSpaceH[sub][sup][arg]` = $\text{ALogSpace-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\ALogSpaceC[sub][sup][arg]` = $\text{ALogSpace-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$

1043 `\defcomclsgrp{LogSpace}`

`\PTime, ...`

- `\PTime[sub][sup][arg]` = $\text{PTime}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\PTimeE[sub][sup][arg]` = $\text{PTime-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\PTimeH[sub][sup][arg]` = $\text{PTime-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\PTimeC[sub][sup][arg]` = $\text{PTime-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\DPTime[sub][sup][arg]` = $\text{DPTime}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DPTimeE[sub][sup][arg]` = $\text{DPTime-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DPTimeH[sub][sup][arg]` = $\text{DPTime-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DPTimeC[sub][sup][arg]` = $\text{DPTime-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\NPTime[sub][sup][arg]` = $\text{NPTime}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\NPTimeE[sub][sup][arg]` = $\text{NPTime-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\NPTimeH[sub][sup][arg]` = $\text{NPTime-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\NPTimeC[sub][sup][arg]` = $\text{NPTime-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\UPTime[sub][sup][arg]` = $\text{UPTime}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\UPTimeE[sub][sup][arg]` = $\text{UPTime-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\UPTimeH[sub][sup][arg]` = $\text{UPTime-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\UPTimeC[sub][sup][arg]` = $\text{UPTime-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\APTime[sub][sup][arg]` = $\text{APTime}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\APTimeE[sub][sup][arg]` = $\text{APTime-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\APTimeH[sub][sup][arg]` = $\text{APTime-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\APTimeC[sub][sup][arg]` = $\text{APTime-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$

1044 `\defcomclsgrp{PTime}`

`\PSpace, ...`

- `\PSpace[sub][sup][arg]` = $\text{PSpace}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\PSpaceE[sub][sup][arg]` = $\text{PSpace-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\PSpaceH[sub][sup][arg]` = $\text{PSpace-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\PSpaceC[sub][sup][arg]` = $\text{PSpace-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
- `\DPSpace[sub][sup][arg]` = $\text{DPSpace}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DPSpaceE[sub][sup][arg]` = $\text{DPSpace-easy}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DPSpaceH[sub][sup][arg]` = $\text{DPSpace-hard}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$
  `\DPSpaceC[sub][sup][arg]` = $\text{DPSpace-complete}^{\text{SUP}}_{\text{SUB}}(\text{ARG})$

- `\NPSpace[sub][sup][arg]` = $\mathrm{NPSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NPSpaceE[sub][sup][arg]` = $\mathrm{NPSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NPSpaceH[sub][sup][arg]` = $\mathrm{NPSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NPSpaceC[sub][sup][arg]` = $\mathrm{NPSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\UPSpace[sub][sup][arg]` = $\mathrm{UPSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UPSpaceE[sub][sup][arg]` = $\mathrm{UPSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UPSpaceH[sub][sup][arg]` = $\mathrm{UPSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UPSpaceC[sub][sup][arg]` = $\mathrm{UPSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\APSpace[sub][sup][arg]` = $\mathrm{APSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\APSpaceE[sub][sup][arg]` = $\mathrm{APSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\APSpaceH[sub][sup][arg]` = $\mathrm{APSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\APSpaceC[sub][sup][arg]` = $\mathrm{APSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$

1045 `\defcomclsgrp{PSpace}`

`\QPTime, ...`

- `\QPTime[sub][sup][arg]` = $\mathrm{QPTIME}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\QPTimeE[sub][sup][arg]` = $\mathrm{QPTIME\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\QPTimeH[sub][sup][arg]` = $\mathrm{QPTIME\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\QPTimeC[sub][sup][arg]` = $\mathrm{QPTIME\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\DQPTime[sub][sup][arg]` = $\mathrm{DQPTIME}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\DQPTimeE[sub][sup][arg]` = $\mathrm{DQPTIME\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\DQPTimeH[sub][sup][arg]` = $\mathrm{DQPTIME\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\DQPTimeC[sub][sup][arg]` = $\mathrm{DQPTIME\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\NQPTime[sub][sup][arg]` = $\mathrm{NQPTIME}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NQPTimeE[sub][sup][arg]` = $\mathrm{NQPTIME\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NQPTimeH[sub][sup][arg]` = $\mathrm{NQPTIME\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NQPTimeC[sub][sup][arg]` = $\mathrm{NQPTIME\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\UQPTime[sub][sup][arg]` = $\mathrm{UQPTIME}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UQPTimeE[sub][sup][arg]` = $\mathrm{UQPTIME\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UQPTimeH[sub][sup][arg]` = $\mathrm{UQPTIME\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UQPTimeC[sub][sup][arg]` = $\mathrm{UQPTIME\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\AQPTime[sub][sup][arg]` = $\mathrm{AQPTIME}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\AQPTimeE[sub][sup][arg]` = $\mathrm{AQPTIME\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\AQPTimeH[sub][sup][arg]` = $\mathrm{AQPTIME\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\AQPTimeC[sub][sup][arg]` = $\mathrm{AQPTIME\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$

1046 `\defcomclsgrp{QPTime}`

`\QPSpace, ...`

- `\QPSpace[sub][sup][arg]` = $\mathrm{QPSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\QPSpaceE[sub][sup][arg]` = $\mathrm{QPSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\QPSpaceH[sub][sup][arg]` = $\mathrm{QPSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\QPSpaceC[sub][sup][arg]` = $\mathrm{QPSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\DQPSpace[sub][sup][arg]` = $\mathrm{DQPSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\DQPSpaceE[sub][sup][arg]` = $\mathrm{DQPSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\DQPSpaceH[sub][sup][arg]` = $\mathrm{DQPSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\DQPSpaceC[sub][sup][arg]` = $\mathrm{DQPSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\NQPSpace[sub][sup][arg]` = $\mathrm{NQPSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NQPSpaceE[sub][sup][arg]` = $\mathrm{NQPSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NQPSpaceH[sub][sup][arg]` = $\mathrm{NQPSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\NQPSpaceC[sub][sup][arg]` = $\mathrm{NQPSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\UQPSpace[sub][sup][arg]` = $\mathrm{UQPSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UQPSpaceE[sub][sup][arg]` = $\mathrm{UQPSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UQPSpaceH[sub][sup][arg]` = $\mathrm{UQPSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\UQPSpaceC[sub][sup][arg]` = $\mathrm{UQPSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
- `\AQPSpace[sub][sup][arg]` = $\mathrm{AQPSPACE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\AQPSpaceE[sub][sup][arg]` = $\mathrm{AQPSPACE\text{-}EASY}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\AQPSpaceH[sub][sup][arg]` = $\mathrm{AQPSPACE\text{-}HARD}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$
  `\AQPSpaceC[sub][sup][arg]` = $\mathrm{AQPSPACE\text{-}COMPLETE}^{\mathrm{SUP}}_{\mathrm{SUB}}(\mathrm{ARG})$

1047 `\defcomclsgrp{QPSpace}`

\ExpTime, ...

- \ExpTime[sub][sup][arg] = $\textsc{ExpTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \ExpTimeE[sub][sup][arg] = $\textsc{ExpTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \ExpTimeH[sub][sup][arg] = $\textsc{ExpTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \ExpTimeC[sub][sup][arg] = $\textsc{ExpTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \DExpTime[sub][sup][arg] = $\textsc{DExpTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \DExpTimeE[sub][sup][arg] = $\textsc{DExpTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \DExpTimeH[sub][sup][arg] = $\textsc{DExpTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \DExpTimeC[sub][sup][arg] = $\textsc{DExpTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \NExpTime[sub][sup][arg] = $\textsc{NExpTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \NExpTimeE[sub][sup][arg] = $\textsc{NExpTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \NExpTimeH[sub][sup][arg] = $\textsc{NExpTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \NExpTimeC[sub][sup][arg] = $\textsc{NExpTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \UExpTime[sub][sup][arg] = $\textsc{UExpTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \UExpTimeE[sub][sup][arg] = $\textsc{UExpTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \UExpTimeH[sub][sup][arg] = $\textsc{UExpTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \UExpTimeC[sub][sup][arg] = $\textsc{UExpTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \AExpTime[sub][sup][arg] = $\textsc{AExpTime}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \AExpTimeE[sub][sup][arg] = $\textsc{AExpTime-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \AExpTimeH[sub][sup][arg] = $\textsc{AExpTime-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \AExpTimeC[sub][sup][arg] = $\textsc{AExpTime-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

```
\defcomclsgrp{ExpTime}
```

\ExpSpace, ...

- \ExpSpace[sub][sup][arg] = $\textsc{ExpSpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \ExpSpaceE[sub][sup][arg] = $\textsc{ExpSpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \ExpSpaceH[sub][sup][arg] = $\textsc{ExpSpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \ExpSpaceC[sub][sup][arg] = $\textsc{ExpSpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \DExpSpace[sub][sup][arg] = $\textsc{DExpSpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \DExpSpaceE[sub][sup][arg] = $\textsc{DExpSpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \DExpSpaceH[sub][sup][arg] = $\textsc{DExpSpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \DExpSpaceC[sub][sup][arg] = $\textsc{DExpSpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \NExpSpace[sub][sup][arg] = $\textsc{NExpSpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \NExpSpaceE[sub][sup][arg] = $\textsc{NExpSpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \NExpSpaceH[sub][sup][arg] = $\textsc{NExpSpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \NExpSpaceC[sub][sup][arg] = $\textsc{NExpSpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \UExpSpace[sub][sup][arg] = $\textsc{UExpSpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \UExpSpaceE[sub][sup][arg] = $\textsc{UExpSpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \UExpSpaceH[sub][sup][arg] = $\textsc{UExpSpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \UExpSpaceC[sub][sup][arg] = $\textsc{UExpSpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
- \AExpSpace[sub][sup][arg] = $\textsc{AExpSpace}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \AExpSpaceE[sub][sup][arg] = $\textsc{AExpSpace-easy}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \AExpSpaceH[sub][sup][arg] = $\textsc{AExpSpace-hard}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$
  \AExpSpaceC[sub][sup][arg] = $\textsc{AExpSpace-complete}^{\textsc{sup}}_{\textsc{sub}}(\textsc{arg})$

```
\defcomclsgrp{ExpSpace}

%%*************************************************************************%%
```

\PH

- \PH[sub][sup][par] = $\textsc{PH}^{\textsc{sup}}_{\textsc{sub}}[\textsc{par}]$

```
\defcomhrc{PH}
```

\WH

- \WH[sub][sup][par] = $\textsc{W}^{\textsc{sup}}_{\textsc{sub}}[\textsc{par}]$

```
\defcomhrc{WH}[W]
```

\AH

- \AH[sub][sup][par] = $\textsc{A}^{\textsc{sup}}_{\textsc{sub}}[\textsc{par}]$

```
\defcomhrc{AH}[A]
```

\DLH, \DBH

- \DLH[sub][sup][par] = $\Delta^{\textsc{sup}}_{\textsc{sub}}[\textsc{par}]$
- \DBH[sub][sup][par] = $\boldsymbol{\Delta}^{\textsc{sup}}_{\textsc{sub}}[\textsc{par}]$

```
\defcomhrc{DLH}[{\mth{\Delta}}]
\defcomhrc{DBH}[{\mth[mathbf]{\Delta}}]
```

\ELH, \EBH

- \ELH[sub][sup][par] = $\Sigma_{\text{SUB}}^{\text{SUP}}[\text{PAR}]$
- \EBH[sub][sup][par] = $\mathbf{\Sigma}_{\text{SUB}}^{\text{SUP}}[\text{PAR}]$

```
\defcomhrc{ELH}[{\mth{\Sigma}}]
\defcomhrc{EBH}[{\mth[mathbf]{\Sigma}}]
```

\ULH, \UBH

- \ULH[sub][sup][par] = $\Pi_{\text{SUB}}^{\text{SUP}}[\text{PAR}]$
- \UBH[sub][sup][par] = $\mathbf{\Pi}_{\text{SUB}}^{\text{SUP}}[\text{PAR}]$

```
\defcomhrc{ULH}[{\mth{\Pi}}]
\defcomhrc{UBH}[{\mth[mathbf]{\Pi}}]

\fi
%%*****************************************************************************%%
%%*****************************************************************************%%
%%** Macros for Games *********************************************************%%
%%*****************************************************************************%%
\ifgam@
%%** Logic Games **************************************************************%%
```

\SATG, ...

```
%% Satisfiability Games
\cmdtxtoparname{SATG}[Sat]

%% Validity Games
\cmdtxtoparname{VALG}[Val]

%% Evaluation Games
\cmdtxtoparname{EVLG}[Evl]

%% Synthesis Games
\cmdtxtoparname{SYNG}[Syn]

%% Model-Checking Games
\cmdtxtoparname{MCG}[MC]

%% Ehrenfeucht-Fraisse Games
\cmdtxtoparname{EFG}[EF]

%%** Syntax ******************************************************************%%
```

\PlrSym, \OppSym ...

```
\newcommand{\plrsym}{E}
\cmdmthsym{Plr}[\plrsym]
\newcommand{\oppsym}{A}
\cmdmthsym{Opp}[\oppsym]
```

\ArenaName, ...

```
\newcommand{\arenaname}{A}
\usrmthlatupp{Arena}{Name}{name}[\arenaname]
```

\PosSet, ...

```
\newcommand{\possym}{v}
\newcommand{\posset}{Ps}
\cmdmthsetext{Pos}[\posset][\possym]
\cmdmthsymelm{ipos}[\possym_{I}]
\cmdmthsymelm{fpos}[\possym_{F}]
\cmdmthset{PPos}[\posset_{\PlrSym}]
\cmdmthsymelm{ppos}[\possym_{\PlrSym}]
\cmdmthset{OPos}[\posset_{\OppSym}]
\cmdmthsymelm{opos}[\possym_{\OppSym}]
```

```
        \PlrFun  ...
                 \newcommand{\plrfun}{pl}
                 \cmdmthfun{plr}[\plrfun]

        \MovRel  ...
                 \newcommand{\movrel}{Mv}
                 \cmdmthrel{Mov}[\movrel]

  \GameName, ...  ...
                 \newcommand{\gamename}{\Game}
                 \usrmthlatupp{Game}{Name}{name}[\gamename]

        \WinSet  ...
                 \newcommand{\winset}{Wn}
                 \cmdmthset{Win}[\winset]

\ObsSet, \obsFun  ...
                 \newcommand{\obsset}{Ob}
                 \cmdmthset{Obs}[\obsset]
                 \cmdmthfun{obs}

                 %%** Semantics *****************************************************************%%

\PthSet, \pthFun  ...
                 \newcommand{\pthsym}{\pi}
                 \newcommand{\pthset}{Pth}
                 \cmdmthsetext{Pth}[\pthset][\pthsym]
                 \cmdmthfun{pth}

    \HstSet, ...  ...
                 \newcommand{\hstsym}{\rho}
                 \newcommand{\hstset}{Hst}
                 \cmdmthsetext{Hst}[\hstset][\hstsym]
                 \cmdmthset{PHst}[\hstset_{\PlrSym}]
                 \cmdmthsymelm{phst}[\hstsym_{\PlrSym}]
                 \cmdmthset{OHst}[\hstset_{\OppSym}]
                 \cmdmthsymelm{ohst}[\hstsym_{\OppSym}]
                 \cmdmthfun{hst}

\PlaySet,\playFun  ...
                 \newcommand{\playsym}{\pi}
                 \newcommand{\playset}{Play}
                 \cmdmthsetext{Play}[\playset][\playsym]
                 \cmdmthfun{play}

    \StrSet, ...  ...
                 \newcommand{\strsym}{\sigma}
                 \newcommand{\strset}{Str}
                 \cmdmthsetext{Str}[\strset][\strsym]
                 \cmdmthset{PStr}[\strset_{\PlrSym}]
                 \cmdmthsymelm{pstr}[\strsym_{\PlrSym}]
                 \cmdmthset{OStr}[\strset_{\OppSym}]
                 \cmdmthsymelm{ostr}[\strsym_{\OppSym}]

\PrfSet, \prfFun  ...
                 \newcommand{\prfsym}{\xi}
                 \newcommand{\prfset}{Prf}
                 \cmdmthsetext{Prf}[\prfset][\prfsym]

\preFun, \sucFun  ...
                 \newcommand{\prefun}{pre}
                 \cmdmthoargfun{pre}[\prefun]
                 \newcommand{\sucfun}{suc}
                 \cmdmthoargfun{suc}[\sucfun]
```

\entFun, \escFun ...

```
\newcommand{\entfun}{ent}
\cmdmthoargfun{ent}[\entfun]
\newcommand{\escfun}{esc}
\cmdmthoargfun{esc}[\escfun]
```

\intFun, \outFun ...

```
\newcommand{\intfun}{int}
\cmdmthoargfun{int}[\intfun]
\newcommand{\outfun}{out}
\cmdmthoargfun{out}[\outfun]
```

\atrFun, \rchFun ...

```
\newcommand{\atrfun}{atr}
\cmdmthoargfun{atr}[\atrfun]
\newcommand{\rchfun}{rch}
\cmdmthoargfun{rch}[\rchfun]
```

\liftFun ...

```
\newcommand{\liftfun}{lift}
\cmdmthoargfun{lift}[\liftfun]
```

\solFun ...

```
\newcommand{\solfun}{sol}
\cmdmthoargfun{sol}[\solfun]
```

```
%%** Qualitative Games on Graph ***********************************************%%
```

\BG, ...

```
%% Buchi Games
\cmdtxtoparname{BG}

%% Co-Buchi Games
\cmdtxtoparname{CG}

%% Parity Games
\cmdtxtoparname{PG}

%% Rabin Games
\cmdtxtoparname{RG}

%% Streett Games
\cmdtxtoparname{SG}

%% Muller Games
\cmdtxtoparname{MG}
```

```
%%** Syntax ********************************************************************%%
```

\EvnSym, \OddSym ...

```
\newcommand{\evnsym}{0}
\cmdmthsym{Evn}[\evnsym]
\newcommand{\oddsym}{1}
\cmdmthsym{Odd}[\oddsym]
```

\PrtSet, \prtFun ...

```
\newcommand{\prtsym}{p}
\newcommand{\prtset}{Pr}
\cmdmthsetext{Prt}[\prtset][\prtsym]
\cmdmthfun{prt}[pr]
```

```
%%** Semantics *****************************************************************%%
```

...

```
%%** Quantitative Games on Graph *********************************************%%
```

\EG, ...

```
%% Energy Games
\cmdtxtoparname{EG}

%% Mean-Payoff Games
\cmdtxtoparname{MPG}

%% Discounted-Payoff Games
\cmdtxtoparname{DPG}
```

```
%%** Syntax ******************************************************************%%
```

\MaxSym, \MinSym ...

```
\newcommand{\maxsym}{\oplus}
\cmdmthsym{Max}[\maxsym]
\newcommand{\minsym}{\boxminus}
\cmdmthsym{Min}[\minsym]
```

\WghSet, \wghFun ...

```
\newcommand{\wghsym}{w}
\newcommand{\wghset}{Wg}
\cmdmthsetext{Wgh}[\wghset][\wghsym]
\cmdmthfun{wgh}[wg]
```

```
%%** Semantics ***************************************************************%%
```

...

```
\fi
%%****************************************************************************%%
```

```
%%****************************************************************************%%
%%** Macros for Logics *******************************************************%%
%%****************************************************************************%%
\iflog@
```

```
%%** Propositional Logics ****************************************************%%
```

\BF, \QBF, ...

```
% Boolean Formulae
\cmdtxtoparname{BF}

% Quantified Boolean Formulae
\DeclareRobustCommand{\QBF}
  {{\txtname{Q}}\BF}
\DeclareRobustCommand{\EBF}
  {\ensuremath{\exists}\BF}
\DeclareRobustCommand{\UBF}
  {\ensuremath{\forall}\BF}
```

```
%%** Syntax ******************************************************************%%
```

\LogSig, ...

```
\newcommand{\logsig}{L}
\usrmthlatupp{Log}{Sig}{sig}[\logsig]
```

\Tt, \Ff ...

```
\newcommand{\ttsym}{\top}
\usrmth{Tt}{}{sym}[\ttsym]
\newcommand{\ffsym}{\bot}
\usrmth{Ff}{}{sym}[\ffsym]
```

```
\LNeg, \LNot  ...
1229 \newcommand{\lnegsym}{\neg}
1230 \usrmth{LNeg}{}{luop}[\lnegsym]
1231 \newcommand{\lnotsym}{\sim}
1232 \usrmth{LNot}{}{luop}[\lnotsym]

\LCon, \LDis  ...
1233 \newcommand{\lconsym}{\land}
1234 \usrmth{LCon}{}{lbop}[\lconsym]
1235 \newcommand{\ldissym}{\lor}
1236 \usrmth{LDis}{}{lbop}[\ldissym]

\LImp, \LCoi  ...
1237 \newcommand{\limpsym}{\rightarrow}
1238 \usrmth{LImp}{}{lbop}[\limpsym]
1239 \newcommand{\lcoisym}{\leftrightarrow}
1240 \usrmth{LCoi}{}{lbop}[\lcoisym]

\LExs, \LAll  ...
1241 \newcommand{\lexssym}{\exists}
1242 \usrmth{LExs}{}{luop}[\lexssym]
1243 \newcommand{\lallsym}{\forall}
1244 \usrmth{LAll}{}{luop}[\lallsym]

 \APSet, ...  ...
1245 \newcommand{\apsym}{p}
1246 \newcommand{\apset}{AP}
1247 \cmdmthsetext{AP}[\apset][\apsym]
1248 \cmdmthfun{ap}\usrmth{ap}{}{argfun}

       \sub  ...
1249 \usrmth{sub}{}{argfun}

\Cnt, \Qnt, \Sym  ...
1250 \usrmth{Cnt}{}{sym}[C]
1251 \usrmth{Qnt}{}{sym}[Q]
1252 \usrmth{Sym}{}{sym}[\odot]

  \QAE, \QEA  ...
1253 \usrmth{QAE}{}{sym}[\forall\exists]
1254 \usrmth{QEA}{}{sym}[\exists\forall]

\QntSet, ...  ...
1255 \newcommand{\qntsym}{\wp}
1256 \newcommand{\qntset}{Qn}
1257 \cmdmthsetext{Qnt}[\qntset][\qntsym]

\free, \bound  ...
1258 \usrmth{free}{}{argfun}
1259 \usrmth{bound}{}{argfun}

  \dep, \alt  ...
1260 \usrmth{dep}{}{argfun}
1261 \usrmth{alt}{}{argfun}

\cnf, \dnf, ...  ...
1262 \cmdtxtabr{cnf}
1263 \cmdtxtabr{dnf}
1264 \cmdtxtabr{pnf}
1265 \cmdtxtabr{nnf}

1266 %%** Semantics ************************************************************%%
```

```
\LogStr, ...  ...
1267 \newcommand{\logstr}{L}
1268 \usrmthlatupp{Log}{Str}{str}[\logstr]

\ValSet, ...  ...
1269 \newcommand{\valsym}{\xi}
1270 \newcommand{\valset}{Val}
1271 \cmdmthsetext{Val}[\valset][\valsym]

\AsgSet, ...  ...
1272 \newcommand{\asgsym}{\chi}
1273 \newcommand{\asgset}{Asg}
1274 \cmdmthsetext{Asg}[\asgset][\asgsym]

1275 %%** First-Order Logics I ***************************************************%%

   \FOL, ...  ...
1276 % First-Order Logic
1277 \cmdtxtoparname{FOL}[Fol]
1278 \cmdtxtoparname{FO}[FO]
1279
1280 % Monadic First-Order Logic
1281 \DeclareRobustCommand{\MFOL}
1282   {{\txtname{M}}\FOL}
1283 \DeclareRobustCommand{\MFO}
1284   {{\txtname{M}}\FO}

1285 %%** Syntax ******************************************************************%%

\VarSig, ...  ...
1286 \newcommand{\varsig}{V}
1287 \usrmthlatupp{Var}{Sig}{sig}[\varsig]
1288 \newcommand{\varsym}{x}
1289 \newcommand{\varset}{Vr}
1290 \cmdmthsetext{Var}[\varset][\varsym]
1291 \usrmth{var}{}{argfun}[vr]
1292 \cmdmthfun{dim}[dm]\usrmth{dim}{}{argfun}[dm]

\ConSig, ...  ...
1293 \newcommand{\consig}{C}
1294 \usrmthlatupp{Con}{Sig}{sig}[\consig]
1295 \newcommand{\consym}{c}
1296 \newcommand{\conset}{Cn}
1297 \cmdmthsetext{Con}[\conset][\consym]
1298 \usrmth{con}{}{argfun}[cn]

\FunSig, ...  ...
1299 \newcommand{\funsig}{F}
1300 \usrmthlatupp{Fun}{Sig}{sig}[\funsig]
1301 \newcommand{\funsym}{f}
1302 \newcommand{\funset}{Fn}
1303 \cmdmthsetext{Fun}[\funset][\funsym]
1304 \usrmth{fun}{}{argfun}[fn]
1305 \cmdmthfun{art}[ar]\usrmth{art}{}{argfun}[ar]

\TerSig, ...  ...
1306 \newcommand{\tersig}{T}
1307 \usrmthlatupp{Ter}{Sig}{sig}[\tersig]
1308 \newcommand{\tersym}{t}
1309 \newcommand{\terset}{Tr}
1310 \cmdmthsetext{Ter}[\terset][\tersym]
1311 \usrmth{ter}{}{argfun}
```

```
\RelSig, ...  ...
1312 \newcommand{\relsig}{R}
1313 \usrmthlatupp{Rel}{Sig}{sig}[\relsig]
1314 \newcommand{\relsym}{r}
1315 \newcommand{\relset}{Rl}
1316 \cmdmthsetext{Rel}[\relset][\relsym]
1317 \usrmth{rel}{}{argfun}[rl]

      \skm  ...
1318 \usrmth{skm}{}{argfun}

1319 %%** Semantics ****************************************************************%%

\ConStr, ...  ...
1320 \newcommand{\constr}{C}
1321 \usrmthlatupp{Con}{Str}{str}[\constr]

\FunStr, ...  ...
1322 \newcommand{\funstr}{F}
1323 \usrmthlatupp{Fun}{Str}{str}[\funstr]

\TerStr, ...  ...
1324 \newcommand{\terstr}{T}
1325 \usrmthlatupp{Ter}{Str}{str}[\terstr]

\RelStr, ...  ...
1326 \newcommand{\relstr}{R}
1327 \usrmthlatupp{Rel}{Str}{str}[\relstr]

1328 %%** First-Order Logics II ****************************************************%%

\DF, \IF, ...  ...
1329 % Dependence-Friendly Logic
1330 \cmdtxtoparname{DF}
1331
1332 % Independence-Friendly Logic
1333 \cmdtxtoparname{IF}
1334
1335 % Dependence/Independence-Friendly Logic
1336 \cmdtxtoparname{DIF}
1337
1338 % Dependence Logic
1339 \cmdtxtoparname{DL}
1340
1341 % Team Logic
1342 \cmdtxtoparname{TL}
1343
1344 % Alternating Dependence-Friendly Logic
1345 \cmdtxtoparname{ADF}
1346
1347 % Alternating Independence-Friendly Logic
1348 \cmdtxtoparname{AIF}
1349
1350 % Alternating Dependence/Independence-Friendly Logic
1351 \cmdtxtoparname{ADIF}

    ...
1352 %%** Syntax ********************************************************************%%

\LEExs, \LAAll  ...
1353 \newcommand{\leexssym}{\Sigma}
1354 \usrmth{LEExs}{}{luop}[\leexssym]
1355 \newcommand{\laallsym}{\Pi}
1356 \usrmth{LAAll}{}{luop}[\laallsym]
```

```
%%** Semantics ****************************************************************%%
```

...

```
%%** Second-Order Logics I ***************************************************%%
```

\SOL, ...

```
% Second-Order Logic
\cmdtxtoparname{SOL}[Sol]
\cmdtxtoparname{SO}

% Weak Second-Order Logic
\DeclareRobustCommand{\WSOL}
  {{\txtname{W}}\SOL}
\DeclareRobustCommand{\WSO}
  {{\txtname{W}}\SO}

% coWeak Second-Order Logic
\DeclareRobustCommand{\coWSOL}
  {{\txtname{coW}}\SOL}
\DeclareRobustCommand{\coWSO}
  {{\txtname{coW}}\SO}

% Monadic Second-Order Logic
\DeclareRobustCommand{\MSOL}
  {{\txtname{M}}\SOL}
\DeclareRobustCommand{\MSO}
  {{\txtname{M}}\SO}

% Weak Monadic Second-Order Logic
\DeclareRobustCommand{\WMSOL}
  {{\txtname{W}}\MSOL}
\DeclareRobustCommand{\WMSO}
  {{\txtname{W}}\MSO}

% coWeak Monadic Second-Order Logic
\DeclareRobustCommand{\coWMSOL}
  {{\txtname{coW}}\MSOL}
\DeclareRobustCommand{\coWMSO}
  {{\txtname{coW}}\MSO}

%%** Syntax ********************************************************************%%
```

\FVarSet, ...

```
\newcommand{\fvarsym}{x}
\newcommand{\fvarset}{FVr}
\cmdmthsetext{FVar}[\fvarset][\fvarsym]
```

\SVarSet, ...

```
\newcommand{\svarsym}{X}
\newcommand{\svarset}{SVr}
\cmdmthsetext{SVar}[\svarset][\svarsym]

%%** Semantics ****************************************************************%%
```

...

```
%%** Second-Order Logics II **************************************************%%
```

\TL, \PL, ...

```
% Tree Logic
\cmdtxtoparname{TL}

% Weak Tree Logic
\DeclareRobustCommand{\WTL}
  {{\txtname{W}}\TL}
```

```
1407
1408 % coWeak Tree Logic
1409 \DeclareRobustCommand{\coWTL}
1410   {{\txtname{coW}}\TL}
1411
1412 % Monadic Tree Logic
1413 \DeclareRobustCommand{\MTL}
1414   {{\txtname{M}}\TL}
1415
1416 % Weak Monadic Tree Logic
1417 \DeclareRobustCommand{\WMTL}
1418   {{\txtname{W}}\MTL}
1419
1420 % coWeak Monadic Tree Logic
1421 \DeclareRobustCommand{\coWMTL}
1422   {{\txtname{coW}}\MTL}
1423
1424 % Path Logic
1425 \cmdtxtoparname{PL}
1426
1427 % Weak Path Logic
1428 \DeclareRobustCommand{\WPL}
1429   {{\txtname{W}}\PL}
1430
1431 % coWeak Path Logic
1432 \DeclareRobustCommand{\coWPL}
1433   {{\txtname{coW}}\PL}
1434
1435 % Monadic Path Logic
1436 \DeclareRobustCommand{\MPL}
1437   {{\txtname{M}}\PL}
1438
1439 % Weak Monadic Path Logic
1440 \DeclareRobustCommand{\WMPL}
1441   {{\txtname{W}}\MPL}
1442
1443 % coWeak Monadic Path Logic
1444 \DeclareRobustCommand{\coWMPL}
1445   {{\txtname{coW}}\MPL}

1446 %%** Syntax ************************************************************%%

   ...

1447 %%** Semantics *********************************************************%%

   ...

1448 %%** Modal Logics I *****************************************************%%

\ML, \GML, ...  ...
1449 % Modal Logic
1450 \cmdtxtoparname{ML}
1451
1452 % Graded Modal Logic
1453 \DeclareRobustCommand{\GML}
1454   {{\txtname{G}}\ML}
1455
1456 % Quantified Modal Logic
1457 \DeclareRobustCommand{\QML}
1458   {{\txtname{Q}}\ML}
1459 \DeclareRobustCommand{\EML}
1460   {\ensuremath{\exists}\ML}
1461 \DeclareRobustCommand{\UML}
1462   {\ensuremath{\forall}\ML}
```

```
%%** Syntax ********************************************************************%%

\Opr  ...
\usrmth{Opr}{}{sym}[Op]

\DMod, \BMod  ...
\usrmth{DMod}{}{sym}[\Diamond]
\usrmth{BMod}{}{sym}[\Box]

\Exs, \All  ...
\DeclareRobustCommand{\Exs}[1]
  {\mth{\defval{\argmid{\langle}{#1}{\rangle}}{\DMod}}}
\DeclareRobustCommand{\All}[1]
  {\mth{\defval{\argmid{\left[}{#1}{\right]}}{\BMod}}}

%%** Semantics ********************************************************************%%

\KrpStr, ...  ...
\newcommand{\krpstr}{K}
\usrmthlatupp{Krp}{Str}{str}[\krpstr]

\WrlSet, ...  ...
\newcommand{\wrlsym}{w}
\newcommand{\wrlset}{W}
\cmdmthsetext{Wrl}[\wrlset][\wrlsym]
\cmdmthsymelm{iwrl}[\wrlsym_{I}]

\AccRel, \TrnRel  ...
\newcommand{\accsym}{R}
\cmdmthrel{Acc}[\accsym]
\cmdmthrel{Trn}[\accsym]

\labFun  ...
\newcommand{\labsym}{\lambda}
\cmdmthfun{lab}[\labsym]

\PthSet, \pthFun  ...
\providecommand{\pthsym}{\pi}
\providecommand{\pthset}{Pth}
\cmdmthsetext{Pth}[\pthset][\pthsym]
\cmdmthfun{pth}

%%** Modal Logics II ***************************************************************%%

\MC, \GMC, ...  ...
% Mu Calculus
\cmdtxtoparname{MC}[\ensuremath{\mu}-Calculus]

% Graded Mu Calculus
\DeclareRobustCommand{\GMC}
  {{\txtname{G}}\MC}

% Quantified Mu Calculus
\DeclareRobustCommand{\QMC}
  {{\txtname{Q}}\MC}
\DeclareRobustCommand{\EMC}
  {\ensuremath{\exists}\MC}
\DeclareRobustCommand{\UMC}
  {\ensuremath{\forall}\MC}

% Alternation-Free Mu Calculus
\DeclareRobustCommand{\AFMC}
  {{\txtname{AF}}\MC}
```

```
1506
1507 % Alternation-Free Graded Mu Calculus
1508 \DeclareRobustCommand{\AFGMC}
1509   {{\txtname{AF}}\GMC}
1510
1511 % Quantified Alternation-Free Mu Calculus
1512 \DeclareRobustCommand{\QAFMC}
1513   {{\txtname{Q}}\AFMC}
1514 \DeclareRobustCommand{\EAFMC}
1515   {\ensuremath{\exists}\AFMC}
1516 \DeclareRobustCommand{\UAFMC}
1517   {\ensuremath{\forall}\AFMC}
1518
1519 %%** Syntax ************************************************************%%
    ...
1520 %%** Semantics ********************************************************%%
    ...
1521 %%** Temporal Logics I *************************************************%%
```

\PTL, \LTL, ...

```
1522 % Propositional Temporal Logic
1523 \cmdtxtoparname{PTL}
1524
1525 % Quantified Propositional Temporal Logic
1526 \DeclareRobustCommand{\QPTL}
1527   {{\txtname{Q}}\PTL}
1528 \DeclareRobustCommand{\EPTL}
1529   {\ensuremath{\exists}\PTL}
1530 \DeclareRobustCommand{\UPTL}
1531   {\ensuremath{\forall}\PTL}
1532
1533 % Linear Temporal Logic
1534 \cmdtxtoparname{LTL}
1535
1536 % Quantified Linear Temporal Logic
1537 \DeclareRobustCommand{\QLTL}
1538   {{\txtname{Q}}\LTL}
1539 \DeclareRobustCommand{\ELTL}
1540   {\ensuremath{\exists}\LTL}
1541 \DeclareRobustCommand{\ULTL}
1542   {\ensuremath{\forall}\LTL}
1543 %%** Syntax ************************************************************%%
```

\X, ...

```
1544 \usrmth{X}{}{sym}[X\,]
1545 \usrmth{F}{}{sym}[F\,]
1546 \usrmth{G}{}{sym}[G\,]
1547 \usrmth{U}{}{sym}[\,U\,]
1548 \usrmth{R}{}{sym}[\,R\,]
```

\Y, ...

```
1549 \usrmth{Y}{}{sym}[G\,]
1550 \usrmth{P}{}{sym}[P\,]\let\SavePilcrow\P
1551 \usrmth{H}{}{sym}[H\,]\let\SaveDoubleAcute\H
1552 \usrmth{S}{}{sym}[\,S\,]\let\SaveSectionSymbol\S
1553 \usrmth{B}{}{sym}[\,B\,]

1554 %%** Semantics ********************************************************%%
    ...
1555 %%** Temporal Logics II ************************************************%%
```

```
\PDL, \CTL, ...  ...
```

```
1556
1557 % Propositional Dynamic Logic
1558 \cmdtxtoparname{PDL}
1559
1560 % Computation Tree Logic
1561 \cmdtxtoparname{CTL}
1562
1563 % Weak Computation Tree Logic
1564 \DeclareRobustCommand{\WCTL}
1565   {{\txtname{W}}\CTL}
1566
1567 % Quantified Computation Tree Logic
1568 \DeclareRobustCommand{\QCTL}
1569   {{\txtname{Q}}\CTL}
1570 \DeclareRobustCommand{\ECTL}
1571   {\ensuremath{\exists}\CTL}
1572 \DeclareRobustCommand{\UCTL}
1573   {\ensuremath{\forall}\CTL}
1574
1575 % Improved Computation Tree Logic
1576 \cmdtxtoparname{CTLP}[CTL$^{+}$]
1577
1578 % Weak Improved Computation Tree Logic
1579 \DeclareRobustCommand{\WCTLP}
1580   {{\txtname{W}}\CTLP}
1581
1582 % Quantified Improved Computation Tree Logic
1583 \DeclareRobustCommand{\QCTLP}
1584   {{\txtname{Q}}\CTLP}
1585 \DeclareRobustCommand{\ECTLP}
1586   {\ensuremath{\exists}\CTLP}
1587 \DeclareRobustCommand{\UCTLP}
1588   {\ensuremath{\forall}\CTLP}
1589
1590 % Full Computation Tree Logic
1591 \cmdtxtoparname{CTLS}[CTL*]
1592
1593 % Weak Full Computation Tree Logic
1594 \DeclareRobustCommand{\WCTLS}
1595   {{\txtname{W}}\CTLS}
1596
1597 % Quantified Full Computation Tree Logic
1598 \DeclareRobustCommand{\QCTLS}
1599   {{\txtname{Q}}\CTLS}
1600 \DeclareRobustCommand{\ECTLS}
1601   {\ensuremath{\exists}\CTLS}
1602 \DeclareRobustCommand{\UCTLS}
1603   {\ensuremath{\forall}\CTLS}
```

```
1604 %%** Syntax ************************************************************%%
```

```
\E, \A  ...
```

```
1605 \usrmth{E}{}{sym}
1606 \usrmth{A}{}{sym}
```

```
1607 %%** Semantics *********************************************************%%
```

```
   ...
```

```
1608 %%** Strategic Logics I ***********************************************%%
```

```
\ATL, ...  ...
```

```
1609 % Alternating Temporal Logic
1610 \cmdtxtoparname{ATL}
```

```
1611
1612 % Weak Alternating Tree Logic
1613 \DeclareRobustCommand{\WATL}
1614   {{\txtname{W}}\ATL}
1615
1616 % Quantified Alternating Temporal Logic
1617 \DeclareRobustCommand{\QATL}
1618   {{\txtname{Q}}\ATL}
1619 \DeclareRobustCommand{\EATL}
1620   {\ensuremath{\exists}\ATL}
1621 \DeclareRobustCommand{\UATL}
1622   {\ensuremath{\forall}\ATL}
1623
1624 % Improved Alternating Temporal Logic
1625 \cmdtxtoparname{ATLP}[ATL$^{+}$]
1626
1627 % Weak Improved Alternating Tree Logic
1628 \DeclareRobustCommand{\WATLP}
1629   {{\txtname{W}}\ATLP}
1630
1631 % Quantified Improved Alternating Temporal Logic
1632 \DeclareRobustCommand{\QATLP}
1633   {{\txtname{Q}}\ATLP}
1634 \DeclareRobustCommand{\EATLP}
1635   {\ensuremath{\exists}\ATLP}
1636 \DeclareRobustCommand{\UATLP}
1637   {\ensuremath{\forall}\ATLP}
1638
1639 % Full Alternating Temporal Logic
1640 \cmdtxtoparname{ATLS}[ATL*]
1641
1642 % Weak Full Alternating Tree Logic
1643 \DeclareRobustCommand{\WATLS}
1644   {{\txtname{W}}\ATLS}
1645
1646 % Quantified Full Alternating Temporal Logic
1647 \DeclareRobustCommand{\QATLS}
1648   {{\txtname{Q}}\ATLS}
1649 \DeclareRobustCommand{\EATLS}
1650   {\ensuremath{\exists}\ATLS}
1651 \DeclareRobustCommand{\UATLS}
1652   {\ensuremath{\forall}\ATLS}
```

```
1653 %%** Syntax ********************************************************************%%
```

\EExs, \AAll ...

```
1654 \DeclareRobustCommand{\EExs}[1]
1655   {\mth{\argmid{\langle\!\langle}{\defval{#1}{\emptyset}}{\rangle\!\rangle}}}
1656 \DeclareRobustCommand{\AAll}[1]
1657   {\mth{\argmid{\left[\left[}{\defval{#1}{\emptyset}}{\right]\right]}}}
```

```
1658 %%** Semantics *****************************************************************%%
```

\CGS ...

```
1659 \cmdtxtname{CGS}
```

\CGSStr, ...

```
1660 \newcommand{\cgsstr}{G}
1661 \usrmthlatupp{CGS}{Str}{str}[\cgsstr]
```

\AgnSet, ...

```
1662 \newcommand{\agnsym}{a}
1663 \newcommand{\agnset}{Ag}
1664 \cmdmthsetext{Agn}[\agnset][\agnsym]
```

```
\PosSet, ...  ...
1665 \providecommand{\possym}{v}
1666 \providecommand{\posset}{Ps}
1667 \cmdmthsetext{Pos}[\posset][\possym]
1668 \cmdmthsymelm{ipos}[\possym_{I}]
1669 \cmdmthsymelm{fpos}[\possym_{F}]
1670 \cmdmthset{PPos}[\posset_{\PlrSym}]
1671 \cmdmthsymelm{ppos}[\possym_{\PlrSym}]
1672 \cmdmthset{OPos}[\posset_{\OppSym}]
1673 \cmdmthsymelm{opos}[\possym_{\OppSym}]

\SttSet, ...  ...
1674 \newcommand{\sttsym}{s}
1675 \newcommand{\sttset}{St}
1676 \cmdmthsetext{Stt}[\sttset][\sttsym]
1677 \cmdmthset{IStt}[\sttset_{I}]
1678 \cmdmthsymelm{istt}[\sttsym_{I}]
1679 \cmdmthset{FStt}[\sttset_{F}]
1680 \cmdmthsymelm{fstt}[\sttsym_{F}]

\ActSet, ...  ...
1681 \newcommand{\actsym}{c}
1682 \newcommand{\actset}{Ac}
1683 \cmdmthsetext{Act}[\actset][\actsym]

\DecSet, ...  ...
1684 \newcommand{\decsym}{d}
1685 \newcommand{\decset}{Dc}
1686 \cmdmthsetext{Dec}[\decset][\decsym]

     \movFun  ...
1687 \newcommand{\movsym}{\tau}
1688 \cmdmthfun{mov}[\movsym]

\HstSet, ...  ...
1689 \providecommand{\hstsym}{\rho}
1690 \providecommand{\hstset}{Hst}
1691 \cmdmthsetext{Hst}[\hstset][\hstsym]
1692 \cmdmthset{PHst}[\hstset_{\PlrSym}]
1693 \cmdmthsymelm{phst}[\hstsym_{\PlrSym}]
1694 \cmdmthset{OHst}[\hstset_{\OppSym}]
1695 \cmdmthsymelm{ohst}[\hstsym_{\OppSym}]
1696 \cmdmthfun{hst}

\PlaySet,\playFun  ...
1697 \providecommand{\playsym}{\pi}
1698 \providecommand{\playset}{Play}
1699 \cmdmthsetext{Play}[\playset][\playsym]
1700 \cmdmthfun{play}

\StrSet, ...  ...
1701 \providecommand{\strsym}{\sigma}
1702 \providecommand{\strset}{Str}
1703 \cmdmthsetext{Str}[\strset][\strsym]
1704 \cmdmthset{PStr}[\strset_{\PlrSym}]
1705 \cmdmthsymelm{pstr}[\strsym_{\PlrSym}]
1706 \cmdmthset{OStr}[\strset_{\OppSym}]
1707 \cmdmthsymelm{ostr}[\strsym_{\OppSym}]

\PrfSet, \prfFun  ...
1708 \providecommand{\prfsym}{\xi}
1709 \providecommand{\prfset}{Prf}
1710 \cmdmthsetext{Prf}[\prfset][\prfsym]
```

```
%%** Strategic Logics II ****************************************************%%
```

\SL, ...

```
% Strategy Logic
\cmdtxtoparname{SL}

\DeclareRobustCommand{\ESL}
  {\ensuremath{\exists}\SL}
\DeclareRobustCommand{\USL}
  {\ensuremath{\forall}\SL}

\DeclareRobustCommand{\FSL}
  {{\txtname{F}}\SL}

\DeclareRobustCommand{\EFSL}
  {\ensuremath{\exists}\FSL}
\DeclareRobustCommand{\UFSL}
  {\ensuremath{\forall}\FSL}

% One-Goal Strategy Logic
\DeclareRobustCommandx{\OGSL}[3][1=, 2=, 3=]
  {\SL[#1][#2][1g\arglef{,}{#3}]}

\DeclareRobustCommand{\EOGSL}
  {\ensuremath{\exists}\OGSL}
\DeclareRobustCommand{\UOGSL}
  {\ensuremath{\forall}\OGSL}

\DeclareRobustCommand{\FOGSL}
  {{\txtname{F}}\OGSL}

\DeclareRobustCommand{\EFOGSL}
  {\ensuremath{\exists}\FOGSL}
\DeclareRobustCommand{\UFOGSL}
  {\ensuremath{\forall}\FOGSL}

% Conjunctive-Goal Strategy Logic
\DeclareRobustCommandx{\CGSL}[3][1=, 2=, 3=]
  {\SL[#1][#2][cg\arglef{,}{#3}]}

\DeclareRobustCommand{\ECGSL}
  {\ensuremath{\exists}\CGSL}
\DeclareRobustCommand{\UCGSL}
  {\ensuremath{\forall}\CGSL}

\DeclareRobustCommand{\FCGSL}
  {{\txtname{F}}\xGSL}

\DeclareRobustCommand{\EFCGSL}
  {\ensuremath{\exists}\FCGSL}
\DeclareRobustCommand{\UFCGSL}
  {\ensuremath{\forall}\FCGSL}

% Disjunctive-Goal Strategy Logic
\DeclareRobustCommandx{\DGSL}[3][1=, 2=, 3=]
  {\SL[#1][#2][dg\arglef{,}{#3}]}

\DeclareRobustCommand{\EDGSL}
  {\ensuremath{\exists}\DGSL}
\DeclareRobustCommand{\UDGSL}
  {\ensuremath{\forall}\DGSL}

\DeclareRobustCommand{\FDGSL}
  {{\txtname{F}}\xGSL}
```

```
1773
1774 \DeclareRobustCommand{\EFDGSL}
1775   {\ensuremath{\exists}\FDGSL}
1776 \DeclareRobustCommand{\UFDGSL}
1777   {\ensuremath{\forall}\FDGSL}
1778
1779 % Alternating-Goal Strategy Logic
1780 \DeclareRobustCommandx{\AGSL}[3][1=, 2=, 3=]
1781   {\SL[#1][#2][ag\arglef{,}{#3}]}
1782
1783 \DeclareRobustCommand{\EAGSL}
1784   {\ensuremath{\exists}\AGSL}
1785 \DeclareRobustCommand{\UAGSL}
1786   {\ensuremath{\forall}\AGSL}
1787
1788 \DeclareRobustCommand{\FAGSL}
1789   {{\txtname{F}}\xGSL}
1790
1791 \DeclareRobustCommand{\EFAGSL}
1792   {\ensuremath{\exists}\FAGSL}
1793 \DeclareRobustCommand{\UFAGSL}
1794   {\ensuremath{\forall}\FAGSL}
1795
1796 % Extended-Goal Strategy Logic
1797 \DeclareRobustCommandx{\EGSL}[3][1=, 2=, 3=]
1798   {\SL[#1][#2][eg\arglef{,}{#3}]}
1799
1800 \DeclareRobustCommand{\EEGSL}
1801   {\ensuremath{\exists}\EGSL}
1802 \DeclareRobustCommand{\UEGSL}
1803   {\ensuremath{\forall}\EGSL}
1804
1805 \DeclareRobustCommand{\FEGSL}
1806   {{\txtname{F}}\xGSL}
1807
1808 \DeclareRobustCommand{\EFEGSL}
1809   {\ensuremath{\exists}\FEGSL}
1810 \DeclareRobustCommand{\UFEGSL}
1811   {\ensuremath{\forall}\FEGSL}
1812
1813 % Boolean-Goal Strategy Logic
1814 \DeclareRobustCommandx{\BGSL}[3][1=, 2=, 3=]
1815   {\SL[#1][#2][bg\arglef{,}{#3}]}
1816
1817 \DeclareRobustCommand{\EBGSL}
1818   {\ensuremath{\exists}\BGSL}
1819 \DeclareRobustCommand{\UBGSL}
1820   {\ensuremath{\forall}\BGSL}
1821
1822 \DeclareRobustCommand{\FBGSL}
1823   {{\txtname{F}}\xGSL}
1824
1825 \DeclareRobustCommand{\EFBGSL}
1826   {\ensuremath{\exists}\FBGSL}
1827 \DeclareRobustCommand{\UFBGSL}
1828   {\ensuremath{\forall}\FBGSL}
1829
1830 % Nested-Goal Strategy Logic
1831 \DeclareRobustCommandx{\NGSL}[3][1=, 2=, 3=]
1832   {\SL[#1][#2][ng\arglef{,}{#3}]}
1833
1834 \DeclareRobustCommand{\ENGSL}
1835   {\ensuremath{\exists}\NGSL}
```

```
\DeclareRobustCommand{\UNGSL}
  {\ensuremath{\forall}\NGSL}

\DeclareRobustCommand{\FNGSL}
  {{\txtname{F}}\xGSL}

\DeclareRobustCommand{\EFNGSL}
  {\ensuremath{\exists}\FNGSL}
\DeclareRobustCommand{\UFNGSL}
  {\ensuremath{\forall}\FNGSL}

% Undefined-Goal Strategy Logic
\DeclareRobustCommandx{\XGSL}[3][1=, 2=, 3=]
  {\SL[#1][#2][xg\arglef{,}{#3}]}

\DeclareRobustCommand{\EXGSL}
  {\ensuremath{\exists}\XGSL}
\DeclareRobustCommand{\UXGSL}
  {\ensuremath{\forall}\XGSL}

\DeclareRobustCommand{\FXGSL}
  {{\txtname{F}}\xGSL}

\DeclareRobustCommand{\EFXGSL}
  {\ensuremath{\exists}\FXGSL}
\DeclareRobustCommand{\UFXGSL}
  {\ensuremath{\forall}\FXGSL}

%%** Syntax ************************************************************%%

\BndSet, ...  ...
\newcommand{\bndsym}{\flat}
\newcommand{\bndset}{Bn}
\cmdmthsetext{Bnd}[\bndset][\bndsym]
\usrmth{bnd}{}{argfun}

      \psn  ...
\usrmth{psn}{}{argfun}

%%** Semantics ********************************************************%%

   \nxtFun  ...
\newcommand{\nxtfun}{nxt}
\cmdmthfun{nxt}[\nxtfun]

\fi
%%*****************************************************************************%%
%%*****************************************************************************%%
%%** Macros for Automata ******************************************************%%
%%*****************************************************************************%%
\ifaut@
%%** Finite Word Automata *****************************************************%%

  \DFA, ...  ...
\cmdtxtoparname{DFA}\cmdtxtoparname{NFA}\cmdtxtoparname{UFA}\cmdtxtoparname{AFA}

\cmdtxtoparname{DWA}\cmdtxtoparname{NWA}\cmdtxtoparname{UWA}\cmdtxtoparname{AWA}

\cmdtxtoparname{DFW}\cmdtxtoparname{NFW}\cmdtxtoparname{UFW}\cmdtxtoparname{AFW}
\cmdtxtoparname{DBW}\cmdtxtoparname{NBW}\cmdtxtoparname{UBW}\cmdtxtoparname{ABW}
\cmdtxtoparname{DCW}\cmdtxtoparname{NCW}\cmdtxtoparname{UCW}\cmdtxtoparname{ACW}
\cmdtxtoparname{DPW}\cmdtxtoparname{NPW}\cmdtxtoparname{UPW}\cmdtxtoparname{APW}
\cmdtxtoparname{DRW}\cmdtxtoparname{NRW}\cmdtxtoparname{URW}\cmdtxtoparname{ARW}
\cmdtxtoparname{DSW}\cmdtxtoparname{NSW}\cmdtxtoparname{USW}\cmdtxtoparname{ASW}
\cmdtxtoparname{DMW}\cmdtxtoparname{NMW}\cmdtxtoparname{UMW}\cmdtxtoparname{AMW}
```

```
\GFG, \PD, ...  ...
                \cmdtxtoparname{GFG}

                \cmdtxtoparname{PD}

                %% ...

                %%** Syntax ********************************************************************%%

 \AutName, ...  ...
                \newcommand{\autname}{A}
                \usrmthlatupp{Aut}{Name}{name}[\autname]
                \newcommand{\autset}{Aut}
                \cmdmthset{Aut}[\autset]

      \WAutSet  ...
                \newcommand{\wautset}{WAut}
                \cmdmthset{WAut}[\wautset]

  \SttSet, ...  ...
                \def\sttsym{q}
                \def\sttset{Q}
                \cmdmthsetext{Stt}[\sttset][\sttsym]
                \cmdmthset{IStt}[\sttset_{I}]
                \cmdmthsymelm{istt}[\sttsym_{I}]
                \cmdmthset{FStt}[\sttset_{F}]
                \cmdmthsymelm{fstt}[\sttsym_{F}]

  \SymSet, ...  ...
                \newcommand{\symsym}{\sigma}
                \newcommand{\symset}{\Sigma}
                \cmdmthsetext{Sym}[\symset][\symsym]

       \trnFun  ...
                \newcommand{\trnsym}{\delta}
                \cmdmthfun{trn}[\trnsym]

                %%** Semantics *********************************************************************%%

      \LangFun  ...
                \newcommand{\langfun}{L}
                \cmdmthfun{Lang}[\langfun]

  \WrdSet, ...  ...
                \newcommand{\wrdsym}{w}
                \newcommand{\wrdset}{Wr}
                \cmdmthsetext{Wrd}[\wrdset][\wrdsym]

                %%** Finite Tree Automata ***********************************************************%%

     \DTA, ...  ...
                \cmdtxtoparname{DTA}\cmdtxtoparname{NTA}\cmdtxtoparname{UTA}\cmdtxtoparname{ATA}

                \cmdtxtoparname{DFT}\cmdtxtoparname{NFT}\cmdtxtoparname{UFT}\cmdtxtoparname{AFT}
                \cmdtxtoparname{DBT}\cmdtxtoparname{NBT}\cmdtxtoparname{UBT}\cmdtxtoparname{ABT}
                \cmdtxtoparname{DCT}\cmdtxtoparname{NCT}\cmdtxtoparname{UCT}\cmdtxtoparname{ACT}
                \cmdtxtoparname{DPT}\cmdtxtoparname{NPT}\cmdtxtoparname{UPT}\cmdtxtoparname{APT}
                \cmdtxtoparname{DRT}\cmdtxtoparname{NRT}\cmdtxtoparname{URT}\cmdtxtoparname{ART}
                \cmdtxtoparname{DST}\cmdtxtoparname{NST}\cmdtxtoparname{UST}\cmdtxtoparname{AST}
                \cmdtxtoparname{DMT}\cmdtxtoparname{NMT}\cmdtxtoparname{UMT}\cmdtxtoparname{AMT}

                %%** Syntax ********************************************************************%%
```

```
\TAutSet  ...
1931 \newcommand{\tautset}{TAut}
1932 \cmdmthset{TAut}[\tautset]

\DirSet, ...  ...
1933 \newcommand{\dirsym}{d}
1934 \newcommand{\dirset}{\Lambda}
1935 \cmdmthsetext{Dir}[\dirset][\dirsym]

1936 %%** Semantics ********************************************************************%%

\TreeSet, ...  ...
1937 \newcommand{\treesym}{T}
1938 \newcommand{\treeset}{Tr}
1939 \cmdmthsetext{Tree}[\treeset][\treesym]

\wotFun  ...
1940 \newcommand{\wotfun}{wot}
1941 \cmdmthfun{wot}[\wotfun]

1942 \fi
1943 %%*************************************************************************************%%

1944 %%*************************************************************************************%%
1945 %%** Format Tricks ********************************************************************%%
1946 %%*************************************************************************************%%
1947 \iffrm@

...  ...
1948 %%...

1949 \fi
1950 %%*************************************************************************************%%

1951 %%*************************************************************************************%%
1952 %%** Figure Tricks ********************************************************************%%
1953 %%*************************************************************************************%%
1954 \iffig@

1955 \RequirePackage{tikz}
1956 \usetikzlibrary{arrows,graphs,matrix,patterns,shapes}

1957 \tikzstyle{every node} =
1958   [draw = none, fill = none, black, thin]
1959 \tikzstyle{every edge} +=
1960   [black, thick]

1961 \tikzstyle{noall} =
1962   [draw = none, fill = none]
1963 \tikzstyle{nodraw} =
1964   [draw = none, fill = white]
1965 \tikzstyle{nofill} =
1966   [draw = black, fill = none]

1967 \ifwrpfig@
1968   % Wrapfig Package
1969   \RequirePackage{wrapfig}
1970 \fi

1971 \fi
1972 %%*************************************************************************************%%

1973 %%*************************************************************************************%%
1974 %%** Table Tricks *********************************************************************%%
1975 %%*************************************************************************************%%
1976 \iftab@

...  ...
1977 %%...
```

```
\fi
%%*****************************************************************************%%
%%*****************************************************************************%%
%%** Algorithm Tricks *********************************************************%%
%%*****************************************************************************%%
\ifalg@
\RequirePackage[ruled,vlined]{algorithm2e}
\DontPrintSemicolon
\SetInd{0.25em}{0.5em}
\setlength{\algomargin}{1.25em}
```

`\Signature` ...

```
\SetKw{Signature}{signature}
```

`\Macro, ...` ...

```
\SetKwFor{Macro}{macro}{}{}
\SetKwFor{Function}{function}{}{}
\SetKwFor{Procedure}{procedure}{}{}
```

`\Let` ...

```
\SetKwFor{Let}{let}{in}{}
```

`\True, \False` ...

```
\SetKw{True}{true}
\SetKw{False}{false}
```

`\From, ...` ...

```
\SetKw{From}{from}
\SetKw{To}{to}
\SetKw{DownTo}{downto}
```

`\GoTo, ...` ...

```
\SetKw{GoTo}{goto}
\SetKw{Break}{break}
\SetKw{Continue}{continue}
```

`\MIf, ...` ...

```
\SetKwIF{MIf}{MElseIf}{MElse}{\#if}{\#then}{\#else \#if}{\#else}{\#endif}
```

`\nlr` ...

```
\DeclareRobustCommand{\nlr}[1]
  {\addtocounter{AlgoLine}{1}%
   \nlset{\arabic{AlgoLine}-\addtocounter{AlgoLine}{#1}\arabic{AlgoLine}}}

\fi
%%*****************************************************************************%%
\endinput
⟨/package⟩
```

2 Change History

3 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

B

C

D

E

F

G

H

I

S

T

U

V

W

X

Y