

Michigan Department
of Transportation
1907J (07/2026)

MDOT REPORT OF COMPACTED LONGITUDINAL JOINT CORE DENSITY & PERCENT COMPACTION

DISTRIBUTION: ORIGINAL - Project Engineer, COPIES - Testing Laboratory and Plant Inspector

QA	QC							
CONTROL SECTION	JOB NUMBER	PROJECT LOCATION			MIXTURE TYPE(S)		MIX DESIGN NUMBER(S)	REPORT NUMBER
CONTRACTOR		PLANT NUMBER			PLANT LOCATION			
PROJECT ENGINEER		NAME OF TESTER (Please print)		QUALIFICATION NUMBER			LONG. JOINT SECTION NUMBER	
DATE								
Avg Core Thickness (After trimming)		”	”	”	”	”	”	”
CORE ID		J	J	J	J	J	J	J
A. WEIGHT OF CORE (in water), g								
B. WEIGHT OF CORE (surface dry), g								
C. WEIGHT OF CORE & PAN (oven dry), g								
PAN ID								
D. WEIGHT OF PAN, g								
E. DRY WEIGHT OF CORE (C - D), g								
F. VOLUME OF CORE (B - A), cc								
G. CORE SPECIFIC GRAVITY, (E / F)								
1911 - G _{mm} VALUE		-	-	-	-	-	-	-
1911 - G _{mm} VALUE		-	-	-	-	-	-	-
H. * AVERAGE G _{mm} VALUE								
I. % CORE COMPACTION (G / H) * 100								
J. LONGITUDINAL JOINT SECTION AVERAGE DENSITY								
LENGTH OF SUB-SECTION (Feet)								
LENGTH OF SECTION (Feet)								
EQ.1 Quality Adj.= (0.3333 * Density) - 30.1635								
EQ.2 Quality Adj.= (4.0850 * Density) - 360.31								
Section Total Quality Adj. (If using EQ. 1, max \$1.00)								
* Average G _{mm} value from the corresponding 1911 used to calculate % Core Compaction.								
REMARKS								