



# @stacks/network

Network configuration constants and utilities for Stacks.

The `@stacks/network` package exports network configurations and helper functions for working with different Stacks networks.

## Installation

>\_ Terminal

npm yarn pnpm bun

```
$ npm install @stacks/network
```

## Network constants

### STACKS\_MAINNET

`STACKS_MAINNET` provides the mainnet network configuration.

```
import { STACKS_MAINNET } from '@stacks/network';

console.log(STACKS_MAINNET);
// {
//   chainId: 1,
//   transactionVersion: 0,
//   peerNetworkId: 385875968,
//   magicBytes: "X2",
//   bootAddress: "SP000000000000000000000002Q6VF78",
//   addressVersion: {
//     singleSig: 22,
//     multiSig: 20,
//   },
//   client: {
//     baseUrl: "https://api.mainnet.hiro.so",
//   },
// }
```

## STACKS\_TESTNET

`STACKS_TESTNET` provides the testnet network configuration.

```
import { STACKS_TESTNET } from '@stacks/network';

console.log(STACKS_TESTNET.chainId); // 2147483648
```

## STACKS\_DEVNET / STACKS MOCKNET

`STACKS_DEVNET` provides the devnet network configuration.

```
import { STACKS_DEVNET, STACKS MOCKNET } from '@stacks/network';

// Use in transactions
import { makeSTXTokenTransfer } from '@stacks/transactions';

const tx = await makeSTXTokenTransfer({
  network: STACKS_DEVNET, // or STACKS MOCKNET
  // ... other options
});
```

## networkFromName

`networkFromName` returns a network configuration for a given name string.

### Signature

```
function networkFromName(name: 'mainnet' | 'testnet' | 'devnet' | 'mocknet'): {
```

### Parameters

| Name              | Type                                                      | Required |
|-------------------|-----------------------------------------------------------|----------|
| <code>name</code> | <code>'mainnet'   'testnet'   'devnet'   'mocknet'</code> | Yes      |

### Examples

```
import { networkFromName } from '@stacks/network';
```

```
const mainnet = networkFromName('mainnet'); // Same as STACKS_MAINNET
const testnet = networkFromName('testnet'); // Same as STACKS_TESTNET
const devnet = networkFromName('devnet'); // Same as STACKS_DEVNET
const mocknet = networkFromName('mocknet'); // Same as STACKS MOCKNET
```

## Using with transactions

```
import { networkFromName } from '@stacks/network';
import { makeContractCall } from '@stacks/transactions';

const network = networkFromName('testnet');

const tx = await makeContractCall({
  network,
  contractAddress: 'ST2ZRX0K27GW0SP3GJCEMHD95TQGJMKB7G9Y0X1MH',
  contractName: 'hello-world',
  functionName: 'say-hi',
  functionArgs: [],
  senderKey: privateKey
});
```

## clientFromNetwork

`clientFromNetwork` extracts the API client configuration from a network.

## Signature

```
function clientFromNetwork(network: StacksNetwork): Required<ClientOpts>
```

## Parameters

| Name                 | Type                       | Required | Description              |
|----------------------|----------------------------|----------|--------------------------|
| <code>network</code> | <code>StacksNetwork</code> | Yes      | Network configuration ok |

## Example

```
import { clientFromNetwork, STACKS_MAINNET } from '@stacks/network';
```

```
const client = clientFromNetwork(STACKS_MAINNET);
console.log(client.baseUrl); // 'https://api.mainnet.hiro.so'

// Use with custom fetch
const customClient = {
  ...client,
  fetch: customFetchFunction
};
```

## Network configuration properties

All network constants share these properties:

| Property                        | Type   | Description                           |
|---------------------------------|--------|---------------------------------------|
| <code>chainId</code>            | number | Unique identifier for the network     |
| <code>transactionVersion</code> | number | Transaction serialization version     |
| <code>peerNetworkId</code>      | number | P2P network identifier                |
| <code>magicBytes</code>         | string | Network magic bytes for serialization |
| <code>bootAddress</code>        | string | Boot contract address                 |

## Default values

The package also exports default configuration values:

```
import { DEFAULT_CHAIN_ID, DEFAULT_TRANSACTION_VERSION } from '@stacks/network'

console.log(DEFAULT_CHAIN_ID); // 1
console.log(DEFAULT_TRANSACTION_VERSION); // 0
```