```
CREATE DATABASE wordpress;
GRANT ALL PRIVILEGES ON wordpress.* TO 'WordPress'@'localhost' IDENTIFIED BY
'mot_de_passe';
FLUSH PRIVILEGES;
use wordpress:
wp commentmeta |
CREATE TABLE `wp_commentmeta` (
 'meta_id' bigint(20) unsigned NOT NULL AUTO_INCREMENT,
 `comment id` bigint(20) unsigned NOT NULL DEFAULT '0',
 `meta_key` varchar(255) COLLATE utf8mb4_unicode_520_ci DEFAULT NULL,
 'meta_value' longtext COLLATE utf8mb4_unicode 520 ci,
 PRIMARY KEY ('meta id'),
 KEY `comment_id` (`comment_id`),
 KEY 'meta_key' ('meta_key'(191))
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4 unicode 520 ci |
wp comments
CREATE TABLE `wp_comments` (
 `comment ID` bigint(20) unsigned NOT NULL AUTO INCREMENT,
 `comment_post_ID` bigint(20) unsigned NOT NULL DEFAULT '0',
 'comment author' tinytext COLLATE utf8mb4 unicode 520 ci NOT NULL,
 `comment_author_email` varchar(100) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 `comment author url` varchar(200) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 `comment_author_IP` varchar(100) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 'comment date' datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 'comment date gmt' datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 'comment content' text COLLATE utf8mb4 unicode 520 ci NOT NULL,
 `comment_karma` int(11) NOT NULL DEFAULT '0',
 `comment_approved` varchar(20) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT '1',
 `comment_agent` varchar(255) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 'comment type' varchar(20) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 `comment_parent` bigint(20) unsigned NOT NULL DEFAULT '0',
 `user_id` bigint(20) unsigned NOT NULL DEFAULT '0',
 PRIMARY KEY ('comment ID'),
 KEY `comment_post_ID` (`comment_post_ID`),
 KEY 'comment approved date gmt' ('comment approved', 'comment date gmt'),
 KEY `comment_date_gmt` (`comment_date_gmt`),
 KEY `comment_parent` (`comment_parent`),
 KEY 'comment author email' ('comment author email'(10))
) ENGINE=InnoDB AUTO_INCREMENT=2 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4_unicode_520_ci |
wp_links |
CREATE TABLE `wp_links` (
 'link id' bigint(20) unsigned NOT NULL AUTO INCREMENT,
 `link_url` varchar(255) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 `link_name` varchar(255) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT "
 `link_image` varchar(255) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 `link_target` varchar(25) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT "
 'link description' varchar(255) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 `link_visible` varchar(20) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT 'Y',
```

```
'link owner' bigint(20) unsigned NOT NULL DEFAULT '1',
 `link rating` int(11) NOT NULL DEFAULT '0',
 'link_updated' datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 `link rel` varchar(255) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 'link notes' mediumtext COLLATE utf8mb4 unicode 520 ci NOT NULL,
 `link_rss` varchar(255) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ".
 PRIMARY KEY ('link id'),
 KEY `link visible` (`link visible`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4 unicode 520 ci |
wp options
CREATE TABLE `wp_options` (
 `option_id` bigint(20) unsigned NOT NULL AUTO_INCREMENT,
 'option name' varchar(191) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 'option value' longtext COLLATE utf8mb4 unicode 520 ci NOT NULL,
 `autoload` varchar(20) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT 'yes',
 PRIMARY KEY (`option_id`),
 UNIQUE KEY `option_name` (`option_name`)
) ENGINE=InnoDB AUTO INCREMENT=261 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4 unicode 520 ci |
wp_postmeta |
CREATE TABLE `wp_postmeta` (
 'meta_id' bigint(20) unsigned NOT NULL AUTO_INCREMENT,
 'post id' bigint(20) unsigned NOT NULL DEFAULT '0',
 `meta_key` varchar(255) COLLATE utf8mb4_unicode_520_ci DEFAULT NULL,
 `meta_value` longtext COLLATE utf8mb4_unicode_520_ci,
 PRIMARY KEY ('meta id').
 KEY `post_id` (`post_id`),
 KEY `meta_key` (`meta_key`(191))
) ENGINE=InnoDB AUTO INCREMENT=79 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4 unicode 520 ci |
wp_posts |
CREATE TABLE `wp_posts` (
 `ID` bigint(20) unsigned NOT NULL AUTO_INCREMENT,
 'post author' bigint(20) unsigned NOT NULL DEFAULT '0',
 'post_date` datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 'post date gmt' datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 'post content' longtext COLLATE utf8mb4 unicode 520 ci NOT NULL,
 `post_title` text COLLATE utf8mb4_unicode_520_ci NOT NULL,
 'post excerpt' text COLLATE utf8mb4 unicode 520 ci NOT NULL,
 'post_status' varchar(20) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT 'publish',
 'comment status' varchar(20) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT 'open',
 'ping_status' varchar(20) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT 'open',
 'post_password` varchar(255) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 'post_name' varchar(200) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 `to_ping` text COLLATE utf8mb4_unicode_520_ci NOT NULL,
 'pinged' text COLLATE utf8mb4_unicode_520_ci NOT NULL,
 'post modified' datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 'post_modified_gmt` datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 'post content filtered` longtext COLLATE utf8mb4 unicode 520 ci NOT NULL,
```

```
'post_parent' bigint(20) unsigned NOT NULL DEFAULT '0',
 'guid' varchar(255) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 `menu_order` int(11) NOT NULL DEFAULT '0',
 'post_type' varchar(20) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT 'post',
 'post mime type' varchar(100) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 `comment_count` bigint(20) NOT NULL DEFAULT '0',
 PRIMARY KEY ('ID'),
 KEY 'post_name' ('post_name'(191)),
 KEY 'type_status_date' ('post_type', 'post_status', 'post_date', 'ID'),
 KEY 'post_parent' ('post_parent'),
 KEY 'post author' ('post author')
) ENGINE=InnoDB AUTO INCREMENT=33 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4_unicode_520_ci |
wp term relationships |
CREATE TABLE `wp_term_relationships` (
 `object_id` bigint(20) unsigned NOT NULL DEFAULT '0',
 'term taxonomy id' bigint(20) unsigned NOT NULL DEFAULT '0',
 `term order` int(11) NOT NULL DEFAULT '0',
 PRIMARY KEY ('object_id', 'term_taxonomy_id'),
 KEY 'term taxonomy id' ('term taxonomy id')
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4 unicode 520 ci |
wp_term_taxonomy |
CREATE TABLE 'wp term taxonomy' (
 `term_taxonomy_id` bigint(20) unsigned NOT NULL AUTO_INCREMENT,
 `term_id` bigint(20) unsigned NOT NULL DEFAULT '0',
 `taxonomy` varchar(32) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 'description' longtext COLLATE utf8mb4 unicode 520 ci NOT NULL,
 'parent' bigint(20) unsigned NOT NULL DEFAULT '0',
 'count' bigint(20) NOT NULL DEFAULT '0',
 PRIMARY KEY ('term taxonomy id'),
 UNIQUE KEY 'term id taxonomy' ('term id', 'taxonomy'),
 KEY 'taxonomy' ('taxonomy')
) ENGINE=InnoDB AUTO INCREMENT=5 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4 unicode 520 ci |
wp_termmeta |
CREATE TABLE `wp termmeta` (
 'meta id' bigint(20) unsigned NOT NULL AUTO INCREMENT,
 `term_id` bigint(20) unsigned NOT NULL DEFAULT '0',
 'meta_key' varchar(255) COLLATE utf8mb4_unicode_520_ci DEFAULT NULL,
 'meta value' longtext COLLATE utf8mb4 unicode 520 ci.
 PRIMARY KEY ('meta id'),
 KEY `term_id` (`term_id`),
 KEY 'meta_key' ('meta_key'(191))
) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4 unicode 520 ci |
wp_terms |
CREATE TABLE `wp_terms` (
 `term_id` bigint(20) unsigned NOT NULL AUTO_INCREMENT,
```

```
'name' varchar(200) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 'slug' varchar(200) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 `term_group` bigint(10) NOT NULL DEFAULT '0',
 PRIMARY KEY (`term_id`),
 KEY 'slug' ('slug'(191)),
 KEY `name` (`name`(191))
) ENGINE=InnoDB AUTO INCREMENT=5 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4 unicode 520 ci |
wp usermeta
CREATE TABLE `wp usermeta` (
 'umeta id' bigint(20) unsigned NOT NULL AUTO INCREMENT,
 `user_id` bigint(20) unsigned NOT NULL DEFAULT '0',
 'meta key' varchar(255) COLLATE utf8mb4 unicode 520 ci DEFAULT NULL,
 'meta value' longtext COLLATE utf8mb4 unicode 520 ci,
 PRIMARY KEY ('umeta id'),
 KEY `user_id` (`user_id`),
 KEY 'meta_key' ('meta_key'(191))
) ENGINE=InnoDB AUTO INCREMENT=49 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4_unicode_520_ci |
wp_users |
CREATE TABLE `wp users` (
 'ID' bigint(20) unsigned NOT NULL AUTO_INCREMENT,
 'user login' varchar(60) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 `user_pass` varchar(255) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 `user_nicename` varchar(50) COLLATE utf8mb4_unicode_520_ci NOT NULL DEFAULT ",
 'user email' varchar(100) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT".
 'user url' varchar(100) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT",
 'user registered' datetime NOT NULL DEFAULT '0000-00-00 00:00:00',
 'user activation key' varchar(255) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT",
 `user status` int(11) NOT NULL DEFAULT '0',
 'display name' varchar(250) COLLATE utf8mb4 unicode 520 ci NOT NULL DEFAULT ",
 PRIMARY KEY ('ID'),
 KEY `user_login_key` (`user_login`),
 KEY 'user nicename' ('user nicename'),
 KEY `user_email` (`user_email`)
) ENGINE=InnoDB AUTO INCREMENT=4 DEFAULT CHARSET=utf8mb4
COLLATE=utf8mb4_unicode_520_ci |
```