

Precoding-oriented Massive MIMO CSI Feedback Design



Fabrizio Carpi¹, Sivarama Venkatesan², Jinfeng Du², Harish Viswanathan², Siddharth Garg¹, Elza Erkip¹

COCIA BELL LABS

¹New York University, ²Nokia Bell Labs

Introduction

Channel state information (CSI) is crucial for FDD MIMO systems. We focus on task-oriented (semantic) compression:

- ► <u>Task</u>: MIMO precoding
- ► Goal: minimal CSI feedback overhead with maximal achievable rate

System Model

- \blacktriangleright MIMO system: one BS with N_t antennas, K single-antennas users
- ▶ Downlink signal with linear precoding: $\mathbf{x} = \sum_{k=1}^{K} \mathbf{v}_k s_k = \mathbf{V}\mathbf{s}$
- ► Received signal at k-th user: $y_k = \mathbf{h}_k^H \mathbf{v}_k s_k + \sum_{j \neq k} \mathbf{h}_k^H \mathbf{v}_j s_j + z_k$
- ► <u>Metric</u>: sum of achievable rates


$$R = \sum_{k=1}^{K} R_k = \sum_{k=1}^{K} \log_2 \left(1 + \frac{|\mathbf{h}_k^H \mathbf{v}_k|^2}{\sum_{j \neq k} |\mathbf{h}_k^H \mathbf{v}_j|^2 + \sigma^2} \right)$$
(1)

Optimization


Loss function including three possible metrics:

$$\mathcal{L}(\theta, \phi, \psi) = \mathcal{O} - \lambda \mathcal{R} + \gamma \mathcal{D}, \tag{2}$$

- ▶ Feedback overhead \mathcal{O} : entropy (feedback rate/overhead) of the pseudo-quantized features $\tilde{\mathbf{t}}_k = \mathbf{t}_k + \text{quantiz.noise}$ as in [1].
- ▶ Performance \mathcal{R} : achievable rates with precoding \mathbf{V} according to (1).
- \triangleright Distortion \mathcal{D} : reconstruction loss when estimating channels $\hat{\mathbf{H}}$ (e.g., MSE).
- \triangleright λ and γ determine the tradeoff between the three components.
- ▶ Precoding-oriented corresponds to $\{\lambda > 0, \gamma = 0\}$.



Conventional vs Semantic CSI 1-A) Channel Estimation 1) Pilots 2) Feedback (1-B) CSI compression: 3) Downlink data UE PROCESSING \mathcal{F} 2) Feedback 2-B) Determine beamforming 1) Pilots 1-A) Channel Estimation 3) Downlink data BS PROCESSING \mathcal{G} : 1-B) CSI compression: UE PROCESSING \mathcal{F}



References

- [1] J. Ballé, D. Minnen, S. Singh, S. J. Hwang, and N. Johnston, "Variational image compression with a scale hyperprior," in International Conference on Learning Representations (ICLR), 2018.
- 2] M. B. Mashhadi, Q. Yang, and D. Gündüz, "Distributed deep convolutional compression for massive MIMO CSI feedback," IEEE Transactions on Wireless Communications, vol. 20, no. 4, pp. 2621–2633, 2021.
- [3] F. Sohrabi, K. M. Attiah, and W. Yu, "Deep learning for distributed channel feedback and multiuser precoding in FDD massive MIMO," IEEE Transactions on Wireless Communications, vol. 20, no. 7, pp. 4044–4057, 2021.
- [4] F. Carpi, S. Venkatesan, J. Du, H. Viswanathan, S. Garg, and E. Erkip, "Precoding-oriented massive MIMO CSI feedback design," in IEEE International Conference on Communications (ICC), May 2023.

Acknowledgments

This work was done in part while F. Carpi was with Nokia Bell Labs. The work of F. Carpi, S. Garg, and E. Erkip was supported in part by the NYU WIRELESS Industrial Affiliates Program, by the NSF-Intel grant 2003182, and by the NSF grant 1925079.