ES1: Mettere in comunicazione il laptop-PT0 con IP 192.168.100.100 con il PC-PT-PC0 con IP 192.168.100.103

```
Device Name: Laptop0
Device Model: Laptop-PT

Port            Link   IP Address         IPv6 Address                              MAC Address
FastEthernet0   Up     192.168.100.100/24 <not set>                                 0090.2BAA.98AD
Bluetooth       Down   <not set>          <not set>                                 0002.4AD1.8C49

Gateway: 192.168.100.1
DNS Server: <not set>
Line Number:  <not set>

Physical Location: Intercity > Home City > Corporate Office > Laptop0
```

```
Device Name: PC0
Device Model: PC-PT

Port            Link   IP Address         IPv6 Address                              MAC Address
FastEthernet0   Up     192.168.100.103/24 <not set>                                 0060.4758.C5D8
Bluetooth       Down   <not set>          <not set>                                 0040.0BB9.782E

Gateway: 192.168.100.1
DNS Server: <not set>
Line Number:  <not set>

Physical Location: Intercity > Home City > Corporate Office > PC0
```

```
Cisco Packet Tracer PC Command Line 1.0
C:\>PING 192.168.100.103

Pinging 192.168.100.103 with 32 bytes of data:

Reply from 192.168.100.103: bytes=32 time<1ms TTL=128
Reply from 192.168.100.103: bytes=32 time<1ms TTL=128
Reply from 192.168.100.103: bytes=32 time<1ms TTL=128
Reply from 192.168.100.103: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.100.103:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
```

ES2: Mettere in comunicazione il laptop-PT0 con IP 192.168.100.100 con il laptop-PT2 con IP 192.168.200.100

```
Device Name: Laptop0
Device Model: Laptop-PT

Port            Link   IP Address         IPv6 Address                              MAC Address
FastEthernet0   Up     192.168.100.100/24 <not set>                                 0090.2BAA.98AD
Bluetooth       Down   <not set>          <not set>                                 0002.4AD1.8C49

Gateway: 192.168.100.1
DNS Server: <not set>
Line Number:  <not set>

Physical Location: Intercity > Home City > Corporate Office > Laptop0
```

```
Device Name: Laptop3
Device Model: Laptop-PT

Port            Link   IP Address         IPv6 Address                              MAC Address
FastEthernet0   Up     192.168.200.100/24 <not set>                                 0009.7C03.20E7
Bluetooth       Down   <not set>          <not set>                                 0002.1635.BC26

Gateway: 192.168.200.1
DNS Server: <not set>
Line Number:  <not set>

Physical Location: Intercity > Home City > Corporate Office > Laptop3
```



ES3: Mostrare qualitativamente (non inserite i valori) come cambiano «source MAC e destination MAC» e «source IP & destination IP» quando un pacchetto viene inviato dal Laptop-PT-Laptop0 verso Laptop-PT-Laptop2

At Device: Laptop0
Source: Laptop0
Destination: 192.168.200.101

In Layers	Out Layers
Layer7	Layer7
Layer6	Layer6
Layer5	Layer5
Layer4	Layer4
Layer3	Layer 3: IP Header Src. IP: 192.168.100.100, Dest. IP: 192.168.200.101 ICMP Message Type: 8
Layer2	Layer 2: Ethernet II Header 0090.2BAA.98AD >> 0001.641B.EA01
Layer1	Layer 1: Port(s): FastEthernet0

At Device: PC2
Source: Laptop0
Destination: 192.168.200.101

In Layers	Out Layers
Layer7	Layer7
Layer6	Layer6
Layer5	Layer5
Layer4	Layer4
Layer 3: IP Header Src. IP: 192.168.100.100, Dest. IP: 192.168.200.101 ICMP Message Type: 8	Layer 3: IP Header Src. IP: 192.168.200.101, Dest. IP: 192.168.100.100 ICMP Message Type: 0
Layer 2: Ethernet II Header 0001.641B.EA02 >> 000C.CF50.7E70	Layer 2: Ethernet II Header 000C.CF50.7E70 >> 0001.641B.EA02
Layer 1: Port FastEthernet0	Layer 1: Port(s): FastEthernet0

At Device: Laptop0
Source: Laptop0
Destination: 192.168.200.101

In Layers	Out Layers
Layer7	Layer7
Layer6	Layer6
Layer5	Layer5
Layer4	Layer4
Layer 3: IP Header Src. IP: 192.168.200.101, Dest. IP: 192.168.100.100 ICMP Message Type: 0	Layer3
Layer 2: Ethernet II Header 0001.641B.EA01 >> 0090.2BAA.98AD	Layer2
Layer 1: Port FastEthernet0	Layer1