

## REPORT - GEOR001669

## Unconfined compressive strength of intact rock and salt core specimens (According to ASTM 7012 D)

## (The test performed according to Lab procedure № 1200)

No.	BS - 30
Depth of tested specimen, m.	-

Project No.	609029
Project Name	Kokhav Hayarden
Date of sampling	-
Date of testing	04/07/2018

Rock description:	Amygdaloidal Basalt
-------------------	---------------------

## Note:

Х	The test was performed at natural moisture content.		
	The test was performed after saturation of	48	hours

Specimen conditions:		Initially	After Saturation
Wet Mass	gr	343.40	
Diameter	cm	4.78	
Length	cm	9.84	
Area	cm <sup>2</sup>	17.90	
Height to diameter ratio		2.06	
Dry Unit Weight	kg/m <sup>3</sup>	1740	
Water content	%	12.1	
Void Ratio	-	-	-
Water Absorpsion	%	-	-

Test Results:	
Maximal Applied Force in failure, kN:	13.91
Unconfined Compressive Stress in failure, MPa :	7.77

Test Conditions:	
Test Time t, sec	271
Temperature during the test T, C°	25



Performed by:

Andrey Makeev Lab. Technician

- 1. This report is the sole property of the Building and Infrastructure Lab Ltd until the Client has fulfilled all his obligations toward the Lab.
- 2. The results pertain to the tested sample material only.
- 3. This report should be taken as one whole report and not to be copied or published in parts or pieces of any kind.
- 4. The data and details of sampling/ testing are according to the information as provided by the client or his representative.

\*\*\*\*\*\*\* סוף דו"ח / תעודה