

DATA MINING PRE- PROCESSING

Outline

1. Why data preprocessing?
2. Data cleaning
3. Data integration and transformation
4. Data reduction
5. Discretization and concept hierarchy generation
6. Summary



1

Why Data Preprocessing?

Why Data Preprocessing?

- Data in the real world is dirty
 - **incomplete**: lacking attribute values, lacking certain attributes of interest, or containing only aggregate data
 - e.g., occupation=""
 - **noisy**: containing errors or outliers
 - e.g., Salary="-10"
 - **inconsistent**: containing discrepancies in codes or names
 - e.g., Age="42" Birthday="03/07/1997"
 - e.g., Was rating "1,2,3", now rating "A, B, C"
 - e.g., discrepancy between duplicate records



Why Data Preprocessing?

- Incomplete data comes from
 - n/a data value when collected
 - different consideration between the time when the data was collected and when it is analyzed
 - human/hardware/software problems
- Noisy data comes from the process of data
 - collection
 - entry
 - transmission
- Inconsistent data comes from
 - Different data sources

Why Data Preprocessing?

- No quality data, no quality mining results!
 - Quality decisions must be based on quality data
e.g., duplicate or missing data may cause incorrect or even misleading statistics.
 - Data warehouse needs consistent integration of quality data
- *Data extraction, cleaning, and transformation comprises the majority of the work of building a data warehouse. —Bill Inmon*


Why Data Preprocessing?

- A well-accepted multidimensional view:
 - Accuracy
 - Completeness
 - Consistency
 - Timeliness
 - Believability
 - Value added
 - Interpretability
 - Accessibility
- Broad categories:
 - intrinsic, contextual, representational, and accessibility.

Major Tasks in Data Preprocessing

- Data cleaning
 - Fill in missing values, smooth noisy data, identify or remove outliers, and resolve inconsistencies
- Data integration
 - Integration of multiple databases, data cubes, files, or notes
- Data transformation
 - Normalization (scaling to a specific range)
 - Aggregation
- Data reduction
 - Obtains reduced representation in volume but produces the same or similar analytical results
 - Data discretization: with particular importance, especially for numerical data
 - Data aggregation, dimensionality reduction, data compression, generalization

Forms of data preprocessing



What is Data?

Collection of data objects and their attributes

An attribute is a property or characteristic of an object

- Examples: eye color of a person, temperature, etc.
- Attribute is also known as variable, field, characteristic, or feature

A collection of attributes describe an object

- Object is also known as record, point, case, sample, entity, or instance

Objects

Attributes

Tid	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Attribute Values

- Attribute values are numbers or symbols assigned to an attribute
- Distinction between attributes and attribute values
 - Same attribute can be mapped to different attribute values
 - Example: height can be measured in feet or meters
 - Different attributes can be mapped to the same set of values
 - Example: Attribute values for ID and age are integers
 - But properties of attribute values can be different
 - ID has no limit but age has a maximum and minimum value

Types of Attributes

- There are different types of attributes
 - **Nominal**
 - Examples: ID numbers, eye color, zip codes
 - **Ordinal**
 - Examples: rankings (e.g., taste of potato chips on a scale from 1-10), grades, height in {tall, medium, short}
 - **Interval**
 - Examples: calendar dates, temperatures in Celsius or Fahrenheit.
 - **Ratio**
 - Examples: temperature in Kelvin, length, time, counts

Properties of Attribute Values

- The type of an attribute depends on which of the following properties it possesses:
 - Distinctness: $= \neq$
 - Order: $< >$
 - Addition: $+ -$
 - Multiplication: $* /$
- Nominal attribute: distinctness
- Ordinal attribute: distinctness & order
- Interval attribute: distinctness, order & addition
- Ratio attribute: all 4 properties

Discrete and Continuous Attributes

- Discrete Attribute
 - Has only a finite or countably infinite set of values
 - Examples: zip codes, counts, or the set of words in a collection of documents
 - Often represented as integer variables.
 - Note: binary attributes are a special case of discrete attributes
- Continuous Attribute
 - Has real numbers as attribute values
 - Examples: temperature, height, or weight.
 - Practically, real values can only be measured and represented using a finite number of digits.
 - Continuous attributes are typically represented as floating-point variables.

Types of data sets

- Record
 - Data Matrix
 - Document Data
 - Transaction Data
- Graph
 - World Wide Web
 - Molecular Structures
- Ordered
 - Spatial Data
 - Temporal Data
 - Sequential Data
 - Genetic Sequence Data



2

Data Cleaning

To be continued