

DATA MINING PRE- PROCESSING

Outline

1. Why data preprocessing?
2. Data cleaning
3. Data integration and transformation
4. Data reduction
5. Discretization and concept hierarchy generation
6. Summary



2



Data Cleaning

Data Quality

- What kinds of data quality problems?
- How can we detect problems with the data?
- What can we do about these problems?
- Examples of data quality problems:
 - Noise and outliers
 - missing values
 - duplicate data


Noise

- Noise refers to modification of original values
 - Examples: distortion of a person's voice when talking on a poor phone and "snow" on television screen



Outliers

- Outliers are data objects with characteristics that are considerably different than most of the other data objects in the data set



Missing Values

- Reasons for missing values
 - Information is not collected
(e.g., people decline to give their age and weight)
 - Attributes may not be applicable to all cases
(e.g., annual income is not applicable to children)
- Handling missing values
 - Eliminate Data Objects
 - Estimate Missing Values
 - Ignore the Missing Value During Analysis
 - Replace with all possible values (weighted by their probabilities)

Duplicate Data

- Data set may include data objects that are duplicates, or almost duplicates of one another
 - Major issue when merging data from heterogenous sources
- Examples:
 - Same person with multiple email addresses
- Data cleaning
 - Process of dealing with duplicate data issues

Data Cleaning

- Data cleaning tasks
 - Fill in missing values
 - Identify outliers and smooth out noisy data
 - Correct inconsistent data
 - Resolve redundancy caused by data integration

Missing Data


- Data is not always available
 - E.g., many tuples have no recorded value for several attributes, such as customer income in sales data
- Missing data may be due to
 - equipment malfunction
 - inconsistent with other recorded data and thus deleted
 - data not entered due to misunderstanding
 - certain data may not be considered important at the time of entry
 - not register history or changes of the data
- Missing data may need to be inferred

How to Handle Missing Data?

- ✓ Ignore the tuple: usually done when class label is missing (assuming the task is classification—not effective in certain cases)
- ✓ Fill in the missing value **manually**: tedious + infeasible?
- ✓ Fill in it automatically with
 - Use a **global constant** to fill in the missing value: e.g., “unknown”, a new class?!
 - Use the **attribute mean** to fill in the missing value
 - Use the **attribute mean for all samples of the same class** to fill in the missing value: smarter
 - Use the **most probable value** to fill in the missing value: inference-based such as regression, Bayesian formula, decision tree


Outlier Detection

- ✓ Univariate outlier detection
 - scatter plot
 - box plot
 - standardized data
- ✓ Multivariate outlier detection



Univariate outlier:
scatterplot

Univariate outlier:
boxplot



Noisy Data

- Q: What is noise?
- A: Random error in a measured variable.
- Incorrect attribute values may be due to
 - faulty data collection instruments
 - data entry problems
 - data transmission problems
 - technology limitation
 - inconsistency in naming convention
- Other data problems which requires data cleaning
 - duplicate records
 - incomplete data
 - inconsistent data

How to Handle Noisy Data?

- ✓ Binning method:
 - first sort data and partition into (equi-depth) bins
 - then one can smooth by bin means, smooth by bin median, smooth by bin boundaries, etc.
 - used also for discretization (discussed later)
- ✓ Clustering
 - detect and remove outliers
- ✓ Semi-automated method: combined computer and human inspection
 - detect suspicious values and check manually
- ✓ Regression
 - smooth by fitting the data into regression functions

Simple Discretization Methods: Binning

- **Equal-width** (distance) partitioning:
 - It divides the range into N intervals of equal size: uniform grid
 - if A and B are the lowest and highest values of the attribute, the width of intervals will be: $W = (B-A)/N$.
 - The most straightforward
 - But outliers may dominate presentation
 - Skewed data is not handled well.
- **Equal-depth** (frequency) partitioning:
 - It divides the range into N intervals, each containing approximately same number of samples
 - Good data scaling
 - Managing categorical attributes can be tricky.

Binning Methods for Data Smoothing

- * Sorted data for price (in dollars): 4, 8, 9, 15, 21, 21, 24, 25, 26, 28, 29, 34
- * Partition into (equi-depth) bins:
 - Bin 1: 4, 8, 9, 15
 - Bin 2: 21, 21, 24, 25
 - Bin 3: 26, 28, 29, 34

- * Smoothing by bin means:
 - Bin 1: 9, 9, 9, 9
 - Bin 2: 23, 23, 23, 23
 - Bin 3: 29, 29, 29, 29
- * Smoothing by bin boundaries:
 - Bin 1: 4, 4, 4, 15
 - Bin 2: 21, 21, 25, 25
 - Bin 3: 26, 26, 26, 34

How to Handle Inconsistent Data?

- Manual correction using external references
- Semi-automatic using various tools
 - To detect violation of known functional dependencies and data constraints
 - To correct redundant data



3

Data Integration and Transformation

To be continued