

# 1 A Learning Algorithm for Optimal Face Recognition in Dynamic Environments

There have been many different challenges for face recognition like lighting, occlusion, pose variation etc , and there's no algorithm which can handle all the challenges together, different face recognition algorithms handle different challenges to different extent. So we try to propose a new novel algorithm named Adaptive Learning Algorithm, which is similar to simple perceptron learning algorithm in neural networks.

A Learning Algorithm for Optimal Face Recognition in Dynamic Environments :

## 1.0.1 Pre-requisite :

- (1) Identification of mapping ( which algorithm suits well for which database )
- (2) Mapping is stored for persistence usage ( Using pickle in python or ObjectSerialization in java )

## 1.0.2 Algorithm :

During the testing two cases are possible :

- 1) The given test database might previously be trained
- 2) The given test database might be new one ( previously might not be trained )

### pseudo code of the adaptive learning algorithm :

```
function checkifgivenistrained(test,train) :
begin :
    (1) extracting the 16 metrics of the randomly selected image in test db
    (2) extracting the 16 metrics of the same [index] randomly selected
        image in train db
        Note: see below for the 16 metrics used
    (3) if (all the metrics match )
        return (1)
end :

function findoutsimilarity() :
begin :
    (1) Obtain the histogram of the entire test database
    (2) Obtain the histogram of the previously trained databases
    (3) Compare the test database histogram with the histogram of all the
        previously trained databases
    (4) select the algorithm of the database which ever matches the most
    (5) return the algorithm
end :
```

```

    ALMain() :
begin:
    for each database in previously trained databases :
        beginfor:
            if(checkifgivenistrained):
                (1) print database identified
                (2) from previously created mapping extract the algo
                    and run the test database using this algorithm
                (3) exit ( means executed properly coz db identified
                    from previous trained one )
            endfor:

        if ( testdatabaseisnew ) :
            begin:
                (1) algo=findoutsimilarity()
                (2) run the given test database with the algo (obtained in
                    previous step )
                (3) Once algo is identified do the following steps in block
                    begin :
                        (1)Add the entire new database to our trained set.
                        (2)Update the mapping data file.
                        (3)So that when ever next time same database comes,
                            our algorithm would have learnt which face-recognition
                            algorithm to use.
                    end :
            end:
        end:
    end:
end:

```