RSpec

Freddy Alejadro Cuellar Garcia Brayan Fabian Prieto Cortes Julian Garzon Jimenez TDD- Test-driven Development (Desarrollo dirigido por test.

```
RSpec.describe "something" do
it "does something" do
end
end
```

```
context 'when logged in' do
  it { is_expected.to respond_with 200 }
end
context 'when logged out' do
  it { is_expected.to respond_with 401 }
end
```

Pruebas aisladas y no aisladas

```
it { should respond_with_content_type(:json) }
it { should assign_to(:resource) }
```

```
it 'creates a resource' do
  response.should respond_with_content_type(:json)
  response.should assign_to(:resource)
end
```

Ver todos los posibles casos

```
describe '#destroy' do
  context 'when resource is found' do
    it 'responds with 200'
    it 'shows the resource'
  end
  context 'when resource is not found' do
    it 'responds with 404'
  end
  context 'when resource is not owned' do
    it 'responds with 404'
  end
end
```

```
let(:grade_levels) { [1, 2, 3] }
```

```
expect(actual).to be > expected
expect(actual).to be >= expected
expect(actual).to be <= expected
expect(actual).to be < expected
expect(actual).to be_between(minimum, maximum).inclusive
expect(actual).to be_between(minimum, maximum).exclusive
expect(actual).to match(/expression/)
expect(actual).to be_within(delta).of(expected)
expect(actual).to start_with expected
expect(actual).to end_with expected

# NOTE: `expect` does not support `=~` matcher.</pre>
```

```
expect(actual).to eql(expected) # passes if actual.eql?(expected)
expect(actual).to equal(expected) # passes if actual.equal?(expected)
# NOTE: `expect` does not support `==` matcher.
```

```
group :development, :test do
  gem 'rspec-rails', '~> 3.7'
end
```

bundle install

rails generate rspec:install

- rspec
- spec/spec_helper.rb
- spec/rails_helper.rb