DREAMS · Diseño de base de datos

D.E.R., relaciones y estructura documentada

Consolidado el 11/11/2026 sobre main 6e4647c9c6f44708a4e39a3b26e183718f2314e6.

Metadatos estructurales documentados el 03/11/2026; no lectura remota nueva ni datos personales. No representa los esquemas internos completos de Supabase.

El alcance conserva los metadatos documentados el 03/11/2026: nueve tablas de public y sólo auth.users.id como frontera del servicio de autenticación. No es un dump, no contiene filas de clientes, contraseñas o hashes y no representa todo el esquema interno de Supabase. Esta limpieza no hizo una nueva consulta a producción.

La página siguiente conserva el D.E.R. vectorial completo. Las páginas posteriores muestran todas las columnas con posición, tipo PostgreSQL, nulabilidad y DEFAULT, las claves y restricciones, y los 32 índices estructurales; no se pierde información única del JSON retirado.

Se distinguen tablas activas, el histórico de pedidos y favorites retirado de la interfaz. El checkout académico intercambia tickets firmados: no inserta pedidos comerciales, no cobra ni cambia stock.

Las migraciones ejecutables y rollback permanecen en app/supabase/. El PDF documenta estructura; no reemplaza esos archivos ni autoriza aplicar cambios.

Origen del archivo de metadatos anterior: commit 305c5fd6ca0f5a72792c4f5e64fa60ac13a70828. La fecha de consolidación no se presenta como fecha de una nueva verificación remota.

DREAMS · D.E.R. remoto verificado03/11/2026 · sólo metadatos

public.account_carts · ACTIVA

PK FK user_id : uuid NOT NULL

items : jsonb NOT NULL

revision : int8 NOT NULL

updated_at : timestamptz NOT NULL

public.account_cart_operations · ACTIVA

PK FK user_id : uuid NOT NULL

PK operation_id : uuid NOT NULL

operation : jsonb NOT NULL

created_at : timestamptz NOT NULL

PK compuesta: user_id, operation_id

user_id → user_id

1 — 0..N

user_id → id

0..1 — 1

auth.users · proveedor Auth

PK id : uuid

Resto de campos no consultados

public.products · ACTIVA

PK id : int8 NOT NULL

marca : text NOT NULL

name : text NOT NULL

gender : text NOT NULL

price : numeric NOT NULL

stock : int4 NOT NULL

image_url : text NOT NULL

featured : bool NOT NULL

public.inquiries · ACTIVA

PK id : int8 NOT NULL

FK user_id : uuid NULL

FK product_id : int8 NULL

product_name : text NOT NULL

user_name : text NULL

user_email : text NULL

created_at : timestamptz NOT NULL

product_id → id

0..1 — 0..N

1 — 0..N

id → id

1 — 0..1

public.profiles · ACTIVA

PK FK id : uuid NOT NULL

name : text NOT NULL

role : text NOT NULL

created_at : timestamptz NOT NULL

user_id → id

0..1 — 0..N

public.favorites · HISTÓRICA

PK FK user_id : uuid NOT NULL

PK FK product_id : int8 NOT NULL

created_at : timestamptz NOT NULL

PK compuesta: user_id, product_id

user_id → id

1 — 0..N

user_id → id

0..1 — 0..N

public.reviews · ACTIVA

PK id : int8 NOT NULL

FK user_id : uuid NULL

user_name : text NOT NULL

rating : int4 NOT NULL

comment : text NOT NULL

created_at : timestamptz NOT NULL

operation_id : uuid NULL

user_id → id

1 — 0..N

public.coupons · ACTIVA

PK id : int8 NOT NULL

code : text NOT NULL

discount_percent : numeric NOT NULL

active : bool NOT NULL

expires_at : timestamptz NULL

max_uses : int4 NULL

per_user_limit : int4 NULL

minimum_purchase : numeric NULL

conditions : jsonb NOT NULL

created_at : timestamptz NOT NULL

updated_at : timestamptz NOT NULL

public.orders · HISTORIAL / consultas

PK id : uuid NOT NULL

FK user_id : uuid NOT NULL

provider : text NOT NULL

status : text NOT NULL

subtotal : numeric NOT NULL

discount : numeric NOT NULL

total : numeric NOT NULL

FK coupon_id : int8 NULL

items : jsonb NOT NULL

coupon_id → id

0..1 — 0..N

Relaciones y alcance

PK identifica una fila; FK exige que exista el padre indicado. En una PK compuesta las columnas funcionan juntas. 1 exige un padre; 0..1 permite ausencia; 0..N admite varios hijos. Una FK no obliga a cada padre a tener hijos.

auth.users → profiles y auth.users → account_carts permiten cero o un registro hijo por usuario. account_carts → account_cart_operations permite muchas operaciones, identificadas por (user_id, operation_id). Favorites tiene PK compuesta (user_id, product_id) y se conserva como tabla histórica, sin interfaz activa.

Inquiries puede tener producto y usuario nulos. Reviews puede perder su referencia de usuario por ON DELETE SET NULL. Orders exige un perfil, permite cupón nulo y conserva un snapshot de artículos. Las definiciones exactas y acciones de borrado figuran por tabla.

Los artículos JSONB de account_carts.items y orders.items se asocian lógicamente con productos: no son FK. El diagrama no dibuja una relación inexistente.

RLS aparece habilitado en las nueve tablas del relevamiento. Eso no prueba por sí solo todas las políticas ni grants; no se revalidaron en esta tarea. Auth.users se limita a id uuid / PRIMARY KEY(id).

Discrepancias e historial

app/supabase/schema.sql es un baseline histórico y usa products.brand. Los metadatos documentados usan marca; la API expone brand, el adaptador Node detecta ambos y el Worker oficial utiliza marca. Reproducir el baseline requiere revisar esta adaptación; no se cambia ni migra producción.

Orders, coupons, carritos e identificadores de operación se incorporan mediante migraciones; el baseline no es un esquema remoto completo.

La migración 20261105160613_modularize_account_cart.sql reemplaza la RPC del carrito por auxiliares invoker. No cambia entidades, columnas, PK/FK, cardinalidades ni datos del diagrama. La definición histórica de 53 líneas y su rollback se conservan; no se reescriben para alterar el conteo académico.

El índice único parcial de opiniones cubre (user_id, operation_id) cuando operation_id no es NULL. Los identificadores de proveedor de orders también tienen índices únicos parciales. No son FK adicionales.

Las fuentes DOT/PNG/JSON documentales se retiran después de consolidar su contenido por solicitud expresa. No se ofrece un comando de regeneración que dependa de fuentes ya retiradas; el historial Git conserva la procedencia.

public.account_cart_operations

ACTIVA · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · user_id	uuid / uuid	NO PK, FK	— (sin DEFAULT)
2 · operation_id	uuid / uuid	NO PK	— (sin DEFAULT)
3 · operation	jsonb / jsonb	NO	— (sin DEFAULT)
4 · created_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.account_cart_operations_pkey · PK

```
PRIMARY KEY (user_id, operation_id)
```

public.account_cart_operations_user_id_fkey · FK

```
FOREIGN KEY (user_id) REFERENCES account_carts(user_id) ON DELETE CASCADE
```

Índices estructurales

account_cart_operations_pkey

```
CREATE UNIQUE INDEX account_cart_operations_pkey ON public.account_cart_operations USING btree (user_id, operation_id)
```

public.account_carts

ACTIVA · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · user_id	uuid / uuid	NO PK, FK	— (sin DEFAULT)
2 · items	jsonb / jsonb	NO	'[]'::jsonb
3 · revision	bigint / int8	NO	0
4 · updated_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.account_carts_items_check · CHECK

```
CHECK (((jsonb_typeof(items) = 'array'::text) AND (jsonb_array_length(items) <= 30)))
```

public.account_carts_pkey · PK

```
PRIMARY KEY (user_id)
```

public.account_carts_revision_check · CHECK

```
CHECK ((revision >= 0))
```

public.account_carts_user_id_fkey · FK

```
FOREIGN KEY (user_id) REFERENCES auth.users(id) ON DELETE CASCADE
```

Índices estructurales

account_carts_pkey

```
CREATE UNIQUE INDEX account_carts_pkey ON public.account_carts USING btree (user_id)
```

public.coupons

ACTIVA · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · id	bigint / int8	NO PK	— (sin DEFAULT)
2 · code	text / text	NO UQ	— (sin DEFAULT)
3 · discount_percent	numeric / numeric	NO	— (sin DEFAULT)
4 · active	boolean / bool	NO	true
5 · expires_at	timestamp with time zone / timestamptz	YES	— (sin DEFAULT)
6 · max_uses	integer / int4	YES	— (sin DEFAULT)
7 · per_user_limit	integer / int4	YES	— (sin DEFAULT)
8 · minimum_purchase	numeric / numeric	YES	— (sin DEFAULT)
9 · conditions	jsonb / jsonb	NO	'{}'::jsonb
10 · created_at	timestamp with time zone / timestamptz	NO	now()
11 · updated_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.coupons_code_format · CHECK

```
CHECK (((code = upper(code)) AND (code ~ '^[A-Z0-9_-]{3,40}$'::text)))
```

public.coupons_code_key · UNIQUE

```
UNIQUE (code)
```

public.coupons_conditions_object · CHECK

```
CHECK ((jsonb_typeof(conditions) = 'object'::text))
```

public.coupons_discount_range · CHECK

```
CHECK (((discount_percent > (0)::numeric) AND (discount_percent <= (100)::numeric)))
```

public.coupons_max_uses_positive · CHECK

```
CHECK (((max_uses IS NULL) OR (max_uses > 0)))
```

public.coupons_minimum_purchase_positive · CHECK

```
CHECK (((minimum_purchase IS NULL) OR (minimum_purchase >= (0)::numeric)))
```

public.coupons_per_user_limit_positive · CHECK

```
CHECK (((per_user_limit IS NULL) OR (per_user_limit > 0)))
```

public.coupons_pkey · PK

```
PRIMARY KEY (id)
```

Índices estructurales

coupons_active_code_idx

```
CREATE INDEX coupons_active_code_idx ON public.coupons USING btree (code) WHERE active
```

coupons_code_key

```
CREATE UNIQUE INDEX coupons_code_key ON public.coupons USING btree (code)
```

coupons_expiry_idx

```
CREATE INDEX coupons_expiry_idx ON public.coupons USING btree (expires_at) WHERE (expires_at IS NOT NULL)
```

coupons_pkey

```
CREATE UNIQUE INDEX coupons_pkey ON public.coupons USING btree (id)
```

public.favorites

HISTÓRICA / interfaz retirada · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · user_id	uuid / uuid	NO PK, FK	— (sin DEFAULT)
2 · product_id	bigint / int8	NO PK, FK	— (sin DEFAULT)
3 · created_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.favorites_pkey · PK

```
PRIMARY KEY (user_id, product_id)
```

public.favorites_product_id_fkey · FK

```
FOREIGN KEY (product_id) REFERENCES products(id) ON DELETE CASCADE
```

public.favorites_user_id_fkey · FK

```
FOREIGN KEY (user_id) REFERENCES profiles(id) ON DELETE CASCADE
```

Índices estructurales

favorites_pkey

```
CREATE UNIQUE INDEX favorites_pkey ON public.favorites USING btree (user_id, product_id)
```

favorites_product_idx

```
CREATE INDEX favorites_product_idx ON public.favorites USING btree (product_id)
```

favorites_user_idx

```
CREATE INDEX favorites_user_idx ON public.favorites USING btree (user_id)
```

public.inquiries

ACTIVA · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · id	bigint / int8	NO PK	— (sin DEFAULT)
2 · user_id	uuid / uuid	YES FK	— (sin DEFAULT)
3 · product_id	bigint / int8	YES FK	— (sin DEFAULT)
4 · product_name	text / text	NO	— (sin DEFAULT)
5 · user_name	text / text	YES	— (sin DEFAULT)
6 · user_email	text / text	YES	— (sin DEFAULT)
7 · created_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.inquiries_pkey · PK

```
PRIMARY KEY (id)
```

public.inquiries_product_id_fkey · FK

```
FOREIGN KEY (product_id) REFERENCES products(id) ON DELETE SET NULL
```

public.inquiries_user_id_fkey · FK

```
FOREIGN KEY (user_id) REFERENCES profiles(id) ON DELETE SET NULL
```

Índices estructurales

inquiries_created_idx

```
CREATE INDEX inquiries_created_idx ON public.inquiries USING btree (created_at DESC)
```

inquiries_pkey

```
CREATE UNIQUE INDEX inquiries_pkey ON public.inquiries USING btree (id)
```

inquiries_product_idx

```
CREATE INDEX inquiries_product_idx ON public.inquiries USING btree (product_id)
```

inquiries_user_idx

```
CREATE INDEX inquiries_user_idx ON public.inquiries USING btree (user_id)
```

public.orders

HISTORIAL / consultas Admin · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · id	uuid / uuid	NO PK	gen_random_uuid()
2 · user_id	uuid / uuid	NO FK	— (sin DEFAULT)
3 · provider	text / text	NO	— (sin DEFAULT)
4 · provider_preference_id	text / text	YES	— (sin DEFAULT)
5 · provider_payment_id	text / text	YES	— (sin DEFAULT)
6 · status	text / text	NO	'created'::text
7 · status_detail	text / text	YES	— (sin DEFAULT)
8 · currency	text / text	NO	'ARS'::text
9 · subtotal	numeric / numeric	NO	— (sin DEFAULT)
10 · discount	numeric / numeric	NO	0
11 · total	numeric / numeric	NO	— (sin DEFAULT)
12 · coupon_id	bigint / int8	YES FK	— (sin DEFAULT)
13 · coupon_code	text / text	YES	— (sin DEFAULT)
14 · coupon_percent	numeric / numeric	YES	— (sin DEFAULT)
15 · items	jsonb / jsonb	NO	— (sin DEFAULT)
16 · paid_at	timestamp with time zone / timestamptz	YES	— (sin DEFAULT)
17 · created_at	timestamp with time zone / timestamptz	NO	now()
18 · updated_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.orders_check · CHECK

```
CHECK (((discount >= (0)::numeric) AND (discount <= subtotal)))
```

public.orders_check1 · CHECK

```
CHECK (((total >= (0)::numeric) AND (total = (subtotal - discount))))
```

public.orders_coupon_id_fkey · FK

```
FOREIGN KEY (coupon_id) REFERENCES coupons(id) ON DELETE SET NULL
```

public.orders_coupon_snapshot · CHECK

```
CHECK ((((coupon_code IS NULL) AND (coupon_percent IS NULL) AND (discount = (0)::numeric)) OR
((coupon_code = upper(coupon_code)) AND (coupon_percent > (0)::numeric) AND (coupon_percent <=
(100)::numeric) AND (discount > (0)::numeric))))
```

public.orders_currency_check · CHECK

```
CHECK ((currency ~ '^[A-Z]{3}$'::text))
```

public.orders_items_array · CHECK

```
CHECK (((jsonb_typeof(items) = 'array'::text) AND (jsonb_array_length(items) > 0)))
```

public.orders_pkey · PK

```
PRIMARY KEY (id)
```

public.orders_provider_check · CHECK

```
CHECK ((provider = ANY (ARRAY['mercado_pago'::text, 'demo'::text])))
```

public.orders_status_check · CHECK

```
CHECK ((status = ANY (ARRAY['created'::text, 'approved'::text, 'rejected'::text, 'pending'::text,
'cancelled'::text, 'error'::text])))
```

public.orders_status_detail_check · CHECK

```
CHECK (((status_detail IS NULL) OR (char_length(status_detail) <= 160)))
```

public.orders_subtotal_check · CHECK

```
CHECK ((subtotal >= (0)::numeric))
```

public.orders_user_id_fkey · FK

```
FOREIGN KEY (user_id) REFERENCES profiles(id) ON DELETE RESTRICT
```

Índices estructurales

orders_coupon_idx

```
CREATE INDEX orders_coupon_idx ON public.orders USING btree (coupon_id) WHERE (coupon_id IS NOT NULL)
```

orders_pkey

```
CREATE UNIQUE INDEX orders_pkey ON public.orders USING btree (id)
```

orders_provider_payment_uidx

```
CREATE UNIQUE INDEX orders_provider_payment_uidx ON public.orders USING btree (provider,
provider_payment_id) WHERE (provider_payment_id IS NOT NULL)
```

orders_provider_preference_uidx

```
CREATE UNIQUE INDEX orders_provider_preference_uidx ON public.orders USING btree (provider,
provider_preference_id) WHERE (provider_preference_id IS NOT NULL)
```

orders_status_created_idx

```
CREATE INDEX orders_status_created_idx ON public.orders USING btree (status, created_at DESC)
```

orders_user_created_idx

```
CREATE INDEX orders_user_created_idx ON public.orders USING btree (user_id, created_at DESC)
```

public.products

ACTIVA · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · id	bigint / int8	NO PK	— (sin DEFAULT)
2 · marca	text / text	NO UQ conjunta	— (sin DEFAULT)
3 · name	text / text	NO UQ conjunta	— (sin DEFAULT)
4 · gender	text / text	NO	— (sin DEFAULT)
5 · category	text / text	NO	'diseñador'::text
6 · size_ml	integer / int4	NO	— (sin DEFAULT)
7 · price	numeric / numeric	NO	— (sin DEFAULT)
8 · stock	integer / int4	NO	0
9 · intensity	integer / int4	NO	— (sin DEFAULT)
10 · family	text / text	NO	— (sin DEFAULT)
11 · top_notes	text / text	NO	— (sin DEFAULT)
12 · heart_notes	text / text	NO	— (sin DEFAULT)
13 · base_notes	text / text	NO	— (sin DEFAULT)
14 · description	text / text	NO	— (sin DEFAULT)
15 · image_url	text / text	NO	— (sin DEFAULT)
16 · featured	boolean / bool	NO	false
17 · created_at	timestamp with time zone / timestamptz	NO	now()
18 · updated_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.products_brand_name_key · UNIQUE

```
UNIQUE (marca, name)
```

public.products_category_check · CHECK

```
CHECK ((category = ANY (ARRAY['diseñador'::text, 'nicho'::text])))
```

public.products_gender_check · CHECK

```
CHECK ((gender = ANY (ARRAY['hombre'::text, 'mujer'::text, 'unisex'::text])))
```

public.products_intensity_check · CHECK

```
CHECK (((intensity >= 1) AND (intensity <= 5)))
```

public.products_pkey · PK

```
PRIMARY KEY (id)
```

public.products_price_check · CHECK

```
CHECK ((price >= (0)::numeric))
```

public.products_size_ml_check · CHECK

```
CHECK ((size_ml > 0))
```

public.products_stock_check · CHECK

```
CHECK ((stock >= 0))
```

Índices estructurales

products_brand_name_key

```
CREATE UNIQUE INDEX products_brand_name_key ON public.products USING btree (marca, name)
```

products_catalog_idx

```
CREATE INDEX products_catalog_idx ON public.products USING btree (marca, gender, category)
```

products_category_idx

```
CREATE INDEX products_category_idx ON public.products USING btree (category)
```

products_featured_idx

```
CREATE INDEX products_featured_idx ON public.products USING btree (featured DESC, id DESC)
```

products_gender_idx

```
CREATE INDEX products_gender_idx ON public.products USING btree (gender)
```

products_pkey

```
CREATE UNIQUE INDEX products_pkey ON public.products USING btree (id)
```

products_price_idx

```
CREATE INDEX products_price_idx ON public.products USING btree (price)
```

public.profiles

ACTIVA · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · id	uuid / uuid	NO PK, FK	— (sin DEFAULT)
2 · name	text / text	NO	— (sin DEFAULT)
3 · role	text / text	NO	'customer'::text
4 · created_at	timestamp with time zone / timestamptz	NO	now()

Restricciones declaradas

public.profiles_id_fkey · FK

```
FOREIGN KEY (id) REFERENCES auth.users(id) ON DELETE CASCADE
```

public.profiles_name_check · CHECK

```
CHECK (((char_length(name) >= 1) AND (char_length(name) <= 80)))
```

public.profiles_pkey · PK

```
PRIMARY KEY (id)
```

public.profiles_role_check · CHECK

```
CHECK ((role = ANY (ARRAY['customer'::text, 'admin'::text])))
```

Índices estructurales

profiles_created_idx

```
CREATE INDEX profiles_created_idx ON public.profiles USING btree (created_at DESC)
```

profiles_pkey

```
CREATE UNIQUE INDEX profiles_pkey ON public.profiles USING btree (id)
```

public.reviews

ACTIVA · RLS documentado: habilitado

# / campo	Tipo PostgreSQL	Nulo / clave	DEFAULT documentado
1 · id	bigint / int8	NO PK	— (sin DEFAULT)
2 · user_id	uuid / uuid	YES FK	— (sin DEFAULT)
3 · user_name	text / text	NO	— (sin DEFAULT)
4 · rating	integer / int4	NO	— (sin DEFAULT)
5 · comment	text / text	NO	— (sin DEFAULT)
6 · created_at	timestamp with time zone / timestamptz	NO	now()
7 · operation_id	uuid / uuid	YES	— (sin DEFAULT)

Restricciones declaradas

public.reviews_comment_check · CHECK

```
CHECK (((char_length(comment) >= 1) AND (char_length(comment) <= 1000)))
```

public.reviews_pkey · PK

```
PRIMARY KEY (id)
```

public.reviews_rating_check · CHECK

```
CHECK (((rating >= 1) AND (rating <= 5)))
```

public.reviews_user_id_fkey · FK

```
FOREIGN KEY (user_id) REFERENCES profiles(id) ON DELETE SET NULL
```

Índices estructurales

reviews_created_idx

```
CREATE INDEX reviews_created_idx ON public.reviews USING btree (created_at DESC)
```

reviews_owner_operation_unique

```
CREATE UNIQUE INDEX reviews_owner_operation_unique ON public.reviews USING btree (user_id, operation_id)
WHERE (operation_id IS NOT NULL)
```

reviews_pkey

```
CREATE UNIQUE INDEX reviews_pkey ON public.reviews USING btree (id)
```

reviews_user_idx

```
CREATE INDEX reviews_user_idx ON public.reviews USING btree (user_id)
```