

TASK 14: #51628

1. Create a S3 bucket inside your aws instace.
2. change the properties of bucket so that it allows website hosting.
3. add a simple static website to the S3 created.

Note: try with a simple index.html file.

4. check the required permission/access control of the bucket.
5. verify the working using the endpoint of bucket.

1. Create the bucket

- Go to S3 → **Create bucket**.
- Enter a bucket name and pick a region.
- Under **Block Public Access settings**, uncheck **Block all public access** and tick the acknowledgement box. You need this for a public website.
- Leave ACLs disabled (the default) and click **Create bucket**.

2. Enable static website hosting

- Open the bucket → **Properties** → scroll to **Static website hosting** → **Edit**.
- Select **Enable**, choose **Host a static website**.
- Set **Index document** to index.html, then **Save changes**.

3. Upload the website

- Open the bucket → **Objects** → **Upload** → **Add files**, choose your index.html, and click **Upload**.

Index.html:

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta name="viewport" content="width=device-width, initial-scale=1">

  <title>Astra | Rocky Linux 9 Server</title>

  <style>
```

```
:root{

  --bg: #f6f8f7;

  --surface: #ffffff;

  --text: #14201b;

  --muted: #55655e;

  --line: #d5ded9;

  --accent: #0b8a5f;

  --code-bg: #eaf0ed;

}

@media (prefers-color-scheme: dark){

  :root{

    --bg: #101613;

    --surface: #17201c;

    --text: #e6eee9;

    --muted: #9db0a7;

    --line: #2a3832;

    --accent: #3ecf98;

    --code-bg: #1f2b26;

  }

}

*{ box-sizing: border-box; }

body{

  margin: 0;

  background: var(--bg);

  color: var(--text);

  font-family: "Segoe UI", "Helvetica Neue", Arial, sans-serif;
```

```
    line-height: 1.6;
  }

  main {
    max-width: 44rem;
    margin: 0 auto;
    padding: 4rem 1.25rem 3rem;
  }

  h1 {
    margin: 0 0 0.5rem;
    font-size: clamp(2.25rem, 6vw, 3.5rem);
    line-height: 1.1;
    letter-spacing: -0.02em;
  }

  h1 span { color: var(--accent); }

  .lead {
    margin: 0 0 2.5rem;
    max-width: 36rem;
    color: var(--muted);
    font-size: 1.125rem;
  }

  h2 {
    margin: 2.5rem 0 0.75rem;
    font-size: 1.25rem;
```

```
}
```

```
.table-wrap {  
  overflow-x: auto;  
  border: 1px solid var(--line);  
  border-radius: 6px;  
  background: var(--surface);  
}
```

```
table {  
  width: 100%;  
  border-collapse: collapse;  
  font-size: 0.975rem;  
}
```

```
th, td {  
  padding: 0.7rem 1rem;  
  text-align: left;  
  border-bottom: 1px solid var(--line);  
  white-space: nowrap;  
}
```

```
th { color: var(--muted); font-weight: 600; }  
tr:last-child td { border-bottom: none; }
```

```
code {  
  padding: 0.1rem 0.4rem;  
  border-radius: 4px;
```

```
background: var(--code-bg);

font-family: Consolas, "Courier New", monospace;

font-size: 0.9em;

}

ol { padding-left: 1.25rem; }
li { margin-bottom: 0.5rem; }

a { color: var(--accent); }
a:focus-visible { outline: 2px solid var(--accent); outline-offset: 2px; }

footer {
    margin-top: 3rem;
    padding-top: 1rem;
    border-top: 1px solid var(--line);
    color: var(--muted);
    font-size: 0.9rem;
}

</style>
</head>
<body>
<main>

<h1>Astra is <span>online</span></h1>

<p class="lead">

    This page is served by Apache on a Rocky Linux 9 virtual machine.

    If you can read it, the web server, network and firewall are working.

</p>
```

<h2>Server details</h2>

<div class="table-wrap">

<table>

<thead>

<tr><th>Item</th><th>Value</th></tr>

</thead>

<tbody>

<tr><td>Hostname</td><td>Astra</td></tr>

<tr><td>Operating system</td><td>Rocky Linux 9</td></tr>

<tr><td>IP address</td><td>192.168.0.100</td></tr>

<tr><td>Document root</td><td><code>/var/www/html</code></td></tr>

</tbody>

</table>

</div>

<h2>Services</h2>

<div class="table-wrap">

<table>

<thead>

<tr><th>Service</th><th>Port</th><th>Used for</th></tr>

</thead>

<tbody>

<tr><td>sshd</td><td>22</td><td>Remote shell (SSH, PuTTY)</td></tr>

<tr><td>xrdp</td><td>3389</td><td>Remote desktop</td></tr>

<tr><td>httpd</td><td>80</td><td>This web page</td></tr>

</tbody>

</table>

</div>

```
<h2>Publish this page</h2>

<ol>

  <li>Install and start Apache:

    <code>sudo dnf install -y httpd &amp;&amp; sudo systemctl enable --now
httpd</code>

  </li>

  <li>Copy this file to <code>/var/www/html/index.html</code>.</li>

  <li>Open the firewall:

    <code>sudo firewall-cmd --permanent --add-service=http &amp;&amp;
sudo firewall-cmd --reload</code>

  </li>

  <li>Browse to <code>http://192.168.0.100</code> from the Windows
host.</li>

</ol>

<footer>

  Sample page. Edit the text and values above to match your own server.

</footer>

</main>

</body>

</html>
```

- Click **Save changes**. The bucket now shows a "Publicly accessible" label.

4. Verify with the endpoint

- Go to **Properties** → **Static website hosting** and copy the **Bucket website endpoint**, then open it in a browser.

OUTPUT:

Task #5InboxFeedCourseFree Clomym-buAstraRoles(B) Whi415Ask Gemini

Not securemy-bucket-fadhil-176938214725-ap-south-1-ans3-website.ap-south-1.amazonaws.com

PracticeAll Bookmarks

Astra is online

This page is served by Apache on a Rocky Linux 9 virtual machine. If you can read it, the web server, network and firewall are working.

Server details

Item	Value
Hostname	Astra
Operating system	Rocky Linux 9
IP address	192.168.0.100
Document root	/var/www/html

Services

Service	Port	Used for
sshd	22	Remote shell (SSH, PuTTY)