

TASK 3.1:

The finance department requires authentication before user can access confidential document

Step 1: Create the folder for confidential documents

```
#sudo mkdir -p /var/www/site2.com/html/finance
```

Step 2: Install the htpasswd tool

```
#sudo yum install httpd-tools -y
```

Step 3: Create a password file with your first user

```
#sudo htpasswd -c /etc/httpd/finance.htpasswd fadhil
```

- -c = create a new file (only use -c the **first** time — it overwrites existing files)
- fadhil = the username you're creating
- It will prompt you to set a password

Step 4: Add more users (without -c, so it doesn't erase the first user)

```
#sudo htpasswd /etc/httpd/finance.htpasswd anotheruser
```

Step 5: Protect the folder in your virtual host config

Edit your config:

```
#sudo nano /etc/httpd/conf.d/vhost.conf
```

Add this **inside** the relevant <VirtualHost> block :

```
<Directory "/var/www/site2.com/html/finance">
    AuthType Basic
    AuthName "Finance Department - Restricted Access"
    AuthUserFile /etc/httpd/finance.htpasswd
    Require valid-user
</Directory>
```

Line	Meaning
AuthType Basic	Use simple username/password popup authentication
AuthName "..."	The message shown in the login popup box
AuthUserFile	Where the list of allowed usernames/passwords is stored
Require valid-user	Any username in that file (with correct password) is allowed in

Step 6: Test config and restart Apache

```
#sudo systemctl restart httpd
```

Step 7: Fix SELinux (RHEL-specific — important!)

SELinux blocks Apache from reading password files outside expected locations by default:

```
#sudo chcon -t httpd_sys_content_t /etc/httpd/finance.htpasswd
```

Step 8: Test it

Visit:

<http://favas.co/finance/>

OUTPUT:



