

TASK #51634

Host a simple PHP website in a user home directory.

1. Create a new user named Alice
2. Create a sample web page under a directory named public_html (/home/Alice/public_html)
3. Access the website using URL: myfirstwebsite.test and www.myfirstwebsite.test

Webpage content:

```
<?
phpinfo();
?>
```

SOLUTION:

Step 1: Create the user Alice

```
# useradd fadhil
# passwd fadhil
```

Creates the Linux user and sets a password.

Step 2: Add user to wheel group

```
#usermod -aG wheel fadhil
```

Add fadhil to wheel group for getting admin privilege

Step 3: Create the public_html directory

```
#sudo mkdir /home/fadhil/public_html
```

Creates the folder as Alice (so she owns it properly).

Step 4: Create the PHP webpage

```
#sudo -u alice nano /home/fadhil/public_html/index.php
```

Paste this content:

```
<? php
phpinfo();
?>
```

type :wq! Save and exit

Step 5: Install PHP (needed to run phpinfo())

```
#sudo yum install php -y  
#sudo systemctl restart httpd
```

Step 6: Fix permissions

```
#chmod 711 /home/fadhil  
#chmod -R 755 /home/fadhil/public_html
```

711 on the home folder lets Apache pass through to reach public_html, without exposing Alice's other files.

Step 7: Fix SELinux

```
#sudo setsebool -P httpd_enable_homedirs 1  
#sudo chcon -R -t httpd_sys_content_t /home/alice/public_html
```

Allows Apache to serve content from home directories under SELinux.

Step 8: Create a VirtualHost for the custom domain

Since you want myfirstwebsite.test , you need a VirtualHost pointing directly at Alice's folder:

```
#sudo nano /etc/httpd/conf.d/fadhi.conf
```

Add:

```
<VirtualHost *:80>  
  
    ServerName myfirstwebsite.test  
  
    ServerAlias www.myfirstwebsite.test  
  
    DocumentRoot /home/fadhil/public_html  
  
    DirectoryIndex index.php  
  
    <Directory "/home/fadhil/public_html">  
        AllowOverride All  
  
        Require all granted  
    </Directory>  
  
    ErrorLog /var/log/httpd/fadhil_error.log
```

```
CustomLog /var/log/httpd/fadhil_access.log combined
</VirtualHost>
```

In simple words:

Line	Meaning
ServerName myfirstwebsite.test	Main domain this block responds to
ServerAlias www.myfirstwebsite.test	Additional domain name(s) that should also match this same block
DirectoryIndex index.php	Tells Apache to load index.php by default (normally it looks for index.html)
Require all granted	Allows public access to this folder (overrides any restrictive defaults)

Step 9: Test config and restart Apache

```
#sudo apachectl configtest
#sudo systemctl restart httpd
```

Step 10: Point both domain names to your server (on Windows hosts file)

```
C:\Windows\System32\drivers\etc\hosts
```

Add:

```
13.203.204.100 myfirstwebsite.test
13.203.204.100 www.myfirstwebsite.test
```

Step 11: Test it

<http://myfirstwebsite.test>

<http://www.myfirstwebsite.test>

Both should show the **PHP info page** with server/PHP configuration details.

OUTPUT:

Domain name:myfirstwebsite.test

PHP Version 8.3.33



System	Linux ip-172-31-9-243.ap-south-1.compute.internal 6.12.0-211.16.1.el10_2.x86_64 #1 SMP PREEMPT_DYNAMIC Mon May 18 10:23:57 EDT 2026 x86_64
Build Date	Jul 28 2026 17:56:10
Build System	Red Hat Enterprise Linux release 10.2 (Coughlan)
Build Provider	Red Hat, Inc.
Compiler	gcc (GCC) 14.3.1 20251022 (Red Hat 14.3.1-4)
Architecture	x86_64
Server API	FPM/FastCGI
Virtual Directory Support	disabled
Configuration File (php.ini) Path	/etc
Loaded Configuration File	/etc/php.ini
Scan this dir for additional .ini files	/etc/php.d
Additional .ini files parsed	/etc/php.d/10-opcache.ini, /etc/php.d/20-bz2.ini, /etc/php.d/20-calendar.ini, /etc/php.d/20-ctype.ini, /etc/php.d/20-curl.ini, /etc/php.d/20-dom.ini, /etc/php.d/20-exif.ini, /etc/php.d/20-fileinfo.ini, /etc/php.d/20-ftp.ini, /etc/php.d/20-gettext.ini, /etc/php.d/20-iconv.ini, /etc/php.d/20-mbstring.ini, /etc/php.d/20-pdo.ini, /etc/php.d/20-phar.ini, /etc/php.d/20-simplexml.ini, /etc/php.d/20-sqlite3.ini, /etc/php.d/20-tokenizer.ini, /etc/php.d/20-xml.ini, /etc/php.d/20-xmlwriter.ini, /etc/php.d/20-xsl.ini, /etc/php.d/30-pdo_sqlite.ini, /etc/php.d/30-xmlreader.ini
PHP API	20230831
PHP Extension	20230831
Zend Extension	420230831
Zend Extension Build	API420230831,NTS
PHP Extension Build	API20230831,NTS
Debug Build	no
Thread Safety	disabled
Zend Signal Handling	enabled
Zend Memory Manager	enabled
Zend Multibyte Support	provided by mbstring
Zend Max Execution Timers	disabled

Ddomain name : www.myfirstwesite.test

Not securemyfirstwebsite.test

Practice

All Bookmarks

PHP Version 8.3.33



System	Linux ip-172-31-9-243.ap-south-1.compute.internal 6.12.0-211.16.1.el10_2.x86_64 #1 SMP PREEMPT_DYNAMIC Mon May 18 10:23:57 EDT 2026 x86_64
Build Date	Jul 28 2026 17:56:10
Build System	Red Hat Enterprise Linux release 10.2 (Coughlan)
Build Provider	Red Hat, Inc.
Compiler	gcc (GCC) 14.3.1 20251022 (Red Hat 14.3.1-4)
Architecture	x86_64
Server API	FPM/FastCGI
Virtual Directory Support	disabled
Configuration File (php.ini) Path	/etc
Loaded Configuration File	/etc/php.ini
Scan this dir for additional .ini files	/etc/php.d
Additional .ini files parsed	/etc/php.d/10-opcache.ini, /etc/php.d/20-bz2.ini, /etc/php.d/20-calendar.ini, /etc/php.d/20-ctype.ini, /etc/php.d/20-curl.ini, /etc/php.d/20-dom.ini, /etc/php.d/20-exif.ini, /etc/php.d/20-fileinfo.ini, /etc/php.d/20-ftp.ini, /etc/php.d/20-gettext.ini, /etc/php.d/20-iconv.ini, /etc/php.d/20-mbstring.ini, /etc/php.d/20-pdo.ini, /etc/php.d/20-phar.ini, /etc/php.d/20-simplexml.ini, /etc/php.d/20-sqlite3.ini, /etc/php.d/20-tokenizer.ini, /etc/php.d/20-xml.ini, /etc/php.d/20-xmlwriter.ini, /etc/php.d/20-xsl.ini, /etc/php.d/30-pdo_sqlite.ini, /etc/php.d/30-xmlreader.ini
PHP API	20230831
PHP Extension	20230831
Zend Extension	420230831
Zend Extension Build	API420230831.NTS
PHP Extension Build	API20230831.NTS
Debug Build	no
Thread Safety	disabled
Zend Signal Handling	enabled
Zend Memory Manager	enabled
Zend Multibyte Support	provided by mbstring
Zend Max Execution Timers	disabled