aurora
OPTOELECTRONIC

OPTIMUS SERIES



OPTIMUS-LS Series

40/60/80/100/120/150/170W





LED Chip



Motion Sensor



Bracket



OPTIMUS-ES Series

40/60/80/100/120/150/170W



LED Chip



Motion Sensor



Bracket

OPTIMUS-LS SERIES

TECHNICAL DATAS:



40W 60W 80W 100W/120W 150W 170W







Model	YF-OPTIMUS -40W-LS	YF-OPTIMUS -60W-LS	YF-OPTIMUS -80W-LS	YF-OPTIMUS -100&120W-LS	YF-OPTIMUS -150W-LS	YF-OPTIMUS -170W-LS
LED Efficiency	230lm/w					
LED Chip	5050 LED					
Charge Controller	MPPT					
PV Module	65W Mono	80W Mono	100W Mono	120W Mono	140W Mono	160W Mono
Battery Type	LiFePO4					
Battery Capacity	384WH	487WH	676WH	896/1030WH	1150WH	1352WH
Working Mode	With Motion Sensor			Time Dimming		
Protection Grade	IP65					
Viewing Angle	70°*140°					
CCT	3000K-6500K, typical value(5500K-6000K)					
Certificate	CE、RoHS					
Working Temperature	-20°C~+60°C					
Product Dimension(mm)	960*445*73	1140*445*73	1270*445*73	1550*445*88	1730*445*88	2010*445*88
Package Dimension(mm)	1010*520*220	1190*520*220	1320*520*220	1600*520*220	1780*520*220	2060*520*220
Installation Height	5-6m Light Pole	6-8m Light Pole	7-10m Light Pole	9-12m Light Pole	10-13m Light Pole	12-15m Light Pole
Warranty	5 years					