

SUNYO



SY-BEK

SUNYO



ITEM

SY-BEK

Nominal Power	60W	90W	110W
Input Voltage	12-40V	12-40V	12-40V
Light Distribution	TYPE I,II,III,IV	TYPE I,II,III,IV	TYPE I,II,III,IV
CCT	2700-6500K	2700-6500K	2700-6500K
CRI	Ra>70	Ra>70	Ra>70
Color Tolerance Adjustment	<5SDCM	<5SDCM	<5SDCM
Protection Grade	IP66,IK09	IP66,IK09	IP66,IK09
LED	Lumileds LUXEON 5050	Lumileds LUXEON 5050	Lumileds LUXEON 5050
LED Lifespan	L70>54000h	L70>54000h	L70>54000h
Pole diameter	40-60mm	40-60mm	40-60mm
Electrical Protection	CLASS I	CLASS I	CLASS I
Luminous Flux	>160Lm/W	>160Lm/W	>160Lm/W
Housing	Die-casting Aluminum	Die-casting Aluminum	Die-casting Aluminum
Ambient temperature	-20℃-50℃	-20℃-50℃	-20℃-50℃
Battery	546WH 10V	760WH 10V	966WH 10V
SCC	20A	20A	20A
PV	>70W	>100W	>110W
Warranty	4 Years	4 Years	4 Years

SY-BEK