

Vertical inverter energy storage integrated machine

PRODUCT FEATURES

- Supports communication protocols such as RS485/RS232/CAN, making battery management more intelligent
- Integrated energy storage system, quick and easy to install
- Multiple charging methods are available, supporting both mains power and photovoltaic input
- Mobile energy storage and reverse control integrated system, solving the problem of electricity usage

PRODUCT INTRODUCTION

The vertical inverter energy storage integrated machine is the core equipment of the new generation of smart home and industrial and commercial energy storage solutions. It innovatively integrates high-performance lithium batteries, high-efficiency bidirectional inverters, and intelligent power management systems into one, adopting a vertical compact design to achieve efficient energy storage, intelligent distribution, and flexible application, creating a safe, efficient, and economical personalized energy ecosystem for you.

- Battery management system
- Mobile & Integrated design
- Overvoltage protection
- Overcurrent protection
- Overcharge protection
- Communication protocol
- High number of cycles
- Long service life
- LCD display screen
- High-level protection

Product model	UBT-N2HT5-P5	UBT-N2HT5-P15	UBT-N2HT11-P15
System parameters			
Product specification	5kW+5kWh	5kW+15kWh	11kW+15kWh
Battery voltage	51.2V	48V	48V
Battery capacity	100Ah	314Ah	314Ah
Energy	5.12kWh	15.07kWh	15.07kWh
Inverter power	5kW	5kW	11kW
Size	750×480×151	880×580×234	1030×580×234
Weight	57kg	120kg	135kg
Max. charging current	100A	100A	157A
Max. discharge current	100A	100A	250A
Inverter parameters			
Mains power mode			
Rated input voltage	220V/230V	220V/230V	220V/230V
Input voltage range	(170Vac~280Vac)±2%	(170Vac~280Vac)±2%	(170Vac~280Vac)±2%
Frequency	50Hz/60Hz	50Hz/60Hz	50Hz/60Hz
Efficiency	95%	95%	95%
Max. bypass overload current	40A	40A	40A
Inverter mode			
Output waveform diagram	Pure sine wave	Pure sine wave	Pure sine wave
Rated output power	5kW	5kW	11kW
Power factor	1	1	1
Rated output voltage	220/230/240V±5%	220/230/240V±5%	220/230/240V±5%
Output frequency	50±0.3Hz/60±0.3Hz	50±0.3Hz/60±0.3Hz	50±0.3Hz/60±0.3Hz
Efficiency	92%	92%	92%
Solar charging			
Max. photovoltaic open-circuit voltage	500Vdc	500Vdc	500Vdc
Operating voltage range	60~500Vdc	60~500Vdc	60~500Vdc
Max. PV output current	20A	20A	20A

UBETTER Vertical inverter energy storage integrated machine

Distributor resmi di Indonesia: Energi.Click by Rekasurya
energi.click · WhatsApp 0811-2241-107