


Any software that has a specific purpose and function



Application Programming Interface

Contract between two applications that dictates how they talk to each other using requests and responses




Application Programming Interface

A way for different applications to communicate with each other

**API** 







Non-technical Analogy



Call

Request

Response



Technical Analogy





Apple decided to set up weather monitoring stations.

These weather monitoring stations are very expensive.

Apple weather app store all data coming from stations.

No one can access Apple weather's data directly.

Apple created Weather.com API to share the data with people.

Anyone can access Apple weather's data through this API but in specific way that weather.com allows.

Apple can populate its weather data through this API.



Apple Weather App

Global Weather Data





Global Weather Data
































#### **Hyper Text Transfer Protocol**



Enable communication between client and server



**Anatomy** 

**URL / URI** 

**Method Type** 

Header

**Body** 

**Anatomy** 

**URL / URI** 

**Method Type** 

Header

**Body** 

**Uniform Resource Identifier** 

**Anatomy** 

**URL / URI** 

**Method Type** 

Header

**Body** 

Many types:

**GET** 

**POST** 

**PUT** 

**DELETE** 

**Anatomy** 

**URL / URI** 

**Method Type** 

Header

**Body** 

**Content type:** 

What kind of content are you sending through this request

**Anatomy** 

**URL / URI** 

**Method Type** 

Header

**Body** 

It is where the content lie.

Some methods have body and other don't.

#### Request Method ?




Can have one of handful of predefined values.

```
GET POST PUT HEAD
DELETE
PATCH OPTIONS
TRACE
CONNECT
```

#### Request Method?

HTTP Request is referred to by the value of its request method



## GET Request?

GET requests are only used to request data (not modify)

GET request can be bookmarked

GET request can be cached

GET request is used to request data from a specified resource GET request should never be used when dealing with sensitive data

GET request have length restrictions

GET request remain in the browser history

The data sent to the server with GET is stored in the request header

## POST Request?

POST request is used to send data to a server to create/update a resource

POST request is never cached

POST request cannot be bookmarked


POST requests have no restrictions on data length

POST request does not remain in the browser history

The data sent to the server with POST is stored in the request body

# Backend?

#### It isn't restricted to only one platform



#### Backend?

**Backend Service** 

#### Backend?

Server


**Backend Service** 




Arrays


Variables


Superglobals




#### **MYSQLI vs PDO**












using built-in functions using OOP
Support MYSQL



#### **MYSQLI vs PDO**









using OOP

Support most databases (12 DBs)

**Framework connection uses PDO** 

# 



