

KEYSTONE4J

ADAPT OPENSTACK KEYSTONE TO JAVA



PRESENTED BY:
PO-HSUN, HUANG
INFINITIESOFT

PO-HSUN, HUANG (黃柏勳)

R&D Engineer

InfinitesSoft, Inc. (數位無限軟體)




- Virtualization and Java guy
- Responsible for skyport, keystone4j development and wins3fs enhancement
- Keystone4j repository:
<https://bitbucket.org/infinites/keystone4j/>
- E-mail: pohsun@infinitessoft.com

AGENDA

- Subject of keystone4j project
- What is keystone?
- Keystone code structure
- How to adapt to java?
- Demo
- Q&A

SUBJECT OF KEYSTONE4J PROJECT

- Easier troubleshooting.
- Understand Openstack's API design and access control .
- Integrated with Skyport.
- Promote Openstack in Java world.



NO RESTFUL API V.S. RESTFUL API


GET [https://ec2.amazonaws.com/?Action=RunInstances &ImageId=ami-1a2b3c4d
&MaxCount=1 &MinCount=1 &NetworkInterface.1.DeviceIndex=0
&NetworkInterface.1.AssociatePublicIpAddress=true
&NetworkInterface.1.SubnetId=subnet-1a2b3c4d &AUTHPARAMS](https://ec2.amazonaws.com/?Action=RunInstances&ImageId=ami-1a2b3c4d&MaxCount=1&MinCount=1&NetworkInterface.1.DeviceIndex=0&NetworkInterface.1.AssociatePublicIpAddress=true&NetworkInterface.1.SubnetId=subnet-1a2b3c4d&AUTHPARAMS)
Body: [empty]




POST|GET|DELETE|PUT|HEAD <https://openstack.com/v2/{tenant}/servers>
Body:
{ "server": { "name": "server-test-1", "imageRef": "b5660a6e-4b46-4be3-9707-6b47221b454f", "flavorRef": "2", "max_count": 1, "min_count": 1, "networks": [{ "uuid": "d32019d3-bc6e-4319-9c1d-6722fc136a22" }], "security_groups": [{ "name": "default" }, { "name": "another-secgroup-name" }] } }


WHAT IS KEYSTONE


- An abstract layer
 - Backend: SQL 、LDAP....
 - Authenticate: OAUTH 、 Password 、 Token....
- User management and Services Catalog
- Server-Client model : keystone, keystonemiddleware.auth_token
- WSGI model



How the CADF Audit Middleware Filter Works in the Nova API Pipeline








```
{
  "access": {
    "metadata": {
      ....metadata goes here....
    },
    "serviceCatalog": [
      ....endpoints goes here....
    ],
    "token": {
      "expires": "2013-05-26T08:52:53Z",
      "id": "placeholder",
      "issued_at": "2013-05-25T18:59:33.841811",
      "tenant": {
        "description": null,
        "enabled": true,
        "id": "925c23eafe1b4763933e08a4c4143f08",
        "name": "user"
      }
    },
    "user": {
      ....userdata goes here....
    }
  }
}
```

WHAT IS KEYSTONE

- An abstract layer
 - Backend: SQL 、LDAP....
 - Authenticate: OAUTH 、 Password 、 Token....
- User management and Services Catalog
- Server-Client model : keystone, keystonemiddleware.auth_token
- WSGI model



WHERE TO BEGIN – CONFIG FILES

- Keystone repository: <https://github.com/openstack/keystone>
- Analysis configuration files
 - **policy.json**: API access control rule
 - keystone.conf : application options
 - keystone-paste.ini : deployment

```
"admin_required": "role:admin or is_admin:1",  
"service_role": "role:service",  
"service_or_admin": "rule:admin_required or rule:service_role",  
"owner" : "user_id:%(user_id)s",  
"admin_or_owner": "rule:admin_required or rule:owner",
```

```
"identity:get_user": "rule:admin_required",  
"identity:list_users": "rule:admin_required",  
"identity:create_user": "rule:admin_required",  
"identity:update_user": "rule:admin_required",  
"identity:delete_user": "rule:admin_required",  
"identity:change_password": "rule:admin_or_owner",
```

WHERE TO BEGIN – CONFIG FILES

- Keystone repository: <https://github.com/openstack/keystone>
- Analysis configuration files
 - policy.json: API access control rule
 - **keystone.conf** : application options
 - keystone-paste.ini : deployment

```
# Amount of time a token should remain valid (in seconds). (integer value)
#expiration = 3600
```

```
# Controls the token construction, validation, and revocation operations.
# Entrypoint in the keystone.token.provider namespace. Core providers are
# [fernet|pkiz|pki|uuid]. (string value)
#provider = uuid
```


```
# Entrypoint for the token persistence backend driver in the
# keystone.token.persistence namespace. (string value)
#driver = sql
```

WHERE TO BEGIN – CONFIG FILES

- Keystone repository: <https://github.com/openstack/keystone>
- Analysis configuration files
 - policy.json: API access control rule
 - keystone.conf : application options
 - **keystone-paste.ini : deployment**

```
[pipeline:admin_api]
# The last item in this pipeline must be admin_service
# application. It cannot be a filter.
pipeline = sizelimit url_normalize request_id build_aut

[pipeline:api_v3]
# The last item in this pipeline must be service_v3 or
# application. It cannot be a filter.
pipeline = sizelimit url_normalize request_id build_aut
```



```
[filter:url_normalize]
```

```
paste.filter_factory = keystone.middleware.NormalizingFilter.factory
```

```
[filter:sizelimit]
```

```
paste.filter_factory = oslo_middleware.sizelimit.RequestBodySizeLimiter.factory
```

```
[pipeline:api_v3]
```

```
# The last item in this pipeline must be service_v3 or an equivalent  
# application. It cannot be a filter.
```

```
pipeline = sizelimit url_normalize request_id build_auth_context t
```

```
[composite:main]
```

```
use = egg:Paste#urlmap
```

```
/v2.0 = public_api
```

```
/v3 = api_v3
```

```
/ = public_version_api
```

```
[composite:admin]
```

```
use = egg:Paste#urlmap
```

```
/v2.0 = admin_api
```

```
/v3 = api_v3
```

```
/ = admin_version_api
```

FROM CONFIG FILES TO CODE

```
[app:service_v3]
```

```
paste.app_factory = keystone.service:v3_app_factory
```

File Explorer:














- __init__.py
- config.py
- controllers.py
- exception.py
- i18n.py
- notifications.py
- routers.py
- service.py

Code Editor:

```
@fail_gracefully
def v3_app_factory(global_conf, **local_conf):
    controllers.register_version('v3')
    mapper = routes.Mapper()
    sub_routers = []
    _routers = []


    # NOTE(dstanek): Routers should be ordered by their fr
    # a live system. This is due to the routes implementat
    # frequently used routers should appear first.
    router_modules = [auth,
```


WHERE TO BEGIN – CODE

 assignment	Merge "Improve a few random docstrings (H4
 auth	Stop calling deprecated assignment manager
 catalog	Use dict.items() rather than six.iteritems()
 cmd	Fix remaining mention of KLWT
 common	Merge "Improve a few random docstrings (H4
 contrib	Stop calling deprecated assignment manager
 credential	Standardize documentation at Service Manag
 endpoint_policy	Move endpoint policy into keystone core
 identity	Merge "Remove unnecessary ldap imports"
 locale	Imported Translations from Transifex
 middleware	Use dict.items() rather than six.iteritems()
 models	Move constants out of federation.core
 policy	Use stevedore for backend drivers

CODE STRUCTURE

- Router(routers.py)
- Controller(controllers.py)
- Manager(core.py)
- Driver
 - Interface(core.py)
 - Implementation(backends)



- Router → Controller → Manager(API) → Driver

CODE STRUCTURE - ROUTER

```
class Routers(wsgi.RoutersBase):

    def append_v3_routers(self, mapper, routers):
        user_controller = controllers.UserV3()
        routers.append(
            router.Router(user_controller,
                           'users', 'user',
                           resource_descriptions=self.v3_resources))

    self._add_resource(
        mapper, user_controller,
        path='/users/{user_id}/password',
        post_action='change_password',
        rel=json_home.build_v3_resource_relation('user_change_password'),
        path_vars={
            'user_id': json_home.Parameters.USER_ID,
        })
```

CODE STRUCTURE - CONTROLLER

```
@dependency.requires('identity_api')
class UserV3(controller.V3Controller):
    collection_name = 'users'
    member_name = 'user'

    @controller.protected()
    def change_password(self, context, user_id, user):
        original_password = user.get('original_password')
        if original_password is None:
            raise exception.ValidationError(target='user',
                                           attribute='original_password')

        password = user.get('password')
        if password is None:
            raise exception.ValidationError(target='user',
                                           attribute='password')

        try:
            self.identity_api.change_password(
                context, user_id, original_password, password)
        except AssertionError:
            raise exception.Unauthorized()
```

CODE STRUCTURE – MANAGER

```
@notifications.listener
@dependency.provider('identity_api')
@dependency.requires('assignment_api', 'credential_api', 'id_mapping_api',
                     'resource_api', 'revoke_api')
class Manager(manager.Manager):
    """Default pivot point for the Identity backend.

    @domains_configured
    def change_password(self, context, user_id, original_password,
                       new_password):

        # authenticate() will raise an AssertionError if authentication fails
        self.authenticate(context, user_id, original_password)

        update_dict = {'password': new_password}
        self.update_user(user_id, update_dict)
```

CODE STRUCTURE – DRIVER

```
class Identity(identity.Driver):
    # NOTE(henry-nash): Override the __init__() method so as to take a
    # config parameter to enable sql to be used as a domain-specific driver.
    def __init__(self, conf=None):
        super(Identity, self).__init__()

    @sql.handle_conflicts(conflict_type='user')
    def update_user(self, user_id, user):
        session = sql.get_session()

        with session.begin():
            user_ref = self._get_user(session, user_id)
            old_user_dict = user_ref.to_dict()
            user = utils.hash_user_password(user)
            for k in user:
                old_user_dict[k] = user[k]
            # user_ref.update_dict(old_user_dict)
```

KEYSTONE4J

- All Identity API v3 and partial v2.0(token)
- SQL driver only, no LDAP
- Support password, token authentication
- Configured using keystone.conf, policy.json
- JRE(Java Runtime Environment) 7
- Jersey framework(RESTful Web Service framework)
 - <https://jersey.java.net/>

HOW TO ADAPT TO JAVA

Router

```
@POST  
@Path("/{userid}/password")  
public Response changePassword(@PathParam("userid") String userid,  
    UserParamWrapper userWrapper) throws Exception {  
    userController.changePassword(userid, userWrapper.getUser());  
    return Response.status(CustomResponseStatus.NO_CONTENT).build();  
}
```


HOW TO ADAPT TO JAVA

Controller

```
public class UserV3ControllerImpl extends BaseController implements UserV3Controller {  
  
    @Override  
    public void changePassword(String userid, UserParam user) throws Exception {  
        User ref = getMemberFromDriver(userid);  
        ProtectedAction<User> command = new ProtectedDecorator<User>(  
            new ChangePasswordAction(identityApi, tokenProviderApi,  
                policyApi, userid, user), tokenProviderApi, policyApi, ref, user);  
        command.execute(getRequest());  
    }  
}
```

Demo

Q&A