prob 1 - Min max difference

November 7, 2019

0.0.1 uni: my2638

0.0.2 name: Mingjia Yu

```
[]: import sys
     import time
     import numpy as np
     import pandas as pd
     from gurobipy import *
     from myMatrixLpSolver import lp_optimize
     data = pd.read_table('dataLR.txt', sep=',', header=None)
     data.rename(
         columns={0: "y",1: "x1",2: "x2",3: "x3",4: "x4",5: "x5",6: "x6",7: "x7",8:
      \rightarrow"x8",9: "x9",10: "x10"},
         inplace=True
     data['b'] = 1
     data = pd.concat([data, data], axis=0).reset_index(drop=True)
     print(data.head(5))
     labelList = data["y"].values.tolist()
     data["v"] = [1] * int(data.shape[0]/2) + [-1] * int(data.shape[0]/2)
     dataList = data.drop("y", axis=1).values.tolist()
     start = time.time()
     lp_optimize(
         rows=data.shape[0],
         cols=12,
         c=[0]*11 + [1],
         obj_sense=GRB.MINIMIZE,
         A=dataList,
         sense=[GRB.GREATER_EQUAL] * int(data.shape[0]/2) + [GRB.LESS_EQUAL] *__
      \rightarrow int(data.shape[0]/2),
```

```
rhs=labelList,
    lb=[-GRB.INFINITY] * 12,
    ub=[GRB.INFINITY] * 12,
    vtype=[GRB.CONTINUOUS] * 12,
    solution=[0] * 12
end = time.time()
print(end - start)
# Dual
start = time.time()
A_transpose = np.array(dataList).T.tolist()
lp_optimize(
    rows=len(A_transpose),
    cols=len(labelList),
    c=labelList,
    obj_sense=GRB.MAXIMIZE,
    A=A_transpose,
    sense=[GRB.EQUAL] * len(A_transpose),
    rhs=[0]*11 + [1],
   lb=[0] * int(len(labelList) / 2) + [-GRB.INFINITY] * int(len(labelList) /__
→2),
    ub=[GRB.INFINITY] * int(len(labelList) / 2) + [0] * int(len(labelList) / 2),
    vtype=[GRB.CONTINUOUS] * len(labelList),
    solution=[0] * len(labelList)
)
end = time.time()
print(end - start)
```

```
↓$ python3 zac.py

      y x1 x2 x3 x4 x5 x6 x7 x8 x9 x10 b
0
     36
         5
             8 -10 30 -17 -29 11 41 -42
                                          -26 1
  -4077
        -3
            0 -8 -37 30 -35 37
                                  46 -7
                                           -58 1
   8176 0 -14 18 -25 -41 -33 -22
                                  66 -34
                                            56 1
3
                     7 -43 -52 46 26 -38
   2190
        2 3 20
                                            1 1
4 -10938 4 -10 23 -14 40 -50 19
                                   6 -29 -88 1
Academic license - for non-commercial use only
Optimize a model with 20000 rows, 12 columns and 237130 nonzeros
Coefficient statistics:
 Matrix range
                 [1e+00, 1e+02]
 Objective range [1e+00, 1e+00]
 Bounds range
                 [0e+00, 0e+00]
 RHS range
                 [6e+00, 2e+04]
Presolve time: 0.11s
Presolved: 12 rows, 20000 columns, 237130 nonzeros
                          Primal Inf.
Iteration
           Objective
                                        Dual Inf.
          -0.0000000e+00 4.000000e+00
                                        6.713220e+09
      0
                                                         Øs
    242
          5.0000000e+01 0.000000e+00 0.000000e+00
                                                         Øs
Solved in 242 iterations and 0.16 seconds
Optimal objective 5.000000000e+01
Obj Value: 49.9999999999997
CØ -8.99999999999716
C1 -1.8430868428878497e-13
C2 -12.00000000000000059
C3 27.99999999999947
C4 -24.9999999999996
C5 5.99999999999854
C6 20.99999999999975
C7 63.99999999999964
C8 36.0000000000000005
C9 100.0
C10 76.99999999999562
C11 49.9999999999997
1.0383250713348389
```

```
Optimize a model with 12 rows, 20000 columns and 237130 nonzeros
Coefficient statistics:
 Matrix range [1e+00, 1e+02]
 Objective range [6e+00, 2e+04]
 Bounds range [0e+00, 0e+00]
 RHS range
                [1e+00, 1e+00]
Concurrent LP optimizer: dual simplex and barrier
Showing barrier log only...
Presolve time: 0.15s
Presolved: 12 rows, 20000 columns, 237130 nonzeros
Ordering time: 0.00s
Barrier statistics:
AA' NZ : 6.600e+01
Factor NZ : 7.800e+01 (roughly 8 MBytes of memory)
Factor Ops : 6.500e+02 (less than 1 second per iteration)
Threads
          : 1
                 Objective
                                        Residual
                        ve Restauat
Dual Primal Dual Compl
Iter
          Primal
                                                                  Time
     2.80806489e-11 -0.000000000e+00 6.71e+02 1.25e+01 2.24e+01
                                                                    0s
  1 -9.72032577e-02 2.69590365e+03 5.75e+01 9.09e-13 2.07e+00
                                                                    0s
  2 -3.46321766e-03 2.35712357e+03 5.68e-14 9.09e-13 1.18e-01
     4.16862741e-03 1.59430584e+02 4.75e-14 9.09e-13 7.97e-03
                                                                    Øs
     5.97110909e-01 1.02042814e+02 7.55e-15 6.82e-13 5.07e-03
                                                                    Øs
  5 2.07055043e+01 1.02794489e+02 1.99e-14 6.82e-13 4.10e-03
                                                                    0s
Barrier performed 5 iterations in 0.25 seconds
Barrier solve interrupted - model solved by another algorithm
Solved with dual simplex
Solved in 49 iterations and 0.25 seconds
Optimal objective 5.0000000000e+01
Obj Value: 50.000000000000073
CØ 0.10976719926660782
C1 0.19978884547085207
C2 0.0
C3 0.0
C4 0.0
C5 0.0
C6 0.0
C7 0.19044395526254007
C8 0.0
C9 0.0
C10 0.0
```

Solved with dual simplex Solved in 49 iterations and 0.25 seconds Optimal objective 5.000000000e+01 Obj Value: 50.0000000000073 C0 0.10976719926660782
C1 0.19978884547085207
C2 0.0
C3 0.0
C4 0.0
C5 0.0
C6 0.0
C7 0.19044395526254007
C8 0.0
C9 0.0
C10 0.0
C11 0.0
C12 0.0
C13 0.0
C14 0.0
C15 0.0
C16 0.0
C17 0.0
C18 0.0
C19 0.0
C20 0.0
C21 0.0
C22 0.0
C23 0.0
C24 0.0
C25 0.0
C26 0.0
C27 0.0

prob 2 - Min sum of difference

November 7, 2019

0.0.1 uni: my2638

0.0.2 name: Mingjia Yu

```
[]: import os
     import sys
     import time
     import numpy as np
     import pandas as pd
     from gurobipy import *
     from myMatrixLpSolver import lp_optimize
     data = pd.read_table('dataLR.txt', sep=',', header=None)
     data.rename(
         columns={0: "y",1: "x1",2: "x2",3: "x3",4: "x4",5: "x5",6: "x6",7: "x7",8:
     \rightarrow"x8",9: "x9",10: "x10"},
         inplace=True
     N = data.shape[0]
     data['b'] = 1
     data = pd.concat([data, data], axis=0).reset_index(drop=True)
     labelList = data["y"]
     data.drop("y", axis=1, inplace=True)
     data = data.values
     I = np.identity(n=N)
     II = np.concatenate((I, np.negative(I)), axis=0)
     data = np.concatenate((data, II), axis=1)
     start = time.time()
     lp_optimize(
         rows=data.shape[0],
```

```
cols=data.shape[1],
    c=[0]*11 + [1]*N,
    obj_sense=GRB.MINIMIZE,
    A=data.tolist(),
    sense=[GRB.GREATER_EQUAL] * int(data.shape[0]/2) + [GRB.LESS_EQUAL] *__
\rightarrowint(data.shape[0]/2),
    rhs=labelList,
    lb=[-GRB.INFINITY] * (11 + N),
    ub=[GRB.INFINITY] * (11 + N),
    vtype=[GRB.CONTINUOUS] * (11 + N),
    solution=[0]*(11 + N)
)
end = time.time()
print(end - start)
# Du.a.l.
start = time.time()
A_transpose = data.T.tolist()
lp_optimize(
    rows=len(A_transpose),
    cols=len(labelList),
    c=labelList,
    obj_sense=GRB.MAXIMIZE,
    A=A_transpose,
    sense=[GRB.EQUAL] * len(A_transpose),
    rhs=[0]*11 + [1]*N,
    lb=[0] * int(len(labelList) / 2) + [-GRB.INFINITY] * int(len(labelList) /__
→2),
    ub=[GRB.INFINITY] * int(len(labelList) / 2) + [0] * int(len(labelList) / 2),
    vtype=[GRB.CONTINUOUS] * len(labelList),
    solution=[0] * len(labelList)
)
end = time.time()
print(end - start)
```

Optimize a model with 20000 rows, 10011 columns and 237130 nonzeros Coefficient statistics: Matrix range [1e+00, 1e+02] Objective range [1e+00, 1e+00] Bounds range [0e+00, 0e+00] RHS range [6e+00, 2e+04] Concurrent LP optimizer: dual simplex and barrier Showing barrier log only... Presolve removed 10000 rows and 0 columns Presolve time: 0.30s Presolved: 10000 rows, 10011 columns, 118565 nonzeros Ordering time: 0.00s Barrier statistics: Dense cols : 11 Free vars : 11 AA' NZ : 1.086e+05 Factor NZ : 1.186e+05 (roughly 10 MBytes of memory) Factor Ops: 1.408e+06 (less than 1 second per iteration) Threads : 1 Objective Residual Primal Dual Primal Dual Time Iter Compl 5.31670428e+08 9.20933000e+05 0.00e+00 2.00e+04 9.96e+05 0s 5.01525896e+08 2.55734794e+01 0.00e+00 1.42e-10 2.51e+04 0s 1.12558303e+06 3.17766341e+01 0.00e+00 1.02e-10 5.63e+01 0s 2.98823552e+04 9.12312611e+02 0.00e+00 5.09e-11 1.45e+00 0s 1.03099481e+03 9.99891159e+02 0.00e+00 2.91e-11 1.56e-03 0s 1.00003099e+03 9.99999891e+02 0.00e+00 5.82e-11 1.56e-06 0s 1.00000003e+03 1.00000000e+03 0.00e+00 9.82e-11 1.56e-09 0s Barrier solved model in 6 iterations and 0.46 seconds Optimal objective 1.00000003e+03 Crossover log... 0 DPushes remaining with DInf 1.7337243e-12 3s 0 PPushes remaining with PInf 0.0000000e+00 3s Push phase complete: Pinf 0.0000000e+00, Dinf 1.7337243e-12 3s Objective Primal Inf. Dual Inf. Iteration Time

0.000000e+00

0.000000e+00

3s

8934

1.0000000e+03

Crossover log						
0 DPushes remaining with DInf 1.7337243e-12						
0 PPushes remaining with PInf 0.0000000e+00						
Push phase complete: Pinf 0.0000000e+00, Dinf 1.7337243e-12						
Iteration Objective Primal Inf. Dual Inf. Time 8934 1.00000000e+03 0.0000000e+00 0.0000000e+00 3s						
Solved with barrier Solved in 8934 iterations and 3.27 seconds Optimal objective 1.0000000000e+03 Obj Value: 999.99999999995 C0 -9.000000000000055						
C1 0.0						
CZ -12.0						
C3 28.00000000000018						
C4 -25.000000000000014						
C5 6.000000000000018						
C6 21.00000000000001						
C7 64.000000000000003						
C8 36.00000000000003						
C9 99.999999999996						
C10 27.00000000001933						
C11 99.999999999864						
C12 99.9999999999						
C13 100.000000000000000000000000000000000						
C14 99.9999999999902						
C15 99.9999999999818						
C16 99.99999999995						

	Objective				Residual				
Iter	Primal Dual								
0	4.38774667e+						Time 0s		
1	2.34772123e+	01 4.3683	8665e+07	1.46e-07	1.14e-12	2.18e+03	0s		
2	8.36102686e+								
3	9.49403501e+								
4	9.99951643e+					6.77e-04			
5 6	9.99999952e+								
0	6 1.00000000e+03 1.00000001e+03 9.46e-11 1.14e-12 6.77e-10								
Barrier solved model in 6 iterations and 0.28 seconds Optimal objective 1.00000000e+03									
Crossover log									
1 DPushes remaining with DInf 0.0000000e+00							0s		
	0 DPushes re	maining wi	th DInf 3	.1254999e-	-12		0s		
99	79 PPushes re	mainina wi	th PInf 0	.0000000e	-00		0s		
	0 PPushes re						0s		
Push	phase comple	te: Pinf 0	. 00000000e	+00, Dinf	2.4300562	e-12	0s		
Iterat	ion Object	ive I	Primal In	f. Dual	Inf.	Time			
		00e+03 0			0000e+00	0s			
Solved with dual simplex Solved in 106 iterations and 0.37 seconds Optimal objective 1.000000000e+03 Obj Value: 999.9999999998399 C0 1.0									
C1 1.0									
C2 1.0									
C3 1.0									
C4 1.0									
C5 1.0									
C6 1.0									
C7 1.0									
C8 1.0									