

Individual Exercise 3 Report

Objective:

The exercise focuses on building a writer identification system using the ICDAR17 dataset. It involves generating a codebook with k-means, encoding images with VLAD, and classifying them using SVMs.

Dataset & Experimental Setup

- Dataset folders follow the ICDAR2017 Historical Writer Identification local-feature structure.
- Training descriptors: 1182 samples, Test descriptors: 3600 samples.
- Random seed fixed to 42 for reproducibility.
- Dictionary size $K = 100$ using MiniBatchKMeans.
- Approximately 500,000 training descriptors sampled to learn the codebook.
- Runs using --overwrite ensure a fair comparison between configurations.

Results:

<i>Experiment</i>	<i>Options</i>	<i>Top-1</i>	<i>mAP</i>	<i>Top-1 after Exemplar SVMs</i>	<i>mAP after Exemplar SVMs</i>
Own SIFT (computed) Given descriptors Baseline GMP $\gamma=1$ GMP $\gamma=10$ GMP $\gamma=100$	default VLAD	0.82056	0.62995	0.88111	0.74187
	default VLAD	0.80583	0.61745	0.87556	0.73125
	-clusters 32 + power norm	0.83250	0.64483	0.89778	0.76466
	Gmp, gamma 1, power norm	0.83861	0.65147	0.90389	0.77989
	Gmp, gamma 10, power norm	0.83472	0.64765	0.89833	0.77238
	Gmp, gamma 100, power norm	0.83139	0.64336	0.89722	0.76524
Multi-VLAD + PCA	Multivlad, codebooks 5, clusters 32, pcadim 1000 , power norm			0.89000	0.74879

Comparative Analysis:

Own descriptors vs given descriptors

The goal was to compare the pipeline performance when using:

- SIFT descriptors computed by us from the images, and
- precomputed descriptors provided with the exercise.

results show that **own computed descriptors perform slightly better** than the given ones:

- Before Exemplar SVMs: mAP improves from **0.61745** → **0.62995**
- After Exemplar SVMs this improvement stays: **0.73125** → **0.74187**

This means our computeDescs + Hellinger normalization implementation is working correctly and produces competitive features.

Part (f): Baseline VLAD vs GMP

GMP improves over the baseline in almost all cases, especially after Exemplar SVMs:

- Baseline after Exemplar SVMs: **mAP = 0.76466**
- Best GMP ($\gamma=1$) after Exemplar SVMs: **mAP = 0.77989**

Among the gamma values i tried, **$\gamma=1$ is the best**. As gamma increases, performance slowly drops closer to baseline.

Part (g): Multi-VLAD + PCA

Multi-VLAD setup (5 codebooks, K=32, PCA=1000, powernorm) achieved:

- **Top-1 = 0.89, mAP = 0.74879** (final output line)

This is good, but it is **slightly below the best GMP run** after Exemplar SVMs (mAP 0.77989). A likely reason is PCA compression or that Multi-VLAD may need different settings (e.g., without PCA or different PCA dimension) to reach its best performance.

Conclusion

- my own extracted SIFT descriptors slightly outperform the provided descriptors, both before and after Exemplar SVMs.
- GMP improves results over baseline VLAD, and the best performance is obtained with **$\gamma=1$** .
- Multi-VLAD + PCA works and produces strong accuracy, but in current run it does not beat the best GMP configuration.

Compare the effect of multi-VLAD with VLAD. Which feature benefits the most of it? What works better for you? E-SVM or multi-VLAD or a combination of both?

