


ENGINEERING BLOG

CATEGORIES ~

JUL 23, 2024

Snowflake Al Research Fine-Tuning Llama 3.1 405B on a Single Node using Snowflake's **Memory-Optimized AI Stack**

SHARE



Fine-tuning and inferencing large models, such as Meta Llama 3.1 405B, present significant challenges due to their enormous size, requiring innovative approaches to overcome memory constraints. This blog outlines a series of optimizations that enable fine-tuning models with 400+ billion parameters on small multi-node clusters or even on a single 8 x H100-80GB host (see our post on inference optimizations here). By combining parameter-efficient fine-tuning (specifically LoRA), FP8 quantization, ZeRO-3-inspired sharding and targeted parameter off-loading, the Snowflake AI Research team dramatically reduced per-GPU memory requirements, from an initial 6.5 TB, to under 80 GB of GPU memory. These techniques, implemented primarily as drop-in replacements for PyTorch's nn.Linear module and upstreamed to DeepSpeed, enable efficient handling of the model's 405 billion parameters while managing activation memory and other overheads. This approach not only makes fine-tuning Meta's Llama 3.1 405B possible, but also demonstrates a path for working with extremely large language models (LLMs) on limited

hardware resources. Our optimized fine-tuning implementation for Llama 3.1 405B is open sourced, and it will also power Cortex fine-tuning of Llama 3.1 405B, coming soon.

Understanding memory consumption

AUTHOR

Llama 3.1 405B truly exemplifies the 'large' in LLM, making basic fine-tuning extremely difficult or impossible — even on the most Snowflake AI Researchanced hardware. To gain a deeper understanding of the memory overheads required by Llama 3.1 405B, let's first break down the parameter counts and memory overheads required by training below.

SHARE

f - in - 🖂					
Мосые	Parameters	Total			
LlamaMLP	2.62 billion x 126 layers	330 billion			
LlamaAttention	0.6 billion x 126 layers	76 billion			
Embedding + norms	2 billion	2 billion			
Grand total		408 billion			

In our setup, we assume a single 8 x H100-80GB host (e.g., p5.48xlarge) and leverage DeepSpeed's ZeRO to help reduce optimizer state memory overheads. The calculations below are based on Figure 1 from ZeRO: Memory Optimizations Toward **Training Trillion Parameter Models.**

ZeRO strategy w. bfloat16	Memory required per GPU
Baseline w/o ZeRO	6.5 TB
ZeRO stage 1	2.2 TB
ZeRO stage 2	1.4 TB
ZeRO stage 3	0.8 TB

As demonstrated above, even by going all the way to ZeRO stage 3 we are unable to fit all the required optimizer states and model weights in a single 8 x H100 host. While more-advanced techniques like ZeRO-Infinity could be explored, we chose to go down a slightly different path in this work.

System Design

We will now go over the optimizations we applied to fine-tune Llama 3.1 405B and update our per-GPU memory overhead along the way.

Parameter-efficient fine-tuning + ZeRO stage 2

AUTHOR

Snowflake AI Research order to reduce the significant overheads of full-precision finetuning, we employed a common practice of parameter-efficient fine-tuning. Specifically, we implemented and upstreamed to DeepSpeed a version of low-rank adaptation (LoRA), using a ירב `val' of 64. This optimization alone reduced our per-GPU SHARE ...emc., req....ements with ZeRO-2 from 1.4 TB down to 825 GB.

FP8 quantization

Following the approach used for Arctic and Llama inference, we have developed hardware-agnostic FP8 quantization kernels. These kernels support both sparse MoE models like Arctic and dense models like Llama 3.1, both have been upstreamed to DeepSpeed. For details on our quantization methods, please see our accompanying post on these optimizations in the context of inferencing Llama 3.1 405B.

More specifically, we applied FP8 quantization to the "base weights" that are frozen during training, which makes applying this type of quantization relatively straightforward since it does not require generating gradients. This optimization further reduces our memory requirements above from 825 GB down to 417 GB.

ZeRO-3 inspired sharding

The total frozen and quantized parameters now sum up to 408 billion parameters. We apply a very similar sharding strategy as ZeRO-3 but targeted specifically at these frozen "base weights." Unlike traditional ZeRO-3, our implementation requires no backward pass, simplifying the implementation of sharding. We shard the weights by 8 and add an allgather during the forward for each frozen linear weight. The allgather is done over NVLink, minimizing performance penalty.

All optimizations described here are developed as a drop-in replacement for torch's nn.Linear module. This allows us to have very tight control over all of our optimizations and simplifies the process of isolating our frozen "base weights" and sharding them across all 8 GPUs.

AUTHOR

By sharding our base weights, we now reduce our memory requirements above from 417 GB down to 60 GB.

Snowflake AI Research

Targeted-parameter off-loading

SHARE

You might think we can now claim victory with the previous ntiments ince we have now brought down the per-GPU .em., requested aments under 80 GB. However, these estimates do not account for several other factors that contribute to memory overheads during training. These other factors include (but are not limited to) activation memory, memory fragmentation, NCCL and other library overheads.

The most significant of these memory overheads, especially for this model, comes from activation memory. A significant portion of this can be reduced by applying activation checkpointing. However, this still requires a non-trivial amount of memory to:

- 1. Store the activation checkpoints,
- 2. Store the full set activations for a single transformer layer between two activation checkpoints, and
- 3. Store the projection-layer forward and backward memory

In addition to these, the LoRA model states also occupy a non-trivial amount of memory for a large model like the Llama-3.1 405B. In combination, these four require roughly 14 GB of memory.

For a batch size of 1K, the memory required for activation checkpoints can be estimated as: 16k (hidden size) x 126 (# of layers) x 1k (# of tokens) x $2/1k/1k/1k \sim= 4GB$.

Similarly, the memory needed to store the full set of activations for a single transformer can be estimated as 16k (hidden size) x

1k (# of tokens) x 64 (estimated scale factor, see eq.1 of Megatron-LM for more details and replace GeLU with SiLU) x 3 (base weight path, LoRA path and some other overhead) / 1k / 1k /1k ~= 3GB.

AUTHOR

The projection-layer forward and backward memory can be estimated as [128k (vocab size) x 1k (# of tokens) x 6 (est. of Snowflake Al Research activation sizes) x 2 + 128k (vocab size) x 16k (embed size)] x 2 (gradient of weights)] $/ 1k / 1k / 1k \sim = 5.5GB$.

SHARE

Finally, the LoRA parameters contribute to 126 (# of layers) x [6 in 6k. 2 (Q,O) + (64x16k+64x2k)x2 (k,V) + $(64x52k+64x16k)x3 (MLP)] \times (2+12) /10^9 = 4.1GB.$

These additions bring our per GPU memory requirement from 60 GB to about 74 GB, which is extremely tight.

To address these remaining requirements, we apply targeted offloading of a percentage of nn.Linear base weights to CPU when we are not using them. All of these optimizations combined finally allow us to fine-tune Llama 3.1 405B on a single node! See Figure 1 (below) for a visualization of the final states and their rough proportions. In an environment with two or more nodes we no longer need CPU off-load due to higher sharding opportunities.




Figure 1. Memory overheads with all optimizations in a one-node scenario.

End-to-end training times

With all of the above optimizations, single node fine-tuning over 20M tokens on 8xH100-80GB takes roughly 24 hours and 4 hours on two nodes at the time of publication. For latest results see our repo.

Quality evaluation

From an end-to-end perspective, all of the optimizations described here have been validated by comparing the training loss, with and without each optimization enabled, using our fine-tuning pipeline on the alpaca data set. We provide this script in our GitHub repo for your reference.

Getting Started

Open source fine-tuning system: For the most up-to-date resources on how to run Meta's Llama 3.1 405B with Snowflake's open source inference and fine-tuning pipelines, see our GitHub repo. This repo includes both example code

and documentation for running Llama 3.1 and Snowflake-Arctic models.

Llama 3.1 405B in Snowflake Cortex: Llama 3.1 405B will be available in public preview for our **Cortex Fine-Tuning** customers soon.

AUTHOR

Contributors

Snowflake AI Research


Snowflake Al Research: Jeff Rasley, Rajhans Samdani, Zhewei Yao, Yuxiong He, Samyam Rajbhandari (Tech Lead)


SHARE

Acknowledgements We would like to thank Meta for their one in all intership, the OSS AI community for their collaboration, and our leadership at Snowflake for their continued support.

SHARE f in

RELATED CONTENT





Because human-machine interaction using natural language is now possible with large language models (LLMs), more data teams and developers can bring AI to their daily workflows. To do this efficiently...

to your Data, Securely Customize LLMs and Streamline Model Operations

Generative AI presents enterprises with the opportunity to extract insights at scale from unstructured data...

More to follow

More

READ OUR EBOOK GENERATIVE AI IN PRACTICE

DOWNLOAD HERE



PLATFORM	SOLUTIONS	RESOURCES	EXPLORE	ABOUT	
Cloud Data	Snowflake for	Resource	News	About	
Platform	Financial	Library	Blog	Snowflake	
Pricing	Services	Webinars	Trending	Investor	
Marketplace	Snowflake for	Documentation		Relations	
Coourity	Advertising,	Advertising,	Community	Guides	Leadership
Security & Trust	Entertainment	Community	Developers	& Board	
11 03 0		Procurement			

Fine-Tune Llama 3.1 405B on a Single Node using Snowflake's AI Stack

Snowflake for Legal Retail & CPG

Snowflake Ventures

Healthcare &

Life Sciences

Careers Contact

Data Cloud Snowflake for

Marketing Analytics

AUTHOR

Snowflake AI Research

Sign up for

diana.shaw@snc United States

Snowflake

SHARE in \searrow

Communications By submitting this form, I understand Snowflake will process my personal information in accordance with their **Privacy Notice**. Additionally, I consent to my information being shared with Event Partners in accordance with Snowflake's Event Privacy Notice. I understand I may withdraw my consent or update my preferences here at any time.

SUBSCRIBE NOW

Privacy Notice | Site Terms | Cookie Settings | Do Not Share My Personal Information

© 2024 Snowflake Inc. All Rights Reserved | If you'd rather not receive future emails from Snowflake, unsubscribe here or customize your communication preferences

