



Print colours & production spec

Building sign 600 × 250 mm · Roll-up banner 830 × 2000 mm



BRAND COLOURS (UIA BRAND GUIDELINES V1.0, P. 13)

	COLOUR	CMYK	PANTONE	HEX	RGB	USED ON
	Midnight	C100 M80 Y40 K70	5395 C	#0B1626	11 22 38	Sign panel · banner ground
	Academy Blue	C85 M50 Y30 K25	7700 C	#29566C	41 86 108	Banner "Floor 4" band
	Academy Gold	C5 M40 Y90 K0	7409 C	#E2A02D	226 160 45	Logo gold · sign base line · floor number + arrow
	Platinum	C14 M9 Y8 K0	Cool Gray 1 C	#D8DADF	216 218 223	Banner small text, thin lines
	White	C0 M0 Y0 K0	—	#FFFFFF	255 255 255	Logo letters · main text
	Charcoal	C70 M60 Y50 K70	433 C	#26292E	38 41 46	Not used on these two jobs
	Paper	C3 M2 Y5 K0	Uncoated white	#F5F4F0	245 244 240	Not used on these two jobs

Important: the artwork PDFs are built in RGB. When preparing the files, **set these exact CMYK values** (or the Pantone for spot/vinyl/acrylic matching). Don't rely on automatic RGB → CMYK conversion. The guidelines say the values must be **confirmed against a printed proof**, so print a colour strip on the final material and send a photo in daylight for approval before the full run.

BUILDING SIGN · 600 × 250 MM

- File: **uia-building-sign-600x250mm-PRINT.pdf** (3 mm bleed, crop marks) or the exact-size PDF for CNC/laser cutting.
- Panel: 5 mm acrylic or 3–4 mm ACP, **Midnight**, matt or satin finish (no gloss: the lobby has strong window light).
- Logo 480 × 108 mm, centred. White + **Academy Gold**: raised 3 mm acrylic letters, or UV print.
- Gold base line: full width, 8 mm, along the bottom edge.
- Gold = flat **Pantone 7409 C** colour. **No mirror or chrome gold**, no gradients.
- Fixing: 4 stand-offs or hidden fixings, positions per installer, clear of the logo.

ROLL-UP BANNER · 830 × 2000 MM

- Files: **uia-rollup-830x2000mm-arrow-up/left/right-PRINT.pdf** (5 mm bleed, crop marks). Print one.
- Material: 440–510 g matt PVC or 200 µm polyester film (anti-curl, non-glare).
- Print ≥ 720 dpi, eco-solvent/latex/UV. Total ink on Midnight ≈ 290%: within large-format limits. Keep it rich, not grey.
- Stand: standard 85 × 200 cm roll-up (visible 83 cm). Bottom 150 mm sits in the cassette, top 30 mm in the rail; nothing important is placed there.
- Thin lines are Platinum at reduced strength and must stay visible but subtle.

NEVER

- Redraw, retype, stretch, rotate or recolour the logo. Use only the supplied files.
- Change the phone number: **+962 79 055 5890**.
- Add effects (shadow, glow, bevel) or put the logo on a busy background.