

# Rajalakshmi Engineering College

Name: Mohamed Faheem A  
Email: 240801198@rajalakshmi.edu.in  
Roll no: 240801198  
Phone: 9952218147  
Branch: REC  
Department: I ECE FB  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 2\_MCQ\_Updated

Attempt : 1  
Total Mark : 20  
Marks Obtained : 13

#### Section 1 : MCQ

1. What will be the output of the following program?

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* next;
    struct Node* prev;
};
```

```
int main() {
    struct Node* head = NULL;
    struct Node* tail = NULL;
    for (int i = 0; i < 5; i++) {
        struct Node* temp = (struct Node*)malloc(sizeof(struct Node));
```

```

temp->data = i + 1;
temp->prev = tail;
temp->next = NULL;
if (tail != NULL) {
    tail->next = temp;
} else {
    head = temp;
}
tail = temp;
}
struct Node* current = head;
while (current != NULL) {
    printf("%d ", current->data);
    current = current->next;
}
return 0;
}

```

**Answer**

1 2 3 4 5

**Status :** Correct

**Marks :** 1/1

2. What is the main advantage of a two-way linked list over a one-way linked list?

**Answer**

Two-way linked lists allow for traversal in both directions.

**Status :** Correct

**Marks :** 1/1

3. Which of the following is true about the last node in a doubly linked list?

**Answer**

Its prev pointer is NULL

**Status :** Wrong

**Marks :** 0/1

4. What does the following code snippet do?

```
struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
newNode->data = value;  
newNode->next = NULL;  
newNode->prev = NULL;
```

**Answer**

Creates a new node and initializes its data to 'value'

**Status :** Correct

**Marks :** 1/1

5. Which pointer helps in traversing a doubly linked list in reverse order?

**Answer**

prev

**Status :** Correct

**Marks :** 1/1

6. What happens if we insert a node at the beginning of a doubly linked list?

**Answer**

The next pointer of the new node is NULL

**Status :** Wrong

**Marks :** 0/1

7. How many pointers does a node in a doubly linked list have?

**Answer**

2

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following code?

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
int main() {  
    struct Node* head = NULL;  
    struct Node* temp = (struct Node*)malloc(sizeof(struct Node));  
    temp->data = 2;  
    temp->next = NULL;  
    temp->prev = NULL;  
    head = temp;  
    printf("%d\n", head->data);  
    free(temp);  
    return 0;  
}
```

**Answer**

1

**Status : Wrong**

**Marks : 0/1**

9. Which of the following is false about a doubly linked list?

**Answer**

It requires more space than a singly linked list

**Status : Wrong**

**Marks : 0/1**

10. What will be the effect of setting the prev pointer of a node to NULL in a doubly linked list?

**Answer**

It will break the list

**Status : Wrong**

**Marks : 0/1**

11. Consider the following function that refers to the head of a Doubly Linked List as the parameter. Assume that a node of a doubly linked list has the previous pointer as prev and the next pointer as next.

Assume that the reference of the head of the following doubly linked list is passed to the below function 1 <--> 2 <--> 3 <--> 4 <--> 5 <--> 6. What should be the modified linked list after the function call?

Procedure fun(head\_ref: Pointer to Pointer of node)

temp = NULL

current = \*head\_ref

While current is not NULL

temp = current->prev

current->prev = current->next

current->next = temp

current = current->prev

End While

If temp is not NULL

\*head\_ref = temp->prev

End If

End Procedure

**Answer**

6 <--> 5 <--> 4 <--> 3 <--> 2 <--> 1.

**Status :** Correct

**Marks :** 1/1

12. Which code snippet correctly deletes a node with a given value from a doubly linked list?

```
void deleteNode(Node** head_ref, Node* del_node) {  
    if (*head_ref == NULL || del_node == NULL) {  
        return;  
    }  
    if (*head_ref == del_node) {  
        *head_ref = del_node->next;  
    }  
}
```

```

    if (del_node->next != NULL) {
        del_node->next->prev = del_node->prev;
    }
    if (del_node->prev != NULL) {
        del_node->prev->next = del_node->next;
    }
    free(del_node);
}

```

**Answer**

Deletes the first occurrence of a given data value in a doubly linked list.

**Status :** Correct

**Marks :** 1/1

13. How do you delete a node from the middle of a doubly linked list?

**Answer**

All of the mentioned options

**Status :** Correct

**Marks :** 1/1

14. How do you reverse a doubly linked list?

**Answer**

By swapping the next and previous pointers of each node

**Status :** Correct

**Marks :** 1/1

15. Which of the following statements correctly creates a new node for a doubly linked list?

**Answer**

```
struct Node* newNode = (struct Node*) malloc(sizeof(struct Node));
```

**Status :** Correct

**Marks :** 1/1

16. What is the correct way to add a node at the beginning of a doubly

linked list?

**Answer**

```
void addFirst(int data){ Node* newNode = new Node(data);  newNode->next = head;      if (head != NULL) {          head->prev = newNode;  }  head = newNode;      }
```

**Status :** Correct

**Marks :** 1/1

17. Where Fwd and Bwd represent forward and backward links to the adjacent elements of the list. Which of the following segments of code deletes the node pointed to by X from the doubly linked list, if it is assumed that X points to neither the first nor the last node of the list?

A doubly linked list is declared as

```
struct Node {  
    int Value;  
    struct Node *Fwd;  
    struct Node *Bwd;  
};
```

**Answer**

```
X->Bwd->Fwd = X->Fwd ; X->Fwd->Bwd = X->Bwd;
```

**Status :** Wrong

**Marks :** 0/1

18. Consider the provided pseudo code. How can you initialize an empty two-way linked list?

```
Define Structure Node  
    data: Integer  
    prev: Pointer to Node  
    next: Pointer to Node  
End Define
```

```
Define Structure TwoWayLinkedList  
    head: Pointer to Node  
    tail: Pointer to Node
```

End Define

**Answer**

```
struct TwoWayLinkedList* list = malloc(sizeof(struct TwoWayLinkedList)); list->head = NULL; list->tail = NULL;
```

**Status :** Correct

**Marks :** 1/1

19. Which of the following information is stored in a doubly-linked list's nodes?

**Answer**

All of the mentioned options

**Status :** Correct

**Marks :** 1/1

20. What is a memory-efficient double-linked list?

**Answer**

An auxiliary singly linked list acts as a helper list to traverse through the doubly linked list

**Status :** Wrong

**Marks :** 0/1