

Rajalakshmi Engineering College

Name: Mohamed Faheem A
Email: 240801198@rajalakshmi.edu.in
Roll no: 240801198
Phone: 9952218147
Branch: REC
Department: I ECE FB
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

3

5

Output: 10 is inserted in the queue.

Elements in the queue are: 10

Invalid option.

Answer

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#define max 5
```

```
int queue[max];
```

```
int front = -1, rear = -1;
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#define MAX_SIZE 5
```

```
struct Queue {  
    int arr[MAX_SIZE];  
    int front, rear;  
};
```

```
void initQueue(struct Queue* q) {  
    q->front = -1;  
    q->rear = -1;  
}
```

```
int isFull(struct Queue* q) {  
    return (q->rear == MAX_SIZE - 1);  
}
```

```
int isEmpty(struct Queue* q) {  
    return (q->front == -1 || q->front > q->rear);  
}
```

```
void enqueue(struct Queue* q, int value) {  
    if (isFull(q)) {  
        printf("Queue is full.\n");  
    } else {
```

```

        if (q->front == -1) {
            q->front = 0;
        }
        q->rear++;
        q->arr[q->rear] = value;
        printf("%d is inserted in the queue.\n", value);
    }
}

```

```

void dequeue(struct Queue* q) {
    if (isEmpty(q)) {
        printf("Queue is empty.\n");
    } else {
        int deletedValue = q->arr[q->front];
        printf("Deleted number is: %d\n", deletedValue);
        q->front++;
    }
}

```

```

void display(struct Queue* q) {
    if (isEmpty(q)) {
        printf("Queue is empty.\n");
    } else {
        printf("Elements in the queue are: ");
        for (int i = q->front; i <= q->rear; i++) {
            printf("%d ", q->arr[i]);
        }
        printf("\n");
    }
}

```

```

int main() {
    struct Queue q;
    initQueue(&q);

    int option, value;

    while (scanf("%d", &option) != EOF) {
        if (option == 1) {
            scanf("%d", &value);
            enqueue(&q, value);
        } else if (option == 2) {

```

```

        dequeue(&q);
    } else if (option == 3) {
        display(&q);
    } else {
        printf("Invalid option.\n");
    }
}

return 0;
}

int main()
{
    int data, reply, option;
    while (1)
    {
        if (scanf("%d", &option) != 1)
            break;
        switch (option)
        {
            case 1:
                if (scanf("%d", &data) != 1)
                    break;
                reply = insertq(&data);
                if (reply == 0)
                    printf("Queue is full.\n");
                else
                    printf("%d is inserted in the queue.\n", data);
                break;
            case 2:
                delq(); // Called without arguments
                break;
            case 3:
                display();
                break;
            default:
                printf("Invalid option.\n");
                break;
        }
    }
    return 0;
}

```

Status : Correct

Marks : 10/10