



V93000 Specifications

V93000 SOC Port Scale RF Pure Clock

Version 8.6.0

Published on 2023-02-24

Notices

Legal Notices

All rights reserved. All text and figures included in this publication are the exclusive property of Advantest Corporation. Reproduction of this publication in any manner without the written permission of Advantest Corporation is prohibited. Information in this document is subject to change without notice.

Trademarks and Registered Trademarks

- ADVANTEST is a trademark of Advantest Corporation.
- All other marks referenced herein are trademarks or registered trademarks of their respective owners.

Warranty

The material contained in this document is provided "as is," and is subject to being changed, without notice, in future editions. Further, to the maximum extent permitted by applicable law, Advantest disclaims all warranties, either express or implied, with regard to this material and any information contained herein, including but not limited to the implied warranties of merchantability and fitness for a particular purpose. Advantest shall not be liable for errors or for incidental or consequential damages in connection with the furnishing, use, or performance of this material or of any information contained herein. Should Advantest and the user have a separate written agreement with warranty terms covering the material in this document that conflict with these terms, the warranty terms in the separate agreement shall control.

Technology Licenses

The hardware and/or software described in this document are furnished under a license and may be used or copied only in accordance with the terms of such license.

Restricted Rights Legend

If software is for use in the performance of a U.S. Government prime contract or subcontract, Software is delivered and licensed as "Commercial computer software" as defined in DFAR 252.227-7014 (June 1995), or as a "commercial item" as defined in FAR 2.101(a) or as "Restricted computer software" as defined in FAR 52.227-19 (June 1987) or any equivalent agency regulation or contract clause. Use, duplication or disclosure of Software is subject to Advantest's standard commercial license terms for 93000 systems and non-DOD Departments and Agencies of the U.S. Government will receive no greater than Restricted Rights as defined in FAR 52.227-19(c)(1-2) (June 1987). U.S. Government users will receive no greater than Limited Rights as defined in FAR 52.227-14 (June 1987) or DFAR 252.227-7015 (b)(2) (November 1995), as applicable in any technical data.

Safety Notices

⚠ CAUTION A CAUTION notice denotes a hazard. It calls attention to an operating procedure, practice, or the like that, if not correctly performed or adhered to, could result in damage to the product or loss of important data. Do not proceed beyond a CAUTION notice until the indicated conditions are fully understood and met.

▲ Warning A WARNING notice denotes a hazard. It calls attention to an operating procedure, practice, or the like that, if not correctly performed or adhered to, could result in death or severe injury. Do not proceed beyond a WARNING notice until the indicated conditions are fully understood and met.

RF Pure Clock specifications

The RF Pure Clock card, also referred to as Low Phase Noise (LPN) clock source, is mainly intended but not limited for use as a reference clock source when testing WiMAX devices.

Note

The underlying card is the same for SmarTest 7 and SmarTest 8. The card is referred to as Port Scale RF Pure Clock card in SmarTest 7.

Frequency range	10 kHz - 200 MHz (without covering phase noise requirements) 1 MHz - 200 MHz (while covering phase noise requirements)
Frequency resolution	Min. 0.153 Hz (without covering phase noise requirements) Min. 10 kHz (while covering phase noise requirements) 625 Hz for exact integer frequencies
Frequency accuracy	Locked to central 10 MHz
Minimum swing	-30 dBm, 19.997 mV _{pp} 50 Ω terminated without covering phase noise requirements 0 dBm, 632.360 mV _{pp} 50 Ω terminated while covering phase noise requirements
Maximum swing	4 dBm, 1.0 V _{pp} 50 Ω terminated while covering phase noise requirements
Swing accuracy	± 25 mV $\pm 5\%$ into 50 Ω
Level offset range	0 - +1.5 V into open (10 kHz - 500 kHz) 0 - +3 V into open (500 kHz - 200 MHz)
Level offset accuracy	± 25 mV $\pm 5\%$ into open
Level resolution	< 1 mV into open
Noise floor	-150 dBm/Hz
Channel to channel isolation	-60 dB

Phase-Noise in dBc/Hz at Offset

Output Frequency	100Hz	1 kHz	10 kHz	100 kHz	1 MHz	10 MHz
26 MHz	-117.7	-147.7	-150	-150	-150	-150
38.4 MHz	-114.3	-144.3	-150	-150	-150	-150

Output Frequency	100Hz	1 kHz	10 kHz	100 kHz	1 MHz	10 MHz
100 MHz	-106	-136	-145	-150	-150	-150
200 MHz	-100	-130	-142	-150	-150	-150

Further information

For more information about the Advantest V93000 SOC Series, please visit www.advantest.com.

Contact information

For more information about the Advantest V93000 SOC cards, please contact your local Advantest sales representative.

This information is subject to change without notice.