PWAccountsRep

PWAccountsRep(connection)
- peewee.Model model

+ create(Account obj)
+ delete(Account obj)
+ update(Account old_obj, Account new_obj)
+ get_all(): [Account]
+ get_by_login(str login): Account

PWCheckpointsRep

PWCheckpointsRep(connection)
- peewee.Model model

+ create(Checkpoint obj)
+ delete(Checkpoint obj)
+ update(Checkpoint old_obj, Checkpoint new_obj)
+ get_all(): [Checkpoint]
+ get_by_id(int id): Checkpoint

PWDeliveryRep

PWDeliveryRep(connection)
- peewee.Model model

+ create(Delivery obj)
+ delete(Delivery obj)
+ update(Delivery old_obj, Delivery new_obj)
+ get_all(): [Delivery]
+ get_by_id(int id): Delivery

PWPersonRep

PWPersonRep(connection)
- peewee.Model model

+ create(Person obj)
+ delete(Person obj)
+ update(Person old_obj, Person new_obj)
+ get_all(): [Person]
+ get_by_login(str login): Person

AccountsRepository

create(Account obj)
delete(Account obj)
update(Account old_obj, Account new_obj)
get_all(): [Account]
get_by_login(str login): Account

CheckpointsRepository

create(Checkpoint obj)
delete(Checkpoint obj)
update(Checkpoint old_obj, Checkpoint new_obj)
get_all(): [Checkpoint]
get_by_id(int id): Checkpoint

DeliveryRepository

create(Delivery obj)
delete(Delivery obj)
update(Delivery old_obj, Delivery new_obj)
get_all(): [Delivery]
get_by_id(int id): Delivery

PersonRepository

create(Person obj)
delete(Person obj)
update(Person old_obj, Person new_obj)
get_all(): [Person]
get_by_login(str login): Person

Repository

- connection

create(obj)
delete(obj)
update(old_obj, new_obj)
get_all()

PassRecordsRepository

create(PassRecord obj)
delete(PassRecord obj)
update(PassRecord old_obj, PassRecord new_obj)
get_all(): [PassRecord]
get_by_login(str login): PassRecord

TrucksRepository

create(Truck obj)
delete(Truck obj)
update(Truck old_obj, Truck new_obj)
get_all(): [Truck]
get_by_number(str number): Truck

DriverDutyRepository

create(DriverDuty obj)
delete(DriverDuty obj)
update(DriverDuty old_obj, DriverDuty new_obj)
get_all(): [DriverDuty]
get_by_number(str number): DriverDuty
get_by_time(begind, endd, str login, str platenumber): [DriverDuty]

GuardDutyRepository

create(GuardDuty obj)
delete(GuardDuty obj)
update(GuardDuty old_obj, GuardDuty new_obj)
get_all(): [GuardDuty]
get_by_number(str number): GuardDuty
get_by_time(begind, endd, str login, int check_id): [GuardDuty]

PWPassRecordsRep

PWPassRecordsRep(connection)
- peewee.Model model

+ create(PassRecord obj)
+ delete(PassRecord obj)
+ update(PassRecord old_obj, PassRecord new_obj)
+ get_all(): [PassRecord]
+ get_by_login(str login): PassRecord

PWTrucksRep

PWTrucksRep(connection)
- peewee.Model model

+ create(Truck obj)
+ delete(Truck obj)
+ update(Truck old_obj, Truck new_obj)
+ get_all(): [Truck]
+ get_by_number(str number): Truck

PWDriverDutyRep

PWDriverDutyRep(connection)
- peewee.Model model

+ create(DriverDuty obj)
+ delete(DriverDuty obj)
+ update(DriverDuty old_obj, DriverDuty new_obj)
+ get_all(): [DriverDuty]
+ get_by_number(str number): DriverDuty
+ get_by_time(begind, endd, str login, str platenumber): [DriverDuty]

PWGuardDutyRep

PWGuardDutyRep(connection)
- peewee.Model model

+ create(GuardDuty obj)
+ delete(GuardDuty obj)
+ update(GuardDuty old_obj, GuardDuty new_obj)
+ get_all(): [GuardDuty]
+ get_by_number(str number): GuardDuty
+ get_by_time(begind, endd, str login, int check_id): [GuardDuty]