

Fair Clustering

Outline

- Introduction to clustering and algorithmic fairness
- Demographic (group) fairness in clustering
- Individual fairness in clustering
- The two-stage approach for solving fair clustering
- Overlooked issues in fair clustering.

Clustering: Motivation

➤ Clustering (**ML + Data Analysis**)

Clustering: Motivation

➤ Clustering (**ML + Data Analysis**)





Explore the data, Reveal existing structure, group similar points to one another, etc

Clustering: Motivation

➤ Clustering (**ML + Data Analysis**)

Explore the data, Reveal existing structure, group similar points to one another, etc

Given Set of
Data Points:







Clustering: Motivation





➤ Clustering (**ML + Data Analysis**)

Explore the data, Reveal existing structure, group similar points to one another, etc

Given Set of
Data Points:



clustering with $k=4$



Clustering: Motivation

- Clustering (**ML + Data Analysis**)

Explore the data, Reveal existing structure, group similar points to one another, etc

- Clustering (**Operations Research**)

Clustering: Motivation

- Clustering (**ML + Data Analysis**)

Explore the data, Reveal existing structure, group similar points to one another, etc

- Clustering (**Operations Research**) ‘

Allocating a collection of facilities or fire stations to serve a collection of users

Clustering: Motivation



➤ Clustering (**ML + Data Analysis**)

Explore the data, Reveal existing structure, group similar points to one another, etc

➤ Clustering (**Operations Research**) ‘

Allocating a collection of facilities or fire stations for a collection of users

Set of Possible
Locations:



clustering with $k=2$



Clustering: Motivation



➤ Clustering (**ML + Data Analysis**)

Explore the data, Reveal existing structure, group similar points to one another, etc



➤ Clustering (**Operations Research**) ‘

Allocating a collection of facilities or fire stations for a collection of users

Set of Possible
Locations:



clustering with $k=2$



Types of Clustering

Types of Clustering

- Center-Based Clustering

- Spectral Clustering

- Correlation Clustering

- Hierarchical Clustering

Center-Based Clustering

- the cluster is decided by choosing k ***centers*** → each point is then assigned to ***its closest center***
- Includes k -means, k -median, and k -center clustering

Formalizing Center-Based Clustering

- *Input:*
 - Set of points: \mathcal{C}
 - Distance between points: $\forall i, j \in \mathcal{C}$ we have $d(i, j)$ (which is a ***Metric***)
 - Number of Clusters: k

Formalizing Center-Based Clustering

- *Input:*

- Set of points: \mathcal{C}
- Distance between points: $\forall i, j \in \mathcal{C}$ we have $d(i, j)$ (which is a ***Metric***)
- Number of Clusters: k

- *Output:*

- Set of centers: S ($|S| \leq k$)
- Assignment Function: $\varphi: \mathcal{C} \rightarrow S$ (assigning points to centers)

Formalizing Center-Based Clustering

Objective Functions:

- **k -center:** $\min_{S, \varphi} \max_{j \in \mathcal{C}} d(j, \varphi(j))$

Formalizing Center-Based Clustering

Objective Functions:

- **k -center:** $\min_{S, \varphi} \max_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the maximum distance (**sensitive to outliers**)

Formalizing Center-Based Clustering

Objective Functions:

- **k -center:** $\min_{S, \varphi} \max_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the maximum distance (**sensitive to outliers**)

- **k -median:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d(j, \varphi(j))$

Formalizing Center-Based Clustering

Objective Functions:

- **k -center:** $\min_{S, \varphi} \max_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the maximum distance (**sensitive to outliers**)

- **k -median:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the sum of the distances (**more noise-tolerant**)

Formalizing Center-Based Clustering

Objective Functions:

- **k -center:** $\min_{S, \varphi} \max_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the maximum distance (**sensitive to outliers**)

- **k -median:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the sum of the distances (**more noise-tolerant**)

- **k -means:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d^2(j, \varphi(j))$

Formalizing Center-Based Clustering

Objective Functions:

- **k -center:** $\min_{S, \varphi} \max_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the maximum distance (**sensitive to outliers**)

- **k -median:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the sum of the distances (**more noise-tolerant**)

- **k -means:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d^2(j, \varphi(j))$

Minimizes the sum of the square of the distances (**more weight on outliers because of squaring**)

Formalizing Center-Based Clustering

Objective Functions:

- **k -center:** $\min_{S, \varphi} \max_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the maximum distance (**sensitive to outliers**)

- **k -median:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d(j, \varphi(j))$

Minimizes the sum of the distances (**more noise-tolerant**)

- **k -means:** $\min_{S, \varphi} \sum_{j \in \mathcal{C}} d^2(j, \varphi(j))$

Minimizes the sum of the square of the distances (**more weight on outliers because of squaring**)

- **In General:** $\min_{S, \varphi} \left\| [d(1, \varphi(1)), d(2, \varphi(2)), \dots, d(n, \varphi(n))] \right\|_p$

$p = \infty \rightarrow k$ -center, $p = 1 \rightarrow k$ -median, $p = 2 \rightarrow k$ -means

Spectral Clustering

- Points are vertices in a graph $G = (V, E)$
- $\forall i, j: w_{ij} \geq 0$, w_{ij} is the similarity between i and j

Spectral Clustering

- Points are vertices in a graph $G = (V, E)$
- $\forall i, j: w_{ij} \geq 0$, w_{ij} is the similarity between i and j
- Cluster (partition) the graph so that the edges *between points in different clusters* have low weight
- From the above, we have a graph cut problem

Spectral Clustering: Formal Definition

- Points are vertices in a graph $G = (V, E)$
- $\forall i, j: w_{ij} \geq 0$, w_{ij} is the similarity between i and j
- $A, B \subset V$, $cut(A, B) = \sum_{i \in A, j \in B} w_{ij}$
- Objective Functions:
 - Given graph $G = (V, E)$ and number of clusters $k \rightarrow$ Partition V into C_1, \dots, C_k
 - $\min RatioCut(C_1, \dots, C_k) = \sum_{i=1}^k \frac{cut(C_i, V \setminus C_i)}{|C_i|}$
 - $\min NormalizedCut(C_1, \dots, C_k) = \sum_{i=1}^k \frac{cut(C_i, V \setminus C_i)}{\sum_{j \in C_i} d_j}$

Correlation Clustering

- Points are vertices in a graph $G = (V, E)$
- $\forall i, j: w_{ij}^+ \geq 0, w_{ij}^- \geq 0,$
 - w_{ij}^+ is the degree to which i and j are **similar**
 - w_{ij}^- is the degree to which i and j are **different**

Correlation Clustering

- Points are vertices in a graph $G = (V, E)$
- $\forall i, j: w_{ij}^+ \geq 0, w_{ij}^- \geq 0,$
 - w_{ij}^+ is the degree to which i and j are **similar**
 - w_{ij}^- is the degree to which i and j are **different**
- Cluster (partition) the graph so that you get:
 - *large w_{ij}^+ edges within a cluster*
 - *large w_{ij}^- edges between different clusters*

Correlation Clustering

- Points are vertices in a graph $G = (V, E)$
- $\forall i, j: w_{ij}^+ \geq 0, w_{ij}^- \geq 0,$
 - w_{ij}^+ is the degree to which i and j are **similar**
 - w_{ij}^- is the degree to which i and j are **different**
- Cluster (partition) the graph so that you get
 - *low weight edges between different clusters*
 - *high weight edges within a cluster*

➤ Objective Function:

Given graph $G = (V, E) \rightarrow$ Partition V into C_1, \dots, C_k

$$\max \sum_{i,j: \text{same cluster}} w_{ij}^+ + \sum_{i,j: \text{different clusters}} w_{ij}^-$$

Number of clusters k **does NOT need to be given** in correlation clustering

Hierarchical Clustering

- Like correlation clustering, you don't need to set k (the number of clusters)
- The output groups the points in a tree, giving groupings at different levels
- **agglomerative clustering** (common traditional method):
 - bottom-up approach, group similar points together forming a cluster, then group similar clusters and so on.

Hierarchical Clustering

- Like correlation clustering, you don't need to set k (the number of clusters)
- The output groups the points in a tree, grouping points at different levels
- **agglomerative clustering** (common traditional method):
 - bottom-up approach*: group similar points together forming a cluster, then group similar clusters and so on.

Hierarchical Clustering

- agglomerative clustering has is **NOT** optimizing an objective function
 - Makes it hard to know the quality

Hierarchical Clustering

➤ agglomerative clustering has is **NOT** optimizing an objective function

→ Makes it hard to know the quality

➤ [Dasgupta, 2016] defines a cost function for hierarchical clustering:

-Given $G = (V, E)$ with w_{ij} specifying the similarity between i and j

Objective Function:

$\min \sum_{i,j} w_{ij} \times (\text{\#of descendents of lowest common ancestor of } i \text{ and } j)$

-the objective places higher penalty when separating points higher in the tree

➤ Further objectives for hierarchical clustering were also introduced [Moseley & Wang, 2017 ; Cohen-Addad et al, 2018].

Algorithmic Fairness

- Much of decision making is done at least partly using algorithms.

Algorithmic Fairness

- Much of decision making is done at least partly using algorithms.

Examples: ML for recidivism prediction, loan approval

Algorithmic Fairness

- Much of decision making is done at least partly using algorithms.

Examples: ML for recidivism prediction, loan approval

- Documented cases of algorithmic bias [O'Neil 2016; Kearns & Roth 2019].
- Substantial progress and interest in algorithmic fairness.

Some Considerations for Fairness in Clustering

- For a point i , its **distance from the center** $d(i, \phi(i))$:
 - closer to the center \rightarrow more represented by the center (**ML**)
 - closer to the center \rightarrow less travel distance (**OR**)
 - \rightarrow points want to be closer the center
- How does a fairness guarantee over the distance look like? How can we achieve that?

Some Considerations for Fairness in Clustering

- Clustering partitions the set of points \mathcal{C} into clusters C_1, C_2, \dots, C_k
 - different clusters will be processed differently, enjoy different outcomes, etc
 - suppose one demographic is under-represented in a cluster or over-represented in another.
 - suppose clustering assigns points which are not faraway from one another to different clusters.
- How do avoid the above situations and guarantee fairness?