NPTEL MOOC

PROGRAMMING, DATA STRUCTURES AND ALGORITHMS IN PYTHON

Week 4, Lecture 1

Madhavan Mukund, Chennai Mathematical Institute http://www.cmi.ac.in/~madhavan

O(n²) sorting algorithms


- * Selection sort and insertion sort are both O(n²)
- * O(n²) sorting is infeasible for n over 5000


A different strategy?


- * Divide array in two equal parts
- * Separately sort left and right half
- * Combine the two sorted halves to get the full array sorted


Combining sorted lists


- * Given two sorted lists A and B, combine into a sorted list C
 - * Compare first element of A and B
 - * Move it into C
 - * Repeat until all elements in A and B are over
- * Merging A and B

















- * Sort A[0:n//2]
- * Sort A[n//2:n]
- * Merge sorted halves into B[0:n]
- * How do we sort the halves?
 - * Recursively, using the same strategy!

43 32 22 78 63 57 91 13






43 32 22 78


RPHE



NPTEL







43 32






















Divide and conquer

- * Break up problem into disjoint parts
- * Solve each part separately
- * Combine the solutions efficiently

Combine two sorted lists A and B into C

- * If A is empty, copy B into C
- * If B is empty, copy A into C
- * Otherwise, compare first element of A and B and move the smaller of the two into C
- * Repeat until all elements in A and B have been moved

Merging

```
def merge(A,B): # Merge A[0:m],B[0:n]
(C,m,n) = ([],len(A),len(B))
 (i,j) = (0,0) # Current positions in A,B
while i+j < m+n: # i+j is number of elements merged so far
  if i == m: # Case 1: A is empty
    C.append(B[j])
     j = j+1
   elif j == n: # Case 2: B is empty
     C.append(A[i])
     i = i+1
   elif A[i] <= B[j]: # Case 3: Head of A is smaller
     C.append(A[i])
     i = i+1
   elif A[i] > B[j]: # Case 4: Head of B is smaller
    C.append(B[j])
    j = j+1
 return(C)
```

Merging, wrong

```
def mergewrong(A,B): # Merge A[0:m],B[0:n]
 (C,m,n) = ([],len(A),len(B))
 (i,j) = (0,0) # Current positions in A,B
 while i+j < m+n:
 # i+j is number of elements merged so far
   # Combine Case 1, Case 4
   if i == m \text{ or } A[i] > B[j]:
     C.append(B[j])
     j = j+1
   # Combine Case 2, Case 3:
   elif j == n \text{ or } A[i] <= B[j]:
     C.append(A[i])
     i = i+1
 return(C)
```

To sort A[0:n] into B[0:n]

- * If n is 1, nothing to be done
- * Otherwise
 - * Sort A[0:n//2] into L (left)
 - * Sort A[n//2:n] into R (right)
 - * Merge L and R into B

```
def mergesort(A,left,right):
 # Sort the slice A[left:right]
 if right - left <= 1: # Base case
    return(A[left:right])
 if right - left > 1: # Recursive call
    mid = (left+right)//2
    L = mergesort(A, left, mid)
    R = mergesort(A, mid, right)
    return(merge(L,R))
```