Intermediate Code Generation using Syntax-Directed Definitions (SDD) and Syntax-Directed Translation (SDT)

Lecture Notes based on *Compilers: Principles, Techniques, and Tools* (the "Dragon Book"), 2nd Edition, Aho, Lam, Sethi, Ullman – Chapters 5 and 6

Suggested Lecture Plan (3–4 lectures)

Lecture 1 Role of intermediate code; forms of IR: syntax trees, DAGs, three-address code, quadruples and triples (indirect triples as a refinement), SSA form and the φ-function.

Lecture 2 *Syntax-directed definitions and translation, from scratch:* why syntax alone is not enough, attributes, semantic rules, synthesized and inherited attributes, dependency graphs, S- and L-attributed definitions; then SDTs: actions inside productions, postfix translation, marker nonterminals.

Lecture 3 Translation of expressions and assignments, array references, type checking and conversion.

Lecture 4 Boolean expressions and short-circuit code, flow-of-control statements, back-patching, switch statements and procedure calls; revision and exercises.

Contents

1 Introduction: Why Intermediate Code? 4

1.1 Advantages of using an intermediate representation 4

2 Variants of Syntax Trees and Intermediate Representations 4

2.1 Syntax trees (abstract syntax trees) 4

2.2 Directed acyclic graphs (DAGs) for expressions 5

2.2.1 The value-number method for constructing DAGs 6

2.3 Three-address code (TAC) 9

2.3.1 Generating three-address code from a DAG 9

2.3.2 Addresses and instructions 10

2.3.3 Representations of three-address code 10

2.3.4 Static single-assignment (SSA) form and the φ-function 12

3 Syntax-Directed Definitions (SDD) 15

3.1 What is an SDD, and what is it for? . . . 15
3.2 Attributes . . . 17
3.3 Semantic rules: a first tiny example . . . 18
3.4 Formal definition . . . 19
3.5 Synthesized and inherited attributes . . . 19
3.6 Annotated parse trees and dependency graphs . . . 20
3.7 Classes of SDDs that are easy to implement . . . 23
3.8 More examples: L-attributed and general (non-circular) SDDs . . . 24
3.9 SDD for constructing syntax trees . . . 26
3.10 SDD for constructing DAGs directly . . . 30

4 Syntax-Directed Translation Schemes (SDT) 32
4.1 From specification to implementation . . . 32
4.2 Definition and the meaning of an action's position . . . 33
4.3 Postfix translation schemes . . . 33
4.4 Worked example: infix to postfix, written out completely . . . 35
4.5 SDTs with actions inside productions . . . 37
4.6 Marker nonterminals (actions in the middle, for bottom-up parsing) . . . 40
4.7 Eliminating left recursion from an SDT . . . 41
4.8 Converting an L-attributed SDD into an SDT . . . 49
4.9 Application: the structure of a type (array types) . . . 50
4.10 Implementing L-attributed SDDs during top-down parsing . . . 52
4.10.1 Method A: recursive descent with arguments and return values . . . 52
4.10.2 Method B: on-the-fly code generation . . . 54
4.10.3 Method C: attributes on the stack of a table-driven LL parser . . . 55

5 Translation of Expressions and Assignments 56
5.1 SDD for three-address code . . . 56
5.2 Incremental translation (SDT with `gen` emitting directly) . . . 58
5.3 Addressing array elements . . . 58
5.4 Translation of array references . . . 59

6 Type Checking and Type Conversion 60
6.1 Type conversion (coercion) . . . 61

7 Control Flow: Boolean Expressions and Statements 62
7.1 Start here: a tiny example with labels . . . 63
7.2 Short-circuit (jumping) code . . . 66

7.3 Flow-of-control statements: SDD with inherited labels 67
7.4 SDD for boolean expressions (jumping code) 68
7.5 Avoiding redundant gotos (fall-through) 69

8 Backpatching **70**
8.1 The problem and the idea 70
8.2 Start here: four small examples by hand 71
8.3 Boolean expressions 75
8.4 Flow-of-control statements 76
8.5 Comparison: inherited labels vs. backpatching 77

9 Switch Statements and Procedure Calls **77**
9.1 Switch statement 78
9.2 Procedure calls 81

10 A Complete Worked Example **85**

11 Summary and Key Takeaways **86**

12 Practice Problems **87**

1 Introduction: Why Intermediate Code?

In the *analysis–synthesis* model of a compiler, the **front end** analyses the source program and produces an **intermediate representation (IR)**; the **back end** synthesises the target program from that IR.




Figure 1: Position of the intermediate code generator in a compiler. The shaded (thick) box is the topic of these notes. In practice, static checking and intermediate code generation are often done together in one pass.

1.1 Advantages of using an intermediate representation

- **Retargeting.** A compiler for m languages and n machines needs only m front ends plus n back ends ($m+n$ pieces instead of $m \times n$ separate compilers) if they share one IR. For example, 3 languages and 4 machines need $3 + 4 = 7$ pieces instead of 12 compilers.
- **Machine-independent optimisation.** Optimisations (common sub-expression elimination, constant folding, loop-invariant code motion, ...) are applied once on the IR.
- **Simplicity.** Complex source constructs are lowered to a few simple operations, making code generation easier.

Static checking vs. intermediate code

Static checking includes type checking and syntactic checks that the grammar cannot enforce (e.g., `break` must be inside a loop). Dragon Book Chapter 6 treats type checking and intermediate-code generation together, because both are done by attaching attributes and actions to the grammar.


2 Variants of Syntax Trees and Intermediate Representations

2.1 Syntax trees (abstract syntax trees)


A **syntax tree** is a condensed form of the parse tree: operators and keywords appear as *interior nodes*, and operands as children. Chains of single productions (such as $E \to T \to F \to \mathbf{id}$) disappear, and so do punctuation tokens such as parentheses. The tree keeps only what later phases need: *which operation is applied to which operands.*

Example: parse tree vs. syntax tree for $a + b * c$

Take the usual grammar $E \to E + T \mid T$, $T \to T * F \mid F$, $F \to \mathbf{id}$.



(a) parse tree: 13 nodes



(b) syntax tree: 5 nodes

Figure 2: Parse tree and syntax tree of $a + b * c$. Precedence survives in the shape of the syntax tree: $*$ is below $+$, so it is evaluated first.

Most parse-tree nodes only record *how the grammar was written* (the chains $E \to T \to F$); the syntax tree has 5 nodes. Parentheses never appear in a syntax tree: $(a + b) * c$ simply has the $+$ node below the $*$ node.


2.2 Directed acyclic graphs (DAGs) for expressions

A **DAG** identifies the *common sub-expressions*: a node is shared if the same sub-expression appears more than once. It shows the same information as a syntax tree but is more compact, and it directly suggests how to generate efficient code that computes a common sub-expression only once.


Example: tree vs. DAG for $a + a * (b - c) + (b - c) * d$

Figure 3 shows the syntax tree (left) and the DAG (right). In the DAG, the leaf a and the sub-expression $b - c$ are each shared by two parents.

Why arrows? A DAG is a *directed* acyclic graph. Each edge points from an operator node to one of its operands ("this operation uses that value"), so a node with two incoming arrows is a value that is used twice. There is no cycle because an expression can never be an operand of itself. In a tree the direction is the same but is left implicit, since every node has exactly one parent.



(a) Syntax tree



(b) DAG

Figure 3: Syntax tree and DAG for $a + a * (b - c) + (b - c) * d$. In the DAG every edge is an arrow from an operator to one of its operands.

2.2.1 The value-number method for constructing DAGs

The problem. While building the tree for an expression, we want to *reuse* a node if the same sub-expression has already been built. To do this we need a fast way to answer: "Have I already created a node for $b - c$?" The **value-number method** gives a simple answer. Here we assume the *syntax tree* of the expression has already been built (Figure 3(a)). We convert it into a DAG by visiting the tree nodes in **post-order** (left subtree, right subtree, then the node itself), so that the children of a node are always handled before the node.

The idea. Keep all nodes in an **array of records**. Each record describes one node of the DAG, and the *position (index) of the record in the array is the node's value number*. The value number is therefore just the node's *name*: "node 4" means "the record at position 4".

What the numbers mean

- **Value number** = the index of a record in the array = the identity of one DAG node. It is *not* the numeric value of the expression (the number 4 does not mean the expression evaluates to 4).
- A **leaf record** stores the kind of leaf and what it is: (**id**, pointer to symbol-table entry) for a variable, or (**num**, value) for a constant.
- An **interior record** has the form (op, *left*, *right*). Here op is the operator, and ***left* and *right* are the value numbers of the two child nodes**, i.e., they are *pointers* to other records (the operands).

Example. The record $(*,\ 1,\ 4)$ means: "a node for the operator $*$ whose left child is node 1 and whose right child is node 4". Looking up the array, node 1 is the leaf a and node 4 is $b - c$; so this record stands for $a * (b - c)$.

Algorithm: finding or creating a node

To create a node with signature $\langle op,\ l,\ r\rangle$ (where l and r are value numbers of the children that were already created):

1. **Search** the array for a record with exactly the same op, *left* $= l$, and *right* $= r$.
2. If such a record **exists**, do not create anything; **return its value number**. (This is the common sub-expression being shared.)
3. Otherwise **append** a new record $(op,\ l,\ r)$ at the end of the array and **return its index** as the new value number.

(For speed, a hash table keyed on (op, l, r) replaces the linear search in step 1.)


Why does comparing only (op, l, r) work? Two nodes represent the same expression exactly when they have the same operator and the same children. Children are the same exactly when they have the same value numbers (because every distinct sub-expression gets exactly one number). So, by building from the leaves upward, equal sub-expressions always get equal numbers.

A second example: $(a + b) * (a + b)$ and the commutativity trap

Post-order requests and the records they create:

1. leaf $a \Rightarrow$ new record 1; leaf $b \Rightarrow$ new record 2; $\langle +, 1, 2\rangle \Rightarrow$ new record 3.
2. Second copy: leaf $a \Rightarrow$ found (1); leaf $b \Rightarrow$ found (2); $\langle +, 1, 2\rangle \Rightarrow$ **found (3)**, shared.
3. $\langle *, 3, 3\rangle \Rightarrow$ new record 4 (both children are the same node).

The DAG has 4 nodes (the tree has 7) and gives `t1 = a + b`, `t2 = t1 * t1`. Note that the $*$ node has *two* arrows into the same node: its left and its right operand are one and the same value.



Now try $(a+b)*(b+a)$: the second sum is $\langle +, 2, 1\rangle$, which is *not* equal to $\langle +, 1, 2\rangle$, so a new node is created and $a+b$ is computed twice. To avoid this, a compiler stores the children of a commutative operator in a canonical order (say, smaller value number first); then $\langle +, 2, 1\rangle$ becomes $\langle +, 1, 2\rangle$ and is shared.

Limits of the method


The test "same *op* and same children" finds only *syntactically identical* sub-expressions (up to the operand-order trick above). It does not know that $x*2$ and $x+x$ are equal; that needs algebraic simplification, a separate optimisation.

Step-by-step example: $a + a*(b-c) + (b-c)*d$**.** We walk the syntax tree of Figure 3(a) in post-order: a, a, b, c, then $-$, $*$, $+$ of the left part, then b, c, $-$, d, $*$, and finally the root $+$. At every tree node we ask the array for the matching DAG node. Table 1 shows each request and what the algorithm does.

Step	Request	Found in array?	Action	Returns
1	leaf a	no	create record 1: $(\mathbf{id}, a)$	1
2	leaf a (2nd time)	**yes, record 1**	nothing created	1
3	leaf b	no	create record 2: $(\mathbf{id}, b)$	2
4	leaf c	no	create record 3: $(\mathbf{id}, c)$	3
5	$\langle -, 2, 3\rangle$ $(b-c)$	no	create record 4: $(-, 2, 3)$	4
6	$\langle *, 1, 4\rangle$ $(a*(b-c))$	no	create record 5: $(*, 1, 4)$	5
7	$\langle +, 1, 5\rangle$ $(a+a*(b-c))$	no	create record 6: $(+, 1, 5)$	6
8	leaf b (2nd time)	**yes, record 2**	nothing created	2
9	leaf c (2nd time)	**yes, record 3**	nothing created	3
10	$\langle -, 2, 3\rangle$ ($b-c$ again)	**yes, record 4**	nothing created – *shared!*	4
11	leaf d	no	create record 7: $(\mathbf{id}, d)$	7
12	$\langle *, 4, 7\rangle$ $((b-c)*d)$	no	create record 8: $(*, 4, 7)$	8
13	$\langle +, 6, 8\rangle$ (whole expression)	no	create record 9: $(+, 6, 8)$	9

Table 1: Trace of the value-number method. Steps 2, 8, 9, 10 reuse existing nodes; step 10 is where the common sub-expression $b-c$ is detected.

The result has only 9 nodes (a plain syntax tree would have 13: it repeats a, b, c and the whole $b-c$ sub-tree). The final value number 9 identifies the root of the DAG.



red number = value number (index of the node's record in the array)

Arrows point from an operator to its operands.

Nodes 1 and 4 each have **two parents** (two incoming arrows): they are shared.

Figure 4: The DAG for $a + a * (b - c) + (b - c) * d$ with the value number of every node in red. Arrows go from operator to operand.

value no.	op	left	right
1	id a	–	–
2	id b	–	–
3	id c	–	–
4	−	2	3
5	$*$	1	4
6	+	1	5
7	id d	–	–
8	$*$	4	7
9	+	6	8

left = 1 points to record 1 (the leaf a)

right = 4 points to record 4 (the node $b - c$)

So record 5 = $(*, 1, 4)$ represents $a * (b - c)$.

Figure 5: The array of records after processing the example. Interior records contain *value numbers of their children*; here record 5 refers to records 1 and 4.

The whole procedure. Converting a syntax tree into a DAG is a single post-order traversal:

```
int buildDAG(TreeNode t) {            // returns a value number
    if (t is a leaf)
        return findOrCreateLeaf(t);   // search (id/num, entry); create if absent
    l = buildDAG(t.left);             // children first (post-order)
    r = buildDAG(t.right);
    return findOrCreateNode(t.op, l, r);   // search (op,l,r); create if absent
}
```

The "search" is only a *lookup of an identical record* in the array (or hash table); it is not a second traversal of the tree.

Looking ahead

Building the tree first and then converting it is easy to understand. Later, after we study syntax-directed definitions (Section 3.10), we will see that the same DAG can be built *directly while parsing*, without constructing the tree at all: the parser simply calls the find-or-create routine each time it recognises an operator.

2.3 Three-address code (TAC)

In **three-address code** every instruction has *at most one operator on the right side* and at most three addresses (two operands and one result). Compound expressions are broken into temporaries, so the order of evaluation is made explicit.

For $a + a * (b - c) + (b - c) * d$ the TAC (from the DAG, reusing $t_1 = b - c$) is:

```
t1 = b - c
t2 = a * t1
t3 = a + t2
t4 = t1 * d
t5 = t3 + t4
```

Without the DAG (from the tree) $b - c$ would be computed twice.

2.3.1 Generating three-address code from a DAG

Three-address code can be generated from the DAG alone; no SDD or SDT is needed.

Idea. Every *interior* node of the DAG becomes exactly *one* three-address instruction, with a fresh temporary holding its result. *Leaves* generate no instruction: they only supply a name (a variable such as a, or a constant). A shared node is still one node, so it produces only one instruction; this is how the DAG removes the common sub-expression.

Order. Process the records of the array in increasing order of value number. A node's children were always created before the node, so their value numbers are smaller, and their results are ready when the node is reached. The array order is therefore already a valid evaluation order.

```
for i = 1 to n:                          // records in the array, in index order
    if record i is a leaf:
        name[i] = the variable or constant it stands for
    else:                                // record i = (op, left, right)
        name[i] = newTemp()
        emit( name[i] = name[left] op name[right] )
```

Here $name[i]$ is the address that holds the value of node i. For an assignment $x = \langle\text{expression}\rangle$ we finish with one more instruction, `x = name[root]`.

Record	Content	$name[left]$	$name[right]$	$name[i]$	Instruction emitted
1	`id` a	–	–	a	(none, leaf)
2	`id` b	–	–	b	(none, leaf)
3	`id` c	–	–	c	(none, leaf)
4	$(-, 2, 3)$	b	c	t_1	`t1 = b - c`
5	$(*, 1, 4)$	a	t_1	t_2	`t2 = a * t1`
6	$(+, 1, 5)$	a	t_2	t_3	`t3 = a + t2`
7	`id` d	–	–	d	(none, leaf)
8	$(*, 4, 7)$	t_1	d	t_4	`t4 = t1 * d`
9	$(+, 6, 8)$	t_3	t_4	t_5	`t5 = t3 + t4`

Table 2: Generating three-address code from the array of Figure 5 (the DAG of $a + a * (b - c) + (b - c) * d$). Node 4 has two parents (nodes 5 and 8) but produces only one instruction; both parents use t_1.

Three ways to obtain three-address code.

Method	How	Common sub-expressions
1. From a finished DAG	Scan the array in index order (above); no SDD/SDT needed.	Computed once (shared nodes).
2. During DAG construction	Whenever find-or-create *creates* a node, emit its instruction; when it finds an existing node, emit nothing. Needs SDD/SDT (Section 3.10).	Computed once.
3. SDD/SDT directly from the parse (Section 5.1)	Each reduction emits an instruction using *newTemp* and *gen*; no DAG is built.	Computed again each time they occur (e.g., $b - c$ twice).

SDD/SDT is the *mechanism* for generating code in one pass while parsing; the DAG is what gives *sharing*. Methods 1 and 2 give the same code.

Caution: assignments inside the DAG

If the DAG covers several statements and a variable is *reassigned* in between (e.g., `a = a + 1`), a later use of a is a different value and must not share the old leaf or any node built from it. Compilers handle this by creating a new leaf (a new value number) after each assignment. For single expressions, as in these notes, the issue does not arise.

2.3.2 Addresses and instructions

An **address** can be: (i) a *name* (source variable; a pointer to its symbol-table entry), (ii) a *constant*, or (iii) a compiler-generated *temporary*.

Instruction form	Meaning
`x = y op z`	binary assignment
`x = op y`	unary assignment (`minus`, `not`, conversions)
`x = y`	copy
`goto L`	unconditional jump
`if x goto L` / `ifFalse x goto L`	conditional jump on truth value
`if x relop y goto L`	conditional jump on comparison
`param x`, `call p, n`, `y = call p, n`, `return y`	procedure calls
`x = y[i]`, `x[i] = y`	indexed copy (memory at address $y + i$)
`x = &y`, `x = *y`, `*x = y`	address and pointer assignments
`L:`	label (a symbolic name for an instruction)

Table 3: Common three-address instruction forms.

2.3.3 Representations of three-address code

Three-address code is an *abstract* language: it says *what* the instructions are. A compiler also has to decide *how to store* them in memory, as records in an array. There are two basic record layouts: **quadruples** and **triples**. Each of them represents the complete code on its own. (A third name,

indirect triples, is introduced at the end of this subsection; it is not a different representation of the code but an *add-on to triples* that makes reordering cheap.)

Take the source statement $a = b * -c + b * -c$.

(a) Three-address code

```
t1 = minus c
t2 = b * t1
t3 = minus c
t4 = b * t3
t5 = t2 + t4
a  = t5
```

(b) Quadruples – (op, arg1, arg2, result)

	op	arg_1	arg_2	result
0	`minus`	c		t1
1	`*`	b	t1	t2
2	`minus`	c		t3
3	`*`	b	t3	t4
4	`+`	t2	t4	t5
5	`=`	t5		a

(c) Triples – (op, arg1, arg2). There is no result field: another instruction refers to this result by the *position* of the triple, written (i).

	op	arg_1	arg_2
0	`minus`	c	
1	`*`	b	(0)
2	`minus`	c	
3	`*`	b	(2)
4	`+`	(1)	(3)
5	`=`	a	(4)

How to read it. Triple 1 means "multiply b by *the result of triple 0*". Triple 4 adds the results of triples 1 and 3. The temporaries $t_1, \ldots, t_5$ have disappeared: the *position* plays their role.

	Advantage	**Disadvantage**
Quadruples	Every result has an explicit name (a temporary), so an instruction can be moved anywhere without editing any other instruction.	Needs an extra field, and temporaries must be entered in the symbol table.
Triples	No temporaries and no result field: more compact.	A result is identified by its position, so *moving* a triple changes its number and every instruction that refers to it must be edited.

Table 4: Quadruples versus triples.

Indirect triples: triples plus an ordering list. The disadvantage of triples shows up in optimisation, where the compiler often wants to *reorder* instructions. Indirect triples fix it by separating two things that plain triples tie together: *the triples themselves* (kept in a fixed array, numbered once and never renumbered) and *the order of execution* (a separate list of pointers to triples). So indirect triples are not a new way of writing the code; they are triples with one extra list.

Example: evaluate $c * d$ before $a + b$ in $x = (a + b) - (c * d)$

The code is $t_1 = a + b$, $t_2 = c * d$, $t_3 = t_1 - t_2$, $x = t_3$. Reordering the two independent sub-expressions is legal. Compare the three situations (edited fields in red):

Triples (original)

	op	a_1	a_2
0	+	a	b
1	*	c	d
2	-	(0)	(1)
3	=	x	(2)

Triples after reordering

	op	a_1	a_2
0	*	c	d
1	+	a	b
2	-	(1)	(0)
3	=	x	(2)

Indirect triples (reordered)

order list

slot	points to
35	(1)
36	(0)
37	(2)
38	(3)

triples (unchanged)

0	+	a	b
1	*	c	d
2	-	(0)	(1)
3	=	x	(2)

With plain triples the two triples swap places, so *every* reference to them (here in triple 2) must be rewritten. With indirect triples the triples keep their numbers; only the order list changes, and no triple is edited. In a large program the number of references to repair can be huge, which is why optimising compilers prefer the extra list.

Which one should I use?

Quadruples are the simplest to reason about and to optimise, and are the usual textbook choice. Triples save space but are fragile under reordering. Indirect triples keep the compactness of triples and recover the flexibility of quadruples at the price of one extra list. All three encode exactly the same three-address code.

2.3.4 Static single-assignment (SSA) form and the φ-function

The idea. In **SSA form** every variable name is assigned in exactly one place in the program text. If the source assigns to the same variable several times, the compiler gives each assignment its own subscripted name. For straight-line code this is nothing more than renaming:

```
p = a + b
q = p - c
p = q * d
p = e - p
q = p + q
```

```
p1 = a + b
q1 = p1 - c
p2 = q1 * d
p3 = e - p2
q2 = p3 + q1
```

On the right p_1, p_2, p_3 are three different values that happened to share the name p on the left. Every *use* now names exactly one *definition*: the p_3 in the last line can only come from `p3 = e - p2`.

Why bother? One definition per name makes optimisation easy

```
a  = 1                a1 = 1
b  = a + 2            b1 = a1 + 2
a  = 10               a2 = 10
c  = a * b            c1 = a2 * b1
```

On the left, to fold `c = a * b` an optimiser must first find out *which* of the two assignments to a reaches that line (a data-flow analysis). On the right the question does not exist: a_2 has a single definition, `a2 = 10`; $b_1 = a_1 + 2 = 3$; hence $c_1 = 10 * 3 = 30$. Once a_1 has no uses left, a quick count shows that `a1 = 1` is dead code and can be deleted. SSA turns "which definition reaches here?" into a lookup by name.


The problem: two paths meet. Straight-line code is easy. The difficulty starts where control flow *joins*:

```
if (flag) x = -1; else x = 1;
y = x * a;
```

Renaming the two assignments gives x_1 (in the **then**-branch) and x_2 (in the **else**-branch). But which name should `y = x * a` use? It depends on `flag`, which is known only at run time, so the compiler cannot choose at compile time. What we need is a *new name* that means "x_1 if we came through the **then**-branch, otherwise x_2". That is exactly what the φ-function provides:

$$x_3 = \varphi(x_1, x_2)$$

```
if (flag) x1 = -1; else x2 = 1;
x3 = phi(x1, x2);
y  = x3 * a;
```



φ takes its *first* operand if control came from pred. 1, its *second* if it came from pred. 2


What a φ-function is (and is not)

- It sits at the *start* of a block that has two or more predecessors (a join point).
- $v = \varphi(v_1, \ldots, v_k)$ has one operand per predecessor, *in the same order as the predecessors*. The value of v is the operand that belongs to the edge along which control actually arrived.
- If a block starts with several φ's, they are evaluated *simultaneously* on entry.
- It is **not** an instruction that the machine executes and it does not test anything. It is notation that the compiler uses to keep "one definition per name" true at a join. It is removed again before machine code is generated (see below).

A loop: φ at the loop header. A loop is also a join: the header can be reached from before the loop (the first time) or from the end of the body (every later time). Take

```
i = 0;  s = 0;
while (i < n) { s = s + i;  i = i + 1; }
return s;
```

The variables i and s both have different definitions arriving at the header, so both need a φ there:



Both φ's list the operand from B0 first ("pred. 1") and the operand from B2 second ("pred. 2"). Note that i_3 and s_3 are used by the φ's *before* they are defined in program order; that is fine, because that operand is only chosen when control arrives from B2, i.e. after B2 has run. Trace for $n = 2$:

visit of B1	**arrived from**	i_2	s_2	$i_2 < 2$?	**then B2 computes**
1	B0 (pred. 1)	$i_1 = 0$	$s_1 = 0$	yes	$s_3 = 0 + 0 = 0$, $i_3 = 1$
2	B2 (pred. 2)	$i_3 = 1$	$s_3 = 0$	yes	$s_3 = 0 + 1 = 1$, $i_3 = 2$
3	B2 (pred. 2)	$i_3 = 2$	$s_3 = 1$	no	leave loop: `return s2` $= 1$

The result $1 = 0 + 1$ is the sum of i over $i = 0, 1$, as the source program computes.

Where is a φ needed? Only at a join point, and only for a variable for which *different definitions* arrive along different paths. A variable that has a single reaching definition needs no φ:

```
y = 7;                          y1 = 7;
if (c) x = 1; else x = 2;       if (c) x1 = 1; else x2 = 2;
z = x + y;                      x3 = phi(x1, x2);   z1 = x3 + y1;
```

Here x gets a φ (two definitions meet) but y does not (only y_1 reaches the join, along both paths). Compilers find the exact places with an algorithm based on *dominance frontiers*, which is beyond these notes; the rule of thumb above is enough for exercises.

Leaving SSA. Real processors have no φ instruction. Before code generation each φ is replaced by *copies at the end of the predecessors*: for $x_3 = \varphi(x_1, x_2)$ the first predecessor gets `x3 = x1` and the second gets `x3 = x2`. Often the register allocator gives x_1, x_2, x_3 the same register and the copies disappear.

Common confusions about SSA

- "Single" counts assignments in the *program text*, not executions. In the loop above `i3 = i2 + 1` runs once per iteration, yet it is the only assignment to i_3 in the text.
- φ chooses by *which edge control arrived on*, not by testing a condition or a value.
- The order of the φ operands must match the order of the predecessors. Swapping them silently gives a different program.
- No φ is needed for a variable that is not reassigned before the join.

3 Syntax-Directed Definitions (SDD)

3.1 What is an SDD, and what is it for?

Division of labour. Up to now the course has used a **context-free grammar (CFG)**. A CFG together with a parser answers exactly two questions:

1. *Is this string a legal program?* (**syntax**)
2. *What is its structure?* The answer is the **parse tree**.

That is all the CFG is needed for. Producing the parse tree is the job of **syntax analysis**, and the grammar alone is enough for it.

But a compiler must also know what the program *means*, and a CFG cannot express this. For example, the parse tree of `3 * 5 + 4` shows that $3 * 5$ is grouped first, but nowhere does it contain the number 19. It also contains no machine or three-address instructions. Typical questions that the parse tree cannot answer are:

- What is the **value** of this expression? (calculators, constant folding)
- What is the **type** of this expression, and do the types fit together? (type checking)
- Was this variable **declared** before it is used? (static checks, symbol table)
- In which temporary or variable is its result **stored**, and which **instructions** implement this statement? (code generation)
- To which **label** should control jump if this condition is true? (control flow)

Example: a program that is syntactically perfect but wrong

```
int x;
y = x + 1;
```

With a grammar such as $S \to \textbf{id} = E$; the second line is a legal statement, and the parser happily builds a parse tree for it. Yet the program is wrong, because y was never declared. The grammar cannot say so: to detect the error, the compiler must look y up in a *symbol table*, and that table is information *outside* the tree structure. (Formally, "declared before use" is not a context-free property.) The same applies to `int a; a = "hi";`: the grammar sees only **id** = **string**, not that the types disagree.

The solution: attach information to the tree. A **syntax-directed definition (SDD)** is a CFG *extended* with two things:

> **SDD** = **CFG** + **attributes** (values stored on grammar symbols) + **semantic rules** (how to compute those values from the production used).

The CFG part is unchanged and still defines the syntax. The new parts add meaning. Applying the rules to a parse tree gives an **annotated parse tree**: the same tree with every node carrying its

attribute values. "Syntax-directed" means that the computation is *driven by the syntactic structure*: which rule fires at a node depends on which production was used there.




Figure 6: Where the CFG ends and the SDD begins. The parser needs only the grammar; everything that computes *meaning* from the tree is specified by semantic rules.

Do real compilers build the parse tree?

Usually not. The parse tree is a *conceptual* object: it is the structure that the grammar assigns to the input, and it is what an SDD is defined on (annotated parse tree, dependency graph). A real parser seldom stores it:

- A recursive-descent parser follows the derivation through its procedure calls, and an LR parser follows it through its stack and reductions. The tree is traversed implicitly, not built.
- At each reduction (or procedure return) the parser executes the semantic actions, which is exactly the SDT idea. Typically these actions build a **syntax tree (AST)** node directly, e.g. $E.node = \textbf{new}\ Node('+', E_1.node, T.node)$ (Section 3.9).

A parse tree has a node for every grammar symbol, including chain steps such as $E \to T \to F \to \textbf{digit}$ and punctuation such as parentheses. A syntax tree keeps only the operators and operands that matter, so it is much smaller and is the usual input of the later phases (type checking, intermediate-code generation).

So the two statements fit together. *Logically*, the CFG gives the structure and the SDD gives the meaning. *In practice*, the parser's actions (an SDT) build the syntax tree directly and the full parse tree is never created. Later phases then evaluate attributes (for example types) over the syntax tree, which is attribute evaluation again, only on a different tree.

What is it used for? To answer the common question directly: yes. A CFG with its parse tree is enough for *syntax*; an SDD is the tool used to specify *semantic analysis* and *intermediate-code generation*, and related jobs:

Task	Attribute computed	Compiler phase
Evaluate an expression	*val*	calculators, constant folding
Check types, declarations	*type*, symbol-table entry	semantic analysis
Build a syntax tree or DAG	*node* (pointer)	front end, intermediate representation
Generate three-address code	*addr*, *code*	intermediate-code generation
Generate jumps for conditions	*true*, *false*, *next* (labels)	intermediate-code generation

Two remarks. First, the boundary between "semantic analysis" and "code generation" is blurred in practice, because one set of semantic rules often does both at once, for instance a rule that checks the types and emits a conversion in the same step. Second, an SDD is a general method, also used outside compilers (for example to evaluate expressions or to convert one data format to another).

	CFG	**SDD**	**SDT**
What it is	productions only	CFG + attributes + semantic rules	CFG + program fragments (*actions*) in the bodies
Question answered	"Is it legal? What is the structure?"	"What does it mean? What should be computed?"	"*At what moment of the parse* is each computation done?"
Output	parse tree	annotated parse tree	the translation itself (values, tree, code)
Order of work	–	only constrained by the dependencies (a partial order; many orders are legal)	one fixed order: left to right, each action at its position in the body
Used in	syntax analysis	semantic analysis, intermediate-code generation (the *specification*)	the *implementation* inside the parser

Table 5: CFG, SDD and SDT. An SDD says *what* to compute and which orders are legal; an SDT (Section 4) fixes *one* order and the moment in the parse at which each computation runs.

Do we need both SDD and SDT?

No: they are *two levels of description of the same translation*, not two separate tools used side by side.

- The **SDD** is the *specification*. It states what every attribute equals, e.g. $E.val = E_1.val + T.val$, and fixes the *dependencies*: an attribute can be computed only after the attributes it uses. This allows many evaluation orders, and the SDD does not choose among them.
- The **SDT** is the *implementation*. The same computation is written as an action inside the production, e.g. $E \to E_1 + T \ \{ \ E.val = E_1.val + T.val \ \}$, and therefore runs at one fixed point during parsing: the SDT *chooses one* of the orders that the SDD allows.

Normally we first think in terms of an SDD (what should be computed?) and then turn it into an SDT (where do the actions go?). The SDD alone defines the meaning but is not yet a procedure; one can also write an SDT directly, but then the correct ordering is our own responsibility.

So does an SDD say nothing about when? It does say something, but only partially. The class of an SDD tells us which evaluation strategy is guaranteed to work: post-order for S-attributed, one left-to-right depth-first traversal for L-attributed, and a topological order of the dependency graph for any other non-circular SDD. These are the *legal* orders. What the SDD cannot express is (i) the order of computations that do not depend on each other, which matters for side effects such as *print*, *gen* and *addType*, and (ii) *when during compilation* the work is done, for instance during parsing, without storing the tree. An SDT fixes both.

3.2 Attributes

An **attribute** is any value that we attach to a grammar symbol. It helps to picture the parse tree as a tree of *records*: every node has the grammar symbol as its name plus a few fields (the attributes).

If X is a symbol and a is an attribute, we write $X.a$ for the value of a at a particular node labelled X. Attributes can be of any kind: numbers, strings, types, pointers to symbol-table entries, or even whole code sequences.

A note on the symbol names. The letters E, T, F, S, B used in this chapter have *no special meaning in CFGs in general.* They are just names that the author of a particular grammar chose, by convention: E for *expression*, T for *term*, F for *factor*, S for *statement* and B for *boolean expression.* The expression grammar we use for examples is

$$E \to E + T \mid T, \qquad T \to T * F \mid F, \qquad F \to (\,E\,) \mid \textbf{digit},$$

and a different grammar could use completely different names. Which attributes a symbol carries is likewise decided by the grammar designer, and an attribute exists only on the symbols for which it is declared ($E.val$ exists, but $B.val$ does not unless we define it).

Examples of attributes. Typical attributes, with the symbols they are usually given in the grammars of this chapter, are:

- $E.val$: the numeric value of an expression (E, T, F in the grammar above).
- $E.type$: the type of an expression (`int`, `float`, ...).
- $E.addr$: the name or temporary that holds the result of the expression.
- $E.node$: a pointer to the syntax-tree node built for the expression.
- $S.code$: the three-address code generated for a statement (or expression).
- $B.true$, $B.false$: the labels to jump to when a boolean expression is true or false.
- **id**.*lexeme*: the actual characters of an identifier, supplied by the lexer.
- **digit**.*lexval*: the numeric value of a number token, supplied by the lexer.

Different *occurrences* of the same nonterminal in a production are distinguished by subscripts, e.g., in $E \to E_1 + T$ the E on the left is the *head* and E_1 is the E in the body; both have a *val*.

3.3 Semantic rules: a first tiny example

A **semantic rule** is attached to a production and says how to compute one attribute from other attributes *of the symbols in that same production.* For the production $E \to E_1 + T$ the rule

$$E.val = E_1.val + T.val$$

says: "the value of the whole expression is the value of the left sub-expression plus the value of the term." Consider the grammar $E \to E + T \mid T,\ T \to \textbf{digit}$, together with the rules

Production	Semantic rule
$E \to E_1 + T$	$E.val = E_1.val + T.val$
$E \to T$	$E.val = T.val$
$T \to \textbf{digit}$	$T.val = \textbf{digit}.lexval$

Evaluate it on the input `2 + 3`. The parse tree is $E \Rightarrow E_1 + T$ with $E_1 \Rightarrow T \Rightarrow \textbf{digit}(2)$ and $T \Rightarrow \textbf{digit}(3)$. Working *from the leaves upward*:

1. The lexer supplies **digit**.*lexval* = 2 and 3.
2. $T \to \textbf{digit}$ gives $T.val = 2$ (left) and $T.val = 3$ (right).
3. $E \to T$ gives $E_1.val = 2$.
4. $E \to E_1 + T$ gives $E.val = 2 + 3 = 5$.

That is all an SDD does: it decorates the parse tree with attribute values by repeatedly applying the rules.

3.4 Formal definition

Syntax-Directed Definition (SDD)

A **syntax-directed definition** is a context-free grammar together with **attributes** attached to grammar symbols and **semantic rules** attached to productions. For a production $A \to \alpha$ every rule has the form

$$b = f(c_1, c_2, \ldots, c_k)$$

where f is a function and either

(1) b is a **synthesized** attribute of A and $c_1, \ldots, c_k$ are attributes of the symbols in α (the children), or other attributes of A itself (allowed only if this creates no cycle); or

(2) b is an **inherited** attribute of a symbol B in α and $c_1, \ldots, c_k$ are attributes of A (the parent) or of symbols in α (the siblings), or of B itself.

3.5 Synthesized and inherited attributes

Analogy

Think of the parse tree as a company. A **synthesized** attribute is a *report sent up* to the manager: the manager's value is built from the reports of the subordinates (e.g., the value of $2 + 3$ is built from the values of 2 and 3). An **inherited** attribute is an *instruction or information passed down or across*, from a parent or from siblings (e.g., the declared type `float` is passed down to every identifier in `float a, b, c`).

- A **synthesized attribute** at a parse-tree node N is computed from attributes of N's *children*. (Occasionally it also uses another attribute of N itself, e.g. $A.t = A.s + 1$; this is allowed as long as there is no cycle.) Information flows *bottom-up*. Terminals have synthesized attributes only (supplied by the lexer, e.g., **digit**.*lexval*).
- An **inherited attribute** at N is computed from attributes of N's *parent and siblings*. Information flows *top-down / sideways*. Useful when the structure of the parse tree does not match the abstract syntax, e.g., passing a type to a list of identifiers, or passing the label to jump to.

Example: synthesized attributes only (desk calculator)

Production	Semantic rules
$L \to E$ **n**	$L.val = E.val$
$E \to E_1 + T$	$E.val = E_1.val + T.val$
$E \to T$	$E.val = T.val$
$T \to T_1 * F$	$T.val = T_1.val \times F.val$
$T \to F$	$T.val = F.val$
$F \to (\, E \,)$	$F.val = E.val$
$F \to$ **digit**	$F.val =$ **digit**.*lexval*




Figure 7: Annotated parse tree for `3*5+4 n`. Each node shows the value of its synthesized attribute *val*.

How to read the figure (evaluation recipe).

1. The lexer supplies the *lexval* of every **digit** leaf (3, 5, 4).
2. Each $F \to$ **digit** copies it into $F.val$; each $T \to F$ copies it up again.
3. $T \to T_1 * F$ is applied once both its children are known: $3 \times 5 = 15$.
4. $E \to E_1 + T$ then adds $15 + 4 = 19$, and $L \to E\,\mathbf{n}$ passes 19 to the root.

Every node is computed *after* its children, i.e., in **post-order**. This is natural for synthesized attributes, and it is exactly the order in which an LR parser performs reductions.

Which evaluation order is needed?

Kind of SDD	Evaluation order	Dependency graph needed?
S-attributed (synthesized only)	post-order (children before parent), i.e. LR reductions	No: every edge points from child to parent, so post-order is already a topological order.
L-attributed	one depth-first, left-to-right traversal	No: inherited attributes depend only on the parent and left siblings.
General (arbitrary mix)	any topological order of the dependency graph	Yes: build the graph, topologically sort it, and reject it if it has a cycle.

So the dependency graph with topological sort is the *general* method; the two special classes are exactly those for which a fixed traversal makes it unnecessary.

3.6 Annotated parse trees and dependency graphs

An **annotated parse tree** shows the attribute values at every node. To evaluate attributes we build a **dependency graph**: one node per attribute instance, and an edge $x \to y$ whenever y is

computed from x. A valid evaluation order is any *topological order* of this graph; if the graph has a cycle, no order exists.


Which way do the arrows point?

Rule: the arrow goes from the attribute that is used to the attribute that is defined. For a semantic rule $b = f(c_1, \ldots, c_k)$ we draw an edge $c_i \to b$ for every c_i: the tail is on the *right-hand side* of the rule (the input), the head is on the *left-hand side* (the result). Reading an arrow $x \to y$ as "y needs x" (so x must be computed first) is what makes a topological order a valid evaluation order.

Example. Take the production $E \to L\ D$ with the rule $D.val = L.val$. The attribute defined is $D.val$ and the attribute used is $L.val$, so the edge is

$$L.val \longrightarrow D.val.$$


The arrow goes from the left sibling L to the right sibling D, *sideways* in the tree. Since $D.val$ is defined by a rule of the production of its *parent* E, it is an inherited attribute of D.



The three cases. The direction of an arrow in the *graph* is always "used → defined". What this means in the *tree* depends on where the two attributes are:

Rule (in production $A \to X\ Y$)	**Edge**	**Direction in the tree**
$A.s = X.s$ (synthesized)	$X.s \to A.s$	child → parent (*up*)
$X.i = A.i$ (inherited from parent)	$A.i \to X.i$	parent → child (*down*)
$Y.i = X.s$ (inherited from sibling)	$X.s \to Y.i$	left sibling → right sibling (*sideways*)

A common mistake is to draw the arrow in the direction of the tree edge or to follow the "flow of the parse"; always look at the rule instead: the arrow points *into* the attribute on the left of the "=".



Dashed arrow $x \to y$: y is computed from x. One valid order: both *lexval*s, then the two $T.val$, then $E_1.val$, then $E.val$.

Figure 8: Dependency graph for `2 + 3` under the SDD of this section (every attribute is synthesized, so every arrow points *up*).

A circular definition

For $A \to B$ with the rules $A.s = B.i + 1$ and $B.i = A.s \times 2$, the value of $A.s$ needs $B.i$, which needs $A.s$. The dependency graph has a *cycle*, so no evaluation order exists. A good SDD must be *non-circular*; the classes S-attributed and L-attributed below guarantee this automatically.

Side effects

A semantic rule may also do something besides computing a value, e.g., $addType(entry, t)$ writes into the symbol table, *print* writes to the output, and *gen* emits an instruction. Such rules are called **side effects**; they are fine as long as the order in which they run does not change the result (or the order is controlled, which is the job of an SDT).

Example: inherited attributes (declaration list)

Production	Semantic rules
$D \to T\ L$	$L.inh = T.type$
$T \to$ **int**	$T.type = integer$
$T \to$ **float**	$T.type = float$
$L \to L_1$, **id**	$L_1.inh = L.inh$; $addType(\textbf{id}.entry,\ L.inh)$
$L \to$ **id**	$addType(\textbf{id}.entry,\ L.inh)$

For the input `float` $\texttt{id}_1$`,` $\texttt{id}_2$ the dashed arrows in Fig. 9 are the dependency-graph edges. The type is passed *down and across* from T to L, then down through the list to each identifier.




Figure 9: Parse tree for `float id1, id2` with dependency edges (dashed) for the inherited attribute *inh*.

One valid evaluation order (any topological order of the dependency graph works):

(1) $T.type = float$ ($T \to$ **float**; depends on nothing)
(2) $L.inh = T.type$ ($D \to T\ L$)
(3) $L_1.inh = L.inh$ ($L \to L_1\ ,\ \mathbf{id}_2$)
(4) $addType(\mathbf{id}_2.entry,\ L.inh)$ (the identifier after the comma)
(5) $addType(\mathbf{id}_1.entry,\ L_1.inh)$ ($L_1 \to \mathbf{id}_1$)

Steps (4) and (5) do not depend on each other, so they may be swapped; both identifiers end up with type *float* either way.

3.7 Classes of SDDs that are easy to implement

S-attributed and L-attributed definitions

- An SDD is **S-attributed** if *every attribute is synthesized*. It can be evaluated in any bottom-up order, e.g., during LR parsing, at the time of reduction.
- An SDD is **L-attributed** if each attribute is either synthesized, or inherited such that, for a production $A \to X_1 X_2 \cdots X_n$, the inherited attribute of X_i depends only on:
  (a) inherited attributes of A, and
  (b) attributes (inherited or synthesized) of $X_1, \ldots, X_{i-1}$ (the symbols to its *left*), and
  (c) attributes of X_i itself, provided there is no cycle.

  Evaluation is possible in a single left-to-right depth-first traversal (e.g., during top-down/LL parsing).

Every S-attributed SDD is also L-attributed.

Not L-attributed

For $A \to B\,C$, the rule $C.i = B.s$ is fine (the inherited attribute of C uses its *left* sibling B). But the rule $B.i = f(C.x)$ makes the inherited attribute of B depend on its *right* sibling C, so the SDD is *not* L-attributed.




Figure 10: How the classes of SDDs nest, with an example of each.

3.8 More examples: L-attributed and general (non-circular) SDDs

Most examples so far are S-attributed. Here are two examples with inherited attributes: one that is L-attributed, and one that is neither S- nor L-attributed, so that a dependency graph and a topological order are really needed.

How to classify an SDD

1. Is every attribute synthesized? ⇒ **S-attributed**: evaluate in post-order (LR reductions).
2. Otherwise, look at *every inherited attribute* $X_i.a$ in a production $A \to X_1 \cdots X_n$. Does its rule use only inherited attributes of A, attributes of $X_1, \ldots, X_{i-1}$ (left siblings), or other attributes of X_i itself? If this holds for all of them ⇒ **L-attributed**: one depth-first left-to-right traversal suffices.
3. If some inherited attribute uses a *right* sibling (or a synthesized attribute that would have to come from the right), the SDD is **not L-attributed**. Draw the dependency graph. If it has no cycle, the SDD is **non-circular** and any topological order evaluates it; if it has a cycle, the SDD is erroneous.

Example 1 (L-attributed, not S-attributed): value of a binary fraction

We evaluate a binary fraction such as `.101` $= \frac{1}{2} + \frac{1}{8} = 0.625$. The weight of a bit depends on its *position counted from the point*, which is passed *down and to the right* as an inherited attribute *pos*.

Production	Semantic rules
$S \to {}'.'\ L$	$L.pos = 1; \quad S.val = L.val$
$L \to B\ L_1$	$B.pos = L.pos; \quad L_1.pos = L.pos + 1; \quad L.val = B.val + L_1.val$
$L \to \varepsilon$	$L.val = 0$
$B \to 0$	$B.val = 0$
$B \to 1$	$B.val = 2^{-B.pos}$

Why L-attributed. The inherited attributes are $L.pos$, $B.pos$ and $L_1.pos$. In $L \to B\,L_1$, $B.pos$ and $L_1.pos$ use only $L.pos$, the inherited attribute of the head, and in S the rule for $L.pos$ uses nothing. No inherited attribute depends on a symbol to its right. It is not S-attributed because *pos* is inherited.

Evaluation for `.101`. A single depth-first left-to-right traversal works. Writing L_a, L_b, L_c, L_d

for the four occurrences of L from left to right (so $L_a \to B_1 L_b$, $L_b \to B_2 L_c$, $L_c \to B_3 L_d$, $L_d \to \varepsilon$):

Step	Rule used	Value
1	$L_a.pos = 1 \quad (S \to {'.'}L)$	1
2	$B_1.pos = L_a.pos,\ \ L_b.pos = L_a.pos + 1$	1, 2
3	$B_1 \to 1$: $B_1.val = 2^{-1}$	0.5
4	$B_2.pos = 2,\ \ L_c.pos = 3;\ \ B_2 \to 0$: $B_2.val = 0$	0
5	$B_3.pos = 3,\ \ L_d.pos = 4;\ \ B_3 \to 1$: $B_3.val = 2^{-3}$	0.125
6	$L_d \to \varepsilon$: $L_d.val = 0$	0
7	going back up: $L_c.val = 0.125 + 0,\ \ L_b.val = 0 + 0.125,\ \ L_a.val = 0.5 + 0.125$	0.625
8	$S.val = L_a.val$	0.625

As an SDT. Following the conversion rules of Section 4.8, each inherited attribute is computed by an action placed immediately before the symbol that uses it; this gives actions at the left end of a body and in the middle:

$$S \to {'.'}\ \{\ L.pos = 1\ \}\ L\ \{\ S.val = L.val\ \}$$
$$L \to \{\ B.pos = L.pos\ \}\ B\ \{\ L_1.pos = L.pos + 1\ \}\ L_1\ \{\ L.val = B.val + L_1.val\ \}$$
$$\mid\ \varepsilon\ \{\ L.val = 0\ \}$$
$$B \to 0\ \{\ B.val = 0\ \}\ \mid\ 1\ \{\ B.val = 2^{-B.pos}\ \}$$

Example 2 (neither S- nor L-attributed, but non-circular): value of a binary integer

Now evaluate an ordinary binary integer such as `101` $= 5$. The weight of a bit is 2^{pos} where *pos* is the number of bits *to its right*. This depends on the *length of the rest of the string*, which is known only after the right part has been examined.

Production	Semantic rules
$L \to B\ L_1$	$B.pos = L_1.len;\quad L.len = L_1.len + 1;\quad L.val = B.val + L_1.val$
$L \to B$	$B.pos = 0;\quad L.len = 1;\quad L.val = B.val$
$B \to 0$	$B.val = 0$
$B \to 1$	$B.val = 2^{B.pos}$

Classification. *pos* is inherited, so the SDD is not S-attributed. In $L \to B\,L_1$ the inherited attribute $B.pos$ is computed from $L_1.len$, an attribute of the *right* sibling, so it is not L-attributed either: a left-to-right traversal reaches B before it knows $L_1.len$. It is nevertheless *non-circular*: *len* depends only on *len* of the part below it, *pos* depends only on *len*, and *val* depends on *pos* and on *val* further down. So we use a dependency graph.

Dependency graph for `101`. The parse tree is $L_a \to B_1 L_b$, $L_b \to B_2 L_c$, $L_c \to B_3$, with $B_1 \to 1$, $B_2 \to 0$, $B_3 \to 1$. Each box in Figure 11 is one attribute instance with its final value; an arrow $x \to y$ means that y is computed from x. The small red numbers give one valid topological order.




Figure 11: Dependency graph for `101` (value 5). *len* flows upward, then crosses over into the inherited *pos* of the left sibling B, then *val* flows upward. The red numbers are one valid topological order.

Topological order (solution).
(1) $L_c.len = 1$ and $B_3.pos = 0$ (rule $L \to B$; no dependence on anything).
(2) $B_3.val = 2^0 = 1$ $(B_3 \to 1)$, then $L_c.val = 1$.
(3) $L_b.len = L_c.len + 1 = 2$ and $B_2.pos = L_c.len = 1$.
(4) $B_2.val = 0$ $(B_2 \to 0)$, then $L_b.val = 0 + 1 = 1$.
(5) $L_a.len = L_b.len + 1 = 3$ and $B_1.pos = L_b.len = 2$.
(6) $B_1.val = 2^2 = 4$ $(B_1 \to 1)$, then $L_a.val = 4 + 1 = 5$.
Other orders are also valid, e.g. all three *len* values first. In practice a compiler evaluates such an SDD in *several passes over the parse tree*: a bottom-up pass for *len*, a top-down pass for *pos*, and a bottom-up pass for *val*.
Remark. The difficulty comes from the right-recursive grammar. With the left-recursive grammar $L \to L_1 B \mid B$ and $L.val = 2 \times L_1.val + B.val$ the same value is computed by an S-attributed SDD, with no *pos* and no *len*. Choosing the grammar well can remove the need for a dependency graph.

3.9 SDD for constructing syntax trees

The goal. The parser recognises an expression such as `a - 4 + c`. We want the compiler to end up with the *syntax tree* of Section 2.1 in memory, with operators as interior nodes and operands as leaves. An SDD does this by attaching one synthesized attribute, *node*, to every grammar symbol that stands for an expression.

The tools. The attribute $E.node$ is a *pointer* to the root of the (sub)tree that E stands for. Two constructor functions create nodes and return a pointer to the new node:

- **new** *Leaf*(**id**, **id**.*entry*) or **new** *Leaf*(**num**, **num**.*val*) creates a *leaf*. It has two arguments:
  - the **token name** (**id** or **num**), which becomes the *label* of the leaf and says what kind of operand it is;
  - the **token attribute**: for an identifier, **id**.*entry* is a *pointer (index) to the symbol-table entry* of that identifier, which the lexer filled in when it recognised the name; for a number, **num**.*val* is the *value* of the constant itself.
- **new** *Node*(*op*, *left*, *right*) creates an *interior node*. It has three arguments:

- *op*, the *label* of the node, the operator (for example $'+'$);
- *left* and *right*, *pointers to the two child nodes* (the roots of the left and the right operand). They are the children of the new node, not neighbours: the new node stores these two pointers.

The SDD. The grammar is $E \to E + T \mid E - T \mid T$, $T \to (E) \mid \textbf{id} \mid \textbf{num}$. The last column says whether the rule *creates* a node or only *passes a pointer upward*.

Production	Semantic rule	New node?
$E \to E_1 + T$	$E.node =$ **new** $Node('+', E_1.node, T.node)$	yes (interior)
$E \to E_1 - T$	$E.node =$ **new** $Node('-', E_1.node, T.node)$	yes (interior)
$E \to T$	$E.node = T.node$	no (copy)
$T \to (E)$	$T.node = E.node$	no (copy)
$T \to$ **id**	$T.node =$ **new** $Leaf($**id**, **id**$.entry)$	yes (leaf)
$T \to$ **num**	$T.node =$ **new** $Leaf($**num**, **num**$.val)$	yes (leaf)

This is an S-attributed SDD: every rule computes the attribute of the head from the attributes of its body symbols. (If the grammar is made LL by eliminating left recursion, the same tree is built with an inherited attribute; see Section 4.8.)

Recipe: building the tree by hand from an SDD

Because this SDD is S-attributed (every attribute is synthesized), its rules can be evaluated by a **post-order traversal** of the parse tree, as in Section 3.1: visit the children from left to right, and only then the node itself.

1. Draw the **parse tree** of the input.
2. Traverse it in **post-order**. When a node is visited, execute the semantic rule of its production.
3. A **leaf rule** ($T \to$ **id**, $T \to$ **num**) creates a leaf node. Give each newly created node the next name $p_1, p_2, p_3, \ldots$ in the order of creation.
4. A **copy rule** ($E \to T$, $T \to (E)$) creates nothing: the pointer of the child is simply written on the parent.
5. An **operator rule** ($E \to E_1 \pm T$) creates *one* interior node. Its left child is the pointer of E_1, its right child is the pointer of T.
6. The *node* of the root of the parse tree points to the finished syntax tree.

Post-order guarantees that the children are visited before their parent, which is exactly what an operator rule needs: it uses the pointers of its operands. An LR parser reduces in the same post-order, so the same rules can also be run during parsing.

Worked example 1: the syntax tree of `a - 4 + c`

Step 1: the annotated parse tree. The input is the token string **id** − **num** + **id**. Figure 12 shows its parse tree. Every grammar symbol carries the value of its *node* attribute. Green nodes are those whose rule *creates* a new node; the others only copy a pointer.




Figure 12: Annotated parse tree of `a - 4 + c` for the SDD above. Five nodes are created $(p_1, \ldots, p_5)$; the node $E \to T$ at the lower left just copies p_1.

Step 2: the order in which the rules run. A post-order traversal of the parse tree visits the nodes in the order below and executes the rule of each visited node (an LR parser reduces in the same order, so each rule runs at its reduction). Read the table from top to bottom and watch the pointers $p_1, \ldots, p_5$ appear.

Step	Node visited (production)	Semantic rule executed	Result
1	$T \to$ **id** (a)	$T.node =$ **new** *Leaf*(**id**, $entry_a$)	p_1
2	$E \to T$	$E.node = T.node$ (copy)	p_1
3	$T \to$ **num** (4)	$T.node =$ **new** *Leaf*(**num**, 4)	p_2
4	$E \to E_1 - T$	$E.node =$ **new** *Node*('−', p_1, p_2)	p_3
5	$T \to$ **id** (c)	$T.node =$ **new** *Leaf*(**id**, $entry_c$)	p_4
6	$E \to E_1 + T$	$E.node =$ **new** *Node*('+', p_3, p_4)	p_5

Step 3: the tree grows during the traversal. Figure 13 shows what exists in memory after steps 3, 4, 5 and 6. Notice that for a while there are *several separate pieces* (a forest); the last rule joins them into one tree.





Figure 13: The syntax tree of `a - 4 + c` is built during the post-order traversal. Red labels are the pointer names of Step 2.

Step 4: the result. The attribute $E.node$ of the root is p_5, the root of the syntax tree. In memory the tree is just five small records that point to each other.



	label	left	right
p_1	**id**	→ entry of a	
p_2	**num**	4	
p_3	−	p_1	p_2
p_4	**id**	→ entry of c	
p_5	+	p_3	p_4

Figure 14: The finished syntax tree (left) and the records that represent it (right). An interior record stores the *pointers* of its two children.

Three things to check.

1. The parse tree has 11 grammar nodes, but only 5 nodes are created: 3 operands + 2 operators. In general an expression with n operands and $n-1$ binary operators gives $2n-1$ nodes, which is a quick self-check.
2. $Node('-', p_1, p_2)$ was called *before* $Node('+', p_3, p_4)$, because the pointer p_3 is an input of the second call. This is why $a-4$ is grouped first: the SDD together with the left-recursive grammar gives left associativity.
3. The first argument of *Node* is always the pointer of the *left* operand E_1, the second is that of T. Swapping them would build the mirror image of the tree.

Worked example 2: parentheses leave no trace in the tree, `a - (4 + c)`

The same SDD is applied to **id** − (**num** + **id**). The new step is the rule $T \to (E)$: it is a copy rule, so the parentheses do not create any node.

Step	Node visited (production)	Semantic rule executed	Result
1	$T \to$ **id** (a)	**new** *Leaf*(**id**, $entry_a$)	p_1
2	$E \to T$	copy	p_1
3	$T \to$ **num** (4)	**new** *Leaf*(**num**, 4)	p_2
4	$E \to T$ (inner E)	copy	p_2
5	$T \to$ **id** (c)	**new** *Leaf*(**id**, $entry_c$)	p_3
6	$E \to E_1 + T$	**new** $Node('+', p_2, p_3)$	p_4
7	$T \to (E)$	copy: $T.node = E.node$	p_4
8	$E \to E_1 - T$	**new** $Node('-', p_1, p_4)$	p_5

Compare the two trees in Figure 15. The input symbols are the same; only the *grouping* differs, and the grouping is visible in the shape of the tree. This is why later phases never need to look at parentheses.



(a) `a - 4 + c`: $(a-4)+c$ (b) `a - (4 + c)`: $a-(4+c)$

Figure 15: Parentheses change the shape of the syntax tree but never appear in it.

Common mistakes when building the tree

- **Creating a node for a copy rule.** $E \to T$ and $T \to (E)$ only pass a pointer upward. If your tree contains a node labelled E or T, you have drawn the parse tree, not the syntax tree.
- **Mixing up the children.** In $E \to E_1 - T$ the left child is $E_1.node$ and the right child is $T.node$; for $a - 4$ the order matters.
- **Forgetting what post-order implies.** The first node created is the leftmost leaf, not the root; the root is visited, and its node created, last.

3.10 SDD for constructing DAGs directly

The problem with the two-step method. In Section 2.2.1 we first built the complete syntax tree and then walked over it in post-order to obtain the DAG. That works, but it builds a structure (the tree) that is thrown away immediately. An SDD lets us skip the tree: the parser creates DAG nodes *while it parses*, and the tree never exists in memory.

The key observation. The SDD of the previous subsection already has the right shape. Its rules for $E \to E_1 + T$ and $T \to T_1 * F$ create a node *after* the nodes of the children are known, and a bottom-up parser performs reductions in exactly that (post-)order, which is also the order used by the value-number method. All we change is *what the constructor functions do*:

- In the tree SDD, **new** $Node(op, l, r)$ *always* allocates a fresh node.
- In the DAG SDD, $Node(op, l, r)$ first *searches* for an existing record with the same (op, l, r) and allocates a new one only if there is none. *Leaf* behaves in the same way.

Both functions return a **value number**, so the attribute $E.node$ is now simply *an integer: the index of the DAG node* (instead of a pointer to a tree node). The attribute rules themselves are unchanged.

The SDD. To have a multiplication operator we use the usual three-level expression grammar (E expression, T term, F factor), and a single synthesized attribute *node*:

Production	Semantic rule
$E \to E_1 + T$	$E.node = Node('+',\ E_1.node,\ T.node)$
$E \to E_1 - T$	$E.node = Node('-',\ E_1.node,\ T.node)$
$E \to T$	$E.node = T.node$
$T \to T_1 * F$	$T.node = Node('*',\ T_1.node,\ F.node)$
$T \to F$	$T.node = F.node$
$F \to (\ E\ )$	$F.node = E.node$
$F \to$ **id**	$F.node = Leaf(\textbf{id},\ \textbf{id}.entry)$
$F \to$ **num**	$F.node = Leaf(\textbf{num},\ \textbf{num}.val)$

The rules that only *copy* a value ($E \to T$, $T \to F$, $F \to (E)$) create nothing: parentheses affect only the *shape* of the DAG, they do not produce a node of their own. Only the rules containing *Node* or *Leaf* touch the array.

The two constructor functions. The array of records and a hash table keyed on the *signature* of a record are *global data*, shared by all semantic rules for the whole input:

```
record table[];                  // table[v] = record of the node with value number v
hash   index;                    // signature -> value number

int Leaf(kind, x) {              // kind is id or num; x is the entry or the value
    sig = (kind, x);
    if (index has sig) return index[sig];     // already exists: share it
    v = append(table, sig);                   // new record at the end
    index[sig] = v;
    return v;
}

int Node(op, l, r) {             // l and r are value numbers of the children
    sig = (op, l, r);
    if (index has sig) return index[sig];     // common sub-expression found
    v = append(table, sig);
    index[sig] = v;
    return v;
}
```

Compare with the `findOrCreate` routines of Section 2.2.1: they are the same functions. The only new idea is *who calls them*: the semantic rules of the grammar, not a tree-walking procedure.

How does the SDD say "tree" or "DAG"?

The *rules* cannot tell the difference: the DAG SDD above and the syntax-tree SDD of the previous subsection have the same productions, the same attribute *node*, and the same dependency graph. Both are S-attributed. What differs is the **meaning of the constructor functions** that the rules call, and that is part of the definition of the SDD, in the same way that the meaning of *gen* or *addType* is:

- **new** $Node(op, l, r)$ *always allocates* a fresh node. Equal sub-expressions get different nodes, so the result is a **syntax tree**.
- $Node(op, l, r)$ *looks for a record with the same* (op, l, r) *first* and allocates only if none exists. Equal sub-expressions get the same node, so the result is a **DAG**.

So whoever writes the SDD must state which of the two is meant. In these notes we use the keyword **new** for "always create" and plain *Node*, *Leaf* for "find or create". Nothing else changes: every later phase simply receives the attribute *node* and does not care whether some nodes are shared (except that shared nodes need to be translated only once).

Why this is a legitimate SDD

Node and *Leaf* have a *side effect* (they change the global table), which Section 3.1 allowed under one condition: the order of the calls must not change the result. Here it is fixed by the dependencies: a parent's *Node* call needs the value numbers of its children, so those calls are made first. The SDD is S-attributed, so it can be evaluated during LR parsing, with each rule executed at the reduction by which its production is recognised.

Example: input $(a + b) * (a + b)$

The table lists the reductions in the order the parser performs them, but only those that call *Leaf* or *Node*. The omitted reductions ($T \to F$, $E \to T$, $F \to (E)$) just copy the value number upward.

Step	Reduction	Call	Result	Value no.
1	$F \to \mathbf{id}$ (first a)	$\mathit{Leaf}(\mathbf{id}, a)$	new record	1
2	$F \to \mathbf{id}$ (first b)	$\mathit{Leaf}(\mathbf{id}, b)$	new record	2
3	$E \to E_1 + T$	$\mathit{Node}(+, 1, 2)$	new record	3
4	$F \to \mathbf{id}$ (second a)	$\mathit{Leaf}(\mathbf{id}, a)$	**found**	1
5	$F \to \mathbf{id}$ (second b)	$\mathit{Leaf}(\mathbf{id}, b)$	**found**	2
6	$E \to E_1 + T$	$\mathit{Node}(+, 1, 2)$	**found: shared**	3
7	$T \to T_1 * F$	$\mathit{Node}(*, 3, 3)$	new record	4

The attribute of the root E is $E.node = 4$: the root of a DAG with four records, $1 : a$, $2 : b$, $3 : (+, 1, 2)$, $4 : (*, 3, 3)$. At step 6 the second copy of $a + b$ is recognised as the first and no new node is made; this is the sharing we wanted. The tree version would have created seven nodes.

For the larger expression $a + a * (b - c) + (b - c) * d$ the sequence of *Leaf* and *Node* calls is exactly the sequence of requests in Table 1. This is no accident: the value-number method visits the tree in post-order, and an LR parser reduces in post-order too. Both methods therefore build the *same DAG with the same value numbers*, and the final $E.node = 9$ identifies its root.

Tree-first versus direct construction.

	Tree first, then DAG (Section 2.2.1)	**Directly with an SDD**
Needs a syntax tree in memory	yes	no
Who calls find-or-create	a tree-walking procedure	the semantic rules, at reductions
Order of calls	post-order of the tree	order of the parser's reductions (the same)
Resulting DAG	identical	identical

Two details.

- **Commutative operators.** If *Node* stores the children of $+$ and $*$ in a canonical order (smaller value number first), then $a + b$ and $b + a$ are shared as well; without this, they are treated as different expressions (Section 2.2.1).
- **Generating code at the same time.** Whenever *Node creates* a record, it can also emit one three-address instruction for it, with a fresh temporary; when it *finds* an existing record, it emits nothing. This is method 2 in the comparison of Section 2.3.1 (the paragraph "Three ways to obtain three-address code"), and it produces code in which $b - c$ is computed only once.

4 Syntax-Directed Translation Schemes (SDT)

4.1 From specification to implementation

An SDD tells us *what* every attribute must equal, but it does not say *when* each rule should run. A real compiler, however, runs the rules *while it is parsing*, in one definite order, and often without

ever building the whole parse tree. A **syntax-directed translation scheme (SDT)** solves this: it takes the program fragments of the rules and writes them *inside the production body, at the exact position where they should run.*

The same rule written both ways:

SDD (specification)	**SDT** (implementation)
$E \to E_1 + T$ rule: $E.val = E_1.val + T.val$	$E \to E_1 + T \ \{ E.val = E_1.val + T.val \}$

	SDD	**SDT**
Nature	High-level specification: rules attached to productions	Concrete implementation: actions embedded in productions
Order of evaluation	Only constrained by the dependencies: any topological order is legal (post-order, left-to-right DFS, ... depending on the class)	One explicit order: actions run in the left-to-right order of the production body, at the moment the parser reaches them
Rules/actions	Written next to the production	Written in braces $\{\ldots\}$ inside the body
Used for	Designing and reasoning about the translation	Building the actual translator

4.2 Definition and the meaning of an action's position

Syntax-Directed Translation Scheme

A **syntax-directed translation scheme** (SDT) is a context-free grammar with **program fragments** (*semantic actions*) embedded within the production bodies, written in braces. The position of an action defines *when* it is executed during parsing.

$$B \to X \ \{a\} \ Y$$

Here action a is executed after X has been recognised (and before Y).

How an SDT is executed. Imagine the parse tree in which every action appears as an *extra child*, exactly at the position where it is written in the production. Perform a **depth-first traversal from left to right**; whenever the traversal reaches an action, it is executed. Figure 16 shows this for a scheme that translates infix to postfix: `expr → expr + term {print('+')} | expr - term {print('-')} | term` and `term → digit {print(digit)}`.

In practice the parser does not need to build this tree. A top-down parser executes an action at the corresponding point of its recursive-descent procedure. A bottom-up (LR) parser can only act when it *reduces*: an action at the right end of a body runs at that reduction (a postfix SDT, next subsection), while an action in the middle of a body needs a marker nonterminal (Section 4.6).

4.3 Postfix translation schemes

If the grammar is LR-parsable and the SDD is **S-attributed**, we can build an SDT with every action at the *right end* of its production (a **postfix SDT**). The actions then execute at *reduction time*, so the attribute of each grammar symbol can be stored beside it on the parser stack.




Figure 16: Parse tree of `9-5+2` with actions (dashed boxes) as extra children. Visiting the tree depth-first, left to right, executes the actions in the order 9, 5, −, 2, +, producing the postfix form.

Postfix SDT for the desk calculator

$L \to E\ \mathbf{n}$	$\{\ print(E.val)\ \}$
$E \to E_1 + T$	$\{\ E.val = E_1.val + T.val\ \}$
$E \to T$	$\{\ E.val = T.val\ \}$
$T \to T_1 * F$	$\{\ T.val = T_1.val \times F.val\ \}$
$T \to F$	$\{\ T.val = F.val\ \}$
$F \to (\ E\ )$	$\{\ F.val = E.val\ \}$
$F \to \mathbf{digit}$	$\{\ F.val = \mathbf{digit}.lexval\ \}$

Implementation on the LR parse stack. Each stack entry holds a grammar symbol and its attribute value. When $A \to XYZ$ is reduced, the actions read the values in the top three entries (`stack[top-2].val`, `stack[top-1].val`, `stack[top].val`), compute $A.val$, pop three entries, and push A with the new value.

Stack (symbol:val)	Remaining input	Action
\$	`3 * 5 + 4 n`	shift
\$ **digit**:3	`* 5 + 4 n`	reduce $F \to$ **digit**
\$ F:3	`* 5 + 4 n`	reduce $T \to F$
\$ T:3	`* 5 + 4 n`	shift $*$, shift **digit**
\$ T:3 $*$ **digit**:5	`+ 4 n`	reduce $F \to$ **digit**
\$ T:3 $*$ F:5	`+ 4 n`	reduce $T \to T * F$ $\quad(3 \times 5 = 15)$
\$ T:15	`+ 4 n`	reduce $E \to T$
\$ E:15	`+ 4 n`	shift $+$, shift **digit**, reduce to T:4
\$ E:15 $+$ T:4	`n`	reduce $E \to E + T$ $\quad(15 + 4 = 19)$
\$ E:19	`n`	shift **n**, reduce $L \to E\,\mathbf{n}$, print 19

4.4 Worked example: infix to postfix, written out completely

The task. In **infix** notation the operator stands between its operands (`a + b`); in **postfix** notation it stands *after* them (`a b +`). Postfix needs no parentheses and no precedence rules: `a*(b+c)-d` becomes `a b c + * d -`, and a stack machine can execute it by pushing operands and letting each operator pop its two arguments. We translate with the usual three-level expression grammar, which already encodes precedence ($*, /$ bind tighter than $+, -$) and left associativity.

Step 1: the SDD. Let every nonterminal have a string attribute t, the postfix form of the part of the input it derives. The operator is appended *after* the strings of its two operands ($\|$ means concatenation):

Production	Semantic rule
$E \to E_1 + T$	$E.t = E_1.t \,\|\| \, T.t \,\|\| \, '+'$
$E \to E_1 - T$	$E.t = E_1.t \,\|\| \, T.t \,\|\| \, '-'$
$E \to T$	$E.t = T.t$
$T \to T_1 * F$	$T.t = T_1.t \,\|\| \, F.t \,\|\| \, '*'$
$T \to T_1 / F$	$T.t = T_1.t \,\|\| \, F.t \,\|\| \, '/'$
$T \to F$	$T.t = F.t$
$F \to (E)$	$F.t = E.t$
$F \to \mathbf{id}$	$F.t = \mathbf{id}.\mathit{lexeme}$
$F \to \mathbf{num}$	$F.t = \mathbf{num}.\mathit{lexval}$

Every rule is S-attributed, so the SDD can be evaluated by a post-order traversal of the parse tree (or during LR parsing). Notice the special form of the rules: the string of the head is made of the strings of the body nonterminals *in the same order*, with extra characters (the operators) inserted in between or appended. For such "simple" SDDs we do not have to build the long strings at all: we may print each piece *at the moment it would have been appended*. That gives the SDT.

Step 2: the SDT. Each rule is replaced by a *print* action at the right end of the body. Since all actions are at the right end, this is a **postfix SDT** and an LR parser can run it. All productions are listed, including those that have no action.

$E \to E_1 + T$	{ $\mathit{print}('+')$ }
$E \to E_1 - T$	{ $\mathit{print}('-')$ }
$E \to T$	
$T \to T_1 * F$	{ $\mathit{print}('*')$ }
$T \to T_1 / F$	{ $\mathit{print}('/')$ }
$T \to F$	
$F \to (E)$	
$F \to \mathbf{id}$	{ $\mathit{print}(\mathbf{id}.\mathit{lexeme})$ }
$F \to \mathbf{num}$	{ $\mathit{print}(\mathbf{num}.\mathit{lexval})$ }

The rules $E \to T$, $T \to F$ and $F \to (E)$ print nothing: they only pass the work on. Operands are printed by the leaf rules, operators by the operator rules, and the position of the action explains the order: when $E \to E_1 + T$ is reduced, E_1 and T have already been reduced, so their output has already appeared and the $+$ comes after both.

Trace 1: `9-5+2` on the LR parse stack

Nothing needs to be stored on the stack; the actions simply print. Read the last column to see the output grow.

#	Stack	Remaining input	Parser step	Output
1	\$	`9-5+2`	shift	
2	\$ **num**	`-5+2`	reduce $F \to$ **num**, **print 9**	`9`
3	\$ F	`-5+2`	reduce $T \to F$	`9`
4	\$ T	`-5+2`	reduce $E \to T$	`9`
5	\$ E	`-5+2`	shift `-`	`9`
6	\$ E −	`5+2`	shift **num**	`9`
7	\$ E − **num**	`+2`	reduce $F \to$ **num**, **print 5**	`95`
8	\$ E − F	`+2`	reduce $T \to F$	`95`
9	\$ E − T	`+2`	reduce $E \to E - T$, **print -**	`95-`
10	\$ E	`+2`	shift `+`	`95-`
11	\$ E +	`2`	shift **num**	`95-`
12	\$ E + **num**		reduce $F \to$ **num**, **print 2**	`95-2`
13	\$ E + F		reduce $T \to F$	`95-2`
14	\$ E + T		reduce $E \to E + T$, **print +**	`95-2+`
15	\$ E		accept	`95-2+`


Step 9 is the important one: the parser reduces $E \to E - T$ *before* shifting the next `+`, so the minus is printed first. That is left associativity: $(9 - 5) + 2$, not $9 - (5 + 2)$.

Trace 2: `a*(b+c)-d`, with parentheses and precedence

Only the reductions that print something are listed; the copy reductions ($T \to F$, $E \to T$, $F \to (E)$) print nothing.

#	Reduction that prints	Prints	Output so far
1	$F \to$ **id** (a)	`a`	`a`
2	$F \to$ **id** (b)	`b`	`ab`
3	$F \to$ **id** (c)	`c`	`abc`
4	$E \to E_1 + T$ $(b + c)$	`+`	`abc+`
5	$T \to T_1 * F$ $(a * (b + c))$	`*`	`abc+*`
6	$F \to$ **id** (d)	`d`	`abc+*d`
7	$E \to E_1 - T$ (whole expression)	`-`	`abc+*d-`

The reduction $F \to (E)$ happens between rows 4 and 5, but it prints nothing: the parentheses have done their job once $b + c$ was reduced as a unit, before the multiplication. The output is the **post-order traversal of the syntax tree**: Figure 17 numbers the nodes in the order in which they are finished, and these are exactly the rows of the table.



Visit order (red): a, b, c, $+$, $*$, d, $-$
Output: `a b c + * d -`

Figure 17: Syntax tree of $a * (b + c) - d$. A node prints itself when its subtree is finished; this is the post-order traversal of Section 2.2.1, so the SDT output is the postfix form.

The position of the action decides the output

Take $E \to E_1 + T$. With the action at the *end*, after T, the operator is printed after both operands: **postfix**. If the action is moved into the *middle*, between E_1 and T (written $E \to E_1\ \{print('+')\}\ +\ T$), the operator is printed between its operands, and the same traversal gives back the **infix** order (without the parentheses). The grammar did not change; only the place of the action did. This is the whole point of an SDT: *where* the action stands defines *when* it runs. (An LR parser could run a middle action only through a marker nonterminal, Section 4.6.)

4.5 SDTs with actions inside productions

When an action is in the middle of a production, it is performed *immediately after all grammar symbols to its left have been matched*. A top-down parser does exactly that: the action is just a statement placed at that point of the recursive-descent procedure. An LR parser cannot: it only takes decisions at reductions, so a mid-production action must first be turned into a reduction using a marker nonterminal (Section 4.6).

Where the action is	**Top-down (LL / recursive descent)**	**Bottom-up (LR)**
At the right end	run after the last symbol of the body is matched	run at the reduction of the body
In the middle	run at that point of the procedure	not possible directly: introduce a marker $M \to \varepsilon$

Complete example: infix to postfix for a *top-down* parser


The postfix SDT of Section 4.4 uses left-recursive productions ($E \to E_1 + T$), which a top-down parser cannot handle. To run the same translation in a recursive-descent parser, we remove the left recursion from the grammar *and keep the actions where they belong*: each print action stays right after the operand it follows. (Why this rewriting works is explained step by step in Section 4.7.)

The simplest version: digits with + and −.

$$E \to T\ R$$
$$R \to +\ T\ \{\ print('+')\ \}\ R_1\ \mid\ -\ T\ \{\ print('-')\ \}\ R_1\ \mid\ \varepsilon$$
$$T \to \textbf{num}\ \{\ print(\textbf{num}.lexval)\ \}$$

Here R stands for "the rest of the expression": zero or more groups of an operator followed by an operand. The action of $R \to +\,T\,\{\dots\}\,R_1$ comes *after* T *and before* R_1: the operand is printed first, then the operator, and only then the rest of the expression is handled. The production $R \to \varepsilon$ has no action: there is nothing left to print.

Execution on `9-5+2`. Figure 18 shows the parse tree with each action as an extra child (dashed box). A depth-first, left-to-right visit executes the actions in the order of the bold numbers.



Output, in the order of the bold numbers:
`9 5 - 2 +` ⇒ `95-2+`

Figure 18: Parse tree of `9-5+2` for the right-recursive scheme, with the actions as extra children. The tree leans to the right, but the actions print the operands and operators in the correct postfix order.

As a recursive-descent parser. A top-down parser has one procedure per nonterminal, and every action is simply a statement written at its position in the production. Here `look` is the current input symbol and `match(c)` consumes it.

```
void E() { T(); R(); }

void R() {
    if (look == '+') { match('+'); T(); print('+'); R(); }
    else if (look == '-') { match('-'); T(); print('-'); R(); }
    else { /* R -> epsilon: do nothing */ }
}

void T() {
    if (isdigit(look)) { c = look; match(look); print(c); }
    else error();
}
```

Compare `R()` with the production: `match('+'); T(); print('+'); R();` is the body $+\ T\ \{print('+')\}\ R_1$ read from left to right.

The complete scheme with ∗, /, parentheses and identifiers. The same trick is repeated for the second precedence level. R is the rest of an expression $(+, -)$ and Q is the

rest of a term $(*, /)$.

$$
\begin{aligned}
&E \to T\ R \\
&R \to +\ T\ \{\ print('+')\ \}\ R_1 \ \mid\ -\ T\ \{\ print('-')\ \}\ R_1 \ \mid\ \varepsilon \\
&T \to F\ Q \\
&Q \to *\ F\ \{\ print('*')\ \}\ Q_1 \ \mid\ /\ F\ \{\ print('/')\ \}\ Q_1 \ \mid\ \varepsilon \\
&F \to (\ E\ ) \ \mid\ \textbf{id}\ \{\ print(\textbf{id}.lexeme)\ \} \ \mid\ \textbf{num}\ \{\ print(\textbf{num}.lexval)\ \}
\end{aligned}
$$

For `a*(b+c)-d` this scheme prints `abc+*d-`, the same output as the bottom-up scheme of Section 4.4: F prints `a`; Q matches $*$, calls F, which parses $(b+c)$ and prints `bc+` inside; only then does Q print `*`; finally R matches $-$, T prints `d`, and R prints `-`.

Worked example: actions in the middle of productions (declarations)

We want to give every identifier in a declaration such as `float x, y` its type. The type is known only after T has been parsed, and the identifiers must receive it *as they are read*. This is why the actions cannot all stand at the end of a production.

$$
\begin{aligned}
&D \to T\ \textbf{id}\ \{\ L.inh = T.type;\ \ addType(\textbf{id}.entry,\ T.type)\ \}\ L \\
&T \to \textbf{int}\ \{\ T.type = integer\ \} \ \mid\ \textbf{float}\ \{\ T.type = float\ \} \\
&L \to ',' \ \textbf{id}\ \{\ addType(\textbf{id}.entry,\ L.inh);\ L_1.inh = L.inh\ \}\ L_1 \ \mid\ \varepsilon
\end{aligned}
$$

The actions of T are at the right end of their bodies, but the actions in D and in L are in the *middle*: each is followed by the nonterminal (L or L_1) that needs the inherited attribute it computes.

Solution for `float x, y`. Figure 19 shows the parse tree with each action as an extra child. A depth-first traversal from left to right executes the actions in the order of the bold numbers.




Figure 19: Parse tree of `float x, y` with the actions as extra children (dashed boxes). The bold numbers give the execution order in a left-to-right depth-first traversal.

(1) Reaching the end of $T \to \textbf{float}$: $T.type = float$.
(2) Back in D, after T and **id** (x) have been visited: $L.inh = float$ and $addType(x, float)$.
(3) In L, after `,` and **id** (y): $addType(y, float)$ and $L_1.inh = float$. The remaining $L_1 \to \varepsilon$ has no action.

Result: the symbol table says $x : float$ and $y : float$.

Why the position matters. If the action of D were written at the *end*, after L, then L would be processed before $L.inh$ has a value, and $addType(y, \dots)$ would use an undefined type. A mid-production action is therefore the way an SDT guarantees that an inherited attribute is computed *before* the symbol that uses it. A top-down parser executes these actions

as statements of its recursive-descent procedures; an LR parser needs marker nonterminals (Section 4.6).

Example: actions at the left end of a production body

An action may be the very first item of a body. (An action cannot be attached to the head of a production; "left" here means the left end of the body.) Such an action runs *before any symbol of the body is matched*, so it can use only the *inherited* attributes of the head. The scheme below prints the nesting depth of every opening parenthesis of a balanced string; $P.d$ is an inherited attribute holding the depth of the current position.

$$S \to \{\ P.d = 0\ \}\ P$$
$$P \to \{\ print(P.d)\ \}\ '('\ \{\ P_1.d = P.d + 1\ \}\ P_1\ ')'\ \{\ P_2.d = P.d\ \}\ P_2 \quad | \quad \varepsilon$$

Here the first action of S *initialises* the inherited attribute of P, and the first action of P *reads* $P.d$, which was set by an action before P was entered. For the input `(()())` the output is `0 1 1`.

4.6 Marker nonterminals (actions in the middle, for bottom-up parsing)

Suppose an action must appear in the middle of a production, e.g., $B \to X\ \{a\}\ Y$. For an LR parser we replace the action by a **marker nonterminal** M with an empty production:

$$B \to X\ M\ Y, \qquad M \to \varepsilon\ \{a\}$$

The action a is then executed upon reducing $M \to \varepsilon$, which happens exactly when X is on top of the stack and Y has not been read yet.

Example: the infix-to-postfix scheme under LR parsing

The top-down scheme $R \to + \ T\ \{print('+')\}\ R_1$ has its action in the middle. For an LR parser we write

$$R \to + \ T\ M\ R_1, \qquad M \to \varepsilon\ \{\ print('+')\ \}$$

When $M \to \varepsilon$ is reduced, the operand T has just been reduced (and printed), so the output order is unchanged: $9\,5\,-\,2\,+$ for `9-5+2`. (This example only illustrates the marker technique. For this translation an LR parser would not use markers at all: the left-recursive postfix SDT of Section 4.4 has every action at the right end of its body.)

Markers can create conflicts

A marker forces the parser to decide to reduce $M \to \varepsilon$ *before* it knows which production will finally be used. If two productions start with the same symbols, say $S \to X\,M\,Y \mid X\,Z$, the parser must choose, using only the next input token, whether to reduce M. If Y and Z can start with the same token, the result is a conflict and the grammar is no longer LR(1). The markers in backpatching (M before a statement, N before **else**) are safe because they always occur at a point where the parser can already tell what is coming.

We will use markers M and N extensively in backpatching (Section 8).

4.7 Eliminating left recursion from an SDT

We go in three small steps: (1) why a top-down parser needs a different grammar, (2) the change of the grammar alone, and (3) how the actions must change with it. The running example is the grammar for sums and differences, $E \to E_1 + T \mid E_1 - T \mid T$.

Two forms of the same question: SDD or SDT

An exam may ask you to remove left recursion from an **SDD** or from an **SDT**. The work is the same; only the way the semantic rules are written differs.

1. **Rewrite the grammar** (Step 2 below). This is identical in both forms.
2. **Rewrite the attribute rules.** The new nonterminal R gets an inherited attribute $R.i$ (the result so far) and a synthesized attribute $R.s$ (the final result). The base case initialises $R.i$; each repeated group updates it and passes it to $R_1.i$; $R \to \varepsilon$ copies $R.i$ into $R.s$; the head copies $R.s$ upward. The outcome is an **SDD**.
3. **Place the rules inside the productions** (SDT only). Each rule becomes an action in braces: an action that computes an inherited attribute of a symbol goes *immediately before* that symbol, and an action that computes a synthesized attribute of the head goes at the *end* of the body (Section 4.8). The outcome is an **SDT**.

	Answer as an SDD	**Answer as an SDT**
Semantic rules are written	as equations next to each production	as $\{\dots\}$ actions inside the body
Does position matter?	no	yes: inherited attribute before the symbol, synthesized attribute of the head at the end
Kind of SDD	L-attributed ($R.i$ is inherited)	the same L-attributed SDD, with its rules placed in the bodies
Evaluated by	depth-first, left-to-right traversal	the parser, as it parses (e.g. recursive descent)

Checklist for a full-marks answer: (a) the new grammar without left recursion; (b) the attributes of the new nonterminal, stating which is inherited and which synthesized; (c) the base-case rule that initialises $R.i$; (d) the update rule for $R_1.i$; (e) the rule $R.s = R.i$ for ε; (f) the rule that copies $R.s$ to the head; (g) for an SDT only, the actions in the correct positions; (h) if an input is given, a trace of $R.i$ and $R.s$.

Which SDDs does this cover? (scope)

The method is the one of the Dragon Book (Section 5.4.4). It removes left recursion from an SDD or SDT in which the left-recursive rules *compute a synthesized attribute of the head from the attributes of the body*: $A \to A_1\, Y$ $\{A.a = g(A_1.a, Y.y)\}$ and $A \to X$ $\{A.a = f(X.x)\}$. In other words, the *given* SDD is S-attributed (or the SDT only prints, as in infix to postfix). The *result* is L-attributed, because the new attribute $R.i$ is inherited. The notes follow the book and do not go beyond this case.

Step 1: why bother? A top-down (recursive-descent) parser has one procedure per nonterminal, and it chooses a production by looking at the next input token. For a left-recursive production the procedure would have to start by calling *itself*:

```
void E() {            // for  E -> E + T
    E();              // calls E() again before reading any token ...
    match('+'); T();  // ... so this line is never reached: infinite recursion
```

```
}
```

No input is consumed between the two calls, so the parser loops forever. A grammar is **left-recursive** when a nonterminal can derive a string that starts with itself, as in $A \to A\,\alpha$. Top-down parsers need that rule rewritten; LR parsers do not (they handle left recursion happily, which is why the postfix SDT of Section 4.4 could use $E \to E_1 + T$).

Step 2: change the grammar (no actions yet). What does $E \to E + T \mid T$ generate? Just a T followed by any number of "$+T$" groups: T, $T + T$, $T + T + T$, ... So we can write the same language directly, left to right:

Left-recursive	**Right-recursive (no left recursion)**
$E \to E + T \mid T$	$E \to T\ R$
	$R \to +\ T\ R \mid \varepsilon$

R means "the rest": zero or more groups of $+T$. Both grammars derive the same string $T + T + T$; only the *order of growth* differs:

$$\begin{aligned} \text{left-recursive:} &\quad E \Rightarrow E + T \Rightarrow E + T + T \Rightarrow T + T + T \\ \text{right-recursive:} &\quad E \Rightarrow T\,R \Rightarrow T + T\,R \Rightarrow T + T + T\,R \Rightarrow T + T + T \end{aligned}$$


In the first derivation the string grows to the left (the first T is produced last); in the second it grows from left to right, the way we read it.

Recipe: removing immediate left recursion (grammar only)

$$A \to A\,\alpha \mid \beta \qquad \text{becomes} \qquad A \to \beta\,R, \qquad R \to \alpha\,R \mid \varepsilon.$$

β is what A can start with, and α is what may be repeated after it. With several alternatives, $E \to E + T \mid E - T \mid T$ gives $E \to T\,R$, $R \to +\,T\,R \mid -\,T\,R \mid \varepsilon$.

Step 3: why the actions must change, too. The new grammar gives the *same strings* but a *different parse tree*. Figure 20 compares the two trees for `9-5+2`.



(a) left-recursive grammar
the tree leans *left*: $(9 - 5) + 2$

(b) right-recursive grammar
the tree leans *right*

Figure 20: Parse trees of `9-5+2` for the two grammars. In (a) the subtree for $9 - 5$ sits below the $+$, so the tree itself shows the grouping. In (b) the 9 and the two operations are siblings along a chain of R's; the grouping is no longer visible in the shape.

In tree (a) the rule $E.val = E_1.val \pm T.val$ gets the grouping $(9-5)+2$ for free, because $9-5$ is a subtree. In tree (b) there is no such subtree. The 9 is a sibling of the whole chain of R's.

The tempting wrong fix

Why not make the grammar right-recursive in the obvious way, $E \to T - E_1 \mid T + E_1 \mid T$, and keep the rules $E.val = T.val \pm E_1.val$? The grammar is fine, but the meaning is wrong: for `9-5+2` we get $9-(5+2) = 2$ instead of $(9-5)+2 = 6$. The tree now groups to the right, and subtraction is not associative. The translation must keep the *left* grouping even though the tree leans right.

The idea: carry a running total. Think of a pocket calculator. You key in 9, then press "−5" (display shows 4), then "+2" (display shows 6). You never needed the whole expression; the display always holds *the result so far*. We give R exactly this display:

- $R.i$ (*inherited*, handed down from the left) is the result **so far** when R starts;
- $R.s$ (*synthesized*, handed back up) is the **final result** when R is finished.

Each rule of the old grammar finds its place in the new one:

1. The **base case** $E \to T$ starts the display: $R.i = T.val$.
2. Each **repeated group** $+T$ or $-T$ updates the display and passes it to the next R: $R_1.i = R.i \pm T.val$.
3. The **end** $R \to \varepsilon$ has nothing more to read, so the display is the answer: $R.s = R.i$. The answer is then copied upward through every R to E.




Figure 21: The running total of `9-5+2` after removing left recursion. Top row: each R receives the total so far in $R.i$, updates it with the next operand, and passes it to the next R. When the input is used up ($R \to \varepsilon$), the total is turned around (bottom row) and copied back through the $R.s$ attributes to $E.val$.

General transformation, SDD form (equations only), with comments

Same colour means same piece: the base case is blue, the repeated part is red. Nothing is invented; every piece of the old rules is only *moved*.

Production	Semantic rules	Why
Left-recursive SDD (given)		
$A \to A_1\, Y$	$A.a = g(A_1.a,\ Y.y)$	
$A \to X$	$A.a = f(X.x)$	
After removing left recursion (answer)		
$A \to X\, R$	$R.i = f(X.x);\ \ A.a = R.s$	The base case *starts* the running value. The final answer is brought back in $R.s$.
$R \to Y\, R_1$	$R_1.i = g(R.i,\ Y.y);\ \ R.s = R_1.s$	Each repetition *updates* the running value: the old $A_1.a$ is now $R.i$. The answer of the rest is passed up unchanged.
$R \to \varepsilon$	$R.s = R.i$	*Nothing left* to read, so the running value is the answer.

$R.i$ is inherited and $R.s$ is synthesized. There are no braces and no order of writing; the dependencies alone fix the order of evaluation. The SDD is now L-attributed, not S-attributed.

General transformation, SDT form (actions inside the body), with comments

given: $A \to A_1\, Y\ \{\ A.a = g(A_1.a,\ Y.y)\ \}\ \mid\ X\ \{\ A.a = f(X.x)\ \}$

answer: $A \to X\ \{\ R.i = f(X.x)\ \}\ R\ \{\ A.a = R.s\ \}$

$R \to Y\ \{\ R_1.i = g(R.i,\ Y.y)\ \}\ R_1\ \{\ R.s = R_1.s\ \}\ \mid\ \varepsilon\ \{\ R.s = R.i\ \}$

Where the actions stand, and why:

- $\{R.i = \dots\}$ and $\{R_1.i = \dots\}$ compute an *inherited* attribute, so they stand *immediately before* the R that uses it (the value must exist before R starts).
- $\{A.a = R.s\}$ and $\{R.s = R_1.s\}$ compute a *synthesized* attribute of the head, so they stand at the *end* of the body (the value exists only after R has finished).
- The action of $R \to \varepsilon$ is the only body, so it is both first and last.




Figure 22: (a) Before: the left-recursive parse tree for the input $X\,Y\,Y$. The values flow up the left spine: $f(X.x)$ first, then the first Y is combined, then the second.




Figure 23: (b) After: the transformed parse tree for the same input $X\,Y\,Y$. Dashed arrows: the running value i is passed down the chain of R's, starting with $f(X.x)$ and combined with each Y in the same order as in (a). Solid arrows: at $R_2 \to \varepsilon$ the value is turned around ($s = i$) and comes back up through the s attributes to $A.a$.

What to write in the exam: the procedure in six steps (SDD or SDT)

Given $E \to E_1 + T \ \{E.val = E_1.val + T.val\} \mid E_1 - T \ \{E.val = E_1.val - T.val\} \mid T \ \{E.val = T.val\}$. The left column is what to do, the right column is the result for this grammar.

Step	Result for the example
1. **Find the parts.** Which alternatives are left-recursive ($A \to A\,\alpha$), which is the base case ($A \to \beta$)? Note the function each one computes.	Recursive: $+T$ with $g_1(a, y) = a + y$ and $-T$ with $g_2(a, y) = a - y$. Base: T with $f(x) = x$.
2. **New grammar.** $A \to \beta\,R$ and $R \to \alpha_1 R \mid \alpha_2 R \mid \cdots \mid \varepsilon$.	$E \to T\,R$, $R \to +T\,R \mid -T\,R \mid \varepsilon$
3. **New attributes.** $R.i$ inherited (value so far), $R.s$ synthesized (final value).	$R.i$ and $R.s$ hold numbers, like $E.val$.
4. **Base case.** Start the running value, bring back the answer.	$E \to T\,R$: $R.i = T.val$; $E.val = R.s$
5. **Each recursive alternative.** New running value = old function with $R.i$ in place of $A_1.a$; pass the answer up.	$R \to +T\,R_1$: $R_1.i = R.i + T.val$; $R.s = R_1.s$. Similarly for $-$: $R_1.i = R.i - T.val$.
6. **The empty case.** The running value is the answer.	$R \to \varepsilon$: $R.s = R.i$

For an SDD the six steps are the whole answer. **For an SDT** add a seventh step: put each equation into the body as an action, the ones for inherited attributes just before their symbol and the ones for synthesized attributes at the end, exactly as in the box above. **Always finish with a check** on a short input such as `9-5+2`: the running value must go $9 \to 4 \to 6$.

Example 1, SDD form: removing left recursion from the SDD of $9 - 5 + 2$

Given (left-recursive, S-attributed):

Production	Semantic rule
$E \to E_1 + T$	$E.val = E_1.val + T.val$
$E \to E_1 - T$	$E.val = E_1.val - T.val$
$E \to T$	$E.val = T.val$
$T \to \mathbf{num}$	$T.val = \mathbf{num}.lexval$

Answer (the SDD after removing left recursion):

Production	Semantic rule
$E \to T\,R$	$R.i = T.val$; $E.val = R.s$
$R \to +T\,R_1$	$R_1.i = R.i + T.val$; $R.s = R_1.s$
$R \to -T\,R_1$	$R_1.i = R.i - T.val$; $R.s = R_1.s$
$R \to \varepsilon$	$R.s = R.i$
$T \to \mathbf{num}$	$T.val = \mathbf{num}.lexval$

Classification and evaluation. $T.val$, $R.s$ and $E.val$ are synthesized; $R.i$ is inherited. The rule for $R_1.i$ uses the inherited attribute of its parent ($R.i$) and the attribute of the sibling T

to its left, so the SDD is **L-attributed** but no longer S-attributed. A single depth-first, left-to-right traversal evaluates it. For `9-5+2` the values are $R.i = 9,\ 4,\ 6$ and finally $E.val = 6$, exactly as in the figure and the table of the next example, which shows the same rules written as an SDT.

Example 1, SDT form: evaluating $9 - 5 + 2$ with a left-recursion-free grammar

The left-recursive grammar $E \to E_1 + T \mid E_1 - T \mid T$, $T \to \textbf{num}$, with $E.val = E_1.val \pm T.val$, becomes

$$
\begin{aligned}
&E \to T \ \{\ R.i = T.val\ \}\ R\ \{\ E.val = R.s\ \}\\
&R \to +\ T\ \{\ R_1.i = R.i + T.val\ \}\ R_1\ \{\ R.s = R_1.s\ \}\\
&\quad \mid\ -\ T\ \{\ R_1.i = R.i - T.val\ \}\ R_1\ \{\ R.s = R_1.s\ \}\ \mid\ \varepsilon\ \{\ R.s = R.i\ \}\\
&T \to \textbf{num}\ \{\ T.val = \textbf{num}.lexval\ \}
\end{aligned}
$$




Figure 24: Annotated parse tree for `9-5+2`. The inherited $R.i$ flows down and to the right ($9 \to 4 \to 6$: first $9 - 5$, then $4 + 2$); the synthesized $R.s$ then carries the final 6 back up to $E.val$.

The running total step by step. Each row is one call of R; read $R.i$ as "the display of the calculator".

Call	$R.i$ **on entry**	**Next input**	**Action**	$R.s$ **on return**
$E \to T\ R$	—	`9`	$R.i = T.val = 9$	—
R (1st)	9	`- 5`	$R_1.i = 9 - 5 = 4$	6
R_1 (2nd)	4	`+ 2`	$R_2.i = 4 + 2 = 6$	6
R_2 (3rd)	6	end of input	ε: $R_2.s = R_2.i = 6$	6

The value goes *down* as $R.i$ ($9 \to 4 \to 6$) and the final 6 is copied back *up* through the $R.s$ attributes to $E.val$.
The tree leans to the right, but the arithmetic is still left-associative: $(9-5)+2=6$, not $9-(5+2)=2$.

Example 2, SDD form: the syntax-tree SDD without left recursion

The syntax-tree SDD of Section 3.9 is left-recursive in E. Here $R.i$ holds a *pointer to the tree built so far*:

Production	Semantic rule
$E \to T\ R$	$R.i = T.node;\ \ E.node = R.s$
$R \to +\ T\ R_1$	$R_1.i =$ **new** $Node('+',\ R.i,\ T.node);\ \ R.s = R_1.s$
$R \to -\ T\ R_1$	$R_1.i =$ **new** $Node('-',\ R.i,\ T.node);\ \ R.s = R_1.s$
$R \to \varepsilon$	$R.s = R.i$
$T \to (\ E\ )$	$T.node = E.node$
$T \to$ **id**	$T.node =$ **new** $Leaf($**id**, **id**$.entry)$
$T \to$ **num**	$T.node =$ **new** $Leaf($**num**, **num**$.val)$

Only the first four rows are new; the three T rows are unchanged. The same rules written as an SDT, together with a trace for `a - 4 + c`, are in the example of Section 4.8. The pattern is the one of Example 1: the base case initialises $R.i$, every repeated group updates it (here: builds a new node with the old tree as its left child), and ε hands the result up.

Example 3, both forms: counting the items of a list

The grammar $L \to L_1\ ','\ \textbf{id} \mid \textbf{id}$ generates lists such as `x, y, z`. The attribute $L.count$ is the number of identifiers.
Left-recursive SDD (given).

$L \to L_1\ ','\ \textbf{id}$	$L.count = L_1.count + 1$
$L \to \textbf{id}$	$L.count = 1$

Step 1, the grammar. L is an **id** followed by any number of "$','$ **id**" groups, so $L \to \textbf{id}\ R$ and $R \to ','\ \textbf{id}\ R \mid \varepsilon$.
Step 2, the SDD form.

$L \to \textbf{id}\ R$	$R.i = 1;\ \ L.count = R.s$
$R \to ','\ \textbf{id}\ R_1$	$R_1.i = R.i + 1;\ \ R.s = R_1.s$
$R \to \varepsilon$	$R.s = R.i$

Step 3, the SDT form (every inherited attribute is computed just before its symbol, every synthesized attribute of the head at the end):

$$L \to \textbf{id}\ \{\ R.i = 1\ \}\ R\ \{\ L.count = R.s\ \}$$
$$R \to ','\ \textbf{id}\ \{\ R_1.i = R.i + 1\ \}\ R_1\ \{\ R.s = R_1.s\ \}\ \mid\ \varepsilon\ \{\ R.s = R.i\ \}$$

Trace for `x, y, z`. $R.i = 1$ after `x`; after `, y` the next R gets $i = 2$; after `, z` the next gets $i = 3$; $R \to \varepsilon$ gives $R.s = 3$, which is copied up to $L.count = 3$.

Example 4: two recursive alternatives (the general case)

Real grammars have several recursive alternatives, such as $E \to E_1 + T \mid E_1 - T \mid T$. The general form is

$$A \to A_1\, Y \;\{\; A.a = g(A_1.a,\; Y.y) \;\} \;\mid\; A_1\, Z \;\{\; A.a = h(A_1.a,\; Z.z) \;\} \;\mid\; X \;\{\; A.a = f(X.x) \;\}.$$

SDD form of the answer. Every recursive alternative becomes one alternative of R, with its *own* function:

$A \to X\, R$	$R.i = f(X.x);\;\; A.a = R.s$
$R \to Y\, R_1$	$R_1.i = g(R.i,\; Y.y);\;\; R.s = R_1.s$
$R \to Z\, R_1$	$R_1.i = h(R.i,\; Z.z);\;\; R.s = R_1.s$
$R \to \varepsilon$	$R.s = R.i$

SDT form of the answer.

$$\begin{aligned} &A \to X \;\{\; R.i = f(X.x) \;\}\; R \;\{\; A.a = R.s \;\} \\ &R \to Y \;\{\; R_1.i = g(R.i,\; Y.y) \;\}\; R_1 \;\{\; R.s = R_1.s \;\} \\ &\quad \mid\; Z \;\{\; R_1.i = h(R.i,\; Z.z) \;\}\; R_1 \;\{\; R.s = R_1.s \;\} \;\mid\; \varepsilon \;\{\; R.s = R.i \;\} \end{aligned}$$

The sum-and-difference grammar is the instance $Y = +T$, $Z = -T$, $g(a, y) = a+y$, $h(a, z) = a - z$, $f(x) = x$. If there are *several base cases* ($A \to X \mid W$), each gets its own copy of the first rule: $A \to X\, R$ with f_1 and $A \to W\, R$ with f_2. If the SDD computes *several attributes*, each one gets its own pair $R.i_k$, $R.s_k$.

Common mistakes when removing left recursion

- **Wrong operand order.** The new running value is $R.i - T.val$ (old value first), never $T.val - R.i$. It does not matter for $+$ and $*$, but it does for $-$ and $/$.
- **Forgetting to start the accumulator,** that is, the rule $R.i = f(X.x)$ in the base case; or forgetting to bring the answer back with $A.a = R.s$.
- **Forgetting the ε rule** $R.s = R.i$. Without it the final value is never turned around.
- **In an SDT: putting the action for $R_1.i$ after R_1.** An inherited attribute must be computed *before* the symbol that uses it.
- **Fixing only the grammar.** The right-recursive grammar with the old rules gives the wrong grouping (see the pitfall box above); the attributes must be rewritten, too.

4.8 Converting an L-attributed SDD into an SDT

Rules for converting an L-attributed SDD to an SDT

1. **Inherited attribute** of a nonterminal X in the body: embed the action that computes it *immediately before* X in the body. If several inherited attributes of X depend on one another, order the actions appropriately.
2. **Synthesized attribute** of the head A: place the action that computes it at the *end* of the production body.

Example: syntax tree for a left-recursion-free grammar

After removing left recursion from $E \to E_1 + T \mid E_1 - T \mid T$ (the SDD form of these rules is Example 2 of Section 4.7):

$$
\begin{aligned}
&E \to T \ \{\ R.i = T.node\ \}\ R\ \{\ E.node = R.s\ \}\\
&R \to + \ T\ \{\ R_1.i = \textbf{new}\ \mathit{Node}('+', R.i, T.node)\ \}\ R_1\ \{\ R.s = R_1.s\ \}\\
&R \to - \ T\ \{\ R_1.i = \textbf{new}\ \mathit{Node}('-', R.i, T.node)\ \}\ R_1\ \{\ R.s = R_1.s\ \}\\
&R \to \varepsilon\ \{\ R.s = R.i\ \}\\
&T \to \textbf{id}\ \{\ T.node = \textbf{new}\ \mathit{Leaf}(\textbf{id}, \textbf{id}.\mathit{entry})\ \}\\
&T \to \textbf{num}\ \{\ T.node = \textbf{new}\ \mathit{Leaf}(\textbf{num}, \textbf{num}.\mathit{val})\ \}
\end{aligned}
$$

Here $R.i$ (inherited) carries the tree built *so far*; $R.s$ (synthesized) returns the final tree. For `a - 4 + c` the tree $((a-4)+c)$ is produced with the correct left-associativity.

Trace for `a - 4 + c`. Now the "running total" is a *pointer to the tree built so far*. The nodes are named $p_1, \ldots, p_5$ in the order of creation, exactly as in Section 3.9.

Call	$R.i$ on entry	Next input	Action	$R.s$ on return
$E \to T\,R$	—	`a`	$T.node = p_1$ (leaf a); $R.i = p_1$	—
R (1st)	p_1	`- 4`	$T.node = p_2$ (leaf 4); $R_1.i = \textbf{new}\ \mathit{Node}('-', p_1, p_2) = p_3$	p_5
R_1 (2nd)	p_3	`+ c`	$T.node = p_4$ (leaf c); $R_2.i = \textbf{new}\ \mathit{Node}('+', p_3, p_4) = p_5$	p_5
R_2 (3rd)	p_5	end	ε: $R_2.s = R_2.i = p_5$	p_5

The same five nodes are created in the same order as with the left-recursive SDD, so the syntax tree is identical (Figure 13); only the way the pointer travels differs: it is handed down in $R.i$ and returned in $R.s$.

4.9 Application: the structure of a type (array types)

The task. A declaration such as `int [2][3]` must be turned into a **type expression**: the array type $\mathit{array}(2,\ \mathit{array}(3,\ \mathit{integer}))$, an array of 2 elements, each of which is an array of 3 integers. The compiler later uses this tree to compute sizes and offsets (Section 5.1) and to check types.

The grammar. $T \to B\,C$, $B \to \textbf{int} \mid \textbf{float}$, $C \to [\,\textbf{num}\,]\,C_1 \mid \varepsilon$. The nonterminal B is the basic type and C is the (possibly empty) list of dimensions.

The SDD. The basic type $B.t$ is known at the *left*, but it has to end up at the *bottom* of the array type, where the last dimension is. So we pass it down in an inherited attribute $C.b$ ("base") and build the type on the way back up in the synthesized attribute $C.t$.

Production	Semantic rules
$T \to B\,C$	$T.t = C.t;\ \ C.b = B.t$
$B \to \textbf{int}$	$B.t = \mathit{integer}$
$B \to \textbf{float}$	$B.t = \mathit{float}$
$C \to [\,\textbf{num}\,]\,C_1$	$C.t = \mathit{array}(\textbf{num}.\mathit{val},\ C_1.t);\ \ C_1.b = C.b$
$C \to \varepsilon$	$C.t = C.b$

$B.t$, $C.t$ and $T.t$ are synthesized; $C.b$ is inherited. The SDD is **L-attributed**: $C.b$ of C depends on its left sibling B, and $C_1.b$ depends on the inherited attribute of its parent. It is not S-attributed, because the base type has to travel *downward*.

Example: the type of `int [2][3]`

The parse tree and the values of the attributes are in Figure 25.




Figure 25: Annotated parse tree of `int [2][3]`. The base type *integer* flows *down* through the inherited attributes $C.b$ to the empty production; the array type is assembled on the way *up* in the synthesized attributes $C.t$.

The order in which the values are computed (depth-first, left to right):

Step	Rule used	Value
1	$B \to \textbf{int}$	$B.t = integer$
2	$T \to B\,C$	$C.b = B.t = integer$
3	$C \to [2]\,C_1$	$C_1.b = C.b = integer$
4	$C_1 \to [3]\,C_2$	$C_2.b = C_1.b = integer$
5	$C_2 \to \varepsilon$	$C_2.t = C_2.b = integer$
6	$C_1 \to [3]\,C_2$	$C_1.t = array(3,\ C_2.t) = array(3, integer)$
7	$C \to [2]\,C_1$	$C.t = array(2,\ C_1.t) = array(2, array(3, integer))$
8	$T \to B\,C$	$T.t = C.t$

Steps 1 to 4 go *down* (inherited attributes), steps 5 to 8 come back *up* (synthesized attributes). The innermost dimension, 3, is applied first, so the result is $array(2, array(3, integer))$ and not the other way round.

As an SDT. Following the rules of Section 4.8, the action that computes the inherited attribute $C.b$ goes immediately before C, and the actions that compute synthesized attributes go at the end:

$$T \to B \ \{\ C.b = B.t\ \}\ C\ \{\ T.t = C.t\ \}$$
$$B \to \textbf{int}\ \{\ B.t = \mathit{integer}\ \} \mid \textbf{float}\ \{\ B.t = \mathit{float}\ \}$$
$$C \to [\ \textbf{num}\ ]\ \{\ C_1.b = C.b\ \}\ C_1\ \{\ C.t = \mathit{array}(\textbf{num}.\mathit{val},\ C_1.t)\ \} \mid \varepsilon\ \{\ C.t = C.b\ \}$$

The grammar is right-recursive, so a top-down parser can use it directly; no left recursion has to be removed. Section 4.10 turns it into a recursive-descent parser.

Why not synthesized attributes only?

Suppose we try $C \to [\textbf{num}]\, C_1$ with $C.t = \mathit{array}(\mathit{num}.\mathit{val},\ C_1.t)$ and $C \to \varepsilon$ with $C.t = B.t$. The base type of B is not visible inside C (it is a sibling of C's parent), so $C \to \varepsilon$ cannot read it. This is exactly why the inherited attribute $C.b$ is needed: it carries $B.t$ down to the place where it is used.

4.10 Implementing L-attributed SDDs during top-down parsing

An L-attributed SDD can be evaluated in a single left-to-right depth-first traversal, which is exactly the order in which a top-down parser works. So an SDT for an L-attributed SDD can be executed *while parsing*, without building the parse tree. There are three ways to do this with a top-down parser; they differ in where the attribute values are kept.

Method	Parser	Where attributes live
A. Arguments and return values	recursive descent	inherited attributes are *parameters* of the procedure of the nonterminal, synthesized attributes are its *return values*
B. On-the-fly generation	recursive descent	the big "code" attribute is not built as a string; its pieces are *emitted* (printed) as soon as they are known
C. Parser-stack records	table-driven LL (stack)	values are kept in *records on the parser stack* and are copied from record to record

A fourth way, for bottom-up parsers (marker nonterminals and attributes on the LR stack), belongs to the bottom-up parsing lectures; Section 4.6 shows the basic marker idea.

4.10.1 Method A: recursive descent with arguments and return values

Recipe: one procedure per nonterminal

For a nonterminal A with inherited attributes $a_1, \ldots$ and synthesized attributes $s_1, \ldots$, write a procedure `A(`$a_1, \ldots$`)` that returns $s_1, \ldots$. In its body, handle the chosen production from left to right:

1. for a terminal: `match(token)` (and save its attribute, e.g. `lexval`, in a local variable if it is needed);
2. for a nonterminal X: compute its inherited attributes from the variables seen so far, **call** `X(...)`, and store the returned synthesized attributes in local variables;
3. for an action: write it as a statement at that point;
4. at the end: `return` the synthesized attributes of A.

Because the SDD is L-attributed, every value an inherited attribute needs has already been

computed when the call is made.

Example A1: the array type of `int [2][3]`

The SDT of the previous subsection becomes three procedures. `C(b)` receives the inherited attribute $C.b$ as its argument and returns $C.t$:

```
Type T() {
    Type b = B();              // B.t
    return C(b);               // C.b = B.t ;  T.t = C.t
}
Type B() {
    if (look == INT)  { match(INT);   return integer; }   // B.t
    else              { match(FLOAT); return float;   }
}
Type C(Type b) {               // b is the inherited attribute C.b
    if (look == '[') {
        match('[');  n = lexval;  match(NUM);  match(']');
        Type c1 = C(b);        // C1.b = C.b
        return array(n, c1);   // C.t = array(num.val, C1.t)
    }
    return b;                  // C -> epsilon:  C.t = C.b
}
```

Trace for `int [2][3]`: `T()` calls `B()` which returns *integer*; then `C(integer)` reads `[2]` and calls `C(integer)`, which reads `[3]` and calls `C(integer)`; this call sees no `[`, so it returns *integer*. The returns then build $array(3, integer)$ and finally $array(2, array(3, integer))$. The values travel *down* as arguments and *up* as return values, exactly as in Figure 25.

Example A2: sums and differences without left recursion

For the SDT of Example 1 in Section 4.7, the inherited attribute $R.i$ is the parameter of `R` and $R.s$ is its return value. The terminal **num** has the attribute `lexval`.

```
int E() { int t = T();  return R(t); }       // R.i = T.val ;  E.val = R.s

int R(int i) {                               // i is R.i
    if (look == '+') { match('+'); int t = T(); return R(i + t); }
    if (look == '-') { match('-'); int t = T(); return R(i - t); }
    return i;                     // R -> epsilon:  R.s = R.i
    // R1.i = R.i +/- T.val  is the argument of the recursive call
}

int T() { int v = lexval;  match(NUM);  return v; }   // T.val = num.lexval
```

For `9-5+2`: `E()` gets 9 from `T()` and calls `R(9)`; `R(9)` reads `-5` and calls `R(4)`; `R(4)` reads `+2` and calls `R(6)`; `R(6)` finds the end of the input and returns 6, which every caller returns unchanged. The pointer-based variant for the syntax tree of Section 4.8 has the same shape: `Node R(Node i)` returns `R(new Node('+', i, t))` instead of `R(i + t)`, and `return i` at the end.

Example A3: code for a `while` statement

The **while** statement of the Dragon Book (Chapter 5) is $S \to \textbf{while}\,(\,C\,)\,S_1$. The attributes are: $S.next$ (inherited; the label after the statement), $C.true$ and $C.false$ (inherited; the jump targets of the condition), and the synthesized $S.code$ and $C.code$. The SDT creates two

labels L_1 and L_2:

$$S \to \textbf{while}\ (\ \{\ L_1 = new();\ L_2 = new();\ C.false = S.next;\ C.true = L_2\ \}\ C\ )$$
$$\{\ S_1.next = L_1\ \}\ S_1\ \{\ S.code = label \parallel L_1 \parallel C.code \parallel label \parallel L_2 \parallel S_1.code\ \}$$

The generated code is L_1: $C.code$ (it jumps to L_2 if the condition is true and to $S.next$ if false), then L_2: $S_1.code$, which ends with a jump back to $S_1.next = L_1$. (The flow-of-control SDD later in these notes, taken from Chapter 6 of the book, writes the same translation with an explicit `goto begin`.)
As a recursive-descent procedure, $S.next$ is the argument, $S.code$ the return value (a string), and the labels are local variables:

```
string S(label next) {
    string Scode, Ccode;               // code strings
    label L1, L2;                      // local labels
    if (look == WHILE) {
        match(WHILE);  match('(');
        L1 = new();  L2 = new();
        Ccode = C(next, L2);           // C.false = S.next, C.true = L2
        match(')');
        Scode = S(L1);                 // S1.next = L1
        return "label" || L1 || Ccode || "label" || L2 || Scode;
    }
    else { /* other statement types */ }
}
```

Each call of `S` or `C` returns the code of its own part, and the caller concatenates the pieces in the order of the SDD.

4.10.2 Method B: on-the-fly code generation

Method A builds the whole code of a statement as one long string and returns it, so the code of a big program is copied over and over as it is returned upward. We can avoid this when the main attribute (here $S.code$) is a *concatenation of the pieces produced by its children, in the same order as the children appear in the body, with fixed strings between them.* Then, instead of building the string, each piece is simply **printed at the moment it is known**; the order of the printing is the order of the concatenation. The SDT of Example A3 changes in just two places: the construction of $S.code$ disappears and two *print* actions are added.

$$S \to \textbf{while}\ (\ \{\ L_1 = new();\ L_2 = new();\ C.false = S.next;\ C.true = L_2;\ print(\text{“label”}, L_1)\ \}\ C\ )$$
$$\{\ S_1.next = L_1;\ print(\text{“label”}, L_2)\ \}\ S_1$$

```
void S(label next) {                   // S.code is not returned: it is printed
    label L1, L2;
    if (look == WHILE) {
        match(WHILE);  match('(');
        L1 = new();  L2 = new();
        print("label", L1);            // the first piece of S.code
        C(next, L2);                   // C prints its own code
        match(')');
        print("label", L2);            // the next piece
        S(L1);                         // S1 prints its own code
    }
    else { /* other statement types */ }
}
```

The output is the same as before, but no code string is ever copied. This is the same idea as the incremental translation with *gen* of Section 5.1.

When on-the-fly generation is not possible

Printing is correct only if the pieces appear in the code in the same order as the symbols in the production body. If a rule used $S.code = S_2.code \,\|\, S_1.code$ (the code of the *later* symbol first), the parser would reach S_1 first and print its code too early. In that case Method A, which returns strings, is needed.

4.10.3 Method C: attributes on the stack of a table-driven LL parser

A table-driven LL parser has no procedures to hold local variables, so the attribute values are kept on its **stack** in extra records. The stack is drawn with its top at the *left*; the next thing to be done is the leftmost entry. The rules below (the book calls them action records and synthesize records) are all we need:

1. The **inherited attributes** of a nonterminal A are stored in the stack entry of A.
2. Every **action** of the SDT becomes an *action record* pushed at its position in the body. An action that computes an inherited attribute of X stands immediately above X, so it can write into the entry of X.
3. Every nonterminal X in a body gets a **synthesize record** X_s pushed immediately *below* X. The action at the end of X's body stores the synthesized attribute of X there.
4. **Copying.** An action record holds copies of the values it needs. They are copied into it at three moments: when the head of the production is expanded (its inherited attributes), when a terminal is matched (its *lexval*), and when a synthesize record reaches the top of the stack (it is popped and its content is copied into the action record below it).
5. A record at the top of the stack is processed by executing the action and popping it.

Example C1: the `while` statement on the LL stack

Take the on-the-fly SDT of Method B, whose production is $S \to$ **while** (a_1 C) a_2 S_1, where a_1 is the first action (creates L_1, L_2, sets C's attributes) and a_2 is the second (sets $S_1.next$). Let $S.next = x$, and let the new labels be $L_1 = y$ and $L_2 = z$. Only inherited attributes occur, so there are no synthesize records.

Moment	Stack (top at the left)	Output
Just before expanding S	$S\,[next = x]$ …	
Immediately after expanding S	**while** ($[a_1 : S.next = x,\ L_1,\ L_2]$ $C\,[true, false]$) $[a_2 : L_1,\ L_2]$ $S_1\,[next]$ …	
After **while**, (are matched and a_1 runs	$C\,[true = z,\ false = x]$) $[a_2 : L_1 = y,\ L_2 = z]$ $S_1\,[next]$ …	`label y`
After C and) are processed and a_2 runs	$S_1\,[next = y]$ …	`label z`

Note the copying: when S is expanded, the entry of S disappears, so its inherited attribute $S.next = x$ is first *copied* into the record of a_1. Action a_1 then creates y and z, writes C's attributes into the entry of C directly below it, and copies y and z into the record of a_2, which will need them later.

Example C2: synthesize records for `9-5+2`

Use the SDT of Example 1 in Section 4.7, with the actions named:

$$E \to T\ \{a_1:\ R.i = T.val\}\ R\ \{a_2:\ E.val = R.s\}$$
$$R \to +\ T\ \{b_1:\ R_1.i = R.i + T.val\}\ R_1\ \{b_2:\ R.s = R_1.s\}$$
$$\mid\ -\ T\ \{b_1:\ R_1.i = R.i - T.val\}\ R_1\ \{b_2:\ R.s = R_1.s\}\ \mid\ \varepsilon\ \{c:\ R.s = R.i\}$$
$$T \to \textbf{num}\ \{d:\ T.val = \textbf{num}.lexval\}$$

Moment	Stack (top at the left)	Input
Start	$E\ E_s$	`9-5+2`
E expanded	$T\ T_s\ a_1\ R\ R_s\ a_2\ E_s$	`9-5+2`
T done (T_s=9 copied into a_1), a_1 run	$R[i{=}9]\ R_s\ a_2\ E_s$	`-5+2`
R expanded by $-$ ($R.i = 9$ copied into b_1)	$-\ T\ T_s\ [b_1:\ R.i{=}9]\ R\ R_s\ b_2\ R_s\ a_2\ E_s$	`-5+2`
T done ($T.val = 5$), b_1 run: $R_1.i = 9 - 5 = 4$	$R[i{=}4]\ R_s\ b_2\ R_s\ a_2\ E_s$	`+2`
second R expanded by $+$, b_1 run: $R_1.i = 4 + 2 = 6$	$R[i{=}6]\ R_s\ b_2\ R_s\ b_2\ R_s\ a_2\ E_s$	end
$R \to \varepsilon$, action c: $R.s = R.i$	$R_s{=}6\ b_2\ R_s\ b_2\ R_s\ a_2\ E_s$	end
each b_2 copies $R_1.s$ into its R_s, then a_2	$E_s{=}6$	end

The inherited value $R.i$ moves *right* through the action records ($9 \to 4 \to 6$), and the final 6 moves *left* through the synthesize records, one for each R, until it reaches E_s.

Which method to use?

Method A is the easiest to write and to read, and it handles any L-attributed SDD; the price is the strings that are returned. Method B is Method A without the strings and is the choice for code generation. Method C is what a generated, table-driven LL parser does; it is rarely written by hand. All three execute the same SDT, and all three need an L-attributed SDD: an inherited attribute that depends on a symbol to its right could not be evaluated, because that symbol has not been parsed yet.

5 Translation of Expressions and Assignments

5.1 SDD for three-address code

We use the following:

- $E.addr$: the address (name, constant, or temporary) that holds the value of E.
- $E.code$ (or $S.code$): the three-address instructions that evaluate E (or execute S).
- *newTemp*() (written **new** *Temp*): returns a fresh temporary $t_1, t_2, \ldots$ in successive calls.
- **gen**$(\cdots)$: builds a three-address instruction. $\|$ denotes concatenation of instruction sequences.

Production	Semantic rules
$S \to \mathbf{id} = E\ ;$	$S.code = E.code \parallel \mathbf{gen}(top.get(\mathbf{id}.lexeme) = E.addr)$
$E \to E_1 + E_2$	$E.addr = \mathbf{new}\ Temp()$
	$E.code = E_1.code \parallel E_2.code \parallel \mathbf{gen}(E.addr = E_1.addr + E_2.addr)$
$E \to E_1 * E_2$	$E.addr = \mathbf{new}\ Temp()$
	$E.code = E_1.code \parallel E_2.code \parallel \mathbf{gen}(E.addr = E_1.addr * E_2.addr)$
$E \to -\,E_1$	$E.addr = \mathbf{new}\ Temp()$
	$E.code = E_1.code \parallel \mathbf{gen}(E.addr = \texttt{minus}\ E_1.addr)$
$E \to (\,E_1\,)$	$E.addr = E_1.addr; \quad E.code = E_1.code$
$E \to \mathbf{id}$	$E.addr = top.get(\mathbf{id}.lexeme); \quad E.code = ''$


Table 6: SDD to produce three-address code for expressions and assignments (Dragon Book Fig. 6.19).

Remark

Here *top* is the current symbol table; $top.get(name)$ returns the symbol-table entry. The code of a node is the *concatenation* of its children's code followed by one new instruction, so the instructions are produced in postfix (evaluation) order. The *.code* attribute is a long string, so this SDD is inefficient in practice, which motivates the incremental approach below.

The grammar $E \to E_1 + E_2 \mid E_1 * E_2 \mid -E_1 \mid (E_1) \mid \mathbf{id}$ is ambiguous. Precedence ($-$ highest, then $*$, then $+$) and left-associativity are supplied either by parser-generator declarations or by rewriting the grammar with levels E, T, F. This does not change the semantic rules: they are written once per *operator*, whatever the grammar levels are called. The $*$ rule is the $+$ rule with the operator replaced; the rule for binary $-$ and for $/$ is identical again.

Worked example: $a = b * -c + b * -c\ ;$



Concatenating the code in the order of evaluation gives:

```
t1 = minus c
t2 = b * t1
t3 = minus c
t4 = b * t3
t5 = t2 + t4
a  = t5
```

5.2 Incremental translation (SDT with `gen` emitting directly)

Building $E.code$ as a string copies code repeatedly. In an *incremental* scheme, $gen()$ **appends** the instruction to an output stream/array as soon as the action is executed. The code attribute is not stored. Since actions run in the correct order (postfix), the instructions come out in the right order.

Production	Translation scheme (actions in braces)
$S \to \mathbf{id} = E\ ;$	$\{\ gen(top.get(\mathbf{id}.lexeme) = E.addr);\ \}$
$E \to E_1 + E_2$	$\{\ E.addr = \mathbf{new}\ Temp();\ gen(E.addr = E_1.addr + E_2.addr);\ \}$
$\mid\ E_1 * E_2$	$\{\ E.addr = \mathbf{new}\ Temp();\ gen(E.addr = E_1.addr * E_2.addr);\ \}$
$\mid\ -E_1$	$\{\ E.addr = \mathbf{new}\ Temp();\ gen(E.addr = \texttt{minus}\ E_1.addr);\ \}$
$\mid\ (E_1)$	$\{\ E.addr = E_1.addr;\ \}$
$\mid\ \mathbf{id}$	$\{\ E.addr = top.get(\mathbf{id}.lexeme);\ \}$

Table 7: Incremental SDT for expressions (all actions are at the right end, so it is a postfix SDT, suitable for LR parsing).

Worked example (incremental SDT): `x = a * b + c * d ;`

An LR parser reduces from left to right, and every reduction that creates a temporary emits *one* instruction at that moment. Reductions $E \to \mathbf{id}$ only set *addr* and emit nothing. The red numbers show the order in which instructions are emitted.




Figure 26: Parse tree of `x = a * b + c * d ;` with the order of emission.

#	Reduction	Instruction emitted
1	$E \to E_1 * E_2$ `(a * b)`	`t1 = a * b`
2	$E \to E_1 * E_2$ `(c * d)`	`t2 = c * d`
3	$E \to E_1 + E_2$	`t3 = t1 + t2`
4	$S \to \mathbf{id} = E\,;$	`x = t3`

Note that `c * d` is reduced only after the parser has seen the `;`: precedence decides that $*$ binds tighter, so the $+$ cannot be reduced earlier.

5.3 Addressing array elements

Let an array be stored in a contiguous block of memory with base address *base* and element width w.

One-dimensional array $A[low \ \ldots \ high]$:

$$\text{address of } A[i] \ = \ base + (i - low) \times w$$

If $low = 0$ this is simply $base + i \times w$.

Two-dimensional array (row-major) $A[n_1][n_2]$ with element width w:

$$\text{address of } A[i_1][i_2] \ = \ base + (i_1 \times n_2 + i_2) \times w$$

k dimensions $A[n_1] \cdots [n_k]$ (row-major, 0-based):

$$base + ((\cdots((i_1 n_2 + i_2)n_3 + i_3)\cdots)n_k + i_k) \times w$$

Equivalently, using the *widths of sub-arrays* $w_1 = n_2 \cdots n_k \cdot w,\ w_2 = n_3 \cdots n_k \cdot w, \ldots,\ w_k = w$:

$$base + i_1 \times w_1 + i_2 \times w_2 + \cdots + i_k \times w_k.$$

This form is the one used in the translation scheme.




Figure 27: Row-major layout of `int a[2][3]` ($w = 4$). Offset of $a[i][j]$ is $i \times 12 + j \times 4$.

5.4 Translation of array references

Grammar (with nonterminal L for an array location):

$$S \to \mathbf{id} = E \ ; \ \mid \ L = E \ ;$$
$$E \to E_1 + E_2 \ \mid \ \mathbf{id} \ \mid \ L$$
$$L \to \mathbf{id}\,[\,E\,] \ \mid \ L_1\,[\,E\,]$$

Attributes of L: $L.array$ (symbol-table entry of the array), $L.type$ (type of the *sub-array* generated by L), $L.addr$ (a temporary accumulating the *offset*).

Worked example: $c + a[i][j]$ where `a` is `int a[2][3]`

Types: $a.type = array(2,\ array(3,\ integer))$, so the width of one row is $3 \times 4 = 12$ and of an element is 4.

1. $L \to \mathbf{id}[E]$ with $E = i$: $L.type = array(3, integer)$, width $12 \ \Rightarrow$ `t1 = i * 12`.
2. $L \to L_1[E]$ with $E = j$: $L.type = integer$, width $4 \ \Rightarrow$ `t2 = j * 4`, `t3 = t1 + t2`.
3. $E \to L$: `t4 = a[t3]`.
4. $E \to E_1 + E_2$: `t5 = c + t4`.

```
t1 = i * 12
t2 = j * 4
t3 = t1 + t2
t4 = a[t3]
t5 = c + t4
```

Production	Semantic action
$S \to \mathbf{id} = E\ ;$	$\{\ gen(top.get(\mathbf{id}.lexeme) = E.addr);\ \}$
$S \to L = E\ ;$	$\{\ gen(L.array.base\ [\ L.addr\ ] = E.addr);\ \}$
$E \to E_1 + E_2$	$\{\ E.addr = \mathbf{new}\ Temp();\ gen(E.addr = E_1.addr + E_2.addr);\ \}$
$E \to \mathbf{id}$	$\{\ E.addr = top.get(\mathbf{id}.lexeme);\ \}$
$E \to L$	$\{\ E.addr = \mathbf{new}\ Temp();\ gen(E.addr = L.array.base\ [\ L.addr\ ]);\ \}$
$L \to \mathbf{id}\,[\,E\,]$	$\{\ L.array = top.get(\mathbf{id}.lexeme);\ L.type = L.array.type.elem;$ $L.addr = \mathbf{new}\ Temp();\ gen(L.addr = E.addr * L.type.width);\ \}$
$L \to L_1\,[\,E\,]$	$\{\ L.array = L_1.array;\ L.type = L_1.type.elem;$ $t = \mathbf{new}\ Temp();\ L.addr = \mathbf{new}\ Temp();$ $gen(t = E.addr * L.type.width);\ gen(L.addr = L_1.addr + t);\ \}$

Table 8: Semantic actions for array references (Dragon Book Fig. 6.22).

And for the assignment $x = a[i][j]$ the code is the first four instructions followed by `x = t4`.

Worked example: a three-dimensional array and a store

Let `int a[2][3][4]` (so $w = 4$). The widths of the sub-arrays are $w_3 = 4$ (one element), $w_2 = 4 \cdot 4 = 16$ (one innermost row of 4 elements) and $w_1 = 3 \cdot 4 \cdot 4 = 48$ (one 3×4 plane); the whole array occupies $2 \cdot 48 = 96$ bytes. The statement `x = a[i][j][k];` becomes

```
t1 = i * 48
t2 = j * 16
t3 = t1 + t2
t4 = k * 4
t5 = t3 + t4
t6 = a[t5]
x  = t6
```

Each extra subscript adds exactly two instructions (a multiplication and an addition), as in the rule for $L \to L_1[E]$. For a *store*, `a[i][j] = x;` with `int a[2][3]` uses the rule $S \to L = E\,;$, which ends with an indexed assignment instead of an indexed load:

```
t1 = i * 12
t2 = j * 4
t3 = t1 + t2
a[t3] = x
```

Index versus offset

In `t4 = a[t3]` the value in `t3` is a *byte offset* from the base of `a`, not an element index as in the C source. That is why every subscript is multiplied by the width of the thing it selects. (In the book's three-address code, `x = y[i]` means "the value at the memory location i units beyond y".)

6 Type Checking and Type Conversion

Type expressions represent the type of a language construct: basic types (`int`, `float`, `char`, `boolean`, `void`), $array(n, T)$, *record*, pointer, and function types $s \to t$.

Type checking comes in two forms: **synthesis** (the type of an expression is built from the types of its sub-expressions, e.g., for $E_1 + E_2$) and **inference** (the type of a construct is determined from the way it is used).

Example: three static checks

Static checking attaches a rule to a production and reports an error when the rule fails. With `int a[10]; int n; float f;`:

Source	Rule that fails	Message
`x = a[2.5];`	in $L \to \mathbf{id}[E]$ the index E must have type `int`	array index must be an integer
`y = a + n;`	$+$ is defined for numeric types only; a has type $\mathit{array}(10, \texttt{int})$	operand of $+$ is not a number
`if (f) x = 1;`	the condition in `if (`E`)` must have type `boolean`	`float` used as condition (C would accept it and test $f \neq 0$)

Each check is just one more semantic rule: it computes nothing, it only compares attribute values and calls an error routine, which is another example of a rule with a side effect.

6.1 Type conversion (coercion)

For $E \to E_1 + E_2$ where operand types may differ (e.g., `int` and `float`), the compiler inserts conversions. Conversions that cannot lose information in principle (*widening*) may be inserted by the compiler automatically (*coercion*); the reverse direction (*narrowing*) needs an explicit cast written by the programmer. Figure 28 shows the usual hierarchy. In these notes we use only `int` < `float`.




Figure 28: Widening (solid) and narrowing (dashed) conversions between primitive types, Java-style. Converting `long` to `float` is allowed implicitly although a few low-order digits may be rounded.

For $E \to E_1 + E_2$ (and likewise for $-$, $*$, $/$) the result has the *wider* of the two operand types,

$$E.\mathit{type} = \max(E_1.\mathit{type},\ E_2.\mathit{type}),$$

and the helper $\mathit{widen}(a, t, w)$ converts address a of type t to type w:

```
Addr widen(Addr a, Type t, Type w) {
    if (t == w) return a;
    else if (t == integer && w == float) {
        temp = new Temp();
        gen(temp '=' '(float)' a);
        return temp;
    }
```

```
    else error;
}
```

Production	Semantic action
$E \to E_1 + E_2$	{ $E.type = \max(E_1.type, E_2.type)$; $a_1 = widen(E_1.addr, E_1.type, E.type)$; $a_2 = widen(E_2.addr, E_2.type, E.type)$; $E.addr =$ **new** $Temp()$; $gen(E.addr = a_1 + a_2)$; }

Example

Let `x` be `float`, and `i, j` be `int`. For $x = i * j + x$ we get:

```
t1 = i * j          // int * int -> int
t2 = (float) t1     // widen to float
t3 = t2 + x         // float + float
x  = t3
```

Worked example: widening on *both* sides, $x = i + j * x$

Let `x` be `float` and `i, j` be `int`. The code is emitted at reductions, so the product $j * x$ (reduced first) comes before the sum:

1. $E \to E_1 * E_2$ with $E_1 = j$ (`int`) and $E_2 = x$ (`float`): $E.type =$ `float`; $widen(j)$ emits `t1 = (float) j`; $widen(x)$ does nothing; then `t2 = t1 * x`.
2. $E \to E_1 + E_2$ with $E_1 = i$ (`int`) and E_2 of type `float`: $widen(i)$ emits `t3 = (float) i`; then `t4 = t3 + t2`.
3. $S \to$ **id** $= E$; emits `x = t4`.

```
t1 = (float) j
t2 = t1 * x
t3 = (float) i
t4 = t3 + t2
x  = t4
```

Note that i, which is written first, is converted *after* j: the order of the instructions follows the order of the reductions, not the order of the source text.

7 Control Flow: Boolean Expressions and Statements

In programming languages, boolean expressions are used for two purposes:

1. to **compute logical values** (e.g., `flag = a < b && c;`), and
2. as **conditional expressions** in `if`, `while`, and `for` (flow-of-control).

We use the grammar

$$B \to B \,\|\, B \;\mid\; B \;\&\&\; B \;\mid\; !B \;\mid\; (B) \;\mid\; E \; rel \; E \;\mid\; \textbf{true} \;\mid\; \textbf{false}$$

with $\|$ standing for the C operator `||`; `||` and `&&` are left-associative, `||` has lower precedence than `&&`, which is lower than `!`.

7.1 Start here: a tiny example with labels

The story. A computer follows the instructions of a program one after the other, like a child walking down a corridor with many numbered doors. A `goto` instruction says: "do not go on to the next door; run to the door with this name instead". An `if` test says: "if the answer is yes, run to door T; if no, run to door F". The names of the doors are called **labels**.

The compiler has a problem: before it can write "run to door T", it must *know the name* of door T. The scheme of this section solves it like a school with a head teacher: **the boss decides the door names first and tells each worker**, and only then does the worker write its instructions.

Word	Meaning in plain language
label	The name of a door (an instruction), written $L_1, L_2, \ldots$
newlabel()	A ticket machine: each press prints a brand-new, unused door name.
label(L)	Fix the name tag L on the *next* instruction that is written, so that jumps to L arrive there.
$S.next$	A sticky note on the statement S that says: "the door *right after you* is called ...".
$B.true$	A sticky note on the test B: "if you are **true**, run to door ...".
$B.false$	A sticky note on the test B: "if you are **false**, run to door ...".
code	The list of instructions that a piece of the program turns into.

These three sticky notes ($S.next$, $B.true$, $B.false$) are the *key attributes* of the whole section. They are **inherited**: they are written by the *parent* and read by the child. That is exactly the boss telling the worker where the exits are, *before* the worker starts.

Example 1: `if (a < b) x = 1;` and then the program ends

The rules used (they are given in full in the next subsections) are

$$
\begin{aligned}
&P \to S: && S.next = newlabel(), \qquad P.code = S.code \parallel label(S.next) \\
&S \to \textbf{if}\ (B)\ S_1: && B.true = newlabel(), \quad B.false = S_1.next = S.next, \\
& && S.code = B.code \parallel label(B.true) \parallel S_1.code \\
&B \to E_1\ rel\ E_2: && B.code = \text{“}\texttt{if}\ E_1\ rel\ E_2\ \texttt{goto}\ B.true\text{”} \parallel \text{“}\texttt{goto}\ B.false\text{”}
\end{aligned}
$$

Order of events (top-down for the sticky notes, then bottom-up for the code):

1. $P \to S$ presses the ticket machine: L_1. It sticks $S.next = L_1$ on S: "after you comes door L_1, the end of the program".
2. $S \to \textbf{if}\ (B)\ S_1$ presses the machine again: L_2. It sticks $B.true = L_2$ on B, and copies its own note L_1 onto B as $B.false$ and onto S_1 as $S_1.next$.
3. B now *knows* both door names and writes its two jumps. S_1 (the assignment) writes `x = 1`.
4. S puts its pieces together in order, inserting the name tag L_2 in front of S_1's code. Finally P appends the name tag L_1.




Figure 29: The sticky notes of Example 1. Blue dashed arrows: the door names travel *down*, from the parent to its children, before any instruction is written (inherited attributes). Red arrows: the instructions travel *up* and are put together in order (synthesized attribute *code*).

The generated code, instruction by instruction. The right column tells you which sticky note each instruction needed, who had written it, and when:

Instruction	**Key attributes: what they hold, who set them, when they are used**
`if a < b goto L2`	$B.true = L_2$. Set by the parent rule $S \to \textbf{if}\,(B)\,S_1$, *before* B wrote any code. Used here: "if the test is true, run to L_2".
`goto L1`	$B.false = L_1$. This is a *copy* of $S.next = L_1$, which came from $P \to S$. Used here: "if the test is false, run to L_1, behind the whole **if**".
`L2: x = 1`	The name tag $L_2 = B.true$ is stuck on this instruction by the rule of S, with $label(B.true)$. So the true jump above arrives exactly at the beginning of the then part. The statement S_1 was told $S_1.next = L_1$, but an assignment never jumps, so it does not use it.
`L1:`	The name tag $L_1 = S.next$ is stuck on the instruction that follows by $P \to S$, with $label(S.next)$. Nothing follows here (the program ends), but the tag must exist, because `goto L1` refers to it.

What to remember: a door name is *invented once* (by *newlabel*()), then *handed down* by copying, and finally *fixed on exactly one instruction* by *label*(...). Every jump that mentions the name arrives at that instruction.

Example 2: `if (a < b) x = 1; else x = 2;` and then the program ends

The rule is $S \to \textbf{if}\,(B)\,S_1\ \textbf{else}\ S_2$. Two new door names are needed this time, one for each branch: $B.true = newlabel() = L_2$ and $B.false = newlabel() = L_3$. Both statements are told $S_1.next = S_2.next = S.next = L_1$.

Instruction	Key attributes: what they hold, who set them, when they are used
`if a < b goto L2`	$B.true = L_2$, new, set by the **if-else** rule.
`goto L3`	$B.false = L_3$, also new now: false must go to the **else** part, not behind the statement.
`L2: x = 1`	Tag L_2 is fixed here by $label(B.true)$: the beginning of the then part.
`goto L1`	*Generated by the rule itself:* after the then part we must run *over* the else part. The destination is $S.next = L_1$, the note that came from $P \to S$.
`L3: x = 2`	Tag L_3 is fixed here by $label(B.false)$: the beginning of the else part.
`L1:`	Tag L_1 is fixed by $P \to S$, behind everything.

What to notice: compare with Example 1. There, $B.false$ was a *copy* of $S.next$. Here it is a *new* name, because the false branch now has work to do (the else part). The `goto L1` in the middle is the reason $S.next$ has to be known to S itself.

Example 3: a loop, `while (a < b) x = x + 1;` and then the program ends

The rule is $S \to \textbf{while}\,(B)\,S_1$. It uses a *local* name *begin* (not an attribute): $begin = newlabel() = L_2$ marks the top of the loop. Also $B.true = newlabel() = L_3$, $B.false = S.next = L_1$, and $S_1.next = begin = L_2$: "when the body is finished, you must run back to the top".

Instruction	Key attributes: what they hold, who set them, when they are used
`L2: if a < b goto L3`	Tag $L_2 = begin$ is fixed here by $label(begin)$: the *top of the loop*, where we come back to. $B.true = L_3$ is the body.
`goto L1`	$B.false = L_1$ is a copy of $S.next$: the way out of the loop.
`L3: x = x + 1`	Tag $L_3 = B.true$, the start of the body. The body was told $S_1.next = L_2$.
`goto L2`	*Generated by the rule itself* with $gen($`goto` $begin)$: after the body, go back to the test.
`L1:`	Tag $L_1 = S.next$, fixed by $P \to S$. This is where the loop exits.

What to notice: the loop needs one more name than the **if**: *begin*, the door to which the body jumps *back*. The sticky note $S_1.next = begin$ is how the body learns it.

The key idea, and what comes later

In this scheme **every jump target is a name that someone has already invented and handed down** through the inherited attributes $S.next$, $B.true$ and $B.false$. The code is built bottom-up, but the *names* are passed *top-down*. That is perfect for a top-down parser. A bottom-up parser works in the opposite direction (it finishes the children first), and for it the notes use **backpatching** (Section 8): leave the jump blank, and fill the blank when the target becomes known. Section 8 starts with similar small examples (an **if**, an **if-else** and a **while**), so you can compare the two schemes side by side.

7.2 Short-circuit (jumping) code

In **short-circuit code**, the operators `&&`, `||` and `!` do not appear in the generated code. Instead a boolean expression is translated into jumps to labels: control *reaches* one position if the expression is true and another if it is false. In

```
if (x < 100 || x > 200 && x != y) x = 0;
```

the first test `x<100` being true makes the other tests unnecessary. The generated code is:

```
        if x < 100 goto L2
        goto L3
L3:     if x > 200 goto L4
        goto L1
L4:     if x != y goto L2
        goto L1
L2:     x = 0
L1:     ...
```

(Compare with *value* code, which would compute 0/1 into temporaries and use `&&` and `||` at run time.)




Figure 30: Control-flow view of `if (x < 100 || x > 200 && x != y) x = 0;`. Each test jumps on its own outcome; no boolean value is ever computed. A *true* arrow out of $x < 100$ skips the other tests.

Short-circuit evaluation is a semantic guarantee, not only an optimisation

In `if (p != NULL && p->x > 0) ...` the second operand must *not* be evaluated when p is null, otherwise the program dereferences a null pointer. Jumping code gives this behaviour for free: the test of `p->x` is only reached through the *true* exit of `p != NULL`. Value code that first computes both operands would crash.

Boolean values in assignments. A boolean expression is also used to compute a *value*, e.g. `flag = a < b && c;`. The jumping code is reused, and the two exits set the variable:

```
        if a < b goto L1
        goto L3
L1:     if c goto L2
        goto L3
L2:     flag = true
        goto L4
L3:     flag = false
L4:
```

7.3 Flow-of-control statements: SDD with inherited labels

Grammar for statements:

$$P \to S, \qquad S \to \textbf{assign} \mid \textbf{if}\,(B)\,S_1 \mid \textbf{if}\,(B)\,S_1\,\textbf{else}\,S_2 \mid \textbf{while}\,(B)\,S_1 \mid S_1\,S_2$$


Inherited attributes (labels):

- $B.true$: the label to jump to if B is true; $B.false$: the label if B is false.
- $S.next$: the label of the instruction that follows the code for S.


Synthesized attribute: $S.code$, $B.code$. The function $newlabel()$ creates a fresh label $L_1, L_2, \ldots$, and $\textbf{label}(L)$ attaches label L to the next instruction.

Production	**Semantic rules**
$P \to S$	$S.next = newlabel(); \quad P.code = S.code \,\|\|\, \textbf{label}(S.next)$
$S \to \textbf{assign}$	$S.code = \textbf{assign}.code$
$S \to \textbf{if}\,(B)\,S_1$	$B.true = newlabel(); \quad B.false = S_1.next = S.next$ $S.code = B.code \,\|\|\, \textbf{label}(B.true) \,\|\|\, S_1.code$
$S \to \textbf{if}\,(B)\,S_1\,\textbf{else}\,S_2$	$B.true = newlabel(); \quad B.false = newlabel();$ $S_1.next = S_2.next = S.next$ $S.code = B.code \,\|\|\, \textbf{label}(B.true) \,\|\|\, S_1.code \,\|\|\, \textbf{gen}(\textbf{goto}\ S.next) \,\|\|$ $\textbf{label}(B.false) \,\|\|\, S_2.code$
$S \to \textbf{while}\,(B)\,S_1$	$begin = newlabel(); \quad B.true = newlabel(); \quad B.false = S.next;$ $S_1.next = begin$ $S.code = \textbf{label}(begin) \,\|\, B.code \,\|\, \textbf{label}(B.true) \,\|\, S_1.code \,\|\, \textbf{gen}(\textbf{goto}\ begin)$
$S \to S_1\,S_2$	$S_1.next = newlabel(); \quad S_2.next = S.next$ $S.code = S_1.code \,\|\|\, \textbf{label}(S_1.next) \,\|\|\, S_2.code$

Table 9: SDD for flow-of-control statements (Dragon Book Fig. 6.36). $S.next$, $B.true$, and $B.false$ are inherited.



(a) **if** (B) S_1 **else** S_2



(b) **while** (B) S_1

Figure 31: Layout of the generated code. $B.code$ contains jumps to $B.true$ or $B.false$; it "falls through" to neither, so the labels can be placed anywhere.

Production	Semantic rules
$B \to B_1 \,\|\|\, B_2$	$B_1.true = B.true$; $B_1.false = newlabel()$; $B_2.true = B.true$; $B_2.false = B.false$ $B.code = B_1.code \,\|\|\, \textbf{label}(B_1.false) \,\|\|\, B_2.code$
$B \to B_1 \;\&\&\; B_2$	$B_1.true = newlabel()$; $B_1.false = B.false$; $B_2.true = B.true$; $B_2.false = B.false$ $B.code = B_1.code \,\|\|\, \textbf{label}(B_1.true) \,\|\|\, B_2.code$
$B \to !\, B_1$	$B_1.true = B.false$; $B_1.false = B.true$; $B.code = B_1.code$
$B \to E_1\ rel\ E_2$	$B.code = E_1.code \,\|\|\, E_2.code \,\|\|$ $\textbf{gen}(\textbf{if}\ E_1.addr\ rel.op\ E_2.addr\ \textbf{goto}\ B.true) \,\|\|\, \textbf{gen}(\textbf{goto}\ B.false)$
$B \to \textbf{true}$	$B.code = \textbf{gen}(\textbf{goto}\ B.true)$
$B \to \textbf{false}$	$B.code = \textbf{gen}(\textbf{goto}\ B.false)$

Table 10: SDD to generate jumping code for boolean expressions (Dragon Book Fig. 6.37).

7.4 SDD for boolean expressions (jumping code)

How to remember the `||` and `&&` rules

- $B_1 \,||\, B_2$: if B_1 is true we are done (go to $B.true$); if false, *test* B_2, so $B_1.false$ is a new label placed in front of $B_2.code$.
- $B_1 \;\&\&\; B_2$: if B_1 is false we are done (go to $B.false$); if true, *test* B_2, so $B_1.true$ is a new label in front of $B_2.code$.
- $!\, B_1$: simply *swap* the true and false labels.

Worked example: `if (x < 100 || x > 200 && x != y) x = 0;`

Step 1. $P \to S$: $S.next = L_1$.
Step 2. $S \to \textbf{if}(B)S_1$: $B.true = L_2$, $B.false = L_1$, $S_1.next = L_1$.
Step 3. $B = B_1 \,||\, B_2$, where $B_1 \equiv x < 100$ and $B_2 \equiv (x > 200 \;\&\&\; x \neq y)$:

- B_1: true $= L_2$, false $= L_3$ (new).
- B_2: true $= L_2$, false $= L_1$.

Step 4. $B_2 = B_3 \;\&\&\; B_4$ with $B_3 \equiv x > 200$, $B_4 \equiv x \neq y$:

- B_3: true $= L_4$ (new), false $= L_1$.
- B_4: true $= L_2$, false $= L_1$.

Step 5. Assemble: $B_1.code \,||\, L_3$: $B_2.code$, with $B_2.code = B_3.code \,||\, L_4$: $B_4.code$, followed by L_2: $S_1.code$ and finally L_1:

```
        if x < 100 goto L2
        goto L3
L3:     if x > 200 goto L4
        goto L1
L4:     if x != y goto L2
        goto L1
L2:     x = 0
L1:
```

Observe the redundant jumps (`goto L3` immediately followed by `L3:`) – a later optimisation phase or the *backpatching* method with fall-through can remove them.

Worked example: `while (a < b) { if (c < d) x = y + z; }`

```
L1:     if a < b goto L2        // begin / B.code
        goto L0                 // B.false = S.next
L2:     if c < d goto L3        // inner if: B.true = L3
        goto L1                 // inner S.next = begin = L1
L3:     t1 = y + z
        x = t1
        goto L1                 // goto begin
L0:                             // S.next
```

7.5 Avoiding redundant gotos (fall-through)

Instead of

```
        if x > 200 goto L4
        goto L1
L4:     ...
```

we can generate the shorter form `ifFalse x > 200 goto L1` followed by the code at `L4`: if the true label is the next instruction (denote it by the special label *fall*), only one jump is needed. The rule for $B \to E_1\ rel\ E_2$ becomes: let $test = E_1.addr\ rel.op\ E_2.addr$:

Condition	**Generated jump code**
$B.true \neq fall$ and $B.false \neq fall$	`if test goto B.true  goto B.false`
$B.true \neq fall$ and $B.false = fall$	`if test goto B.true`
$B.true = fall$ and $B.false \neq fall$	`ifFalse test goto B.false`
both $= fall$	(no instruction)

The statement and operator rules change too. Let *fall* mean "the next instruction in sequence". The new rules (Dragon Book Section 6.6.5) are:

Production	**Semantic rules**
$S \to \textbf{if}\,(B)\,S_1$	$B.true = fall$; $B.false = S_1.next = S.next$; $S.code = B.code \parallel S_1.code$
$B \to B_1 \parallel B_2$	$B_1.true = (B.true$ if $\neq fall$, else a new label); $B_1.false = fall$; $B_2.true = B.true$; $B_2.false = B.false$
	$B.code = B_1.code \parallel B_2.code$ if $B.true \neq fall$; otherwise $B_1.code \parallel B_2.code \parallel \textbf{label}(B_1.true)$
$B \to B_1\ \&\&\ B_2$	$B_1.true = fall$; $B_1.false = (B.false$ if $\neq fall$, else a new label); $B_2.true = B.true$; $B_2.false = B.false$
	$B.code = B_1.code \parallel B_2.code$ if $B.false \neq fall$; otherwise $B_1.code \parallel B_2.code \parallel \textbf{label}(B_1.false)$

The extra label in the "otherwise" case is needed because when B_1 is decisive the control must jump *past* B_2, to the end of $B.code$.

Worked example: the same statement with fall-through

For `if (x < 100 || x > 200 && x != y) x = 0;` start with $B.true = fall$ and $B.false = L_1$. For $B_1 \,||\, B_2$: since $B.true = fall$, $B_1.true = L_2$ (new) and $B_1.false = fall$; B_2 inherits

$B.true = fall$ and $B.false = L_1$. For $B_2 = B_3 \,\&\&\, B_4$: $B_3.true = B_4.true = fall$ and $B_3.false = B_4.false = L_1$. The relational rule then gives

```
        if x < 100 goto L2
        ifFalse x > 200 goto L1
        ifFalse x != y goto L1
L2:     x = 0
L1:
```

Only 4 instructions (3 tests and the assignment) instead of 7, and no useless `goto`s.

8 Backpatching

8.1 The problem and the idea

The problem: a jump to a place that does not exist yet. Look at the code for `if (a < b) x = 1;` followed by some later statement. The compiler writes the three-address instructions one after the other and numbers them:

```
100:  if a < b goto ?   true: go to the then part (instruction 102)
101:  goto ?            false: skip the then part; but where does the next statement start?
102:  x = 1
```

When instruction 101 is written, the compiler has not yet seen the statement after the **if**, so it cannot know the number after which to jump. A jump to an instruction that has not been generated yet is a **forward jump**. Every **if**, **while** and boolean expression with && or || produces such jumps, so the compiler needs a trick.

Two ways out. The earlier scheme (the flow-of-control SDD with inherited labels, earlier in this chapter) *invents a label name in advance* and passes it down to the code that needs it: that needs inherited attributes, which are awkward for a bottom-up parser. A second solution is to translate twice, with the first pass only counting instructions. **Backpatching** does it in one pass, with synthesized attributes only.

The idea of backpatching in three sentences

1. When a jump is generated and its target is not known, write the jump **with a blank target** (`goto _`).
2. Write down the **number of that instruction** in a **list**: all jumps that must go to the same place share one list.
3. As soon as the target becomes known, go through the list and **patch** (fill in) the blank of every instruction on it.

Analogy: you are writing a book and, in many places, you write "see page _" because the index page is not finished. You keep a list of the places that need that page number. When the index gets its page number, you walk through the list once and fill in every blank.

Words you will meet.

Word	Meaning in plain language
instruction number	The position of a three-address instruction in the output, for example 100, 101, 102. Jumps refer to these numbers.
nextinstr	The number that the *next* instruction to be written will get. It is a counter that grows by 1 with every instruction.
blank target `_`	A jump written as `goto _`: the destination will be filled in later.
list of jumps	A set of instruction numbers, such as $\{100, 102\}$, whose jumps share one destination.
$B.truelist$	The jumps out of the code of the boolean expression B that must go to the place where B *is true*.
$B.falselist$	The same for B *is false*.
$S.nextlist$	The jumps out of the statement S that must go to the instruction that comes *right after* S.
marker M	An empty production $M \to \varepsilon$ whose only job is to take a *bookmark*: $M.instr = nextinstr$, the number of the next instruction at that moment. It stands exactly where we need to know an address.
marker N	An empty production $N \to \varepsilon$ that writes one `goto _` (used to jump over the **else** part) and keeps its number in $N.nextlist$.

Backpatching primitives

- *makelist*(i): create a new list containing only i, an index into the instruction array; return a pointer to it. *Example:* *makelist*$(100) = \{100\}$.
- *merge*(p_1, p_2): concatenate the lists pointed to by p_1 and p_2; return the merged list. *Example:* *merge*$(\{100\}, \{102\}) = \{100, 102\}$.
- *backpatch*(p, i): insert i as the target label for each instruction on the list p. *Example:* *backpatch*$(\{100, 102\}, 104)$ turns `100: if a<b goto _` into `100: if a<b goto 104` and does the same for 102.
- *nextinstr*: global variable containing the index of the next instruction to be generated. *emit*$(\dots)$ appends an instruction and increments it.

Why only synthesized attributes? The translation rules run when the parser has *finished* a piece of the input (a bottom-up, post-order evaluation, as for every S-attributed SDD). At that moment the lists $B.truelist$, $B.falselist$, $S.nextlist$ are already complete, and they are simply handed upward to the parent. The destination is never needed in advance, so nothing has to be passed *down*.

8.2 Start here: four small examples by hand

The formal rules follow in the next two subsections. First we see what they do on four tiny programs. In every example the relational test is between simple names, so a test `a < b` needs exactly *two* instructions: `if a < b goto _` (the true jump) and `goto _` (the false jump). The first instruction of the whole program has number 100.

Example 1: `if (a < b) x = 1;` followed by `y = 2;`

The rules used (given in full later): $S \to \textbf{if}\ (B)\ M\ S_1$ with $backpatch(B.truelist,\ M.instr)$ and $S.nextlist = merge(B.falselist,\ S_1.nextlist)$, and $L \to L_1\ M\ S$ with $backpatch(L_1.nextlist,\ M.instr)$.

1. **The condition B is translated.** Write `100: if a < b goto _` and `101: goto _`. $B.truelist = \{100\}$, $B.falselist = \{101\}$. Both targets are blank.
2. **The marker** M comes next and takes a bookmark: $M.instr = 102$, because 102 is the number the next instruction will get. This is where the *then* part starts. $backpatch(\{100\}, 102)$ fills the true jump: `100: if a < b goto 102`.
3. **The statement** S_1 is written: `102: x = 1`. An assignment never jumps, so $S_1.nextlist =$ **null** (empty). The **if** statement concludes: $S.nextlist = merge(\{101\}, \textbf{null}) = \{101\}$. In words: "instruction 101 must go to whatever comes after the **if**". The blank stays.
4. **The next statement starts.** The marker M of the statement list takes a bookmark: $M.instr = 103$. $backpatch(\{101\}, 103)$ fills the last blank: `101: goto 103`. Then `103: y = 2` is written.

The code as it grows (red `_` is a blank, green is a value that was just filled in):


	after step 1	after step 3	after step 4 (final)
100	`if a<b goto _`	`if a<b goto 102`	`if a<b goto 102`
101	`goto _`	`goto _`	`goto 103`
102		`x = 1`	`x = 1`
103			`y = 2`

What to remember: the *true* jump was patched *immediately* (the then part follows right behind it), and the *false* jump had to wait on a list until the next statement was known.

Example 2: why lists? `if (a < b || c < d) x = 1;`

Now there are *two* tests, and *both* jump to the then part when they succeed. The rule is $B \to B_1\ ||\ M\ B_2$: $backpatch(B_1.falselist,\ M.instr)$, $B.truelist = merge(B_1.truelist,\ B_2.truelist)$, $B.falselist = B_2.falselist$. In words: "if the first test is false, try the second test; the expression is true if either test is true".

1. B_1 is `a < b`: `100: if a<b goto _`, `101: goto _`. $B_1.truelist = \{100\}$, $B_1.falselist = \{101\}$.
2. **The marker** M takes a bookmark: $M.instr = 102$, the start of the second test. $backpatch(B_1.falselist, 102)$ fills `101: goto 102`: "if $a < b$ is false, go and test $c < d$".
3. B_2 is `c < d`: `102: if c<d goto _`, `103: goto _`. $B_2.truelist = \{102\}$, $B_2.falselist = \{103\}$.
4. B **is finished.** $B.truelist = merge(\{100\}, \{102\}) = \{100, 102\}$ *(two jumps, one destination)*, and $B.falselist = \{103\}$.
5. **The if rule:** the marker for the then part has $M.instr = 104$. $backpatch(\{100, 102\}, 104)$ fills *both* true jumps with one call. Then `104: x = 1` is written, and $S.nextlist = \{103\}$, which is patched later (say, with 105).



1. `101` is patched when M is read: $backpatch(B_1.falselist = \{101\},\ M.instr = 102)$

2. when B is finished the two true lists are joined: $B.truelist = merge(\{100\}, \{102\}) = \{100, 102\}$

Figure 32: The attributes of `a<b || c<d`. The false jump of the first test is patched at once (to the second test); the true jumps of both tests wait together on one list and are patched together later.

The final code, with the destination 105 supplied by whatever follows:

No.	Instruction	Comment
100	`if a<b goto 104`	first test true → then part
101	`goto 102`	first test false → try the second test
102	`if c<d goto 104`	second test true → then part
103	`goto 105`	second test false → skip the then part
104	`x = 1`	the then part

What to remember: a list is needed because *several jumps share one destination*. *merge* collects them, and one *backpatch* call fixes all of them.

Example 3: the marker N and the else part: `if (a < b) x = 1; else x = 2;` followed by `y = 3;`

The rule is $S \to \textbf{if}\,(B)\,M_1\,S_1\,N\,\textbf{else}\,M_2\,S_2$. After the then part is executed we must *jump over* the else part; the marker N writes that jump, and its number goes on a list.

1. B: `100: if a<b goto _`, `101: goto _`. $B.truelist = \{100\}$, $B.falselist = \{101\}$.
2. $M_1.instr = 102$ (start of the then part). $backpatch(B.truelist, 102)$: `100: if a<b goto 102`.
3. S_1 is `102: x = 1`.
4. **The marker** N writes `103: goto _`; $N.nextlist = \{103\}$. This jump is only executed after the then part, and it must go behind the else part: the destination is not known yet.
5. $M_2.instr = 104$ (start of the else part). $backpatch(B.falselist, 104)$: `101: goto 104`. Then S_2 is `104: x = 2`.
6. The statement ends: $S.nextlist = merge(S_1.nextlist,\ N.nextlist,\ S_2.nextlist) = \{103\}$. The next statement starts at 105, so the statement list patches `103: goto 105` (and `y = 3` is 105).

No.	Instruction	Written by	Blank filled by
100	`if a<b goto 102`	B (true jump)	M_1 (start of then part)
101	`goto 104`	B (false jump)	M_2 (start of else part)
102	`x = 1`	S_1	
103	`goto 105`	N (skip the else part)	the next statement (via $S.nextlist$)
104	`x = 2`	S_2	
105	`y = 3`	next statement	

What to remember: the *false* jump is patched at once now (to the else part); the *only* jump that waits for the next statement is the one written by N.

Example 4: a loop, `while (a < b) x = x + 1;` followed by `y = 3;`

The rule is $S \to \textbf{while}\, M_1\, (B)\, M_2\, S_1$. A loop must jump *back* to the test after every pass; that target is known early, so it needs no list. The ordinary exit jump is the one that waits.

1. $M_1.instr = 100$ is a bookmark of the beginning of the test (it will be the target of the jump *back*).
2. B: `100: if a<b goto _`, `101: goto _`. $B.truelist = \{100\}$, $B.falselist = \{101\}$.
3. $M_2.instr = 102$ (start of the body). $backpatch(B.truelist, 102)$: `100: if a<b goto 102`.
4. S_1 (the body) is `102: x = x + 1`. It does not jump: $S_1.nextlist = \textbf{null}$.
5. The rule now closes the loop: $backpatch(S_1.nextlist,\ M_1.instr)$ (nothing to patch here), then $emit($`goto` $M_1.instr)$ writes `103: goto 100`, a jump with a *known* target. Finally $S.nextlist = B.falselist = \{101\}$.
6. The next statement starts at 104, so the statement list patches `101: goto 104`.

No.	Instruction	Written by	Blank filled by
100	`if a<b goto 102`	B (true jump)	M_2 (start of body)
101	`goto 104`	B (false jump)	the next statement (via $S.nextlist$)
102	`x = x + 1`	S_1	
103	`goto 100`	the **while** rule	known at once ($M_1.instr$)
104	`y = 3`	next statement	

What to remember: a jump *back* never needs backpatching, because its target is already behind us. Only *forward* jumps wait on lists.

Cheat sheet: who fills which blank?

- The **true** jump of a test is filled by the marker at the start of the code that must run when it is true (the then part, the loop body, or the second operand of &&).
- The **false** jump is filled either by the marker at the start of the else part, or by the marker at the start of the second operand of ||, or it *waits* on $S.nextlist$.
- The jump written by N always waits on $S.nextlist$.
- $S.nextlist$ is filled by whoever starts the *next statement* (the rule $L \to L_1\, M\, S$) or, at the end of the program, by the code that follows.

8.3 Boolean expressions

The four examples above used the rules informally. Here they are in full, for boolean expressions first and then for statements. Read each rule together with the example it belongs to: $B \to B_1 \,||\, M\, B_2$ is Example 2, the **if** rules are Examples 1 and 3, the **while** rule is Example 4.

Synthesized attributes: $B.truelist$ (instructions that jump when B is true) and $B.falselist$ (when false). A **marker nonterminal** $M \to \varepsilon$ records the index of the next instruction ($M.instr$).

Production	**Semantic action**
$B \to B_1 \,\|\, M\ B_2$	{ $backpatch(B_1.falselist,\ M.instr)$; $B.truelist = merge(B_1.truelist,\ B_2.truelist)$; $B.falselist = B_2.falselist$; }
$B \to B_1\ \&\&\ M\ B_2$	{ $backpatch(B_1.truelist,\ M.instr)$; $B.truelist = B_2.truelist$; $B.falselist = merge(B_1.falselist,\ B_2.falselist)$; }
$B \to !\, B_1$	{ $B.truelist = B_1.falselist$; $B.falselist = B_1.truelist$; }
$B \to (\, B_1\,)$	{ $B.truelist = B_1.truelist$; $B.falselist = B_1.falselist$; }
$B \to E_1\ rel\ E_2$	{ $B.truelist = makelist(nextinstr)$; $B.falselist = makelist(nextinstr+1)$; $emit($`if` $E_1.addr\ rel.op\ E_2.addr$ `goto _`$)$; $emit($`goto _`$)$; }
$B \to$ **true**	{ $B.truelist = makelist(nextinstr)$; $emit($`goto _`$)$; }
$B \to$ **false**	{ $B.falselist = makelist(nextinstr)$; $emit($`goto _`$)$; }
$M \to \varepsilon$	{ $M.instr = nextinstr$; }

Table 11: Translation scheme for boolean expressions using backpatching (Dragon Book Fig. 6.43).


Worked example: $x < 100 \,||\, x > 200\ \&\&\ x \neq y$ **(instructions start at index 100)**

Parse structure: $B \Rightarrow B_1 \,||\, M_1\, B_2$, where $B_2 \Rightarrow B_3\ \&\&\ M_2\, B_4$.

1. $B_1 \equiv x < 100$: emit `100: if x<100 goto _`, `101: goto _`
   $B_1.truelist = \{100\}$, $B_1.falselist = \{101\}$.
2. $M_1.instr = 102$.
3. $B_3 \equiv x > 200$: emit `102: if x>200 goto _`, `103: goto _`
   $B_3.truelist = \{102\}$, $B_3.falselist = \{103\}$.
4. $M_2.instr = 104$.
5. $B_4 \equiv x \neq y$: emit `104: if x!=y goto _`, `105: goto _`
   $B_4.truelist = \{104\}$, $B_4.falselist = \{105\}$.
6. Reduce $B_2 \to B_3\ \&\&\ M_2\, B_4$: $backpatch(\{102\}, 104) \Rightarrow$ instruction 102 becomes `if x>200 goto 104`.
   $B_2.truelist = \{104\}$, $B_2.falselist = merge(\{103\}, \{105\}) = \{103, 105\}$.
7. Reduce $B \to B_1 \,||\, M_1\, B_2$: $backpatch(\{101\}, 102) \Rightarrow$ instruction 101 becomes `goto 102`.
   $B.truelist = merge(\{100\}, \{104\}) = \{100, 104\}$, $B.falselist = \{103, 105\}$.

Result (still incomplete – the lists will be patched by the enclosing statement):

```
100:  if x < 100 goto _       <- on truelist
101:  goto 102
102:  if x > 200 goto 104
103:  goto _                  <- on falselist
104:  if x != y goto _        <- on truelist
105:  goto _                  <- on falselist
```



Blue jumps are already complete. The green and red jumps have a blank target; they are exactly the entries of the two lists that the parent will patch.

8.4 Flow-of-control statements

Synthesized attribute $S.nextlist$: list of jumps to the instruction that follows S. We use markers $M \to \varepsilon$ (records *nextinstr*) and $N \to \varepsilon$ (emits an incomplete `goto` and returns it on a list).

Grammar:

$$S \to \textbf{if}\,(B)\,S_1 \mid \textbf{if}\,(B)\,S_1\,\textbf{else}\,S_2 \mid \textbf{while}\,(B)\,S_1 \mid \{\,L\,\} \mid A\,;$$
$$L \to L_1\,S \mid S$$

Production	**Semantic action**
$S \to \textbf{if}\,(B)\;M\;S_1$	{ *backpatch*($B.truelist$, $M.instr$); $S.nextlist = merge(B.falselist,\ S_1.nextlist)$; }
$S \to$ $\textbf{if}\,(B)\;M_1\;S_1\;N\;\textbf{else}\;M_2\;S_2$	{ *backpatch*($B.truelist$, $M_1.instr$); *backpatch*($B.falselist$, $M_2.instr$); $temp = merge(S_1.nextlist,\ N.nextlist)$; $S.nextlist = merge(temp,\ S_2.nextlist)$; }
$S \to \textbf{while}\;M_1\,(B)\;M_2\;S_1$	{ *backpatch*($S_1.nextlist$, $M_1.instr$); *backpatch*($B.truelist$, $M_2.instr$); $S.nextlist = B.falselist$; *emit*(`goto` $M_1.instr$); }
$S \to \{\;L\;\}$	{ $S.nextlist = L.nextlist$; }
$S \to A\;;$	{ $S.nextlist = \textbf{null}$; }
$L \to L_1\;M\;S$	{ *backpatch*($L_1.nextlist$, $M.instr$); $L.nextlist = S.nextlist$; }
$L \to S$	{ $L.nextlist = S.nextlist$; }
$M \to \varepsilon$	{ $M.instr = nextinstr$; }
$N \to \varepsilon$	{ $N.nextlist = makelist(nextinstr)$; *emit*(`goto _`); }

Table 12: Translation of statements with backpatching (Dragon Book Fig. 6.46).

Why the markers?

M remembers a position: "this is where the code for S_1 (or for the test) begins". *N generates the jump over the else-part* and returns it for later patching. In the **while** rule the loop-back jump uses M_1, which was recorded *before* $B.code$ was generated.

Worked example: `while (a < b) { if (c < d) x = y + z; }`

Assume numbering starts at 100; $M_1.instr = 100$.

1. $B \equiv a < b$: `100: if a<b goto _`, `101: goto _`; $B.truelist = \{100\}$, $B.falselist = \{101\}$.
2. $M_2.instr = 102$.
3. Inner $B' \equiv c < d$: `102: if c<d goto _`, `103: goto _`; $B'.truelist = \{102\}$, $B'.falselist = \{103\}$.
4. $M.instr = 104$; assignment $x = y + z$: `104: t1 = y + z`, `105: x = t1`; $S_1.nextlist =$ **null**.
5. Inner **if**: $backpatch(\{102\}, 104)$; $S.nextlist = merge(\{103\}, \textbf{null}) = \{103\}$.
6. **while**: $backpatch(\{103\}, 100)$ (i.e., `103: goto 100`); $backpatch(\{100\}, 102)$ (i.e., `100: if a<b goto 102`); $S.nextlist = B.falselist = \{101\}$; emit `106: goto 100`.

```
100:  if a < b goto 102
101:  goto _              <- S.nextlist, patched by whoever follows
102:  if c < d goto 104
103:  goto 100
104:  t1 = y + z
105:  x = t1
106:  goto 100
107:  ...                 <- (101 will be backpatched with 107)
```

Worked example: `if (a < b) x = 1; else x = 2;`

```
100:  if a < b goto 102      // B.truelist = {100}, patched to M1 = 102
101:  goto 104               // B.falselist = {101}, patched to M2 = 104
102:  x = 1
103:  goto _                 // N: on S.nextlist
104:  x = 2
105:  ...                    // 103 is patched to 105 by the enclosing construct
```

8.5 Comparison: inherited labels vs. backpatching

	Label-based SDD (Fig. 6.36/6.37)	**Backpatching (Fig. 6.43/6.46)**
Attributes	Inherited labels (*true, false, next*)	Synthesized lists (*truelist, falselist, nextlist*)
Class of SDD	L-attributed	S-attributed (with markers M, N)
Best suited for	Top-down / recursive-descent (or AST traversal)	Bottom-up (LR) parsing, single pass
Code storage	Attribute *.code*, or incremental *gen*	Instruction array; patched later
Labels	Symbolic labels generated eagerly	Instruction indices known late

9 Switch Statements and Procedure Calls

Both constructs fit the pattern of this chapter: an SDD with attributes, and an SDT that is obtained from it. We use the label-based style of Section 7.1: $S.next$ is the name of the door right after S, handed down by the parent, and $newlabel()$, $label(L)$ and $gen(\dots)$ have the meaning given there. The expression rules of Section 5.1 provide $E.addr$ (where the value of E lives) and $E.code$.

9.1 Switch statement

The intuition: a menu with a doorman. Think of a hotel reception. The guest shows a number (the value t of the selector E); the doorman looks at a list (*if the number is 1, go to room 1; if 2, room 2; . . . ; otherwise the default room*) and sends the guest to the right room. Each room is the code of one **case**. We write the rooms first and the doorman's list at the *end*, for two reasons: (1) while we write the rooms we do not yet know how many cases there will be, so the list can only be completed at the end; and (2) all tests stand together in one block, so a good code generator can replace them by a **jump table** (one indexed jump) when the values are dense.




Figure 33: The layout of the code of a **switch**. The rooms (case bodies) come first and the doorman's list (the tests) comes last. Each room ends with `goto next`, which leaves the switch.

The same layout as code:

```
        code to evaluate E into t
        goto test
L1:     code for S1
        goto next
L2:     code for S2
        goto next
 ...
Ld:     code for the default part
        goto next
test:   if t = V1 goto L1
        if t = V2 goto L2
        ...
        goto Ld
next:
```

`case` instructions may replace the tests: `case t V1 L1`, ..., `case t t Ld` (the last entry is the default).

The grammar. To keep it small, the default part is last and the cases come in a list:

$$\begin{aligned} S &\to \textbf{switch}\ (\ E\ )\ \{\ CL\ \textbf{default}\ :\ S_1\ \} \\ CL &\to C\ \ CL_1\ \ \mid\ \ \varepsilon \\ C &\to \textbf{case num}\ :\ S_1 \end{aligned}$$

CL is the list of cases and C is one case. The statements S_1 inside are arbitrary statements, for example assignments or further **if** and **switch** statements.

The attributes: who holds what.

Attribute	Kind	What it holds, and when it is used
$S.next$	inherited	The door after the whole switch; given by the parent. Every case body ends with a jump to it.
$CL.next$, $C.next$	inherited	A copy of $S.next$, passed down to the cases so that each one can write `goto next`.
$CL.t$, $C.t$	inherited	The address of the selector value (a copy of $E.addr$), passed down so that each case can write *its own* test `if t = V goto L`.
$C.code$	synthesized	The code of one case: its label, the body, and `goto next`.
$C.test$	synthesized	The one test instruction of this case: `if t = V goto L`.
$CL.code$, $CL.tests$	synthesized	The bodies of all cases put together, and the tests of all cases put together. Two separate strings.
L, $test$, L_d	local names	Door names invented by $newlabel()$ inside a rule: one for each case, one for the test block, one for the default part.

The SDD for the switch statement

Production	Semantic rules
$S \to \textbf{switch}\,(E)\,\{$ CL **default** : $S_1\,\}$	$test = newlabel();\ \ L_d = newlabel();$ $CL.t = E.addr;\ \ CL.next = S.next;\ \ S_1.next = S.next;$ $S.code = E.code \parallel gen(\texttt{goto}\ test) \parallel CL.code \parallel label(L_d) \parallel S_1.code$ $\parallel gen(\texttt{goto}\ S.next) \parallel label(test) \parallel CL.tests \parallel gen(\texttt{goto}\ L_d)$
$CL \to C\ \ CL_1$	$C.t = CL_1.t = CL.t;\ \ C.next = CL_1.next = CL.next;$ $CL.code = C.code \parallel CL_1.code;\ \ CL.tests = C.test \parallel CL_1.tests$
$CL \to \varepsilon$	$CL.code = \varepsilon;\ \ CL.tests = \varepsilon$
$C \to \textbf{case num}\ :\ S_1$	$L = newlabel();\ \ S_1.next = C.next;$ $C.code = label(L) \parallel S_1.code \parallel gen(\texttt{goto}\ C.next);$ $C.test = gen(\texttt{if}\ C.t = \textbf{num}.val\ \texttt{goto}\ L)$

(Here ε denotes the empty string.) **How to read it.** Two strings grow side by side while the list of cases is traversed: $CL.code$ collects the *bodies*, $CL.tests$ collects the *tests*. The rule for S then places them in two different spots of the final code: bodies first, tests last. Every case builds *both* of its pieces itself, because it knows both its own label L and its own value.

Example 1: the code and the attributes of a switch

```
switch (c) {
    case 1:  x = 10;
    case 2:  x = 20;
    default: x = 0;
}
```

The selector is a variable, so $E.code$ is empty and $E.addr = c$. The parent gave $S.next = L_1$. The SDD (with the label numbers in order of creation: $test = L_2$, case 1 $= L_3$, case 2 $= L_4$, $L_d = L_5$) produces:

Instruction	Key attributes: what they hold, who set them, when they are used
`goto L2`	*gen*(`goto` *test*) in the rule for S. The name $test = L_2$ was invented at the start of the rule, so the jump can be written *before* the test block exists.
`L3: x = 10`	Case 1: $L = L_3$ is *newlabel*() of this case; *label*(L) puts the tag in front of the body $S_1.code$.
`goto L1`	*gen*(`goto` $C.next$). $C.next = L_1$ is a copy of $S.next$, which came down from the parent.
`L4: x = 20`	Case 2, the same way: $L = L_4$.
`goto L1`	The same $C.next = L_1$ again.
`L5: x = 0`	The default part: *label*(L_d) with $L_d = L_5$, then $S_1.code$.
`goto L1`	*gen*(`goto` $S.next$) after the default body.
`L2: if c = 1 goto L3`	*label*(*test*), then the first piece of $CL.tests$: $C.test$ of case 1, with $C.t = c$ (copied down from $E.addr$), value 1 and its own label L_3.
`if c = 2 goto L4`	$C.test$ of case 2: value 2, label L_4.
`goto L5`	*gen*(`goto` L_d): no case matched, go to the default part.
`L1:`	*label*($S.next$) placed by the *parent* rule $P \to S$, not by the switch.

Because the tests are together at the end and the values are dense $(1, 2)$, a code generator may replace them by a jump table: after the range check $1 \le c \le 2$ one indexed jump through the table $[L_3, L_4]$. (Each body ends with `goto L1`: this is the Pascal-style **case**; see the note on **break** below.)

Break and fall-through (C and Java)

The SDD above writes `goto next` after *every* body, which is the behaviour of Pascal-like **case** statements. In C and Java a body *falls through* into the next one unless it ends with **break**. To translate those, write the `goto next` only for a **break** (the rule $S \to$ **break**; is $S.code =$ *gen*(`goto` $S.next$) with the right *next*) and omit the automatic one at the end of $C \to$ **case num** : S_1.

The SDT. The SDD builds two long strings. An SDT can instead print the pieces at once, as in Method B of Section 4.10. The bodies are printed immediately, in order, but the tests cannot, because they must come *after* all the bodies. So we *collect* the pairs (value, label) in a synthesized list attribute $CL.list$ and print the tests at the very end. Here *gen* appends an instruction to the output at once. The actions for inherited attributes stand immediately before the symbol that uses

them (Section 4.8).

$$
\begin{aligned}
S \to \textbf{switch}\ (\ E\ )\ \{\ \{\ & test = newlabel();\ \ gen(\texttt{goto}\ test);\ \ CL.next = S.next\ \}\ CL \\
\textbf{default}\ :\ \{\ & L_d = newlabel();\ \ label(L_d);\ \ S_1.next = S.next\ \}\ S_1 \\
\{\ & gen(\texttt{goto}\ S.next);\ \ label(test); \\
& \quad \textbf{for}\ \text{each}\ (V, L)\ \text{in}\ CL.list: \\
& \quad\quad gen(\texttt{if}\ E.addr = V\ \texttt{goto}\ L); \\
& \quad gen(\texttt{goto}\ L_d)\ \}\ \} \\
CL \to\ \{\ & C.next = CL.next\ \}\ C\ \{\ CL_1.next = CL.next\ \}\ CL_1 \\
\{\ & CL.list = [C.pair]\ +\!\!+\ CL_1.list\ \} \\
CL \to\ & \varepsilon\ \{\ CL.list = [\,]\ \} \\
C \to \textbf{case num}\ :\ \{\ & L = newlabel();\ \ label(L);\ \ S_1.next = C.next\ \}\ S_1 \\
\{\ & gen(\texttt{goto}\ C.next);\ \ C.pair = (\textbf{num}.val,\ L)\ \}
\end{aligned}
$$

The expression E prints its own code before the first action, so the instructions come out in the right order: E's code, `goto test`, the bodies, the default body, the tests.

Example 2: how the list of pairs is built

For the switch of Example 1, parsing proceeds from left to right. Read the right column to see the list grow.

Moment	Printed	List attributes
after `switch (c) {`	`goto L2`	
case 1 parsed	`L3: x = 10, goto L1`	$C.pair = (1, L_3)$
case 2 parsed	`L4: x = 20, goto L1`	$C.pair = (2, L_4)$
$CL \to \varepsilon$		$CL.list = [\,]$
back in CL (case 2)		$CL.list = [(2, L_4)]$
back in CL (case 1)		$CL.list = [(1, L_3), (2, L_4)]$
`default:` body	`L5: x = 0, goto L1`	
the closing `}`	`L2:, if c = 1 goto L3, if c = 2 goto L4, goto L5`	the list is read once, from the front

The pairs are *prepended* one level at a time, so the final list has the cases in the order of the program, and the tests come out in that order.

One global queue breaks nested switches

A common textbook description keeps the pairs in *one queue*, and "at the end of the switch" reads it. With a **switch** inside a case of another **switch**, the inner cases would be appended to the *outer* queue (or the queue would be reset), and the tests of the outer switch would jump to labels of the inner one. Making the list a *synthesized attribute* $CL.list$ gives every switch its own list for free: the list of the inner switch is finished and used inside the inner S and never reaches the outer one.

9.2 Procedure calls

The intuition: ordering a pizza by phone. First you decide every topping, then you read the toppings out one by one, and only then you say "please deliver". A call is the same: the compiler

must (1) work out the value of every argument, (2) hand the values over to the callee, and (3) transfer control. Three-address code has one instruction for each of these: the arguments are first computed into temporaries, then each is announced with `param`, and then one `call` jumps to the procedure.

Instruction	Meaning
`param x`	Put the value of `x` where the callee will find its next parameter (for example, push it on the stack).
`call p, n`	Call the procedure `p`, which has `n` parameters (the last n `param` instructions). Control returns to the next instruction.
`y = call p, n`	The same, for a procedure that returns a value; the value is stored into `y`.
`return y`	In the callee: give the value `y` back to the caller (`return` alone if there is no value).

The grammar. A call may be a statement (`call p(a, b);`) or part of an expression (`y = f(a, b) + 1;`). A is the possibly empty list of arguments and *Elist* is a non-empty one:

$$
\begin{aligned}
S &\to \textbf{call id}\ (\ A\ )\ ;\ \mid\ \textbf{return}\ E\ ;\ \mid\ \textbf{return}\ ; \\
E &\to \textbf{id}\ (\ A\ ) \\
A &\to \mathit{Elist}\ \mid\ \varepsilon \\
\mathit{Elist} &\to \mathit{Elist}_1\ ,\ E\ \mid\ E
\end{aligned}
$$

The attributes. The **key idea** is that the *param* instructions can only be written *after* all arguments have been evaluated. So the addresses of the arguments are collected in a *list* that travels upward, and the *param* instructions are written once, in the rule for the call.

Attribute	Kind	What it holds, and when it is used
$E.addr$	synthesized	The address that holds the value of E: a name, a constant, or a temporary. For a call it is a new temporary that receives the result.
$E.code$	synthesized	The instructions that compute E.
$\mathit{Elist.list}$, $A.list$	synthesized	The *addresses* of the arguments, in order: $[addr_1, addr_2, \dots]$. Used in the rule for the call to write the *param* instructions and to count the arguments.
$\mathit{Elist.code}$, $A.code$	synthesized	The code that evaluates *all* arguments, from left to right.

All the attributes are synthesized, so the SDD is S-attributed and can be evaluated by a post-order traversal of the parse tree. The notation $params(L)$ means $gen(\texttt{param}\ a_1) \parallel \cdots \parallel gen(\texttt{param}\ a_n)$ for the list $L = [a_1, \dots, a_n]$, and $|L|$ is its length.

The SDD for procedure calls

Production	Semantic rules
$S \to \textbf{call id}\,(A)\,;$	$S.code = A.code \,\|\|\, params(A.list) \,\|\|\, gen(\texttt{call id}.addr,\ \|A.list\|)$
$E \to \textbf{id}\,(A)$	$E.addr = \textbf{new}\ Temp();$ $E.code = A.code \,\|\|\, params(A.list) \,\|\|$ $gen(E.addr = \texttt{call id}.addr,\ \|A.list\|)$
$S \to \textbf{return}\ E\,;$	$S.code = E.code \,\|\|\, gen(\texttt{return}\ E.addr)$
$S \to \textbf{return}\,;$	$S.code = gen(\texttt{return})$
$A \to Elist$	$A.list = Elist.list;\ \ A.code = Elist.code$
$A \to \varepsilon$	$A.list = [\,];\ \ A.code = \varepsilon$
$Elist \to Elist_1\ ,\ E$	$Elist.list = Elist_1.list \ +\!\!+\ [E.addr]$ (add at the end); $Elist.code = Elist_1.code \,\|\|\, E.code$
$Elist \to E$	$Elist.list = [E.addr];\ \ Elist.code = E.code$

For the call $E \to \textbf{id}\,(A)$ the order of the pieces is the whole story: first the code that evaluates the arguments ($A.code$), then the `param` instructions, then the `call`.

The SDT. With actions at the right end (a postfix SDT, so also usable by a bottom-up parser) and with *gen* appending instructions at once, the argument code is printed by the expression rules as each argument is parsed, from left to right. Only the list has to be built:

$Elist \to E\ \{\ Elist.list = [E.addr]\ \}$

$Elist \to Elist_1\ ,\ E\ \{\ Elist.list = Elist_1.list \ +\!\!+\ [E.addr]\ \}$

$A \to Elist\ \{\ A.list = Elist.list\ \}\ \mid\ \varepsilon\ \{\ A.list = [\,]\ \}$

$E \to \textbf{id}\ (\ A\ )\ \{\ E.addr = \textbf{new}\ Temp();\ \textbf{for}$ each a in $A.list:\ gen(\texttt{param}\ a);$
$gen(E.addr = \texttt{call id}.addr,\ |A.list|)\ \}$

$S \to \textbf{call id}\ (\ A\ )\ ;\ \{\ \textbf{for}$ each a in $A.list:\ gen(\texttt{param}\ a);\ gen(\texttt{call id}.addr,\ |A.list|)\ \}$

$S \to \textbf{return}\ E\ ;\ \{\ gen(\texttt{return}\ E.addr)\ \}$

Example 1: `y = f(a + b, c * 2);`

Use the assignment rule of Section 5.1, $S \to \textbf{id} = E\,;$, and the rule $E \to \textbf{id}\,(A)$. The right column shows the attributes involved.

Instruction	Key attributes: what they hold, who set them, when they are used
`t1 = a + b`	The first argument. The rule $E \to E_1 + E_2$ makes the temporary t_1: $E.addr = t_1$. Then $Elist \to E$ starts the list: $Elist.list = [t_1]$.
`t2 = c * 2`	The second argument: $E.addr = t_2$. Now $Elist \to Elist_1, E$ appends it: $Elist.list = [t_1, t_2]$.
`param t1`	The rule $E \to \mathbf{id}(A)$ runs *after* all the arguments are evaluated. $A.list = [t_1, t_2]$; *params* writes the first element.
`param t2`	The second element of $A.list$.
`t3 = call f, 2`	The new temporary $E.addr = t_3$ was created by this rule; $2 = \|A.list\|$ is the number of arguments.
`y = t3`	The assignment rule copies $E.addr$: $y = t_3$. (A later optimisation merges the last two instructions into `y = call f, 2`.)

Example 2: a call inside a call, `z = f(a, g(b));`

This example shows why the arguments are kept in a *list* that belongs to each call. The parse tree and the lists are in Figure 34.




Figure 34: Parse tree of `f(a, g(b))` with the list attributes (the tokens `f`, `(`, `,`, `)` are not drawn). Each call has its own $A.list$. The inner call finishes first and emits its `param` and `call`; the outer call can only write its `param` instructions when its own list is complete.

Instruction	Key attributes: what they hold, who set them, when they are used
`param b`	Rule $E \to \mathbf{id}(A)$ of the *inner* call `g(b)`: $A.list = [b]$. This happens while the outer argument list is still being built.
`t1 = call g, 1`	$E.addr = t_1$ is the result of the inner call; $Elist.list$ of the outer call becomes $[a, t_1]$.
`param a`	Rule $E \to \mathbf{id}(A)$ of the *outer* call: its list $[a, t_1]$ is complete only now.
`param t1`	The second element of the outer list: the *value* of `g(b)`.
`t2 = call f, 2`	$E.addr = t_2$ of the outer call; $\lvert A.list \rvert = 2$.
`z = t2`	The assignment rule.

If the `param` instructions of `f` were written as soon as each argument was evaluated, `param a` would come *before* `param b` of the inner call, and the parameters of the two calls would be mixed up on the stack.

Why not one global queue for the arguments?

Many descriptions keep the arguments in a single global queue: $Elist \to E$ starts the queue and $Elist \to Elist_1, E$ appends to it. With the call $f(a,\ g(b))$ the queue of f is $[a]$ when the inner call starts; $Elist \to E$ of $g(b)$ then *resets* the same queue to $[b]$ and destroys the pending a. Keeping the list as a *synthesized attribute* of $Elist$ gives every call its own list, exactly as with the switch statement.

What the callee does with it

The notes stop at the three-address code. At run time, `param` places the values where the procedure expects them (for example on the stack, in an activation record), `call` saves the return address and jumps, and `return` stores the value and jumps back. The count `n` in `call p, n` tells the machine how many of the last `param` instructions belong to this call, which is why nested calls need no extra bookkeeping.

10 A Complete Worked Example

Translating a small program fragment to three-address code

Source fragment (all variables are `int`; `a` is `int a[10]`, so $w = 4$):

```
i = 0;
while (i < n && a[i] != key)
    i = i + 1;
```

Using the label-based SDD. $P \to S$ gives $S.next = L_0$. For the sequence $S_1\, S_2$ (the assignment, then the loop) a label $L_1 = S_1.next$ is placed between them. For the loop, $begin = L_2$, $B.true = L_3$, $B.false = L_0$, and the body's $S_1.next = L_2$. For $B = B_1 \,\&\&\, B_2$ a new label $L_4 = B_1.true$ is created, with $B_1.false = L_0$, $B_2.true = L_3$, $B_2.false = L_0$.

```
        i = 0
L1:
L2:     if i < n goto L4      // B1 (begin of while)
        goto L0               // B1 false -> exit loop
```

```
L4:     t1 = i * 4          // B2: a[i] != key
        t2 = a[t1]
        if t2 != key goto L3
        goto L0             // B false -> exit loop
L3:     t3 = i + 1          // loop body
        i = t3
        goto L2             // back to begin
L0:
```

(L1 and L2 label the same instruction; a later pass can merge them.)
Using backpatching (instruction numbering from 100). Here $M_1.instr = 101$ (start of loop), the marker of && gives 103, and $M_2.instr = 107$ (start of body).

```
100:  i = 0
101:  if i < n goto 103         // patched by the && marker
102:  goto _                    // on B.falselist = S.nextlist
103:  t1 = i * 4
104:  t2 = a[t1]
105:  if t2 != key goto 107     // truelist patched with M2 = 107
106:  goto _                    // on B.falselist = S.nextlist
107:  t3 = i + 1
108:  i = t3
109:  goto 101                  // emitted by the while rule (M1)
110:  ...                       // {102, 106} are backpatched with 110
```

Both of the incomplete jumps at 102 and 106 form *S.nextlist* of the loop; whoever follows the loop will patch them with the index of the next instruction, here 110.

11 Summary and Key Takeaways

- Intermediate code (syntax trees, DAGs, three-address code in quadruple/triple form) decouples front and back ends and enables machine-independent optimisation.
- A CFG gives syntax (is it a legal program, what is its structure) but not meaning. An **SDD** attaches *attributes* to grammar symbols and *semantic rules* to productions; **synthesized** attributes flow upward, **inherited** attributes flow downward or sideways. **S-attributed** $\subset$ **L-attributed**.
- An **SDT** embeds the actions in the grammar and fixes the order of evaluation. S-attributed SDDs $\rightarrow$ *postfix SDTs* (bottom-up). L-attributed SDDs can be implemented during top-down parsing, or, for LR grammars and with marker nonterminals, during bottom-up parsing.
- Expressions: *E.addr* holds the result; *gen* emits TAC; temporaries are created by *newTemp*. Array references use offsets computed from the widths of sub-arrays.
- Boolean expressions are translated into **jumping code**, using the inherited labels *true/false*. Statements use *next*.
- **Removing left recursion** (needed for top-down parsing) works for an SDD and for an SDT alike: rewrite the grammar as $A \rightarrow X\,R$, $R \rightarrow Y\,R \mid \varepsilon$; initialise the inherited $R.i$ in the base case, update it in each repeated group, copy $R.i$ to the synthesized $R.s$ at ε, and copy $R.s$ to the head. For an SDD write these as equations (the result is L-attributed); for an SDT place them as actions, inherited ones just before their symbol and synthesized ones of the head at the end.
- **Switch and procedure calls** follow the same pattern. A switch writes the case bodies first and collects (value, label) pairs in a synthesized list that is turned into the tests at the end; a

call writes the code of all arguments first, then one `param` per entry of a synthesized argument list, then `call p, n`. Each switch and each call has its own list, so nesting works.

- An L-attributed SDT can be executed during **top-down parsing** in three ways: (A) recursive descent in which the inherited attributes are arguments and the synthesized attributes are return values; (B) on-the-fly generation, where the pieces of the code attribute are printed instead of being concatenated (possible when they appear in the same order as in the body); (C) a table-driven LL parser that keeps the attributes in action records and synthesize records on its stack.
- **Backpatching** replaces inherited labels by synthesized lists (*makelist, merge, backpatch*), allowing one-pass bottom-up generation with markers M and N.

Common mistakes (check your own answers against these)

- Reading a *value number* as the value of the expression. It is only the index of a record.
- Forgetting that a DAG shares a node only if *operator and both children* match; $b + a$ and $a + b$ are different unless the operands are put in canonical order.
- Using $B.true$ where $S.next$ is meant: $S.next$ is where control goes *after* a statement, $B.true$ is where it goes *into* the body.
- In a postfix SDT, putting an action in the middle of a body and expecting an LR parser to run it there; use a marker.
- Off-by-one errors in backpatching: $M.instr$ is the index of the *next* instruction to be emitted, not of the last one.
- Treating array subscripts as indices in the three-address code; they are scaled to byte offsets.
- Evaluating both operands of && / || in jumping code, which loses short-circuit behaviour.

12 Practice Problems

Q1. Translate $x = a * (b + c) - d/(b + c)$ into (a) a syntax tree and DAG, (b) three-address code, (c) quadruples and triples (and the order list that turns the triples into indirect triples).

Q2. Using the SDD of Table 6, annotate the parse tree and generate TAC for $a = -(b+c)*(b+c)$.

Q3. For `int a[5][4]` (int width = 4), write the TAC for $x = a[i][j] + a[j][i]$. Give the width used at each dimension.

Q4. Generate jumping code (with inherited labels) for `if (a < b && !(c < d)) x = 1; else x = 2;`

Q5. Show, step by step, the *truelist/falselist* and the final code (with backpatching, starting at 100) for $a < b \,||\, c < d \;\&\&\; e < f$.

Q6. Using backpatching, translate: `while (x < 10) { x = x + 1; if (x == 5) y = 0; }`

Q7. Classify as S-attributed, L-attributed, or neither: (a) $A \to B\,C$ with $C.i = B.s$ and $A.s = C.s$; (b) $A \to B\,C$ with $B.i = C.s$; (c) the SDD of Table 6.

Q8. Write the SDT for $E \to E_1 * E_2 \mid E_1 + E_2 \mid (E) \mid \mathbf{id}$ that prints the *postfix* form, and show its output for `a + b * (c + d)`.

Q9. Build the array of value-number records for $a * b + a * b + c$ and give the three-address code obtained from it.

Q10. Translate `switch (n) { case 1: s = 1; break; case 5: s = 2; break; default: s = 0; }` using the scheme of Section 9.1.

Q11. Let `x` be `float` and `i, j` be `int`. Using the widening rules, write the code for $x = i + j * x$.

Q12. Generate the fall-through jumping code for `if (a < b || c < d) x = 1;` starting with $B.true = fall$.

Q13. Convert to SSA form: `x = 1; if (c) x = x + 1; y = x * 2;`

Q14. Convert to SSA form and draw the blocks: `k = 1; while (k < 10) k = k * 2; return k;`

Q15. For $x = (a + b) - (c * d)$, write the triples, then reorder the two sub-expressions. State what must be edited (a) with triples, (b) with indirect triples.

Q16. For each task say whether a CFG with its parse tree suffices or an SDD is needed: (a) accept `a = b + c;`, (b) reject the use of an undeclared variable, (c) compute the value of `3 * 5 + 4`, (d) check that both operands of + are numbers, (e) produce the parse tree of `a = b + c;`.

Q17. Using the SDD of Section 3.9, build the syntax tree of `a - (b + 3) - c`. Name the nodes $p_1, p_2, \ldots$ in the order in which they are created, and say which reductions create no node.

Q18. Using the postfix SDT of Section 4.4, list the order of the *print* actions for `(a+b)*c - d/e` and give the postfix output. Then give the output of the right-recursive scheme of Section 4 for the same input.

Q19. The SDD $B \to B_1\, D \mid D$, $B.val = 2 \cdot B_1.val + D.val$ (for $B \to B_1 D$), $B.val = D.val$ (for $B \to D$), $D \to \mathbf{0} \mid \mathbf{1}$ with $D.val = 0$ or 1, computes the value of a binary number. Remove the left recursion and give the result (a) as an SDD and (b) as an SDT. Evaluate it for `101`.

Q20. Using the SDD of Section 4.9, annotate the parse tree of `float [4][5][6]` and give the resulting type expression. Then write the recursive-descent procedure `C(b)`.

Q21. For the list-count SDT of Example 3 in Section 4.7, write recursive-descent procedures `L()` and `R(i)` in which the inherited attribute is an argument and the synthesized attribute is a return value.

Q22. Consider $S \to \textbf{if}\,(\,C\,)\,S_1$ with the inherited attributes $S.next$, $C.true$, $C.false$ and $S_1.next$, where the code is $C.code$, then the label $C.true$, then $S_1.code$, and $C.false = S_1.next = S.next$. Write an SDT that generates the code *on the fly* (with *print*) and the corresponding recursive-descent procedure `S(next)`. Why is on-the-fly generation possible here?

Q23. Remove the left recursion from the SDD $T \to T_1 * F$ ($T.val = T_1.val \cdot F.val$), $T \to T_1/F$ ($T.val = T_1.val \,/\, F.val$), $T \to F$ ($T.val = F.val$), $F \to \textbf{num}$ ($F.val = \textbf{num}.lexval$). Give the answer (a) as an SDD and (b) as an SDT, and evaluate `12/3*2`.

Q24. Using the SDT of Section 9.2, translate `z = f(g(x), y + 1);` and give the list $A.list$ of each call.

Q25. Using the switch SDT of Section 9.1 with $S.next = L_1$, give the code and the list $CL.list$ for `switch (n) { case 3: s = 1; case 7: s = 2; default: s = 0; }`. Why can the tests not be printed while the cases are being parsed?

Answers to selected problems

Q1(b). The DAG shares $b + c$, so the TAC is

```
t1 = b + c
t2 = a * t1
t3 = d / t1
t4 = t2 - t3
x  = t4
```

Q3. Row width $= 4 \times 4 = 16$; element width $= 4$.

```
t1 = i * 16
t2 = j * 4
t3 = t1 + t2
t4 = a[t3]
t5 = j * 16
t6 = i * 4
t7 = t5 + t6
t8 = a[t7]
t9 = t4 + t8
x  = t9
```

Q4. $B.true = L_2$, $B.false = L_3$, $S.next = L_1$; for B_1 && B_2 with $B_2 = !B_3$: $B_1.true = L_4$, $B_3.true = L_3$, $B_3.false = L_2$.

```
        if a < b goto L4
        goto L3
L4:     if c < d goto L3
        goto L2
L2:     x = 1
        goto L1
L3:     x = 2
L1:
```

Q7. (a) L-attributed ($C.i$ depends on the left sibling B) but not S-attributed. (b) Neither (inherited attribute of B depends on the right sibling C). (c) S-attributed (and hence L-attributed).

Q8. Postfix SDT: $E \to E_1 * E_2$ $\{print('*')\}$, $E \to E_1 + E_2$ $\{print('+')\}$, $E \to (E)$, $E \to$ **id** $\{print(\textbf{id}.lexeme)\}$ (with precedence/associativity declared or via an unambiguous grammar). Output for `a + b * (c + d)`: `a b c d + * +`.

Q2. Unary minus binds tighter than $*$, so the expression is $(-(b+c)) * (b+c)$. The SDD (no DAG) computes $b + c$ twice:

```
t1 = b + c
t2 = minus t1
t3 = b + c
t4 = t2 * t3
a  = t4
```

Q5. $B_1 \equiv a < b$ at 100–101, $M_1 = 102$, $B_3 \equiv c < d$ at 102–103, $M_2 = 104$, $B_4 \equiv e < f$ at 104–105. Reducing B_3 && M_2 B_4 patches $\{102\}$ with 104 and gives $truelist = \{104\}$, $falselist = \{103, 105\}$. Reducing B_1 || M_1 B_2 patches $\{101\}$ with 102 and gives $truelist = \{100, 104\}$, $falselist = \{103, 105\}$.

```
100:  if a < b goto _     <- truelist
101:  goto 102
102:  if c < d goto 104
103:  goto _              <- falselist
104:  if e < f goto _     <- truelist
105:  goto _              <- falselist
```

Q6. $M_1 = 100$; test at 100–101; $M_2 = 102$; body: `102:  t1 = x + 1`, `103:  x = t1`; inner marker 104; inner test 104–105; inner marker 106; `106:  y = 0`. The inner **if** has $nextlist = \{105\}$, which

the **while** patches with $M_1 = 100$.

```
100:  if x < 10 goto 102
101:  goto _              <- S.nextlist (patched later)
102:  t1 = x + 1
103:  x = t1
104:  if x == 5 goto 106
105:  goto 100
106:  y = 0
107:  goto 100
108:  ...                 <- 101 is patched with 108
```

Q9. Records: 1 `id` a; 2 `id` b; 3 $(*, 1, 2)$; (second $a * b$ is found, value number 3); 4 $(+, 3, 3)$; 5 `id` c; 6 $(+, 4, 5)$. Code: `t1 = a * b`, `t2 = t1 + t1`, `t3 = t2 + c`.

Q10.

```
        goto test
L1:     s = 1
        goto next
L2:     s = 2
        goto next
L3:     s = 0
        goto next
test:   if n = 1 goto L1
        if n = 5 goto L2
        goto L3
next:
```

Here the values 1 and 5 are *sparse*, so the code generator would prefer a binary search or the comparison chain above to a jump table of five entries.

Q11.

```
t1 = (float) j
t2 = t1 * x
t3 = (float) i
t4 = t3 + t2
x  = t4
```

Q12. $B.true = fall$, $B.false = L_1$; for $B_1 \,||\, B_2$: $B_1.true = L_2$ (new), $B_1.false = fall$, $B_2.true = fall$, $B_2.false = L_1$.

```
        if a < b goto L2
        ifFalse c < d goto L1
L2:     x = 1
L1:
```

Q13. The test block branches to the then-block (which defines x_2) or directly to the join. At the join the two predecessors are the then-block and the test block, so

```
B0:  x1 = 1
     if c goto B1 else B2
B1:  x2 = x1 + 1              (then-block)
B2:  x3 = phi(x2, x1)         (join: pred. 1 = B1, pred. 2 = B0)
     y1 = x3 * 2
```

Note that a φ is needed even though there is no **else**: the "missing" branch is itself an edge into the join, carrying x_1.

Q14.

```
B0:  k1 = 1
B1:  k2 = phi(k1, k3)          (pred. 1 = B0, pred. 2 = B2)
     if k2 < 10 goto B2 else B3
B2:  k3 = k2 * 2               (back to B1)
B3:  return k2
```

Trace: $k_2 = 1, 2, 4, 8, 16$; the test fails for $k_2 = 16$ and the function returns 16.

Q15. Triples: $0 : (+, a, b)$, $1 : (*, c, d)$, $2 : (-, (0), (1))$, $3 : (=, x, (2))$. After evaluating $c * d$ first: (a) with triples the triples swap places, so triple 2 must become $(-, (1), (0))$ and every other reference to either of them must be rewritten; (b) with indirect triples the four triples stay exactly as they are and only the order list changes, from $(0), (1), (2), (3)$ to $(1), (0), (2), (3)$.

Q16. (a) CFG suffices (it is a syntax question). (b) SDD needed: it needs a symbol table and a rule that consults it. (c) SDD needed (an attribute *val*). (d) SDD needed (an attribute *type* and a rule comparing it). (e) CFG suffices: the parse tree is the output of syntax analysis.

Q17. Creation order: p_1 = leaf a; p_2 = leaf b; p_3 = leaf 3; $p_4 = \mathit{Node}('+', p_2, p_3)$; $p_5 = \mathit{Node}('-', p_1, p_4)$; p_6 = leaf c; $p_7 = \mathit{Node}('-', p_5, p_6)$. The rules $E \to T$ and $T \to (E)$ create nothing. The root p_7 has the children p_5 (the node $a - (b + 3)$) and p_6 (c); seven nodes for four operands ($2 \cdot 4 - 1 = 7$).

Q18. The prints occur in the order `a, b, +, c, *, d, e, /, -`, so the output is `ab+c*de/-`. The right-recursive scheme prints the same string, because its actions stand right after the operand they follow.

Q19. Grammar: $B \to D\,R$, $R \to D\,R \mid \varepsilon$, $D \to \mathbf{0} \mid \mathbf{1}$.
(a) SDD: $B \to D\,R$: $R.i = D.val$, $B.val = R.s$; $R \to D\,R_1$: $R_1.i = 2 \cdot R.i + D.val$, $R.s = R_1.s$; $R \to \varepsilon$: $R.s = R.i$; D unchanged.
(b) SDT:

$$B \to D \;\{\; R.i = D.val \;\}\; R \;\{\; B.val = R.s \;\}$$
$$R \to D \;\{\; R_1.i = 2 \cdot R.i + D.val \;\}\; R_1 \;\{\; R.s = R_1.s \;\} \;\mid\; \varepsilon \;\{\; R.s = R.i \;\}$$

For `101`: $R.i = 1$; after the digit 0 the next R gets $2 \cdot 1 + 0 = 2$; after the digit 1 it gets $2 \cdot 2 + 1 = 5$; $R \to \varepsilon$ gives $R.s = 5$, so $B.val = 5$.

Q20. $B.t = \mathit{float}$ is copied down as $C.b = \mathit{float}$ through three levels; the empty production gives $C.t = \mathit{float}$, and on the way up $C.t$ becomes $\mathit{array}(6, \mathit{float})$, then $\mathit{array}(5, \mathit{array}(6, \mathit{float}))$, and finally $T.t = \mathit{array}(4, \mathit{array}(5, \mathit{array}(6, \mathit{float})))$. The procedure is the one of Example A1: if the next token is `[`, read the number n, call `C(b)` recursively and return `array(n, c1)`; otherwise return `b`.

Q21.

```
int L()      { match(ID);  return R(1); }          // R.i = 1 ;  L.count = R.s
int R(int i) {
    if (look == ',') { match(',');  match(ID);  return R(i + 1); }
    return i;                                      // R -> epsilon:  R.s = R.i
}
```

For `x, y, z`: `L()` calls `R(1)`, then `R(2)`, then `R(3)`, which returns 3.

Q22. SDT:

$$S \to \textbf{if}\ (\ \{\; L_1 = \mathit{new}();\ C.\mathit{true} = L_1;\ C.\mathit{false} = S.\mathit{next} \;\}\ C\ )$$
$$\{\; \mathit{print}(\text{“label”}, L_1);\ S_1.\mathit{next} = S.\mathit{next} \;\}\ S_1$$

```
void S(label next) {
    label L1;
    if (look == IF) {
```

```
        match(IF);  match('(');
        L1 = new();
        C(next, L1);              // C.false = S.next, C.true = L1 ; C prints its code
        match(')');
        print("label", L1);
        S(next);                  // S1.next = S.next ; S1 prints its code
    }
    else { /* other statement types */ }
}
```

On-the-fly generation is possible because $S.code$ is the concatenation of $C.code$, the label, and $S_1.code$, in the same order as C, S_1 appear in the body. Printing each piece when it becomes available gives the right order.

Q23. Grammar: $T \to F\,R$, $R \to *\,F\,R \mid /\,F\,R \mid \varepsilon$.
(a) SDD: $T \to F\,R$: $R.i = F.val$, $T.val = R.s$; $R \to *\,F\,R_1$: $R_1.i = R.i \cdot F.val$, $R.s = R_1.s$; $R \to /\,F\,R_1$: $R_1.i = R.i \,/\, F.val$, $R.s = R_1.s$; $R \to \varepsilon$: $R.s = R.i$; $F \to$ **num** unchanged.
(b) SDT:

$$
\begin{aligned}
&T \to F \;\{\; R.i = F.val \;\}\; R \;\{\; T.val = R.s \;\}\\
&R \to * \;F \;\{\; R_1.i = R.i \cdot F.val \;\}\; R_1 \;\{\; R.s = R_1.s \;\}\\
&\quad \mid \;/\; F \;\{\; R_1.i = R.i \,/\, F.val \;\}\; R_1 \;\{\; R.s = R_1.s \;\} \;\mid\; \varepsilon \;\{\; R.s = R.i \;\}
\end{aligned}
$$

For `12/3*2`: $R.i = 12$; after `/3` the next R gets $12/3 = 4$; after `*2` the next gets $4 \cdot 2 = 8$; $R \to \varepsilon$ gives $R.s = 8$, so $T.val = 8$. The order matters: $R.i \,/\, F.val$ gives $12/3 = 4$, whereas $F.val \,/\, R.i$ would give $3/12$.

Q24. The inner call `g(x)` has $A.list = [x]$; the outer call has $A.list = [t_1, t_2]$, where t_1 is the value of `g(x)` and t_2 the value of `y + 1`.

```
param x
t1 = call g, 1
t2 = y + 1
param t1
param t2
t3 = call f, 2
z = t3
```

Q25. Labels: $test = L_2$, case $3 = L_3$, case $7 = L_4$, $L_d = L_5$; $CL.list = [(3, L_3), (7, L_4)]$.

```
        goto L2
L3:     s = 1
        goto L1
L4:     s = 2
        goto L1
L5:     s = 0
        goto L1
L2:     if n = 3 goto L3
        if n = 7 goto L4
        goto L5
```

The tests must stand *after* all the bodies, and while the cases are parsed the compiler does not yet know how many cases follow (nor, for the last test, the default label). The pairs are therefore collected in the list and printed at the closing brace.

References

1. A. V. Aho, M. S. Lam, R. Sethi, J. D. Ullman, *Compilers: Principles, Techniques, and Tools*, 2nd ed., Pearson, 2007. – Chapter 5 (Syntax-Directed Translation) and Chapter 6 (Intermediate-Code Generation).