

JavaScript

Browser Object

Window Object Properties

Property	Description
closed	Returns a Boolean value indicating whether a window has been closed or not
defaultStatus	Sets or returns the default text in the statusbar of a window
document	Returns the Document object for the window (See Document object)
frames	Returns an array of all the frames (including iframes) in the current window
history	Returns the History object for the window (See History object)
innerHeight	Sets or returns the inner height of a window's content area
innerWidth	Sets or returns the inner width of a window's content area
length	Returns the number of frames (including iframes) in a window
location	Returns the Location object for the window (See Location object)
name	Sets or returns the name of a window
navigator	Returns the Navigator object for the window (See Navigator object)
opener	Returns a reference to the window that created the window
outerHeight	Sets or returns the outer height of a window, including toolbars/scrollbars
outerWidth	Sets or returns the outer width of a window, including toolbars/scrollbars
pageXOffset	Returns the pixels the current document has been scrolled (horizontally) from the upper left corner of the window
pageYOffset	Returns the pixels the current document has been scrolled (vertically) from the upper left corner of the window
parent	Returns the parent window of the current window
screen	Returns the Screen object for the window (See Screen object)
screenLeft	Returns the x coordinate of the window relative to the screen
screenTop	Returns the y coordinate of the window relative to the screen
screenX	Returns the x coordinate of the window relative to the screen
screenY	Returns the y coordinate of the window relative to the screen
self	Returns the current window
status	Sets or returns the text in the statusbar of a window
top	Returns the topmost browser window

Window Object Methods

Method	Description
alert()	Displays an alert box with a message and an OK button
blur()	Removes focus from the current window
clearInterval()	Clears a timer set with setInterval()
clearTimeout()	Clears a timer set with setTimeout()
close()	Closes the current window
confirm()	Displays a dialog box with a message and an OK and a Cancel button
createPopup()	Creates a pop-up window
focus()	Sets focus to the current window
moveBy()	Moves a window relative to its current position
moveTo()	Moves a window to the specified position
open()	Opens a new browser window
print()	Prints the content of the current window
prompt()	Displays a dialog box that prompts the visitor for input
resizeBy()	Resizes the window by the specified pixels
resizeTo()	Resizes the window to the specified width and height
scroll()	
scrollBy()	Scrolls the content by the specified number of pixels
scrollTo()	Scrolls the content to the specified coordinates
setInterval()	Calls a function or evaluates an expression at specified intervals (in milliseconds)
setTimeout()	Calls a function or evaluates an expression after a specified number of milliseconds

JavaScript

Browser Object

Navigator Object Properties

Property	Description
appName	Returns the code name of the browser
appName	Returns the name of the browser
appVersion	Returns the version information of the browser
cookieEnabled	Determines whether cookies are enabled in the browser
onLine	Boolean, returns true if the browser is on line, otherwise false.
platform	Returns for which platform the browser is compiled
userAgent	Returns the user-agent header sent by the browser to the server

Navigator Object Methods

Method	Description
javaEnabled()	Specifies whether or not the browser has Java enabled
taintEnabled()	Specifies whether or not the browser has data tainting enabled

Screen Object Properties

Property	Description
availHeight	Returns the height of the screen (excluding the Windows Taskbar)
availWidth	Returns the width of the screen (excluding the Windows Taskbar)
colorDepth	Returns the bit depth of the color palette for displaying images
height	Returns the total height of the screen
pixelDepth	Returns the color resolution (in bits per pixel) of the screen
width	Returns the total width of the screen

History Object Properties

Property	Description
length	Returns the number of URLs in the history list

History Object Methods

Method	Description
back()	Loads the previous URL in the history list
forward()	Loads the next URL in the history list
go()	Loads a specific URL from the history list

Location Object Properties

Property	Description
hash	Returns the anchor portion of a URL
host	Returns the hostname and port of a URL
hostname	Returns the hostname of a URL
href	Returns the entire URL
pathname	Returns the path name of a URL
port	Returns the port number the server uses for a URL
protocol	Returns the protocol of a URL
search	Returns the query portion of a URL

Location Object Methods

Method	Description
assign()	Loads a new document
reload()	Reloads the current document
replace()	Replaces the current document with a new one