glossary | Status: current | App v1.0.20 | Reviewed 2026-10-24

Glossary

Terms are alphabetical. `Code` names a type or constant. The code column says where to look.

Term	Definition	Code
Accelerator	Hardware backend for inference: CPU, GPU, NPU, or TPU (on Pixel the NPU is relabelled TPU).	`Accelerator`, `BackendSpec.accelerators`
AgentRuntimeExecutor	Runs agent turns (ReAct loop) on an initialized model and streams `AgentEvent`s.	`agent/AgentRuntimeExecutor.kt`
Agent Skills	The task (`llm_agent_chat`) where the LLM can use skills, MCP tools, and intents.	`customtasks/agentchat/`
AICore	Android system service that hosts on-device foundation models. Reached through ML Kit GenAI Prompt.	`runtime/aicore/`
Allowlist (model)	Versioned JSON catalog of models the app offers, fetched from GitHub.	`data/ModelAllowlist.kt`, `model_allowlists/`
Allowlist (skill)	Remote list of featured skills. URL empty in this build.	`data/SkillAllowlist.kt`, `SKILL_ALLOWLIST_URL`
appassets origin	`https://appassets.androidplatform.net`. The virtual origin that serves bundled and imported skill files to the WebView.	`LOCAL_URL_BASE`, `GalleryWebView`
BackendSpec	A model's runtime type, AICore stage and preference, and accelerators.	`data/BackendSpec.kt`
Built-in task	A task shipped with the app, with an id in `BuiltInTaskId`.	`data/Tasks.kt`
Capability	An optional model feature (`llm_thinking`, `speculative_decoding`), gated per task by `capabilityToTaskTypes`.	`ModelCapability`
Category	A home-screen tab grouping tasks (`llm`, `classical_ml`, `experimental`).	`data/Categories.kt`
Context compaction	Summarizing a long conversation and resetting the KV cache. Disabled in this build.	`SummarizationContextCompactor`
CustomTask	The plug-in interface every feature implements.	`customtasks/common/CustomTask.kt`
EmbeddingGemma 2	Multimodal embedding model behind Instant Media Search and Video Moment Finder.	`services/semanticretrieval/`

Term	Definition	Code
Extra data files	Optional components downloaded with a model (e.g. `samples.zip`).	`ModelDataFile`
FunctionGemma	270M Gemma fine-tunes for function calling (Mobile Actions, Tiny Garden).	allowlist `MobileActions-270M`, `TinyGarden-270M`
Gated model	A Hugging Face model that needs license acceptance and an auth token.	`ModelAccessibility.GATED`
Imported model	A model file the user adds manually, stored under `__imports/`.	`ImportedModel` (proto)
Intent (agent)	A native Android action the model can run through `run_intent`.	`intents/IntentHandler.kt`
LiteRT	Google's on-device ML runtime (formerly TensorFlow Lite).	—
LiteRT-LM	LiteRT's LLM engine (`Engine`, `Conversation`, tools, constrained decoding). `.litertlm` files.	`LlmChatModelHelper`
LlmModelHelper	The runtime abstraction for LLMs.	`runtime/LlmModelHelper.kt`
LlmSessionManager	Owns conversation sessions, history, inference calls, and compaction.	`agent/sessions/`
MCP	Model Context Protocol. Remote tool servers the agent can call.	`McpManagerViewModel`, `RunMcpTool`
Model	A runnable model entry (from the allowlist, an import, or inline in a task).	`data/Model.kt`
ModelDownloader	Per-runtime strategy for status, download, cancel, and delete.	`data/ModelDownloader.kt`
normalizedName	Model name with non-alphanumerics replaced by `_`. Used for storage paths.	`Model.normalizedName`
Runtime helper	The `LlmModelHelper` picked for a model (`Model.runtimeHelper`).	`runtime/ModelHelperExt.kt`
RuntimeType	`litert_lm`, `aicore`, `unknown`, with behaviour flags (download via repo, auto-download, deletable).	`data/ModelEnums.kt`
Session	A conversation history, identified by a UUID and independent of the model.	`generateSessionId()`
Skill	An instruction pack (`SKILL.md`) plus optional JS scripts and assets.	`skills/`, `skill.proto`
SoC model files	Per-chipset NPU builds of a model, chosen by `Build.SOC_MODEL`.	`socToModelFiles`

Term	Definition	Code
Supplementary model	An allowlist model not bound to a task (`modelType != task`).	`Model.isSupplementary`
Task	A home-screen feature: metadata, models, and capability flags.	`data/Tasks.kt`
Tool	A Kotlin method exposed to the model with `@Tool`.	`tools/ToolDefinition.kt`
Tool action	An event from a running tool to the UI (run JS, ask a secret, request permission, MCP consent, progress).	`tools/ToolAction.kt`
`.gallerytmp`	Extension of partially downloaded files, used to resume downloads.	`TMP_FILE_EXT`