known-issues | Status: current | App v1.0.20 | Reviewed 2026-10-24

Known Issues, Risks, and Doc/Code Mismatches

These were found while reviewing the code for this documentation set. **No fixes have been applied.** Each item has a stable id. Use it in issues and commits, and update the **State** column when an item is resolved.

Type: `bug` · `security` · `risk` (latent defect) · `mismatch` (docs vs code) · `debt` · `config`. **Confidence:** `confirmed` (read in code) · `to verify` (needs a runtime check).

1. Code

Id	Type	Sev.	Summary	Evidence
KI-01	bug	Med	HF token expiry "5-minute buffer" subtracts `5 * 60` **ms** (300 ms). Fix: `5 * 60 * 1000L`.	`ModelManagerViewModel.kt:1104`
KI-02	security	High	The WebView serves all of `filesDir` (including `datastore/user_data.pb` with tokens, secrets, and chat history) on the origin that local and imported skills run on.	`GalleryWebView.kt:69-85`
KI-03	security	Med	Tokens, skill secrets, and MCP headers are stored unencrypted. `security-crypto` is declared but unused. Backup rules are unmodified samples with `allowBackup=true`.	`DataStoreRepository.kt`, `res/xml/*rules.xml`
KI-04	bug / security	Low	`RunJsTool` logs `secret.substring(0, 3)`. It leaks a prefix and throws `StringIndexOutOfBoundsException` for secrets of 1–2 characters.	`RunJsTool.kt:104`
KI-05	security	Low	`DownloadWorker` logs the first 10 characters of the HF token. The token is also passed through WorkManager input `Data`, which is persisted.	`DownloadWorker.kt:112,144`
KI-06	security	Low	`MainActivity` logs every intent extra (a "Debug" dump), in release builds too.	`MainActivity.kt`

Id	Type	Sev.	Summary	Evidence
KI-07	risk	Med	`AgentTools` is a Hilt `@Singleton`, but its `lateinit` fields (`context`, `dataStoreRepository`, `mcpManagerViewModel`, `taskId`) are assigned from the `AgentChatScreen` composable. The singleton then holds a screen-scoped ViewModel, which can leak or go stale. `AgentChatTask.initializeModelFn` reads `agentTools.mcpManagerViewModel`, so it would throw `UninitializedPropertyAccessException` if it ran before the screen composed. `runMcpTool` is `by lazy` and captures the first `taskId`.	`AgentChatScreen.kt:137-141`, `AgentTools.kt`, `AgentChatTaskModule.kt`
KI-08	risk	Low	Tool names are inconsistent. The system prompt says `load_skill` and `run_intent` (snake_case) but `runMcpTool` (camelCase). The Kotlin methods are `loadSkill`, `runJs`, `runIntent`, `runMcpTool`. Whichever convention LiteRT-LM exposes, one of the names in the prompt is wrong.	`AgentChatTaskModule.kt` prompts, `tools/*`
KI-09	config	Info	Context compaction is fully built (compactor, UI banner, per-task setting) but hard-disabled: `Config.isContextCompactEnabled()` returns `false`.	`Config.kt:180`
KI-10	debt	Info	`ModelAllowlist.flags` (remote flag overrides) is parsed but never read.	`ModelAllowlist.kt`
KI-11	bug	Low	`Category.CLASSICAL_ML` uses `R.string.category_llm` as its label. `category_classical_ml` exists.	`Categories.kt:42`
KI-12	bug	Low	`ExampleCustomTask` `docUrl` and `sourceCodeUrl` are missing `/blob/main/`, so the links 404.	`ExampleCustomTask.kt:75,77`
KI-13	risk	Low	`DownloadWorker` catches only `IOException`. The zip-slip `SecurityException` and other runtime errors fail the work with no error message for the UI.	`DownloadWorker.kt:344,359`

Id	Type	Sev.	Summary	Evidence
KI-14	debt	Low	`DefaultAgentRuntimeExecutor` ignores the `Attachment.ImageUri`, `AudioUri`, and `File` attachment types.	`DefaultAgentRuntimeExecutor.kt`
KI-15	risk	Low	DataStore reads and writes use `runBlocking`. Calls from the main thread can jank or ANR.	`DataStoreRepository.kt`
KI-17	security	Med	The model allowlist is fetched from GitHub `main` without a signature or pinned hashes, and downloaded models aren't hash-verified. Write access to `main` controls model URLs for every install of that version.	`ModelManagerViewModel.loadModelAllowlist`, `DownloadWorker`
KI-16	debt	Low	The `SKILL.md` front-matter parser is line-based, not YAML. Quoted, multi-line, or nested values parse incorrectly, and a `---` inside a value breaks the split.	`SkillManager.convertSkillMdToProto`

2. Build, CI, and configuration

Id	Type	Sev.	Summary	Evidence	S
KI-20	debt	Med	No automated tests or lint in CI. Allowlist and skill changes ship with no validation.	06-testing, `.github/workflows/`	o
KI-21	config	Info	The release build is debug-signed, `isMinifyEnabled = false`, and `proguard-rules.pro` is referenced but missing.	`app/build.gradle.kts`	o
KI-22	config	Info	`SKILL_ALLOWLIST_URL = ""`, so the "community-featured skills" list described in `skills/README.md` is always empty in this build.	`SkillManager.kt:54`	o
KI-23	config	Info	`applicationId` `com.google.aiedge.gallery` differs from the Play listing id `com.google.ai.edge.gallery` in the README. OSS builds therefore install next to the store app (probably intentional **[inferred]**).	`app/build.gradle.kts`, `README.md`	o
KI-24	debt	Info	A stray `gallery/worker/AndroidManifest.xml` (targetSdk 35) sits inside the Java source tree and isn't used by Gradle.	`.../gallery/worker/AndroidManifest.xml`	o

Id	Type	Sev.	Summary	Evidence	St
KI-25	debt	Info	The root `model_allowlist.json` (4 legacy `.task` models) isn't referenced by current code **[inferred]**.	`ModelManagerViewModel.ALLOWLIST_BASE_URL`	op

3. Documentation vs code mismatches

Initially reported by the graph-extraction pass, then confirmed by direct reading.

Id	Where	Docs say	Code does
KI-30	`skills/README.md:381`	Links `customtasks/agentchat/IntentHandler.kt`	The file is `intents/IntentHa`
KI-31	`skills/featured/mood-music`	`SKILL.md` documents `genre_blend` and `bpm`	`scripts/index.html` sends `duration`, `energy`
KI-32	`skills/built-in/qr-code`	`SKILL.md` doesn't mention `shape`	The script accepts `shape` (`square` / `circle`)
KI-33	`skills/built-in/text-spinner`	—	`<title>Create github issu` is left over, and `label` goes bview URL without `encodeUR`
KI-34	`skills/built-in/mood-tracker`	The dashboard shows when `show_dashboard` is requested	`showDashboard = input.sho` `|| action === 'get_history` ways shows on history
KI-35	`skills/featured/virtual-piano`	`SKILL.md`: `index.js` "returns the webview URL pointing to the GitHub-hosted UI"	Returns the relative `ui.html` (served from the skill's `asse`
KI-36	`skills/built-in/interactive-map/SKILL.md` vs `assets/skills/interactive-map/SKILL.md`	The published copy should match the bundled one	The two files differ
KI-37	`DEVELOPMENT.md`	Links `app/build.gradle.kts` at an old commit (`c1b50e1…#L41-L44`)	The placeholder is now at `Android/src/app/build.gra` `45` on `main`