




# Minimum Spanning Trees

SUBJECT-CODE : KCS-503

Dr. Ragini Karwayun



1

## Minimum Spanning Tree

### What is a Spanning Tree?

Given an undirected and connected graph  $G=(V,E)$ , a spanning tree of the graph  $G$  is a tree that spans  $G$  (that is, it includes every vertex of  $G$ ) and is a subgraph of  $G$  (every edge in the tree belongs to  $G$ )

2

## Minimum Spanning Tree


### What is a Minimum Spanning Tree?

- The cost of the spanning tree is the sum of the weights of all the edges in the tree. There can be many spanning trees. Minimum spanning tree is the spanning tree where the cost is minimum among all the spanning trees. There also can be many minimum spanning trees.
- Minimum spanning tree has direct application in the design of networks. It is used in algorithms approximating the travelling salesman problem, multi-terminal minimum cut problem and minimum-cost weighted perfect matching.

*weight are unique.*  
① 4


*only be one (1,2,3)*

## Minimum Spanning Tree



## Minimum Spanning Tree

- Problem: given a connected, undirected, weighted graph:
- find a spanning tree using edges that minimize the total weight




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

5

## Minimum Spanning Tree



COST = 46

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

6

## Minimum Spanning Tree

- A spanning tree whose weight is minimum over all spanning trees is called minimum spanning tree.
- Greedy approach is followed to achieve MST.
- Problem: Connect a set of nodes by a network of minimal total length
- Some applications:
  - Communication networks
  - Circuit design
  - Layout of highway systems
- The resulting connection graph is connected, undirected, and acyclic, i.e., a *free tree* (sometimes called simply a *tree*).

## Formal Definition of MST

- Given a connected, undirected, graph  $G = (V, E)$ , a **spanning tree** is an acyclic subset of edges  $T \subseteq E$  that connects all the vertices together.
- Assuming  $G$  is weighted, we define the **cost** of a spanning tree  $T$  to be the sum of edge weights in the spanning tree

$$w(T) = \sum_{(u,v) \in T} w(u,v)$$

- A **minimum spanning tree (MST)** is a spanning tree of minimum weight.

## Generic Approaches

- ▶ Two greedy algorithms for computing MSTs:
  - ▶ Kruskal's Algorithm (similar to connected component)
  - ▶ Prim's Algorithm (similar to Dijkstra's Algorithm)

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

9

## Facts about (Free) Trees

- ▶ A tree with  $n$  vertices has exactly  $n-1$  edges  
( $|E| = |V| - 1$ )
- ▶ There exists a unique path between any two vertices of a tree
- ▶ Adding any edge to a tree creates a unique cycle; breaking any edge on this cycle restores a tree

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

10

## Intuition Behind Greedy MST

- We maintain in a subset of edges  $A$ , which will initially be empty, and we will add edges one at a time, until equals the MST.
- We say that a subset  $A \subseteq E$  is *viable* if  $A$  is a subset of edges in some MST.
- We say that an edge  $(u,v) \in E-A$  is *safe* if  $A \cup \{(u,v)\}$  is viable.
- Basically, the choice  $(u,v)$  is a safe choice to add so that  $A$  can still be extended to form an MST.
- Note that if  $A$  is viable it cannot contain a cycle.
- A generic greedy algorithm operates by repeatedly adding any *safe edge* to the current spanning tree.

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

11

## Generic-MST ( $G, w$ )

1.  $A \leftarrow \emptyset$      //  $A$  trivially satisfies invariant  
      // lines 2-4 maintain the invariant
2. while  $A$  does not form a spanning tree
3.     find an edge  $(u,v)$  that is safe for  $A$
4.      $A \leftarrow A \cup \{(u,v)\}$
5. return  $A$      //  $A$  is now a MST

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

12

## MST-Prim( $G, w, r$ )

1.  $Q \leftarrow V[G]$
2. for each vertex  $u \in Q$     // initialization:  $O(V)$  time
  3. do  $key[u] \leftarrow \infty$
  4.  $\pi[u] \leftarrow \text{NIL}$
4.  $key[r] \leftarrow 0$     // start at the root
5.  $\pi[r] \leftarrow \text{NIL}$     // set parent of  $r$  to be NIL
6. while  $Q \neq \emptyset$     // until all vertices in MST
  7.  $u \leftarrow \text{Extract-Min}(Q)$     // vertex with lightest edge
  8. for each  $v \in \text{adj}[u]$ 
    9. if  $v \in Q$  and  $w(u,v) < key[v]$
    10.  $\pi[v] \leftarrow u$
    11.  $key[v] \leftarrow w(u,v)$     // new lighter edge out of  $v$
    12.  $\text{decrease\_Key}(Q, v, key[v])$

IPEC


KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

13

## PRIM( $V, E, w, r$ )

1.  $Q \leftarrow \emptyset$
2. for each  $u \in V$ 
  3. do  $key[u] \leftarrow \infty$
  4.  $\pi[u] \leftarrow \text{NIL}$
  5.  $\text{INSERT}(Q, u)$
6.  $\text{DECREASE-KEY}(Q, r, 0)$
7. while  $Q \neq \emptyset$ 
  8. do  $u \leftarrow \text{EXTRACT-MIN}(Q)$ .
  9. for each  $v \in \text{Adj}[u]$ 
    10. do if  $v \in Q$  and  $w(u, v) < key[v]$
    11. then  $\pi[v] \leftarrow u$
    12.  $\text{DECREASE-KEY}(Q, v, w(u, v))$


 $Q = \{a, b, c, d, e, f, g, h, i\}$ 
 $V_A = \emptyset.$ 

a	b	c	d	e	f	g	h	i
$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$

 $\text{DECREASE-KEY}(Q, a, 0)$ 

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

14



**Example**

$Q = \{a, b, c, d, e, f, g, h, i\}$   
 Extract-MIN( $Q$ )  $\Rightarrow a$   
 $V_A = \{a\}$ .

	a	b	c	d	e	f	g	h	i
0	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$

key [b] = 4     $\pi$  [b] = a  
 key [h] = 8     $\pi$  [h] = a  
 $Q = \{b, c, d, e, f, g, h, i\}$   
 $V_A = \{a\}$ .    Extract-MIN( $Q$ )  $\Rightarrow b$

	a	b	c	d	e	f	g	h	i
0	4	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	8	$\infty$

IPEC    KCS-503. Design and Analysis of Algorithms    Dr. Ragini Karwayun

15

**Example**

key [c] = 8     $\pi$  [c] = b  
 key [h] = 8     $\pi$  [h] = a    - unchanged  
 $Q = \{c, d, e, f, g, h, i\}$      $V_A = \{a, b\}$   
 Extract-MIN( $Q$ )  $\Rightarrow c$

	a	b	c	d	e	f	g	h	i
0	4	8	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	8	$\infty$

key [d] = 7     $\pi$  [d] = c  
 key [f] = 4     $\pi$  [f] = c  
 key [i] = 2     $\pi$  [i] = c  
 $Q = \{d, e, f, g, h, i\}$      $V_A = \{a, b, c\}$   
 Extract-MIN( $Q$ )  $\Rightarrow i$


	a	b	c	d	e	f	g	h	i
0	4	8	7	$\infty$	4	$\infty$	8	2	$\infty$

IPEC    KCS-503. Design and Analysis of Algorithms    Dr. Ragini Karwayun

16



## Example



key [h] = 7    $\pi$  [h] = i  
 key [g] = 6    $\pi$  [g] = i  
 $Q = \{d, e, f, g, h\}$     $V_A = \{a, b, c, i\}$   
 Extract-MIN(Q)  $\Rightarrow$  f

a	b	c	d	e	f	g	h	i
0	4	8	7	$\infty$	4	6	7	2

key [g] = 2    $\pi$  [g] = f  
 key [d] = 7    $\pi$  [d] = c unchanged  
 key [e] = 10    $\pi$  [e] = f  
 $Q = \{d, e, g, h\}$     $V_A = \{a, b, c, i, f\}$   
 Extract-MIN(Q)  $\Rightarrow$  g

a	b	c	d	e	f	g	h	i
0	4	8	7	10	4	6	7	2


IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

17

## Example



key [h] = 1    $\pi$  [h] = g  
 $Q = \{d, e, h\}$     $V_A = \{a, b, c, i, f, g\}$   
 Extract-MIN(Q)  $\Rightarrow$  h

a	b	c	d	e	f	g	h	i
0	4	8	7	10	4	6	7	2

$Q = \{d, e\}$     $V_A = \{a, b, c, i, f, g, h\}$   
 Extract-MIN(Q)  $\Rightarrow$  d

a	b	c	d	e	f	g	h	i
0	4	8	7	10	4	6	7	2


IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

18

## Example



key[e] = 9     $\pi[e] = d$

$Q = \{e\}$      $V_A = \{a, b, c, i, f, g, h, d\}$


Extract-MIN(Q)  $\Rightarrow e$

a, b, c, d, e, f, g, h, i

0 4 8 7 10 4 6 7 2

$Q = \emptyset$

$V_A = \{a, b, c, i, f, g, h, d, e\}$



IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

19

## PRIM(V, E, w, r)

1.  $Q \leftarrow \emptyset$
2. for each  $u \in V$
3.    do key[u]  $\leftarrow \infty$
4.     $\pi[u] \leftarrow \text{NIL}$
5.    INSERT(Q, u)
6. DECREASE-KEY(Q, r, 0)     $\blacktriangleright$  key[r]  $\leftarrow 0$
7. while  $Q \neq \emptyset$      $\leftarrow$  Executed V times
8.    do  $u \leftarrow \text{EXTRACT-MIN}(Q)$      $\leftarrow$  Takes  $O(\lg V)$
9.    for each  $v \in \text{Adj}[u]$      $\leftarrow$  Executed  $O(E)$  times
10.    do if  $v \in Q$  and  $w(u, v) < \text{key}[v]$      $\leftarrow$  Constant
11.    then  $\pi[v] \leftarrow u$      $\leftarrow$  Takes  $O(\lg V)$
12.    DECREASE-KEY(Q, v,  $w(u, v)$ )

Total time:  $O(V \lg V + E \lg V) = O(E \lg V)$

$O(V)$  if Q is implemented as a min-heap

Min-heap operations:  
 $O(V \lg V)$

$O(E \lg V)$

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun


20

## Performance of PRIM's Algorithm

Total time:  $O(V \lg V + E \lg V) = O(E \lg V)$


- Time Complexity of the above program is  $O(V^2)$  ,if the input graph is represented using adjacency list,
- The time complexity of Prim's algorithm can be reduced to  $O(E \log V)$  with the help of binary heap.
- The time complexity of Prim's algorithm can be reduced to  $O(E + \log V)$  with the help of Fibonacci Heap

## Prim's Algorithm



*Run on example graph*

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

23

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms


Dr. Ragini Karwayun

24


## Prim's Algorithm



## Prim's Algorithm



## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

27

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

28

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

29

## Prim's Algorithm



IPEC


KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

30



## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

31

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

32

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

33

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

34

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

35

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

36

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

37

## Prim's Algorithm




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

38

## Prim's Algorithm





IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

39

## Prim's Algorithm



IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

40

## Basics of Kruskal's Algorithm

- Attempts to add edges to  $A$  in increasing order of weight (lightest edge first)
  - If the next edge does not induce a cycle among the current set of edges, then it is added to  $A$ .
  - If it does, then this edge is passed over, and we consider the next edge in order.
  - As this algorithm runs, the edges of  $A$  will induce a forest on the vertices and the trees of this forest are merged together until we have a single tree containing all vertices.

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

41

## MST-Kruskal( $G, w$ )

1.  $A \leftarrow \emptyset$  // initially  $A$  is empty
2. for each vertex  $v \in V[G]$  // line 2-3 takes  $O(V)$  time
3.   do Make-Set( $v$ ) // create set for each vertex
4. sort the edges of  $E$  by nondecreasing weight  $w$
5. for each edge  $(u,v) \in E$ , in order by nondecreasing weight
6.   do if Find-Set( $u$ )  $\neq$  Find-Set( $v$ ) //  $u$  &  $v$  on different trees
7.     then  $A \leftarrow A \cup \{(u,v)\}$
8.     Union( $u,v$ )
9. return  $A$    Total running time is  $O(E \lg E)$ .

IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

42

## MST-Kruskal( $G, w$ )

- Lines 1-3 (initialization):  $O(V)$
- Line 4 (sorting):  $O(E \lg E)$
- Lines 6-8 (set-operation):  $O(E \log E)$
- Total:  $O(E \log E)$
- As  $\log E = O(\log V)$
- Total :  $O(E \log V)$





IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

43

## Kruskal Example



IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

44



**Kruskal Example**

$\{h, g, f, c, i\}$   $\{a, b\}$   $\{h, g, f, i, c\}$   $\{a, b\}$

reject as  $i, g$  belong to same set

reject as  $i, h$  belong to same set

$\{h, g, f, i, c, d\}$   $\{a, b\}$

IPEC KCS-503. Design and Analysis of Algorithms Dr. Ragini Karwayun

45

**Kruskal Example**

$\{h, g, f, i, c, d, a, b\}$  reject


reject

$\{h, g, f, i, c, d, a, b, e\}$  reject.


IPEC KCS-503. Design and Analysis of Algorithms Dr. Ragini Karwayun

46

## Kruskal Example



Reject



Reject


IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

47

## Kruskal Example - 2



{e, d}


IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

48

## Kruskal Example - 2




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

49

## Kruskal Example - 2




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

50

## Kruskal Example - 2



$\{E, D, B, A\}$


IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

51

## Kruskal Example - 2



$\{E, D, B, A, F\}$


IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

52

## Kruskal Example - 2




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

53

## Kruskal Example - 2




IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

54

## Kruskal Example - 2



IPEC

KCS-503. Design and Analysis of Algorithms


Dr. Ragini Karwayun

55

## Kruskal Example - 2

minimum- spanning tree

$\{E, D, B, A, F, C\}$   
final.



IPEC

KCS-503. Design and Analysis of Algorithms

Dr. Ragini Karwayun

56